The representational dynamics of visual objects in rapid serial visual processing streams

Tijl Grootswagers*[a,b,c,1], Amanda K. Robinson*[a,b,c,2], Thomas A. Carlson[a,b,3]

*equal contribution

[a] School of Psychology, University of Sydney, NSW, 2006, Australia

[b] ARC Centre of Excellence in Cognition and Its Disorders, NSW, 2109, Australia

[c] Department of Cognitive Science, Macquarie University, NSW, 2109, Australia

[1] tijl.grootswagers@sydney.edu.au

[2] amanda.robinson@sydney.edu.au

[3] thomas.carlson@sydney.edu.au

Abstract

In our daily lives, we are bombarded with a stream of rapidly changing visual input. Humans have the remarkable capacity to detect and identify objects in fast-changing scenes. Yet, when studying brain representations, stimuli are generally presented in isolation. Here, we studied the dynamics of human vision using a combination of fast stimulus presentation rates, electroencephalography and multivariate decoding analyses. Using a rapid presentation rate of 5 images per second, we obtained the representational structure of a large number of stimuli, and showed the emerging abstract categorical organisation of this structure. In a second experiment, we replicated these results using an ultra-rapid presentation rate of 20 images per second. Our results show that the combination of naturalistic stimulus presentation rates and multivariate decoding analyses has unprecedented potential for studying the temporal dynamics of the structure of representations in the human visual system.

Introduction

The human brain can effortlessly extract abstract meaning, such as categorical object information, from a visual image, and can do so in less than 200 milliseconds (Carlson, Tovar, Alink, & Kriegeskorte, 2013; Cichy, Pantazis, & Oliva, 2014; Contini, Wardle, & Carlson, 2017; Keysers, Xiao, Földiák, & Perrett, 2001; Mack, Gauthier, Sadr, & Palmeri, 2008; Mack & Palmeri, 2011; Potter, 1975, 1976; Potter, Wyble, Hagmann, & McCourt, 2014; VanRullen & Thorpe, 2001). The temporal dynamics of the emerging representation of visual objects has been studied extensively using multivariate decoding methods and neuroimaging methods with high temporal resolution, such as EEG and MEG. In these experiments, stimuli are generally presented with a large inter-stimulus interval (ISI) to avoid contamination from temporally adjacent stimuli, typically around one second (Carlson et al., 2013; Cichy et al., 2014; Grootswagers, Ritchie, Wardle, Heathcote, & Carlson, 2017; Isik, Meyers, Leibo, & Poggio, 2014; Kaneshiro, Guimaraes, Kim, Norcia, & Suppes, 2015). This design allows the brain to process each stimulus and avoids temporally overlapping stimulus representations. While such designs have yielded important insights into the representational dynamics of object processing, in the natural world, we are bombarded with a constant stream of changing visual input. The standard paradigm, in which stimuli are presented in isolation with a large ISI, thus may not yield the most accurate description the temporal dynamics of emerging object representations in the real world. One major advantage of multivariate decoding methods (Grootswagers, Wardle, & Carlson, 2017; Haynes, 2015) is that they allow testing for statistical dependencies in data without a resting baseline. Exploring representational dynamics using decoding and fast visual presentation rates therefore offers unique potential for investigating visual processing.

Here, we diverge from the traditional approach and propose a new method for studying the representational dynamics of human vision. It has been shown previously that stimuli, when are presented at high presentation rates, are all processed to some degree by the visual system and that their neural representations can co-exist in the visual system (Marti & Dehaene, 2017; Mohsenzadeh, Qin,

Cichy, & Pantazis, 2018; Rossion, Torfs, Jacques, & Liu-Shuang, 2015; Rousselet, Fabre-Thorpe, & Thorpe,

2002). Behavioural work has additionally shown that the human visual system can extract abstract

information from a visual stimulus at very fast presentation rates (Crouzet, Kirchner, & Thorpe, 2010;

Keysers et al., 2001; Macé, Thorpe, & Fabre-Thorpe, 2005; Mack et al., 2008; Mack & Palmeri, 2015; Marti

& Dehaene, 2017; Potter, 1975, 1976; Potter et al., 2014; Rossion et al., 2015; Thorpe, Fize, & Marlot,

1996). In the current study, we draw on this human capacity and study visual object recognition using fast

stimulus presentation rates and multivariate decoding analyses of EEG evoked responses (Grootswagers,

Wardle, et al., 2017). We used a rapid serial visual presentation (RSVP) paradigm to study the

representations of a large set of visual objects presented at a speed of 5 images per second (200ms per

image; "rapid" condition). The objects were carefully selected to allow categorisation at three different

levels of abstraction. The high presentation rate enabled us to obtain 40 repetitions of 200 different

stimuli in a short EEG session. We additionally examined the effect of higher level cognitive processes on

the emerging representations by having participants detect targets that were identifiable based on low-

level visual features or abstract categories in separate trials. We successfully decoded different categorical

contrasts for the 200 objects, suggesting that individual stimuli were processed up to abstract categorical

representations. Strikingly, we found similar results in a follow-up experimental session, where we used

a much higher presentation rate of 20 images per second (50ms per image: "ultra-rapid" condition). The

unprecedented ability to test such large numbers of different stimuli in relatively short scanning sessions

shows great potential for studying the dynamics of the structure of information in the human visual

system.

Figure 1. Stimuli and design. A) Experimental stimuli. There were 200 images of objects (obtained from www.pngimg.com), organised in categories at three different levels: Animacy (animate, inanimate), category (10 categories e.g., mammal, tool, flower) and object (50 categories e.g., cow, dog, giraffe). In the experiment, participants were asked to count the number of target objects from two categories: boats and geometric star shapes, each with eight images. B) Experimental design. Trials consisted of all 200 images presented in random order, with 1-4 targets interspersed throughout. Images were presented in rapid sequences (5Hz; 200ms each) in session 1, and ultra-rapid sequences (20Hz; 50ms each) in session 2. C) Decoding the categorical levels from deep neural network activation profiles. For each layer in the VGG19-network (x-axis), we decoded the three categorical levels using a leave-one-exemplar-out cross-validation procedure. Plotted is the mean decoding accuracy (y-axis) for each layer of the network.

Methods

Stimuli

We collected a stimulus set of 200 visual objects from different categories. Stimuli were obtained from the free image hosting website www.pngimg.com. The categories were manually selected, guided by categorical hierarchies described in the literature (Caramazza & Mahon, 2003; Caramazza & Shelton, 1998; Carlson et al., 2013; Connolly et al., 2012; Grill-Spector & Weiner, 2014; Kiani, Esteky, Mirpour, & Tanaka, 2007; Kriegeskorte, Mur, Ruff, et al., 2008; Mahon & Caramazza, 2011; Peelen & Caramazza, 2012; E. H. Rosch, 1973). There were two high level categories (animate, inanimate) consisting of 10 categories (5 animate, and 5 inanimate categories). Each of these 10 categories (e.g., mammal, tool, flower) was further separated into 5 object categories (e.g., cow, dog, giraffe, etc.), which consisted of 4 images each (Figure 1a). During the experiment, participants were instructed to count target stimuli (Figure 1b). To examine how attending to different features of the stimuli affected the emerging representations, we used two different sets of target stimuli. The target stimuli were either boats, or geometric star shapes, and there were eight exemplars of each target type (Figure 1 – inset). We hypothesized that detecting the star shapes among the other objects was possible using low level visual cues, while for recognising boat targets, it was necessary to process stimuli to a more abstract categorical level.

To predict the contribution of low level visual features to our results, we trained classifiers on activation profiles obtained from a pre-trained deep neural network (DNN), VGG-19 (Simonyan & Zisserman, 2014), which has a high performance on ImageNet object classification and has been found to correspond well to early visual areas (Schrimpf et al., 2018). This network was originally trained to classify objects into 1000 categories using 45 hidden layers. For each of our 200 experimental stimuli, we obtained the activation values of all units in each layer of the DNN. As there are many more units in a layer than we

have stimuli, we applied principal component analysis (PCA) on the activation patters to retain the first 200 components without loss of information. Then, for each layer, we applied a linear discriminant analysis classifier to the activation of units in this layer. The leave-one-exemplar-out cross-validated classification accuracy was calculated for the three categorical contrasts used in this study (Figure 1c), which indicated category decoding accuracy increased with deep neural network layer.

Participants and experimental procedure

Participants were 16 adults recruited from the University of Sydney (5 females; age range 18-38 years) in return for payment or course credit. The study was approved by the University of Sydney ethics committee and informed consent was obtained from all participants. Participants viewed 40 sequences of objects, each lasting between 40.2 - 40.8 seconds (depending on the number of targets in the sequence). In each sequence, the 200 stimuli were presented in random order, for a duration of 200ms each with no gap between successive images (5 images per second; "rapid" condition). In addition to the 200 stimuli, target stimuli were inserted throughout the sequence (Figure 1c). In half of the sequences, the target stimuli were boats, and in the other sequences, the target stimuli were geometric stars (Figure 1). A random number between 1 and 4 targets were presented in the sequence, with the condition that targets could not appear within the first 10 or last 10 images, and ensuring there were at least 12 non-target stimuli between subsequent targets. At the start of each sequence, participants were prompted to count the number of targets in the sequence ("Count the boats in the trial" or "Count the stars in the trial" in random order) and the 8 potential targets were shown. They were instructed to respond at the end of the sequence using a 4-way button box. After each sequence, participants received feedback. They started the next sequence with a button press. This session lasted approximately 40 minutes in total. After a short break, the second experimental session started, and participants performed another 40 sequences using the same procedure as session one, except that the images were presented for only 50ms (a presentation speed of 20 images per second; "ultra-rapid" condition). The second session lasted about 10 minutes.

EEG recordings and preprocessing

Continuous EEG data were recorded using a BrainVision ActiChamp system, digitized at a 1000-Hz sample rate. The 64 electrodes were arranged according to the international standard 10–10 system for electrode placement (Oostenveld & Praamstra, 2001). During recording, all scalp electrodes were referenced to Cz. Preprocessing was performed offline using EEGlab (Delorme & Makeig, 2004). Data were filtered using a Hamming windowed FIR filter with 0.1 Hz highpass and 100Hz lowpass filters, and were downsampled to 250Hz. No further preprocessing steps were applied, and the channel voltages at each time point were used for the remainder of the analysis. Epochs were created for each stimulus presentation (except targets) ranging from [-100 to 1000ms] relative to stimulus onset. We initially had used the same range for target-distractor decoding but found that this window did not capture the full process. Therefore, for comparing targets versus distractors, we created larger epochs ranging from [-100 to 2000ms] relative to the onset of a target. For each target t, we selected at random another distractor in the same sequence and created a matching epoch relative to the onset of that distractor. Choosing distractors in this way meant that the number of targets and distractors were balanced and matched per sequence (and chance level accuracy is 50%) and that the neural representations of targets and distractors were unlikely to overlap in a consistent manner.

Decoding analysis

We applied an MVPA decoding pipeline (Grootswagers, Wardle, et al., 2017; Oosterhof, Connolly, & Haxby, 2016) to the EEG channel voltages, consisting of a regularised linear discriminant analysis (LDA) classifier applied in an exemplar-by-sequence-cross-validation approach. Decoding was performed within subject, and the results were analysed at the group level. This pipeline was applied to each stimulus presentation epoch in the sequence to investigate object representations in fast sequences. To investigate the temporal dynamics of target selection, we compared neural responses to targets with those to non-

target distractor stimuli. Classifiers were then trained to distinguish targets from non-targets separately

for the rapid (5Hz) and ultra-rapid (20Hz) sequences, and for boat and star target sequences.

We investigated object representations for the 200 non-target images using multiple categorical

distinctions. First, we decoded three contrasts that impose different amounts of categorical abstraction.

At the highest level, we decoded animacy (i.e., animate versus inanimate objects). The next contrast was

the category tier (10 classes, e.g., mammal, insect, furniture, tool, etc.) where we decoded all 45 possible

pairwise combinations. The lowest categorical level was the object level (50 classes, e.g., cow, butterfly,

table, hammer, etc.). Here, we decoded all 1225 possible pairwise object combinations (i.e., cow versus

butterfly, cow versus table, etc.). Finally, at the lowest level, we investigated image-level representations

by decoding all 19900 possible pairwise combinations of the 200 stimuli. We report the mean pairwise

classification accuracies, so that chance-level accuracy for all comparisons is at 50%, which aids comparing

accuracies across contrasts.

To investigate similarities in underlying object representation signals between the rapid (5Hz) and ultra-

rapid (20Hz) presentations, we used a temporal generalisation approach (Carlson, Hogendoorn, Kanai,

Mesik, & Turret, 2011; King & Dehaene, 2014; Meyers, Freedman, Kreiman, Miller, & Poggio, 2008). To

test generalisation between the conditions, we trained classifiers on all time points in the data from the

rapid sequences and tested them on all time points in the data from the ultra-rapid sequences. We

repeated this for the inverse (training on ultra-rapid and testing on rapid), and averaged the resulting

time-generalisation matrices (Kaiser, Azzalini, & Peelen, 2016).

All steps in the decoding analysis were implemented in CoSMoMVPA (Oosterhof et al., 2016). For the

categorical contrasts that grouped more than one image, we used an image-by-sequence-cross-validation

scheme so that identical images were not part of both training and test set (Carlson et al., 2013;

Grootswagers, Wardle, et al., 2017). This was implemented by first splitting the data into four sets, where

the first set consisted of the first images from each of the 50 object categories (i.e., cow-1, table-1 etc.),

the second set of the second images (i.e., cow-2, table-2 etc.), etc. One of these sets was used as test

data, and the other three as training data for the leave-one-sequence out cross-validation, where all data

from one sequence was used as test data, and data from the remaining sequences as training data. For

each decoding contrast, this resulted in 160 (4 images by 40 sequences) cross-validation partitions. Where

image-by-sequence cross-validation was not possible (i.e., image-level and target-distractor decoding),

we used a leave-one-sequence-out cross-validation scheme, where all epochs from one sequence were

used as test set, resulting in 40 cross-validation partitions. We used a linear discriminant analysis (LDA)

classifier (implemented in CoSMoMVPA) and report the mean cross-validated decoding accuracy.

Representational Similarity Analysis

To study the emerging representational structure of our 200 stimuli, we analysed our data using the

Representational Similarity Analysis (RSA) framework (Kriegeskorte & Kievit, 2013; Kriegeskorte, Mur, &

Bandettini, 2008; Kriegeskorte, Mur, Ruff, et al., 2008), which allows comparing models of object

representations. The decoding results at the image level were organised into a 200 by 200 neural

representational dissimilarity matrix (RDM), which for each pair of images, contained the mean cross-

validated decoding accuracy (images that evoke more dissimilar neural responses are better decodable).

One neural RDM was created for each subject, and each time point (group mean RDM at 100-400ms

shown in Figure 2, top row). We compared the neural RDMs to six candidate models; first, we created one

model for each of the three categorical levels, grouping images from the same category (Figure 2, second

row). We also used three low-level image feature control models (Figure 2, third row), which were created

by correlating the vectorized experimental images. The models consisted of an image silhouette similarity

model, which is based on the binary alpha layer of the stimuli and is a good predictor of differences in

brain responses (Carlson et al., 2011; Teichmann, Grootswagers, Carlson, & Rich, 2018; Wardle,

Kriegeskorte, Grootswagers, Khaligh-Razavi, & Carlson, 2016)), a model based on the CIELAB-colour values

of the stimuli, and a model based on the difference in luminance of the stimuli. Figure 2 shows the

candidate models and the correlation distance between each of the candidate models (bottom row).

The time-varying neural RDMs of each subject were then modelled as a linear combination of the

candidate models using a GLM (Oosterhof et al., 2016; Proklova, Kaiser, & Peelen, 2017); for each time

point, the lower triangles of the neural RDM and candidate models were vectorised, and regression

coefficients were obtained for all candidate models. This resulted in one beta estimate for each model,

subject, and time point. We then analysed at the group level the mean beta estimates across subjects. To

visualise the dynamic representational structure, at each point in time, we created a two-dimensional

embedding of all 200 images. To compute the two-dimensional embedding, we applied t-SNE (Maaten &

Hinton, 2008) to the mean neural RDMs. This approach finds an embedding of the multi-dimensional

space in a two-dimensional representation so that the distances between points reflect their

multidimensional pattern dissimilarities as best as possible.

Figure 2. Candidate models used in the RSA. Top row: time-averaged neural RDMs for rapid and ultra-rapid conditions. Each point in the 200 by 200 matrix represents the dissimilarity (here: decoding accuracy) between a pair of images. Second row: categorical models predict that responses to stimuli from the same category are more similar than responses to stimuli for different categories. Third row: image properties entered the regression as control models to quantify the contribution of low-level visual differences to the neural dissimilarities. Bottom row left: dissimilarities (1-correlation) between all candidate models. Bottom row right: model dissimilarities projected in a 2-dimensional space using classical multi-dimensional scaling, which returns a configuration so that the distance between points approximates their dissimilarities. The order of the images in the 200 x 200 RDMs are the same as in Figure 1.

Statistical inference

In this study, we used Bayes factors (Dienes, 2011; Jeffreys, 1998; Rouder, Speckman, Sun, Morey, & Iverson, 2009; Wagenmakers, 2007) to determine the evidence for the null and alternative hypotheses. For the alternative hypothesis of above-chance decoding or correlation, a uniform prior was used ranging from the maximum value observed during the baseline (before stimulus onset) up to 1 (e.g., 100% decoding). For testing a non-zero difference between decoding accuracies, a uniform prior was used ranging from the maximum absolute difference observed during the baseline up to 50% (0.5). We then calculated the Bayes factor (BF) which is the probability of the data under the alternative hypothesis relative to the null hypothesis. We thresholded BF>3 and BF>10 as substantial and strong evidence for the alternative hypothesis, and BF<1/3 and BF<1/10 for substantial/strong evidence in favour of the null hypothesis (Jeffreys, 1998; Wetzels et al., 2011). BF that lie between 1/3 and 3 indicate insufficient evidence for either hypothesis.

Results

We examined the representational dynamics of 200 different visual objects (Figure 1A), presented in rapid and ultra-rapid sequences (Figure 1B) using EEG. During the sequences, participants detected targets (boats or stars).

The effect of target type and target selection

Participants were generally above chance (25%) at detecting targets (boats or stars) in the rapid 5Hz and ultra-rapid 20Hz sequences (Figure 3A-B). There was no difference in performance between the boat and star conditions (all BF < 1/3). On incorrect trials, responses often differed no more than one from the correct answer (Figure 3, right columns). This indicates that in general, participants missed at most one target when they responded incorrectly.

Figure 3: Behavioural results of target detection performance for rapid (A) and ultra-rapid (B) experimental sessions. Left columns show the mean proportion of correct responses for each participant separately for boat target sequences and star target sequences. Right columns show the mean approximately-correct (i.e., response differed by at most 1 from the correct answer) accuracy for each participant. Bayes Factors (BF) comparing mean accuracies between the boat and star sequences are listed above the x-axis.

The temporal dynamics of target selection were revealed by decoding targets from non-targets. The time-varying mean target-distractor decoding accuracy was computed separately for boat sequences and star sequences (Figure 4). Target-distractor decoding performance peaked around 67% in the rapid 5Hz session (Figure 4A), and around 60% in the ultra-rapid 20Hz session (Figure 4B). For both presentation durations, peak decoding performance was around 500ms. In both sessions, decoding for star targets was

274   above chance earlier than for boats, which suggests that stars targets were easier to distinguish overall.

275   Decoding performance remained above chance for over 1000 ms in the rapid sequences, and for

276   approximately 800 ms in the ultra-rapid sequences.

Figure 4. Decoding target versus distractor. For each target, a distractor was randomly selected from the same sequence, and classifiers were trained on target versus distractor. Plots show the mean leave-one-sequence-out cross-validated accuracy for the rapid 5Hz session (A), and the ultra-rapid 20Hz session (B). Shaded areas show the standard error of the mean across participants. Results are shown separately for boat target sequences and star target sequences. Dots below plots indicate thresholded Bayes Factors

(BF, see inset) for the boat (top row) and star (middle row) sequences compared to chance and for the difference between boat and star sequences (bottom row). C-D temporal generalisation results. The left columns show classifier generalisation performance for the boat (C) and star (D) between the different presentation durations. The right columns show corresponding thresholded Bayes Factors (Yellow indicating above chance, and blue indicating below chance decoding). Higher than chance generalisation (yellow) above the diagonal indicates slower processing of images in the rapid session relative to the ultra-rapid session.

The temporal generalisation approach revealed target selection was very similar between the rapid 5Hz and ultra-rapid 20Hz sequences. For both boat and star target sequences, the onset of target decoding occurred around the same time, and cross-decoding was most evident along the diagonal, suggesting that target selection processes occurred at the same latencies regardless of the sequence speed and image duration (Figure 4c-d).

Decoding categorical contrasts of 200 stimuli

In the rapid (5Hz) condition, we observed above chance decoding for all categorical levels (Figure 5, blue lines), starting at 100ms after stimulus onset. For the animacy level, the results showed three distinct peaks in decoding (150, 200ms and 400ms). In contrast, peak decoding happened around 200ms for category and object decoding and 130ms for image decoding. For all categorical levels, above-chance decoding was sustained until around 500ms. Note that at 500ms, there were already two new stimuli presented.

In the ultra-rapid condition (Figure 5, green lines), we again observed above-chance decoding for all levels. Notably, the onset of decoding was around the same time point as in the rapid session and subsequent decoding followed the same trajectory but diverged later in the time series (indicated by the bottom row of Bayes factors). The overall peak decoding performance was lower, and the peak decoding time points appeared earlier in the time series. Decoding for all comparisons except object decoding remained above chance until around 300ms, which included five subsequent stimulus presentations. There was no

difference between distractor processing on boat target and star target trials (BF < 1/10) for all categorical

contrasts.

Temporal generalisation analyses were performed to compare categorical decoding between the rapid

and ultra-rapid conditions. For all three categorical levels, we observed similar onsets between

presentation durations, but longer subsequent processing for the rapid condition relative to the ultra-

rapid condition (Figure 6). Notably, for the animacy distinction there was no evidence of generalisation

between the rapid sequence around 500-600ms and the ultra-rapid sequence at any time point, despite

a difference between decoding accuracies during this time period (as was seen in Figure 5). This suggests

that a high-level animacy-related process was present in the slower condition but absent in the faster

condition. The temporal generalisation analyses also showed consistent below chance generalisation

between the early and late responses. This phenomenon is consistent with previous decoding studies on

visual object categorisation, and has been suggested to be caused by the stimulus offset, or by an

adaptation or inhibition signal (Carlson et al., 2011, 2013; Contini et al., 2017).

A   Decoding Animacy

B   Decoding Category

C   Decoding Object

D   Decoding Image

Figure 5. Mean decoding accuracy for rapid and ultra-rapid image duration sessions. A) Decoding animacy
(animate versus inanimate). B) Mean pairwise decoding for the 10 categories (e.g., mammal, tools). C)
Mean pairwise decoding for 50 object categories (e.g., dog, giraffe). D) Mean pairwise decoding for all 200
images. Shaded areas depict standard error of the mean across subjects. Dots below plots indicate
thresholded Bayes Factors (BF, see inset) for the rapid session compared to chance (top rows), ultra-rapid
session compared to chance (middle rows) and for the difference between rapid and ultra-rapid results
(bottom rows).

Figure 6. Temporal generalisation results. The left columns show classifier generalisation performance for the three categorical levels (A-C) between the different presentation durations. The right columns show corresponding thresholded Bayes Factors (Yellow indicating above chance, and blue indicating below chance decoding). Higher than chance generalisation (yellow) above the diagonal indicates slower processing in the rapid session relative to the ultra-rapid session.

Representational dynamics of 200 stimuli

Emerging representational structures of the 200 stimuli were studied in the Representational Similarity Analysis (RSA) framework (Kriegeskorte & Kievit, 2013; Kriegeskorte, Mur, & Bandettini, 2008; Kriegeskorte, Mur, Ruff, et al., 2008). A neural representational dissimilarity matrix (neural RDM) was created for each subject, and each time point containing the dissimilarities between all 200 stimuli. Neural RDMs were modelled as a linear combination of six candidate models; low-level image silhouette, colour and luminance models, and one model for each of the three categorical levels. We then analysed the mean beta estimates of the candidate models (Figure 7). For both presentation rates, the silhouette model captured the early response in the data, followed by the colour, object, and category models. In the rapid condition, the animacy model emerged last, while in the ultra-rapid sequences the animacy model did not explain the neural RDM at any time point. To visualise and qualitatively explore the dynamic representational structure, we created a two-dimensional embedding of all 200 images at three time points (200, 300, and 400ms), where the distance between images reflects their mean dissimilarity across subjects (Figure 8).

Figure 7. RSA model tests. The neural RDMs of each subject were modelled as linear combination of six candidate models: three categorical models (A&B), and three image feature models (C&D), separately for the rapid (5Hz) sequences (A&C), and for the ultra-rapid (20Hz) sequences (B&D). Lines show estimated betas for the models. Shaded areas reflect the standard error across subjects. Dots below plots indicate the thresholded Bayes Factors (BF, see inset) for each beta estimate.

A RSA rapid - MDS at 200ms

B RSA ultra-rapid - MDS at 200ms

aquatic
bird
human
insect
mammal
clothing
fruits
furniture
plants
tools

C RSA rapid - MDS at 300ms

D RSA ultra-rapid - MDS at 300ms

E RSA rapid - MDS at 400ms

F RSA ultra-rapid - MDS at 400ms

Figure 8. Representational structure at three time points. Stimuli are embedded in a two-dimensional space that reflects their pairwise distances. Stimuli that are shown further apart in this representation evoked more dissimilar neural responses. The rows show three time points in the response, and the left and right columns show data for the rapid and ultra-rapid conditions respectively. In the bottom left corner of each plot, the same arrangement is shown, with images represented by dots coloured according to the 10 categories (see inset). In the top left corner of each plot, the neural RDMs for each time point are shown using the same scale as each other, ranging between 0.5 (chance) and 0.6 with lighter colours representing higher pairwise decoding accuracies.

Discussion

In the current study, we characterised the representational dynamics of a large number of images in fast presentation sequences. Previous work has used MEG and EEG decoding to investigate representations of much smaller image sets using slow image presentation paradigms (Carlson et al., 2013; Cichy et al., 2014; Contini et al., 2017; Grootswagers, Ritchie, et al., 2017; Kaiser et al., 2016; Kaneshiro et al., 2015; Proklova et al., 2017; Ritchie, Tovar, & Carlson, 2015; Simanova, van Gerven, Oostenveld, & Hagoort, 2010); here we extend this work by looking at the representations of 200 objects during RSVP using standard 64-channel EEG. For rapid 5Hz and ultra-rapid 20Hz sequences, all 200 images could be decoded at four different categorical levels. Furthermore, neural responses to targets were distinct from those to distractor stimuli. Above-chance decoding outlasted subsequent image presentations, supporting the idea that multiple object representations can co-exist in the visual system at different stages of processing (Marti & Dehaene, 2017). In keeping with the known hierarchical nature of the visual system, RSA model testing suggested neural responses relied on low-level visual features early in the time series, and subsequent processing was associated with increasing category abstraction (Carlson et al., 2013; Cichy et al., 2014). Overall, we show the unprecedented ability of the human brain to process images when pushing the limits of temporal perception.

Target decoding results revealed that neural responses to distractors diverged from star target responses much earlier than boat targets. This supports our initial hypothesis that star targets would be distinct from

other images based on low-level visual features, unlike boat targets. The behavioural results, however, revealed target detection did not differ across boat and star trials, indicating that there was no "pop-out" effect of stars. This is despite anecdotal reports that participants found the star targets easier. Target versus distractor decoding for boats and stars peaked at 500ms, supporting previous evidence that high level cognitive processes mediate temporal selection (Marti & Dehaene, 2017; Sergent, Baillet, & Dehaene, 2005). These results suggest that distinguishable low-level features do not help with target detection in RSVP sequences, at least in the current design with such high variation in distractor images.

Target processing did not differ markedly across the different experimental durations. In both the rapid and ultra-rapid sessions, targets could be distinguished from distractors for a long period of time, but this was exaggerated for the rapid session, where decoding was above chance for over 1000ms, compared to 800ms in the ultra-rapid condition. Decoding was also higher in the rapid session relative to the ultra-rapid session, but the dynamics of temporal selection processes were largely the same. The time of peak decoding (500ms) was the same for both sessions, and time generalisation analyses revealed neural processes occurred at the same latency in both sessions. This suggests that processes of target selection are largely the same regardless of image presentation duration and frequency. Notably, target processing was much more prolonged than categorical decoding for distractors, again indicative of higher level cognitive processes at play for target detection. Note that the current experimental design did not allow us to see which targets in the stream were missed, but effects are likely to be amplified for correctly detected targets. Indeed, Marti & Dehaene (2017) found that late responses were sustained for reported stimuli. Taken together, our results show that late target-related responses do not differ dramatically in faster sequences relative to slower sequences.

Neural responses to the 200 non-task-relevant (distractor) objects are indicative of fairly automatic early visual processing and divergence at later processing stages according to image duration. For all contrasts,

image presentation duration and cognitive task set did not influence the earliest processing stages. When looking at decoding for the durations separately, onsets seemed to be earlier for the rapid than ultra-rapid conditions, in accordance with recent work showing earlier onsets for longer image durations (Mohsenzadeh et al., 2018). It is important to note, however, that higher signal strengths can also lead to earlier decoding onsets (Grootswagers, Wardle, et al., 2017), thus differences between onsets must be interpreted with caution in the context of larger peak decoding. Crucially, here Bayes factors revealed evidence that there was no difference in decoding at these early time points between the rapid and ultra-rapid image sequences (<150ms from image onset). Results from the temporal generalisation approach supported this view, by showing that initial processing stages occurred at the same time for the rapid and ultra-rapid sequences, as seen by the above-chance decoding on the diagonal in Figure 5. Finally, for the three categorical levels (animacy, category and object), Bayesian analyses revealed distractor processing did not differ between boat and star trials. These results suggest initial neural responses to all visual stimuli were similar regardless of their presentation duration.

Despite similar early processing stages, later processing diverged according to image presentation duration. Representations during rapid sequences were stronger and lasted longer than those during ultra-rapid sequences, and temporal generalisation analyses showed that processes were prolonged for the rapid relative to the ultra-rapid condition. It could be that longer image durations allow more consolidation, potentially due to recurrent processing. It is also possible that longer durations allow time to reach some kind of threshold, which triggers further processing. Note that image duration and ISI are conflated in this design, so we cannot conclude whether or if stronger and longer processing occurs due to longer image presentation or due to delayed masking from the next stimulus. Future work can build on this approach to investigate the temporal limits of visual perception.

The RSA regression analyses provided insight into the differences in processing between the rapid and ultra-rapid sequences. The deep neural network decoding results (Figure 1) clearly showed that animacy, category and object can be decoded based on low-level visual features, demonstrating that the different category levels are inherently inter-related (See also Figure 2). The regression RSA technique aimed to dissociate the unique contributions of each model. In accordance with the decoding results, processes early in the time series (~100-150ms) were mostly explained by the low-level silhouette model and then the colour model for the rapid and ultra-rapid conditions (Carlson et al., 2011). Subsequent processing, however, elucidated the differential contributions of the different categorical contrasts, and how this varied for the different image durations. For the rapid condition, the category model appeared to have the largest unique contribution around 200ms, and the animacy model accounted for the most variance at about 400ms, indicating that increasing category abstraction occurred at higher levels of visual processing (Carlson et al., 2013; Cichy et al., 2014; Contini et al., 2017; Kriegeskorte, Mur, Ruff, et al., 2008). In contrast, the animacy model had no unique contribution to the signal for the in ultra-rapid sequences. The time course of the animacy model regression for the rapid condition (>350ms) suggests that the animate-inanimate difference might exclusively account for the prolonged decoding in the rapid condition relative to the ultra-rapid condition. This could imply that a high-level animacy effect requires sufficient evidence accumulation to proceed, which does not happen at ultra-rapid presentation rates. The finding that longer image presentations allow higher level processing is supported by steady-state visual evoked potential (SSVEP) work showing that images presented at faster frequencies are biased towards earlier visual processes in contrast to slower frequencies which allow higher level processing (Collins, Robinson, & Behrmann, 2018).

When qualitatively inspecting the visualisation of the representational structure (Figure 8), we noticed a clear animate versus inanimate organisation in the rapid presentation condition. At 200ms in the response, the structure reflected mostly natural versus artificial, with plants, fruits and animals all

clustering on one side. In line with the decoding and RSA results, the structure at 400ms showed a clear

animate – inanimate distinction (Caramazza & Shelton, 1998), which is commonly observed in neural

responses in the ventral temporal cortex (Cichy et al., 2014; Konkle & Caramazza, 2013; Kriegeskorte,

Mur, Ruff, et al., 2008; Proklova, Kaiser, & Peelen, 2016) and has been shown to match human

categorisation behaviour well (Bracci & Op de Beeck, 2016; Carlson, Ritchie, Kriegeskorte, Durvasula, &

Ma, 2014; Grootswagers, Cichy, & Carlson, 2018; Mur et al., 2013; Ritchie, Tovar, & Carlson, 2015). In the

animate – inanimate organisation primates were located at the far end of the animate side, which may

reflect a continuum of biological classes in the brain (Connolly et al., 2012; Sha et al., 2015) or typicality

(Grootswagers, Ritchie, et al., 2017; Iordan, Greene, Beck, & Fei-Fei, 2016; Posner & Keele, 1968; E. H.

Rosch, 1973; E. Rosch & Mervis, 1975). No animacy structure was apparent for the ultra-rapid condition

(as evidenced by the RSA results), but rather individual categorical clusters seem to have emerged (in line

with the RSA results), such as human faces, and, later, humans and primates as a category. Interestingly,

in these visualisations gloves were grouped with humans and primates, which could mean they were

perceived as body parts, rather than inanimate objects. While these visualisations allow for such

qualitative speculation, the quantitive RSA modelling results highlight the level of detail in the

representation structure that can be obtained using EEG decoding and fast presentation rates. Here, we

used a common 64-channel EEG, but future work can use this approach in combination with high-density

EEG or other neuroimaging methods that are sensitive to finer spatial patterns, such as MEG.

One remaining question is the role that low-level image statistics play in our results. The RSA approach

showed that low-level control models explained early neural responses to the stimuli. The current

stimulus set consisted of segmented coloured objects, which was not matched on low-level features such

as colour, orientation, shape, and size. Future work can build on the current paradigm using a stimulus

set that for example contains orthogonal shape and category dimensions (Bracci, Kalfas, & Op de Beeck,

2017; Bracci & Op de Beeck, 2016; Proklova et al., 2017, 2016), or test the decodability of these features

using for example texture stimuli with similar features (Long, Konkle, Cohen, & Alvarez, 2016; Long, Yu, &

Konkle, 2017). Such extensions can help unravel the relationship between object features and categories,

and increase our understanding of how this inherent relationship guides categorical abstraction in the

visual system.

In conclusion, our results show that we can study the representational dynamics of more than 200 objects

in one short EEG session. We were able to characterise the time courses of multiple categorical contrasts

from the same images, indicating that all objects reached abstract categorical stages of perception despite

being presented for short durations. Here, we took advantage of the high temporal resolution of both the

human visual system and common neuroimaging techniques such as EEG and MEG. These results confirm

that long ISIs are not necessary for multivariate analyses, as they do not require a resting baseline as in

ERP analyses. Thus, future MVPA studies on visual perception should consider using fast presentation

rates as this allows for a substantial increase of the number of presentations, stimuli, or experimental

conditions. This offers unprecedented potential for studying the temporal dynamics of visual perception

and attention.

Acknowledgements

We thank Nick McNair for assisting with data collection. This research was supported by an Australian

Research Council Future Fellowship (FT120100816) and an Australian Research Council Discovery project

(DP160101300) awarded to T.A.C. The authors acknowledge the University of Sydney HPC service for

providing High Performance Computing resources. The authors declare no competing financial interests.

References

Bracci, S., Kalfas, I., & Op de Beeck, H. P. (2017). The ventral visual pathway represents animal

appearance over animacy, unlike human behavior and deep neural networks. *BioRxiv*, 228932.

https://doi.org/10.1101/228932

Bracci, S., & Op de Beeck, H. P. (2016). Dissociations and Associations between Shape and Category

Representations in the Two Visual Pathways. *Journal of Neuroscience*, *36*(2), 432–444.

https://doi.org/10.1523/JNEUROSCI.2314-15.2016

Caramazza, A., & Mahon, B. Z. (2003). The organization of conceptual knowledge: the evidence from

category-specific semantic deficits. *Trends in Cognitive Sciences*, *7*(8), 354–361.

https://doi.org/10.1016/S1364-6613(03)00159-1

Caramazza, A., & Shelton, J. R. (1998). Domain-Specific Knowledge Systems in the Brain: The Animate-

Inanimate Distinction. *Journal of Cognitive Neuroscience*, *10*(1), 1–34.

https://doi.org/10.1162/089892998563752

Carlson, T. A., Hogendoorn, H., Kanai, R., Mesik, J., & Turret, J. (2011). High temporal resolution

decoding of object position and category. *Journal of Vision*, *11*(10), 9.

https://doi.org/10.1167/11.10.9

Carlson, T. A., Ritchie, J. B., Kriegeskorte, N., Durvasula, S., & Ma, J. (2014). Reaction Time for Object

Categorization Is Predicted by Representational Distance. *Journal of Cognitive Neuroscience*,

26(1), 132–142. https://doi.org/10.1162/jocn_a_00476

Carlson, T. A., Tovar, D. A., Alink, A., & Kriegeskorte, N. (2013). Representational dynamics of object

vision: The first 1000 ms. *Journal of Vision*, *13*(10), 1. https://doi.org/10.1167/13.10.1

Cichy, R. M., Pantazis, D., & Oliva, A. (2014). Resolving human object recognition in space and time.

Nature Neuroscience, *17*(3), 455–462. https://doi.org/10.1038/nn.3635

Collins, E., Robinson, A. K., & Behrmann, M. (2018). Distinct neural processes for the perception of

familiar versus unfamiliar faces along the visual hierarchy revealed by EEG. *NeuroImage*, *181*,

120–131. https://doi.org/10.1016/j.neuroimage.2018.06.080

Connolly, A. C., Guntupalli, J. S., Gors, J., Hanke, M., Halchenko, Y. O., Wu, Y.-C., … Haxby, J. V. (2012).

The Representation of Biological Classes in the Human Brain. *The Journal of Neuroscience*, *32*(8),

2608–2618. https://doi.org/10.1523/JNEUROSCI.5547-11.2012

Contini, E. W., Wardle, S. G., & Carlson, T. A. (2017). Decoding the time-course of object recognition in

the human brain: From visual features to categorical decisions. *Neuropsychologia*, *105*, 165–176.

https://doi.org/10.1016/j.neuropsychologia.2017.02.013

Crouzet, S. M., Kirchner, H., & Thorpe, S. J. (2010). Fast saccades toward faces: Face detection in just 100

ms. *Journal of Vision*, *10*(4), 16. https://doi.org/10.1167/10.4.16

Delorme, A., & Makeig, S. (2004). EEGLAB: an open source toolbox for analysis of single-trial EEG

dynamics including independent component analysis. *Journal of Neuroscience Methods*, *134*(1),

9–21. https://doi.org/10.1016/j.jneumeth.2003.10.009

Dienes, Z. (2011). Bayesian Versus Orthodox Statistics: Which Side Are You On? *Perspectives on*

Psychological Science, *6*(3), 274–290. https://doi.org/10.1177/1745691611406920

Grill-Spector, K., & Weiner, K. S. (2014). The functional architecture of the ventral temporal cortex and

its role in categorization. *Nature Reviews Neuroscience*, *15*(8), 536–548.

https://doi.org/10.1038/nrn3747

Grootswagers, T., Cichy, R. M., & Carlson, T. A. (2018). Finding decodable information that can be read

out in behaviour. *NeuroImage*, *179*, 252–262.

https://doi.org/10.1016/j.neuroimage.2018.06.022

Grootswagers, T., Ritchie, J. B., Wardle, S. G., Heathcote, A., & Carlson, T. A. (2017). Asymmetric

Compression of Representational Space for Object Animacy Categorization under Degraded

Viewing Conditions. *Journal of Cognitive Neuroscience*, *29*(12), 1995–2010.

https://doi.org/10.1162/jocn_a_01177

Grootswagers, T., Wardle, S. G., & Carlson, T. A. (2017). Decoding Dynamic Brain Patterns from Evoked

Responses: A Tutorial on Multivariate Pattern Analysis Applied to Time Series Neuroimaging

Data. *Journal of Cognitive Neuroscience*, *29*(4), 677–697. https://doi.org/10.1162/jocn_a_01068

Haynes, J.-D. (2015). A Primer on Pattern-Based Approaches to fMRI: Principles, Pitfalls, and

Perspectives. *Neuron*, *87*(2), 257–270. https://doi.org/10.1016/j.neuron.2015.05.025

Iordan, M. C., Greene, M. R., Beck, D. M., & Fei-Fei, L. (2016). Typicality sharpens category

representations in object-selective cortex. *NeuroImage*, *134*, 170–179.

https://doi.org/10.1016/j.neuroimage.2016.04.012

Isik, L., Meyers, E. M., Leibo, J. Z., & Poggio, T. (2014). The dynamics of invariant object recognition in

the human visual system. *Journal of Neurophysiology*, *111*(1), 91–102.

https://doi.org/10.1152/jn.00394.2013

Jeffreys, H. (1998). *The theory of probability*. OUP Oxford.

Kaiser, D., Azzalini, D. C., & Peelen, M. V. (2016). Shape-independent object category responses revealed

by MEG and fMRI decoding. *Journal of Neurophysiology*, *115*(4), 2246–2250.

https://doi.org/10.1152/jn.01074.2015

Kaneshiro, B., Guimaraes, M. P., Kim, H.-S., Norcia, A. M., & Suppes, P. (2015). A Representational

Similarity Analysis of the Dynamics of Object Processing Using Single-Trial EEG Classification.

PLOS ONE, *10*(8), e0135697. https://doi.org/10.1371/journal.pone.0135697

Keysers, C., Xiao, D.-K., Földiák, P., & Perrett, D. I. (2001). The Speed of Sight. *Journal of Cognitive*

Neuroscience, *13*(1), 90–101. https://doi.org/10.1162/089892901564199

Kiani, R., Esteky, H., Mirpour, K., & Tanaka, K. (2007). Object Category Structure in Response Patterns of

Neuronal Population in Monkey Inferior Temporal Cortex. *Journal of Neurophysiology*, *97*(6),

4296–4309. https://doi.org/10.1152/jn.00024.2007

King, J.-R., & Dehaene, S. (2014). Characterizing the dynamics of mental representations: the temporal

generalization method. *Trends in Cognitive Sciences*, *18*(4), 203–210.

https://doi.org/10.1016/j.tics.2014.01.002

Konkle, T., & Caramazza, A. (2013). Tripartite Organization of the Ventral Stream by Animacy and Object

Size. *Journal of Neuroscience*, *33*(25), 10235–10242. https://doi.org/10.1523/JNEUROSCI.0983-

13.2013

Kriegeskorte, N., & Kievit, R. A. (2013). Representational geometry: integrating cognition, computation,

and the brain. *Trends in Cognitive Sciences*, *17*(8), 401–412.

https://doi.org/10.1016/j.tics.2013.06.007

Kriegeskorte, N., Mur, M., & Bandettini, P. A. (2008). Representational Similarity Analysis - Connecting

the Branches of Systems Neuroscience. *Frontiers in Systems Neuroscience*, *2*, 4.

https://doi.org/10.3389/neuro.06.004.2008

Kriegeskorte, N., Mur, M., Ruff, D. A., Kiani, R., Bodurka, J., Esteky, H., … Bandettini, P. A. (2008).

Matching Categorical Object Representations in Inferior Temporal Cortex of Man and Monkey.

Neuron, *60*(6), 1126–1141. https://doi.org/10.1016/j.neuron.2008.10.043

Long, B., Konkle, T., Cohen, M. A., & Alvarez, G. A. (2016). Mid-level perceptual features distinguish

objects of different real-world sizes. *Journal of Experimental Psychology: General*, *145*(1), 95.

Long, B., Yu, C.-P., & Konkle, T. (2017). A mid-level organization of the ventral stream. *BioRxiv*, 213934.

https://doi.org/10.1101/213934

Maaten, L. van der, & Hinton, G. (2008). Visualizing Data using t-SNE. *Journal of Machine Learning*

Research, *9*(Nov), 2579–2605.

Macé, M. J.-M., Thorpe, S. J., & Fabre-Thorpe, M. (2005). Rapid categorization of achromatic natural

scenes: how robust at very low contrasts? *European Journal of Neuroscience*, *21*(7), 2007–2018.

https://doi.org/10.1111/j.1460-9568.2005.04029.x

Mack, M. L., Gauthier, I., Sadr, J., & Palmeri, T. J. (2008). Object detection and basic-level categorization:

613   Sometimes you know it is there before you know what it is. *Psychonomic Bulletin & Review*,

614   *15*(1), 28–35. https://doi.org/10.3758/PBR.15.1.28

615   Mack, M. L., & Palmeri, T. J. (2011). The Timing of Visual Object Categorization. *Frontiers in Psychology*,

616   *2*. https://doi.org/10.3389/fpsyg.2011.00165

617   Mack, M. L., & Palmeri, T. J. (2015). The Dynamics of Categorization: Unraveling Rapid Categorization.

618   *Journal of Experimental Psychology: General*, No Pagination Specified.

619   https://doi.org/10.1037/a0039184

620   Mahon, B. Z., & Caramazza, A. (2011). What drives the organization of object knowledge in the brain?

621   *Trends in Cognitive Sciences*, *15*(3), 97–103. https://doi.org/10.1016/j.tics.2011.01.004

622   Marti, S., & Dehaene, S. (2017). Discrete and continuous mechanisms of temporal selection in rapid

623   visual streams. *Nature Communications*, *8*(1), 1955. https://doi.org/10.1038/s41467-017-02079-

624   x

625   Meyers, E. M., Freedman, D. J., Kreiman, G., Miller, E. K., & Poggio, T. (2008). Dynamic Population

626   Coding of Category Information in Inferior Temporal and Prefrontal Cortex. *Journal of*

627   *Neurophysiology*, *100*(3), 1407–1419. https://doi.org/10.1152/jn.90248.2008

628   Mohsenzadeh, Y., Qin, S., Cichy, R., & Pantazis, D. (2018). Ultra-Rapid Serial Visual Presentation Reveals

629   Dynamics of Feedforward and Feedback Processes in the Ventral Visual Pathway. *BioRxiv*,

630   350421. https://doi.org/10.1101/350421

631   Mur, M., Meys, M., Bodurka, J., Goebel, R., Bandettini, P. A., & Kriegeskorte, N. (2013). Human Object-

632   Similarity Judgments Reflect and Transcend the Primate-IT Object Representation. *Frontiers in*

633   *Psychology*, *4*. https://doi.org/10.3389/fpsyg.2013.00128

634   Oostenveld, R., & Praamstra, P. (2001). The five percent electrode system for high-resolution EEG and

635   ERP measurements. *Clinical Neurophysiology*, *112*(4), 713–719. https://doi.org/10.1016/S1388-

636   2457(00)00527-7

Oosterhof, N. N., Connolly, A. C., & Haxby, J. V. (2016). CoSMoMVPA: Multi-Modal Multivariate Pattern

Analysis of Neuroimaging Data in Matlab/GNU Octave. *Frontiers in Neuroinformatics*, *10*.

https://doi.org/10.3389/fninf.2016.00027

Peelen, M. V., & Caramazza, A. (2012). Conceptual Object Representations in Human Anterior Temporal

Cortex. *Journal of Neuroscience*, *32*(45), 15728–15736.

https://doi.org/10.1523/JNEUROSCI.1953-12.2012

Posner, M. I., & Keele, S. W. (1968). On the genesis of abstract ideas. *Journal of Experimental*

Psychology, *77*(3p1), 353. http://dx.doi.org/10.1037/h0025953

Potter, M. C. (1975). Meaning in visual search. *Science*, *187*(4180), 965–966.

Potter, M. C. (1976). Short-term conceptual memory for pictures. *Journal of Experimental Psychology:*

Human Learning and Memory, *2*(5), 509.

Potter, M. C., Wyble, B., Hagmann, C. E., & McCourt, E. S. (2014). Detecting meaning in RSVP at 13 ms

per picture. *Attention, Perception, & Psychophysics*, *76*(2), 270–279.

Proklova, D., Kaiser, D., & Peelen, M. (2017). MEG sensor patterns reflect perceptual but not categorical

similarity of animate and inanimate objects. *BioRxiv*, 238584. https://doi.org/10.1101/238584

Proklova, D., Kaiser, D., & Peelen, M. V. (2016). Disentangling Representations of Object Shape and

Object Category in Human Visual Cortex: The Animate–Inanimate Distinction. *Journal of*

Cognitive Neuroscience, 1–13. https://doi.org/10.1162/jocn_a_00924

Ritchie, J. B., Tovar, D. A., & Carlson, T. A. (2015). Emerging Object Representations in the Visual System

Predict Reaction Times for Categorization. *PLoS Comput Biol*, *11*(6), e1004316.

https://doi.org/10.1371/journal.pcbi.1004316

Rosch, E. H. (1973). Natural categories. *Cognitive Psychology*, *4*(3), 328–350.

https://doi.org/10.1016/0010-0285(73)90017-0

Rosch, E., & Mervis, C. B. (1975). Family resemblances: Studies in the internal structure of categories.

Cognitive Psychology, *7*(4), 573–605. https://doi.org/10.1016/0010-0285(75)90024-9

Rossion, B., Torfs, K., Jacques, C., & Liu-Shuang, J. (2015). Fast periodic presentation of natural images

reveals a robust face-selective electrophysiological response in the human brain. *Journal of*

Vision, *15*(1), 18–18. https://doi.org/10.1167/15.1.18

Rouder, J. N., Speckman, P. L., Sun, D., Morey, R. D., & Iverson, G. (2009). Bayesian t tests for accepting

and rejecting the null hypothesis. *Psychonomic Bulletin & Review*, *16*(2), 225–237.

Rousselet, G. A., Fabre-Thorpe, M., & Thorpe, S. J. (2002). Parallel processing in high-level categorization

of natural images. *Nature Neuroscience*, *5*(7), 629–630. https://doi.org/10.1038/nn866

Schrimpf, M., Kubilius, J., Hong, H., Majaj, N. J., Rajalingham, R., Issa, E. B., … DiCarlo, J. J. (2018). Brain-

Score: Which Artificial Neural Network for Object Recognition is most Brain-Like? *BioRxiv*,

407007. https://doi.org/10.1101/407007

Sergent, C., Baillet, S., & Dehaene, S. (2005). Timing of the brain events underlying access to

consciousness during the attentional blink. *Nature Neuroscience*, *8*(10), 1391.

Sha, L., Haxby, J. V., Abdi, H., Guntupalli, J. S., Oosterhof, N. N., Halchenko, Y. O., & Connolly, A. C.

(2015). The Animacy Continuum in the Human Ventral Vision Pathway. *Journal of Cognitive*

Neuroscience, *27*(4), 665–678. https://doi.org/10.1162/jocn_a_00733

Simanova, I., van Gerven, M., Oostenveld, R., & Hagoort, P. (2010). Identifying Object Categories from

Event-Related EEG: Toward Decoding of Conceptual Representations. *PLoS ONE*, *5*(12), e14465.

https://doi.org/10.1371/journal.pone.0014465

Simonyan, K., & Zisserman, A. (2014). Very Deep Convolutional Networks for Large-Scale Image

Recognition. In *International Conference on Learning Representations*. Retrieved from

http://arxiv.org/abs/1409.1556

Teichmann, L., Grootswagers, T., Carlson, T., & Rich, A. N. (2018). Decoding Digits and Dice with

Magnetoencephalography: Evidence for a Shared Representation of Magnitude. *Journal of*

Cognitive Neuroscience, *30*(7), 999–1010. https://doi.org/10.1162/jocn_a_01257

Thorpe, S., Fize, D., & Marlot, C. (1996). Speed of processing in the human visual system. *Nature*,

381(6582), 520–522. https://doi.org/doi:10.1038/381520a0

VanRullen, R., & Thorpe, S. J. (2001). The Time Course of Visual Processing: From Early Perception to

Decision-Making. *Journal of Cognitive Neuroscience*, *13*(4), 454–461.

https://doi.org/10.1162/08989290152001880

Wagenmakers, E.-J. (2007). A practical solution to the pervasive problems of p values. *Psychonomic*

Bulletin & Review, *14*(5), 779–804. https://doi.org/10.3758/BF03194105

Wardle, S. G., Kriegeskorte, N., Grootswagers, T., Khaligh-Razavi, S.-M., & Carlson, T. A. (2016).

Perceptual similarity of visual patterns predicts dynamic neural activation patterns measured

with MEG. *NeuroImage*, *132*, 59–70. https://doi.org/10.1016/j.neuroimage.2016.02.019

Wetzels, R., Matzke, D., Lee, M. D., Rouder, J. N., Iverson, G. J., & Wagenmakers, E.-J. (2011). Statistical

Evidence in Experimental Psychology: An Empirical Comparison Using 855 t Tests. *Perspectives*

on Psychological Science, *6*(3), 291–298. https://doi.org/10.1177/1745691611406923