Learning unsupervised feature representations for single cell microscopy images with paired cell inpainting

Alex X Lu[1], Oren Z Kraus[2], Sam Cooper[2], and Alan M Moses[1,3,4]

[1]Department of Computer Science, University of Toronto, Toronto, Canada
[2]Phenomic AI, Toronto, Canada
[3]Department of Cell and Systems Biology, University of Toronto, Toronto, Canada
[4]Center for Analysis of Genome Evolution and Function, University of Toronto, Toronto, Canada

Abstract

Cellular microscopy images contain rich insights about biology. To extract this information, researchers use features, or measurements of the patterns of interest in the images. Here, we introduce a convolutional neural network (CNN) to automatically design features for fluorescence microscopy. We use a self-supervised method to learn feature representations of single cells in microscopy images without labelled training data. We train CNNs on a simple task that leverages the inherent structure of microscopy images and controls for variation in cell morphology and imaging: given one cell from an image, the CNN is asked to predict the fluorescence pattern in a second different cell from the same image. We show that our method learns high-quality features that describe protein expression patterns in single cells both yeast and human microscopy datasets. Moreover, we demonstrate that our features are useful for exploratory biological analysis, by capturing high-resolution cellular components in a proteome-wide cluster analysis of human proteins, and by quantifying multi-localized proteins and single-cell variability. We believe paired-cell inpainting is a generalizable method to obtain feature representations of single cells in multichannel microscopy images.

Introduction

Feature representations of cells within microscopy images are critical for quantifying cell biology in an objective way. Classically, researchers have manually designed features that measure phenomena of interest within images: for example, a researcher studying protein subcellular localization may measure the distance of a fluorescently-tagged protein from the edge of the cell (1), or the correlation of punctuate proteins with microtubules (2). By extracting a range of different features, an image of a cell can be represented as a set of values: these feature representations can then be used for numerous downstream applications, such as classifying the effects of pharmaceuticals on cancer cells (3), or exploratory analyses of protein localization (1,4). The success of these applications depends highly on the quality of the features used: good features are challenging to define, as they must be sensitive to differences in biology, but robust to nuisance variation such as microscopy illumination effects or single cell variation (5).

Convolutional neural networks (CNNs) have achieved sate-of-the-art performance in tasks such as classifying cell biology in high-content microscopy and imaging flow cytometry screens (6–9), or segmenting single cells in images (10,11). A key property driving this performance is that CNNs automatically learn features that are optimized to represent the components of an image necessary for solving a training task (12). Donahue *et al*. (13) and Razavian *et al*. (14) demonstrate that the feature representations extracted by the internal layers of CNNs trained as classifiers achieve state-of-the-art results on even very different applications than the task the CNN was originally trained for; studies specific to bio-imaging report similar observations about the quality of CNN features (6). The features learned by CNNs are thought to be more sensitive to relevant image content than human-designed features, offering a promising alternative for feature-based image analysis applications.

However, learning high-quality features with CNNs is a current research challenge because it depends highly on the training task. For example, autoencoders, or unsupervised CNNs trained to reconstruct input images, usually do not learn features that generalize well to other tasks (15–17). On the other hand, classification tasks result in high-quality features (13,14), but they rely on large, manually-labeled datasets, which are expensive and time-consuming to generate. For example, to address the challenge of labeling microscopy images in the Human Protein Atlas, the project launched a massive crowd-sourcing initiative in collaboration with an online video game, spanning over one year and involving 322,006 gamers (18). Because advances in high-content throughput microscopy are leading to routine generation of thousands of images (19), the new cell morphologies and phenotypes discovered and need for integration of datasets (4) may require the continuous update of models. Unsupervised methods that result in the learning of high-quality features without the use of manual labels would resolve the bottleneck of collecting and updating labels: we would, in principle, be able to learn feature representations for any dataset, without the need for experts to curate, label, and maintain training images.

If obtaining expert-assigned labels for microscopy images is challenging, then obtaining labels for the single cells within these images is even more difficult. Studying biological phenomena at a single-cell level is of current research interest (20): even in genetically-identical cell cultures, single-cell variability can originate from a number of important regulatory mechanisms (21), including the cell cycle (22), stochastic shuttling of transcription factors between compartments (23), or variability in the DNA damage response (24). Thus, ideally, a method would efficiently generate feature representations of single cells for arbitrary datasets using deep learning, without the need for labelled single-cell training data.

In this study, we asked if CNNs could automatically learn high-quality features for representing single cells in microscopy images, without using manual labels for training. We investigate *self-supervised learning,* which proposes training CNNs using labels that are automatically available from input images. Self-supervised learning aims to develop a feature representation in the CNN that is useful for other tasks: the training task is only a pretext, and the CNN may not achieve a useful level of performance at this pretext task. After training, the output of the CNN is discarded, and internal layers of the CNN are used as the features. The logic is that by learning to solve the pretext task, the CNN will develop features that are useful for other applications.

The central challenge in self-supervised learning is defining a pretext task that encourages the learning of generalizable features (25). Successful self-supervised learning strategies in the context of natural images, include CNNs trained to predict the appearance of withheld image patches based upon its context (26), the presence and location of synthetic artifacts in images (25), or geometric rotations applied to input images (27). The idea is that in order to succeed at the pretext task, the CNN needs to develop a strong internal representation of the objects and patterns in the images. When transferred to tasks such as classification, segmentation, or detection, features developed by self-supervised methods have shown state-of-the-art results compared to other unsupervised methods, and in some cases, perform competitively with features learned by supervised CNNs (15,25,27–29).

Here, we present a novel self-supervised learning method designed for microscopy images of protein expression in single cells. Our approach leverages the typical structure of these images to define the pretext training task: in many cases, each image contains multiple genetically identical cells, growing under the same experimental condition, and these cells exhibit similar patterns of protein expression. The cells are imaged in multiple "channels" (such as multiple fluorescence colours) that contain very different information. By exploiting this structure, we define a pretext task that relies only upon image content, with no prior human labels or annotations incorporated. In our examples, one set of channels represents one or more structures in the cell (e.g. the cytosol, nucleus, or cytoskeleton), and another channel represents proteins of interest that have been fluorescently tagged to visualize their localization (with a different protein tagged in each image). Then, given both channels for one cell and the structural markers

for a different cell from the same image, our CNN is trained to predict the appearance of the protein of interest in the second cell, a pretext task that we term "paired cell inpainting" (Figure 1A). To solve this pretext task, we reason that the CNN must identify protein localization in the first (or "source") cell, and reconstruct a similar protein localization in the second (or "target") cell in a way that adapts to single cell variability. In Figure 1, the protein is localized to the nucleoli of human cells – the network must recognize the localization of the protein in the source cell, but also transfer it to the equivalent structures in the target cell, despite differences in the morphology of the nucleus between the two cells. Thus, by design of our pretext task, our method learns representations of single cells.

Figure 1.   An overview of the inputs and targets to the network in paired cell inpainting, and of our proposed architecture. (A) Inputs and targets to the network. We crop a source cell (green border) and a target cell (orange border) from the same image. Then, given all channels for the source cell, and the structural markers for the target cell (in this dataset, the nucleus and the microtubule channels), the network is trained to predict the appearance of the protein channel in the target cell. Images shown are of human cells, with the nucleus colored blue, microtubules colored red, and a specific protein colored

green. (B) Example images from the main proteome-scale datasets we use in this study. The CyCLOPS yeast dataset has proteins tagged with green fluorescent protein (GFP – shown in green), and a cytosolic red fluorescent protein to visualize the cytosol (shown in red) The Human Protein Atlas images as described above in A. (C) Our proposed architecture. Our architecture consists of a source cell encoder and a target marker encoder. The final layers of both encoders are concatenated, and fed into a decoder that outputs the prediction of the target protein $\hat{y}_t$. Layers in our CNN are shown as solid-colored boxes; we label each of the convolutional layers (solid grey boxes) with the number of filters used (e.g. 3x3 Conv 96 means 96 filters are used). We show a real example of a prediction from our trained human cell model given the input image patches in this schematic.

To demonstrate the generalizability of our method, we automatically learn feature representations for datasets of both human and yeast cells, with different morphologies, microscopes and resolutions, and fluorescent tagging schemes (Figure 1B). We demonstrate the quality of the features learned by our models in several use-cases. First, we show that for building classifiers, the features learned through paired cell inpainting exhibit improvements in discriminating protein subcellular localization classes at a single-cell level compared to other unsupervised methods. Next, we demonstrate that our features can be used for unsupervised exploratory analysis, by performing the first proteome-wide cluster analysis of protein analysis in human cells, capturing clusters of proteins in cellular components at a resolution challenging to annotate by human eye. Finally, we demonstrate that our features are useful for single-cell analyses, showing that our features can distinguish phenotypes in spatially-variable single cell populations.

Methodology

Paired Cell Inpainting

We would like to learn a representation for single cells in a collection of microscopy images, I. We define each image i as a collection of single cells, $i = \{c_{i,1} \dots c_{i,n}\}$. We note that the only constraint on i is that its single cells C_i must be considered similar to each other, so i does not need to be strictly defined as a single digital image so long as this is satisfied; in our experiments, we consider an "image" i to be all fields of view corresponding to an experimental well.

We define single cells to be image patches, so $c \in \mathbb{R}^{H \times W \times Z}$, where Z are the channels. We split the images by channel into $c = (x, y)$, where $x \in \mathbb{R}^{H \times W \times Z_1}$, $y \in \mathbb{R}^{H \times W \times Z_2}$, and $Z_1, Z_2 \subseteq Z$. For this work, we assign to Z_1 channels corresponding to structural markers, or fluorescent tags designed to visualize structural components of the cell, where all cells in the collection of images have been labeled with the tag. We assign to Z_2 channels corresponding to proteins, or channels where the tagged biomolecule will vary from image to image.

We define a source cell c_s, which is associated with a target cell c_t satisfying constraints that both cells are from the same image, $c_s \in i_s, c_t \in i_t, i_s = i_t$, and $c_s \neq c_t$. Our goal is to train a neural network that will solve the prediction problem $\hat{y}_t = f(x_s, y_s, x_t) \forall c_s, c_t \in I$, where $\hat{y}_t$ represents the predicted protein channels that vary between images.

For this work, we train the network on the prediction problem by minimizing a standard pixel-wise mean-squared error loss between the predicted target protein $\hat{y}_t$ and the actual target protein y_t:

$$L(\hat{y}_t, y_t) = \frac{1}{h \cdot w} \sum_{h,w} (\hat{y}_{t_{h,w}} - y_{t_{h,w}})^2$$

As with other self-supervised methods, our pretext training task is only meant to develop the internal feature representation of the CNN. After training, $\hat{y}_t$ is discarded, and the CNN is used as a feature extractor. Importantly, our pretext task is unsupervised, because our collection of single cells i are defined solely on image content and not using any human-assigned classes.

One limitation in our pretext task is that some protein localizations are not fully deterministic in respect to the structure of the cell, and are therefore challenging to predict given the inputs we define. In these cases, we observe that the network produces smoothed predictions that we hypothesize are an averaged guess of the localization. We show an example in Figure 1C; while the source protein is localized to the nucleus in a punctate pattern, the target protein is predicted as a smooth distribution throughout the nucleoplasm. However, as our inpainting task is a pretext and discarded after training, we are not concerned with outputting fully realistic images.

Architecture

As the goal of our training task is to obtain a CNN that can encode single cell image patches into feature representations, we construct independent encoders for (x_s, y_s) and for x_t, which we call the "source cell encoder" and the "target marker encoder", respectively. After training with our self-supervised task, we isolate the source cell encoder, and discard all other components of our model. This architecture allows us to obtain a feature representation of any single cell image patch independently without also having to input target cell markers. To obtain single cell features, we simply input a single cell image patch, and extract the output of an intermediate convolutional layer in the source cell encoder.

We show a summary of our architecture in Figure 1C. Following other work in self-supervised learning (15,26,27), we use an AlexNet architecture for the source cell encoder, although we set all kernel sizes to 3 due to the smaller sizes of our image patches, and we add batch normalization after each convolutional layer. As we are concerned about the possibility of artifacts in the target marker channel that may hint at the localization of the target cell protein, we attempt to limit the information extracted from the target markers by using a smaller number of filters and fewer convolutional layers in the architecture of the target marker encoder; we use three convolutional layers, with 16, 32, and 32 filters, respectively. Finally, for the decoder, we reverse the AlexNet architecture.

The goal of our training is to develop the learned features of our source cell encoder, which will later be used to extract single cell feature representations. One way we could fail to achieve this outcome is if there is enough information in the target cell marker image for the network to fully predict the target protein. In this scenario, the output would not depend on any information in the source cell images, so the network would not have to learn to extract information from these images. To rule this out, we produced inpainting results from a trained model, where we paired source cells with target cells from different images, where the network has never seen the pair during training. We qualitatively confirmed that our trained networks were capable of synthesizing realistic results agreeing with the protein localization of the source cell, even when the actual protein localization of the target cell was very different (Supplementary Figure 1), suggesting that our models are not trivially overfitting to the target marker images.

Sampling Pairs

Because the training inputs to our self-supervised task consist of pairs of cells, the number of possible combinations is large, as each cell may be paired with one of many other cells. This property is analogous to data augmentation, increasing the number of unique training inputs to our network. To sample training inputs, for each epoch, we iterate through every single cell in our training dataset, set it as the source cell, and draw with uniform probability a target cell from the set of all valid possible target cells.

Our pretext task relies on the assumption that protein expression in single cells from the same image is similar. This assumption is not always true: in the datasets used in this work, some proteins exhibit significant single cell variability in their protein abundance or localization (31,32). These proteins may contribute noise because paired single cells will have (unpredictably) different protein expression patterns and the model will not learn. Although the Human Protein Atlas documents variable proteins (22), for our experiments we do not remove these and confirm that our model still learns good features in spite of this noise.

Datasets, Preprocessing, and Training

For yeast cells, we used the WT2 dataset from the CYCLoPS database (33). This collection expresses a cytosolic red fluorescent protein (RFP) in all cells, and tags proteins of interest with green fluorescent protein (GFP). We use the RFP channel as the structural marker, and the GFP channel as the protein. To extract single cell crops from the images in this dataset, we segmented our images using a mask-RCNN model (34) that was pre-trained on a dataset of diverse nuclei images available from the Kaggle Data Science Bowl 2018 competition on nuclear segmentation (35), and extract a 64x64 pixel crop around the identified cell centers; we discarded any single cells with an area smaller than 5% or greater than 95% of the image crop, as these are likely artifacts arising from under- or over-segmentation. We discard any images with fewer than 30 cells. These preprocessing operations result in a total of 1,165,713 single cell image patches grouped into 4,069 images (where each image is 4 fields of view), with a total of 4,069 of 4,138 proteins passing this filter.

We also trained a second different yeast cell model, using a NOP1pr-GFP library previously published by Weill et al. (37) This collection tags all proteins of interest with GFP at the N' terminal of proteins with a NOP1 promoter, and is also imaged in brightfield. We used the brightfield channel as a structural marker and the GFP channel as the protein. We extracted single cell crops using the same procedure for the CYCLoPS dataset, and discarded any images with fewer than 30 single cells. These preprocessing operations result in a total of 563,075 single cell image patches grouped into 3,067 images (where each image is 3 fields of view), with a total of 3,067 of 3,916 proteins passing this filter.

For human cells, we use images from version 18 of the Human Protein Atlas (22). We were able to download jpeg images for a total of 12,068 protein. Each protein may have multiple experiments, which image different cell line and antibody combinations. We consider an image to be of a protein for the same cell line and antibody combination; accordingly, we have 41,517 images (where each image is usually 2 fields of view). We downloaded 3 channels for these images. Two visualize the nuclei and microtubules, which we use as the structural marker channels. The third channel is an antibody for the protein of interest, which we use as the protein channel. To extract single cell crops from this image, we binarize the nuclear channel with an Otsu filter and find nuclei by labeling connected components as objects using the scikit-image package (36). We filter any objects with an area of less than 400 pixels, and extract a 512x512 pixel crop around the center of mass of remaining objects. To reduce training time, we rescale the size of each crop to 64x64 pixels. Finally, we remove any images with fewer than 5 cells, leaving a total of 638,640 single cell image patches grouped into 41,285 images, with a total of 11,995 of 12,068 proteins passing this filter.

For all datasets, we rescale the image intensity of each single cell image patch to be in the range [0, 1]. During training, we apply random horizontal and vertical flips to source and target cells independently as data augmentation. We trained models for 30 epochs using an Adam optimizer with an initial learning rate of 1e-4.

Comparing Pairwise Distances in Feature Spaces

To directly measure and compare how a feature set groups together cells with similar localizations in their feature spaces, measured the average pairwise distance between cells in the feature space. We preprocess single cell features by scaling to zero mean and unit variance, to control for feature-to-feature differences in scaling within feature sets. Then, to calculate the distance between two single cells c, we use the Euclidean distance between their features f: $d(c_x, c_y) = \left\| f_{c_x} - f_{c_y} \right\|_2$.

Given two images with the same localization term, we calculate the average distance of all cells in the first image paired with all cells in the second image and normalize these distances to an expectation of the average pairwise distance between images with different localization terms. A negative normalized average pairwise distance score indicates that the distances are smaller than expectation (so single cells in images with the same label are on average closer in the feature space).

For the Human Protein Atlas images, we restricted our analysis to proteins that only had a single localization term shared by at least 30 proteins, resulting in proteins with 18 distinct localization terms (as listed in Figure 2B). For each localization term, we calculated average pairwise distances for 1,000 random protein pairs with the same localization term, relative to an expectation from 1,000 random protein pairs with each of the possible other localization terms (for a total of 17,000 pairs sampled to control for class imbalance). For our experiments controlling for cell line, we also introduce the constraint that the images must be of cells of the same or different cell lines, depending on the experiment. Because some localization terms and cell line combinations are rare, we did not control for class imbalance and drew 10,000 random protein pairs with any different localization terms (not necessarily each other different term), and compared this to 10,000 random protein pairs with the same localization term. Hence, the distances in the two experiments are not directly comparable.

Single cell analysis of Multiply-Localized Proteins

For proteins localized to two compartments, we calculated a score for each cell based upon its distance to the first compartment versus its distance to the second compartment. To do so, we averaged the feature vectors for all single-cells in images annotated to localize to each compartment alone to define the average features for the two compartments. Then, for every single-cell, we calculated the distance of the single-cell's features relative to the two compartments' averages and take a log ratio of the distance to the first compartment divided by the distance to the second compartment. A negative number reflects that the single-cell is closer to the first compartment in the feature space, while a positive number reflects that the single-cell is closer to the second compartment.

<u>**Experimental Results**</u>

Paired cell inpainting features discriminate protein subcellular localization in yeast single cells

To assess the quality of feature learned through paired cell inpainting we trained a model for yeast fluorescent microscopy images using paired cell inpainting, on an unlabelled training set comprising of the entire WT2 screen in the CyCLOPS dataset, encompassing 1,165,713 single cells from 4,069 images.

Good features are sensitive to differences in biology, but robust to nuisance variation (5). As a first step to understanding if our features had these properties, we compared paired cell inpainting features with other feature sets at the task of discriminating different subcellular localization classes in yeast single cells. To do this, we made use of a test set of 30,889 single cell image patches manually assigned to 17 different protein subcellular localization classes by Chong *et al*. (37). These single cells have been curated from a different image screen than the one we used to train our model, and thus represent an independent test dataset that was never seen by the model during training.

To evaluate feature sets, we constructed a simple kNN classifier ($k = 11$; we obtained similar relative performances of the feature regardless of the k we chose) and evaluated classification performance by comparing the predicted label of each single cell based on its neighbors to its actual label. While more elaborate classifiers could be used, the kNN classifier is simple and transparent, and is frequently employed to compare feature sets for morphological profiling (38,39). Like these previous works, the goal of our experiment is to assess the relative performance of various feature sets in a controlled setting, not to present an optimal classifier.

To use the feature representation from self-supervised CNN, we must first identify which layers represent the generalizable information about protein expression patterns. Different layers in self-supervised models may have different properties: the earlier layers may only extract low-level features, but the later layers may be too specific to production of the pretext task (12). For this reason, identifying self-supervised features with a layer-by-layer evaluation of the model's properties is standard (18–20,28,29,31). Since our model has five convolutional layers, it can be interpreted as outputting five different feature sets for each input image. To determine which feature set would be best for the task of classifying yeast single cells, we constructed a classifier on our test set for the features from each layer independently, as shown in Table 1. Overall, we observe that the third (Conv3) and fourth (Conv4) convolutional layers result in the best performance.

Layer	Overall Classification Accuracy
Conv1	43.09
Conv2	70.52
Conv3	**84.30**
Conv4	**87.98**
Conv5	81.89

Table 1.   Classification accuracies using various layers in our CNN, for single yeast cell localization classes using a kNN classifier ($k = 11$) on our test set. For each layer, we take the maximum activation of each feature map. We report the overall accuracy as the balanced accuracy of all classes.

Next, we sought to compare our features from paired cell painting with other unsupervised feature sets commonly used for cellular microscopy images. First, we compared our features with feature sets designed by experts: CellProfiler features (40) that were previously extracted from segmented single cells by Chong *et al*. to train their single cell classifier (37), and with interpretable features measuring yeast protein localization calculated using yeast-specific segmentation and feature extraction software developed by Handfield *et al*. (1). Second, we compared our features with those obtained from transfer learning, i.e., repurposing features from previously-trained supervised CNNs in other domains (13,14): we used features from a VGG16 model (41), a previous supervised CNN trained on Imagenet, a large-scale classification dataset of natural images (42). Finally, we transferred features from an autoencoder (an unsupervised CNN) trained on the same dataset as our paired cell inpainting models, using our source cell encoder and decoder architecture.

Overall, the CellProfiler and VGG16 features perform at 68.15% and 69.33% accuracy respectively on our evaluation set, while the yeast-specific, interpretable features are worse at 62.04%. Autoencoder features achieve 42.50% accuracy. Our features from convolutional layer 4 (Conv4) perform better than any of the other features benchmarked by a large margin, achieving 87.98% (Figure 2A).

Figure 2. (A) Overall and class-by-class performance benchmark for yeast single cell protein localization classes using unsupervised feature sets and a kNN classifier ($k = 11$) on our test set. For all approaches extracting features from CNNs (Transfer Learning, Autoencoder, and Paired Cell Inpainting), we take the maximum activation of each feature map, and report the top-performing layer. We report the overall accuracy as the balanced accuracy of all classes. (B) The normalized pairwise distance between cells with the same localization terms according to gene ontology labels, for proteins in the Human Protein Atlas. A more negative score indicates that cells are closer in the feature set compared to a random expectation.

Finally, as an estimate of the upper bound of classification performance with our classifier, we evaluated the performance of features extracted by the layers of the state-of-the-art supervised CNN single-cell

classifier trained with most of the test set used here (6). The features from the best performing layer from this supervised model achieve 92.44% accuracy, which is comparable to the 87.98% accuracy achieved by the self-supervised paired cell inpainting features. Taken together, these results suggest that paired cell inpainting learns features comparable with those learned by supervised neural networks for discriminating protein subcellular localization in yeast single cells.

Human cells with similar proteins are closer in the paired cell inpainting feature space

To test the generalizability of the method, we trained a model for human fluorescent microscopy images with paired cell inpainting, on the entirety of the Human Protein Atlas, encompassing 638,640 single cells from 41,285 images. While the Human Protein Atlas does contain information about the general protein localization for each image, our goal is to demonstrate that our method can work on high-content human datasets without expert labels. Hence, for training our model, we do not make use of these labels in any form.

To evaluate the feature representation of single human cells, we directly analyzed the pairwise distances in the feature space. In contrast to the previous analysis (Figure 2A), we do not have a labeled single cell dataset for human cells: annotations in the Human Protein Atlas are at image-level. We therefore did not analyze classification performance. Instead, since we expect features to give similar representations to cells with similar protein localization patterns (ideally independent of cell morphologies, illumination effects, or cell lines), we compared the distance between cells with similar localization patterns in the feature space to cells with different localization patterns. We computed the normalized average distance between cells in images for proteins with the same gene ontology (GO) localization term (see Methods): a more negative score indicates that cells with the same GO term are on average closer together in the feature space (Figure 2B). We observed that features from both the Conv3 (-0.574 overall) and Conv4 (-0.349 overall) layers show smaller distances for proteins with the same GO localizations than CellProfiler features (-0.274 overall), autoencoder features (-0.281 overall), and features transferred from a pre-trained VGG16 model (-0.325 overall).

To test the robustness of the feature representation to morphological differences, we repeated the above experiment, but controlling for cell line. We reasoned that if a feature set was robust, cells with similar localization patterns would show smaller distances, even if the cells had different morphologies. We compared the normalized average pairwise distance between cells from images with the same GO localization term, when both images were constrained to be from different cell lines, compared to when both images were constrained to be from the same cell lines (Table 2). We note that we normalized the results shown in Table 2 differently from that of Figure 2B, so that the distances are not directly comparable (see Methods).

Feature Set	Normalized Average Pairwise Distance (Same Cell Lines)	Normalized Average Pairwise Distance (Different Cell Lines)	Difference
CellProfiler	-0.3027	-0.1813	0.1214
Transfer Learning	-0.2525	-0.1515	0.1010
Autoencoder	-0.2486	-0.0965	0.1521
Paired Cell Inpainting (Conv3)	**-0.4855**	**-0.3953**	**0.0902**
Paired Cell Inpainting (Conv4)	**-0.2656**	**-0.2271**	**0.0385**

Table 2. Normalized average pairwise distance scores between cells in image pairs with the same GO localization term, with the additional constraint of both images between from either the same cell line, or from different cell lines. We also report the difference between the two sets of scores; a smaller difference means that the model's performance drops less when cell lines are different.

As expected, all feature sets have higher distances in their feature spaces for cells with similar localizations, when cells come from different cell lines. However, paired cell inpainting features have the smallest drop, and still perform the best of all feature sets, even when cells come from different cell lines with different typical cell morphologies. These results indicate that our method produces single cell features that not only place similar cells closer together in the feature space, but that they are more robust to morphological variation.

Interestingly, while features from Conv4 were worse at separating different protein localizations than Conv3, its features were the most robust to cell line. Based upon this observation, we hypothesize that the earlier layers in our model may represent sensitive information directly extracted from the images, whereas later layers assemble this information into a more robust, morphology-invariant form. We also noticed that the best overall performing layer differed from our yeast model to our human model. These results suggest that the behavior of layers may differ from dataset to dataset, and a preliminary evaluation of layer-by-layer properties is important for selecting the best layer for subsequent applications of the features. However, the middle layers in our model (Conv3 and Conv4) still outperformed other unsupervised feature sets in both models, suggesting that the selection of layer to use is still robust even in the absence of this preliminary evaluation.

Proteome-wide clustering of human proteins with paired cell inpainting features discover localization classes not visible by human eye

We next sought to demonstrate the utility of the features to various applications in cell biology. First, we used the paired cell inpainting features from Conv3 of our human model in an exploratory cluster analysis of human proteins (Figure 3). Similar clustering experiments have been performed for yeast proteins, and have found clusters that not only recapitulate previously-defined subcellular localization patterns, but discover protein localization and function at a higher resolution than manual assignment (1). For this analysis, we included every protein in the Human Protein Atlas that we obtained enough single cells for (a total of 11995 of 12068 proteins.) All of these proteins are shown in Figure 3. We averaged the features of all single cells for each protein (pooling together all single cells from different cell lines and antibodies), and clustered the averaged features using hierarchical agglomerative clustering. While hierarchical clustering has previously been applied to a subset of human proteins in a single cell line to identify misannotated proteins (43), our analysis is, to our knowledge, the most comprehensive for the Human Protein Atlas.

Figure 3. Proteins in the Human Protein Atlas, ordered using maximum likelihood agglomerative hierarchical clustering. We visualize the average of paired cell inpainting features for all cells for each proteins as a heat map, where positive values are colored yellow and negative values are colored blue, with the intensity of the color corresponding to magnitude. Columns in this heat map are features, while rows are proteins. Features have been mean-centered and normalized. We manually select major clusters (grey and black bars on the right), as well as some sub-clusters within these major clusters (orange and purple bars on the right), for enrichment analysis, presented in Table 3. On the right panels (panels a-f), we show representative examples of the protein channel (green) of cells from proteins (as labeled) in the clusters indicated by arrows from the images.

Cluster	GO Annotation	Enrichment (FDR Adjusted)	Number of Proteins
A	Nucleoplasm	5.25E-139	752/1383
A1	Chromosomal Part	3.25E-12	34/114
A2	Nuclear Speck	4.37E-16	26/91
	Spliceosomal Complex	3.39E-17	21/91
A3	Nuclear Speck	8.92E-17	25/76
B	Nucleoplasm	2.63E-24	303706
	Cytosol	1.55E-19	360/706
C	Nuclear Membrane	6.32E-40	44/122
D	Nucleolus	6.48E-122	209/553
D1	Nucleolar Rim	(Manual)	14/32
D2	Preribosome	2.81E-22	58/112
E	Cytosol	2.22E-64	564/935
E1	Endoplasmic Reticulum	1.28E-8	28/117
E2	Endoplasmic Reticulum Membrane	1.72E-10	17/38
E3	Ribonucleoprotein Complex	7.01E-15	26/54
F	Plasma Membrane	7.83E-19	68/115
	Adherens Junction	3.39E-16	30/115
G	Plasma Membrane	1.09E-11	230/781
H	Microtubule Cytoskeleton	4.14E-18	24/152
I	Vesicle	4.94E-5	115/439
J	Mitochondrion	1.09E-108	230/564
J1	Mitochondrial Membrane	1.19E-30	51/88
K	Golgi Apparatus	5.03E-5	22/99
L	Membrane Part	1.75E-59	964/2170
L1	Mitochondrial Part	2.16E-14	31/82
L2	Golgi Membrane	1.12E-4	18/114
L3	Extracellular Region	1.32E-7	42/226
M	Nucleus	5.63E-43	1190/2480
M1	Nuclear Body	4.17E-8	26.97
M2	Nuclear Speck	9.86E-19	26/72

Table 3.   Gene ontology (GO) enrichments for manually identified clusters in Figure 3. For each cluster, we report selected GO annotation terms in the component ontology for *Homo sapiens*, their enrichment (adjusted with the false discovery rate), and the number of proteins with the enrichment versus the total number of proteins in the cluster. We used all human proteins in our clustering solution as the background for these enrichments. We used the GOrilla tool (44), a bioinformatics tool for identifying enriched GO terms. Full lists of the proteins in each cluster are available as part of Supplementary Data 1.

We find that proteins in the same cellular components generally cluster together (Table 3). We identified clusters enriched for about 15 of the 18 localization classes with more than 30 proteins. As these are the cellular components manually annotated by the Human Protein Atlas, these results suggest that our unbiased, unsupervised clustering of proteins broadly agrees with the protein localization classes assigned by biologists. Within large clusters of more general localizations, we also identified smaller sub-clusters of protein complexes or functional protein classes, including the spliceosomal complex (Cluster A2), the ribonucleoprotein complex (Cluster E3), and the preribosome (Cluster D2). These are cellular

components that are not typically identifiable by human eye, suggesting that our features are describing the localization of the proteins at a higher-resolution than human annotation.

To assess the ability of our clustering to find rare localization patterns, we asked if we could identify proteins localized to the nucleolar rim. The Human Protein Atlas gives only gives example of one protein, MKI67, that localizes to this pattern (22), but otherwise does not document nucleolar rim proteins systematically. We found MKI67 in Cluster D1. Of the 32 proteins closest to MKI67 in our hierarchical clustering, we identified 13 other proteins with an unambiguous nucleolar rim localization (we list these proteins in Supplementary Data 1 and provide links to their images in the Human Protein Atlas), although there may also be others too ambiguous to determine by eye. We show three of these in Figure 3, NCL (Figure 3b), EN1 (Figure 3c), and ETV4 (Figure 3d). This supports the idea that unsupervised analysis in the feature space can identify rare patterns for which training classifiers would be difficult.

We observed several clusters of nuclear speck proteins, including clusters A1, A2, and M2. We decided to evaluate images for proteins in these clusters to determine if there is any distinction in their phenotype. We observed that proteins in clusters A1 and A2 tended to localize purely to nuclear specks (Figure 3a), whereas proteins in cluster M2 tended to localize to both nuclear specks and the cytosol (Figure 3e). Consistent with this interpretation, we found a strong enrichment for the spliceosomal complex for cluster A1, but no enrichment for cluster M2. To further test the possibility that the unsupervised analysis in the feature space reveals higher resolution functional information than expert annotation, we asked if our features could be used to discover higher-resolution subclasses of proteins that are difficult for experts to annotate visually. First, previous work with vesicle-localized proteins in the Human Protein Atlas has suggested that these proteins can be distinguished into many subclasses (2,45). We clustered features for human proteins annotated to localize to the vesicle only, and found structure in the feature representation that corresponds to visually-distinct vesicle patterns (Abundantly and more evenly distributed in the cytosol, concentrated closer to the nucleus or sparse puncta, Supplementary Figure 2, Clusters A, B and C respectively). However, we were unable to associate these with any biological functions, so it is unclear if these distinctions in the patterns of vesicle distribution are functional. Next, we used features obtained from paired cell inpainting to organize proteins labelled as "punctate" in yeast dataset of images of a NOP1pr-GFP library (46) (see Methods). We find that we can distinguish Golgi, peroxisome and another cluster that contained singular or sparse foci in the cells (Supplementary Figure 3, Cluster B, C and A respectively). These analysis support the idea that unsupervised analysis of our features can reveal higher biological resolution than visual inspection of images.

Paired cell inpainting features enable quantitative analysis of multi-localizing and spatially variable proteins

Next, we asked if features from our models could be used for the analysis of single cells of multiply-localized proteins. While multiply-localized proteins are critical to study as they are often hubs for protein-protein interactions (47,48), these proteins have posed a challenge for imaging methods. Most supervised methods hold out multiply-localized proteins from their training and evaluation sets (6,9,37,49), focusing on only proteins localized to a single subcellular compartment. While generative models have been proposed for modeling these proteins (50,51), they generally rely on elaborate user-defined models of the conditional dependencies between different compartments.

We applied our features to analyze human single cells in images annotated to localize to the cytosol-and-nucleoplasm and to the nucleus-and-nucleoli by the Human Protein Atlas. Using the single-cell features from Conv3 of our human model, we measured a simple score based on distances in our feature space (see Methods). For our cytosol-and-nucleoplasm analysis, a negative score indicates that the cell is closer to the average cytosol-only cell than the average nucleoplasm-only cell in the feature space, while a

positive score indicates that the cell is closer to the average nucleoplasm-only cell than the average cytosol-only cell. For our nucleoli-and-nucleus analysis, a negative score indicates that the cell is closer to the average nucleoli cell than the average nucleus cell, while a positive score indicates that the cell is closer to the average nucleus cell than the average nucleoli cell. We calculated this score for every single-cell localized to both compartments, or to either compartment alone (Figure 4).

Figure 4. Single-cell scores (as explained in the text) for cytosolic-and-nucleoplasm cells (A), and nucleoli-and-nucleus cells (B). We visualize single cells as violin plots. The black boxes inside the violin plots show the interquartile ranges and the white dots show the medians. To the right of the violin plots, we show all of the single-cells for four different images of proteins annotated to be multi-localizing to either the cytosol-or-nucleoplasm or the nucleolus-and-nucleus as black dots, as labeled in the x-axis. For each image, we show either a representative crop of the image, or multiple single cell crops; in both cases, the protein is shown in green, while the microtubule is shown as red. Note that while the violin plots include all cell-lines, we show four examples from the same cell-line for each plot, to demonstrate that images from the same cell-line can have different scores depending on their phenotype.

We observe that single-cells with a cytosol-only annotation have a more positive score, while single-cells with a nucleus-only annotation have a more negative score (Figure 4A). In contrast, single-cells annotated to localize to both compartments have a score closer to 0. We observed that the skew of multiply-localized single-cells towards a positive or negative score reflects the proportion of protein localized to the two compartments: for example, for single cells stained for the spatially-variable protein LYPD5 in the U-251 MG cell line, we observed that positive scores corresponded to a more dominant nuclear localization, negative scores corresponded to a more dominant cytosol localization, and scores closer to 0 corresponded to a more even mix of both localizations (Figure 4A). We made similar observations for nucleoli-and-nucleus single-cells (Figure 4B). However, we also noticed that while most of the single-cells with a nucleoli-only annotation had negative scores, some had more positive scores, suggesting that the nucleoli-and-nucleus images are often annotated as nucleoli-only. These results suggest that simple distances in our feature space could be used to not only identify multiply-localized proteins, but also quantitate the relative distribution of protein between its compartments. We have included the mean scores for every cytosol-and-nucleoplasm and nucleoli-and-nucleus protein by cell line as Supplementary Data 2.

We observed that proteins with spatial-variability sometimes had different distributions over our scores compared to more homogeneously-localized proteins (Figure 4). This observation suggested that the standard deviation could be useful in discovering proteins with single-cell variability. We looked at the 10 images with the highest standard deviations for cytosol-and-nucleoplasm single-cells, and for nucleoli-and-nucleus single-cells. For cytosol-and-nucleoplasm single-cells, 6/10 are previously annotated by the Human Protein Atlas to have single-cell variability, and we observed unambiguous, but previously unannotated, single-cell variability in the images for the remaining 4. For nucleus-and-nucleoli single-cells, 5/10 are previously annotated, and we observed unambiguous and previously unannotated single-cell variability for the remaining 5 (we show one example of a previously unannotated image in Figure 4B, for MYL5 in the A-431 cell line). While, this simple metric would be less sensitive to variable proteins where the single-cells are imbalanced in their distribution of the different phenotypes, these results suggest that simple statistics in our feature space can identify at least some kinds of single-cell variability. We include the standard deviation of scores for every cytosol-and-nucleoplasm and nucleoli-and-nucleus protein by cell line in Supplementary Data 2.

Clustering of single cells organizes spatial variability in proteins

To organize single-cell variability, without prior knowledge of the specific compartments the protein is localized to, we decided to analyze single-cells using clustering in the feature space. We selected three proteins with spatial variability at the single-cell level: SMPDL3A, which localizes to the nucleoli and mitochondria (Figure 5A); DECR1, which localizes to the cytosol and mitochondria (Figure 5B); and NEK1, which localizes to the nucleoli and nuclear membrane (Figure 5C). We clustered the single cells of each protein using hierarchical agglomerative clustering. Figure 5 shows the dendograms of the clustering solution for each protein, as well as the single-cell image crops associated with representative branches of the dendogram.

Figure 5.   Dendograms from clustering the single-cell paired cell inpainting features of three spatially variable proteins: (A) SMPDL3A, (B) DECR1, (C) NEK1. For each dendogram, we show single-cell image crops associated with representative branches of the dendogram. For (A) SMPDL3A,

we also show a field of view of the image, and where various single-cell crops originate from in the full image (yellow boxes). We label clades in the dendogram (grey boxes) with the apparent localization of the single cells.

In general, we observe distinct clusters of single cells for spatially variable proteins, visible as distinct clades in the dendograms (Figure 5.) For SMPDL3A, we observe clusters of mitochondria-localized and of nucleoli-localized single cells, and for DECR1, we observe clusters of mitochondria-localized and cytosol-and-mitochondria-localized single cells, consistent with their labels in the Human Protein Atlas. For NEK1, we observed distinct clusters for the nuclear membrane and nucleoli, consistent with its label, but also for single-cells of a third phenotype, which appeared to localize as nuclear speckles, which is not recorded in the Human Protein Atlas (22). We hypothesize this may be due to the challenges in manually annotating a visually complex image with a heterogenous mixture of cells. These results suggest that single-cell clustering in the feature space can organize the phenotypes in a heterogeneous image, and quantify the relative proportion of each phenotype.

Discussion

We present a simple, but effective self-supervised learning task for learning feature representations of single cells in fluorescent microscopy images. Features learned through paired cell inpainting easily achieve state-of-the-art performance in unsupervised benchmarks for both yeast and human cells. We believe that the effectiveness can be attributed to several factors.

First, our pretext training task controls for nuisance variation. Because our task requires the network to predict the phenotype in a different cell, the network must ignore cell-specific variation to learn more general features about the phenotype. As we show the network the target cell structural markers during training, the network is directly given experimental effects like local illumination, meaning that it does not have to learn features for these in the source cell encoder.

Second, self-supervised methods learn features directly from data. Here, our method learns a set of features for reconstructing visual patterns in microscopy image datasets. Our training inputs follow the natural structure of and can be extracted from many imaging experiments without manual labeling. Caicedo *et al*. (17) also propose training a CNN to classify cells by their experimental treatment. Compared to their method, ours has technical advantages. First, classifying experimental treatments may not scale as the number of experiments grows: their study uses datasets that comprise of at most, a few hundred experimental labels, but the classification problem becomes more difficult as the number of experiments grows. In our experiments, we trained cells belonging to 41,285 experiments with no complications. Second, our method does not force the CNN to discriminate between experiments that yield identical phenotypes. For example, protein complexes localize identically, so to perform well on discriminating these labels, a CNN would have to overfit to experimental variation. Our task is predictive, rather discriminative, controlling for this issue.

We performed, to our knowledge, the first global analysis of protein localization spanning the entire Human Protein Atlas. Despite pooling all cell lines and antibodies together for proteins, we capture enrichments for high-resolution cellular components in our cluster analysis. Moreover, we showed that we could identify rare phenotypes, and use our features to discover distinct subclasses of proteins unsupervised. These results emphasize the importance of unbiased analysis, in contrast to supervised approaches. Rare phenotypes may be excluded from classifiers due to lack of training data, or lack of knowledge of which images to mine training data from. We discovered several proteins with a nucleolar rim localization, based upon the one example given by the Human Protein Atlas. Similarly, pre-defined classes may hide functionally-important variability within classes, and may be biased by human pre-conceptions of the data. We showed that coarse human-annotated classes can be clustered into distinct

subclasses, and that functional protein classes such as the preribosome or splicesomal complex are clustered in protein localization data. Overall, these results demonstrate the power of unsupervised analysis in discovering new and unexpected biology, a task that supervised methods are fundamentally unable to perform, no matter how accurate they are at annotating pre-defined human knowledge.

While the quality of the features we learned were generally robust to different parameters and preprocessing operations on the dataset, outperforming other unsupervised methods regardless of settings, we found several factors that we believe could improve the features. First, filtering proteins that have single-cell variability in their protein expression, for example, by using labels in the Human Protein Atlas (22). Likely, this would reduce amount of noise caused by pairing single cells with different protein expression during training. Second, while our method does not rely on accurate single-cell segmentations (1,40), it uses a crop centered around single cells in the image. We found that the method we used to detect cell centers for cropping was important, with classic segmentation techniques based on watershedding (1) resulting in poorer features the methods used here (see Methods). We hypothesize that this is because artifacts included as cells increase noise during training when a cell gets paired with an artifact.

Future work in improving some of the technical limitations of our work may further improve the quality of the learned features. First, we use an older AlexNet architecture, as we focused on the learning task; as our datasets are large, we wanted to use a simple architecture with fewer parameters to reduce training time. Future work in optimizing the architecture will likely improve the results. Second, as discussed, some proteins localize in a pattern that cannot be predicted deterministically from the structural markers of the cell alone. The inability of the network to accurately reconstruct these proteins may limit its feature learning; strategies like incorporating an adversarial loss may improve this. Third, for our experiments, we iterated over all cells in our training dataset and sampled pairs randomly. A more sophisticated pair sampling scheme may improve the quality of the features: for example, focusing on harder pairs where the morphology of the cells differs more drastically. Finally, there are some protein localization patterns correlated with the cell cycle, such as the mitotic spindle. Due to their low penetrance in an image (for example, only a fraction of the cells will be undergoing mitosis), we do not expect our model to learn these patterns very well. Even if these cells are paired correctly, there may only be one or two cells with the specific cell cycle stage required to exhibit the pattern in the entire image. Better datasets with more fields of view, or work in finding an unsupervised method for balancing the patterns in the data, may improve this issue.

Code Availability

Code and pre-trained weights for the models used in this work will be made available at https://github.com/alexxijielu/paired_cell_inpainting.

Acknowledgements

We thank Shadi Zabad, Taraneh Zarin, Nirvana Nursimulu, and Purnima Kompella for valuable comments on the manuscript. We thank Maya Schuldiner, Uri Weill, and Amir Fadel for help in accessing the NOP1pr-ORF yeast collection. This work was funded by the National Science and Engineering Research Council (Pre-Doctoral Award), Canada Research Chairs (Tier II Chair), and the Canadian Foundation for Innovation.

Contributions

A.X.L and A.M.M conceptualized the idea and designed the experiments. A.X.L collected the data, implemented the software, and conducted the experiments and analyses. A.X.L wrote the manuscript with

suggestions and edits from the other authors. O.Z.K and S.M. provided training and supervision in implementing the computational methods. A.M.M supervised the project.

References

1. Handfield L-F, Chong YT, Simmons J, Andrews BJ, Moses AM. Unsupervised clustering of subcellular protein expression patterns in high-throughput microscopy images reveals protein complexes and functional relationships between proteins. PLoS Comput Biol. 2013 Jan;9(6):e1003085.
2. Johnson GR, Li J, Shariff A, Rohde GK, Murphy RF. Automated Learning of Subcellular Variation among Punctate Protein Patterns and a Generative Model of Their Relation to Microtubules. Tresch A, editor. PLOS Comput Biol. Public Library of Science; 2015 Dec 1;11(12):e1004614.
3. Caicedo JC, Cooper S, Heigwer F, Warchal S, Qiu P, Molnar C, et al. Data-analysis strategies for image-based cell profiling. Nat Methods. Nature Publishing Group; 2017 Aug 31;14(9):849–63.
4. Lu AX, Chong YT, Hsu IS, Strome B, Handfield L-F, Kraus O, et al. Integrating images from multiple microscopy screens reveals diverse patterns of change in the subcellular localization of proteins. Elife. eLife Sciences Publications Limited; 2018 Apr 5;7:e31872.
5. Uchida S. Image processing and recognition for biological images. Dev Growth Differ. Wiley-Blackwell; 2013;55(4):523.
6. Kraus OZ, Grys BT, Ba J, Chong Y, Frey BJ, Boone C, et al. Automated analysis of high-content microscopy data with deep learning. Mol Syst Biol. 2017;13(4):924.
7. Eulenberg P, Köhler N, Blasi T, Filby A, Carpenter AE, Rees P, et al. Reconstructing cell cycle and disease progression using deep learning. Nat Commun. Nature Publishing Group; 2017 Dec 6;8(1):463.
8. Dürr O, Sick B. Single-Cell Phenotype Classification Using Deep Convolutional Neural Networks. J Biomol Screen. 2016 Oct;21(9):998–1003.
9. Godinez WJ, Hossain I, Lazic SE, Davies JW, Zhang X. A multi-scale convolutional neural network for phenotyping high-content cellular images. Bioinformatics. 2017 Jul 1;33(13):2010–9.
10. Ronneberger O, Fischer P, Brox T. U-Net: Convolutional Networks for Biomedical Image Segmentation. In: Medical Image Computing and Computer-Assisted Intervention (MICCAI). Springer; 2015. p. 234–41.
11. Kraus OZ, Ba JL, Frey BJ. Classifying and segmenting microscopy images with deep multiple instance learning. Bioinformatics. 2016 Jun 15;32(12):i52–9.
12. LeCun Y, Bengio Y, Hinton G. Deep learning. Nature. Nature Publishing Group; 2015 May 28;521(7553):436–44.
13. Donahue J, Jia Y, Vinyals O, Hoffman J, Zhang N, Tzeng E, et al. DeCAF: A Deep Convolutional Activation Feature for Generic Visual Recognition. In: Proceedings of the 31st International Conference on Machine Learning. 2014. p. 647–55.
14. Razavian AS, Azizpour H, Sullivan J, Carlsson S. CNN Features off-the-shelf: an Astounding Baseline for Recognition. In: CVPRW '14 Proceedings of the 2014 IEEE Conference on Computer Vision and Pattern Recognition Workshops. 2014. p. 512–9.
15. Zhang R, Isola P, Efros AA. Split-Brain Autoencoders: Unsupervised Learning by Cross-Channel Prediction. In: 2017 IEEE Conference on Computer Vision and Pattern Recognition. 2017.
16. Pathak D, Krahenbuhl P, Donahue J, Darrell T, Efros AA. Context Encoders: Feature Learning by Inpainting. 2016 Apr 25;
17. Caicedo JC, McQuin C, Goodman A, Singh S, Carpenter AE. Weakly supervised learning of single-cell feature embeddings. bioRxiv. Cold Spring Harbor Laboratory; 2018 Apr 2;293431.
18. Sullivan DP, Winsnes CF, Åkesson L, Hjelmare M, Wiking M, Schutten R, et al. Deep learning is combined with massive-scale citizen science to improve large-scale image classification. Nat Biotechnol. Nature Publishing Group; 2018 Aug 20;36(9):820–8.

19.   Mattiazzi Usaj M, Styles EB, Verster AJ, Friesen H, Boone C, Andrews BJ. High-Content Screening for Quantitative Cell Biology. Trends Cell Biol. 2016;26(8):598–611.

20.   Pelkmans L. Using Cell-to-Cell Variability--A New Era in Molecular Biology. Science (80-). 2012 Apr 27;336(6080):425–6.

21.   Snijder B, Pelkmans L. Origins of regulated cell-to-cell variability. Nat Rev Mol Cell Biol. Nature Publishing Group; 2011 Feb 12;12(2):119–25.

22.   Thul PJ, Åkesson L, Wiking M, Mahdessian D, Geladaki A, Ait Blal H, et al. A subcellular map of the human proteome. Science (80-). 2017 May 26;356(6340):eaal3321.

23.   Dalal CK, Cai L, Lin Y, Rahbar K, Elowitz MB. Pulsatile dynamics in the yeast proteome. Curr Biol. NIH Public Access; 2014 Sep 22;24(18):2189–94.

24.   Karanam K, Loewer A, Lahav G. Dynamics of the DNA damage response: insights from live-cell imaging. Brief Funct Genomics. Oxford University Press; 2013 Mar;12(2):109–17.

25.   Jenni S, Favaro P. Self-Supervised Feature Learning by Learning to Spot Artifacts. In: CVPR 2018. 2018.

26.   Pathak D, Krahenbuhl P, Donahue J, Darrell T, Efros AA. Context Encoders: Feature Learning by Inpainting. In: CVPR 2016. 2016.

27.   Gidaris S, Singh P, Komodakis N. Unsupervised Representation Learning by Predicting Image Rotations. In: ICLR 2018. 2018.

28.   Kim KAIST D, Cho D, Yoo KAIST D. Learning Image Representations by Completing Damaged Jigsaw Puzzles. In: WACV 2018. 2018.

29.   Mundhenk TN, Ho D, Chen BY. Improvements to context based self-supervised learning. In: CVPR 2018. 2018.

30.   Waters JC. Accuracy and precision in quantitative fluorescence microscopy. J Cell Biol. 2009 Jun 29;185(7):1135–48.

31.   Smith S, Grima R. Single-cell variability in multicellular organisms. Nat Commun. Nature Publishing Group; 2018 Dec 24;9(1):345.

32.   Handfield L-F, Strome B, Chong YT, Moses AM. Local statistics allow quantification of cell-to-cell variability from high-throughput microscope images. Bioinformatics. Oxford University Press; 2015 Mar 15;31(6):940–7.

33.   Koh JLY, Chong YT, Friesen H, Moses A, Boone C, Andrews BJ, et al. CYCLoPs: A Comprehensive Database Constructed from Automated Analysis of Protein Abundance and Subcellular Localization Patterns in Saccharomyces cerevisiae. G3 (Bethesda). 2015 Jun;5(6):1223–32.

34.   He K, Gkioxari G, Dollár P, Girshick R. Mask R-CNN. In: 2017 IEEE International Conference on Computer Vision (ICCV). 2017.

35.   Caicedo J, Roth J, Goodman A, Becker T, Karhohs KW, McQuin C, et al. Evaluation of Deep Learning Strategies for Nucleus Segmentation in Fluorescence Images. bioRxiv. Cold Spring Harbor Laboratory; 2018 May 31;335216.

36.   van der Walt S, Schönberger JL, Nunez-Iglesias J, Boulogne F, Warner JD, Yager N, et al. scikit-image: image processing in Python. PeerJ. PeerJ, Inc; 2014;2:e453.

37.   Chong YT, Koh JLY, Friesen H, Kaluarachchi Duffy S, Cox MJ, Moses A, et al. Yeast Proteome Dynamics from Single Cell Imaging and Automated Analysis. Cell. 2015 Jun;161(6):1413–24.

38.   Ljosa V, Caie PD, Ter Horst R, Sokolnicki KL, Jenkins EL, Daya S, et al. Comparison of methods for image-based profiling of cellular morphological responses to small-molecule treatment. J Biomol Screen. 2013 Dec;18(10):1321–9.

39.   Singh S, Bray M-A, Jones TR, Carpenter AE. Pipeline for illumination correction of images for high-throughput microscopy. J Microsc. Wiley-Blackwell; 2014 Dec;256(3):231–6.

40.   Carpenter AE, Jones TR, Lamprecht MR, Clarke C, Kang IH, Friman O, et al. CellProfiler: image analysis software for identifying and quantifying cell phenotypes. Genome Biol. 2006 Jan;7(10):R100.

41.   Simonyan K, Zisserman A. Very Deep Convolutional Networks for Large-Scale Image

Recognition. In: ILSVRC-2014. 2014.

42. Deng J, Dong W, Socher R, Li L-J, Kai Li, Li Fei-Fei. ImageNet: A large-scale hierarchical image database. In: 2009 IEEE Conference on Computer Vision and Pattern Recognition. IEEE; 2009. p. 248–55.

43. Li J, Newberg JY, Uhlén M, Lundberg E, Murphy RF. Automated Analysis and Reannotation of Subcellular Locations in Confocal Images from the Human Protein Atlas. Ranganathan S, editor. PLoS One. Public Library of Science; 2012 Nov 30;7(11):e50514.

44. Eden E, Navon R, Steinfeld I, Lipson D, Yakhini Z. GOrilla: a tool for discovery and visualization of enriched GO terms in ranked gene lists. BMC Bioinformatics. BioMed Central; 2009 Feb 3;10(1):48.

45. Li Y, Majarian TD, Naik AW, Johnson GR, Murphy RF. Point process models for localization and interdependence of punctate cellular structures. Cytom Part A. Wiley-Blackwell; 2016 Jul 1;89(7):633–43.

46. Weill U, Yofe I, Sass E, Stynen B, Davidi D, Natarajan J, et al. Genome-wide SWAp-Tag yeast libraries for proteome exploration. Nat Methods. Nature Publishing Group; 2018 Aug 9;15(8):617–22.

47. Ota M, Gonja H, Koike R, Fukuchi S. Multiple-Localization and Hub Proteins. PLoS One. Public Library of Science; 2016;11(6):e0156455.

48. Zhang S, Xia X, Shen J, Zhou Y, Sun Z. DBMLoc: a Database of proteins with multiple subcellular localizations. BMC Bioinformatics. BioMed Central; 2008 Feb 28;9:127.

49. Pärnamaa T, Parts L. Accurate Classification of Protein Subcellular Localization from High-Throughput Microscopy Images Using Deep Learning. G3 (Bethesda). Genetics Society of America; 2017;7(5):1385–92.

50. Murphy RF. Building cell models and simulations from microscope images. Methods. 2016 Mar 1;96:33–9.

51. Johnson GR, Donovan-Maiye RM, Maleckar MM. Generative Modeling with Conditional Autoencoders: Building an Integrated Cell. 2017 Apr 28;

Supplementary Figure 1. Paired cell inpainting results where the source and target cells have different localizations. Here, we take four source human cells with different localizations (a), belonging in the nucleoli, nuclear membrane, nucleoplasm, and cytosol, respectively. For each of our source cells, we run our human cell model end-to-end with the same target cell marker (b) as input, generating four

separate predictions (c). Finally, we merge these into a composite image showing all four predicted localizations simultaneously, in additional to the original target antibody (d). For real data, we color the nuclear channels blue, the microtubule channels red, and the protein channels green. For predicted proteins, we color nucleoli cyan, nuclear membrane white, nucleoplasm purple, and cytosol green. Channels in composite image have been rescaled and thresholded for visualization purposes.

Supplementary Figure 2.   Averaged paired cell inpainting features for vesicle-only proteins in the Human Protein Atlas, using features from Conv3 of our human model trained on the Human Protein Atlas dataset, ordered using maximum likelihood agglomerative hierarchical clustering. We visualize features as a heat map, where positive values are colored yellow and negative values are colored blue, with the intensity of the color corresponding to magnitude. Columns in this heat map are features, while rows are proteins. Features have been mean-centered and normalized using all proteins in the dataset. We show three clusters (black and grey bars on the right), and crops of three representative images of the proteins within each of the clusters. For image crops, we show the protein channel in green, and the nucleus channel in blue.

Supplementary Figure 3. Averaged paired cell inpainting features from Conv4 of our yeast model trained on the NOP1pr-GFP dataset, for proteins labeled as punctuate in the NOP1pr-GFP library images, ordered using maximum likelihood agglomerative hierarchical clustering. We visualize features as a heat map, where positive values are colored yellow and negative values are colored blue, with the intensity of the color corresponding to magnitude. Columns in this heat map are features, while rows are proteins. Features have been mean-centered and normalized using all proteins in the dataset. We show three clusters (black and grey bars on the right), and crops of three representative images of the proteins within each of the clusters. For image crops, we show the protein channel only in green. For clusters B and C, we show the GO enrichment of the clusters relative to all punctate proteins; we list the q-value (the FDR-corrected p-value) and the number of proteins in the cluster with that annotation relative to the full size of the cluster.