Interpretable multimodal deep learning for real-time pan-tissue pan-disease pathology search on social media

Andrew J. Schaumberg[1,2,3,a,*] Wendy Juarez[3,4,❷], Sarah J. Choudhury[3,4,❷], Laura G. Pastrián MD[5,β], Bobbi S. Pritt MD DTM&H[6,β], Mario Prieto Pozuelo MD PhD[7,β], Ricardo Sotillo Sánchez MD[8,β], Khanh Ho MD[9,β], Nusrat Zahra MD[10,β], Betul Duygu Sener MD[11,β], Stephen Yip MD PhD[12,β], Bin Xu MD PhD[13,β], Srinivas Rao Annavarapu MD[14,β], Aurélien Morini MD[15,β], Karra A. Jones MD PhD[16,β], Kathia Rosado-Orozco MD[17,β], Sanjay Mukhopadhyay MD[18,β], Carlos Miguel MD[19,β], Hongyu Yang MD PhD[20,β], Yale Rosen MD[21,β], Rola H. Ali MD[22,β], Olaleke O. Folaranmi MD[23,β], Jerad M. Gardner MD[24,β], Corina Rusu MD[25,β], Celina Stayerman MD[26,β], John Gross MD[27,β], Dauda E. Suleiman MD[28,β], S. Joseph Sirintrapun MD[29], Mariam Aly PhD[30,31,b,δ,*], Thomas J. Fuchs Dr.Sc.[2,29,c,δ,*]

1 Memorial Sloan Kettering Cancer Center and the Tri-Institutional Training Program in Computational Biology and Medicine, NY, USA
2 Weill Cornell Graduate School of Medical Sciences, NY, USA
3 Weill Cornell High School Science Immersion Program
4 Manhattan/Hunter Science High School, NY, USA
5 Hospital Universitario La Paz, Madrid, Spain
6 Mayo Clinic, Department of Laboratory Medicine and Pathology, MN, USA
7 Hospital Universitario HM Sanchinarro, Laboratorio de Dianas Terapéuticas, Madrid, Spain
8 Virgen de Altagracia Hospital, Departamento de Patología, Spain
9 Centre Hospitalier de Mouscron, Département de Pathologie. Belgium
10 Allama Iqbal Medical College, Department of Pathology, Lahore, Pakistan
11 Konya Training and Research Hospital, Department of Pathology, Konya, Turkey
12 BC Cancer, Department of Pathology, British Columbia, Canada
13 Sunnybrook Health Sciences Centre, Department of Pathology, Toronto, Ontario, Canada
14 Royal Victoria Infirmary, Department of Cellular Pathology, England, UK
15 Université Paris Est Créteil, Faculté de médecine de Créteil, France
16 University of Iowa, Department of Pathology, IA, USA
17 HRP Labs, San Juan, Puerto Rico, USA
18 Cleveland Clinic, Department of Pathology, Cleveland, OH, USA
19 Centro Médico de Asturias, Department of Pathology, Oviedo, Spain
20 St Vincent Evansville Hospital, Department of Pathology, Evansville, IN, USA
21 SUNY Downstate Medical Center, Department of Pathology, NY, USA
22 Kuwait University, Department of Pathology, Faculty of Medicine, Kuwait
23 University of Ilorin Teaching Hospital, Department of Pathology, Nigeria
24 University of Arkansas for Medical Sciences, Department of Pathology, Little Rock, AK, USA
25 Augusta Hospital, Department of Pathology, Bochum, Germany
26 Laboratorio TechniPath, San Pedro Sula, Honduras
27 Mayo Clinic, Bone and Soft Tissue and Surgical Pathology, Rochester, MN, USA
28 Abubakar Tafawa Balewa University Teaching Hospital, Department of Histopathology, Bauchi, Nigeria
29 Memorial Sloan Kettering Cancer Center, Department of Pathology, NY, USA
30 Columbia University, Department of Psychology, NY, USA
31 Affiliate Member of the Zuckerman Mind Brain Behavior Institute, Columbia University

❷These authors contributed equally to this work.
β These pathologist authors generously donated cases.
δ These authors are Principal Investigators of this work.
* Correspondence may be addressed to authors:
a ajs625@cornell.edu (Twitter @schaumberg_a),
b ma3631@columbia.edu (Twitter @mariam_s_aly), and
c fuchst@mskcc.org (Twitter @ThomasFuchsAI).

Abstract

Background

Pathologists are responsible for rapidly providing a diagnosis on critical health issues, from infection to malignancy. Challenging cases benefit from additional opinions of pathologist colleagues. In addition to on-site colleagues, there is an active worldwide community of pathologists on social media for complementary opinions. Such access to pathologists worldwide has the capacity to (i) improve diagnostic accuracy and (ii) generate broader consensus on next steps in patient care.

Methods and findings

From Twitter we curate 13,626 images from 6,351 tweets from 25 pathologists from 13 countries. We supplement the Twitter data with 113,161 images from 1,074,484 PubMed articles. We develop machine learning and deep learning models to (i) accurately identify histopathology stains, (ii) discriminate between tissues, and (iii) differentiate disease states. For deep learning, we derive novel regularization and activation functions for set representations related to set cardinality and the Heaviside step function. Area Under Receiver Operating Characteristic is 0.805-0.996 for these tasks. We repurpose the disease classifier to search for similar disease states given an image and clinical covariates. We report precision@k=1 = 0.701±0.003 (chance 0.397±0.004, mean±stdev). The classifiers find texture and tissue are important clinico-visual features of disease. For search, deep features and cell nuclei features are less important.

We implement a social media bot (@pathobot on Twitter) to use the trained classifiers to aid pathologists in obtaining real-time feedback on challenging cases. The bot activates when mentioned in a social media post containing pathology text and images. The bot generates quantitative predictions of disease state (normal/artifact/ infection/injury/nontumor, pre-neoplastic/benign/low-grade-malignant-potential, or malignant) and provides a ranked list of similar cases across social media and PubMed.

Conclusions

Our project has become a globally distributed expert system that facilitates pathological diagnosis and brings expertise to underserved regions or hospitals with less expertise in a particular disease. This is the first pan-tissue pan-disease (i.e. from infections to malignancy) method for prediction and search on social media, and the first pathology study prospectively tested in public on social media. We expect our project to cultivate a more connected world of physicians and improve patient care worldwide.

Author summary

Why was this study done?

- No publicly available pan-tissue pan-disease dataset exists for computational pathology. This limits the general application of machine learning in histopathology.

- Pathologists use social media to obtain both (i) opinions for challenging patient cases and (ii) continuing education. Connecting pathologists and linking to similar cases leads to more informative exchanges than computational predictions – e.g. to diagnose best, pathologists may discuss patient history and next tests to order. Additionally, pathologists seek the most interesting rare cases and new articles.

What did the researchers do and find?

- We generated a pan-tissue, pan-disease dataset comprising 10,000+ images from social media and 100,000+ images from PubMed. Classifiers applied to social media data suggest texture and tissue are important clinico-visual features of disease. Learning from both clinical covariates (e.g. tissue type or marker mentions) and visual features (e.g. local binary patterns or deep learning image features), these classifiers are multimodal.

- These data and classifiers power the first social media bot for pathology. It responds to pathologists in real time, searches for similar cases, and encourages collaboration.

What do these findings mean?

- This diverse dataset will be a critical test for machine learning in computational pathology, e.g. search for cures of rare diseases.

- Interpretable real-time classifiers can be successfully applied to images on social media and PubMed to find similar diseases and generate disease predictions. Going forward, similar methods may elucidate important clinico-visual features of specific diseases.

Introduction

The United Nations' Sustainable Development Goal 3: Good Health and Well-Being suggests that "ensuring healthy lives and promoting the well-being at all ages is essential", and "increased access to physicians" should be a focus. We therefore take connecting pathologists worldwide to be important. Indeed, Nix *et al.* [1] find pathologists in developing countries (e.g. India, Brazil, and Pakistan) frequently use social media, and 220/1014 (22%) of the posts they analyzed involved "asking for opinions on diagnosis". The use of social media by pathologists occurs worldwide for both challenging cases and education [2–4]. This suggests social media can facilitate global collaborations among pathologists for novel discoveries [5]. We expand on these approaches by combining (i) real-time machine learning with (ii) expert pathologist opinions via social media to facilitate (i) search for similar cases and (ii) pathological diagnosis by sharing expertise on a particular disease, often with underserved hospitals.

For machine learning to work in general practice, it must be trained on data (i) of sufficient diversity to represent the true variability of what is observed (ii) in a sufficiently realistic setting that may differ from tightly controlled experimental conditions [6]. We therefore (i) collaborate with pathologists worldwide where we (ii) use for training the images that these pathologists share to obtain opinions, which are often histopathology microscopy pictures from a smartphone. We did not observe many images from whole slide scanners, which at a global scale have been adopted slowly, due in part to cost and complexities of digital pathology workflows [7,8].

For machine learning to work accurately, it must be trained on a sufficiently large dataset. Our first aim is therefore to curate a large dataset of pathology images for training a machine learning classifier. This is important because in other machine learning domains, e.g. natural vision tasks, datasets of millions of images are often used to train and benchmark, e.g. ImageNet [9] or CIFAR-10 [10]. Transfer learning allows limited repurposing of these classifiers for other domains, e.g. pathology [11–14]. Indeed, we [15] are among many who start in computational pathology [16] with deep-neural networks pre-trained on ImageNet [17–19], and we do so here.

Fig 1. Graphical summary. Pathologists are recruited worldwide (**A**). If a pathologist consents to having their images used (**B**), we download those images (**C**) and manually annotate them (**D**). Next, we train a Random Forest classifier to predict image characteristics, e.g. disease state (**E**). This classifier is used to predict disease and search. If a pathologist posts a case to social media and mentions @pathobot (**F**), our bot will use the post's text and images to find similar cases on social media and PubMed (**G**). The bot then posts summaries and notifies pathologists with similar cases (**H**). Pathologists discuss the results (**I**), and some also decide to share their cases with us, initiating the cycle again (**A**). *Procedure overview* in the supplement explains further.

However, computational pathology datasets annotated for supervised learning are often much smaller than millions of images. For example, there are only 32 cases in the training data for a Medical Image Computing and Computer Assisted Intervention challenge (available at `http://miccai.cloudapp.net/competitions/82`) for distinguishing brain cancer subtypes, and this includes both pathology and radiology images. Other studies are larger, such as the TUmor Proliferation Assessment Challenge (TUPAC16) dataset of 821 cases [20] – all 821 cases being whole slide images from The Cancer Genome Atlas (TCGA) (`http://cancergenome.nih.gov/`). TCGA has tens of thousands of whole slide images available in total, but these images are only hematoxylin and eosin (H&E) stained slides, and do not represent non-neoplastic lesions such as infections, which are clinically important to correctly diagnose [21]. The main limitation is that obtaining annotations from a pathologist is difficult due to outstanding clinical service obligations, which prevented our earlier efforts from scaling up [22]. We overcome this limitation by curating a large and diverse dataset of 13,626 images from Twitter and 113,161 images from PubMed, where text annotations came from social media post text, hashtags, article titles, abstracts, and/or figure captions.

Equipped with our large dataset, we then address our second main aim, which is to utilize machine learning trained on this dataset to facilitate prospective disease state predictions and search from pathologists in real-time on social media. To that end, we capitalize on a common and systematic approach to diagnosis in which a disease is in one of three classes [21]. Specifically, we use machine learning on pathology images from social media and PubMed to classify images into one of three disease states: *nontumor* (e.g. normal, artifact (Fig S1), injury, infection, or nontumor), *low grade* (e.g. pre-neoplastic, benign, or low grade malignant potential), and *malignant*.

We then implement a social media bot that in real time applies our machine learning

classifiers in response to pathologists on social media to (i) search for similar cases, (ii) provide quantitative predictions of disease states, and (iii) encourage discussion (Fig 1). When this bot links to a similar case, the pathologist who shared that case is notified. The ensuing discussions among pathologists are more informative and context-specific than a computational prediction. For instance, to make a diagnosis of Kaposi's sarcoma, first-world countries have access to an HHV8 histopathology stain, but a pathologist in a developing country may instead be advised to check patient history of HIV because the HHV8 stain is prohibitively expensive. Obviously, a computational prediction of cancer/non-cancer is far less helpful than what humans do: discuss.

In order for machine learning approaches to be useful in a clinical setting, it is critical that these approaches be interpretable and undergo rigorous prospective testing [23]. Furthermore, these approaches need to be accompanied by quantified measures of prediction uncertainty [24]. It may be argued whenever human life is at risk, interpretability, and uncertainty quantification, and prospective testing are essential, whether the context is medicine or self-driving cars [25, 26]. Our social media bot and methods are the first in computational pathology to meet all of these criteria in that (i) we provide multiple levels of interpretability (i.e. Random Forest feature importance, deep learning activation heatmaps), (ii) we quantify prediction uncertainty using ensemble methods, and (iii) we prospectively test in full public view on social media.

Materials and methods

Social media data

From Twitter we curate 13,626 images from 6,351 tweets from 25 pathologists from 13 countries. We chose Twitter primarily for its brevity, i.e. one Tweet is at most 280 characters, so we did not expect to need complicated text processing logic to parse tissues or diagnoses. Written permission to download and use the data was obtained from each collaborating pathologist. One pathologist publicly declared their data free to use, so we use these data with acknowledgement. One pathologist donated his glass slide library to another pathologist, and the receiving pathologist shared some received cases on social media, which we treat as belonging to the receiving pathologist. Images are annotated with their tweet text and replies. We use these data for supervised learning.

PubMed data

To represent PubMed data, we download the PubMed Central "Open Access Subset" of 1,074,484 articles. We first trained a classifier to distinguish H&E images from all others on social media (Figs 2, S4, S5), then used the classifier to identify PubMed articles that have at least one H&E figure. From the identified 30,585 articles we retain 113,161 H&E images to comprise our PubMed dataset. Images are annotated with figure caption, article abstract, and article title. This expanded dataset may contain disease that is too rare to be represented in social media data.

Image processing

We manually curate all social media images, separating pathology from non-pathology images. *Defining an acceptable pathology image* details this distinction in the supplement (Fig S4). Some pathologists use our Integrated Pathology Annotator (IPA) tool to browse their data and manually curate the annotations for their cases (Figs S6, S7). We retain non-pathology data publicly posted by consenting pathologists that cannot be publicly distributed to enable building a machine learning classifier that can reliably distinguish pathology from non-pathology images.

Fig 2. Technique, tissue, and disease diversity. Panel set A shows diverse techniques in our data. Initials indicate author owning image. **(A1)** *R.S.S.*: Papanicolaou stain. **(A2)** *L.G.P.*: Periodic acid-Schiff (PAS) stain, glycogen in pink. **(A3)** *L.G.P.*: PAS stain, lower magnification. **(A4)** *L.G.P.*: H&E stain c.f. Panel A3. **(A5)** *L.G.P.*: H&E stain, human appendix, including parasite *Enterobius vermicularis* (c.f. Fig S2). **(A6)** *L.G.P.*: Higher magnification *E. vermicularis* c.f. Panel A5. **(A7)** *L.G.P.*: Gömöri trichrome, collagen in green. **(A8)** *L.G.P.*: Diff-quik stain, for cytology. **(A9)** *R.S.S.*: GMS stain (*Intra-stain diversity* in supplement details variants), fungi black. **(A10)** *M.P.P.*: Giemsa stain. **(A11)** *A.M.*: Immunohistochemistry (IHC) stain, positive result. **(A12)** *A.M.*: IHC stain, negative result. **(A13)** *R.S.S.*: Congo red, polarized light, plaques showing green birefringence. **(A14)** *M.P.P.*: Fluorescence *in situ* hybridization (FISH) indicating breast cancer *Her2* heterogeneity. **(A15)** *S.Y.*: Head computed tomography (CT) scan. **(A16)** *L.G.P.*: Esophageal endoscopy.

In panel set B we show differing morphologies for all ten histopathological tissue types on Twitter. **(B1)** *C.S.*: bone and soft tissue. We include cardiac here. **(B2)** *K.H.*: breast. **(B3)** *R.S.S.*: dermatological. **(B4)** *L.G.P.*: gastrointestinal. **(B5)** *O.O.F.*: genitourinary. **(B6)** *M.P.P.*: gynecological. **(B7)** *B.X.*: otorhinolaryngological a.k.a. head and neck. We include ocular, oral, and endocrine here. **(B8)** *C.S.*: hematological, e.g. lymph node. **(B9)** *S.Y.*: neurological. **(B10)** *S.M.*: pulmonary.

In panel set C we show the three disease states we use: nontumor, low grade, and malignant. **(C1)** *M.P.P.*: Nontumor disease, i.e. herpes esophagitis with Cowdry A inclusions. **(C2)** *K.H.*: Nontumor disease, i.e. collagenous colitis showing thickened irregular subepithelial collagen table with entrapped fibroblasts, vessels, and inflammatory cells. **(C3)** *A.M.*: Low grade, i.e. pulmonary hamartoma showing entrapped clefts lined by respiratory epithelium. **(C4)** *R.S.S.*: Low grade, i.e. leiomyoma showing nuclear palisading. We show IHC completeness but it is not included for machine learning. **(C5)** *B.D.S.*: Malignant, i.e. breast cancer with apocrine differentiation. **(C6)** *L.G.P.*: Malignant, i.e. relapsed gastric adenocarcinoma with diffuse growth throughout the anastomosis and colon. Gross sections (e.g. Fig S3) shown for completeness but not used.

Fig 3. Deep learning methods summary. (A) An overall input image may be of any size, but must be at least 512×512 pixels [px]. **(B)** We use a ResNet-50 [27] deep convolutional neural network to learn to predict disease state (nontumor, low grade, or malignant) on the basis of a small 224×224px patch. This small size is required to fit the ResNet-50 and image batches in limited GPU memory. **(C)** For set learning, this network transforms each of the 21 patches sampled evenly from the image in a grid to a 100-dimensional vector. These 21 patches span the overall input image entirely. For instance, if the overall input image is especially wide, the 21 patches will overlap less in the X dimension. The ResNet-50 converts these 21 patches to 21 vectors. These 21 vectors are summed to represent the overall image, regardless of the original image's size, which may vary. This sum vector is concatenated with tissue covariates (which may be missing for some images), marker mention covariate, and hand-engineered features. A Random Forest then learns to predict disease state on this concatenation that encodes (i) task-agnostic hand-engineered features (Fig S9) near the image center, (ii) task-specific features from deep learning throughout the image, (iii) whether IHC or other markers were mentioned for this case, and (iv) optionally tissue type. Other machine learning tasks, e.g. histology stain prediction and tissue type prediction, were simpler. For simpler tasks, we used only the Random Forest and 2,412 hand-engineered features, without deep learning.

Text processing

Text data overview in the supplement discusses our text processing to derive ground truth from social media posts (Fig S8). We use hashtags, e.g. #dermpath and #cancer, as labels for supervised learning. We process the text of the tweet and the replies, searching for terms that indicate tissue type or disease state. For instance, "ovarian" typically indicates gynecological pathology, while "carcinoma in situ" typically indicates low grade disease (specifically, pre-neoplastic disease in our low grade disease state category). Our text processing algorithm (Fig S8) is the result of author consensus.

Random Forest classifier

We train a Random Forest of 1,000 trees as a baseline for all tasks. A white-balanced image is scaled so its shortest dimension is 512 pixels (px). The 512×512px center crop is then extracted, and 2,412 image features are calculated for this crop (Figs 3, S9).

Customized hybrid deep-learning-random-forest model and clinical covariates

Preprocessing, data augmentation, and ResNet-50 To maximize performance by learning disease-state-specific features, we additionally consider deep learning for the most challenging task of disease state prediction. Our deep learning architecture is a

Fig 4. Random Forest feature importance for prioritizing deep features, when non-deep, deep, and clinical features are used together for learning. We use the mean decrease in accuracy to measure Random Forest feature importance. To do this, first, a Random Forest is trained on task-agnostic hand-engineered features (e.g. color histograms), task-specific deep features (i.e. from the ResNet-50), and the tissue type covariate that may be missing for some patients. Second, to measure the importance of a feature, we randomly permute/shuffle the feature's values, then report the Random Forest's decrease in accuracy. When shuffling a feature's values this way, more important features result in a greater decrease in accuracy, because accurate prediction relies on these features more. We show the most important features at the top of these plots, in decreasing order of importance, for deep features (*at left*) and non-deep features (*at right*). The most important deep feature is "r50_46", which is the output of neuron 47 of 100 (first neuron is 0, last is 99), in the 100-neuron layer we append to the ResNet-50. Thus of all 100 deep features, r50_46 may be prioritized first for interpretation. Of non-deep features, the most important features include local binary pattern pyramids (LBPP), color histograms, and "tissue" (the tissue type covariate). LBPP and color histograms are visual features, while tissue type is a clinical covariate. LBPP are pyramid-based grayscale texture features that are scale-invariant and color-invariant. LBPP features may be important because we neither control the magnification a pathologist uses for a pathology photo, nor do we control staining protocol. *Marker mention and SIFT features excluded from Random Forest feature importance analysis* discusses in the supplement.

ResNet-50 [27] (Fig 3B) pretrained on ImageNet, which we train end-to-end without freezing layers (Fig S11). For deep learning, the white-balanced image is similarly scaled to be 512 pixels in its shortest dimension, but 224×224px patches are sampled for ResNet-50 training. We use data augmentation of random rotations, random flips, random zoom/rescaling, random brightness variations, Gaussian noise, and Mixup [28]. *Deep learning* in the supplement discusses further.

Covariates and features To best predict disease state and find similar cases, we seek to include as much patient-related context as possible in our computational pathology machine learning models, so we additionally include clinical information, i.e. tissue type and marker mentions. To represent the tissue type covariate, we include a ten-dimensional one-hot-encoded binary vector to encode which one of the ten possible tissue types is present for this case. It is all zeroes if the tissue type is unknown. We also include a binary one-dimensional marker mention covariate, which is 1 if any pathologist discussing the case mentions a marker test, e.g. "IHC" or "desmin". We append a 100-neuron fully-connected layer atop the ResNet-50, connecting to the ResNet-50 and covariates (Fig 3B). *Deep learning instance and set feature vectors* in the supplement discusses this and the interpretability related to the Heaviside step function (Eqns 6, 8).

Disease state classifier repurposed for similarity-based search

After we train a *Random Forest classifier* to predict/classify disease state from a variety of deep and non-deep features (Fig 3C), we then use this classifier's Random Forest

Fig 5. Interpretable spatial distribution of deep learning predictions and features. (**A**) An example image for deep learning prediction interpretation, specifically a pulmonary vein lined by enlarged hyperplastic cells, which we consider to be low grade disease state. Case provided by *Y.R.* (**B**) The image is tiled into a 5×5 grid of overlapping 224×224px image patches. For heatmaps, we use the same 5×5 grid as in Fig 1C *bottom left*, imputing with the median of the four nearest neighbors for 4 of 25 grid tiles. (**C**) We show deep learning predictions for disease state of image patches. *At left* throughout the image, predictions have a weak activation value of ~0 for malignant, so these patches are not predicted to be malignant. *At middle* the centermost patches have a strong activation value of ~1, so these patches are predicted to be low grade. This spatial localization highlights the hyperplastic cells as low grade. *At right* the remaining normal tissue and background patches are predicted to be nontumor disease state. Due to our use of softmax, we note that the sum of malignant, low grade, and nontumor prediction activation values for a patch equals 1, like probabilities sum to 1, but our predictions are not Gaussian-distributed probabilities. (**D**) We apply the same heatmap approach to interpret our ResNet-50 deep features as well. (**D1**) the most important deep feature corresponds to the the majority class prediction, i.e. C1, malignant. (**D2**) the second most important deep feature corresponds to prediction of the second most abundant class, i.e. C2, low grade. (**D3**) the third most important deep feature corresponds to prediction of the third most abundant class, i.e. C3, nontumor. The fourth (**D4**) and fifth (**D5**) most important features also correspond to nontumor. (**D6**) the sixth most important deep feature does not have a clear correspondence when we interpret the deep learning for this case and other cases (Fig S10), so we stop interpretation here.

similarity metric for search. Repurposing the classifier this way, we report the first pan-tissue (i.e. bone and soft tissue, breast, dermatological, gastrointestinal, genitourinary, gynecological, head and neck, hematological, neurological, pulmonary, etc) pan-disease (i.e. nontumor, low grade, and malignant) case search in pathology.

Three levels of sanity checking for search

To inform the physician and to avoid mistakes, sanity checks are important in medicine, or wherever human life may be at risk. Quantifying uncertainty is particularly important [24] in medicine, to assess how much trust to put in predictions that will affect the patient's care. We are the first to offer three sanity checks for each individual search: (i) prediction uncertainty, (ii) prediction as a check for search, and (iii) prediction heatmaps. *Machine learning sanity checking for search* discusses further. Briefly, "prediction uncertainty" relies on an ensemble of classifiers to assess if prediction strength is statistically significant, and if not, the prediction and search using this image should not be trusted. Second, "prediction as a check for search" indicates that if the disease state classification for a given image is assessed as incorrect by a pathologist, search results using this image should not be trusted, because the same classifier is used for both prediction and search. Third, we use "prediction heatmaps" to show disease-state predictions for each component of a given image, based on deep learning. If a pathologist disagrees with these heatmaps, deep-learning-based search for that image cannot be trusted. A failure of any one of these three checks indicates that search results may be incorrect, and they are flagged as such.

Three levels of method interpretability

Interpretability is critical in medicine [23] for physicians to understand whether or not the machine learning is misinterpreting the data, e.g. it is incorrect to learn a history of asthma is protective for pneumonia patients, even though such patients may often be admitted directly to an intensive care unit and have lower mortality risk [29, 30]. Asthma is not protective, intensive care is.

Ideally, interpretability facilitates both deductive and inductive human reasoning about the machine learning findings. Deductively, interpretability allows human reasoning about what machine learning finds in specific patient cases, e.g. explaining the malignant prediction overall for a patient by spatially localizing malignancy-related feature activations. Inductively, interpretability allows human reasoning about broad principles that may be inferred from the machine learning findings overall for a task, e.g. texture importance in disease state prediction. To the best of our knowledge, it is novel to offer both in a pan-tissue pan-disease manner in computational pathology. We do this with hand-engineered feature interpretability, Random Forest feature importance, and important deep feature activation maps (Fig 5D). *Machine learning interpretability for search* in the supplement discusses further.

Interpretability uncovers correspondences Considering both introspective/inductive interpretability (Fig 4) and demonstrative/deductive interpretability (Fig 5), we find a correspondence between important deep features (Fig 4) and the spatial localization of deep learning predictions (Fig 5). We find that using (Eqn 14) the three most important interpretable deep features slightly but significantly improve search performance (Table S1). *Deep set learning feature interpretation* discusses further.

Experimental design and evaluation

We evaluate our classifiers using 10-fold cross validation to estimate bounds of accuracy and Area Under Receiver Operating Characteristic (AUROC) performance metrics. *Supplementary Experimental design and evaluation* explains further. Because we intend for our methods to accurately find similar cases for any pathologist worldwide, we rigorously test search using leave-one-pathologist-out cross validation and report precision@k. Leave-one-pathologist-out cross validation isolates pathologist cases from one another, so a test set is independent from the corresponding training set. This isolates to a test set pathologist-specific or institution-specific imaging artifacts that may occur from microscopy, lighting, camera, or staining protocol. Thus our leave-one-pathologist-out cross validation measurements quantify our method's reproducibility, which is critical to measure in medical machine learning [6].

Social media bot for public prospective testing

We present the first pathology-specific social media bot, @pathobot, on Twitter. This bot is a case similarity search tool that applies our methods. Pathologists on Twitter mention the bot in a tweet containing an image. The bot uses our Random Forest classifier to provide disease-state prediction for that image, and search for similar results. Its prediction and search results, along with quantitative assessments of prediction uncertainty, are provided to pathologists in real time. In this way, the bot facilitates prospective tests, and encourages collaboration: as pathologists use the bot, they provide us with complementary qualitative feedback and help us recruit additional collaborators. In this way, the bot facilitates prospective tests, and encourages collaboration: as pathologists publicly use the bot, they provide us with complementary qualitative feedback and these interactions help us recruit additional collaborators.

Fig 6. H&E performance. Predicting if an image is acceptable H&E human tissue or not (*left*), or if image is H&E rather than IHC (*right*). Ten replicates of ten-fold cross validation (10-fold) and leave-one-pathologist-out cross validation (LOO) had similarly strong performance. This suggests the classifier may generalize well to other datasets. We use the "H&E vs others" classifier to find H&E images in PubMed. Shown replicate AUROC for H&E vs others is 0.9735 for 10-fold (10 replicates of 10-fold has mean±stdev of 0.9746±0.0043) and 0.9549 for LOO (10 reps 0.9547±0.0002), while H&E vs IHC is 0.9967 for 10-fold (10 reps 0.9977±0.0017) and 0.9907 for LOO (10 reps 0.9954±0.0004). For this and other figures, we show the first replicate.

Computational hardware

For machine learning, we use Weka version 3.8.1 [31] on a laptop. For deep learning, we use Tensorflow Keras [32] on GPUs and a supercomputing cluster. *Supplementary Computational hardware and software* discusses further. We perform feature importance analyses in R with the randomForest package [33].

Results

Identifying and filtering for H&E images

We ran increasingly difficult tests using increasingly sophisticated machine learning methods. Our first question is the most basic, but arguably the most important: can machine learning distinguish acceptable H&E-stained human pathology images from all others (Figs 2A, S4, S5)? We show acceptable H&E-stained human pathology images can be distinguished from other images – e.g. natural scenes or different histochemistry stains (Fig 6 *at left*) with high performance (AUROC 0.95+). Because of the high performance of this classifier, it can be used to partially automate one of our manual data curation tasks, i.e. identifying acceptable images on social media. More importantly, when confronted with over one million PubMed articles, we apply this classifier to filter out all the articles that do not have at least one H&E image. To our knowledge, this is the first H&E image detector to filter PubMed articles. PubMed figures increase our searchable dataset by over an order of magnitude, without any additional manual curation effort. Only with a large dataset may we expect to successfully search for rare diseases, and we currently have 126,787 searchable images. This task also serves as a positive control.

Distinguishing common stain types

H&E and IHC stain types are the most common in our dataset and are common in practice. We therefore ask if machine learning can distinguish between these stain types, which vary in coloration (Fig 2A). Indeed, the classifier performs very well at this discrimination (AUROC 0.99+, Fig 6 *at right*). Thus, although IHC coloration can vary between red and brown, machine learning can still successfully differentiate it from H&E (*Intra-stain diversity* explains further). A well-performing classifier such as this

Fig 7. 10-tissue type and 3-disease state prediction performance and counts. **(A)** Classifier performance for predicting histopathology tissue type (10 types, 8331 images). **(B)** Classifier performance for predicting disease state (3 disease states; 6549 images). Overall AUROC is the weighted average of AUROC for each class, weighted by the instance count in the class. Each panel **(A and B)** shows AUROC (with ten-fold cross-validation) for the chosen classifier. Random Forest AUROC for tissue type prediction is 0.8133 (AUROC for the ten replicates: mean±stdev of 0.8134±0.0007). AUROC is 0.8085 for an ensemble of our deep-learning-random-forest hybrid classifiers for disease state prediction (AUROC for the ten replicates: mean±stdev of 0.8035±0.0043). **(C)** Disease state counts per tissue type. The proportion of nontumor vs. low grade vs. malignant disease states varies as a function of tissue type. For example, dermatological tissue images on social media are most often low grade, but malignancy is most common for genitourinary images. **(D)** Disease state counts as a function of whether a marker test (e.g. IHC, FISH) was mentioned (~25% of cases) or not. IHC is the most common marker discussed and is typically, but not necessarily, used to subtype malignancies.

can be useful with large digital slide archives that contain a mixture of H&E and IHC slides that lack explicit labels for staining information. Our classifier can automatically and accurately distinguish these stains, so that downstream pipelines may process each stain type in a distinct manner.

Distinguishing ten histopathology tissue types

We next ask if machine learning can distinguish the ten tissue types present in our Twitter dataset (Fig 2B; *Tissue hashtags and keywords* discusses this further). The tissue types were distinguishable (AUROC 0.81+, Fig 7A) and, as expected, this task was more difficult than stain-related tasks. Being able to identify tissue types may help the detection of contaminating tissue in a slide.

Deep learning predicts disease state across many tissue types

Pathologists routinely make decisions about whether a tissue shows evidence of nontumoral disease, low grade disease, or malignant disease, while ignoring spurious artifacts (Fig S1). We therefore ask whether machine learning can perform well on this clinically important task. For this, we use our most common stain type, H&E, including only those images that are single-panel and deemed acceptable (Fig S4). We systematically test increasingly sophisticated machine learning methods (Fig 8) with the goal of achieving the highest possible performance. The simplest baseline model we consider, a Random Forest on the 2,412 hand-engineered features (Fig S9), achieves an AUROC of 0.6843±0.0012 (mean±stdev, Fig 8). Conversely, an ensemble of our deep-learning-random-forest hybrid classifiers achieves much higher performance, with AUROC 0.8+ (Fig 8). To our knowledge, this is the first classifier that predicts the full spectrum of disease states, i.e. nontumor, low grade, and malignant (Figs 2, 7B, 8).

Method	mean	stdev
Only Shallow	0.6843	0.0012
Shallow+Tissue	0.7515	0.0018
Shallow+Tissue+Marker	0.7846	0.0023
Shallow+Tissue+Marker+SIFT$_{k5}$	0.7796	0.0019
Only Deep Center Net	0.7402	0.0039
Only Deep Center	0.7461	0.0038
Only Deep	0.7766	0.0027
Shallow+Deep+Tissue	0.7803	0.0019
Shallow+Deep+Tissue Ens	**0.8035**	**0.0043**
Shallow+Deep+Tissue+Marker Ens	**0.8025**	**0.0021**
Shallow+Deep+Tissue+SIFT$_{k5}$ Ens	**0.8014**	**0.0022**

Fig 8. Disease state prediction performance for machine learning methods. For deep learning we use a ResNet-50. For shallow learning we use a Random Forest. We train a Random Forest on deep features (and other features), to combine deep and shallow learning (Fig 3C *top*). Error bars indicate standard error of the mean. Points indicate replicates. Gray lines indicate means. Performance increases markedly when including tissue type covariate for learning (even though tissue type is missing for some patients), when using deep learning to integrate information throughout entire image rather than only the center crop, and when using an ensemble of classifiers. Performance exceeds AUROC of 0.8 (*at right*). Methods are, from left to right, (i) Random Forest with 2412 hand-engineered features alone for 512×512px scaled and cropped center patch, (ii) Random Forest with tissue covariates, (iii) Random Forest with tissue and marker covariates, (iv) method iii additionally with SIFT$_{k5}$ features for Random Forest, (v) ResNet-50 at same scale as method i with center 224×224px center patch and prediction from top 3 neurons (Fig 3B *top*), (vi) ResNet-50 with Random Forest trained on 100 features from 224×224px center patch per method v and 2412 hand-engineered features per method i, (vii) ResNet-50 features at 21 locations throughout image summed and Random Forest learning on this 100-dimensional set representation with 2412 features, (viii) method vi with tissue covariates for ResNet-50 and Random Forest learning (Fig 3C sans marker information), (ix) an ensemble of three classifiers per method viii, (x) an ensemble of three classifiers per method viii with marker covariate for Random Forest (Fig 3C as an ensemble), (xi) an ensemble of three classifiers per method viii additionally with SIFT$_{k5}$ features for the Random Forest.

Texture and tissue are important clinico-visual features of disease

We next determine which features are important to our machine learning classifier for disease state prediction. To do this, we interpret the Random Forest feature importance to gain insight into the clinico-visual features that are predictive of disease state. Our analyses suggest that texture (e.g. Local Binary Patterns) and color (e.g. Color Histograms) features are most important for pathology predictions and search, followed by the tissue type clinical covariate (Fig 4; *Marker mention and SIFT features excluded from Random Forest feature importance analysis* discusses further). Our method is therefore multimodal, in that it learns from both visual information in the images and their associated clinical covariates (e.g. tissue type and marker mention). Both modalities improve search performance, as discussed in the following section.

Disease state search, first pan-tissue pan-disease method

In light of pathology-agnostic approaches to pathology search [17, 18], we ask if pathology-specific approaches to pathology search may perform better. Indeed, search is the main purpose of our social media bot. Moreover, others have noted task-agnostic features may suffer from poorly understood biases, e.g. features to distinguish major categories (e.g. cats and dogs) in natural images may systematically fail to distinguish

Fig 9. Case similarity search performance. We report search performance as precision@k for leave-one-pathologist-out cross validation for (**A**) tissue and (**B**) disease state. We note search based on SIFT features performs better than chance, but worse than all alternatives we tried. Marker mention information improves search slightly, and we suspect cases that mention markers may be more relevant search results if a query case also mentions markers. Deep learning and $SIFT_{k5}$ features improve performance even less (Table S1). (**C**) We show per-pathologist variability in search, with outliers for both strong and weak performance. Random chance is dashed gray line. We suspect variability in staining protocol, variability in photography, and variability in per-pathologist shared case diagnosis difficulty may underlie this search performance variability. The pathologist where precision@k=1 is lowest shared six images total for the disease prediction task, and these images are of a rare tissue type. Table S2 shows per-pathologist performance statistics.

major categories in medical images (e.g. ophthalmology or pathology) [34]. To evaluate performance of search, we show precision@k for k=1...10 (Fig 9). As a positive control, we first test search for similar tissues (Fig 9A), e.g. if the search query image is breast pathology then the top search results should be breast pathology. Here, precision@k=1 = 0.6 means 60% of the time the search query image and top search result image have matching tissue types, e.g. both are breast, or both are gastrointestinal, etc. We subsequently test search for similar disease states (Fig 9B, Table S1), e.g. if the search query image is malignant then the top search results should be malignant. Here, precision@k=1 = 0.7 means 70% of the time the search query image and top search result image have matching disease states (e.g. both malignant, both nontumor, etc), while precision@k=8 = 0.55 means the search query image matches 55% of the top 8 search results, i.e. 4-5 of the top 8 search results are malignant when the search query image is malignant. To estimate performance in general for each method, we perform 10 replicates of leave-one-pathologist-out cross validation with different random seeds (i.e. 0,1,...,9). This allows variance to be estimated for Random Forest learning, but methods based exclusively on the L1 norm are fully deterministic, so these have zero estimated variance (Table S1). We follow two-sample hypothesis testing, where one set of 10 replicates is compared to a different set of 10 replicates. To calculate a U statistic and a p-value, we use the two-tailed Wilcoxon rank-sum test on precision@k=1, which tests for significant differences in precision for the first search result on average. For search's statistical null model, we train a Random Forest on images with randomly shuffled class labels and evaluate precision@k, as a permutation test (i.e. "RandomForest(2412 + tissue), permutation test" precision@k=1 = 0.3967±0.0044 in Table S1, shown in Fig 9B). We conclude search performs significantly better than chance (0.7006±0.0026 vs 0.3967±0.0044, $U = 100, p = 1.083e-05$) and offer specifics below.

Results for disease state search are detailed in *Supplementary Disease state search results*. Here, we briefly describe three main findings. First, *Clinical covariates improve search performance*. Both tissue type (0.5640±0.0024 vs 0.6533±0.0025, $U = 100, p = 0.0001796$) and marker mention (0.6533±0.0025 vs 0.6908±0.0021, $U = 100, p = 0.0001796$) covariates significantly improve search performance. This suggests that for search these clinical features provide disease state information above and beyond the visual characteristics we have of each image. Second, *In the context of*

other features, nuclear features of disease are better represented by the most prevalent $_{309}$
SIFT clusters rather than all SIFT, and the effect of SIFT clusters on search is small $_{310}$
but significant $(0.6908\pm0.0021$ vs 0.6935 ± 0.0029, $U = 19.5$, $p = 0.02308)$. This $_{311}$
indicates nuclear features, as represented by SIFT, provide limited but complementary $_{312}$
disease-related information for search. Third, *Deep features synergize with other* $_{313}$
features, informing search more than nuclear SIFT features, but less than clinical $_{314}$
covariates. Specifically, deep features improve search performance less than tissue type $_{315}$
$(0.5720\pm0.0036$ vs 0.6533 ± 0.0025, $U = 0$, $p = 0.0001806)$ and less than marker mentions $_{316}$
$(0.6602\pm0.0022$ vs 0.6908 ± 0.0021, $U = 0$, $p = 0.0001817)$, but more than SIFT clusters $_{317}$
$(0.6983\pm0.0016$ vs 0.6948 ± 0.0032, $U = 83.5$, $p = 0.01251)$. Taken together, we conclude $_{318}$
(i) texture and tissue features are important, (ii) deep features are less important, and $_{319}$
(iii) nuclear/SIFT features are least important for disease state search. $_{320}$

Discussion $_{321}$

Summary $_{322}$

Pathologists worldwide reach to social media for opinions, often sharing rare or unusual $_{323}$
cases, but replies may not be immediate, and browsing potentially years of case history $_{324}$
to find a similar case can be a time-consuming endeavor. Therefore, we implemented a $_{325}$
social media bot that in real-time searches for similar cases, links to these cases, and $_{326}$
notifies pathologists who shared the cases, to encourage discussion. To facilitate disease $_{327}$
prediction and search, we maintain a large pathology-focused dataset of 126,787 images $_{328}$
with associated text, from pathologists and patients the world over. This is the first $_{329}$
pan-tissue, pan-disease dataset in pathology, which we will share with the community to $_{330}$
promote novel insights in computational pathology. After performing stain- and $_{331}$
tissue-related baselines with a Random Forest, we performed a number of analyses on $_{332}$
this dataset for disease state prediction and search. To accomplish this, we developed a $_{333}$
novel synthesis of a deep convolutional neural network for image set representations and $_{334}$
a Random Forest learning from these representations (Figs 3, S12). We found this model $_{335}$
can classify disease state with high accuracy, and be repurposed for real-time search of $_{336}$
similar disease states on social media. This interpretable model, combined with its social $_{337}$
media interface, facilitates diagnoses and decisions about next steps in patient care by $_{338}$
connecting pathologists all over the world, searching for similar cases, and generating $_{339}$
predictions about disease states in shared images. Our approach also allowed us to $_{340}$
make a number of important methodological advances and discoveries. For example, we $_{341}$
found that both image texture and tissue are important clinico-visual features of disease $_{342}$
state – motivating the inclusion of both of feature types in multimodal methods such as $_{343}$
ours. In contrast, deep features and cell nuclei features were less important for search. $_{344}$
Finally, we provide important technical advances, because our novel deep feature $_{345}$
regularization and activation functions yield approximately binary features and set $_{346}$
representations that may be applicable to other domains. In sum, these advances $_{347}$
readily translate to patient care by taking advantage of cutting-edge machine learning $_{348}$
approaches, large and diverse datasets, and interactions with pathologists worldwide. $_{349}$

Comparison with prior studies $_{350}$

Our approach builds on, but greatly extends, prior work in the field of computational $_{351}$
pathology. We will comment on this briefly here, and describe more fully in $_{352}$
Supplementary Comparison with prior studies. First, much of prior work involves a $_{353}$
subset of tissue types or disease states [35–37]. However, our study encompasses diverse $_{354}$
examples of each. Second, prior studies investigating pathology search take a variety of $_{355}$

pathology-agnostic approaches, e.g. (i) using neural networks that were not trained with ₃₅₆
pathology data [17,18] or (ii) using scale-invariant feature transform (SIFT) ₃₅₇
features [18,38,39] that do not represent texture or color [40]. Our inclusive approach is ₃₅₈
different, training a model on pathology data represented by thousands of features – ₃₅₉
including SIFT clusters, neural networks, other visual features, and clinical covariates. ₃₆₀
Our model outperforms pathology-agnostic baselines. ₃₆₁

Prior work has found texture and/or color to be important for tissue-related tasks in ₃₆₂
computational pathology [41–43]. We find texture and color to be important for ₃₆₃
disease-related tasks. Additionally, we go a step further by comprehensively considering ₃₆₄
the relative contributions of many clinico-visual features to the prediction and search of ₃₆₅
disease. Such important features include texture, color, tissue type, marker mentions, ₃₆₆
deep features, and SIFT clusters. ₃₆₇

Caveats and future directions ₃₆₈

Below we discuss the primary caveats (also see *Supplementary Caveats*) and future ₃₆₉
directions (also see *Supplementary Future directions*). ₃₇₀

Diagnosis disagreement or inaccuracy First, there is a risk of error in our data ₃₇₁
because many different pathologists share cases, and they may disagree on the most ₃₇₂
appropriate hashtags or diagnosis. Moreover, there may be diagnostic inaccuracies from ₃₇₃
the pathologist who posted the case, or other pathologists. We find these situations to ₃₇₄
be rare, but if they occur, the case tends to have an increased amount of discussion, so ₃₇₅
we can identify these situations. Second, our nontumor/low-grade/malignant keyword ₃₇₆
rules may be incorrect or vague. For these first and second caveats, we take a majority ₃₇₇
vote approach, manually curate as needed, and discuss. Indeed, as we discussed ₃₇₈
amongst ourselves the hyperplasia in Figure 5, it became clear we needed to explicitly ₃₇₉
mention pre-neoplastic disease is included in the low grade disease state category. ₃₈₀

Dataset case sampling and region of interest biases Our dataset may have ₃₈₁
both (i) a case sampling bias and (ii) a region of interest sampling bias. First, there ₃₈₂
may be case sampling bias if we typically have unusual cases that pathologists consider ₃₈₃
worth sharing, and our cases by necessity only come from pathologists on social media. ₃₈₄
We plan to advocate sharing of normal tissue and less unusual cases to circumvent this ₃₈₅
bias. Second, the pathologist who shares the case chooses which images to share, ₃₈₆
typically sharing images of regions of interest that best illustrate the diagnosis, while ₃₈₇
ignoring other slides where the diagnosis is less straightforward. In future work, we will ₃₈₈
include whole slide images for additional context. ₃₈₉

Dataset size and granularity To increase the granularity and accuracy of tissue ₃₉₀
type predictions, we first plan to expand the size of this dataset by recruiting more ₃₉₁
pathologists via social media, aiming to have representative images for each organ. ₃₉₂
There are many organs within the gastrointestinal tissue type, for instance. ₃₉₃
Additionally, we expect our dataset to broaden, including more social media networks ₃₉₄
and public pathology resources such as TCGA, with our bot integrating these data for ₃₉₅
search and predictions. ₃₉₆

Conclusion ₃₉₇

We believe this is the first use of social media data for pathology case search and the ₃₉₈
first pathology study prospectively tested in full public view on social media. ₃₉₉
Combining machine learning for search with responsive pathologists worldwide on social ₄₀₀

media, we expect our project to cultivate a more connected world of physicians and improve patient care worldwide. We invite pathologists and data scientists alike to collaborate with us to help this nascent project grow.

Acknowledgments

A.J.S. thanks Dr. Marcus Lambert and Pedro Cito Silberman for organizing the Weill Cornell High School Science Immersion Program. A.J.S. thanks Terrie Wheeler and the Weill Cornell Medicine Samuel J. Wood Library for providing vital space for A.J.S., W.C., and S.J.C. to work early in this project. A.J.S. thanks Dr. Joanna Cyrta of Institut Curie for H&E-saffron (HES) discussion. A.J.S. thanks Dr. Takehiko Fujisawa of Chiba University for his free pathology photos contributed to social media and this project via @Patholwalker on Twitter.

A.J.S. was supported by NIH/NCI grant F31CA214029 and the Tri-Institutional Training Program in Computational Biology and Medicine (via NIH training grant T32GM083937). This research was funded in part through the NIH/NCI Cancer Center Support Grant P30CA008748.

S.Y. is a consultant and advisory board member for Roche, Bayer, Novartis, Pfizer, and Amgen – receiving an honorarium.

T.J.F. is a founder, equity owner, and Chief Scientific Officer of Paige.AI.

We are grateful to the patients who made this study possible.

Author Contributions

Conceptualization: AJS, MA.

Data curation: AJS, WJ, SJC, LGP, BSP, MPP, NZ, BDS, SY, AM.

Methodology, Software, Validation, Formal analysis, Investigation, Writing (original draft): AJS.

Funding acquisition: AJS, TJF.

Project administration: AJS, WJ, SJC, MA, TJF.

Resources (pathology) and discussion: LGP, BSP, MPP, RSS, KH, NZ, BDS, SY, BX, SRA, AM, KAJ, KRO, SM, CM, HY, YR, RHA, OOF, JMG, CR, CS, JG, DES.

Resources (computational): AJS, TJF.

Supervision: MA, TJF.

Visualization, wrote annotation files: AJS, WJ, SJC.

Writing (editing): AJS, MA.

Writing (reviewing): AJS, LGP, BSP, MPP, SY, BX, AM, OOF, JMG, CS, SJS, MA, TJF.

Answered annotator questions: LGP, BSP, MPP, NZ, BDS, SY, BX, SRA, AM, SM, CM, HY, YR, RHA, OOF, CS, SJS.

Fig S1. Artifact and foreign body images. Our dataset includes artifacts and foreign bodies which machine learning should not consider prognostic. All panels human H&E. **(A)** *B.X.*: Colloid. **(B)** *L.G.P.*: Barium. **(C)** *L.G.P.*: Oxidized regenerated cellulose, a.k.a. gauze, granuloma may mimic mass lesion [44]. **(D)** *R.S.S.*: Hemostatic gelatin sponge, a.k.a. Spongostan™, may mimic necrosis. **(E)** *S.Y.*: Sutures, may mimic granuloma or adipocytes. **(F)** *L.G.P.*: Crystallized kayexelate, may mimic mass lesion or parasite.

Fig S2. Parasitology images. Our dataset includes diverse parasitology samples. **(A)** *B.S.P.*: *Strongyloides stercoralis*, light microscopy. **(B)** *B.S.P.*: *Dirofilaria immitis*, in human, H&E stain. **(C)** *B.S.P.*: *Plasmodium falciparum*, in human, Giemsa stain. **(D)** *B.S.P.*: Incidental finding of unspecified mite in human stool, light microscopy. **(E)** *B.S.P.*: *Dermatobia hominis*, live gross specimen. **(F)** *B.S.P.*: *Acanthamoeba*, in human, H&E of corrective contact lenses. **(G)** *B.S.P.*: *Trichuris trichiura*, gross specimen.

S1 Supporting information

S1.1 Image data overview

The goal of obtaining images from practicing pathologists worldwide is to create a dataset with a diverse and realistic distribution of cases. A worldwide distribution (Fig 1A) may be appropriate to overcome potential biases inherent at any single institution, such as stain chemistries or protocols. Our dataset includes a wide variety of stains and techniques (Fig 2A) – even variety for a single stain, e.g. H&E stains (Fig S5). H&E stain composition may vary by country – e.g. in France, H&E typically includes saffron, which stains collagen fibers. Phyloxin may be used instead of eosin. This helps differentiate between connective tissue and muscle, or to see cell cytoplasm better against a fibrous background. This stain may be referred to as "HES" or "HPS", and we consider it H&E. *Intra-stain diversity* discusses further. Our dataset includes gross sections (Fig S3) that pathologists share alongside images of stained slides. In addition to variation in the signal of interest (i.e., stain, tissue, or disease), we find variability in the noise (i.e. pathology artifacts, Fig S1). Such noise may initially seem undesirable, but is likely important for machine learning techniques to robustly predict which image motifs are relatively unimportant rather than prognostic. Finally, our dataset includes a variety of parasites and other [micro]organisms (Fig S2, and Fig S5A,E), an important consideration in developing countries.

S1.1.1 Defining an acceptable pathology image

To create our pathology social media database, we first identified pathology images, and second, narrowed down the set of pathology images into those that were of sufficient quality to be used and could be shared publicly. By "pathology image", we mean images that a pathologist may see in clinical practice, e.g. gross sections, microscopy images, endoscopy images, or X-rays. An image designated as a "pathology image" is not necessarily an image of diseased tissue. After we identified pathology images, we

Fig S3. Gross images. Gross sections are represented in our dataset, putting the slide images in context. **(A)** *M.P.P*: Urothelial carcinoma. **(B)** *M.P.P.*: Lung adenocarcinoma. **(C)** *S.R.A.*: Barth syndrome. **(D)** *N.Z.*: Enlarged spleen. **(E)** *S.R.A.*: Arteriovenous malformation. **(F)** *L.G.P.*: Kidney adrenal heterotopia.

Fig S4. Image acceptability criteria. Examples of images that are rejected, because they are not pathology images that a pathologist would see in clinical practice. **(A)** *top M.P.P., bottom B.D.S*: "art" rejects. **(B)** *top B.S.P., bottom S.Y.*: "non-pathology" rejects. **(C)** *top B.X., bottom A.M.*: "overdrawn" rejects. **(D)** *top S.R.A., bottom L.G.P.*: "panel" is rejected for some tasks, e.g. H&E vs IHC or disease state prediction, but not for others, e.g. H&E vs others. The H&E vs others task retains multi-panel images because multi-panel images that include an H&E panel should be included in our PubMed search results, and this classifier is used to filter PubMed. **(E)** *top and bottom S.R.A.*: top is acceptable H&E (see Sec S1.1.1 for definition), bottom is "dup" [duplicate] rejection.

screened them for inclusion in our dataset. "Acceptable images" are those that do not meet rejection or discard criteria defined below. If an acceptable image is personally identifiable or private (see criteria below), we retain the image for some machine learning analyses, but do not distribute the image publicly [for legal reasons]. ⁴⁷⁵ ⁴⁷⁶ ⁴⁷⁷ ⁴⁷⁸

Criteria for rejected, discarded, private, or acceptable images For our manual data curation process, we defined several rejection criteria (Fig S4), detailed in Section S1.2.1. Figure S4A shows examples of images rejected as "art", because they are artistically manipulated H&E pathology microscopy images. Figure S4B shows examples of images rejected as "non-pathology", e.g. parasitology-inspired cupcakes (*top*) and a natural scene image (*bottom*). Non-pathology images are relatively common on pathologists' social media accounts, though we try to minimize their frequency by recruiting pathologists who primarily use their accounts for sharing and discussing pathology. Figure S4C shows examples of images rejected as "overdrawn". Overdrawn images are those that have hand-drawn marks from a pathologist (which pathologists refer to as "annotations"), which prevent us from placing a sufficiently large bounding box around regions of interest while still excluding the hand-drawn marks.

Fig S5. H&E images. Our dataset includes diverse H&E-stained slide microscopy images. **(A)** *S.R.A.*: Acute villitis due to septic *Escherichia coli*. **(B)** *R.S.S.*: Garlic. **(C)** *R.S.S.*: "Accellular" leiomyoma after ulipristal acetate treatment. **(D)** *R.S.S.*: Brownish appearance from dark lighting. **(E)** *K.R.O.*: *Sarcina* in duodenum. **(F)** *B.D.S.*: Mature teratoma of ovary, pigmented epithelium. **(G)** *K.A.J.*: Central core myopathy.

Section S1.2.2 discusses our "overdrawn" criterion in detail. Figure S4D shows examples of images rejected as "panel", because they consist of small panels (*top*) or have small insets (*bottom*); splitting multi-panel images into their constituent single-panel images would substantially increase our manual curation burden. Figure S4E *top* is an acceptable H&E-stained pathology image. Figure S4E *bottom* is rejected as a duplicate of the S4E *top* image, though the colors have been slightly modified, and the original image is a different size.

S1.2 Supplementary Image processing

S1.2.1 Criteria details for rejected, discarded, private, or acceptable images

Though criteria are outlined in *Criteria for rejected, discarded, private, or acceptable images* – more formally, we reject the following image types, during our manual data curation process:

1. Non-pathology images, such as pictures of vacations or food.

2. Multi-panel images, such as a set of 4 images in a 2×2 grid. Images with insets are also rejected. For "H&E vs IHC", "tissue type", and "disease state" tasks, we only accept single-panel images, and leave for future work the complexities of splitting multi-panel images into sets of single-panel images. We accept multi-panel images for the "H&E vs others" task, because we use the classifier trained for this task to filter PubMed, and many H&E images in PubMed are multi-panel, which are useful as search results. Multi-panel images may have black dividers, white dividers, no dividers, square insets in a corner, or floating circular insets somewhere in the image. There may be two or more panels/insets. Per-pixel labels for each panel may be the best solution here, and would support a machine learning approach to split multi-panel images to reduce this additional manual data curation burden.

3. Overdrawn images, where a 256×256px region could not bound all regions of interest in an image. This occurs most frequently if a pathologist draws by hand a tight circle around a region of interest, preventing image analysis on the region of interest in a way that completely avoids the hand-drawn marks.

4. Images that manipulate pathology slides into artistic motifs, such as smiley faces or trees. In contrast, a picture of a painting would be a non-pathology image.

Moreover, we completely discard from analysis certain types of images:

1. Duplicate images, according to identical SHA1 checksums or by a preponderance of similar pixels. However, duplicate images may be shown in search results, if the images are contained in different tweets, because there may be different replies to these tweets as well.

2. Corrupt images, which either could not be completely downloaded or employed unusual JPEG compression schemes that Java's ImageIO[1] library could not open for reading.

3. Pathology images that are owned by pathologists who have not given us explicit written permission to use their images. Consider the following example. When a pathlogist gives us permission to download data, our software bot downloads thousands of that pathologists's social media posts regardless if some of the images in those posts are actually owned by a different pathologist who did not give us permission. We detect these cases when we manually curate the

---

[1]ImageIO documentation available here: `https://docs.oracle.com/javase/7/docs/api/javax/imageio/ImageIO.html`

pathologist's data, and discard these images belonging to pathologists who have   537
not given us permission. To elaborate, pathology images that are taken by   538
pathologists and shared on social media are treated the same way as pathology   539
images taken from case reports or copyrighted manuscripts, i.e. if the pathologist   540
or publisher has not provided us explicit written permission to use the image, we   541
discard the pathology image and do not use it.   542

Images that are not rejected or discarded are deemed "acceptable" pathology images.   543
However, for legal reasons, we cannot distribute all of the images we have from social   544
media, namely: 545

1. Pathology images obtained from children (including fetuses), which may be   546
identifiable. The data shared on social media are anonymized; thus, we do not   547
have contact information for the child's parent and therefore cannot obtain   548
consent to distribute a picture of e.g. a child's X-rays or gross specimens.   549
Although unlikely to be identified by the parent if these images were made public,   550
we prefer to err on the side of caution. However, microscopy slide images are not   551
personally identifiable, so we may distribute these.   552

2. Personally identifiable pictures involving adults, because they have the right to   553
consent or not to their likeness being distributed. We consider faces, body profiles,   554
automobile license plates, etc to all be personally identifiable pictures involving   555
adults, especially because these data may be cross-referenced against timestamp,   556
location, clinician, institution, medical condition, other people in the picture, etc.   557

3. Copyrighted content, which includes images of copyrighted manuscripts, pictures   558
of slideshow presentations, and pictures of any brand or logo. A lab picture that   559
includes boxes bearing logos would be a non-pathology image that we cannot   560
distribute, because we do not have permission to distribute any images with the   561
protected logos. A picture of a powerpoint slide at a conference that shows some   562
text outlining a new way to make a clinical decision would also be a   563
non-pathology image that we hold privately and do not distribute. We similarly   564
hold privately an image of text taken from a non-open-access manuscript because   565
it may not be possible to identify the original source to provide a proper citation,   566
and even if we could, this poses an additional data curation burden that we would   567
rather avoid. Moreover, we prefer to err on the side of caution and not distribute   568
these images, rather than rely on "fair use" or similar law that may expose us to   569
legal challenges and costs[2]. By retaining these images privately, we can train a   570
machine learning classifier to detect these types of images and potentially reduce   571
our manual data curation burden.   572

S1.2.2 Overdrawn rejection criterion   573

Here we discuss the details of rejecting images as "overdrawn". Figure S4C *top* is   574
rejected as "overdrawn", because the regions of interest (ROIs) in the H&E image that   575
the pathologist refers to in the social media post's text have hand-drawn circles and   576
arrows such that it is not possible to place a 256×256px square over all ROIs without   577
including these circle and arrow marks. We chose 256×256px because deep   578
convolutional neural networks in computational pathology [11] typically require   579
227×227px (i.e. AlexNet [45] or CaffeNet [46]) or 224×224px (i.e. ResNet [27]) images,   580
and we have used these sizes in the past [15, 22]. We note the Inception [47] family of   581
deep convolutional neural networks takes a 299×299px image input, which is larger than   582
256×256px and is also frequently used in computational pathology [11]. Ideally, each   583

---

[2]Courts in the United States have ruled that images posted to social media are still owned by their
authors and are not public domain. Indeed, in *Morel v. AFP*, AFP was ordered to pay Morel $1.2
million for copyright infringement because AFP used images that Morel posted to social media.

image would have ROIs and hand-drawn arrows/circles annotated at the pixel level, so each image could be annotated as "overdrawn" to arbitrary bounding box sizes, whether 256×256px or 299×299px, and we leave this to future work. Smaller "overdrawn" bounding boxes may allow more images to pass as acceptable, rather than be rejected. A 256×256px image size allows minor rotations and crops for deep learning data augmentation using 224×224px input image sizes. Minor upsampling and/or image reflection at the image's outer boundaries may allow a 256×256px image to work for 299×299px input image sizes. Figure S4C *bottom* is rejected as "overdrawn", because this image was originally 783×720px and the arrow marks prevent us from capturing each of the two indicated regions of interest in their own 256×256px square.

S1.2.3 Uniform cropping and scaling of original images

Images shared on social media may be any rectangular shape. However, machine learning methods typically require all images be the same size. To accommodate this, we use the following procedure:

1. Take the minimum of two numbers: the original image's height and width.
2. Crop from the center of the original image a square with a side whose length is the minimum from the prior step.
3. Scale this square to 512×512px.

This square is intended to be large enough to represent small details, such as arrows and circles drawn one pixel wide by the pathologist. Such arrows and circles may then be used to predict if an image is "overdrawn" or not. Ideally, the tweet's text would be available alongside the image to give the machine learning the fullest information possible about potential ROIs in the image, for "overdrawn" prediction, but for simplicity here we perform only image-based machine learning.

The motivation for the 256×256px "overdrawn" criterion detailed in Sec S1.2.2 is that there may be an attention layer that scans the original image for 256×256px squares that have no marks from the pathologist. Such marks include circles or arrows for ROI indication, or the pathologist's name to indicate copyright/ownership. Such mark-free 256×256px images may then be used for machine learning on only patient pathology pixels.

S1.3   Data diversity discussion

S1.3.1   Intra-stain diversity

There is an art and variability in histochemical stains that we have not discussed in the main text, but for completeness mention here. We note that in clinical practice we have observed high variability stains, for instance H&E stains that appear almost neon pink, to GMS stains (discussed below) that had silver (black) deposition throughout the slide. One reason for this is that there are a number of reagents that may be used for staining, each with different qualities that can make the stain darker, brighter, pinker, bluer, etc.

IHC stains typically use an antibody conjugated to a brown stain, namely 3,3'-Diaminobenzidine (DAB). The blue counterstain is typically hematoxylin. However, some laboratories conjugate the antibody to a red stain instead. A small minority of our IHC images are this red variant, which should not be confused with H&E.

There is counterstain variability in Grocott's modification of the Gömöri methenamine silver stain [GMS stain]. Typically the counterstain is green, but a pink counterstain is also available. We may see the pink variant as we acquire more data. Currently we see only green.

S1.3.2 Intra-tissue-type diversity

630

The tissue type hashtags we use are very broad, e.g. #gipath encompasses several ⁶³¹
organs, such as stomach, small intestine, large intestine, liver, gallbladder, and pancreas. ⁶³²
We note, for instance, liver morphology looks nothing like the stomach. Moreover, ⁶³³
gynecological pathology, i.e. #gynpath, includes vulva (which looks just like skin, i.e. ⁶³⁴
dermatological pathology, #dermpath), vagina, cervix, uterus, fallopian tubes and ⁶³⁵
ovaries. Again, vulva looks nothing like uterus. A number of tissue features also overlap, ⁶³⁶
such as adipocytes in breast tissue and adipocytes in the subcutaneous fat layer in skin. ⁶³⁷
The amount and distribution of adipocytes typically differs between these tissues ⁶³⁸
however. However, a lipoma in any tissue has a great deal of adipocytes and should not ⁶³⁹
strictly be confused with breast tissue. For all these motivating reasons, we have a ⁶⁴⁰
future direction to sample every organ within a tissue type hashtag category, for all ⁶⁴¹
tissue type hashtag categories. ⁶⁴²

S1.4 Procedure overview ⁶⁴³

S1.4.1 Consent, data acquisition, curation, and review ⁶⁴⁴

We follow the procedure outlined in Fig 1, and we first obtain data in steps A-D. In step ⁶⁴⁵
A, we find pathologists on social media (Twitter) who share many pathology cases, or ⁶⁴⁶
share infrequently shares tissues, e.g. neuropathology. In step B, we contact the ⁶⁴⁷
pathologist via social media and ask for permission to use their cases. In step C, we ⁶⁴⁸
download the consenting pathologist's cases shared on social media. In step D, we ⁶⁴⁹
manually annotate these posted cases for acceptability, e.g. if overdrawn, corrupt, ⁶⁵⁰
duplicate, multi-panel, art, or non-pathology rejecting per Fig S4. *Defining an* ⁶⁵¹
acceptable pathology image is explained in further sections. We additionally annotate ⁶⁵²
technique (Fig 2A), species (Figs S2, S5A,B,E), and private status (e.g. personally ⁶⁵³
identifiable pictures of adults or pictures of children). *Image data overview* and *Criteria* ⁶⁵⁴
for rejected, discarded, private, or acceptable images explain further, e.g. our definition ⁶⁵⁵
of "overdrawn" or what is [not] pathology. Moreover, if the ⁶⁵⁶
nontumor/low-grade/malignant status in a tweet is not clear, we read the Twitter ⁶⁵⁷
discussion thread for this case and manually annotate the case appropriately if possible. ⁶⁵⁸
Step D also involves clarifying cases that we have trouble annotating, e.g. if it is not ⁶⁵⁹
clear what stain was used for the image. We first ask the pathologist who posted this ⁶⁶⁰
case to social media. If we do not obtain an answer from that pathologist, we (i) ask a ⁶⁶¹
pathologist at our local institution (i.e. author *S.J.S.*) for an opinion or (ii) ask ⁶⁶²
pathologist coauthors would have shared cases with us. Pathologist validation of tissue ⁶⁶³
and disease labels is an important part of step D, and we use two tools for this. The ⁶⁶⁴
first tool is the Interactive Pathology Annotator (IPA) (Figs S6, S7), which pathologists ⁶⁶⁵
may run on their desktop to browse their case annotations. The second tool is our social ⁶⁶⁶
media bot "pathobot" (Fig 1), which interacts with collaborating pathologists, then ⁶⁶⁷
publicly posts results of search and disease state predictions. Pathobot search results ⁶⁶⁸
may indicate annotation issues, e.g. if a bone and soft tissue pathology search returns a ⁶⁶⁹
breast pathology result, we may check if the breast result was mistakenly labeled as ⁶⁷⁰
bone and soft tissue. Though we sometimes manually annotate some cases, most cases ⁶⁷¹
are annotated in a crowd sourced fashion. We use social media post hashtags and a ⁶⁷²
pathologist-reviewed rule-based text processing algorithm to determine tissue type and ⁶⁷³
disease state (Fig S8). ⁶⁷⁴

Interactive Pathology Annotator discussion   For completeness, we show another ⁶⁷⁵
example of the use of our Interactive Pathology Annotator (IPA) tool (Fig S7), which ⁶⁷⁶
some pathologists have used to check that tissue and disease state annotations were ⁶⁷⁷

Fig S6. Interactive Pathology Annotator tool and social media dialogue. *At left*: Pathologist (author *S.R.A.*) discusses a case. Without mentioning the diagnosis himself, he confirms the diagnosis suggested by a second pathologist, i.e. cystadenofibroma, which we explicitly annotate. *At right*: Our Interactive Pathology Annotator (IPA) tool displays an image from this case, in the context of the tweet overall. IPA is a portal for pathologists to (i) browse tweets and images in the dataset; (ii) validate our data annotations; (iii) check our tissue type categorization algorithm results, (iv) check our nontumor, low grade, and malignant categorization algorithm results; (v) search tweets for specific keywords or diagnoses; (vi) filter out all cases except those from a specific pathologist; and (vii) click the link to the original tweet on Twitter for context.

correct. This is a case of metastatic disease, from breast to gastrointestinal tissue, showing a diffuse pattern of lobular carcinoma that is more common in breast. ₆₇₈ ₆₇₉

S1.4.2 Machine learning, search, checks, and social media bot 680

Our procedure (Fig 1) continues with data analysis in steps E-G. In step E, we use 681 machine learning to train a classifier for a supervised learning task. For example, a task 682 may be to predict the disease state evident in a H&E image: malignant, benign / low 683 grade malignant potential [low grade], or nontumoral pathology. This is a three-class 684 classification task. Our baseline classifier is a Random Forest, [48] which we compare to 685 deep learning. We reuse the classifier to compute a similarity metric for search. In step 686 F, a pathologist posts to social media three key pieces of information together: (i) 687 pathology images, (ii) text descriptions, and (iii) the text "@pathobot". Our social 688 media bot is triggered when mentioned this way, with parts (i) and (ii) forming the 689 pathology search query. In step G, our bot first searches its social media database of 690 cases, then searches its larger PubMed database. A search result will be ranked highly 691 when the query and result tissue types match, when more clinical keywords are shared 692 between the query and result, and when the images are similar. Additionally, the bot 693 will use an ensemble of classifiers to compute with uncertainties the probability of each 694 disease state in each image. This prediction is a sanity check for search, i.e. if the 695 prediction is uncertain or inaccurate, then the search results may be suspect. 696

S1.4.3 Social media interactions, search, notifications, recruitment 697

One cycle of our procedure (Fig 1) culminates with concluding social media interactions 698 in steps H and I, before ultimately repeating at step A. The social media bot posts its 699

Fig S7. Interactive Pathology Annotator tool and tissue type hashtags. *At left*: Pathologist (author *K.H.*) discusses case. Without mentioning the diagnosis himself, he confirms diagnoses suggested by other pathologists, i.e. lobular breast carcinoma metastasized to ileum, which we explicitly annotate. *At right*: IPA shows that our tissue type categorization algorithm categorizes this tweet as breast pathology rather than gastrointestinal. The primary tumor is in breast. We define the tissue classification task this way to have applications for tumor site of origin prediction.

social media search results, PubMed search results, and disease state prediction results. The social media search results include links to similar cases posted to social media. The social media platform may notify pathologists that their posted case has been linked. These pathologists may discuss the putatively similar case. Our bot leverages text information from the pathologist's search post and reply posts. In this way our bot's search is informed by any diagnosis in the differential from any replying pathologist. When multiple pathologists mention the same clinical or diagnostic keywords, those keywords are weighted more highly for search. In effect, search is a collective endeavor by all pathologists in the community discussing the case. The same search repeated over time may be more informed when more pathologist discussion has accumulated over that time. We find that integrating our bot into social media discussions sometimes inspires pathologists to contact us, share with us, and collaborate with us. We then return to step A, and we collect more data for search and classifier training.

S1.5 Text data overview

For supervised learning, we use regular expressions to detect keywords in a tweet's text, to determine labels for the tweet's images. The text and included hashtags may indicate tissue type or disease state.

S1.5.1 Tissue type categories from text

Prior work has discussed pathology-related hashtags as a way to make pathology more accessible on social media [49]. Pathologists use hashtags to indicate histopathology tissue types, such as "#gynpath" to indicate gynecological pathology (Fig 2B). Sometimes alternative spellings are used, such as "#ginpath". Abbreviations are also common, e.g. "#breastpath" and "#brstpath" all mean the same thing: breast

Fig S8. 3-disease text processing algorithm flowchart. Flowchart of algorithm that processes a single tweet's text to categorize it as nontumor (309 images), benign/low grade malignant potential [low grade] (347 images), or malignant (385 images). A tweet may be skipped (132 images, i.e. 11.3% of images) when the pathologist discusses multiple possible diagnoses for this case or when no pathology keywords are found. Dashed line indicates early steps where tumor/-oma detected, and a later step where detected tumor/-oma considered for possible low grade categorization. Nontumor, low grade, and malignant are defined in Sec S1.7. Flowchart steps are detailed in Sec S1.7.1. The algorithm has many steps in order to parse overlapping words that have different diagnoses. For instance, if "Lobular carcinoma in situ of the breast" (which is a low grade disease) was the tweet text, the algorithm has an early step to categorize "carcinoma in situ" as low grade (which is correct here) because a later step categorizes "carcinoma" as malignant (which is not correct here). Indeed, tweet text "Carcinoma of the breast" describes a malignant disease and the algorithm categorizes it malignant because "in situ" is absent. Besides "carcinoma in situ" (low grade) and "carcinoma" (malignant), the algorithm distinguishes "chorangiomatosis" (nontumor) from "angioma" (low grade), "hydatidiform mole" (low grade) from "hydatid cyst" (nontumor) from "ovarian cyst" (low grade) from "cholecystitis" (nontumor), and "intravenous leiomyomatosis" (nontumor) from "leiomyoma" (low grade).

---

pathology (Fig S7). A pathology hashtag ontology is available here or alternatively   723
here[3]. Because a tweet can have more than one hashtag, we took the first tissue type   724
hashtag to be the "primary" tissue type of the tweet, and ignored the others.   725
Section S1.6.1 discusses a special case. As detailed in Section S1.6.2, we used hashtags   726
and keywords for all tweets in a message thread to identify the ten tissue types on   727
Twitter, finding 233 bone and soft tissue tweets, 155 breast tweets, 415 dermatological   728
tweets, 794 gastrointestinal tweets, 239 genitourinary tweets, 218 gynecological tweets,   729
308 head and neck tweets, 115 hematological tweets, and 559 pulmonary tweets.   730

S1.5.2   Nontumor, low grade, and malignant categories from text   731

We define three broad disease state categories (Figs 2C, S8) to use as labels for   732
supervised learning. Our "nontumor" category of 589 tweets includes normal tissue,   733
artifacts, injuries, and nontumoral diseases, e.g. Crohn's disease, herpes simplex   734
infection, and myocardial infarction. Our "malignant" category of 1079 tweets includes   735
all malignant disease, including carcinoma, blastoma, sarcoma, lymphoma, and   736
metastases. Our definition of malignancy in epithelial cancers is the ability to breach   737
the basement membrane, i.e. a malignant tumor escapes containment and is therefore   738
no longer treatable with surgical resection. Our "pre-neoplastic/benign/low grade   739
malignant potential" [low grade] category of 919 tweets is then all tumors or   740
pre-cancer/neoplastic lesions that are not yet invasive/malignant, e.g. hamartomas,   741
carcinoid tumors, adenomas, and carcinoma *in situ*. Details in Section S1.7. For the   742
nontumoral vs low grade vs malignant task, text processing was more complicated than   743
the tissue type task (Sec S1.6.2) because (i) of a heavy reliance on diagnosis keyword   744
matching (flowchart in Fig S8), and (ii) additional per-tweet and per-image annotations   745
to clarify nontumor/low-grade/malignant state, which may involve feedback from a   746
pathologist. Details in Section S1.7.   747

S1.6   Supplementary Text processing   748

S1.6.1   Hashtag special case   749

A hashtag special case is "#bstpath", bone and soft tissue pathology, which we include   750
in our breast pathology category only when the social media post's text also includes   751
the word "breast" or other breast-related keywords. Such keywords are listed further   752
below in this subsection. Examples of such tweets are *"Pleomorphic lobular carcinoma*   753
of the breast: Beautiful cells but nasty tumour #pathology #pathologists #BSTPath"   754
and *"Now at my desk, W(47y-o) breast nodule...Could be it siliconoma?? But it isn't*   755
noted giant cells #pathology #pathologists #BSTpath".   756

S1.6.2   Tissue hashtags and keywords   757

We found a large number of pathology-related hashtags. We grouped alternative   758
spellings, e.g. #ginpath is #gynpath, #brstpath is #breastpath, and   759
#headandneckpath is #entpath. We also grouped less common hashtags with more   760
common hashtags, e.g. #cardiacpath is #bstpath (bone and soft tissue). Some   761
groupings were broad, e.g. #headandneckpath, #thyroid, #salivary, #oralpath,   762
#endocrine, #endopath, #oralpath, #eyepath, and #ocularpath are all #entpath.   763
    To expand the per-tissue tweet counts, we moved beyond the hashtags and next   764
searched for keywords in the tweet using Perl regular expressions. Further, if a tweet's   765
tissue type could not be determined by hashtags and keywords, we assigned the tissue   766

---

[3]These URLs are `http://bit.ly/2g4mUFi` and `https://www.symplur.com/healthcare-hashtags/ontology/pathology/`

type of any other tweet in the message thread of tweets. For example, if a tweet of ₇₆₇ unknown tissue type were a reply to a tweet of known genitourinary type, then we ₇₆₈ considered both tweets to be genitourinary. ₇₆₉

S1.7 Nontumoral, Low grade, and Malignant task details ₇₇₀

Tasks involving distinguishing nontumoral disease, low grade tumors, and malignant ₇₇₁ tumors (Fig 2C) are our most difficult tasks. The acknowledged definition of ₇₇₂ "malignant" in epithelial cancers is the ability to breach the basement membrane, i.e. a ₇₇₃ malignant tumor escapes containment and is therefore no longer "treatable with surgical ₇₇₄ resection". A malignant tumor can invade into the adjacent tissue, lymphatics, and ₇₇₅ blood vessels. For machine learning, we define a three categories of disease: (a) normal ₇₇₆ tissue and nontumoral disease; (b) benign, low grade, and oncovirus-driven tumoral ₇₇₇ disease; and (c) malignant tumors – but there are number of caveats with this, because: ₇₇₈

1. there is a spectrum of pathology rather than an oversimplified 3-class ₇₇₉ nontumoral/low-grade/malignant system. ₇₈₀

2. the benign/malignant dichotomy may be more vague in certain tissues e.g. central ₇₈₁ nervous system (CNS) primary tumors such as chordomas. ₇₈₂

3. vague terms like adenoma are typically benign but may be malignant, and likewise ₇₈₃ vague terms like anaplasia are more often associated with malignancy but not ₇₈₄ always. ₇₈₅

4. vague terms like anaplasia and neoplasia make no real reference to the malignancy ₇₈₆ of lesions i.e. there are benign anaplastic lesions, while neoplasia is almost ₇₈₇ synonymous with tumor. ₇₈₈

5. terms like tumor do not provide information about benign or malignant state, ₇₈₉ though normal/nontumoral can be ruled out. ₇₉₀

6. there may be some disagreement if some terms, e.g. "carcinoma *in situ*", are more ₇₉₁ appropriate to include as low grade, or if instead should be considered malignant ₇₉₂ due to their malignant potential or treatment implications. For instance, ductal ₇₉₃ carcinoma *in situ* (DCIS) typically needs to be removed with surgery or ₇₉₄ radiotherapy, whereas lobular carcinoma *in situ* (LCIS) typically does not. DCIS's ₇₉₅ lower grade counterpart, atypical ductal hyperplasia, may get surgery or not. We ₇₉₆ believe treatment implications are a separate task. Typically, tweets do not ₇₉₇ include a decision to perform surgery or not, so additional annotations may be ₇₉₈ needed for the surgery task. We assign all pre-cancer and tumoral disease with ₇₉₉ malignant potential to the "low grade" category, in light of these ₈₀₀ benign/malignant ambiguities and data limitations. ₈₀₁

7. the diagnosis should be known before deciding benign/malignant, but it is very ₈₀₂ difficult to know the full diagnosis from the brief, generic, descriptive terms in the ₈₀₃ tweet. ₈₀₄

S1.7.1 Text processing for Nontumoral, Low grade, and Malignant tasks ₈₀₅

To determine if an acceptable H&E human microscopy image is nontumoral, low grade, ₈₀₆ or malignant, we use regular expressions (Fig S8) as we did for tissue type classification. ₈₀₇ However, keywords differed and we considered all tweets in a message thread per ₈₀₈ Sec S1.5.1. To infer these message threads of tweets, we downloaded from Twitter each ₈₀₉ tweet's metadata (in JavaScript Object Notation (JSON) format), which describes the ₈₁₀ parent tweet for each tweet. If tweet A is a reply to tweet B, then tweet A is the parent ₈₁₁ of tweet B, and both tweets are in the same message thread. ₈₁₂

Our heirarchical algorithm for nontumor/low-grade/malignant keyword-matching ₈₁₃
shown in Fig S8, and details for each step follow. First, to determine if a single tweet ₈₁₄
indicated nontumoral, low grade, or malignant, we looked for specific hashtags in a ₈₁₅
tweet's text that indicated malignancy, tumoral status, or nontumoral status. For ₈₁₆
illustartion, what follows is a subset of our rules, with commentary. ₈₁₇

1. Malignant: `/#[a-z]*cancer/i` or `/#metastas[ei]s/i` ₈₁₈

   - The first regular expression in this set matches #ANYcancer, where ANY ₈₁₉
     can be any non-whitespace characters, e.g. "#bladdercancer" and ₈₂₀
     "#breastcancer" both match, as well as "#cancer". ₈₂₁
   - Metastasis is a sign of malignant cancer, so tweets with #metastasis or ₈₂₂
     #metastases hashtags are malignant. ₈₂₃
   - If any matching keyword is detected, no further keyword processing is ₈₂₄
     performed. The tweet is malignant. ₈₂₅

2. Nontumoral: `/#crohn/i` or `/#neurodegeneration/i` or `/#pathbug/i` ₈₂₆

   - Crohn's disease and neurodegeneration are not tumoral diseases, so this ₈₂₇
     tweet is in the nontumoral/normal category. This `/#crohn/i` regular ₈₂₈
     expression is case-insensitive, so it matches "#crohn", "#Crohn", and ₈₂₉
     "#CROHN". The #pathbug hashtag indicates a parasite or other ₈₃₀
     microorganism is in the image, which is also nontumoral. ₈₃₁
   - If any matching keyword is detected, no further keyword processing is ₈₃₂
     performed. The tweet is nontumoral. ₈₃₃

3. Tumoral status (ambiguously low grade or malignant): `/#[a-z]*tumou?r/i` or ₈₃₄
   `/#[a-z]*oma/i` ₈₃₅

   - The first regular expression in this set matches #ANYtumor or ₈₃₆
     #ANYtumour, where ANY can be any non-whitespace characters, e.g. ₈₃₇
     "#BrainTumor" and "#phyllodestumour" both match, as well as "#tumor". ₈₃₈
   - The second regular expression matches #ANYoma, e.g. #Lymphoma and ₈₃₉
     #leiomyoma both match. ₈₄₀
   - Because "tumor" and "-oma" do not necessarily mean a tumor is low grade ₈₄₁
     or malignant, further keyword matching is performed. It is unlikely that the ₈₄₂
     tweet is nontumoral. If no other specific information is found after all further ₈₄₃
     keyword matching is performed, the tumor is presumed to be low grade. ₈₄₄

Second, if no hashtags matched, we then analyzed keywords in the tweet text. ₈₄₅

1. Skip: `/mistake/i` or `/misinterpret/i` or `/confuse/i` or `/suspect/i` or ₈₄₆
   `/worry/i` or `/surprise/i` or `/mimic/i` or `/simulate/i` or `/lesson/i` or ₈₄₇
   `/\bhelp\b/i` or `/usually/i` or `/difficult/i` or `/pathart/i` or ₈₄₈
   `/pathchallenge/i` or `/pathquiz/i` or `/pathgame/i` or `/^http/` ₈₄₉

   - We skip tweets where (i) the pathologist discusses points of the case which ₈₅₀
     may be easily mistaken – instead of providing a single diagnosis, (ii) the ₈₅₁
     pathologist provides a diagnosis but may suspect an alternative diagnosis, or ₈₅₂
     (iii) the tweet is simply a link to another tweet. No further keyword ₈₅₃
     matching is performed for this tweet. ₈₅₄

2. Tumoral status (ambiguously low grade or malignant): `/phyllod/i` or ₈₅₅
   `/\bgrade\b/i` or `/tumou?r/i` or (`/[a-z]{3,}oma\b/i` and not ₈₅₆
   `/schistost?oma/i`) ₈₅₇

- Phyllodes tumors, mentions of "tumor" or "tumour", mentions of tumor "grade", and mentions of words that end in "oma" but are not "Schistosoma" – are all detected here.
- Loosely speaking, phyllodes tumors are only slightly more likely to be low grade than malignant. Because "tumor", "-oma", and "grade" do not necessarily mean a tumor is low grade or malignant, further keyword matching is performed. It is unlikely that the tweet is nontumoral. If no other specific information is found after all further keyword matching is performed, the tumor is presumed to be low grade.
- *Schistosoma* (and its misspelling "Schistostoma") refers to a genus of parasitic worm, rather than a tumor, though *Schistosoma* ends in "oma" like many tumor types.

3. Low grade: `/oma in situ/i` or `/chondroblastoma/i`

   - If we did not skip this tweet, but the tweet does mention "oma *in situ*", e.g. "carcinoma *in situ*" or "melanoma *in situ*", then we consider this tweet and images to represent low grade disease. Carcinoma *in situ* is pre-cancer, and we consider it more low grade than malignant. If a tweet contains only "carcinoma" but not "*in situ*", subsequent steps will consider the tweet as malignant.
   - If the tweet includes "chondroblastoma", this tweet is low grade. This is not to be confused with other blastomas, such as glioblastoma or lymphoblastoma, which are malignant and matched in subsequent steps.
   - No further keyword matching is performed if these patterns match. The tweet is low grade.

4. Malignant: `/malignant/i` or `/malignancy/i` or `/cancer/i` or `/\bCA\b/i` or `/carc?inoma/i` or `/sarcoma/i` or `/blastoma/i` or `/\bWilms/i` or `/GBM/i` or `/anaplas(?:ia|tic)/i` or `/metastas[ie]s/i` or `/metastatic/i` or `/\bmets?\b/i` or `/adenoca/i` or `/melanoma/i` or `/seminoma/i` or `/lymphoma/i` or `/leuka?emia/i` or `/mesothelioma/i` or `/myeloma/i` or `/hodgkin/i` or `/\bHL\b/i` or `/burkitt/i` or `/plasmoc[yi]toma/i` or (`/paget/i` and `/breast/i`) or `/\bCLL\b/i` or `/PCNSL/i` or `/NSCHL/i` or `/\bCHL\b/i` or `/NSCC/i` or `/\bI[LD]C\b/i` or `/\bASPS\b/i` or `/mtscc/i` or `/sq?cc/i` or `/rcc/i` or `/bcc/i`

   - Many diagnoses and abbreviations may indicate cancerous malignancy, e.g. carcinoma, sarcoma, Wilms' tumor, leukemia, RCC [renal cell carcinoma], NSCC [non-small cell lung carcinoma], or the stand-alone abbreviation "CA" [cancer].
   - We consider "anaplastic/anaplasia" to be more malignant than low grade disease.
   - No further keyword matching is performed if these patterns match. The tweet is malignant.

5. Nontumoral: `/congenital/i` or `/cholecystitis/i` or `/chorangiomatosis/i` or `/mycobacteri(?:um|al)\s*spindle\s*cell\s*pse?udotumor/i` or `/intravenous\s*leiomyomatosis/i` or `/helicobacter/i` or `/dirofilaria/i` or `/tuberculo/i` or `/enterobius/i` or `/echinococcus/i` or `/hydatid\s*cyst/i` or `/giardia/i` or `/cryptosporidium/i` or `/ascaris/i` or `/sarcina/i` or `/worm/i` or `/spiroquet(?:osis|es)/i` or `/diverticulosis/i` or `/villitis/i` or `/colitis/i` or `/gastritis/i` or `/esophagitis/i` or `/appendicitis/i` or or `/xanthoma/i`

- Many diagnoses and abbreviations may indicate nontumoral disease, e.g. $_{907}$ congenital conditions, *Helicobacter* infection, and villitis. Nontumoral disease $_{908}$ keywords that contain "cyst", e.g. "cholecystitis" and "hydatid cyst", are $_{909}$ detected here, because subsequent keyword matching steps will detect "cyst" $_{910}$ as a sign of low grade tumoral disease. $_{911}$
- If one of these nontumoral keywords matches, no further keyword matches $_{912}$ are attempted, and the tweet is considered nontumoral, even if prior steps $_{913}$ detected "tumor" or "-oma". For instance, a "xanthoma" is a lipid aggregate, $_{914}$ not a tumoral disease, even though xanthoma ends in -oma. $_{915}$

6. Low grade: `/benign/i` or `/cyst/i` or `/polyp/i` or `/hamartoma/i` or $_{916}$ `/chorangioma/i` or `/ha?ematoma/i` or `/cylindroma/i` or `/fibroma/i` or $_{917}$ `/luteoma/i` or `/c[yi]toma/i` or `/cond[yi]loma/i` or $_{918}$ `/neoplas(?:ia|tic|m)/i` or `/LCIS/i` or `/DCIS/i` or `/\b[LD]IN\b/i` or $_{919}$ `/lipoma/i` or `/carcinoid/i` or `/neuroma/i` or `/meningioma/i` or $_{920}$ `/perineurioma/i` or `/cavernoma/i` or `/\bLGG\b/i` or `/\bODG\b/i` or $_{921}$ `/oligodendroglioma/i` or `/craniopharyngioma/i` or `/le[yi]om[iy]oma/i` or $_{922}$ `/schwannoma/i` or `/osteochondroma/i` or `/ependymoma/i` or `/angioma/i` or $_{923}$ `/syringoma/i` or `/acanthoma/i` or `/collagenoma/i` or `/hidradenoma/i` or $_{924}$ `/papilloma/i` or `/pilomatrixoma/i` or `/hydatidiform\s*mole/i` or `/wart/i` $_{925}$ or `/molluscum/i` or `/\bHPV\b/i` or `/\bEBV\b/i` or `/kerat?osis/i` or $_{926}$ `/fibrokeratoma/i` or $_{927}$ `/melanoc[iy]tosis/i` or `/brenner/i` or `/granular\s+cell\s+tumou?r/i` or $_{928}$ `/metaplas(?:ia|tic)/i` or `/dysplas(?:ia|tic)/i` or $_{929}$ `/dysembryoplas(?:ia|tic)/i` or `/hyperplas(?:ia|tic)/i` or `/\bLFH\b/i` or $_{930}$ `/\bDNE?T\b/i` or `/\bNET\b/i` or `/\bPTC\b/i` or `/\bGIST\b/i` or `/\bSTIC\b/i` $_{931}$ or `/\b[LD]ISN\b/i` or `/adenoma/i` or `/adenosis/i` $_{932}$

   - Many diagnoses may indicate benign tumor, e.g. hamartoma, fibroma, $_{933}$ condyloma, papilloma, lipoma, adenoma, adenosis, or cyst. $_{934}$
   - We consider "neoplastic/neoplasia", "metaplastic/metaplasia", $_{935}$ "hyperplastic/hyperplasia", and "dysplastic/dysplasia" to be more indicative $_{936}$ of benign/low-grade/non-invasive/pre-malignant disease than malignant $_{937}$ disease, but these terms are vague. $_{938}$
   - We broadly consider oncovirus-driven tumors and wart-like growths to be in $_{939}$ this low grade category also, e.g. HPV [human papilloma virus] warts and $_{940}$ *Molluscum contagiosum* "water warts". $_{941}$
   - We similarly consider abbreviations "LCIS" [lobular carcinoma *in situ*], $_{942}$ "DCIS" [ductal carcinoma *in situ*], "LISN" [lobular *in situ* neoplasia], and $_{943}$ "DISN" [ductal *in situ* neoplasia] to be more benign than malignant disease, $_{944}$ so we categorize them as low grade. Though DCIS may require surgical or $_{945}$ radiological intervention to be removed while LCIS may not, we consider our $_{946}$ "low grade" and "malignant" categories to be defined by the apparent $_{947}$ histopathology rather than the appropriate medical intervention. Predicting $_{948}$ appropriate medical intervention would be a different machine learning task. $_{949}$
   - If one of these keywords match, the tweet is considered low grade and no $_{950}$ further keyword matching is performed. $_{951}$

7. Nontumoral: `/normal/i` or `/ulcer/i` or `/embolism/i` or `/thromb/i` or $_{952}$ `/rupture/i` or `/infarct/i` or `/aneurysm/i` or `/ha?emorrhag/i` or $_{953}$ `/injur(?:y|ed)/i` or `/inflam/i` or `/swell/i` or $_{954}$ `/balloon\s*cell\s*na?ev(?:us|i)/i` or `/decidua/i` or `/foreign/i` or $_{955}$ `/lymphadenopath?y/i` or `/vasculopathy/i` or `/vasculitis/i` or `/synovitis/i` $_{956}$ or `/pulmonary\s*interstitial\s*glycogenosis/i` or $_{957}$

```
/essential\s*thrombocythemia/i or /endometriosis/i or          958
/mastoc[iy]tosis/i or /castleman/i or /herpe(?:s|tic)/i or /\bHSV\b/i   959
or /\bCMV\b/i or /cytomegalovir/i or /viral/i or                960
/bacteri(?:a|um)/i or /fung(?:al|us)/i or /mycetoma/i or        961
/myco(?:sis|tic)/i or                                           962
/infect(?:ion|ed)/i or /tauopathy/i or /amyloidosis/i or /neurodegen/i   963
or /\brabies\b/i or /hemosiderosis/i or /polymicrogyria/i or    964
/status\s*verrucosus/i or /\bIUGR\b/i or                        965
/storage\s*dis(?:ease|order)/i or /athero(?:sis|ma)/i or        966
/atherosclero(?:sis|tic)/i or /gauzoma/i or /colchicine/i or /\bIBD\b/i   967
or /GVHD/i or /crohn/i                                          968
```

- Many diagnoses may indicate normal tissue of nontumoral disease, e.g.   969
  normal, embolism, decidua, tauopathy, foreign body, mycetoma, CMV   970
  [cytomegaolovirus] infection, GVHD [graft versus host disease], and Crohn's   971
  disease.   972
- If one of these nontumoral keywords matches, no further keyword matches   973
  are attempted, and the tweet is considered nontumoral, even if prior steps   974
  detected "tumor" or "-oma". For instance, a mycetoma is not a tumor, even   975
  though mycetoma ends with -oma.   976

8. Nontumoral: (not tumor/oma) and (`/#[a-z]*path/i` or `/cerebell(?:um|ar)/i`   977
   or `/nodul(?:e|arity)/i`). Low grade if tumor/oma.   978

- If the tweet does not have tumor or "-oma" keywords detected from prior   979
  steps, and if the tweet has a #ANYpath hashtag (e.g. "#pulmpath" or   980
  "#pathology"), mention of "nodule"/"nodularity", or mention of the   981
  cerebellum, then we consider the tweet to be nontumoral. If instead the   982
  tweet has tumor or -oma keywords, then we consider the tweet to be low   983
  grade. The tweet is skipped if no steps identified the tweet as nontumoral,   984
  low grade, or malignant.   985
- Cerebellum is mentioned in several tweets, e.g. to depict normal cerebellar   986
  tissue[4]. Currently, we group normal tissue with tissue having nontumoral   987
  disease. We expect more tissue-based keywords may be used here in the   988
  future, as we expand our study to include more pathologists, tissues, and   989
  normal cases.   990
- In practice, we manually inspect all tweet message text to minimize the   991
  number of cases that are classified as nontumoral here. We typically write   992
  regular expressions to match specific keywords that indicate if a tweet   993
  represents nontumoral, low grade, or malignant disease.   994
- As part of our manual data curation, if on Twitter there was discussion   995
  among pathologists, and a different pathologist mentioned a correct   996
  diagnosis, and our consenting contributing pathologist concurred, then we   997
  write an auxiliary annotation file for the tweet with a summarized diagnosis[5].   998
  This summary is also used for pattern matching. This is an additional way   999
  that we minimize how many cases are handled at this late step.   1000
- Moreover, if the contributing pathologist wrote diagnostic text directly in the   1001
  image, we will write this text in the auxiliary annotation file for text   1002
  matching also.[6]   1003

---

[4]Normal cerebellum case by S.Y. at `https://twitter.com/Sty_md/status/821840894634565632`
[5]A case of this is from author *K.H.*, where a different pathologist gave the diagnosis, and he agreed.
We summarized this as "metastatic lobular carcinoma" in the auxiliary annotation file for the tweet
`https://twitter.com/Ho_Khanh_MD/status/999989201734197250`.
[6]A case of this is from author *M.P.P.*, where M.P.P. wrote "IDC DIN LISN" directly on a shared

Fig S9. Machine learning features. We use a variety of color, texture, and edge features for baseline machine learning analyses. Some features, such as color histograms, detect only color. Other features, such as Color Correlograms, detect both colors and textures. Pyramid features are scale-invariant. We separately consider SIFT features, which detect edges in a scale-invariant, rotation-invariant, and color-invariant manner, localized at interest points in an image.

- The way this "default nontumoral or low grade" rule is intended to be used is as a catch-all for unusual but non-malignant conditions[7]. Our motivation for this rule is to minimize our manual data curation burden. We do not wish to write an auxiliary annotation file or make a new regular expression for each unusual type of case, and we observe many of these cases are not malignant. It remains important to inspect the cases manually for correctness.

Tweets that do not match any nontumoral, low grade, or malignant rules are skipped in the same manner that Tweets matching skip rules are skipped. An additional caveat is this keyword matching may need refinement as we accumulate data.

S1.8 Image features for machine learning

To perform baseline machine learning analyses on the images from social media, we derive a feature representation for each image, as follows. We crop each image to the center square and resize it to 512×512 pixels [px]. See Sec S1.2.3 for more discussion of the 512×512px image size and how it relates to the 256×256px image size for the "overdrawn" criterion. This 512×512px image is then converted to a feature vector of 2,412 dimensions. The features we use (Fig S9) are available in Apache LiRE [50]. These features, and their dimension counts, are as follows: CEDD (144) [51], Color Correlogram (256) [52], Color Histogram (64) [50], FCTH (192) [53], Gabor (60) [50], Local Binary Patterns (256) [54], Local Binary Patterns Pyramid (756) [55], PHOG (630) [56], Rotation Invariant Local Binary Patterns (36) [57], and Tamura (18) [58].

S1.8.1 Deep learning instance and set feature vectors

After training, our appended 100-neuron layer (Fig 3B) is a 100-dimensional disease feature representation for a 224×224px patch. Due to our custom activation function and regularization (Fig S11), these 100 features are approximately binary (Fig S12C). A

---

histology image in the tweet `https://twitter.com/dr_MPrieto/status/890118713155997696` so we wrote this text in the auxiliary annotation file for the tweet.

[7]A case of this is from K.H., observing iron pill lesions in stomach biopsy `https://twitter.com/Ho_Khanh_MD/status/963800933716123648`.

vector sum of these 100-dimensional approximately binary feature vectors is a ¹⁰²⁸
100-dimensional feature counter vector, which we relate to set cardinality (Eqn 8). ¹⁰²⁹
Inspired by Deep Sets [59] and continuous bag-of-words [60] methods, we sample 21 ¹⁰³⁰
patches throughout the white-balanced image, then add the 21 100-dimensional feature ¹⁰³¹
vectors to derive a 100-dimensional set representation for the white-balanced image ¹⁰³²
(Fig 3C). In the set representation, if a feature's value is 21, then all 21 image patches ¹⁰³³
have this feature. An approximate intuition follows that if the value is 20, then 1 of the ¹⁰³⁴
21 patches does not have this feature. This set-based approach offers limited ¹⁰³⁵
interpretability and facilitates learning on large pathology images on social media, ¹⁰³⁶
despite the receptive field of a deep neural network being much smaller (1 million pixels ¹⁰³⁷
versus 224×224px, respectively). We train a Random Forest on the concatenation of (i) ¹⁰³⁸
this 100-dimensional set representation, (ii) our 2,412-dimensional hand-engineered ¹⁰³⁹
feature vector, (iii) the 10-dimensional tissue type covariate vector, and (iv) the ¹⁰⁴⁰
1-dimensional marker mention covariate vector (Fig 3C). Like Deep Sets, we use deep ¹⁰⁴¹
learning for instance learning, and add instance representations for a set representation. ¹⁰⁴²
However, our approach differs from Deep Sets in that (i) we use a Random Forest to ¹⁰⁴³
learn on set representations and side information (which is not differentiable end-to-end), ¹⁰⁴⁴
(ii) we add approximately binary Centered Soft Clipping (Fig S11) features in the range ¹⁰⁴⁵
(0,1) to implement counter-like set representations rather than add ReLU features in the ¹⁰⁴⁶
range [0,∞) which do not necessarily count instance features, and (iii) we use Random ¹⁰⁴⁷
Forest feature importance to interpret the relative influence of deep features, ¹⁰⁴⁸
hand-engineered features, and optional covariates on prediction/classification (Fig 4). ¹⁰⁴⁹

S1.9 Machine learning sanity checking for search ¹⁰⁵⁰

S1.9.1 Prediction uncertainty quantified with ensemble ¹⁰⁵¹

For disease state predictions posted to social media by the bot, we use an ensemble of ¹⁰⁵²
classifiers to quantify prediction uncertainty. This ensemble consists of the set of ¹⁰⁵³
classifiers for leave-one-pathologist-out precision@k search testing, so the ensemble size ¹⁰⁵⁴
is equal to the number of pathologists who contributed data. Leaving one pathologist ¹⁰⁵⁵
out from each classifier's training ensures some variability between classifiers. One ¹⁰⁵⁶
classifier makes one prediction per image. We use a Z-test to determine if a disease ¹⁰⁵⁷
state prediction's mean is significantly above chance. If no prediction is above chance, ¹⁰⁵⁸
then the predictions may be due to chance alone and ignored by a pathologist. Likewise, ¹⁰⁵⁹
search results may be ignored. This is our first prospective sanity check, and only ¹⁰⁶⁰
requires a statistical interpretation of predictions. ¹⁰⁶¹

Training data detection with ensemble This leave-one-out ensemble provides an ¹⁰⁶²
additional non-prospective sanity check – if only one classifier in the ensemble makes a ¹⁰⁶³
prediction that is strongly different from all the other classifiers in the ensemble, it is ¹⁰⁶⁴
possible that the bot was requested to make a prediction on a case that was in the ¹⁰⁶⁵
training data. This one "outlier" classifier that makes the strongly different prediction ¹⁰⁶⁶
is the classifier that left this pathologist's case out for training. The distribution of ¹⁰⁶⁷
predictions from these classifiers is depicted in a boxplot posted to social media by our ¹⁰⁶⁸
bot (Fig 1 *at lower left*). An outlier is indicated by a circle in the boxplot, and a circle ¹⁰⁶⁹
in a strongly different direction that the boxplot's interquartile range may suggest the ¹⁰⁷⁰
"outlier classifier sanity check" has been encountered. ¹⁰⁷¹

S1.9.2 Classifier repurposed, so if prediction suspect, then search suspect ¹⁰⁷²

If the Z-test of our distribution of predictions indicates the evidence in favor of a ¹⁰⁷³
particular disease state, e.g. nontumor, is not due to chance alone, but this is surprising ¹⁰⁷⁴

to a pathologist's expectations, the pathologist may consider the prediction to be ₁₀₇₅ suspect, so search results may be suspect as well. This is our second prospective sanity ₁₀₇₆ check, which requires a pathologists's expert opinion. ₁₀₇₇

Whole-patient prediction and disagreement detection Our method calculates ₁₀₇₈ the probability of a disease state per image, but given 1-4 images are in a tweet, we are ₁₀₇₉ left with two questions. First, what is the overall probability that this patient has a ₁₀₈₀ particular disease state, e.g. malignant? For this, we make the naïve statistical ₁₀₈₁ independence assumption of probabilities, multiply the prediction probabilities, and ₁₀₈₂ normalize them to sum to one. Second, what should we do when the prediction for one ₁₀₈₃ image differs from another for a given patient? In this case, the bot includes a warning ₁₀₈₄ in its tweet message and suggests mistakes are more likely, but we do not consider this a ₁₀₈₅ prospective sanity check, because images could indeed show different disease states. ₁₀₈₆

S1.9.3   Deep learning prediction heatmaps comparable to pathologist ₁₀₈₇ expectations ₁₀₈₈

Heatmaps from our deep learning can localize disease states within an image (Figs 5, ₁₀₈₉ S10), offering our third prospective sanity check to pathologists. If localization of ₁₀₉₀ predicted disease is suspect, then prediction may be suspect, and search may be suspect. ₁₀₉₁

S1.10   Machine learning interpretability for search ₁₀₉₂

S1.10.1   Hand-engineered feature interpretability ₁₀₉₃

We use existing hand-engineered visual features extensively (Fig S9). *Image features for* ₁₀₉₄ *machine learning* discusses the combination of color, texture, and edge features we use ₁₀₉₅ (Fig S9). All of have human-defined mathematical or algorithmic behavior written in ₁₀₉₆ software code. We know by definition a color histogram feature is invariant to rotation, ₁₀₉₇ because such a feature may simply be the sum of each pixel's red value in an image. ₁₀₉₈ Similarly, rotating an image should not change the diagnosis, so rotation invariance ₁₀₉₉ makes sense for disease state prediction. We also know properties of other features, such ₁₁₀₀ as the important Local Binary Patterns Pyramid (LBPP) [55]. LBPP is globally ₁₁₀₁ color-invariant because it operates on grayscale pixel values, not color pixel values. This ₁₁₀₂ may provide robustness to staining protocol differences between institutions. LBPP is ₁₁₀₃ globally scale-invariant because it employs a pyramid for multi-scale representation. ₁₁₀₄ This is the same pyramid used by PHOG [56]. This pyramid may support robust ₁₁₀₅ machine learning despite pathologists sharing images at different magnifications. LBPP ₁₁₀₆ is locally rotation-invariant because it consists of rotation-invariant local binary ₁₁₀₇ patterns at every level of the multi-scale pyramid representation. These ₁₁₀₈ rotation-invariant local binary pattern features are locally robust to localized ₁₁₀₉ orientation changes of a pathology image, e.g. minor perturbations in the orientation of ₁₁₁₀ a cell or tissue fiber. In contrast, PHOG consists of oriented gradients at every pyramid ₁₁₁₁ level, rather than rotation-invariant local binary patterns. LBPP is not globally ₁₁₁₂ rotation-invariant because, like PHOG, most pyramid grid cells are spatially localized, ₁₁₁₃ so a rotated image will have a different feature representation. LBPP is a texture ₁₁₁₄ feature because it compares the value of a center pixel to the value of many pixels at a ₁₁₁₅ particular radius from the center. Prior groups have used texture features to distinguish ₁₁₁₆ stroma, lymphocytes, necrosis, etc. Hand-engineered feature interpretability provides a ₁₁₁₇ simple foundation on which to build more abstract levels of interpretability. We can also ₁₁₁₈ reason about what features do not improve disease state prediction, e.g. SIFT features, ₁₁₁₉ which are thought to cover nuclei. ₁₁₂₀

S1.10.2   Random Forest feature importance   ₁₁₂₁

We use Random Forest feature importance to infer which features are important for ₁₁₂₂
disease state predictions. Hand-engineered visual features, clinical covariates, and deep ₁₁₂₃
learning features are concatenated together for a Random Forest to learn to predict ₁₁₂₄
disease state, so this single Random Forest classifier provides interpretability of each ₁₁₂₅
feature, in context together (Fig 4). We use this to infer broad principles, e.g. ₁₁₂₆
important clinico-visual features of disease state are texture (e.g. LBPP features) and ₁₁₂₇
tissue type covariates. Moreover, Random Forest feature importance identified several ₁₁₂₈
deep features were more important than the others for disease state prediction, so we ₁₁₂₉
focused our analyses on these important deep features. ₁₁₃₀

In principle, for classification, any interpretable classifier may be used in place of the ₁₁₃₁
Random Forest, e.g. logistic regression, support vector machine, or generalized additive ₁₁₃₂
model [30]. A careful choice here may demonstrate favorable accuracy and ₁₁₃₃
interpretability. We choose a Random Forest as a simple baseline that requires (i) little ₁₁₃₄
tuning or preprocessing, (ii) learns interpretable nonlinear relationships among features ₁₁₃₅
and covariates, and (iii) provides a measure of similarity for search. ₁₁₃₆

Marker mention and SIFT features excluded from Random Forest feature ₁₁₃₇
importance analysis   We excluded from our Random Forest feature importance ₁₁₃₈
analysis the marker mention covariate and SIFT features, primarily because both did ₁₁₃₉
not improve 10-fold cross validation prediction performance when using an ensemble of ₁₁₄₀
classifiers, which performed best for prediction (Fig 8: marker 0.8035 ± 0.0043 vs ₁₁₄₁
0.8025 ± 0.0021, $U = 3$, $p = 0.7$; SIFT 0.8035 ± 0.0043 vs 0.8014 ± 0.0022, $U = 7$, $p = 0.4$, ₁₁₄₂
two-tailed Wilcoxon rank-sum test). Moreover, SIFT reduces performance when an ₁₁₄₃
ensemble is not used (0.7846 ± 0.023 vs 0.7796 ± 0.0019, $U = 85$, $p = 0.0004114$). This ₁₁₄₄
may suggest that for sufficiently strong disease state classifiers using H&E images and ₁₁₄₅
tissue covariates, the marker mention covariate and SIFT features provide at best only ₁₁₄₆
redundant information. For example, if the decision to order a marker test, e.g. IHC, is ₁₁₄₇
typically based on the H&E, and a classifier is sufficiently accurate at predicting disease ₁₁₄₈
state from H&E, the decision to order a marker test provides no additional disease state ₁₁₄₉
information. Secondarily, we excluded the marker mention covariate because it is based ₁₁₅₀
on the clinical opinion of all pathologists commenting on this case. Disease state is ₁₁₅₁
based on the diagnosis, which is also a clinical opinion. Rather than seeking to explain ₁₁₅₂
one opinion in terms of another opinion, we seek to explain opinions in terms of ₁₁₅₃
objective information in the H&E or clinicals, e.g. tissue type. We note 10-fold cross ₁₁₅₄
validation may provide inflated measures of performance, so for a less inflated ₁₁₅₅
examination of the possible contributions of the marker covariate, SIFT features, and ₁₁₅₆
deep features, we turn to leave-one-pathologist-out cross validation for search. *Disease* ₁₁₅₇
state search, first pan-tissue pan-disease method discusses this. ₁₁₅₈

S1.10.3   Interpretability of important deep features through activation ₁₁₅₉
maps   ₁₁₆₀

Deep neural networks have a restricted field of view, but this is an advantage for ₁₁₆₁
interpretability, because one can systematically sweep a trained neural network across ₁₁₆₂
an image to localize deep feature activations. At each location in the sweep, a ₁₁₆₃
224×224px image patch is fed to the trained neural network for interpretation. However, ₁₁₆₄
our Random Forest uses a set representation of the deep features, formed as a sum of ₁₁₆₅
deep feature vectors systematically sampled throughout the overall image of arbitrary ₁₁₆₆
size (Fig 1). Therefore, for spatial localization of disease state we make heatmaps to ₁₁₆₇
depict the deep feature activations at those sampled locations. These heatmaps indicate ₁₁₆₈
a correspondence between the most important deep features and the class labels. This ₁₁₆₉

Fig S10. Interpretable spatial distribution of deep learning predictions and features of multiple cases. We compare four cases side-by-side, in the manner of Fig 5. The most important deep feature is r50_46 (Fig 4 *at left*), which predicts the majority class, e.g. **A3** *left* corresponds to **A4** *upper left*. The second most important feature (r50_30) predicts the second most abundant class, low grade. The third most important feature (r50_85) predicts the third most abundant of three classes, nontumor. The strong class correspondence in important deep features may suggest that removing the top layer's three class-predictor neurons may incur only a small loss of learned information (Fig 3B *top*). **(A)** *B.X.*: metastatic lobular carcinoma in satellite lymph node, where malignant activation is high throughout, except the lower right background. **(B)** *C.S.*: juvenile polyp, where nontumor activation is high both for the lentil at lower center and the dark *Ascaris* ova at right, showing the breadth of the nontumor disease state category. **(C)** *R.S.*: is a proliferating epidermoid cyst. Despite viral wart change, we consider this in the low grade disease state (Fig S8). This example also illustrates a different image size and microscope eyepiece field of view artifact. **(D)** *Y.R.*: pulmonary vein lined by enlarged hyperplastic cells, which we consider to be low grade disease state, and **D3** *center* highlights these low grade cells.

approach facilitates deductive reasoning about predictions, e.g. (i) in Fig 5 the image overall is predicted by the deep-learning-random-forest hybrid classifier to be low grade (not shown), (ii) this classifier includes deep features (Fig 1C), (iii) a deep feature of ours is by definition a vector sum of images (Fig 1C) shown in the grid (Fig 5D2), (iv) the second most important deep feature (r50_30 in Fig 4) is known to correspond to low grade (e.g. Fig 5C2), (v) r50_30 is active with a value of more than 0.5 for images shown in the grid center (Fig 5D2), (vi) therefore the classifier predicts low grade partly because images near the grid center have the low grade feature. Similar to our work, previous work used Random Forest feature importance for feature selection on a pretrained deep neural network [61], though to the best of our knowledge we are the first to use Random Forest feature importance for feature selection on a deep neural network retrained on the same task as the Random Forest.

S1.11 Machine learning methods discussion

Because our image feature vectors are so wide, e.g. 2,412 dimensions (Fig S9) or more, we found best results with Random Forests when the number of features to consider for a decision/split was half (rounded up) of the total attribute count. This was especially important for covariates, e.g. the tissue covariate for disease state prediction. For search using Random Forest similarity, we grew each tree to a maximum depth of 10.

S1.11.1 Deep learning

Cross entropy loss for learning We optimize the deep neural network with an unweighted cross entropy loss (Eqn 1, where $I_{y_i \in C_i}$ is the indicator function being 1

Fig S11. Deep learning performance curves. Loss and accuracy for training and validation sets, for one fold of 10-fold cross validation, using a ResNet-50 to predict disease state, for individual 224×224px image patches. Validation accuracy improves with training, though high validation accuracy may suggest (i) the ground truth label may not apply universally throughout the image which is larger than 512×512px, (ii) samples whose state may not fit with our three-class disease state schema, (iii) mislabeled samples, (iv) deep learning overfit. Indeed, we see in many of our images mixtures of diseases and disease-free tissue, so (i) may be especially likely, and more advanced methods, such as multiple instance learning, may overcome this as we acquire more data. Observing that validation accuracy improved with training, we proceeded with this simple supervised deep learning approach as a proof-of-principle.

when the example x class label y_i is class C_i, and 0 otherwise)[8], for minibatches of size $N = 64$ 224×224px images and typically $C = 3$ classes (nontumor, low grade, malignant). We use stratified bootstrap sampling for each epoch, so all classes have equal weight.

$$\mathcal{L}_{unweighted}(\{x_1, x_2, ..., x_N\}) = -\frac{1}{N}\sum_{i=1}^{N}\sum_{c=1}^{C}[I_{y_i \in C_i}]log(p_{model}[y_i \in C_i]) \qquad (1)$$

ResNet-50 learning   For our deep learning, we freeze no layers of the ResNet-50. We train end-to-end with learning rate of 0.01 and Nesterov accelerated gradient momentum of 0.9 [62–64]. We use Keras' learning rate decay of 10^{-5}, which reduces the learning rate each batch. Moreover, we follow a learning rate schedule, where learning rate is divided by 100 until the end of epoch 1, but by 10 until the end of epoch 3. We train with Mixup [28], mixing according to draws from a beta distribution with $alpha = 1.4$ and $beta = 0.4$. Our data augmentation is random flips, random free rotations, grayscale Gaussian noise in RGB color space (mean=0, stdev=0.5), and random brightness adjustment (uniform distribution, -0.05 to 0.05). We white-balance images before processing.

Freezing layers lowered validation accuracy. Alternative architectures such as

---

[8]For this formula please see `https://github.com/keras-team/keras/issues/6444`

Fig S12. Deep features. We appended a 100 neuron fully connected layer on top of a ResNet-50 to learn a concise 100-dimensional "bottleneck" feature vector representation of a 224×224px image patch (Fig 3). This feature vector takes different distributions, depending on regularization. The top row shows a 100-dimensional activation distribution as standard deviations from the mean, and training proceeds left to right. The bottom row shows the same activation distribution as the top row, but as a histogram, with training proceeding from dark red at the top to orange at the bottom. **(A)** Feature values are centered at 0.5 when L1 regularization on the activation value before a sigmoid squashing function is applied, because a sigmoid transforms a 0 value to 0.5. **(B)** Feature values are approximately bimodal when L1 regularization on the activation value after sigmoid squashing is applied, because L1 regularization enforces sparsity by penalizing non-zero values. **(C)** Feature values are more strongly bimodal when our binarizing regularization (a.k.a. centered L1 regularization, Fig S13C,D) on the activation value after our centered soft clipping activation function is applied, because this regularization penalizes values near 0.5 and centered soft clipping saturates to 0 or 1 more quickly than a sigmoid. We ultimately chose our centered L1 regularization and centered soft clipping activation to represent the deep feature space for disease state prediction, because (i) it performed better with Random Forest learning over feature vector sums of a set of multiple images (Fig S13A), (ii) it demonstrated comparable validation accuracy in deep learning (Fig S11), (iii) Random Forests have a bias to select features that take many values [65,66] so approximately binary deep features may reduce this bias by having a restricted distribution of values, and (iv) we believe approximately binary deep features to be simple and interpretable as set scalar cardinality, i.e. counters (Fig 5 and Eqn 8).

DenseNet, Inception, and Xception trained more slowly and lowered validation accuracy. We do not report these results.

S1.11.2 Deep set learning feature interpretation

As our ResNet-50 deep neural network trains (Fig S11), a 100-dimensional feature representation is learned (Fig S12), by the 100-neuron layer we append to the ResNet-50 (Fig 3C). A spatially-localized empirical interpretation of deep learning predictions and feature activations is available in Figure 5. We analytically interpret our deep features through their activation functions, regularization, and relationship with set scalar cardinality, below.

Centered soft clipping activation function definition To learn sharply binary features from the deep learning, we define a steep activation function, called centered soft clipping (CSC) (Fig S13B and Eqn 3). This is derived from soft clipping (SC) [67], which is not centered at x=0 (Fig S13B and Eqn 2). Like centered soft clipping, the sigmoid and hyperbolic tangent activation functions centered at x=0, but they are not as steep. There is a steepness parameter (p) in [centered] soft clipping, and we let $p = 2$

Fig S13. Sigmoid vs centered soft clipping performance. (A) Random Forest AUROC when ResNet-50 trained with sigmoid activation function with L1 regularization, versus centered soft clipping activation function with centered L1 regularization. Centered soft clipping demonstrates higher performance. Increasing the number of regions of interest (ROI) images in a deep set from 13 to 21 (Fig 1C shows 21) improves performance slightly. Quantizing features to either 0 or 1 slightly reduces performance when using centered soft clipping. **(B)** Comparison of sigmoid activation function with soft clipping [67] (Eqn 2) and our centered soft clipping (Eqn 3). Our centered soft clipping is centered at x=0 and steeper than sigmoid, which we argue is amenable for learning interpretable (Fig 5) and sharply binary hash codes. **(C)** Comparison of L1 (Eqn 11), L2, and our centered L1 (Eqn 13) regularizers in two dimensions, x_0 and x_1. Our L1 regularizer penalizes values close to 0.5, to encourage a binarized feature representation. **(D)** Comparison of L1 and our centered L1 regularizers, in one dimension, for clearer depiction of our centered L1 regularizer's margin $m = 0.1$ (Eqn 13), for stable learning and vanishing gradient avoidance.

for our experiments (Eqns 2, 3).

$$\text{SC}_p(x) = \frac{1}{p}log(\frac{1 + e^{px}}{1 + e^{p[x-1]}}) \tag{2}$$

$$\text{CSC}_p(x) = \frac{1}{p}log(\frac{1 + e^{p[x+0.5]}}{1 + e^{p[x-0.5]}}) \tag{3}$$

Centered soft clipping in the limit as Heaviside step function   Furthermore, we note in the limit $p \to \infty$, centered soft clipping converges to the Heaviside step function $H(x)$, a type of indicator function which is 1 for positive values, 0 for negative values, and 0.5 for zero values (Eqn 6). In the limit $p \to \infty$, $\text{CSC}_p(x)$ is a binary indicator of the presence or absence of a feature in a 224×224px image patch (Fig 1B), representing binary logic. Smaller values, e.g. $p = 2$, allow the representation of a small amount of probabilistic uncertainty regarding this presence or absence, where this area

of uncertainty is infinitesimally small for $p \to \infty$.

$$\lim_{p \to \infty} \mathrm{CSC}_p(x) = \frac{1}{p}[log(1 + e^{p[x+0.5]}) - log(1 + e^{p[x-0.5]})] \tag{4}$$

$$\lim_{p \to \infty} \mathrm{CSC}_p(x) = \begin{cases} \frac{1}{p}[log(1+0) - log(1+0)] = \frac{0}{p} = 0 & \forall x < 0, \\ \frac{1}{p}[log(1 + e^{p(0.5)}) - log(1+0)] = \frac{p(0.5)}{p} = 0.5 & \forall x = 0, \\ \frac{1}{p}[p(x+0.5) - p(x-0.5)] = \frac{p}{p} = 1 & \forall x > 0 \end{cases} \tag{5}$$

$$\lim_{p \to \infty} \mathrm{CSC}_p(x) = H(x) = \begin{cases} 0 & \forall x < 0, \\ 0.5 & \forall x = 0, \\ 1 & \forall x > 0 \end{cases} \tag{6}$$

Deep feature as set scalar cardinality   To our Random Forest, a deep feature is the scalar cardinality (Eqns 7-8) of the set of these presences measured at 21 different locations throughout the original image (Fig 1C). Here, x represents one of the 100 features from the trained layer atop the ResNet-50 in Figure 1B, and I is an indicator function of set membership.

$$\mathrm{Card(set)} = |\mathrm{set}| = |\{x_1, x_2, \ldots, x_N\}| = \sum_{n=1}^{N=21} I(x_n) \tag{7}$$

$$= \sum_n H(x_n) = \sum_n [\lim_{p \to \infty} \mathrm{CSC}_p(x_n)] \approx \sum_n \mathrm{CSC}_p(x_n) \ \ \forall p > 0 \tag{8}$$

Data as Bernoulli process, deep features, and expected value   To consider some input data passed through the ResNet-50, we model a random set as a Bernoulli process, with each set member taking some value on the interval $(0, \infty)$ at probability φ, otherwise some value on the interval $(-\infty, 0)$. Let $\mathbb{P}_\varphi(x)$ be a Bernoulli trial that is $(0, \infty)$ at probability φ, otherwise $(-\infty, 0)$ A Heaviside step function (Eqn 6), which our centering soft clipping (CSC) activation function approximates in the limit of $p \to \infty$, transforms this $\mathbb{P}_\varphi(x)$ to a standard Bernoulli trial taking value 1 at probability φ, otherwise 0. Thus the cardinality of this random set is proportional to the Bernoulli trial's expected value $\mathbb{E} = \varphi$ (Eqn 10). In a sense, for a fixed set size e.g. $N = 21$, the Random Forest may learn what thresholds of $\mathbb{E}$ of these deep features are predictive of the classes of interest, in the context of the other available deep and non-deep features (Fig 1C).

$$\mathrm{Card(set)} = |\mathrm{set}| = |\{\mathbb{P}_\varphi(x_1), \mathbb{P}_\varphi(x_2), \ldots, \mathbb{P}_\varphi(x_N)\}| = \sum_n^N H(\mathbb{P}_\varphi(x_n)) = \tag{9}$$

$$= \sum_n^N [\lim_{p \to \infty} \mathrm{CSC}_p(\mathbb{P}_\varphi(x_n))] = N\mathbb{E}(x) = N\varphi \tag{10}$$

Centered L1 regularizer in the context of Gaussian initialization   Neural network weights are often initialized with Gaussian noise having mean of zero [62], so centering the activation function at zero removes initial bias towards learning a 0 or 1 when combined with our centered L1 regularizer (Eqn 3). Whereas a standard L1 regularizer (Eqn 11) penalizes all non-zero values, our centered L1 regularizer penalizes values close to 0.5 (Eqn 13), with the assumption that all values are between 0 and 1,

which is true for values from centered soft clipping (Eqn 3).

$$L1(x_0, x_1) = |x_0 + x_1| \tag{11}$$

$$\text{CL1penalty}(x, m) = max(m, 0.5 - |x - 0.5|) - m \tag{12}$$

$$\text{CL1}(x_0, x_1, m) = |\text{CL1penalty}(x_0, m) + \text{CL1penalty}(x_1, m)| \tag{13}$$

To approximately binarize deep features, our centered L1 regularizer penalizes output values close to 0.5, which occur when $x = 0$ with sigmoid and centered soft clipping activations. (Fig S13D). For stable learning, and to help avoid the vanishing gradient problem [68,69] from values infinitesimally close to 0 or 1, our centered L1 regularizer has no penalty for values less than 0.1 or greater than 0.9. Restated, we let the L1 regularizer's margin parameter $m \in [0, 0.5]$ be $m = 0.1$.

Binary hash code learning   Lin *et al* [70]. use deep learning with sigmoid activations to learn binary hash codes for search of clothing images. We intend to learn sharply binary hash codes with centered soft clipping and centered L1 regularization together, for interpretability, pathology search, and set representation learning. We find centered soft clipping performed slightly better for classification (Fig S13A) and provided a small but significant increase in search performance (Fig 9B).

S1.12   Disease state search distance function and performance

Pathology search performance is shown in Figure 9B, and detailed in Table S1. We found a combined distance measure (Eqn 14) worked best for search (i.e. Table S1 top row). The combined distance between two examples (i.e. $\text{Dist}(x_0, x_1)$) is the number of trees in the Random Forest (i.e. 1000), minus the Random Forest similarity of the covariates and non-deep features (i.e. $\text{Sim}_{\text{RF}}(x_0, x_1)$), plus five times (i.e. $\alpha_{SIFT} = 5$) the L1 norm of the 5 largest SIFT cluster medoids vector sum (i.e. $\text{L1}_{\text{SIFT}_{k5}}(x_0, x_1)$), plus the L1 norm of the top three deep features from each example (i.e. $\text{L1}_{\text{Deep}_3}(x_0, x_1)$). For Deep$_3$, we use the top three most class-associated features of example x, one such feature for each of the three classes (nontumor, low grade, or malignant per Fig 5C). We initially found these three features using Random Forest similarity (Fig 4), but subsequently identify these features by minimizing the feature's error with respect to a class label in the training data, for computational expediency.

$$\text{Dist}(x_0, x_1) = 1000 - \text{Sim}_{\text{RF}}(x_0, x_1) + [\alpha_{\text{SIFT}}]\text{L1}_{\text{SIFT}_{k5}}(x_0, x_1) + \text{L1}_{\text{Deep}_3}(x_0, x_1) \tag{14}$$

S1.13   Supplementary Disease state search results

S1.13.1   Clinical covariates improve search performance

We ask if pathology-specific clinical covariates improve search performance. Including the tissue type covariate significantly improves performance compared to not using this covariate (0.5640 ± 0.0024 vs 0.6533 ± 0.0025, $U = 100, p = 0.0001796$). We find including the marker mention covariate significantly improves performance further (0.6533 ± 0.0025 vs 0.6908 ± 0.0021, $U = 100, p = 0.0001796$). Therefore including pathology-specific clinical covariates for pathology search is currently justified, because these improve search performance. We reason that disease states are reported at tissue-type-specific rates, and cases that mention marker tests (e.g. IHC) tend to be more similar to other cases that mention marker tests. Often, marker tests are used to subtype malignancies (e.g. TTF-1), but this is not always the case (e.g. Ki-67). We believe this is the first multimodal classifier that demonstrates improved search performance when combining pathology imaging features with clinical covariates (i.e. tissue type and mention of marker tests) that may be missing for some patients (Fig 9B).

| Method († = plotted in Fig 9B) | prec@k=1 | prec@k=2 | prec@k=3 | prec@k=4 | prec@k=5 |
	prec@k=6	prec@k=7	prec@k=8	prec@k=9	prec@k=10
RandomForest(2412 + tissue + marker) +	**0.7006±0.0026**	0.6493±0.0023	0.6196±0.0017	0.5983±0.0009	0.5826±0.0007
5×SIFT$_{k5}$ + Deep$_3$†	0.5698±0.0007	0.5597±0.0007	0.5511±0.0008	0.5440±0.0007	0.5380±0.0005
RandomForest(2412 + tissue + marker) +	**0.6991±0.0023**	0.6483±0.0022	0.6194±0.0012	0.5984±0.0009	0.5833±0.0008
1×SIFT$_{k5}$ + Deep$_3$	0.5708±0.0007	0.5610±0.0007	0.5519±0.0006	0.5443±0.0008	0.5382±0.0005
RandomForest(2412 + tissue + marker) +	0.6983±0.0016	0.6479±0.0018	0.6187±0.0017	0.5977±0.0012	0.5828±0.0009
Deep$_3$	0.5705±0.0011	0.5604±0.0009	0.5516±0.0006	0.5442±0.0005	0.5381±0.0006
RandomForest(2412 + tissue + marker) +	0.6982±0.0026	0.6491±0.0013	0.6177±0.0013	0.5965±0.0013	0.5811±0.0007
5×SIFT$_{k5}$ + EnsDeep$_3$	0.5687±0.0007	0.5591±0.0011	0.5505±0.0010	0.5432±0.0010	0.5376±0.0011
RandomForest(2412 + tissue + marker) +	0.6974±0.0025	0.6474±0.0016	0.6182±0.0015	0.5970±0.0014	0.5815±0.0007
EnsDeep$_3$	0.5689±0.0009	0.5594±0.0007	0.5510±0.0007	0.5440±0.0008	0.5381±0.0007
RandomForest(2412 + tissue + marker) +	0.6948±0.0032	0.6449±0.0021	0.6154±0.0016	0.5941±0.0016	0.5791±0.0014
5×SIFT$_{k5}$	0.5668±0.0011	0.5569±0.0011	0.5479±0.0008	0.5404±0.0002	0.5344±0.0007
RandomForest(2412 + tissue + marker) +	0.6935±0.0029	0.6439±0.0021	0.6152±0.0012	0.5943±0.0016	0.5793±0.0015
1×SIFT$_{k5}$	0.5669±0.0012	0.5569±0.0012	0.5484±0.0009	0.5412±0.0008	0.5350±0.0008
RandomForest(2412 + tissue + marker +	0.6918±0.0030	0.6436±0.0021	0.6166±0.0020	0.5965±0.0017	0.5819±0.0010
SIFT$_{k5}$) + Deep$_3$	0.5699±0.0010	0.5608±0.0009	0.5518±0.0008	0.5443±0.0008	0.5380±0.0008
RandomForest(2412 + tissue + marker)†	0.6908±0.0021	0.6435±0.0017	0.6148±0.0015	0.5941±0.0013	0.5793±0.0016
	0.5671±0.0014	0.5568±0.0009	0.5482±0.0009	0.5409±0.0012	0.5351±0.0009
RandomForest(2412 + tissue) + Deep$_3$	0.6602±0.0022	0.6129±0.0019	0.5845±0.0014	0.5656±0.0010	0.5530±0.0005
	0.5419±0.0008	0.5333±0.0006	0.5265±0.0010	0.5209±0.0010	0.5156±0.0005
RandomForest(2412 + tissue)†	0.6533±0.0025	0.6064±0.0023	0.5784±0.0013	0.5599±0.0010	0.5481±0.0009
	0.5386±0.0008	0.5297±0.0009	0.5227±0.0008	0.5167±0.0007	0.5119±0.0007
RandomForest(2412 + tissue +	0.6527±0.0024	0.6073±0.0027	0.5803±0.0014	0.5638±0.0018	0.5518±0.0016
SIFT$_{k5}$) + Deep$_3$	0.5412±0.0016	0.5331±0.0012	0.5262±0.0010	0.5202±0.0012	0.5148±0.0010
RandomForest(2412 + tissue + marker) +	0.6376±0.0014	0.5875±0.0016	0.5549±0.0010	0.5351±0.0009	0.5214±0.0009
SIFT	0.5119±0.0005	0.5034±0.0008	0.4961±0.0006	0.4900±0.0004	0.4851±0.0005
RandomForest(2412 + tissue + marker +	0.5728±0.0022	0.5329±0.0023	0.5108±0.0013	0.4969±0.0009	0.4874±0.0010
SIFT)†	0.4803±0.0011	0.4751±0.0008	0.4701±0.0007	0.4654±0.0008	0.4617±0.0007
RandomForest(2412) + Deep$_3$	0.5720±0.0036	0.5363±0.0027	0.5153±0.0021	0.5014±0.0024	0.4915±0.0016
	0.4839±0.0015	0.4774±0.0009	0.4728±0.0010	0.4692±0.0008	0.4658±0.0007
RandomForest(2412 features)†	0.5640±0.0024	0.5283±0.0025	0.5085±0.0018	0.4955±0.0021	0.4854±0.0014
	0.4775±0.0012	0.4717±0.0010	0.4667±0.0010	0.4631±0.0007	0.4600±0.0006
L1(2412 features)†	0.5479±0.0000	0.5124±0.0000	0.4927±0.0000	0.4831±0.0000	0.4746±0.0000
	0.4672±0.0000	0.4626±0.0000	0.4568±0.0000	0.4536±0.0000	0.4510±0.0000
RandomForest(2412 + tissue + Deep)	0.5427±0.0025	0.5135±0.0015	0.5001±0.0015	0.4915±0.0017	0.4860±0.0011
	0.4806±0.0010	0.4756±0.0007	0.4719±0.0007	0.4690±0.0007	0.4671±0.0007
RandomForest(SIFT)†	0.4636±0.0024	0.4489±0.0021	0.4389±0.0016	0.4353±0.0013	0.4326±0.0009
	0.4304±0.0011	0.4282±0.0008	0.4266±0.0008	0.4249±0.0009	0.4235±0.0009
L1(SIFT)†	0.4630±0.0000	0.4495±0.0000	0.4399±0.0000	0.4376±0.0000	0.4324±0.0000
	0.4296±0.0000	0.4268±0.0000	0.4260±0.0000	0.4252±0.0000	0.4242±0.0000
L1(SIFT$_{k5}$)	0.4205±0.0000	0.4127±0.0000	0.4125±0.0000	0.4109±0.0000	0.4107±0.0000
	0.4107±0.0000	0.4102±0.0000	0.4104±0.0000	0.4112±0.0000	0.4105±0.0000
RandomForest(SIFT$_{k5}$)	0.4102±0.0050	0.4097±0.0020	0.4087±0.0017	0.4088±0.0014	0.4089±0.0013
	0.4092±0.0017	0.4090±0.0015	0.4088±0.0015	0.4087±0.0012	0.4088±0.0011
RandomForest(2412 + tissue),	0.3967±0.0044	0.3991±0.0036	0.3999±0.0033	0.3996±0.0030	0.4001±0.0033
permutation test†	0.3999±0.0027	0.4000±0.0029	0.3996±0.0030	0.3997±0.0027	0.3998±0.0026

Table S1. Case similarity search performance in detail. Precision@k for search as shown in Figure 9B, with additional experiments. To estimate 95% confidence intervals, recall standard error of the mean is the sample standard deviation (i.e. stdev) divided by $\sqrt{10}$, since we perform ten replicates. L1(…) indicates distance is the L1 norm of the feature vector. RandomForest(…) indicates distance is the number of trees in the forest (i.e. 1000) minus Random Forest similarity calculated on the feature vector. "2412"/"2412 features" indicates our 2,412 features are used (Fig S9). Tissue and/or marker covariate use are indicated by "tissue" and/or "marker", respectively. "Deep" indicates the full 100-dimensional feature vector is used (Fig 1). "Deep$_3$" indicates only the top 3 class-correlated features are used (Fig 5, see Eqn 14 for combining distances). "EnsDeep$_3$" indicates the top 3 class-correlated features are used, averaged across three neural networks in an ensemble. "SIFT" indicates all SIFT interest points are summed to represent an image. "SIFT$_{k5}$" indicates the 5 largest of 25 medoids are summed to represent an image. "5×SIFT$_{k5}$" indicates the SIFT$_{k5}$ vector is multiplied by five (i.e. $\alpha_{\mathrm{SIFT}} = 5$), which changes L1-based distances (Eqn 14). We find best performance for "RandomForest(2412 + tissue + marker) + 5×SIFT$_{k5}$ + Deep$_3$", which is 1000 minus Random Forest similarity, plus five times L1(SIFT$_{k5}$), plus L1(Deep$_3$).

	median	median 95% CI	mean	stdev	mean 95% CI
prec@k=1	0.7360	0.7007-0.7797	0.7055	0.1211	0.6569-0.7498
prec@k=2	0.6739	0.6155-0.7284	0.6584	0.1089	0.6151-0.7001
prec@k=3	0.6369	0.5983-0.6830	0.6319	0.1043	0.5910-0.6723
prec@k=4	0.6135	0.5577-0.6603	0.6082	0.1028	0.5677-0.6490
prec@k=5	0.5979	0.5357-0.6418	0.5921	0.1027	0.5516-0.6325
prec@k=6	0.5855	0.5177-0.6279	0.5770	0.1010	0.5372-0.6164
prec@k=7	0.5734	0.5033-0.6178	0.5660	0.0990	0.5266-0.6042
prec@k=8	0.5627	0.4924-0.6112	0.5570	0.0946	0.5205-0.5939
prec@k=9	0.5504	0.4834-0.6075	0.5487	0.0922	0.5129-0.5848
prec@k=10	0.5411	0.4774-0.6024	0.5422	0.0916	0.5058-0.5786

Table S2. Case similarity search performance per-pathologist. Precision@k per-pathologist, corresponding to Fig 9C *at right*, for the best performing search method *RandomForest(2412 + tissue + marker) + 5×SIFT$_{k5}$ + Deep$_3$*, c.f. Table S1. Leave-one-pathologist-out cross validation is repeated ten times. Each pathologist's performance is averaged over these ten repetitions. This average performance is plotted in Fig 9C, where the 24 lines correspond to 24 pathologists, and error bars are standard error for these ten replicates. For precision@k=1 mean, each of the 24 pathologists' ten-repetition average precision@k=1 is averaged and reported. In this way, the mean prec@k=1 (i.e. 0.7055) is what precision@k=1 may be expected for a pathologist whose data we have not seen before, when averaged over many images for that pathologist. Bootstrapped confidence intervals (CI) for median and mean are shown for 10,000 replicates. There is not a significant difference between the means and medians, so any differences may be due to chance alone.

S1.13.2 In the context of other features, nuclear features of disease are better represented by the most prevalent SIFT clusters rather than all SIFT

Used alone, all SIFT is better than chance, but does not complement other features We ask if cell nuclei features, as represented by SIFT, may represent disease state, and if so, which SIFT representations perform better than others for pathology search. Inspired by continuous bag-of-words methods that represent a context as a vector sum of words [60] and bag-of-visual-words methods that leverage SIFT [71], our simplest baseline detects all SIFT interest points in an image, then takes the sum of all these SIFT feature vectors to represent an image overall. This way, an image is represented by a 128-dimensional SIFT set representation, where the set cardinality is equal to the number of SIFT interest points in the image, which varies among images. Because SIFT features are non-negative and cover nuclei, the magnitude of this vector may increase as nuclear density increases. This performs better than chance when used alone (0.4636 ± 0.0024 vs 0.3967 ± 0.0044, $U = 100$, $p = 1.083e$-05), but reduces performance when used in the context of our 2,412 hand-engineered features, tissue covariate, and marker covariate (0.6908 ± 0.0021 vs 0.5728 ± 0.0022, $U = 100$, $p = 0.0001796$). We conclude that naïvely using SIFT features this way to estimate nuclear density allows limited discrimination of disease state when used alone, but does not complement other features when used together for pathology search.

SIFT learning challenging, but a combined distance function of L1 norm and Random Forest similarity improves search In light of the aforementioned reduced performance with SIFT, we ask if Random Forest similarity contributes to this performance reduction. We observe the SIFT L1 norm and SIFT Random Forest similarity performance differences may be due to chance alone (0.4630 ± 0.0000 vs 0.4636 ± 0.0024, $U = 40$, $p = 0.4429$). The Random Forest does not appear to learn from this SIFT representation. We additionally observe search performance is reduced less when adding the SIFT L1 norm to Random Forest similarity as a combined distance measure (Eqn 14), rather than training the Random Forest on SIFT features (0.5728 ± 0.0022 vs 0.6376 ± 0.0014, $U = 0, p = 0.0001796$). This may suggest the

Random Forest overfits or cannot learn from these continuous bag-of-words SIFT features, but this may be mitigated by a combined distance function that does not rely on Random Forest learning from SIFT features (Eqn 14).

SIFT clusters provide complimentary information for search We then ask if SIFT may provide complimentary information for search, when using SIFT to estimate nuclear shape and edge distributions, rather than nuclear density. For this approach, we (i) detect all SIFT interest points in an image, (ii) form 25 clusters using k-medoids++ clustering with the L1 norm of the SIFT feature vectors for all interest points, (iii) retain the 5 medoids corresponding to the 5 most abundant clusters, and (iv) take the sum of the medoid SIFT features to represent the image overall. This way, an image is represented by a 128-dimensional SIFT set representation, where the set cardinality is always 5, the number of retained medoids. We call this a $SIFT_{k5}$ set representation, for k=5 medoids from k-medoids++ clustering. Because SIFT features represent shapes and edges, and because we use only the most abundant cluster medoids, this vector may represent the prevailing shapes and edges of nuclei in the image overall. This performs better than chance when used alone (0.4102 ± 0.0050 vs 0.3967 ± 0.0044, $U = 100$, $p = 0.0001817$), and significantly improves performance when used in the context of 2,412 features, tissue covariate, and marker covariate (0.6908 ± 0.0021 vs 0.6935 ± 0.0029, $U = 19.5$, $p = 0.02308$), though the effect is small.

Combined distance function coefficient allows SIFT prioritization, but careful calibration not needed Because SIFT feature vector magnitude is small, and the number of medoids we retain is small (i.e. 5), we ask if search would benefit from a SIFT coefficient greater than one in the combined distance function (i.e. α_{SIFT} in Eqn 14), to increase the relative contribution of SIFT features to search. We let $\alpha_{SIFT} = 5$. When combined with deep features, which we discuss later, we report a very small but significant improvement in search performance when $\alpha_{SIFT} = 5$ (0.6983 ± 0.0016 vs 0.7006 ± 0.0026, $U = 21.5$, $p = 0.03423$) but not when $\alpha_{SIFT} = 1$ (0.6983 ± 0.0016 vs 0.6991 ± 0.0023, $U = 34$, $p = 0.2408$). However, search performance is not significantly different depending on the choice of α_{SIFT} here (0.6991 ± 0.0023 vs 0.7006 ± 0.0026, $U = 30$, $p = 0.14$). Therefore, we do not observe compelling evidence in favor of selecting α_{SIFT} carefully, and caution that careful selection risks overfit. We note $\alpha_{SIFT} = 5$ may be viewed as a micro-optimization, but this effect is very small. It appears this effect is carried by $SIFT_{k5}$ rather than α_{SIFT}, so we conclude it may be better to focus on feature engineering or learning, rather than coefficient selection. We report this to show α selection in the combined distance function has only a slight effect.

S1.13.3   Deep features synergize with other features, informing search more than nuclear SIFT features, but less than clinical covariates

For deep features, a combined distance function of L1 norm and Random Forest similarity also improve search Because search performance improves when considering $SIFT_{k5}$ set features in a combined distance function, we ask if search performance improves when considering deep set features in a combined distance function (Eqn 14). We observe that naïvely concatenating the full 100-dimensional deep set representation with other features for Random Forest learning reduces performance (0.6533 ± 0.0025 vs 0.5427 ± 0.0025, $U = 100$, $p = 0.0001796$). We then select the interpretable top 3 most class-associated deep features (Figs 4, 5D1-3) and observe using these in a combined distance function improves search performance (0.6533 ± 0.0025 vs 0.6602 ± 0.0022, $U = 4$, $p = 0.0005773$). Performance remains improved when including the marker mention covariate (0.6908 ± 0.0021 vs 0.6983 ± 0.0016, $U = 0$, $p = 0.0001817$).

Given that both SIFT set features and deep set features both perform better in a combined distance function rather than within Random Forest similarity, we suspect our Random Forest parameters facilitate sensitive learning from few covariates, but may be oversensitive to a large number of set features that each take many different values. *Machine learning methods discussion* in the supplement discusses further. We conclude an interpretable reduced representation of deep set features improves search performance when considered in a combined distance function, though this effect is small. We expect the effect to increase with more data, because deep learning can refine feature representations in a scalable data-driven manner, and because more advanced deep learning methods may be possible with more data.

Deep features from supervised learning inform search more than nuclear SIFT features   Given that both SIFT_{k5} and Deep_3 features improve search performance, we ask if pathology-specific Deep_3 features improve search performance more than pathology-agnostic SIFT_{k5} features. Indeed, we observe Deep_3 features improve search performance significantly (i) more than SIFT features (0.6983 ± 0.0016 vs 0.6376 ± 0.0014, $U = 100$, $p = 0.0001817$), (ii) more than $1\times\text{SIFT}_{k5}$ features (0.6983 ± 0.0016 vs 0.6935 ± 0.0029, $U = 94$, $p = 0.0003248$), and (iii) more than $5\times\text{SIFT}_{k5}$ features (0.6983 ± 0.0016 vs 0.6948 ± 0.0032, $U = 83.5$, $p = 0.01251$). We conclude learned pathology-specific deep features inform pathology search more than hand-engineered pathology agnostic SIFT features, though SIFT may cover nuclei.

Deep features and SIFT features are complementary   To determine if SIFT and deep features represent non-overlapping concepts in pathology, we ask if combining SIFT_{k5} and Deep_3 features improves performance, compared to using either one, in the context of other features. We observe Deep_3 features significantly improve performance when considering $5\times\text{SIFT}_{k5}$ and all other features (0.6983 ± 0.0016 vs 0.7006 ± 0.0026, $U = 21.5$, $p = 0.03423$). We likewise observe $5\times\text{SIFT}_{k5}$ features significantly improve performance when considering Deep_3 and all other features (0.6948 ± 0.0032 vs 0.7006 ± 0.0026, $U = 7$, $p = 0.0004871$). These small effects suggest SIFT_{k5} and Deep_3 features represent complementary, rather than redundant, pathology features for search.

Deep features improve search performance less than tissue and marker clinical covariates   Interested in the relative importance of deep features and clinical covariates, we then ask if Deep_3 features or the tissue type covariate are more important for search. In the context of our 2,412 hand-engineered features, we find Deep_3 features improve search performance less than the tissue type covariate (0.5720 ± 0.0036 vs 0.6533 ± 0.0025, $U = 0$, $p = 0.0001806$). We additionally ask if Deep_3 features or the marker mention covariate are more important for search. In the context of our 2,412 features and tissue type covariate, we find Deep_3 features improve search performance less than the marker mention covariate (0.6602 ± 0.0022 vs 0.6908 ± 0.0021, $U = 0$, $p = 0.0001817$). We conclude that for our dataset's size and diversity, search benefits most from carefully identifying and integrating simple clinical covariates for context, rather than focusing on advanced image analysis techniques such as deep learning.

S1.14   Supplementary Experimental design and evaluation

We evaluate our classifiers using 10-fold cross validation, which is the default evaluation scheme in Weka [31]. Our data are saved in ARFF file format, so our findings can be reproduced in Weka without the need for writing software code. This approach allows software code we write to be compared against the unperturbed gold standard of Weka defaults. We follow Weka's default of ten replicates of 10-fold cross validation, to

estimate bounds of accuracy and Area Under Receiver Operating Characteristic   1362
(AUROC) performance metrics. This approach will give reproducible results wherever   1363
Java and Weka run, e.g. a laptop, a server, a supercomputer, or a cloud computer. This   1364
approach will work on all operating systems that support Java, e.g. Linux, Mac, and   1365
Windows.   1366

S1.15   Supplementary Computational hardware and software   1367

We use Weka version 3.8.1 [31] on a ASUS Intel core i7-6700HQ 2.6GHz 4-CPU laptop   1368
with 16GB RAM for baseline analyses and Random Forests This laptop was also used   1369
for software development and automatically downloading Twitter data from   1370
participating pathologists. This laptop ran the Windows 10 operating system, which in   1371
turn ran the Oracle VirtualBox virtual machine manager, which in turn ran Debian   1372
Jessie 3.16.7-ckt20-1+deb8u3 and Linux kernel 3.16.0-4-amd64. Weka and our other   1373
pipeline components ran within Debian.   1374

For deep learning, we use Keras version 2.1.4 and TensorFlow version 1.10.0 on an   1375
MSKCC supercomputer with several Nvidia Titan-X GPUs and dozens of Nvidia GTX   1376
1080 GPUs running CUDA 8 and cuDNN 5.   1377

S1.16   Supplementary Comparison with prior studies   1378

S1.16.1   Pathology-agnostic neural nets, SIFT nuclear features, and   1379
texture features   1380

Many other groups perform pathology search with deep neural networks or   1381
hand-engineered features. Komura *et al* [17]. and Hegde *et al* [18]. use a deep neural   1382
network for pathology image search, taking a pathology-agnostic approach by not   1383
performing machine learning on histopathology images. Hegde *et al.* go further by   1384
comparing search performance of their neural network method, called SMILY, to a   1385
simpler baseline method using Scale-invariant feature transform (SIFT) [40]. Zhang *et*   1386
al. suggest SIFT interest points tend to cover cell nuclei [72]. However, Lowe, the author   1387
of SIFT, notes SIFT features do not represent color or texture, "features [. . .] use only   1388
a monochrome intensity image [and] texture measures [. . .] could be incorporated" [40].   1389
For pathology search this may handicap SIFT compared to a neural network that can   1390
represent color or texture. Indeed, when we train our neural-network-random-forest   1391
hybrid classifier (Fig 3) on pathology images, we find features that represent texture   1392
(Local Binary Patterns Pyramid [55], Local Binary Patterns [54]) and color (Color   1393
Histogram [50], Color Correlogram [52], etc [51,53]) are the most important non-deep   1394
visual features (Fig 4). For decades, texture and color have been known to be important   1395
in pathology [41], and this motivates reproducible procedures for staining and slide   1396
preparation. Recently, Linder *et al* [42]. report Local Binary Patterns are important   1397
texture features to distinguish epithelium from stroma in colorectal cancer. Kather *et*   1398
al [43] go further, using Local Binary Patterns and other texture features to distinguish   1399
stroma, epithelium, immune cells, normal tissue, etc in colorectal cancer. Linder posit   1400
Local Binary Patterns are robust to changes in staining, illumination, and camera   1401
settings – useful properties for building a robust classifier from a globally distributed   1402
dataset like ours. Though we find using SIFT features alone for search performs better   1403
than chance, we find search performance is best when machine learning is used and   1404
SIFT features are not (Fig 9). This suggests that the visual signatures of disease state   1405
in pathology involve more than covering cell nuclei, and some of these signatures may   1406
be uncovered by a Random Forest [48] as nonlinear relationships of texture and color.   1407
For pathology search, we use Random Forest similarity derived from our interpretable   1408
classifier trained on pathology images, rather than require explicit similarity   1409

annotations from pathologists as training data [73]. We find pathology-specific   1410
covariates improve our classifier and search performance (Figs 9B, 8). A variety of   1411
search approaches for pathology search, also known as Content-based image retrieval   1412
(CBIR), have been reported [74,75], including SIFT [38], SIFT with neural   1413
networks [39], and dimensionality reduction [76].   1414

S1.16.2   Pathology-specific neural networks   1415

Otàlora et al [19]. take a transfer learning [11–14] approach to pathology search by   1416
adding an auxilary layer on top of a frozen pretrained deep neural network. They train   1417
this auxilary layer to predict if a prostate image shows Gleason [77] grade of 4 or more,   1418
or not. They do not report classification performance. The auxiliary layer feature vector   1419
is used for prostate image search, and the search is shown to perform better than a   1420
simple baseline, i.e. Color and Edge Directivity Descriptor (CEDD) [51]. We also use   1421
CEDD in our work and find it important (Fig 4). However, our classifier training is   1422
pan-tissue and pan-disease, neither specifically prostate nor specifically high Gleason.   1423
Like Otàlora, we search PubMed (Fig 1). However, to filter PubMed for histopathology   1424
images, Otàlora use a light microscopy detection algorithm [78] while we use a Random   1425
Forest trained for H&E detection with leave-one-pathologist-out AUROC of 0.95+   1426
(Fig 6). In prior work, we trained a deep neural network end-to-end to predict SPOP   1427
mutation in prostate and repurposed the classifier for search [15]. Peng et al [79].   1428
jointly train a deep neural network for prediction and search, using colorectal   1429
histopathology images labeled with nine possible classes, i.e. adipose tissue, background,   1430
cellular debris, lymphocytes, extra-cellular mucus, smooth muscle, normal colon mucosa,   1431
cancer-associated stroma, and colorectal cancer epithelium. However Peng do not report   1432
search performance as mean average precision or precision@k for k=1,2,3,...,10   1433
(Fig 9B), so Peng's results may be difficult for others to interpret. Instead, Peng report   1434
how many images had "perfect retrieval precision of 10 true neighbours", and find their   1435
method performs 30% higher than their baseline. Peng cite Cao [80] and Cao [81] for   1436
reporting this way, but both report mean average precision, so Peng search results   1437
between data sources are not clear to us.   1438

S1.16.3   Computational pathology studies not pan-tissue pan-disease   1439

For dermatopathology, Esteva et al [35]. predict if an image shows disease that is   1440
benign, malignant, or either benign/malignant – but do not consider nontumoral disease   1441
such as infections. For a few tissues including prostate, Campanella et al [37]. predict if 1442
an image shows cancer or not, but similarly do not differentiate non-neoplastic from   1443
benign disease, which may be an important clinical consideration [21]. Neither perform   1444
search. From optimal coherence tomography (OCT) imaging of eye pathology, De Fauw   1445
et al [36] predict referral urgency as urgent, semi-urgent, routine, or observation. This is 1446
not a prediction of disease state. De Fauw do not mention cancer, but instead focus on   1447
diseases we consider to be nontumor, such as diabetes and macular degeneration. We   1448
are not aware of any pan-tissue pan-disease datasets other than ours. We believe our   1449
pan-disease method serves patients with diseases of poverty (e.g. many forms of   1450
infection, $\tilde{}\frac{1}{5}$ of diseases in our data) as well as patients with diseases of affluence (e.g.   1451
many forms of cancer, $\tilde{}\frac{2}{5}$ of diseases in our data).   1452

S1.16.4   Deep and shallow learning not on same task   1453

In the field of cardiology, deep learning has been trained on a separate task (i.e.   1454
epicardial adipose tissue volume), then used by shallow learning (i.e. XGBoost) to   1455
predict myocardial infarction [82]. Our approach differs in that we train both deep and   1456

shallow learning (i.e. a Random Forest) on the same task, namely disease state   1457
prediction (Fig 3B,C). In principle, our approach allows deep learning to, in a   1458
data-driven manner, derive features that are important for disease state prediction,   1459
which may complement the hand-engineered features and clinical covariates we use for   1460
shallow learning. Indeed, we find there are such important and complementary deep   1461
features for shallow learning of disease state prediction (Fig 4) and search (Fig 9).   1462

S1.17   Supplementary Caveats   1463

S1.17.1   Patient case across multiple tweets   1464

A feature of these data is that a particular patient might be represented in more than   1465
one image. Any given patient might be discussed in multiple tweets, each of which   1466
contain one or more images. A patient case may be spread across multiple Twitter   1467
threads as well, e.g. the first tweets asks pathologists for their opinions as a quiz, while   1468
a second tweets in a new thread provides the correct diagnosis. We believe   1469
leave-one-pathologist-out cross validation is a reliable way to prevent the same patient's   1470
data from being in both a training and a test set for machine learning evaluation.   1471
However, in the future, we may find a patient is shared by multiple pathologists, e.g.   1472
when a pathologist donates his/her slides to another pathologist. Currently, we have not   1473
observed the same patient case being shared by multiple pathologists.   1474

S1.17.2   Near-duplicate detection   1475

There is room for improvement in automated duplicate detection methods. A   1476
pathologist may first tweets an image that has no hand-drawn marks, but later reply   1477
with an image that includes hand-drawn marks such as circles and arrows to indicate a   1478
region of interest. Pathologists may also re-share the cases of other pathologists, with   1479
minor modifications, such as white balancing. In future work, these near-duplicates   1480
should be automatically detected. Duplicates may artificially inflate performance   1481
metrics.   1482

S1.17.3   Disease state annotations vary in text   1483

Our dataset is only as good as the accuracy of the hashtags and diagnoses made by the   1484
collaborating pathologists and pathologists who comment on the cases. The more   1485
pathologists that contribute to the database, the higher the risk for errors and   1486
inconsistencies. Indeed we note some uses of the #bstpath hashtag to describe breast   1487
pathology (Section S1.6.1). We should remember the fun and voluntary nature of   1488
sharing cases on social media.   1489
    While our disease state text processing algorithms take a consensus vote among the   1490
pathologists discussing the patient case, these methods are not perfect, and our manual   1491
annotations to correct this may be incomplete. We hope that by sharing our data with   1492
the community, more corrections may be made, improving the quality of our dataset.   1493

S1.17.4   Disease state evidence varies in images   1494

For our Random Forest baselines, we crop images to convert rectangular images to be   1495
uniformly square for the machine learning. However, pathologists may include   1496
diagnostic information only at the extreme edges of an image that are cropped out. A   1497
case of this from B.X. involves a hydatid cyst in the extreme right of an image, which   1498
would be cropped out[9]. This hydatid cyst indicates *Echinococcus* infection, so the case   1499

---

[9]Case at `https://twitter.com/BinXu16/status/980404471833313280` "Kudo to @drkennethtang
@luishcruzc and @DrGeeONE The answer of this case can be seen in the right corner of the 3rd picture.

is nontumoral. Our set-based deep learning approach is an incomplete remedy to this problem, where we train on 224×224px image patches sampled throughout the original image, then test using 21 224×224px patches systematically sampled throughout the original image. Although this approach samples the entire image, the remedy is incomplete in that the ground truth is not uniform throughout the image. For example, it is only based on one corner of the image that there is histological evidence of nontumor disease. It may be helpful here to use more advanced methods, which make fewer assumptions about the ground truth and allow weaker supervision, but such methods may come at a cost of requiring more data than we have currently.

S1.17.5   Algorithm and labeling inaccuracies

We do not expect that our text classification algorithm (Fig S8) perfectly interprets disease state from the text associated with an image. Moreover, we also do not expect our manual annotation process to be perfect, e.g. some stains may be incorrectly labeled as H&E, IHC, etc. We manually curate 10,000+ images, so human error as low as 1% means a handful of images are incorrectly labeled, but there could be more. By sharing our data with more pathologists and data scientists, we intend to gather feedback and correct any inaccuracies here, then measure disease state classification performance changes.

S1.17.6   No automated quality control

Finally, the size of the dataset is both a blessing and a curse. A large and diverse dataset is required to provide the most benefit to computational pathology. However, quality control for such large datasets is most feasible if done automatically, and automated quality control cannot deal with all issues. For example, some pathology images include marks designating a particular pathologist as the contributor of that image. Other pathology images have been marked by pathologists with arrows and circles. Our automated quality control pipeline enables us to rapidly discriminate pathology from non-pathology images, but is not able to address these other challenges. Future steps will need to be taken for more specialized quality control.

S1.18   Supplementary Future directions

S1.18.1   Acquiring more data

The first step is to expand the size of this dataset by recruiting more pathologists via social media. With more data, we hope to improve performance on discriminations that were the most difficult (e.g. those involving gynecological pathology). More data may facilitate machine learning methods that discriminate between similar but less frequently used stains, such as H&E vs Diff-quik, rather than H&E vs IHC. More data might also enable us to distinguish particular organs or tissues within a histopathology tissue type, e.g. distinguish kidney tissue from bladder tissue. With increased sample size and increased tissue of origin granularity, it may be possible to predict metastatic tissue of origin. Finally, a larger dataset might also include more rare cases that can be useful for machine learning techniques that can support diagnoses.

S1.18.2   Expanded and specific hashtags

A second step is advocacy on social media, for (i) sharing normal tissue data, and (ii) expanded pathology hashtags. Normal tissue complements our existing "relatively

---

Dx: Echinococcus (hydatid cyst) with necrotizing pneumonia, abscess, and granulomatous inflammation. Additional high power pictures attached."

unimportant" artifact and foreign body data, such as colloids and gauze, which are   ₁₅₄₃ typically not prognostic of disease. Normal tissue also complements the description of   ₁₅₄₄ tissue morphology in our data, if we tend to have only cancerous or diseased tissue.   ₁₅₄₅ Separately, more descriptive hashtags may reduce our manual annotation burden, and   ₁₅₄₆ obviate the need for us to ask pathologists to clarify what stain was used or what the   ₁₅₄₇ tissue is. Moreover, molecular hashtags may complement the histology we see. However,   ₁₅₄₈ we understand that for pathologists sharing cases on social media is probably a fun and   ₁₅₄₉ voluntary activity, rather than a rigorous academic endeavor, so it may not be   ₁₅₅₀ appropriate for us to suggest pathologists use terms from synoptic reporting in hashtag   ₁₅₅₁ format in their Tweets. Moreover, the size of tweets is limited to 280 characters, so   ₁₅₅₂ more than 3-4 hashtags per tweets is probably infeasible. Some pathologists are already   ₁₅₅₃ close to this limit without using additional hashtags.   ₁₅₅₄

We encourage the adoption of hashtags that explicitly identify what stains or   ₁₅₅₅ techniques are used (this is not an exhaustive list):   ₁₅₅₆

1. #he indicates there are one or more H&E-stained images in the tweets.   ₁₅₅₇

2. #ihc indicates there are one or more IHC-stained images in the tweets.   ₁₅₅₈

3. #pas indicates there are one or more periodic acid-Schiff images in the tweets.   ₁₅₅₉

4. #diffq indicates there are one or more diff-quik images in the tweets. There is a   ₁₅₆₀ common misspelling of diff-quick, so our hashtag avoids this misspelling.   ₁₅₆₁

5. #gross indicates one or more gross section images are in the tweets. This is   ₁₅₆₂ typically fresh cut tissue, e.g. an entire excised tumor or a large piece of an organ.   ₁₅₆₃

6. #macro indicates an unmagnified picture of a microscopy slide. Unfortunately,   ₁₅₆₄ such pictures are occasionally referred to as gross.   ₁₅₆₅

7. #endo indicates one or more endoscopy images are in the tweets.   ₁₅₆₆

8. #ct indicates one or more CT scan images are in the tweets.   ₁₅₆₇

9. #xray indicates one or more X-ray images are in the tweets.   ₁₅₆₈

We encourage hashtags to describe not only the histological features of a case, but   ₁₅₆₉ also the molecular features of a case. Again, this hashtag list is far from exhaustive.   ₁₅₇₀

1. #braf indicates the BRAF gene is known to be mutated, perhaps through   ₁₅₇₁ sequencing.   ₁₅₇₂

2. #msi indicates micro-satellite instability, which again may be evident from   ₁₅₇₃ sequencing.   ₁₅₇₄

3. #desmin indicates that the IHC used targets desmin.   ₁₅₇₅

We encourage the adoption of hashtags that explicitly identify any artifacts, art, or   ₁₅₇₆ pathologist annotations/marks on the image.   ₁₅₇₇

1. #artifact or #artefact indicates there are artifacts or foreign bodies in one or   ₁₅₇₈ more images, such as colloids, barium, sutures, Spongostan^{TM}, gauze, etc. We   ₁₅₇₉ encourage the tweets message text to identify what the artifact or foreign body is.   ₁₅₈₀

2. #pathart is a hashtag in use today, but unfortunately it is used in two ways: (i)   ₁₅₈₁ to identify naturally-occurring and unmodified pathology images that are "pretty"   ₁₅₈₂ or "interesting" as natural works of art, and (ii) to identify images that have been   ₁₅₈₃ modified by the pathologist herself/himself to be "funny" or "interesting". The   ₁₅₈₄ trouble is (i) is "acceptable" pathology for analysis while (ii) is not. We advocate   ₁₅₈₅ for the continued use of the #pathart hashtag, but with clarification, below: ₁₅₈₆

3. #drawn or #annotated indicates the pathologist made hand-drawn marks on one   ₁₅₈₇ or more images, such as arrows, circles, or artistic manipulations. Artistic   ₁₅₈₈

manipulations may include drawing exclamation points, question marks, eyes, mouths, faces, skulls, cartoon bodies, etc on the image. So, "#pathart #drawn" is likely a pathology image with artistic drawn marks that prevents the image from being an "acceptable" pathology image for analysis, while "#pathart" without "#drawn" is likely a pathology image that is a naturally occurring unmodified histology image that is an "acceptable" pathology image for analysis.

4. Alternatively, "#pathfun" or "#pathdrawing" may refer artistically manipulated pathology pictures, leaving "#pathart" exclusively for naturally-occurring pathology that are "pretty" or "interesting" from an artistic perspective.

We encourage the adoption of hashtags that give other information about the image.

1. #pathbug is an existing hashtag that indicates a parasite or other co-occurring non-human organism is depicted in one or more images in the tweets. The #parasite tag is sometimes used instead.

2. #panel indicates one or more multi-panel images are in the tweets.

We encourage all adopted pathology-related hashtags to be registered in an ontology, e.g. `https://www.symplur.com/healthcare-hashtags/ontology/pathology/`. A hashtag ontology can standardize the hashtags used, which in turn can (i) help pathologists in the same subspecialty find each other, and (ii) simplify computational analyses of hashtag text.

References

1. Nix J, Gardner J, Costa F, Soares A, Rodriguez F, Moore B, et al. Neuropathology Education Using Social Media. Journal of neuropathology and experimental neurology. 2018;77(6):454–460.

2. Crane G, Gardner J. Pathology Image-Sharing on Social Media: Recommendations for Protecting Privacy While Motivating Education. AMA journal of ethics. 2016;18(8):817–825.

3. Dirilenoglu F, Önal B. A welcoming guide to social media for cytopathologists: Tips, tricks, and the best practices of social cytopathology. CytoJournal. 2019;16:4–4. doi:10.4103/cytojournal.cytojournal_1_18.

4. Gardner J, Allen T. Keep Calm and Tweet On: Legal and Ethical Considerations for Pathologists Using Social Media. Archives of pathology & laboratory medicine. 2018;.

5. Lepe M, Wu R, Oltulu P, Alex D, Canepa M, Deeken A, et al. #EBUSTwitter: Novel Use of Social Media for Conception, Coordination and Completion of an International, Multi-Center Pathology Study. Journal of the American Society of Cytopathology. 2018;7(5):S88–S89. doi:10.1016/j.jasc.2018.06.015.

6. Liu Y, Chen PHC, Krause J, Peng L. How to Read Articles That Use Machine Learning: Users' Guides to the Medical Literature. JAMA. 2019;322(18):1806–1816. doi:10.1001/jama.2019.16489.

7. Montalto MC. An industry perspective: An update on the adoption of whole slide imaging. Journal of Pathology Informatics. 2016;7. doi:10.4103/2153-3539.180014.

8. Zarella MD, Bowman; D, Aeffner F, Farahani N, Xthona; A, Absar SF, et al. A Practical Guide to Whole Slide Imaging: A White Paper From the Digital Pathology Association. Archives of Pathology & Laboratory Medicine. 2018;143(2):222–234. doi:10.5858/arpa.2018-0343-RA.

9. Deng J, Dong W, Socher R, Li LJ, Li K, Fei-Fei L. ImageNet: A large-scale hierarchical image database. IEEE; 2009. p. 248–255. Available from: http://dx.doi.org/10.1109/cvpr.2009.5206848.

10. Krizhevsky A. Learning Multiple Layers of Features from Tiny Images; 2009. Available from: https://www.cs.toronto.edu/~kriz/learning-features-2009-TR.pdf.

11. Litjens G, Kooi T, Bejnordi B, Setio A, Ciompi F, Ghafoorian M, et al. A survey on deep learning in medical image analysis. Medical Image Analysis. 2017;42:60–88. doi:10.1016/j.media.2017.07.005.

12. Christiansen E, Yang S, Ando M, Javaherian A, Skibinski G, Lipnick S, et al. In Silico Labeling: Predicting Fluorescent Labels in Unlabeled Images. Cell. 2018;173(3).

13. Bayramoglu N, Heikkila J. Transfer Learning for Cell Nuclei Classification in Histopathology Images. Springer International Publishing; 2016. p. 532–539. Available from: http://dx.doi.org/10.1007/978-3-319-49409-8_46.

14. Tajbakhsh N, Shin J, Gurudu S, Hurst T, Kendall C, Gotway M, et al. Convolutional Neural Networks for Medical Image Analysis: Full Training or Fine Tuning? IEEE transactions on medical imaging. 2016;35(5):1299–1312.

15. Schaumberg A, Rubin M, Fuchs T. H&E-stained Whole Slide Deep Learning Predicts SPOP Mutation State in Prostate Cancer. bioRxiv. 2016; p. 064279. doi:10.1101/064279.

16. Fuchs T, Buhmann J. Computational pathology: challenges and promises for tissue analysis. Computerized medical imaging and graphics : the official journal of the Computerized Medical Imaging Society. 2011;35(7-8):515–530. doi:10.1016/j.compmedimag.2011.02.006.

17. Komura D, Fukuta K, Tominaga K, Kawabe A, Koda H, Suzuki R, et al. Luigi: Large-scale histopathological image retrieval system using deep texture representations. bioRxiv. 2018; p. 345785. doi:10.1101/345785.

18. Hegde N, Hipp JD, Liu Y, Emmert-Buck M, Reif E, Smilkov D, et al. Similar image search for histopathology: SMILY. npj Digital Medicine. 2019;2(1):1–9. doi:10.1038/s41746-019-0131-z.

19. Otalora S, Schaer R, Atzori M, Jimenez del Toro O, Muller H. Deep learning based retrieval system for gigapixel histopathology cases and open access literature. bioRxiv. 2018;doi:10.1101/408237.

20. Veta M, Heng Y, Stathonikos N, Bejnordi B, Beca F, Wollmann T, et al. Predicting breast tumor proliferation from whole-slide images: the TUPAC16 challenge. 2018;.

21. Jang SJ, Gardner JM, Ro JY. Diagnostic approach and prognostic factors of cancers. Advances in Anatomic Pathology. 2011;18(2):165–172. doi:10.1097/PAP.0b013e31820cb39e.

22. Schaumberg A, Sirintrapun S, Al-Ahmadie H, Schueffler P, Fuchs T. DeepScope: Nonintrusive Whole Slide Saliency Annotation and Prediction from Pathologists at the Microscope. bioRxiv. 2016; p. 097246. doi:10.1101/097246.

23. Rajkomar A, Dean J, Kohane I. Machine Learning in Medicine. New England Journal of Medicine. 2019;380(14):1347–1358. doi:10.1056/NEJMra1814259.

24. Begoli E, Bhattacharya T, Kusnezov D. The need for uncertainty quantification in machine-assisted medical decision making. Nature Machine Intelligence. 2019;1(1):20–23. doi:10.1038/s42256-018-0004-1.

25. Marshall A, Davies A. Uber's Self-Driving Car Didn't Know Pedestrians Could Jaywalk. Wired. 2019;.

26. Vlasic B, Boudette NE. Self-Driving Tesla Was Involved in Fatal Crash, U.S. Says. The New York Times. 2016;.

27. He K, Zhang X, Ren S, Sun J. Deep Residual Learning for Image Recognition. 2015;.

28. Zhang H, Cisse M, Dauphin YN, Lopez-Paz D. mixup: Beyond Empirical Risk Minimization. arXiv:171009412 [cs, stat]. 2018;.

29. Cabitza F, Rasoini R, Gensini GF. Unintended Consequences of Machine Learning in Medicine. JAMA. 2017;318(6):517–518. doi:10.1001/jama.2017.7797.

30. Caruana R, Lou Y, Gehrke J, Koch P, Sturm M, Elhadad N. Intelligible Models for HealthCare: Predicting Pneumonia Risk and Hospital 30-day Readmission. In: Proceedings of the 21th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining. KDD '15. New York, NY, USA: ACM; 2015. p. 1721–1730. Available from: `http://doi.acm.org/10.1145/2783258.2788613`.

31. Hall M, Frank E, Holmes G, Pfahringer B, Reutemann P, Witten I. The WEKA Data Mining Software: An Update. SIGKDD Explor Newsl. 2009;11(1):10–18. doi:10.1145/1656274.1656278.

32. Chollet F, others. Keras; 2015. Available from: `https://github.com/keras-team/keras`.

33. Liaw A, Wiener M. Classification and Regression by randomForest. R News. 2002;2(3):18–22.

34. Doshi-Velez F, Perlis RH. Evaluating Machine Learning Articles. JAMA. 2019;322(18):1777–1779. doi:10.1001/jama.2019.17304.

35. Esteva A, Kuprel B, Novoa R, Ko J, Swetter S, Blau H, et al. Dermatologist-level classification of skin cancer with deep neural networks. Nature. 2017;542(7639):115–118. doi:10.1038/nature21056.

36. De Fauw J, Ledsam J, Romera-Paredes B, Nikolov S, Tomasev N, Blackwell S, et al. Clinically applicable deep learning for diagnosis and referral in retinal disease. Nature Medicine. 2018;doi:10.1038/s41591-018-0107-6.

37. Campanella G, Hanna MG, Geneslaw L, Miraflor A, Werneck Krauss Silva V, Busam KJ, et al. Clinical-grade computational pathology using weakly supervised deep learning on whole slide images. Nature Medicine. 2019;25(8):1301–1309. doi:10.1038/s41591-019-0508-1.

38. Mehta N, Alomari RS, Chaudhary V. Content based sub-image retrieval system for high resolution pathology images using salient interest points. Conference proceedings: Annual International Conference of the IEEE Engineering in Medicine and Biology Society IEEE Engineering in Medicine and Biology Society Annual Conference. 2009;2009:3719–3722. doi:10.1109/IEMBS.2009.5334811.

39. Zheng Y, Jiang Z, Zhang H, Xie F, Ma Y, Shi H, et al. Histopathological Whole Slide Image Analysis Using Context-Based CBIR. IEEE Transactions on Medical Imaging. 2018;37(7):1641–1652. doi:10.1109/TMI.2018.2796130.

40. Lowe D. Distinctive Image Features from Scale-Invariant Keypoints. International Journal of Computer Vision. 2004;60(2):91–110. doi:10.1023/b%253avisi.0000029664.99615.94.

41. Nazeran H, Rice F, Moran W, Skinner J. Biomedical image processing in pathology: a review. Australasian Physical & Engineering Sciences in Medicine. 1995;18(1):26–38.

42. Linder N, Konsti J, Turkki R, Rahtu E, Lundin M, Nordling S, et al. Identification of tumor epithelium and stroma in tissue microarrays using texture analysis. Diagnostic Pathology. 2012;7(1):22. doi:10.1186/1746-1596-7-22.

43. Kather JN, Weis CA, Bianconi F, Melchers SM, Schad LR, Gaiser T, et al. Multi-class texture analysis in colorectal cancer histology. Scientific Reports. 2016;6:27988. doi:10.1038/srep27988.

44. Tefik T, Sanli O, Oktar T, Yucel OB, Ozluk Y, Kilicaslan I. Oxidized regenerated cellulose granuloma mimicking recurrent mass lesion after laparoscopic nephron sparing surgery. International journal of surgery case reports. 2012;3(6):227–230.

45. Krizhevsky A, Sutskever I, Hinton G. Imagenet classification with deep convolutional neural networks; 2012.Available from: http://papers.nips.cc/paper/4824-imagenet-classification-with-deep-convolutional-neural-networks.

46. Jia Y, Shelhamer E, Donahue J, Karayev S, Long J, Girshick R, et al. Caffe: Convolutional Architecture for Fast Feature Embedding. 2014;.

47. Szegedy C, Liu W, Jia Y, Sermanet P, Reed S, Anguelov D, et al. Going Deeper with Convolutions. 2014;.

48. Breiman L. Random Forests. Machine Learning. 2001;45(1):5–32. doi:10.1023/a%253a1010933404324.

49. Oltulu P, Mannan AASR, Gardner J. Effective use of Twitter and Facebook in pathology practice. Human pathology. 2018;73:128–143.

50. Lux M, Chatzichristofis S. Lire: Lucene Image Retrieval: An Extensible Java CBIR Library. ACM; 2008. p. 1085–1088. Available from: http://dx.doi.org/10.1145/1459359.1459577.

51. Chatzichristofis S, Boutalis Y. CEDD: Color and Edge Directivity Descriptor: A Compact Descriptor for Image Indexing and Retrieval. In: Gasteratos A, Vincze M, Tsotsos J, editors. Computer Vision Systems. vol. 5008. Springer Berlin Heidelberg; 2008. p. 312–322. Available from: http://dx.doi.org/10.1007/978-3-540-79547-6_30.

52. Huang J, Kumar S, Mitra M, Zhu WJ, Zabih R. Image indexing using color correlograms. In: Computer Vision and Pattern Recognition, IEEE Computer Society Conference on. vol. 0. IEEE; 1997. p. 762–768. Available from: http://dx.doi.org/10.1109/cvpr.1997.609412.

53. Chatzichristofis S, Boutalis Y. FCTH: Fuzzy Color and Texture Histogram - A Low Level Feature for Accurate Image Retrieval. In: Image Analysis for Multimedia Interactive Services, 2008. WIAMIS '08. Ninth International Workshop on. IEEE; 2008. p. 191–196. Available from: http://dx.doi.org/10.1109/wiamis.2008.24.

54. Ojala T, Pietikainen M, Harwood D. Performance evaluation of texture measures with classification based on Kullback discrimination of distributions. In: Proceedings of 12th International Conference on Pattern Recognition. vol. 1; 1994. p. 582–585 vol.1. Available from: http://dx.doi.org/10.1109/ICPR.1994.576366.

55. Ahonen T, Hadid A, Pietikainen M. Face Description with Local Binary Patterns: Application to Face Recognition. IEEE Transactions on Pattern Analysis and Machine Intelligence. 2006;28(12):2037–2041. doi:10.1109/TPAMI.2006.244.

56. Bosch A, Zisserman A, Munoz X. Representing Shape with a Spatial Pyramid Kernel. In: Proceedings of the 6th ACM International Conference on Image and Video Retrieval. CIVR '07. New York, NY, USA: Association for Computing Machinery; 2007. p. 401–408. Available from: https://doi.org/10.1145/1282280.1282340.

57. Ojala T, Pietikainen M, Maenpaa T. Multiresolution gray-scale and rotation invariant texture classification with local binary patterns. IEEE Transactions on Pattern Analysis and Machine Intelligence. 2002;24(7):971–987. doi:10.1109/TPAMI.2002.1017623.

58. Tamura H, Mori S, Yamawaki T. Textural Features Corresponding to Visual Perception. IEEE Transactions on Systems, Man, and Cybernetics. 1978;8(6):460–473. doi:10.1109/TSMC.1978.4309999.

59. Zaheer M, Kottur S, Ravanbakhsh S, Poczos B, Salakhutdinov RR, Smola AJ. Deep Sets. In: Guyon I, Luxburg UV, Bengio S, Wallach H, Fergus R, Vishwanathan S, et al., editors. Advances in Neural Information Processing Systems 30. Curran Associates, Inc.; 2017. p. 3391–3401. Available from: http://papers.nips.cc/paper/6931-deep-sets.pdf.

60. Mikolov T, Chen K, Corrado G, Dean J. Efficient Estimation of Word Representations in Vector Space. arXiv:13013781 [cs]. 2013;.

61. Bai S. Growing random forest on deep convolutional neural networks for scene categorization. Expert Systems with Applications. 2017;71:279–287. doi:10.1016/j.eswa.2016.10.038.

62. Sutskever I, Martens J, Dahl G. On the importance of initialization and momentum in deep learning. 2013; p. 9.

63. Nesterov Y. A method of solving a convex programming problem with convergence rate O(1/sqr(k)). In: Soviet Mathematics Doklady. vol. 27; 1983. p. 372–376.

64. Nesterov Y. Introductory Lectures on Convex Optimization: A Basic Course. Applied Optimization. Springer US; 2004. Available from: https://www.springer.com/gp/book/9781402075537.

65. Kim H, Loh WY. Classification Trees With Unbiased Multiway Splits. Journal of the American Statistical Association. 2001;96(454):589–604. doi:10.1198/016214501753168271.

66. Breiman L, Friedman J, Olshen RA, Stone CJ. Classification and regression trees. New York: Chapman and Hall; 1984.

67. Klimek MD, Perelstein M. Neural Network-Based Approach to Phase Space Integration. arXiv:181011509 [hep-ex, physics:hep-ph, physics:physics, stat]. 2018;.

68. Hochreiter S, Schmidhuber J. Long Short-Term Memory. Neural Computation. 1997;9(8):1735–1780. doi:10.1162/neco.1997.9.8.1735.

69. Hochreiter S, Bengio Y, Frasconi P, Schmidhuber J. Gradient flow in recurrent nets: the difficulty of learning long-term dependencies. IEEE Press; 2001.

70. Lin K, Yang HF, Hsiao JH, Chen CS. Deep learning of binary hash codes for fast image retrieval. IEEE; 2015. p. 27–35. Available from: http://dx.doi.org/10.1109/cvprw.2015.7301269.

71. Sivic J, Zisserman A. Efficient Visual Search of Videos Cast as Text Retrieval. IEEE Transactions on Pattern Analysis and Machine Intelligence. 2009;31(4):591–606. doi:10.1109/TPAMI.2008.111.

72. Zhang X, Liu W, Dundar M, Badve S, Zhang S. Towards Large-Scale Histopathological Image Analysis: Hashing-Based Image Retrieval. IEEE Transactions on Medical Imaging. 2015;34(2):496–506. doi:10.1109/TMI.2014.2361481.

73. Qi X, Wang D, Rodero I, Diaz-Montes J, Gensure R, Xing F, et al. Content-based histopathology image retrieval using CometCloud. BMC Bioinformatics. 2014;15(1):287. doi:10.1186/1471-2105-15-287.

74. Wang JZ. Pathfinder: multiresolution region-based searching of pathology images using IRM. Proceedings of the AMIA Symposium. 2000; p. 883–887.

75. Mosquera-Lopez C, Agaian S, Velez-Hoyos A, Thompson I. Computer-Aided Prostate Cancer Diagnosis From Digitized Histopathology: A Review on Texture-Based Systems. IEEE Reviews in Biomedical Engineering. 2015;8:98–113. doi:10.1109/RBME.2014.2340401.

76. Sridhar A, Doyle S, Madabhushi A. Content-based image retrieval of digitized histopathology in boosted spectrally embedded spaces. Journal of pathology informatics. 2015;6. doi:10.4103/2153-3539.159441.

77. Gleason Donald F , Mellinger George T , Group TVACUR. Prediction of Prognosis for Prostatic Adenocarcinoma by Combined Histological Grading and Clinical Staging. Journal of Urology. 1974;111(1):58–64. doi:10.1016/S0022-5347(17)59889-4.

78. Markonis D, Schaer R, de Herrera AGS, Müller H. The Parallel Distributed Image Search Engine (ParaDISE). arXiv:170105596 [cs]. 2017;.

79. Peng T, Boxberg M, Weichert W, Navab N, Marr C. Multi-task Learning of a Deep K-Nearest Neighbour Network for Histopathological Image Classification and Retrieval. In: Shen D, Liu T, Peters TM, Staib LH, Essert C, Zhou S, et al., editors. Medical Image Computing and Computer Assisted Intervention – MICCAI 2019. Lecture Notes in Computer Science. Cham: Springer International Publishing; 2019. p. 676–684.

80. Cao Z, Long M, Wang J, Yu PS. HashNet: Deep Learning to Hash by Continuation. arXiv:170200758 [cs]. 2017;.

81. Cao Y, Long M, Liu B, Wang J. Deep Cauchy Hashing for Hamming Space Retrieval. In: 2018 IEEE/CVF Conference on Computer Vision and Pattern Recognition. Salt Lake City, UT: IEEE; 2018. p. 1229–1237. Available from: https://ieeexplore.ieee.org/document/8578232/.

82. Commandeur F, Slomka PJ, Goeller M, Chen X, Cadet S, Razipour A, et al. Machine learning to predict the long-term risk of myocardial infarction and cardiac death based on clinical risk, coronary calcium, and epicardial adipose tissue: a prospective study. Cardiovascular Research. 2019;doi:10.1093/cvr/cvz321.