EMPIRICAL ANALYSIS AND MODELING OF ARGOS DOPPLER LOCATION

ERRORS IN ROMANIA

Laurentiu Rozylowicz[1], Florian P. Bodescu[2], Cristiana M. Ciocanea[1], Athanasios A. Gavrilidis[2],

Steluta Manolache[1], Marius L. Matache[1], Iulia V. Miu[1], Ionut C. Moale[2], Andreea Nita[1], Viorel

D. Popescu[1,3]

[1] Center for Environmental Research and Impact Studies, University of Bucharest, Bucharest,

Romania

[2] Multidimension SRL, Bucharest, Romania

[3] Biological Sciences, Ohio University, Athens Ohio, USA

Corresponding author:

Laurentiu Rozylowicz[1]

University of Bucharest, Center for Environmental Research and Impact Studies, 1 N. Balcescu,

010041, Bucharest, Romania

email address: laurentiu.rozylowicz@g.unibuc.ro

ABSTRACT

Background. Advances in wildlife tracking technology have allowed researchers to understand

the spatial ecology of many terrestrial and aquatic animal species. Argos Doppler is a technology

that is widely used for wildlife tracking owing to the small size and low weight of the Argos

transmitters. This allows them to be fitted to small-bodied species. The longer lifespan of the

Argos units in comparison to units outfitted with miniaturized global positioning system (GPS)

technology has also recommended their use. In practice, large Argos location errors often occur

due to communication conditions such as transmitter settings, local environment, and the

behavior of the tracked individual.

Methods. Considering the geographic specificity of errors and the lack of benchmark studies in

Eastern Europe, the research objectives were: (1) to evaluate the accuracy of Argos Doppler

technology under various environmental conditions in Romania, (2) to investigate the

effectiveness of straightforward destructive filters for improving Argos Doppler data quality, and

(3) to provide guidelines for processing Argos Doppler wildlife monitoring data. The errors

associated with Argos locations in four geographic locations in Romania were assessed during

static, low-speed and high-speed tests. The effectiveness of the Douglas Argos distance angle

filter algorithm was then evaluated to ascertain its effect on the minimization of localization

errors.

Results. Argos locations received in the tests had larger associated horizontal errors than those

indicated by the operator of the Argos system, including under ideal reception conditions.

Positional errors were similar to those obtained in other studies outside of Europe. The errors

were anisotropic, with larger longitudinal errors for the vast majority of the data. Errors were

mostly related to speed of the Argos transmitter at the time of reception, but other factors such as

topographical conditions and orientation of antenna at the time of the transmission also

contributed to receiving low-quality data. The Douglas-Argos filter successfully excluded the

largest errors while retaining a large amount of data when the threshold was set to the local scale

(2 km).

Discussion. Filter selection requires knowledge about the movement patterns and behavior of the

species of interest, and the parametrization of the selected filter typically requires a trial and error

approach. Selecting the proper filter reduces the errors while retaining a large amount of data.

However, the post-processed data typically includes large positional errors; thus, we recommend

incorporating Argos error metrics such as error ellipse or use complex modeling approaches

when working with filtered data.

INTRODUCTION

Advances in wildlife tracking technologies allow researchers to track the movement of many terrestrial and aquatic species (Thomas et al. 2012). Movement analysis has evolved from short-term local studies on small numbers of individuals to long-term global studies on hundreds of individuals, allowing researchers to answer more complex questions about animal movement and space use (Block et al. 2011; Sequeira et al. 2018). These data can be included in statistical models and used to understand movement patterns, population redistribution, habitat use, habitat selection, and conservation needs (Bridge et al. 2011; Doherty et al. 2017; Hooten et al. 2017; Pendoley et al. 2014; Pop et al. 2018; Schofield et al. 2013).

Collecting good quality movement data remains a challenging task mainly due to technological constraints (Hooten et al. 2017). Well-known tracking technologies such as radio telemetry (VHF telemetry), satellite-based telemetry (GPS, Argos), and light-level geolocation have certain limitations (Bridge et al. 2011). The main challenges are the physical size and the mass of the devices. In particular, the mass of the device must not exceed 5% of the animal's body-weight (Silvy 2012). Furthermore, transmitters must be protected from environmental hazards and damage and must include a long-lasting battery or alternative power source for consistent one-way or two-way communication (Bridge et al. 2011). As such, devices meeting these parameters can be cumbersome and heavy (Silvy 2012), and not well suited for many small-bodied animals.

The most accurate available tracking technology is the Global Positioning System (GPS), capable of a horizontal location accuracy of under 10 m (Madry 2015). The weight of present-day GPS receivers varies between a minimum of 4 grams (lifespan limited to a few transmission days and suitable for individuals weighing ~80 grams) to in excess of one kilogram (typically a lifespan averaging 2 years and suitable only for large animals). An alternate option for long-term animal movement studies is the Argos satellite Doppler-based system, which relies on transmitters with extended lifespans that now weigh less than 4 grams, and are able to deliver an unlimited number of locations in near real-time (Bridge et al. 2011; Hooten et al. 2017; Thomas et al. 2012). However, the small size comes at a cost in terms of accuracy of localization compared to GPS. Thus, data interpretation may pose a challenge for inexperienced users (Rozylowicz et al. 2018). Regardless of the device size, Argos transmitters, or Platform Transmitter Terminals (PTT), provide locations with the same error rate. In addition, the data requires the application of complex control processes, such as filtering and modeling (Thomas et

al. 2012). If the PTT's are equipped with GPS receivers, the location precision can be increased

by retaining only validated locations (Lopez et al. 2015). Adding a GPS unit to a PTT device

results in increasing the minimum device weight to approximately 20 grams per unit.

The Argos system utilizes positioning instruments on board six polar-orbiting satellites, in

addition to ground-based receiving stations and data processing centers. It delivers near real-time

localization of transmitters to end-users. Argos locations are calculated from the Doppler shift of

a PTT radio frequency during a satellite pass (CLS 2016). Collecte Localisation Satellites (CLS),

the operator of the Argos system, provides several metrics for data quality, such as a location

class (LC) based on the number of messages received for each location. The estimated upper

bound errors are 250 m for LC 3 (best accuracy class), 500 m for LC 2, 1500 m for LC 1, and

over 1500 m for LC 0. For locations derived from three or fewer messages (LC A, LC B), Argos

does not provide error thresholds. Invalid locations are labeled as LC Z and GPS locations as LC

G (CLS 2016). CLS pre-processes these locations using one of Argos's nominal filters such as

the Least Squares algorithm or the Kalman filter (Lopez et al. 2015). In practice, location errors

of 10 to 100 kilometers often occur due to communication conditions driven by the environment

or animal behavior (e.g., animal speed, terrain fragmentation, rain, cloud cover, temperature)

(Christin et al. 2015; Costa et al. 2010; Douglas et al. 2012; Dubinin et al. 2010; Sauder et al.

2012; Witt et al. 2010). Thus, filtering the data to exclude implausible Argos locations before

employing movement analysis has become a standard approach for researchers (Hooten et al.

2017). Furthermore, the quality of data seems to be highly dependent on geographic location.

The Argos transmission systems in Eastern Europe are lower in power, their signals being hidden

by background radio noise that is present across the Argos frequency (Gros et al. 2006).

Location errors can be filtered using destructive (i.e., removing implausible locations) and

reconstructive filters (i.e., evaluation of uncertainty in the estimation of locations) (Douglas et al.

2012). Destructive filters remove duplicates (e.g., identical timestamps), locations outside of a

defined range (e.g., thresholds for geometric dilution of precision, latitude, longitude, location

class), or locations exceeding a fixed movement rate or a turning angle (Douglas et al. 2012;

Kranstauber et al. 2011). One such advanced destructive filter is the Douglas Argos filter

algorithm, available on the Movebank database of animal tracking data (Kranstauber et al. 2011).

The Douglas Argos filter algorithm uses thresholds to mark the outliers as implausible locations.

It is available in three settings: the maximum redundant distance filter (MRD) (which retains

near-consecutive locations within a distance threshold), the Douglas Argos distance angle filter

(DAR) (which retains near-consecutive locations within a distance threshold and location-

passing movement-rate and turning-angle tests), and the hybrid filter (HYB) (which combines

MRD and DAR parameters specifically for migratory species) (Douglas et al. 2012). In contrast,

reconstructive filters employ advanced statistical methods to detect animal movement

characteristics without removing locations (e.g., discrete-time movement model, correlated

random walk state-space models, movement-based kernel density estimates, Bayesian State-

Space Models, and hidden Markov models), or model the data using the errors associated with

movement (e.g., Argos error ellipse) (Hooten et al. 2017; Jonsen et al. 2005; Lopez et al. 2015;

Silva et al. 2014).

Considering the behavioral, environmental and geographic specificity of the errors associated

with Argos data and the lack of benchmark studies in Eastern Europe, the research objectives for

this study are: (1) to provide empirical evidence of the accuracy of locations collected via the

Argos Doppler system in Romania, (2) to investigate the effectiveness of straightforward

destructive filters for improving Argos data quality, and (3) to provides guidelines for processing

Argos wildlife monitoring data in Eastern Europe. The errors associated with Argos locations

were assessed in four geographic locations from Romania under three spatial movement

conditions: static, low-speed and high-speed. The effectiveness of the Douglas Argos distance

angle filter algorithm was then evaluated in terms of location error minimization.

MATERIALS & **METHODS**

Trial sites

The accuracy of Argos locations was analyzed in four areas in Romania. These areas varied both

topographically and in terms of reception conditions and could be categorized as:

(1) Urban: two urban parks within a residential area of Romania's largest metropolis, Bucharest

(within the Tineretului Park for the static test, 44°24'N 26°06'E; and the shoreline of Vacaresti

Lake for the mobile tests, 44°24'N, 26°07'E).

(2) Unobstructed flat rural lowland: Saveni, Ialomita County (44°35', 27°37'E).

(3) Highly fragmented rural topography: Iron Gates Natural Park, Mehedinti County (44°41'N

22°21'E), along the Danube River.

(4) Moderately fragmented rural upland: Sighisoara (within Breite for the static tests, 46°12'N
24°45'E; and Sighisoara-Apold for the mobile tests, 46°09'N 24°46'E)).
At all trial sites, three tests were carried out: a static test, a low-speed test, and a high-speed test
(Fig. 1).

Experimental protocol

Five Argos PTTs were used, all identical GeoTrack 23g Solar PTT units (GeoTrack Ink., Apex,
NC) with a repetition period of 60 seconds. The PTTs were initially programmed for an 8 hours
'on' and 43 hours 'off' transmission cycle. They were then manually activated at the start of the
working day and restarted if the transmission cycle lasted longer than 8 hours. Daily activation
occurred 10 minutes before the first Argos satellite was scheduled to be visible, according to the
satellite pass prediction (CLS 2016). During the experiment, a transmission day started after the
activation of the PTTs, when the first Argos message was received by a given PTT, and ended
after a minimum of 6 hours, when the satellite transmitting the last message was no longer
visible to the PTTs. The PTTs were glued on a stake 20 cm from each other, with their antennas
pointing in the same direction towards the sky. Argos messages were processed by CLS using
the standard Kalman filter algorithm (CLS 2016), with a predefined average speed of 16 m/s. To
estimate the accuracy of the Argos locations, each Doppler location was matched with a GPS
location (Garmin Oregon 650, Garmin Ltd.) obtained within a 5-minute time period. Garmin
GPS receivers have a precision of under 10 m in low-rise residential areas (Beekhuizen et al.
2013). GPS locations could thus be considered accurate.
Each speed test lasted a total of 6 transmission days, with a minimum of 6 transmission hours per
cycle. For static tests, the five PTTs were positioned 30 cm above ground in unobstructed
transmission conditions. For low-speed tests, researchers carried the PTTs attached to a backpack
at normal walking speed (4–5 km/h). For the high-speed tests, the PTTs were mounted on a
bicycle traveling at 15 km/h. In each test, the GPS receiver was set to record a location every 30
seconds.

Data processing and analyses

Argos messages were downloaded daily. Each Argos message was assigned to the corresponding
trial site and movement test. Prior to statistical analysis, the dataset was cleaned to eliminate
records without coordinates or with identical timestamps.

The magnitude of spatial errors was estimated using several error metrics. Distances between
Argos locations and the corresponding GPS locations were calculated as the geodesic distance
using the WGS 1984 reference ellipsoid (i.e., *location error*, in meters). The direction of the
error was calculated as bearing along a rhumb line between the Argos and GPS locations (i.e.,
error bearing, 0–360º) (Hijmans et al. 2017). Latitudinal and longitudinal errors were calculated
as the difference between the UTM coordinates of Argos latitude and longitude and the
corresponding GPS latitude and longitude (i.e., *Latitudinal* and *Longitudinal errors* in km).
Furthermore, Argos locations were classified as *"in"* or *"out"* of Argos ellipse error by plotting
them in the ArcGIS 10.3 (ESRI, CA) software package along with the ellipse error components
provided by CLS for each location (Data S1).
The variability of log-transformed location errors was evaluated using linear-mixed effects
models with *motion* (speed: static, low-speed, high-speed), *place* (trial sites: Saveni, Bucharest,
Sighisoara, Iron Gates), and a *terrain ruggedness index* (TRI) (Riley 1999) as fixed effects and
the *receiving points* (locations generated simultaneously by all transmitting PTTs at a satellite
pass) nested within the *satellite* generating the Argos locations as random effects. Grouping the
locations by receiving points allowed control of pseudoreplication and latent variation
unaccounted for by the fixed effects (Harrison et al. 2018).
Several linear-mixed effects models were fitted using different combinations of fixed effects
with the same nested random effects structure using function *lmer* with restricted maximum
likelihood (REML) in the package *lme4* (Bates et al. 2015) in program R (R Core Team 2018).
To select the best model predicting the variance of log-transformed location errors we used
Akaike's Information Criterion, corrected for small sample size (AICc) (Table S1). The model fit
was evaluated as the variance in the data explained by fixed effects (marginal R-squared) and
collectively by fixed and random effects (conditional R-squared) (Nakagawa & Schielzeth 2013).
To evaluate the effectiveness of the data filters to minimize the location errors when the tracked
species move within a given site, we partitioned the data by trial sites and then ran distance,
angle, and rate Douglas Argos filter (DAR) on Movebank tracking platform
(www.movebank.org) (Douglas et al. 2012; Kranstauber et al. 2011). The two other versions of
the Douglas Argos filter are either a truncated version of the distance, angle and rate filter
(maximum redundant distance, MRD filter) or specifically designed for migration movement
(HYB filter), which was not the case in this experiment (Douglas et al. 2012).

The DAR filter was applied twice: with the threshold radius set to encompass 2 locations which
were considered self-confirming (MAXREDUN) at 2 km (DAR 2) and at 15 km (DAR 15).
Smaller threshold values, such as 2 km are suitable for local scale movement while larger values
(e.g., 15 km) are suitable for macro scale movements (Douglas et al. 2012). It is recommended
by the authors of the Douglas Argos algorithm to retain locations above LC 1 (locations with
higher accuracy class); however, because our test was focused on the effectiveness of this filter
at eliminating location errors from the whole dataset, a location class threshold was not provided.
The two other user-defined parameters of the DAR filter were kept fixed in both filtering
sessions because the experimental conditions were similar. MINRATE (maximum sustained rate
of movement over a period of several hours) was set at 15 km/h (maximum velocity achieved
during the test) and RATECOEF was set at 10 (specifically used for movements following a very
circuitous pattern). MINRATE confirms the plausibility of a location based on a reasonable rate
of movement that the animal of interest might sustain and RATECOEF is a scaling parameter
which influences how the angle between two consecutive locations is evaluated (parameter
values vary between 10, for species displaying out-and-back movement, and 40, for species with
directional movement) (Douglas et al. 2012). The results of the two user-specific filters (DAR 2
and DAR 15) were compared to the unfiltered data. For comparison purposes, the results for two
intermediary MAXREDUN thresholds are presented in a supplementary file: 5 km (DAR 5) and
10 km (DAR 10).
We used R 3.5.1 (R Core Team 2018) package *dplyr* (Wickham et al. 2018) for cleaning data,
geosphere (Hijmans et al. 2017) for calculating error metrics, *dunn.test* (Dinno 2017) for testing
differences between various datasets, *lme4* (Bates et al. 2015), *MuMIn* (Barton 2018), *merTools*
(Knowles et al. 2018) for linear-mixed effects models, *ggpubr* (Kassambara 2018), *ggeffects*
(Lüdecke 2018), and *openair* (Carslaw & Ropkins 2012) for figures.
229
RESULTS
Between June 2017 and September 2017, the five PTTs received 3705 valid Argos locations
(Data S1). Each PTT generated a similar number of locations (min = 717, max = 760, χ^2 (df = 4,
n = 3705) = 1.86, p = 0.76). For each location, the Argos PTTs transmitted between 1 and 14
messages to one of the six polar-orbiting satellites fitted with Argos instruments. The Argos

satellites resulted in the calculation of a dissimilar number of locations (min = 310, NOAA-N,

NP'; max = 890, NOAA-18, NN, χ^2 (df = 5, n = 3705) = 399.87, p < 0.001).

The dataset was dominated by low-quality data, with over 29% of locations labeled as LC B.

46% of the locations were classified by the CLS as error bounded (Argos LC 3, 2, and 1), from

which 14.25% were of high estimated quality (LC 3, < 250 m estimated accuracy) (Table 1).

The empirical mean location error for the five PTTs was 3583.66 m (stdev = 8225.97 m).

Location errors differed significantly by Argos location classes (Kruskal-Wallis chi-squared =

1170.95, df = 5, p < 0.001), except for the LC 1 and LC A which showed identical ranking. All

the error-bounded location classes (Argos LC 3, 2, and 1) had measured errors which were

significantly larger than the location-class-specific 68th percentile estimated by CLS. Argos LC

A and LC B had smaller associated errors than LC 0, a location class which is considered more

accurate by CLS (Fig. 2, Table 1).

On average, longitudinal errors were larger (mean = 2872 m, stdev = 7678 m) than latitudinal

errors (mean = 1604.4 m, stdev = 3272.3 m). This pattern was found to be consistent in all

location classes (Table 1). The largest proportion of longitudinal errors were in LC 0 (73.96% of

locations) and LC 1 (73.44% of locations), while the largest proportion of latitudinal errors was

found in the LC B (39.29%) and LC A (38.42%) classes. Geographically, most errors were to the

East and West, followed by the North-East and South-West. Those oriented toward the North

and South were less present in the dataset (Fig. S1, Fig. S2).

The best linear mixed model showed that the fixed factors *Motion* (speed tests) and *Place* (trial

areas) had a significant impact on the errors (Table S1). The fixed factors Motion and Place

accounted for 17.45% of the variance in the error data (marginal R-squared), while the fixed and

random structures (*reception points* nested in the *satellite*) combined accounted for 56.79% of

the variance (conditional R-squared). The proportion of variance in errors accounted for by the

reception points nested in the satellite (Intra Class Correlation Coefficient, ICC) was 41.91%,

while the satellites themselves accounted for only 5.73%, suggesting that reception conditions at

transmission time strongly influenced the quality of the data (Table 2).

A comparison of the confidence intervals of the fixed factors showed that the locations from

motion-controlled trials differed significantly. Errors from high-speed tests were larger than

those in the low-speed tests, and errors in the low-speed tests were larger than in the static tests.

The mean error for the static tests was 2708.84 m, the mean error for the low-speed tests was

3779.73 m, and the mean error for high-speed tests was 4550 m, (Fig. 3, Table 3). The trial sites

also contributed to the error variance, with locations from Iron Gates (a narrow valley)

generating larger errors when compared to locations from the other sampling areas. As a

comparative example, the mean error for Iron Gates was 4698.35 m and the mean error for

Saveni was 3122.01 m (Fig. 3, Table 4). Interestingly, it was found that substantial errors existed

in the static tests from Iron Gates which were as large as the location errors associated with the

low-speed tests conducted in Saveni, Bucharest, and Sighisoara (Fig. 3).

The DAR filter applied to raw data, successfully excluded the largest errors when MAXREDUN

was defined for local (2 km, DAR 2) and regional (15 km, DAR 15) scales of study. However,

the DAR 2 filter was more effective at excluding large errors, by retaining 84.35% of the initial

locations compared to 94.82% for the DAR 15 filter (Table S2, Table S3). The mean error for the

DAR 2 filtered data was 2313.51 meters (stdev = 3134.67), a 35.45% improvement compared to

the error associated with the raw data, while the improvement after the DAR 15 filter was

applied was only 27.05%. The DAR 15 filter retained almost all the locations in LC 3, LC 2 and

LC 1 classes, while the DAR 2 filter altered the number of LC 2 and LC 1 locations slightly. The

most heavily-impacted location class was LC 0 - the class with the most substantial errors

amongst the data - with only 68.35% of locations retained by the DAR 2 filter and 90.42% by the

DAR 15 filter (Table S2, Table S3, Fig. 4). The intermediate thresholds (DAR 5 and DAR 10)

did not improved the data accuracy in comparison to DAR 2, and the results were only

marginally different when compared to DAR 15 (Fig. S3). Douglas Argos algorithms filtered

longitudinal and latitudinal errors equally; thus, the filtered data are also anisotropic, with the

longitudinal errors larger than the latitudinal errors (Fig. 5).

DISCUSSION

The accuracy of the Argos Doppler locations received from Romania was negatively influenced

by the movement speed and topographic characteristics of the trial sites. The empirical data

showed that Argos locations yielded a lower accuracy, even in stationary tests performed in

unobstructed areas. This suggests that Argos Doppler telemetry data must undergo a

comprehensive filtering process before being used in movement analysis.

In our experiment, 14% of locations were considered category LC 3, the most accurate Argos

location class (CLS 2016). However, the 68[th] percentile of LC 3 locations was twice as large as

the 68[th] percentile provided by CLS as the upper bound error (520.85 m vs. 250 m). All error-

bounded Argos locations classes (LC 2, LC 1, and LC 0) included larger positional errors than

those indicated by CLS (CLS 2016), which is in line with the results demonstrated in other

controlled and real-life studies. For example, a stationary and mobile test in Southern Russia

(Dubinin et al. 2010) and tests on marine species (Costa et al. 2010) yielded errors similar to ours

for LC 3 data. Data recovered from these other studies and our results indicate higher errors than

those indicated by CLS for all location classes. LC 0 was the most inaccurate location class (68[th]

percentile = 5877.38 m), which corroborates the results of other studies (Douglas et al. 2012;

Lowther et al. 2015). This suggests that LC 0 locations must be filtered together with LC A and

LC B, and should not be considered an accurate location class. Argos errors are not isotropic,

and longitudinal errors were larger than latitudinal errors (CLS 2016; Douglas et al. 2012), as

already reported by all benchmark studies (Lowther et al. 2015; Sauder et al. 2012; Witt et al.

2010). In this study, the mean latitudinal errors for LC 3, LC 2, and LC 1 were only slightly

larger than the CLS 68[th] percentile for the respective location classes. However, these data are

not likely to be useful for movement studies, such as home-range analysis (Hooten et al. 2017)

since longitudinal errors were significant even in optimal reception environments (e.g., flat areas,

unobstructed by vegetation). South-Eastern Europe is considered an area with poor reception

quality due to the broadband noise covering the Argos 401.65 MHz $\pm$ 30 kHz frequency (Gros et

al. 2006), which might have a negative impact on quantity and quality of data. Since these errors

were similar to those obtained in other studies outside of Europe, the broadband noise affecting

Southeastern Europe (Gros et al. 2006) seems to have had only a minimal influence on the

accuracy of Argos data.

The accuracy of Argos Doppler locations is influenced by a plethora of factors such as the PTTs'

repetition rate, topography, vegetation, terrain ruggedness, electromagnetic noise, and

geographic area (Freitas et al. 2008; Lowther et al. 2015; Nicholls et al. 2007; Sauder et al.

2012). The best linear mixed effects model for this study showed that the movement speed of the

PTT had the most significant influence on Argos location errors, while the trial area contributed

only marginally to the variation in errors. As expected, motion-controlled tests generated

significantly varying errors. Static tests generated smaller errors than low-speed tests, and high-

speed tests generated larger errors than low-speed tests. However, topographical obstruction of

the sky influenced data acquisition. Data obtained from the highly-fragmented Iron-Gates trial

area contained larger errors than the other three trial areas, including Bucharest city potentially

affected by electromagnetic interference (Gros et al. 2006). In the Iron Gates area, the static test

generated positional errors as large as in the low-speed motion tests performed in the other three

areas. This suggests that locations from fragmented areas may be highly imprecise and can lead

to biased conclusions about animal movement and location if not adequately filtered (Lopez et

al. 2015). The variance explained by the random part of the linear mixed effects model suggests

that the satellite detecting the location of the PTT had a minimal impact on accuracy, while the

dominant source of positional errors were probably due to other random factors, such as poor

line of sight to the satellite as a result of local topography, the presence of obstructing vegetation

or the relative orientation of the respective PTT with respect to the sky (Christin et al. 2015;

Doherty et al. 2017; Dubinin et al. 2010; Soutullo et al. 2007).

Due to the large positional errors, Argos Doppler data should be filtered or modeled, considering

the uncertainty of locations (McClintock et al. 2014). Data filtering is a challenge, as the aim is

to reduce low-quality data as much as possible while retaining the necessary amount of data for

analysis (Hooten et al. 2017). In the filtering exercise conducted in this study, we tested the

effect of the Douglas Argos distance, angle, and rate filter. This filter retains spatially redundant

locations, passing movement rates, and turning angle tests (Douglas et al. 2012). The results

indicated that the selection of a proper self-validating distance threshold significantly reduces the

errors while retaining a large amount of data. In this study, a larger threshold, MAXREDUN =

15 km, reduced the efficacy of the filter considerably by retaining 10% more locations than when

the threshold was set at 2 km. The differences between the two approaches suggested that

previous knowledge of movement behavior of species of interest is essential to ensure good

quality data. For example, if the species of interest is known to perform frequent long-distance

movements, then a larger MAXREDUN is required. The DAR filter was tested by targeting all

the location classes; however, LC 3, LC 2, and LC 1 were only slightly impacted, and thus it is

recommended to run the filter using LC 1 as the threshold location class as suggested by Douglas

et al. (2012).

Even if selecting the optimal threshold, the post-processed data may include large positional

errors; therefore, we recommend incorporating Argos error metrics such as error ellipse into

models (McClintock et al. 2014). As an alternative, complex statistical approaches such as state-
space modeling can be used instead of standard movement analysis (Hooten et al. 2017). While
the results were provided based on the distance, angle, and rate filter which fitted the data, other
available filtering approaches might be more effective for a given species (e.g., speed filters,
Douglas Argos MRD, Douglas Argos HYB).

CONCLUSIONS

To provide guidance for processing Argos Doppler-derived locations obtained from Eastern
Europe, we assessed the errors associated with Argos locations in four geographic locations in
Romania using static, low-speed and high-speed tests. The effectiveness of destructive filters was
evaluated in terms of the minimization of location errors, using the Douglas Argos distance angle
filter algorithm as an example. The results indicated that the received Argos locations had larger
positional errors than those indicated by the operator of the Argos system. This included cases
where the reception conditions were ideal. The magnitude of the errors varied among location
classes; however, locations in the LC 0 class were prone to large errors. Positional errors were
anisotropic, predominantly oriented East and West, which resulted in larger longitudinal errors.
Errors were mostly related to the speed of the transmitters and the reception conditions at the
time of transmission (e.g., the orientation of the transmitter with respect to the sky), but other
factors such as topography contributed to receiving low-accuracy data as well. The destructive
Douglas Argos distance angle filter removed between 15% (self-confirming distance threshold =
2 km) and 5% (threshold = 15 km) of locations. However, the mean errors remained larger than
those indicated by the operator of Argos system. The Argos data should therefore be used with
caution in movement ecology studies, especially for species with small home ranges, such as
songbirds, reptiles, or small mammals. Filter selection for data processing requires knowledge
about the movement patterns and behaviors of the species of interest, and parametrization of the
selected filter must follow a trial and error approach. Argos Doppler is unsuitable for movement
analysis of species with limited movement capabilities. GPS tags would be preferable for such
species, enabling detailed analysis of habitat selection and movement, with the caveat that store-
on-board systems might be required owing to the larger sizes of the units that send data remotely
via satellite.

REFERENCES

Barton K. 2018. Package 'MuMIn'. Multi-Model Inference. v. 1.42.1. R package.
https://CRAN.R-project.org/package=MuMIn
Bates D, Mächler M, Bolker B, and Walker S. 2015. Fitting linear mixed-effects models using
lme4. *Journal of Statistical Software* 67. 10.18637/jss.v067.i01
Beekhuizen J, Kromhout H, Huss A, and Vermeulen R. 2013. Performance of GPS-devices for
environmental exposure assessment. *Journal of Exposure Science and Environmental*
Epidemiology 23:498. 10.1038/jes.2012.81
Block BA, Jonsen ID, Jorgensen SJ, Winship AJ, Shaffer SA, Bograd SJ, Hazen EL, Foley DG,
Breed G, and Harrison A-L. 2011. Tracking apex marine predator movements in a dynamic
ocean. *Nature* 475:86. 10.1038/nature10082
Bridge ES, Thorup K, Bowlin MS, Chilson PB, Diehl RH, Fléron RW, Hartl P, Kays R, Kelly JF,
and Robinson WD. 2011. Technology on the move: recent and forthcoming innovations
for tracking migratory birds. *Bioscience* 61:689-698. 10.1525/bio.2011.61.9.7
Carslaw DC, and Ropkins K. 2012. Openair - an R package for air quality data analysis.
Environmental Modelling & Software 27:52-61. 10.1016/j.envsoft.2011.09.008
Christin S, St-Laurent MH, and Berteaux D. 2015. Evaluation of Argos Telemetry Accuracy in the
High-Arctic and Implications for the Estimation of Home-Range Size. *PLoS One*
10:e0141999. 10.1371/journal.pone.0141999
CLS. 2016. Argos User's Manual. *Available at http://www.argos-system.org/manual/* (accessed
07/22/2018).
Costa DP, Robinson PW, Arnould JP, Harrison AL, Simmons SE, Hassrick JL, Hoskins AJ,
Kirkman SP, Oosthuizen H, Villegas-Amtmann S, and Crocker DE. 2010. Accuracy of
ARGOS locations of Pinnipeds at-sea estimated using Fastloc GPS. *PLoS One* 5:e8677.
10.1371/journal.pone.0008677
Dinno A. 2017. dunn. test: Dunn's test of multiple comparisons using rank sums. v. 1.3.5. R
package. https://CRAN.R-project.org/package=dunn.test
Doherty P, Baxter J, Gell F, Godley B, Graham R, Hall G, Hall J, Hawkes L, Henderson S, and
Johnson L. 2017. Long-term satellite tracking reveals variable seasonal migration
strategies of basking sharks in the north-east Atlantic. *Scientific reports* 7:42837.
10.1038/srep42837
Douglas DC, Weinzierl R, C. Davidson S, Kays R, Wikelski M, Bohrer G, and Giuggioli L. 2012.
Moderating Argos location errors in animal tracking data. *Methods in Ecology and*
Evolution 3:999-1007. 10.1111/j.2041-210X.2012.00245.x
Dubinin M, Lushchekina A, and Radeloff VC. 2010. Performance and accuracy of Argos
transmitters for wildlife monitoring in Southern Russia. *European Journal of Wildlife*
Research 56:459-463. 10.1007/s10344-009-0354-4
Freitas C, Lydersen C, Fedak MA, and Kovacs KM. 2008. A simple new algorithm to filter marine
mammal Argos locations. *Marine Mammal Science* 24:315-325. 10.1111/j.1748-
7692.2007.00180.x
Gros P, Malardé J, and Woodward B. 2006. Argos performance in Europe. Part 2. *Tracker News*
7:8.

Harrison XA, Donaldson L, Correa-Cano ME, Evans J, Fisher DN, Goodwin CED, Robinson BS,
Hodgson DJ, and Inger R. 2018. A brief introduction to mixed effects modelling and multi-
model inference in ecology. *PeerJ* 6:e4794. 10.7717/peerj.4794
Hijmans RJ, Williams E, and Vennes C. 2017. Package 'geosphere'. Spherical Trigonometry. v.
1.5-7. R package. https://CRAN.R-project.org/package=geosphere.
Hooten MB, Johnson DS, McClintock BT, and Morales JM. 2017. *Animal movement: statistical*
models for telemetry data. Boca Raton: CRC Press.
Jonsen ID, Flemming JM, and Myers RA. 2005. Robust state–space modeling of animal movement
data. *Ecology* 86:2874-2880.
Kassambara A. 2018. ggpubr: 'ggplot2' Based Publication Ready Plot. v. 0.1.7. R package.
https://CRAN.R-project.org/package=ggpubr.
Knowles JE, Frederick C, and Whitworth A. 2018. merTools: Tools for Analyzing Mixed Effect
Regression Models. v 0.4.1. R package. https://CRAN.R-project.org/package=merTools.
Kranstauber B, Cameron A, Weinzerl R, Fountain T, Tilak S, Wikelski M, and Kays R. 2011. The
Movebank data model for animal tracking. *Environmental Modelling & Software* 26:834-
835. 10.1016/j.envsoft.2010.12.005
Lopez R, Malardé J-P, Danès P, and Gaspar P. 2015. Improving Argos Doppler location using
multiple-model smoothing. *Animal Biotelemetry* 3:32. 10.1186/s40317-015-0073-4
Lowther AD, Lydersen C, Fedak MA, Lovell P, and Kovacs KM. 2015. The Argos-CLS Kalman
Filter: Error Structures and State-Space Modelling Relative to Fastloc GPS Data. *PLoS*
One 10:e0124754. 10.1371/journal.pone.0124754
Lüdecke D. 2018. ggeffects: Create Tidy Data Frames of Marginal Effects for 'ggplot' from Model
Outputs. v. 0.5.0. R package. https://CRAN.R-project.org/package=ggeffects.
Madry S. 2015. *Global navigation satellite systems and their applications*. New York: Springer.
McClintock BT, London JM, Cameron MF, and Boveng PL. 2014. Modelling animal movement
using the Argos satellite telemetry location error ellipse. *Methods in Ecology and Evolution*
6:266-277. 10.1111/2041-210X.12311
Nakagawa S, and Schielzeth H. 2013. A general and simple method for obtaining R2 from
generalized linear mixed-effects models. *Methods in Ecology and Evolution* 4:133-142.
10.1111/j.2041-210x.2012.00261.x
Nicholls D, Robertson C, and Murray M. 2007. Measuring accuracy and precision for CLS: Argos
satellite telemetry locations. *Notornis* 54:137-157.
Pendoley K, Schofield G, Whittock P, Ierodiaconou D, and Hays G. 2014. Protected species use
of a coastal marine migratory corridor connecting marine protected areas. *Marine Biology*
161:1455-1466. 10.1007/s00227-014-2433-7
Pop IM, Bereczky L, Chiriac S, Iosif R, Nita A, Popescu VD, and Rozylowicz L. 2018. Movement
ecology of brown bears (Ursus arctos) in the Romanian Eastern Carpathians. *Nature*
conservation 26:15-31. 10.3897/natureconservation.26.22955
R Core Team. 2018. R: A language and environment for statistical computing. Vienna, Austria:
the R Foundation for Statistical Computing.
Riley SJ., DeGloria SD, and Elliot SD. 1999. A terrain ruggedness index that quantifies
topographic heterogeneity. *Intermountain Journal of sciences* 5:23-27.
Rozylowicz L, Bodescu FP, Gavrilidis AA, Miu IV, Moale C, Manolache S, Nita A, Matache ML,
and Ciocanea CM. 2018. *Tehnici de monitorizare a deplasărilor animalelor sălbatice.*
Manual. Bucharest: University of Bucharest. 10.5281/zenodo.1344840

Sauder JD, Rachlow JL, and Wiest MM. 2012. Influence of topography and canopy cover on argos
satellite telemetry performance. *Wildlife Society Bulletin* 36:813-819. 10.1002/wsb.157
Schofield G, Scott R, Dimadi A, Fossette S, Katselidis KA, Koutsoubas D, Lilley MK, Pantis JD,
Karagouni AD, and Hays GC. 2013. Evidence-based marine protected area planning for a
highly mobile endangered marine vertebrate. *Biological Conservation* 161:101-109.
10.1016/j.biocon.2013.03.004
Sequeira AM, Rodríguez JP, Eguíluz VM, Harcourt R, Hindell M, Sims DW, Duarte CM, Costa
DP, Fernández-Gracia J, and Ferreira LC. 2018. Convergence of marine megafauna
movement patterns in coastal and open oceans. *Proceedings of the National Academy of*
Sciences: 201716137. 10.1073/pnas.1716137115
Silva MA, Jonsen I, Russell DJ, Prieto R, Thompson D, and Baumgartner MF. 2014. Assessing
performance of Bayesian state-space models fit to Argos satellite telemetry locations
processed with Kalman filtering. *PLoS One* 9:e92277. 10.1371/journal.pone.0092277
Silvy NJ. 2012. *The Wildlife Techniques Manual: Volume 1: Research. Volume 2: Management*.
Baltimore: JHU Press.
Soutullo A, Cadahia L, Urios V, Ferrer M, and Negro JJ. 2007. Accuracy of Lightweight Satellite
Telemetry: a Case Study in the Iberian Peninsula. *Journal of Wildlife Management*
71:1010-1015. 10.2193/2006-042
Thomas B, Holland JD, and Minot EO. 2012. Wildlife tracking technology options and cost
considerations. *Wildlife Research* 38:653-663. 10.1071/WR10211
Wickham H, Francois R, Henry L, and Müller K. 2018. dplyr: A grammar of data manipulation. v
0.7.6. R package. https://CRAN.R-project.org/package=dplyr.
Witt MJ, Åkesson S, Broderick AC, Coyne MS, Ellick J, Formia A, Hays GC, Luschi P, Stroud S,
and Godley BJ. 2010. Assessing accuracy and utility of satellite-tracking data using Argos-
linked Fastloc-GPS. *Animal Behaviour* 80:571-581. 10.1016/j.anbehav.2010.05.022
500
501

FIGURES

Figure 1 - Trial sites for the motion-controlled tests within Romania (static, low-speed, highspeed).

Figure 2 - Cumulative distribution of Argos location errors (km) partitioned by Argos location classes (LC). The 68th percentile of
measured errors is larger than the 68th percentile provided by Argos CLS for error bounded LCs (upper error LC 3, LC 2 and LC1).

Figure 3 - Mean (±95% CI) fitted values for the best mixed-effects model predicting Argos location errors by Motion and Place
(trial site).

Figure 4 - Effectiveness of Douglas Argos filter (DAR) in moderating Argos location errors by location class. NoF = unfiltered data,
DAR 2 = Douglas Argos DAR with MAXREDUN = 2 km, DAR 15 = Douglas Argos DAR with MAXREDUN = 15 km.

Figure 5 - Latitudinal and longitudinal errors (km from GPS locations) for LC 0, LC A, LC B, and all LCs (red = rejected Argos locations; blue = accepted Argos locations).

S Fig 1 - Latitudinal and longitudinal locations errors (km from GPS locations) for A) all data and B) Argos locations with errors
under 20 km from GPS locations.

S Fig 2 - Magnitude and frequency of Argos errors relative to GPS locations. The first three intervals of error magnitude resemble
upper bound errors for LC 3, LC 2 and LC 1.

S Fig 3 - Effectiveness of Douglas Argos DAR filter in moderating Argos location errors by location class.

TABLES

Table 1 - Location error metrics for all Argos location classes (3705 valid locations received on four trial sites within Romania,
during three motion-controlled tests).

Location class	Sample size	Mean error (stdev), meters	68[th] percentile of errors, meters	Mean error longitude (stdev), meters	Mean error latitude (stdev), meters	% locations in error ellipse	% locations out of error ellipse
LC 3	528	578.61 (802.52)	520.85	466.71 (744.47)	254.79 (375.95)	10.42	89.58
LC 2	520	1230.64 (1281.56)	1383.81	969.24 (1099.82)	580.09 (818.49)	4.62	95.38
LC 1	674	2222.78 (2466.15)	2280.64	1784.74 (2158.28)	1010.66 (1467.00)	5.64	94.36
LC 0	376	7127.17 (14869.71)	5877.38	6195.25 (14492.92)	2630.38 (4064.45)	11.17	88.23
LC A	505	3669.57 (6816.14)	2981.35	2894.15 (6484.07)	1622.35 (2617.89)	9.90	90.10
LC B	1102	5717.70 (10456.50)	4820.25	4444.84 (9611.44)	2739.37 (4725.23)	28.04	71.96
Total	3705	3583.66 (8225.96)	2758.73	2872.49 7677.608	1604.44 (3272.32)	13.98	86.02

535 *Table 2 - Summary of best mixed effect model (log errors ~ Motion – 1 + Place + (1|Satellite/Reception point). Saveni trial site is*
536 *kept as reference.*

Parameter	β	SE	t-value	Lower CI	Upper CI
Static	2.89	0.06	48.35	2.771	3.016
Low-speed	0.38	0.03	11.74	0.319	0.446
High-speed	0.57	0.03	17.08	0.501	0.630
Bucharest	-0.03	0.04	-0.90	-0.103	0.038
Iron Gates	0.13	0.04	3.65	0.061	0.205
Sighisoara	-0.02	0.04	-0.45	-0.093	0.058

539 *Table 3 - Location error metrics in the three motion-controlled tests carried out within Romania*

Motion	Sample size	Mean error (stdev), meters	Mean error longitude (stdev), meters	Mean error latitude (stdev), meters	% locations in error ellipse	% locations out of error ellipse
Static	1496	2708.84 (9588.76)	2315.32 (9215.04)	1042.22 (2810.01)	16.51	81.68
Low-speed	1137	3779.73 (7779.31)	2879.02 (6871.40)	1851.93 (3977.74)	11.96	88.04
High-speed	1099	4550.15 (6381.86)	3610.44 (5958.59)	2099.89 (2909.25)	12.28	87.72

542   *Table 4 - Location error metrics in the four trial sites within Romania.*

Place (trial site)	Sample size	Mean error (stdev), meters	Mean error longitude (stdev), meters	Mean error latitude (stdev), meters	% locations in error ellipse	% locations out of error ellipse
Saveni	1106	3122.01 (5862.75)	2489.22 (5427.42)	1410.09 (2539.10)	13.29	86.71
Bucharest	969	3311.57 (7146.49)	2595.00 (6438.32)	1545.76 (3379.37)	16.10	83.90
Sighisoara	734	3277.75 (6439.44)	2615.05 (5982.89)	1529.57 (2690.64)	12.26	87.74
Iron Gates	896	4698.35 (12113.6)	3856.52 (11495.36)	1969.13 (4229.34)	13.95	86.05

546
547
548

S Table 1 -Model selection for the mixed effects model of Argos locations errors. Place = trial sites, motion = static, low-speed, high-speed, TRI = terrain ruggedness index, 1 = baseline model, AICc = Akaike's Information Criterion corrected for small sample size. The random effects part includes reception points nested in the satellite providing the respective location.

Model fixed factors	df	AIC_c	AIC_cwt	weight
Place + Motion	9	4831.7	0.00	0.685
Motion	6	4834.1	2.44	0.202
Place + Motion + TRI	10	4835.3	3.61	0.113
Place × Motion	15	4846.9	15.19	< 0.001
Place × Motion + TRI	16	4850.5	18.83	< 0.001
1 (null model)	4	5078.7	247.07	< 0.001
Place	7	5085.2	253.53	< 0.001

551 *S Table 2 - Location error metrics by Argos location class (LC) after filtering with Douglas Argos DAR filter MAXREDUN = 2 km*
552 *(DAR 2).*

Location class	% locations retained	Mean error (stdev), meters	68th percentile of errors, meters	Mean error longitude (stdev), meters	Mean error latitude, (stdev) meters	% locations in error ellipse retained	% locations out of error ellipse retained
LC 3	96.02	567.53 (798.32)	507.96	456.28 (744.12)	249.71 (366.92)	96.36	95.98
LC 2	90.38	1198.12 (1295.45)	1337.51	936.48 (1100.64)	570.29 (835.83)	95.83	90.12
LC 1	85.46	1996.58 (2351.56)	2108.89	1589.89 (2039.98)	915.01 (1408.85)	97.37	84.75
LC 0	68.35	3907.59 (4124.47)	4667.51	3233.44 (4018.79)	1646.00 (1719.10)	97.37	65.86
LC A	80.00	2441.70 (3190.12)	2534.84	1844.42 (2948.79)	1183.93 (1622.59)	84.00	79.56
LC B	82.66	3554.50 (3880.18)	3641.73	2649.74 (3465.52)	1862.83 (2275.08)	89.32	84.29
Total	84.35	2313.51 (3134.67)	2252.89	1784.746 (2788.20)	1126.42 (1715.18)	90.93	82.26

555 *S Table 3 - Location error metrics by Argos location class (LC) after filtering with Douglas Argos DAR filter MAXREDUN = 15 km*
556 *(DAR 15).*

Location class	% locations retained	Mean error (stdev), meters	68th percentile of errors, meters	Mean error longitude (stdev), meters	Mean error latitude, (stdev) meters	% locations in error ellipse retained	% locations out of error ellipse retained
LC 3	97.35	580.40 (806.93)	525.80	466.73 (747.80)	257.20 (379.84)	98.18	97.25
LC 2	97.88	1239.32 (1289.91)	1392.26	976.06 (1106.08)	583.57 (825.63)	95.83	97.98
LC 1	96.74	2201.28 (2478.88)	2268.96	1765.88 (2163.2)	998.19 (1480.09)	100	96.54
LC 0	90.42	4783.05 (5281.87)	5255.86	3949.20 (5050.06)	2020.31 (2360.83)	95.24	89.82
LC A	93.86	2763.46 (3247.40)	2824.62	2063.67 (2993.83)	1365.62 (1757.32)	88	94.51
LC B	92.92	4095.57 (4665.61)	4331.42	3061.02 (4260.98)	2130.64 (2541.18)	94.82	92.18
Total	94.82	2702.64 (3732.31)	2629	2090.37 (3358.29)	1308.30 (1965.46)	94.98	94.79