**Title:**

Tree-sequence recording in SLiM opens new horizons for forward-time simulation of whole
genomes

**Running Title:** Tree-sequence recording in SLiM

**Authors:**

Benjamin C. Haller ‡
Dept. of Biological Statistics and Computational Biology
Cornell University, Ithaca, NY 14853, USA
9
10  Jared Galloway
11  Institute of Ecology and Evolution
12  University of Oregon, Eugene, OR 97403, USA
13
14  Jerome Kelleher
15  Big Data Institute, Li Ka Shing Centre for Health Information and Discovery
16  University of Oxford
17  Oxford, OX3 7FZ, UK
18
19  Philipp W. Messer *
20  Dept. of Biological Statistics and Computational Biology
21  Cornell University, Ithaca, NY 14853, USA
22
23  Peter L. Ralph ‡ *
24  Institute of Ecology and Evolution
25  University of Oregon, Eugene, OR 97403, USA
26
27  ‡ Corresponding authors
28  * Joint senior authors

29  **Corresponding Authors:**

30  Benjamin C. Haller, bhaller@benhaller.com
31  Peter Ralph, plr@uoregon.edu

## Abstract

There is an increasing demand for evolutionary models to incorporate relatively realistic

dynamics, ranging from selection at many genomic sites to complex demography, population

structure, and ecological interactions. Such models can generally be implemented as individual-

based forward simulations, but the large computational overhead of these models often makes

simulation of whole chromosome sequences in large populations infeasible. This situation

presents an important obstacle to the field that requires conceptual advances to overcome. The

recently developed tree-sequence recording method (Kelleher et al., 2018), which stores the

genealogical history of all genomes in the simulated population, could provide such an advance.

This method has several benefits: (1) it allows neutral mutations to be omitted entirely from

forward-time simulations and added later, thereby dramatically improving computational

efficiency; (2) it allows neutral burn-in to be constructed extremely efficiently after the fact, using

"recapitation"; (3) it allows direct examination and analysis of the genealogical trees along the

genome; and (4) it provides a compact representation of a population's genealogy that can be

analyzed in Python using the msprime package. We have implemented the tree-sequence

recording method in SLiM 3 (a free, open-source evolutionary simulation software package) and

extended it to allow the recording of non-neutral mutations, greatly broadening the utility of this

method. To demonstrate the versatility and performance of this approach, we showcase several

practical applications that would have been beyond the reach of previously existing methods,

opening up new horizons for the modeling and exploration of evolutionary processes.

## Keywords

pedigree recording, coalescent, background selection, genealogical history, selective sweeps, tree sequences

## Introduction

Forward simulations are increasingly important in population genetics and evolutionary biology. For example, they can be useful for modeling the expected evolutionary dynamics of real-world systems (Fournier-Level et al., 2016; Cotto et al., 2017; Matz et al., 2018; Ryan et al., 2018), for discovering the ecological and evolutionary mechanisms that led to present-day genomic patterns in a species (Enard et al., 2014; Nowak et al., 2014; Arunkumar et al., 2015; Patel et al., 2018), for testing or validating empirical and statistical methods (Haller and Hendry, 2013; Caballero et al, 2015; Ewing et al., 2016; Haller and Messer, 2017a), and for exploring theoretical ideas about evolution (Haller et al., 2013; Assaf et al., 2015; Mafessoni and Lachmann, 2015; Champer et. al, 2018), among other purposes. Because of this broad utility, there is a growing desire to run simulations with increased realism in a variety of areas: longer genomic regions up to the scale of full genome sequences, large populations, selection at multiple loci with linkage effects, complex demography, ecological interactions with other organisms and the environment, explicit space with continuous landscapes, spatial variation in environmental variables, spatial interactions such as competition and mate choice between organisms, and so forth.

However, this type of realism comes at a price, in both processing time and memory usage. Since computational resources are finite, this can often make it difficult or, in practical terms, impossible to run some models. Advances in computing power have gradually extended the boundaries of what is possible, as have performance improvements due to improved forward simulation software (Messer, 2013; Thornton, 2014; Haller and Messer, 2017b), but computational overhead continues to hold back progress in the field by limiting the level of realism that can be attained in models.

From this perspective, the recently developed pedigree recording or "tree-sequence recording"

method (Kelleher et al., 2018) is potentially transformative.  Kelleher et al. (2018) have shown

that, perhaps counterintuitively, the recording of all ancestry information for the entire population

can actually improve the runtime by orders of magnitude.  These gains in efficiency are made

possible by the succinct tree sequence data structure (or "tree sequence", for brevity) that lies at

the heart of the msprime coalescent simulator (Kelleher et al., 2016), subsequently refined in

Kelleher et al. (2018).  The tree sequence data structure is a concise encoding of the correlated

genealogies along a chromosome resulting from evolution in sexually reproducing populations

(Figure 1).  The sequence of trees along a genome has been studied for some time (Hudson,

1983), and is closely linked to the concept of an "Ancestral Recombination Graph" or ARG

(Griffiths, 1991; Griffiths & Marjoram, 1997).  The use of the term "ARG" has historically been

ambiguous, however, sometimes referring to the stochastic process generating these trees, rather

than the resulting tree sequence itself, so we use the term "tree sequence" here to refer to this

sequence of trees in the particular representation described by Kelleher et al. (2016, 2018).

Precisely the same tree sequence data structure can be used to record each generation's parent–

child relationships.  This data structure will then record who each individual inherited each

section of chromosome from, for every individual that ever lived.  However, there is a massive

amount of redundancy in this information, since many of the individuals simulated in the past

will leave no descendants in the extant population.  The key insight of Kelleher et al. (2018) was

to provide an efficient algorithm to remove this redundancy by periodically "simplifying" the tree

sequence.  This combination – the tree sequence data structure and an efficient algorithm for

simplifying it – allows complete genealogies for all extant individuals to be recorded efficiently

in forward simulations for the first time.

The most immediate advantage of recording a tree sequence during forward simulation is that it

allows neutral mutations to be omitted entirely; neutral mutations can simply be overlaid onto the

tree sequence after forward simulation has completed, because by definition they do not affect the

genealogies. This provides an immense efficiency benefit, since neutral mutations then only need

to be added along those branches of the tree from which the individuals of interest at the end of

the simulation have inherited; all other ancestral branches, which typically comprise the vast

majority of the full tree, can be ignored since they do not contribute to those individuals. Given

that many forward simulations spend the large majority of their time managing neutral mutations,

with considerable bookkeeping overhead in each generation, neutral mutation overlay following

forward simulation has been shown to improve performance by an order of magnitude or more

while producing provably statistically identical results (Kelleher et al., 2018).

A second advantage of recording genealogies is that the recorded tree sequence from a forward

simulation can be used as the basis for the construction of a neutral "burn-in" history for the

simulated population after forward simulation is complete, using (usually much faster) coalescent

simulation. The burn-in period of a simulation can be immensely time-consuming, often taking

much longer than the simulation of the evolutionary dynamics that are actually of interest; the

overhead of burn-in can therefore present a large obstacle for many models. With a method that

we call "recapitation", we can leverage the information in the tree sequence to prepend a

coalescent simulation of the burn-in period, speeding up the burn-in process by many orders of

magnitude.

A third important advantage is that the pattern of ancestry and inheritance is in itself very

useful. For many statistics of interest, and in particular for inferring specific events that occurred

in the past, sequence-based data from mutations is essentially an extra layer of noise over the

signal of interest contained in the genealogies. Direct access to the precise genealogical history

of the simulated population allows the signal to be analyzed without the noise, gaining significant

statistical power. An expanding set of open-source tools makes it possible to load, analyze, and

even manipulate a recorded tree sequence using simple Python code, allowing open-ended

flexibility in analysis.

A fourth compelling advantage is that the recorded tree sequence files are very small and

enable very efficient calculation of population-genetic statistics (Kelleher et al. 2016, 2018). The

files output from even the largest simulations are rarely bigger than a few hundred megabytes,

and may be tens of thousands of times smaller than alternatives such as VCF and Newick.

Despite this high level of compression, tree sequences can be processed very efficiently; statistics

of interest such as allele frequencies within cohorts can often be computed incrementally, leading

to very efficient algorithms (Kelleher et al. 2016). Calculation of statistics of this sort from

simulated data can be very time-consuming, especially when long genomes are involved and

many replicate simulation runs have been performed, so the ability to speed up such calculations

is quite important.

Given these advantages, we have worked to integrate tree-sequence recording into SLiM 3, a

new major release of the free, open-source SLiM simulation software package

(http://messerlab.org/slim/). It is now possible to enable tree-sequence recording in any SLiM

model with a simple flag set in the model's script, and then to output the recorded tree sequence

at any point in the simulation. In addition, we have extended the original tree-sequence recording

method (Kelleher et al. 2018) to allow for the recording of mutations during forward simulation.

This allows the tree-sequence output format, a `.trees` file, to be used in SLiM as a way of saving

and then restoring the state of a simulation while preserving information about ancestry, and

allows the mutations that occurred during forward simulation to be accessed later in Python-based

analyses.

To illustrate the large advantages provided by tree-sequence recording, and to show how to

take advantage of those benefits when using SLiM for forward simulation, we will present four

practical examples of the method. In the first example, we will show the impressive performance

benefits that can be achieved with tree-sequence recording compared to a classical forward

simulation. The second example will use tree-sequence recording to efficiently simulate

background selection near genes undergoing deleterious mutations, quantifying the expected

effect of background selection on levels of neutral diversity by measuring the heights of trees in

the recorded tree sequence. Our third example will be a model of admixture between two

subpopulations, showing how to use the recorded tree sequence in calculating the mean true local

ancestry at every position along a chromosome. Finally, the fourth example will illustrate how

the "recapitation" method allows msprime to be used to extremely efficiently add a "neutral burn-

in" history to a completed SLiM simulation of a selective sweep, by coalescing the simulation's

initial population backward in time.

**Examples**

Examples were executed on a MacBook Pro (2.9 GHz Intel Core i7, 16 GB RAM) running

macOS 10.13.5, using Python 3.4.8, R 3.5.0, SLiM 3.1, msprime 0.6.1, and pyslim 0.1. Reported

times were measured with the Python `timeit` package. Peak memory usage for SLiM runs was

assessed with SLiM's –m command-line option. The timing comparison (Figure 2) was executed

on the same hardware, with macOS 10.13.4, R 3.4.3, SLiM 3.0, and msprime 0.6.0, using the

Un*x tool `/usr/bin/time` for timing (summing the reported user time and system time); we

believe the times measured would not change significantly with the newer software versions.  The

full source code for the examples and timing tests, including timing and plotting code that is

omitted here, may be found at https://github.com/bhaller/SLiMTreeSeqPub.  These examples use

the `matplotlib` (Hunter, 2007) and `numpy` (Oliphant, 2006) packages for Python.

*Example I: A simple neutral model*

Our first example is a model of a neutrally evolving chromosome of length $L = 10^8$ base

positions, with uniform mutation rate $\mu = 10^{-7}$ and recombination rate $r = 10^{-8}$ (both expressed as

the event probability per base per generation), in a panmictic diploid population of size $N = 500$,

running for a duration of $10N = 5000$ non-overlapping generations.  The SLiM configuration

script for this basic model is very simple:

```
178     initialize() {
179        initializeMutationRate(1e-7);
180        initializeMutationType("m1", 0.5, "f", 0.0);
181        initializeGenomicElementType("g1", m1, 1.0);
182        initializeGenomicElement(g1, 0, 1e8-1);
183        initializeRecombinationRate(1e-8);
184     }
185     1 {
186        sim.addSubpop("p1", 500);
187     }
188     5000 late() {
189        sim.outputFull("ex1_noTS.slimbinary", binary=T);
190     }
```

This sets up a single "genomic element" spanning the full length of the chromosome, with

neutral mutations of type `m1` generated at the desired rate, and with the desired recombination

rate.  In generation 1 a new subpopulation of the desired size is created, and the model runs to

generation 5000, after which it outputs the full simulation state.  The SLiM manual provides

additional explanation of these concepts (Haller and Messer, 2016). This model took 211.9

seconds to run, and reached a peak memory usage of 443.8 MB.

Tree-sequence recording can easily be enabled for this model with a call to

`initializeTreeSeq()`:

```
199  initialize() {
200     initializeTreeSeq();
201     initializeMutationRate(0);
202     initializeMutationType("m1", 0.5, "f", 0.0);
203     initializeGenomicElementType("g1", m1, 1.0);
204     initializeGenomicElement(g1, 0, 1e8-1);
205     initializeRecombinationRate(1e-8);
206  }
207  1 {
208     sim.addSubpop("p1", 500);
209  }
210  5000 late() {
211     sim.treeSeqOutput("ex1_TS.trees");
212  }
```

Note that we have now also set the mutation rate to zero; SLiM no longer needs to model

neutral mutations because they can be overlaid in a later step more efficiently. A `.trees` file is

output at the end of the run, instead of calling SLiM's `outputFull()` method, so that the recorded

tree sequence is preserved. In all other respects these models are identical. This is typical of

adapting a SLiM model to use tree-sequence recording: in general, the aim is to remove the

modeling of neutral mutations while preserving other aspects of the model verbatim.

After simulation has completed, neutral mutations are overlaid upon the saved tree sequence.

The full model – running the SLiM model and then doing the final mutation overlay step – can be

executed with a simple Python script:

```
222  import subprocess, msprime, pyslim
223
224  # Run the SLiM model
225  subprocess.check_output(["slim", "-m", "-s", "0", "ex1_TS.slim"])
226
227  # Overlay neutral mutations
228  ts = pyslim.load("ex1_TS.trees")
229  mutated = msprime.mutate(ts, rate=1e-7, random_seed=1, keep=True)
230  mutated.dump("ex1_TS_overlaid.trees")
```

This script uses the msprime Python package to overlay neutral mutations upon the recorded

tree sequence.  The result is precisely the same, statistically, as if the neutral mutations were

included in the forward simulation, except that the vast majority of the bookkeeping work in each

generation is avoided because mutations only need to be overlaid upon the ancestral genomic

regions that persisted to the end of the simulation.

Note that pyslim is used to load the `.trees` file; this package provides a bridge between SLiM

and msprime, and should generally be used to load and save `.trees` files in Python if the files are

coming from or going to SLiM.  The pyslim package extends the msprime tree sequence class by

adding support for SLiM's metadata annotations to the tree sequence, providing an interface for

reading or modifying that metadata as well as for generating SLiM-compliant `.trees` files that

contain the required metadata.  The `.trees` files output by SliM can be read directly by msprime,

but the returned object will have reduced functionality compared to those returned by pyslim.

The total time to execute this Python code is 4.37 seconds, almost 50 times faster than the

model without tree-sequence recording.  Most of the runtime (4.09 seconds) is spent running the

SLiM model; the final mutation overlay by msprime is extremely fast.  The peak memory usage

during the SLiM run is 145.8 MB, less than one-third of the memory usage of the model without

tree-sequence recording.  Tree-sequence recording can often reduce memory usage, since the tree

sequence data structure is quite compact compared to SLiM's in-memory representation of the

neutral mutations that would be segregating in such a model.  Tree sequences are also very

compact on disk; the final `.trees` file here, with mutations overlaid, takes about 8.9 MB, as

compared to 84.2 MB for the `ex1_noTS.slimbinary` file from the SLiM model without tree-

sequence recording, 559 MB for a Newick file, and 366 MB for a VCF file – even though the

`.trees` file contains ancestry information not included by the SLiM and VCF formats. A VCF

file containing the sequences of the final generation can be produced from a `.trees` file with

msprime's `write_vcf()` method, but the ancestry information is lost.

The speedup produced by this tree-sequence recording method can vary dramatically

depending upon the details of the simulation; all of the work to track neutral mutations is

eliminated, but new work is added involving the recording of all the recombination events that go

into producing the tree sequence. In general, the largest speedup will be observed with very long

chromosomes with many neutral mutations when the recombination rate is not too high; indeed,

when modeling a very short chromosome the overhead of tree-sequence recording can outweigh

the savings from omitting neutral mutations (see Discussion).

To further illustrate the performance benefits of tree-sequence recording, we conducted a set of

timing comparisons between SLiM without tree-sequence recording, SLiM with tree-sequence

recording, and msprime's coalescent simulation method. These comparisons involved essentially

the same model as shown above: a neutral panmictic model of diploids with non-overlapping

generations, with a population size $N = 500$, recombination rate $r = 10^{-8}$ per base position per

generation, and mutation rate $\mu = 10^{-7}$ per base position per generation. The chromosome length

$L$ was varied over $\{10^5, 10^6, 10^7, 10^8, 10^9, 10^{10}\}$, with ten runs of each model at each value of $L$

using different random seeds. The number of generations varied with $L$ (details below). The

msprime coalescent was run both with a final haploid sample size $n$ equal to the full population

size ($n = 2N$), and with a much smaller sample size ($n = 2N/100$); in both cases, $N_e = N$ was used.

To verify that tree-sequence recording produced results equivalent to the coalescent, we checked

that the mean TMRCAs for the $L = 10^{10}$ runs for the two methods did not differ significantly

($p = 0.7791$).

The average runtimes obtained are shown in Figure 2. As $L$ increased, the benefit of tree-

sequence recording compared to SLiM without tree-sequence recording became increasingly

large, topping out at a performance improvement of more than two orders of magnitude for

$L = 10^9$ and $L = 10^{10}$. Coalescent simulations with msprime were much faster than the tree-

sequence recording method, as expected, except at $L = 10^{10}$, where msprime's speed was

comparable to that of SLiM with tree-sequence recording. It appears that SLiM with tree-

sequence recording would be faster for $L$ larger than $10^{10}$. The number of events the coalescent

must simulate is quadratic in $L$, empirically, but with a small leading coefficient such that

msprime is quite fast even for reasonably large chromosome sizes (Kelleher et al. 2016). With

very large values of $L$, however, this $O(L^2)$ term begins to dominate and SLiM with tree-sequence

recording becomes faster. This may be chiefly of theoretical interest, since $L = 10^{10}$ is already a

very long chromosome (approximately three times the length of the full human genome). It is

also noteworthy that the msprime coalescent is only marginally faster for a sample of $n = 2N/100$

than for a full population sample of $n = 2N$; as more samples are added to a gene tree, the new

samples tend to attach to already existing branches quite quickly (Kingman, 1982).

Although the coalescent remains an order of magnitude faster for most practical purposes, it

can only be used in a few simple scenarios such as this; for models that require forward

simulation, tree-sequence recording offers large performance benefits over more traditional

forward simulation techniques. It is also worth noting that the coalescent is only an

approximation of the Wright–Fisher model, and will diverge from it under certain conditions

(Wakeley et al., 2012; Bhaskar et al., 2014) – one such condition being a sample size that is no

longer small compared to the population size, as is the case for our $n = 2N$ msprime runs here.

Forward simulation may therefore be preferable in order to obtain exact results under such

conditions.

**How long do we run it?**  In general, it is desirable to run forward-time simulations "until

convergence" – until the effects of the starting configuration are forgotten.  This occurs (in most

situations) when all genealogical trees have coalesced, meaning that at every position in the

genome a common ancestor to the entire final generation has appeared.  In practice, models are

often run for $10N$ generations, a rule of thumb that is thought to suffice in most cases.  However,

this is a thorny problem: longer chromosomes tend to require longer for coalescence, simply

because with more sites it is more likely that coalescence takes exceptionally long at some site.

In the simulations of Figure 2, we ran each simulation for the expected number of generations

required for coalescence at that value of $L$, which increased linearly with $\log(L)$, from about $3N$

for $L = 1e5$ to $15N$ for $L = 1e10$.  This sufficed to make the comparison between SLiM and

msprime "fair", but a better practical solution, recapitation, will be shown in Example 4.  We

determined the expected number of generations empirically by running the same model 500 times

at each value of $L$ with "coalescence detection" enabled (by passing `checkCoalescence=T` to

`initializeTreeSeq()`). The mean and other summary statistics for each value of $L$ (Table S1)

agree with expectations from extreme value theory (Berman, 1964), with the expected time until

coalescence growing roughly as $1000 \log(L) - 10000$.

*Example II: Background selection*

Our second example is a model of background selection, a term which describes the effect that

purifying selection against deleterious mutations imposes on genetic variation at linked sites.

Such purifying selection should be particularly common in genic regions, where many genomic

positions should be subject to selective constraints. This background selection, like many types

of linked selection more generally, is expected to produce a "dip in diversity" in the surrounding

non-coding regions, with a signature of decreasing genetic diversity with decreasing distance to

the nearest gene (Charlesworth et al. 1993; Hudson 1994; Sattath et al., 2011; Elyashiv et al.,

2016). Here is a SLiM model that uses tree-sequence recording to model this scenario:

```
325    initialize() {
326      defineConstant("N", 10000);  // pop size
327      defineConstant("L", 1e8);    // total chromosome length
328      defineConstant("L0", 200e3); // between genes
329      defineConstant("L1", 1e3);   // gene length
330      initializeTreeSeq();
331      initializeMutationRate(1e-7);
332      initializeRecombinationRate(1e-8, L-1);
333      initializeMutationType("m2", 0.5, "g", -(5/N), 1.0);
334      initializeGenomicElementType("g2", m2, 1.0);
335
336      for (start in seq(from=L0, to=L-(L0+L1), by=(L0+L1)))
337          initializeGenomicElement(g2, start, (start+L1)-1);
338    }
339    1 {
340      sim.addSubpop("p1", N);
341      sim.rescheduleScriptBlock(s1, 10*N, 10*N);
342    }
343    s1 10 late() {
344      sim.treeSeqOutput("ex2_TS.trees");
345    }
```

This model sets up a chromosome that consists of genes of length $L_1 = 1$ kb, separated by non-

coding regions of length $L_0 = 200$ kb. The total chromosome length is $L = 10^8$ bases, and 496

genes fit within it. The model uses a mutation rate of $\mu = 10^{-7}$ for deleterious mutations that can

arise within the genes; no other mutations are modeled. The deleterious mutations are given

selection coefficients drawn from a Gamma distribution with mean $-5/N$ and shape parameter

$\alpha = 1$ (modeling a scenario of moderately deleterious mutations with $2Ns = -10$ on average). We

assume co-dominance with $h = 0.5$. A population of size $N = 10000$ is started in generation 1,

and the model runs until generation $G = 10N$ (the output event, `s1`, is rescheduled dynamically to

that generation).

We can run this model and then conduct post-run analysis with a Python script:

```python
import os, subprocess, msprime, statistics, pyslim
import matplotlib.pyplot as plt
import numpy as np

# Run the SLiM model and load the resulting .trees file
subprocess.check_output(["slim", "-m", "-s", "0", "ex2_TS.slim"])
ts = pyslim.load("ex2_TS.trees").simplify()

# Measure the tree height at each base position
height_for_pos = np.zeros(int(ts.sequence_length))
for tree in ts.trees():
    mean_height = statistics.mean([tree.time(root) for root in tree.roots])
    left, right = map(int, tree.interval)
    height_for_pos[left: right] = mean_height

# Convert heights along the chromosome into heights at distances from a gene
height_for_pos = height_for_pos - np.min(height_for_pos)
L, L0, L1 = int(1e8), int(200e3), int(1e3)
gene_starts = np.arange(L0, L - (L0 + L1) + 1, L0 + L1)
gene_ends = gene_starts + L1 - 1
max_distance = L0 // 4
height_for_left_distance = np.zeros(max_distance)
height_for_right_distance = np.zeros(max_distance)
for d in range(max_distance):
    height_for_left_distance[d] = np.mean(height_for_pos[gene_starts - d - 1])
    height_for_right_distance[d] = np.mean(height_for_pos[gene_ends + d + 1])
height_for_distance = np.hstack([height_for_left_distance[::-1],
        height_for_right_distance])
distances = np.hstack([np.arange(-max_distance, 0), np.arange(1, max_distance + 1)])

# Make a simple plot
plt.plot(distances, height_for_distance)
plt.show()
```

The first line after the import statement runs the SLiM model; this took 15643 seconds (4.35

hours) to execute. This is not short – it is still a fairly complex model! – but it is far shorter than

the alternative, a SLiM model without tree-sequence recording and including neutral mutations in

the non-coding regions. That alternative model would take ~83 hours, by extrapolation –

probably a conservative estimate, since the model had not yet reached mutation–selection balance

and was still slowing down when its timing was measured. The use of tree-sequence recording

here results, then, in a relatively modest speedup of 19 times. This makes sense, since the model

with tree-sequence recording still must keep track of a very large number of segregating

deleterious mutations. However, it is worth noting that the final result from this alternative

model would provide far less statistical power, since inference from it would be based only upon

the observed pattern of neutral mutations in one run, rather than the actual pattern of ancestry at

each chromosome position; to provide the same power, this alternative model would likely have

to be run many times or use a much higher mutation rate. If more performance gains were

needed, the model could perhaps be rescaled as well (see Discussion).

The rest of the code conducts post-run analyses. First, the `.trees` file from the SLiM run is

read in with `pyslim.load()` as in the previous example; here, however, we call `simplify()`

(Kelleher et al. 2018) upon the loaded tree sequence, which requires some explanation. SLiM

automatically retains, in the tree sequence, nodes corresponding to the original ancestors of each

subpopulation that was created with `addSubpop()`. This is done for various reasons, including

allowing ancestry to be more easily traced and enabling recapitation (see Example 4). When

SLiM saves a `.trees` file, these ancestors are present in the tree sequence but are not marked as

"samples", and will therefore disappear after a `simplify()` operation. In many cases these

ancestors are harmless, as in Example 1; in fact, in Example 1, calling `simplify()` to remove

them would mean that mutations would be overlaid only back to the point of coalescence, rather

than to the beginning of forward simulation. Here, however, since we want to measure the

heights of trees in the tree sequence, these ancestors would complicate things for us; all trees

would be rooted in those ancestors, at the beginning of forward simulation. We therefore call

`simplify()` to remove them (when the model has coalesced below them; they are retained when

still in use by the tree sequence). Example 4 will delve into this matter further.

Next, a vector containing the mean tree height at each base position (`height_for_pos`) is

constructed by walking through the tree sequence to find the set of trees representing the ancestry

of every individual in the final generation at a given position. The mean tree height is a metric of

the time to the most recent common ancestor at a given base position, and thus of diversity at that

base position; background selection will tend to reduce the mean tree height, thereby lowering the

expected levels of diversity at a locus.

An aside: there can be a set of trees for a given position, rather than just a single tree, if the

forward simulation was not run sufficiently long for coalescence to have occurred at every

position in the genome. In msprime this is modelled by allowing trees to have multiple roots.

Each root represents the most recent common ancestor of some subset of the extant population at

that location in the genome; if coalescence has not occurred, then the final population should still

contain genetic variation that was segregating in the initial population, since different individuals

inherit from different roots of the ancestry tree. Since the model here ran for $10N$ generations, we

can hope that it has coalesced at most or all positions; but unless a model is explicitly run out to

coalescence (or recapitated), it is always possible that multiple roots will exist, and so robust code

ought to handle that case by looping over the roots for each tree as we do here.

These mean tree heights along the chromosome are then converted to mean tree heights at

distances from the nearest gene (`height_for_distance`), taking into account the somewhat

complex genetic structure of the model. Finally, the relationship between distance to the nearest

gene and tree height is plotted. These analyses took 12.39 seconds to complete. Note that neutral

mutations were never simulated at all; the analysis is based upon the tree sequence itself, not

upon the distribution of neutral mutations.

A plot of the results can be seen in Figure 3, showing the well-known "dip in diversity"

realized here through simulation. As the distance to the nearest gene decreases, diversity dips due

to the background selection exerted by selection against deleterious mutations within the gene.

*Example III: True local ancestry mapping*

Our third example involves mapping the true local ancestry at every position along a

chromosome in a two-subpopulation admixture model with adaptive introgression at two partially

linked loci. This is an important dynamic in all sorts of biological systems, from human–

Neanderthal admixture to hybrid zones between divergent bird populations; one often wishes to

be able to find which ancestral population each chromosomal region traces back to. The SLiM

model looks like this:

```
450        initialize() {
451           defineConstant("L", 1e8);
452           initializeTreeSeq();
453           initializeMutationRate(0);
454           initializeMutationType("m1", 0.5, "f", 0.1);
455           initializeGenomicElementType("g1", m1, 1.0);
456           initializeGenomicElement(g1, 0, L-1);
457           initializeRecombinationRate(1e-8);
458        }
459        1 late() {
460           sim.addSubpop("p1", 500);
461           sim.addSubpop("p2", 500);
462           sim.treeSeqRememberIndividuals(sim.subpopulations.individuals);
463
464           p1.genomes.addNewDrawnMutation(m1, asInteger(L * 0.2));
465           p2.genomes.addNewDrawnMutation(m1, asInteger(L * 0.8));
466
467           sim.addSubpop("p3", 1000);
468           p3.setMigrationRates(c(p1, p2), c(0.5, 0.5));
469        }
470        2 late() {
471           p3.setMigrationRates(c(p1, p2), c(0.0, 0.0));
472           p1.setSubpopulationSize(0);
473           p2.setSubpopulationSize(0);
474        }
475        2: late() {
476           if (sim.mutationsOfType(m1).size() == 0)
```

```
477        {
478            sim.treeSeqOutput("ex3_TS.trees");
479            sim.simulationFinished();
480        }
481    }
482    10000 late() {
483        stop("Did not reach fixation of beneficial alleles.");
484    }
```

The `initialize()` callback sets up tree-sequence recording with a mutation rate of $\mu = 0$ and a

recombination rate of $r = 10^{-8}$ along a chromosome of length $L = 10^8$. Although the mutation rate

is zero, a mutation type `m1` is defined representing beneficial mutations with a selection

coefficient of $s = 0.1$; mutations of this type will be added in generation 1.

In generation 1 we create two subpopulations, `p1` and `p2`, of 500 individuals each; these are the

original subpopulations that will admix. We tell SLiM to remember these individuals forever as

ancestors in the tree sequence, with `treeSeqRememberIndividuals()`, because we want them to

act as the roots of all recorded trees so that we can establish local ancestry using them. Note that

this is not strictly necessary, since (as discussed in Example 2) SLiM automatically retains the

root ancestors for each population; we could rely upon that, and we would be fine as long as we

did not `simplify()` after loading the tree sequence in Python. The use of

`treeSeqRememberIndividuals()` has been shown here for purposes of illustration, however,

since some models may wish to remember non-root individuals for analysis. Next, we add a

beneficial mutation at $0.2L$ in `p1`, and another at $0.8L$ in `p2`; the expectation is that by the end of

the run all individuals will be recombinants that carry both of these mutations. Finally, we create

subpopulation `p3` and tell SLiM that it will be composed entirely of migrants from `p1` and `p2` in

equal measure.

By the end of generation 2, subpopulation `p3` has received its offspring generation from `p1` and

`p2` as intended, so we can now remove `p1` and `p2` from the model and allow `p3` to evolve. At this

stage, all individuals in `p3` are still unmixed, having been generated from parents in either `p1` or

`p2`, but beginning in generation 3 they will start to mix.

Finally, we have some output and termination code. If both `m1` mutations fix, they are

converted to `Substitution` objects by SLiM, and when that is detected the model writes out a

final `.trees` file and terminates. If we reach generation 10000 without that happening, the

admixture failed, and we stop with an error. This model is conceptually similar to recipe 13.9 in

the SLiM manual (Haller and Messer, 2016), but has been converted to use tree-sequence

recording, so you can refer to the manual's recipe for additional commentary.

We can run this model from a Python script and do post-run analysis, as we did in Example 2:

```python
513    import os, subprocess, msprime, pyslim
514    import matplotlib.pyplot as plt
515    import numpy as np
516
517    # Run the SLiM model and load the resulting .trees file
518    subprocess.check_output(["slim", "-m", "-s", "0", "ex3_TS.slim"])
519    ts = pyslim.load("ex3_TS.trees").simplify()
520
521    # Assess the true local ancestry at each base position
522    breaks = np.zeros(ts.num_trees + 1)
523    ancestry = np.zeros(ts.num_trees + 1)
524    for tree in ts.trees(sample_counts=True):
525        subpop_sum, subpop_weights = 0, 0
526        for root in tree.roots:
527            leaves_count = tree.num_samples(root) - 1  # subtract one for the root
528            subpop_sum += tree.population(root) * leaves_count
529            subpop_weights += leaves_count
530        breaks[tree.index] = tree.interval[0]
531        ancestry[tree.index] = subpop_sum / subpop_weights
532    breaks[-1] = ts.sequence_length
533    ancestry[-1] = ancestry[-2]
534
535    # Make a simple plot
536    plt.plot(breaks, ancestry)
537    plt.show()
```

The first line after the import statements runs the SLiM model, which completes in just 0.416

seconds, with peak memory usage of 55.6 MB; since it tracks only two mutations, and typically

terminates by generation 150 or so, it is very quick.

The equivalent SLiM model to achieve true local ancestry mapping without tree-sequence

recording has to model a mutation at each base position, as can be seen in recipe 13.9 in the SLiM

manual (Haller and Messer, 2016). A direct comparison is not possible, because recipe 13.9

scaled up to a chromosome length of $L = 10^8$ would take an estimated 7.2 days to run, and worse,

would require 8.1 TB (terabytes) of memory. Those estimates are derived from the pattern of

performance observed for recipe 13.9 with $L = 5 \times 10^5$, $L = 10^6$, and $L = 2 \times 10^6$ (the upper limit on

our test machine due to memory usage), extrapolated out to $L = 10^8$. Implementing this model

with tree-sequence recording therefore reduces the runtime by a factor of more than 1.35 million,

and reduces the memory usage by a factor of more than 160,000.

Similar to Example 2, the post-run analysis walks through the tree sequence, but in this case,

computes the mean true local ancestry (the fractional ancestry from subpopulation p1 versus p2)

for each tree. This is done by finding the roots for the tree, assessing the subpopulations of origin

of those root individuals, and averaging those together weighted by the number of descendants

from each root. A simple plot is then produced. In this example, the analysis took 62.2 seconds;

the analysis runtime is relatively long because the trees here typically have many roots, so the

inner loop is executed a great many times.

The final plot of true local ancestry by chromosome position is shown in Figure 4. The mean

true local ancestry at the points where the beneficial mutations were introduced into p1 and p2 has

to be 100% p1 and 100% p2, respectively, since both beneficial mutations fixed by the end of the

run. At other points along the genome there is more variation, but with a general pattern of being

more completely admixed at the chromosome ends and middle, with gradations toward the

absolute p1 and p2 points. Since this is a single run of the model, the pattern is quite stochastic;

an average across many runs of this model could produce a smooth plot if desired, and since it

takes only a couple of minutes to execute the pipeline here, that would be very quick to do.  This

method of calculating true local ancestry could be used by any SLiM model with tree-sequence

recording, so models with more complex demography, under any scenario of selection and

mating, with any recombination map, etc., could just as easily be explored.

*Example IV: Neutral burn-in for a non-neutral model*

Our final example illustrates a solution to the problem of neutral burn-in.  In many applications

one wishes to execute a non-neutral forward simulation beginning with an equilibrium amount of

extant neutral genetic diversity, and the simulation needed to generate that pre-existing diversity,

typically called the model "burn-in", can take quite a long time – often much longer than it takes

to execute the non-neutral portion of the simulation.  For a model with a long chromosome or

large population size, this burn-in can be so long as to limit the practical scale of the simulations

that can be conducted. One solution to this is a "hybrid" approach, in which a forward simulation

is initialized with the result of a (much faster) coalescent simulation (similar to Bhaskar 2014).

This is now possible using tree sequences in SLiM, but we go a step further: even a great deal of

the work done in a coalescent simulation of this burn-in period is unnecessary.  All of the

genealogical branches that go extinct are irrelevant; all that matters are those segments of

ancestral genomes from which the final generation inherits.  With tree-sequence recording, one

can simulate only the histories of those segments, saving an immense amount of computation

relative to a forward-time burn-in simulation.

Here we will look at a fairly large model ($N = 10^5$; $L = 10^6$) that evolves under neutral

dynamics until coalescence (the neutral burn-in), after which follows some relatively brief non-

neutral dynamics (a selective sweep). Running the burn-in period for this model in SLiM would

take an exceedingly long time, given the scale of the model, as we will see below. A better idea

is to use what we call "recapitation": we can run the SLiM model forward from an initial state

that conceptually follows burn-in, and then use msprime to generate *after the fact* the coalescent

history for the initial individuals of the forward simulation. This can be done without simulating

neutral mutations, but if neutral mutations are desired as an end product of the simulation, they

can be overlaid at the end as in Example 1.

We begin with the SLiM model, which simulates the introduction and sweep to fixation of a

beneficial mutation. For simplicity, we will select a run of the model that happens to result in

fixation, rather than using a recipe that is conditional upon fixation; the random number seed

specified in the Python script below should produce that outcome. The SLiM model:

```
596    initialize() {
597      initializeTreeSeq(simplificationRatio=INF);
598      initializeMutationRate(0);
599      initializeMutationType("m2", 0.5, "f", 1.0);
600      m2.convertToSubstitution = F;
601      initializeGenomicElementType("g1", m2, 1);
602      initializeGenomicElement(g1, 0, 1e6 - 1);
603      initializeRecombinationRate(3e-10);
604    }
605    1 late() {
606      sim.addSubpop("p1", 100000);
607    }
608    100 late() {
609      sample(p1.genomes, 1).addNewDrawnMutation(m2, 5e5);
610    }
611    100:10000 late() {
612      mut = sim.mutationsOfType(m2);
613      if (mut.size() != 1)
614          stop(sim.generation + ": LOST");
615      else if (sum(sim.mutationFrequencies(NULL, mut)) == 1.0)
616      {
617          sim.treeSeqOutput("ex4_TS_decap.trees");
618          sim.simulationFinished();
619      }
620    }
```

This specifies a simple model with population size $N = 10^5$ diploid individuals, chromosome

length $L = 10^6$ base positions, and a recombination rate of $r = 3 \times 10^{-10}$ per base position per

generation, without mutation.  It runs to generation 100 and then introduces the sweep mutation

(the delay before introduction is just to provide separation between the simulation start and the

start of the sweep in the plot produced below).  When the sweep mutation is found to have fixed,

it then outputs a `.trees` file and stops.  It specifies an infinite "simplification ratio" in the call to

`initializeTreeSeq()` so that simplification happens only once, at the point when the `.trees` file

is written out at the end; with this large of a model simplification takes a significant amount of

time, so this optional setting speeds the model up somewhat at the price of a higher peak memory

footprint.

As in previous examples, we will run this from a Python script that does post-run analysis:

```
632    import os, subprocess, msprime, pyslim
633    import numpy as np
634    import matplotlib.pyplot as plt
635
636    # Run the SLiM model and load the resulting .trees file
637    subprocess.check_output(["slim", "-m", "-s", "2", "ex4_TS.slim"])
638    ts = pyslim.load("ex4_TS_decap.trees")    # no simplify!
639
640    # Calculate tree heights
641    def tree_heights(ts):
642        heights = np.zeros(ts.num_trees + 1)
643        for tree in ts.trees():
644            if tree.num_roots > 1:  # not fully coalesced
645                heights[tree.index] = ts.slim_generation
646            else:
647                root_children = tree.children(tree.root)
648                real_root = tree.root if len(root_children) > 1 else root_children[0]
649                heights[tree.index] = tree.time(real_root)
650        heights[-1] = heights[-2]  # repeat the last entry for plotting with step
651        return heights
652
653    # Plot tree heights before recapitation
654    breakpoints = list(ts.breakpoints())
655    heights = tree_heights(ts)
656    plt.step(breakpoints, heights, where='post')
657    plt.show()
658
659    # Recapitate
660    recap = ts.recapitate(recombination_rate=3e-10, Ne=1e5, random_seed=1)
661    recap.dump("ex4_TS_recap.trees")
662
663    # Plot tree heights after recapitation
664    breakpoints = list(recap.breakpoints())
665    heights = tree_heights(recap)
666    plt.step(breakpoints, heights, where='post')
667    plt.show()
```

After the import, we run the SLiM model (which takes 46.05 seconds) and load the `.trees` file

it saves out. We then immediately make a plot of mean tree heights along the chromosome. This

is similar to what we did in Example 2, but here it requires some extra finesse because we did not

simplify the tree sequence after loading it as we did then. To perform recapitation, we cannot

first simplify – we need the ancestral individuals that started the SLiM simulation to remain in the

tree sequence, so that recapitation can build upon them correctly. For this reason, every root in

the loaded tree sequence has the same time, corresponding to the beginning of the forward

simulation. The code in the `tree_heights()` function corrects for that, getting the height of the

child of the root if the forward simulation has coalesced below the original ancestor. This

provides the red line in Figure 5, showing that the area immediately around the introduced

mutation has coalesced at the time of the introduction (due to hitchhiking), but that the remainder

of the chromosome has not yet coalesced and thus has a tree height corresponding to the start of

forward simulation. These uncoalesced plateaus are what we will fix with recapitation.

The next step, then, is to perform the recapitation. This process works backwards from the tree

sequence information recorded by SLiM, constructing a full coalescent history for all of the

individuals alive at the end of the run. Since the non-neutral dynamics eliminated much of the

genetic diversity from the population as it existed at the beginning of forward simulation, this

coalescence requires very little work – much less than even a normal coalescent simulation for

this population size would require. In the example run discussed here, the process took 0.41

seconds. If neutral mutations are desired, they can then be overlaid on the recapitated tree

sequence following the method of Example 1; that code is not shown again here, but that

operation took another 0.58 seconds (with $\mu = 10^{-7}$).

Finally, we plot the mean tree heights for the recapitated tree sequence; this produces the black

line in Figure 5. The uncoalesced plateaus have now coalesced to times as far as a million

generations in the past. This plot nicely illustrates the classical sweep pattern in which regions

closer to the position of the sweep tend to coalesce more recently, due to hitchhiking, than

regions farther away (Maynard-Smith and Haigh, 1974).

Simulating the neutral burn-in period in SLiM instead, with neutral mutations occurring at a

rate of $\mu = 10^{-7}$, would take an estimated 114.7 hours (from extrapolation; this is a very

conservative estimate since the model was nowhere near mutation–drift balance when times were

measured). Recapitation and neutral mutation overlay, with a total time of 0.99 seconds,

therefore sped up the burn-in process in this example by more than 400,000 times.

Recapitation is clearly much faster than conducting burn-in with forward simulation, then; it

should be faster than a rescaled forward simulation model too (since rescaling can generally not

be taken that far without introducing problematic artifacts; see Discussion), and faster even than

constructing the burn-in state with the coalescent (since recapitation is based upon the coalescent

but handles far fewer events). Recapitation provides other benefits as well, since it means that

neutral burn-in can be deferred until after forward simulation is complete, and can even be

conducted as an afterthought on existing model output. It also allows the non-neutral forward

simulation to run without a burn-in history needing to be loaded (likely making it faster and

leaner), and allows one to avoid the question of how many generations must be simulated for

complete burn-in. It is worth noting that the coalescent (and thus recapitation) does not produce

identical results to forward simulation of a Wright–Fisher model, but the differences are small

and are mostly in the pattern of the most recent branches (Wakeley et al., 2012; Bhaskar et al.,

2014); using recapitation as an approximation for neutral forward simulation should therefore

produce practically identical results as long as the forward portion of the simulation runs for at

least a few generations.  Similarly, although spatial models differ substantially from the standard

coalescent, this difference is mostly seen in the more recent portion of the trees; lineages that

have "mixed" across the species range without coalescing behave statistically like lineages in a

randomly mating population (Wilkins, 2004; Matsen and Wakeley, 2006). Recapitation with an

unstructured coalescent should therefore be a good approximation to pre-existing diversity in a

spatial simulation as well.

Note that constructing a burn-in history with recapitation is only equivalent to a period of

forward simulation if the burn-in period is completely neutral.  If a non-neutral burn-in to

equilibrium is needed, the best approach is probably to run the burn-in period in SLiM with tree-

sequence recording turned on and neutral mutations turned off (thus avoiding the cost of

simulating the neutral mutations during burn-in, as in Example 1).  If a neutral burn-in is desired,

but the neutral mutations are then needed by the non-neutral portion of the simulation (perhaps

because some of the neutral mutations become non-neutral due to an environmental change), one

might simulate the burn-in period with the coalescent in msprime (including mutation), and then

save the result as a `.trees` file using pyslim; one could then read that `.trees` file into SLiM to

provide the initial state for further simulation.  These techniques go beyond what we have space

to illustrate here, but the manual for SLiM 3 provides further recipes showing the use of tree-

sequence recording.  Since it is possible to move simulation data with full ancestry records back

and forth between msprime and SLiM, one can imagine many ways to combine the two to

leverage their strengths while avoiding their weaknesses.

## Discussion

We have integrated support for tree-sequence recording (Kelleher et al., 2018) into the popular

SLiM forward simulation software package.  Tree-sequence recording can now be enabled in any

SLiM simulation, and the results output to a `.trees` file that can be loaded into Python for further

simulation or analysis using the msprime package (a part of the tskit framework).  We have also

extended the tree-sequence recording method to allow the recording and output of mutations that

arise during forward simulation.

We provided four examples demonstrating the power of the tree-sequence recording method.

The first example, of a simple neutral model, showed how to enable tree-sequence recording with

a few trivial modifications to a SLiM model's script.  The second example illustrated the use of

recorded tree sequences in post-simulation analysis in Python to estimate the characteristic

reduction in neutral diversity expected around functional regions due to background selection.

The third example mapped the mean true local ancestry along the chromosome in a model of the

admixture of two subpopulations, again using post-simulation Python analysis.  Finally, our

fourth example illustrated the use of msprime to "recapitate" a SLiM run, using the coalescent to

construct a neutral burn-in period after the completion of forward simulation.

All of these examples illustrated the large performance benefits that can be achieved with tree-

sequence recording.  Indeed, for very large neutral simulations our timing comparison indicated

that the speedup due to tree-sequence recording can exceed two orders of magnitude, and can put

the performance of forward simulation on par with an efficient coalescent-based simulation such

as msprime (Example 1).  For a large simulation with many non-neutral mutations, we still

observed a speedup of more than an order of magnitude (Example 2); simulations with a lower

density of non-neutral mutations should benefit even more.  Similarly, compared to standard

forward simulation methods, using recapitation to construct a neutral burn-in period provided a

speedup of more than five orders of magnitude (Example 4), and using the tree sequence to obtain

true local ancestry information provided a speedup of more than six orders of magnitude

(Example 3). Memory savings observed in these models were also quite substantial.

Although we have not made use of it in these examples, SLiM records substantial metadata in

the tree sequence it outputs about genomes, individuals, and mutations. This includes sex, age,

and spatial location of remembered individuals, and times of origination and selection

coefficients of mutations. This information, along with the tree sequence, could enable

substantially more detailed dissection of evolutionary trajectories. Access to this SLiM metadata

is mediated by the new pyslim package that bridges SLiM and msprime. Furthermore, the

`.trees` file contains all of the information necessary to reconstruct the internal state of the

simulation in SLiM, so it can be loaded back into SLiM, examined graphically using SLiMgui,

and even used as a starting point for further simulation (with some caveats; see the manual).

Tree-sequence recording is not a panacea. Models that do not involve neutral mutations will

not realize a speed benefit from tree-sequence recording's ability to defer neutral mutation

overlay; in fact, they will run more slowly, since the overhead of recording will not be

compensated by eliminating neutral mutation simulation. Models that involve a very high

recombination rate relative to the mutation rate may also not see a speed benefit from tree-

sequence recording, since tracking the recombination breakpoints can become very time-

consuming; informal tests indicate that this becomes important, for neutral simulations, when the

recombination rate is two or more orders of magnitude larger than the mutation rate, however, so

it may not be a practical concern for most models. Even if simulation performance is not

improved by tree-sequence recording, the ancestry information provided by the tree sequence

may still speed up analysis or provide additional statistical power, which can also be quite

important in reducing total runtimes.  The benefit of tree-sequence recording also depends upon

factors such as the proportion of neutral to non-neutral mutations, the distribution of fitness

effects from which the non-neutral mutations are drawn, the genetic architecture, the frequency

with which tree-sequence simplification is performed, and many other factors.  In practice, it may

be worthwhile to simply compare the performance of both methods for a particular model; it is

difficult to distill any reliable rule of thumb.  These considerations were discussed further in

Kelleher et al. (2018).

A commonly used technique for speeding up large forward simulations is model rescaling.

This involves scaling down the population size ($N$) by some factor $Q$, while scaling up the

mutation rate ($\mu$), the recombination rate ($r$), and selection coefficients ($s$) by the same factor; this

holds many common population-genetic parameters constant, since they involve products of these

variables (e.g., $N\mu$, $Nr$, and $Ns$).  Since these factors (as well as genetic drift) are *rates*, one

generation in the rescaled model corresponds to $Q$ generations in the original model.  Therefore,

rescaling by a factor $Q$ can provide a speedup of up to a factor of $Q^2$ due to the $Q$-times smaller

population size *and* the $Q$-times smaller number of generations that need to be simulated.

However, this technique has important limitations, because it can introduce artifacts due to the

discretization of mutation frequencies and of time.  For example, if a model with an original

population size of $N = 10{,}000$ were rescaled to a model with $N = 100$, the smallest possible

mutation frequency will also have increased from 0.00005 to 0.005, which could severely affect

studies in which one is concerned about the behavior of low-frequency polymorphisms. There are

more serious issues related to the process of adaptation; since rescaled values of $s$ are larger,

rescaling has the net effect of substituting many mutations of small effect with a single one of

large effect (with $Q=100$, replacing 100 mutations with $s=0.001$ by a single one of $s=0.1$). Thus,

rescaling must not be taken too far, and careful comparisons are needed between the unscaled and

the rescaled model to ensure that results are not altered by rescaling artifacts. The SLiM manual

(Haller and Messer, 2016) has an extended discussion of model rescaling and provides instructive

examples. Since tree-sequence recording does not introduce such artifacts, it probably ought to

be used to full advantage before any model rescaling is applied. If that does not bring the desired

simulation within practical computational bounds, rescaling may be used in conjunction with

tree-sequence recording, but with the same caveats mentioned above. Note, however, that the

effectiveness of combining both strategies is hard to predict, since the increased recombination

rate in the scaled model means that roughly the *same* number of recombination events must be

recorded.

Although tree-sequence recording is not appropriate in every model, the examples we have

presented demonstrate that the performance gains it provides can make simulations possible that

would previously have been beyond reach, opening up new horizons for exploration. The

software packages used here – SLiM, msprime, Python, R – are all free and open-source, and the

examples and analyses shown here are all available on GitHub. We hope that the practical

examples we have provided will raise the level of awareness among evolutionary biologists

regarding this exciting new method.

## Acknowledgements

Thanks to Kevin Thornton and Dom Nelson for helpful discussions. This work was supported by funding from the College of Agriculture and Life Sciences at Cornell University, Predator Free 2050 (grant SS/05/01), and the NIH (grants R21AI130635 and R01GM127418) to PWM; by funding from the Sloan Foundation and the NSF (under DBI-1262645) to PLR; and by the Wellcome Trust (grant 100956/Z/13/Z) to Gil McVean for JK.

## References

Arunkumar, R., Ness, R.W., Wright, S.I., and Barrett, S.C. (2015). The evolution of selfing is accompanied by reduced efficacy of selection and purging of deleterious mutations. *Genetics 199*(3), 817-829.

Assaf, Z.J., Petrov, D.A., and Blundell, J.R. (2015). Obstruction of adaptation in diploids by recessive, strongly deleterious alleles. *PNAS 112*(20), E2658-E2666.

Berman, S.M. (1964). Limit theorems for the maximum term in stationary sequences. *Ann. Math. Statist. 35*(2), 502–516.

Bhaskar, A., Clark, A.G., and Song, Y.S. (2014). Distortion of genealogical properties when the sample is very large. *PNAS 111*(6), 2385–2390.

Caballero, A., Tenesa, A., & Keightley, P.D. (2015). The nature of genetic variation for complex traits revealed by GWAS and regional heritability mapping analyses. *Genetics 201*(4), 1601–1613.

Charlesworth, B., Morgan, M.T., and Charlesworth, D. (1993). The effect of deleterious mutations on neutral molecular variation. *Genetics 134*(4), 1289–1303.

Champer, J., Liu, J., Oh, S.Y., Reeves, R., Luthra, A., Oakes, N., Clark, A.G., and Messer, P.W. (2018). Reducing resistance allele formation in CRISPR gene drive. *PNAS (early access)*, 1–6. DOI: https://doi.org/10.1073/pnas.1720354115

Cotto, O., Wessely, J., Georges, D., Klonner, G., Schmid, M., Dullinger, S., Thuiller, W., and Guillaume, F. (2017). A dynamic eco-evolutionary model predicts slow response of alpine plants to climate warming. *Nature Communications 8*, 15399.

Elyashiv, E., Sattath, S., Hu, T. T., Strutsovsky, A., McVicker, G., Andolfatto, P., Coop, G. & Sella, G. (2016). A genomic map of the effects of linked selection in *Drosophila*. *PLoS Genetics 12*(8), e1006130.

Ewing, G.B., and Jensen, J.D. (2016). The consequences of not accounting for background selection in demographic inference. *Molecular Ecology 25*(1), 135–141.

Enard, D., Messer, P.W., and Petrov, D.A. (2014). Genome-wide signals of positive selection in human evolution. *Genome Research 24*(6), 885–895.

Fournier-Level, A., Perry, E.O., Wang, J.A., Braun, P.T., Migneault, A., Cooper, M.D., Metcalf,
C.J.E., and Schmitt, J. (2016). Predicting the evolutionary dynamics of seasonal
adaptation to novel climates in *Arabidopsis thaliana*. *PNAS 113*(20), E2812–E2821.

Griffiths, R.C. The two-locus ancestral graph. In: Basawa, I.V., Taylor, R.L., eds. *Selected*
*Proceedings of the Sheffield Symposium on Applied Probability, 1989*. Hayward,
California: Institute of Mathematical Statistics, 1991: 100–117.

Griffiths, R.C., and Marjoram, P. (1997). An ancestral recombination graph. In: Donnelly P.,
Tavare S., eds. *Progress in Population Genetics and Human Evolution.* Berlin, Germany:
Springer-Verlag, 1997: 257–270.

Haller, B.C., and Hendry, A.P. (2013). Solving the paradox of stasis: Squashed stabilizing
selection and the limits of detection. *Evolution 68*(2), 483–500.

Haller, B.C., R Mazzucco, R., and Dieckmann, U. (2013). Evolutionary branching in complex
landscapes. *American Naturalist 182*(4), E127-E141.

Haller, B.C., and Messer, P. W. (2016). SLiM: An Evolutionary Simulation Framework. URL:
http://benhaller.com/slim/SLiM_Manual.pdf

Haller, B.C., and Messer, P.W. (2017a). asymptoticMK: A web-based tool for the asymptotic
McDonald–Kreitman test. *G3: Genes, Genomes, Genetics 7*(5), 1569–1575.

Haller, B.C., and Messer, P.W. (2017b). SLiM 2: Flexible, interactive forward genetic
simulations. *Molecular Biology and Evolution 34*(1), 230–240. DOI:
http://dx.doi.org/10.1093/molbev/msw211

Hudson, R.R. (1983). Properties of a neutral allele model with intragenic recombination.
*Theoretical Population Biology 23*(2), 183–201.

Hudson, R.R. (1994). How can the low levels of DNA sequence variation in regions of the
*Drosophila* genome with low recombination rates be explained? *PNAS 91*(15), 6815–
6818.

Hunter, J.D. (2007). Matplotlib: A 2D graphics environment. *Computing In Science &*
*Engineering 9*(3), 90–95.

Kelleher, J, Etheridge, A.M., and McVean, G. (2016). Efficient coalescent simulation and
genealogical analysis for large sample sizes. *PLoS Computational Biology 12*(5):
e1004842. DOI: https://doi.org/10.1371/journal.pcbi.1004842

Kelleher, J., Thornton, K.R., Ashander, J., and Ralph, P.L. (2018). Efficient pedigree recording
for fast population genetics simulation. *PLoS Computational Biology 14*(11): e1006581.
DOI: https://doi.org/10.1371/journal.pcbi.1006581

Kingman, J.F.C. (1982). On the genealogy of large populations. *Journal of Applied Probability*
*19*, 27–43.

Mafessoni, F., and Lachmann, M. (2015). Selective strolls: fixation and extinction in diploids are
slower for weakly selected mutations than for neutral ones. *Genetics 201*(4), 1581–1589.

Matsen, F.A., and Wakeley, J. (2006). Convergence to the island-model coalescent process in
populations with restricted migration. *Genetics 172*(1), 701–708.

Matz, M.V., Treml, E.A., Aglyamova, G.V., and Bay, L.K. (2018). Potential and limits for rapid
895           genetic adaptation to warming in a Great Barrier Reef coral. *PLoS Genetics 14*(4),
896           e1007220.

897    Maynard-Smith, J., and Haigh, J. (1974). The hitch-hiking effect of a favourable gene. *Genetics*
898           *Research 23*(1), 23–35.

899    Messer, P.W. (2013). SLiM: Simulating evolution with selection and linkage. *Genetics 194*(4),
900           1037–1039.

901    Nowak, M.D., Haller, B.C., and Yoder, A.D. (2014). The founding of Mauritian endemic coffee
902           trees by a synchronous long-distance dispersal event. *Journal of Evolutionary Biology*
903           *27*(6), 1229–1239.

904    Oliphant, T.E. (2006). A guide to NumPy. U.S.A.: Trelgol Publishing.

905    Patel, R., Scheinfeldt, L.B., Sanderford, M.D., Lanham, T.R., Tamura, K., Platt, A., Glicksberg,
906           B.S., Xu, K., Dudley, J.T., and Kumar, S. (2018). Adaptive landscape of protein variation
907           in human exomes. *Molecular Biology and Evolution 35*(8): 2015–2025. DOI:
908           https://doi.org/10.1093/molbev/msy107

909    Ryan, S.F., Deines, J.M., Scriber, J.M., Pfrender, M.E., Jones, S.E., Emrich, S.J., and Hellmann,
910           J.J. (2018). Climate-mediated hybrid zone movement revealed with genomics, museum
911           collection, and simulation modeling. *PNAS 115*(10) E2284-E2291.

912    Sattath, S., Elyashiv, E., Kolodny, O., Rinott, Y., and Sella, G. (2011). Pervasive adaptive protein
913           evolution apparent in diversity patterns around amino acid substitutions in *Drosophila*
914           *simulans*. *PLoS Genetics 7*(2), e1001302.

915    Thornton, K.R. (2014). A C++ template library for efficient forward-time population genetic
916           simulation of large populations. *Genetics 198*(1), 157–166.

917    Wakeley, J., King, L., Low, B.S., and Ramachandran, S. (2012). Gene genealogies within a fixed
918           pedigree, and the robustness of Kingman's coalescent. *Genetics 190*(4), 1433–1445.

919    Wilkins, J.F. (2004). A separation-of-timescales approach to the coalescent in a continuous
920           population. *Genetics 168*(4), 2227–2244.

## Data Accessibility

SLiM 3 is available online at https://messerlab.org/slim/. It is open source, under the GPL 3.0

license, and its source code is on GitHub at https://github.com/MesserLab/SLiM.

msprime is available online at https://pypi.org/project/msprime/. It is open source, under the GPL

3.0 license, and its source code is on GitHub at https://github.com/tskit-dev/msprime.

pyslim is open source, under the MIT license, and is available on GitHub at

https://github.com/tskit-dev/pyslim.

The examples and performance assessments presented in this paper are available on GitHub at

https://github.com/bhaller/SLiMTreeSeqPub.

## Author Contributions

*We have used the CRediT taxonomy for contributions (https://casrai.org/credit/).*

BCH: Conceptualization, Investigation, Methodology, Software, Validation, Visualization,

Writing – Original Draft Preparation, Writing – Review & Editing.

JG: Conceptualization, Methodology, Software, Writing – Review & Editing.

JK: Conceptualization, Methodology, Software, Validation, Visualization, Writing – Review &

Editing.

PWM: Conceptualization, Funding Acquisition, Supervision, Writing – Review & Editing.

PLR: Conceptualization, Funding Acquisition, Methodology, Software, Supervision, Validation,

Writing – Review & Editing.

**Figures**

Genome coordinates

Figure 1. An example tree sequence for a model of five extant genomes, with a chromosome
ten base positions long.  Each interval between $x$ axis ticks is a genomic interval with a
distinct ancestry tree.  The leaves of each tree [0–4] represent the extant genomes,
whereas the internal nodes [5–12] represent ancestral genomes from which the extant
genomes descend.  The pattern of ancestry at adjacent sites is typically highly correlated,
as seen here.  Full coalescence has been achieved for the first, second, and fourth
intervals, but the third interval has not yet fully coalesced; the tree for that interval
therefore has multiple roots.  See Kelleher et al. (2016, 2018) for further discussion of the
tree sequence data structure.

951
Figure 2. A speed comparison between SLiM without tree-sequence recording, SLiM with
tree-sequence recording and mutation overlay, and msprime's coalescent simulation for a
simple neutral model (Example 1; see text for model description).  Each point represents
the mean runtime across 10 replicates using different random number seeds; bars showing
standard error of the mean would be smaller than the size of the plotted points in all cases.
Runs for SLiM without tree-sequence recording (filled blue diamonds) were not
conducted for $L = 10^{10}$ because the memory usage was prohibitive, so a linear
extrapolation is shown (hollow blue diamond).  Runs for SLiM with tree-sequence
recording and mutation overlay (filled green circles) are subdivided here to show the
runtime for SLiM alone, prior to mutation overlay (hollow green circles), illustrating that
the time for mutation overlay is negligible.  The runtimes for the msprime coalescent for a
full population sample of $n = 2N = 1000$ (filled red squares) and for a sample of size
$n = 2N/100 = 10$ (hollow red squares) are both shown.  Note that the $x$ and $y$ axes are both
on a log scale.

Figure 3. Mean diversity (as measured by mean tree height) as a function of distance from the
nearest gene (Example 2). The center of the x-axis (red line) represents a distance of zero,
immediately adjacent to a gene; moving away from the x-axis center to the left/right
represents moving away from the nearest gene to the left/right respectively. The pattern
of decreased diversity near a gene is the "dip in diversity" due to background selection.

Figure 4. Mean true local ancestry at each position along the chromosome (Example 3). The
red vertical bars indicate the positions at which beneficial mutations were originally
introduced into p1 and p2. The beneficial mutations, which both fixed, are points where
the true local ancestry is 100% p1 or p2. True local ancestry regresses toward equal
admixture with increasing distance from those fixed points.

Figure 5. Mean tree height (on a cube-root-scaled *y*-axis) at each position along the
chromosome, before and after recapitation (Example 4).  The red line shows mean tree
heights prior to recapitation; the region surrounding the introduced sweep mutation
coalesces at the start of the sweep, whereas the plateaus outside that region are
uncoalesced and have a height corresponding to the start of forward simulation (100
generations earlier).  The black line shows heights after recapitation; the uncoalesced
plateaus have now been coalesced backward in time, producing tree heights as long as a
million generations in the past.