1
2
3
4 Real-world expectations and their affective value modulate object processing

11 Laurent Caplette[1], Frédéric Gosselin[1], Martial Mermillod[2] et Bruno Wicker[1,3]
12
13
14 [1]Département de psychologie, Université de Montréal, Montréal, Québec, H3C 3J7, Canada
15 [2]LPNC, CNRS & Université Grenoble Alpes, 38058 Grenoble, France
16 [3]LNC, CNRS & Aix-Marseille Université, 13331 Marseille, France
17
18

19 Keywords: expectations, predictions, object recognition, fMRI, emotion.
20
21
22 Conflicts of interest: The authors declare no competing financial interests.
23
24

25 Acknowledgements: This study was funded by the Fondation Planiol (BW), by the Institut
26 Universitaire de France (MM) and by the Social Sciences and Humanities Research Council
27 of Canada (LC).

28
29
30

Correspondence should be addressed to:
Laurent Caplette
Department of Psychology
Yale University
2 Hillhouse Ave
New Haven, CT 06520
U.S.A.
Email : laurent.caplette@yale.edu

Abstract

It is well known that expectations influence how we perceive the world. Yet the neural mechanisms underlying this process remain unclear. Studies about the effects of prior expectations have focused so far on artificial contingencies between simple neutral cues and events. Real-world expectations are however often generated from complex associations between contexts and objects learned over a lifetime. Additionally, these expectations may contain some affective value and recent proposals present conflicting hypotheses about the mechanisms underlying affect in predictions. In this study, we used fMRI to investigate how object processing is influenced by realistic context-based expectations, and how affect impacts these expectations. First, we show that the precuneus, the inferotemporal cortex and the frontal cortex are more active during object recognition when expectations have been elicited a priori, irrespectively of their validity or their affective intensity. This result supports previous hypotheses according to which these brain areas integrate contextual expectations with object sensory information. Notably, these brain areas are different from those responsible for simultaneous context-object interactions, dissociating the two processes. Then, we show that early visual areas, on the contrary, are more active during object recognition when no prior expectation has been elicited by a context. Lastly, BOLD activity was shown to be enhanced in early visual areas when objects are less expected, but only when contexts are neutral; the reverse effect is observed when contexts are affective. This result supports the proposal that affect modulates the weighting of sensory information during predictions. Together, our results help elucidate the neural mechanisms of real-world expectations.

We expect to find hairdryers in bathrooms, tombstones in cemeteries, and baguettes in bakeries,

but not tombstones in bathrooms, refrigerators in cemeteries and hairdryers in bakeries. That

is, we live in a world where most objects are associated with specific contexts. Throughout a

lifetime of experiences, we come to learn these associations, which lead us to form expectations

about the objects to be encountered when we navigate the world. Congruent contexts have been

shown to facilitate an object's recognition, compared to incongruent contexts (Bar and Ullman,

1996; Biederman et al., 1982; Davenport and Potter, 2004); in addition, objects are recognized

more accurately when a semantically consistent scene has been shown prior to the object's

recognition (Palmer, 1975; see Bar, 2004, for a review of related studies).

Perception can be understood as the process of integrating such top-down expectations

with incoming sensory information. It has been proposed that predictions from high-level areas

are transmitted to adjacent lower-level areas and compared with incoming sensory signals, such

that only the discrepancy between these two signals – the prediction error – is transmitted up

the visual hierarchy (Friston, 2005; see also Mumford, 1992; Ullman, 1995; Rao and Ballard,

1999). In support of this model, the expectation of a visual stimulus elicits a specific pattern of

activity in the primary visual cortex (Kok et al., 2014, 2017; Hindy et al., 2016) and the

perception of an expected stimulus results in reduced neural activity in sensory cortices

(Summerfield et al., 2008; den Ouden et al., 2010; Alink et al., 2010; Kok et al., 2012a;

Todorovic and de Lange, 2012; see de Lange et al., 2018, for a review). Some predictions,

however, may require a different mechanism than feedback from adjacent visual areas (Bar,

2007; Hindy et al., 2016): for instance, the hippocampus has been shown to play a role in the

generation of predictions (Hindy et al., 2016; Kok and Turk-Browne, 2018), and there is some

evidence that parahippocampal (PHC) and retrosplenial (RSC) cortices initiate context-based

expectations (Bar, 2003, 2004; Bar and Aminoff, 2003; Bar et al., 2006; Livne and Bar, 2016;

Brandman and Peelen, 2017).

Most neuroimaging studies examining the mechanisms underlying predictions in visual

perception have used very simple cues such as tones (Summerfield and Koechlin, 2008; den

Ouden et al., 2010; Kok et al., 2012a, 2017) or a repetition of the same object (Summerfield et

al., 2008; Todorovic and de Lange, 2012). By contrast, expectations about everyday objects

usually stem from the surrounding context. Several previous studies investigated the processing

of context-object relationships but did so by using a simultaneous presentation of the object and

the scene (Faivre et al., 2019; Goh et al., 2004; Jenkins et al., 2010; Kirk, 2008; Rémy et al.,

2014; see also Gronau et al., 2008, who use semantically related objects analyzed as a single

event), which makes it hard to disentangle context-object interactions (occurring while both are

being recognized) from context-based predictions (occurring prior to the object's recognition).

For example, context-object interactions can comprise matching processes or low-level

crowding. While studying these processes is of interest, we focus here on predictions arising

from an earlier processing of scenes and influencing a later processing of objects. To isolate

this process, we used a sequential design in which scenes alone are presented before objects

alone, just like when someone walks towards a cemetery and sees tombstones when he gets in.

In fact, contexts are typically processed before the objects that they comprise (and they guide

the eyes to these objects; Bar, 2003; Oliva & Torralba, 2007). Ganis & Kutas (2003) used a

quasi-sequential scene-object presentation in their electroencephalography (EEG) study but

their objects were shown overlayed to the scene previously presented; therefore, the effect of

predictions on object recognition was not as isolated as in our design in which objects appear

alone. They found a modulation of an N400-like component by the semantic congruency of the

scene and object. Their use of EEG, however, prevented them from looking at the specific brain

regions at play. To our knowledge, our study is the first neuroimaging study to explore context-

based predictions using a sequential context-object design.

Relatedly, the effect of predictions has not been considered in the setting of an

ecological object recognition task. Simple detection tasks (Jiang et al., 2013), delayed

discrimination tasks (Kok et al., 2012a, 2014, 2017) or categorization tasks using few stimuli

(den Ouden et al., 2010; Kok et al., 2012b) are typically used. Moreover, previous studies on

prediction have manipulated predictability by artificial means, either by repeating and

alternating stimuli (Summerfield et al., 2008; Todorovic and de Lange, 2012), by having stimuli

appearing after different cues with different probabilities during the experiment (den Ouden et

al., 2010; Kok et al., 2012a, 2012b, 2014, 2017; Jiang et al., 2013), or by developing arbitrary

contingencies shortly before the experiment (Hindy et al., 2016). Associations between contexts

and objects formed over a lifetime of experiences may involve mechanisms distinct from these.

For instance, these associations learned a long time ago may be stored independently of the

hippocampus and so, predictions would not originate from this area.

Moreover, real-world expectations are often tinted by some affective value. A visual

context can elicit emotional reactions that may influence the recognition of objects in the scene

(Lebrecht et al., 2012). In an emotional context (e.g., a cemetery), the affective value may be

partially processed before the scene's objects (e.g., a tombstone) and contribute to the object's

recognition (Barrett and Bar, 2009). In such a case, there would be a greater difference in brain

activation between validly predicted and invalidly predicted objects for emotional contexts than

for neutral contexts (due to the presence of additional affective information).

Alternatively, the prediction's affective value might interact with its validity. Based on

a recent proposal according to which sub-cortical nuclei have a modulating power over

prediction errors (Kanai et al., 2015), and on the fact that many subcortical circuits are

coordinated with bodily processes, Miller & Clark (2018) proposed that affect (relating to

internal bodily states) exerts a continuous influence on perception by increasing the weight

attributed to prediction errors during perceptual inference. When prediction errors are up-

weighted, observers will rely more on the sensory input instead of their predictions to recognize

a target object. This increased weight might be implemented by increasing the postsynaptic

gain of neurons representing prediction errors (Kok et al., 2012b; Feldman & Friston, 2010).

According to recent predictive coding models, the pattern of neural responses to valid and

invalid predictions should reverse when prediction errors are given more weight (Feldman &

Friston, 2010; Kok et al., 2012b). In our case, this would lead to a greater response to invalidly

predicted stimuli than validly predicted stimuli when there is no affect, and to the opposite

result when there is affect (see Kok et al., 2012b, for a description of a similar phenomenon,

supplemented with diagrams).

In the present study, we aimed to address previous shortcomings by investigating how

object recognition mechanisms are influenced by task-irrelevant implicit expectations

generated by a predictive or non-predictive visual context. Which brain regions are responding

to objects whether they were preceded by expectations or not will inform us about how high-

level predictions are matched to sensory data. Furthermore, we aimed to investigate the effect

of the affective value of predictions, and to disentangle between competing hypotheses on this

matter. The pattern of results across the different affective value and predictive value conditions

will teach us about how affect modulates the influence of predictions.

153   **Materials and Methods**

Participants

Seventeen healthy adults (9 female; mean age = 24.8; standard deviation = 4.3) were

recruited on the campus of Aix-Marseille Université. Participants did not suffer from any

neurological, psychological or psychiatric disorder and were free of medication. The

experimental protocol was approved by the ethics board of CPP Sud-Méditerranée 1 and the

study was carried in accordance with the approved guidelines. Written informed consent was

obtained from all participants after the procedure had been fully explained, and a monetary

compensation was provided upon completion of the experiment.

Stimuli

We conducted several validation studies. For all these studies, subjects were French and

had unlimited time to respond. In a first validation study, 35 different subjects (20 female; 22

to 54 years, mean = 29.2 years) were shown thirty-three context names and had to give the

names of three objects with a high probability of being present in that context. Then, thirty-two

public domain scene color images were selected from the internet as context images (see

examples in Figure 1a). Context images were selected to ensure that their three most associated

objects did not appear in them while still being representative of the context category.

Ninety-six color images of objects corresponding to the three most cited names for each

context were then selected for the experiment (e.g., swimsuit, diving board and pool ladder for

swimming pool; Figure 1a, Table S1). For each context, the experimenters also chose three non-

associated objects (selected from the ones that had never been associated with the context in

the first validation study). Every object was the associated object of only one context and the

non-associated object of only one other context; moreover, for each context, each one of the

three non-associated objects was associated with a different context. Additionally, the

experimenters (i.e. the four authors) divided contexts in Affective (*Aff*) and Neutral (*Neut*)

categories according to their judgment of their affective intensity: the category of each context

was determined by consensus.

We validated this categorization *a posteriori* with a second validation study. In this

study, an independent sample of 22 subjects (12 female; 20 to 58 years, mean = 23.5 years)

identified what they thought the context images represented (to confirm that the image

represented the context; all contexts were largely correctly identified), indicated if the context

elicited an emotion and, if so, what were its valence (negative to positive, from 0 to 10) and

intensity (no emotion to very intense emotion, from 0 to 10); if the subject indicated that the

context elicited no emotion, this was coded as 0 intensity. Valence was not included in the

experimental design. We performed a Spearman correlation between our classification (binary

variable) and the affective intensity score: we obtained a correlation coefficient of 0.78 solely

with our binary classification, indicating that we explained a large part of the explainable

variance; affective contexts had a mean intensity of 5.42 while neutral contexts had a mean

intensity of 2.37. Looking more closely, only 4 contexts were miscategorized according purely

to the validation's intensity score; we repeated our fMRI analyses excluding these contexts and

obtained very similar results (the regions activated were largely the same; see supplementary

materials).

A third and final validation study was conducted to collect quantitative measures of the

associations between objects and contexts. Forty-four new subjects (29 female; 18 to 86 years,

mean = 40.7 years) indicated on a scale from 0 to 10 exactly how much each object was

associated to its associated and non-associated contexts (context-object pairs were randomized).

Measures were z-scored within each subject. Associated objects had a vastly greater associative

weight with their context (F = 38353, $p < 4.4 \times 10^{-65}$). Neutral contexts had a greater association

to their associated objects on average, and a smaller association to their non-associated objects

(significant interaction between association and affective value; F = 17.43, p = .0001). To get

rid of this potential confound, we used these weights, z-scored within predictive value condition

but not within affective value condition, as covariates in the analysis.

Finally, we randomized the phases of the mean of the context images in the Fourier

domain – separately for each RGB color channel – to obtain 96 different phase-scrambled

images.

Data acquisition

Functional imaging data were acquired with an AVANCE 3 Tesla scanner (Bruker Inc.,

Ettlingen, Germany) equipped with a 2-channel head-coil. Functional images sensitive to

BOLD contrast were acquired with a T2*-weighted gradient echo EPI sequence (TR 2400 ms,

TE 30 ms, matrix 64 x 64 mm, FOV 192 mm, flip angle 81.6°). Thirty-six slices with a slice

gap of 0 mm were acquired within the TR; voxels were 3 x 3 x 3 mm. Between 303 and 311

volumes were acquired in each run, excluding the six dummy scans acquired at the beginning

of each run for signal stabilization. Additionally, a high resolution (1 x 1 x 1 mm) structural

scan was acquired from each participant with a T1-weighted MPRAGE sequence.

Experimental Design

The LabVIEW (National Instruments Inc., Austin, TX, USA) software was used to

project stimuli during the experiment. Stimuli were projected to a screen positioned in the back

of the scanner using a video projector. Subjects could see the video reflected in a mirror (15 x

9 cm) suspended 10 cm in front of their face and subtending visual angles of 42 degrees

horizontally and 32 degrees vertically.

Each trial was built as follows: a large cue image (see below) spanning the whole screen

during 1 s, a blank screen during 1.5 to 4 s (duration randomly selected from a truncated

exponential distribution with mean of 2 s), a centered object image on a white background (20

x 26 degrees of visual angle) during 133 ms, a blank screen during 1.5 to 4 s, and an object

name shown until the subject answered or for a maximum of 1 s (Figure 1b). During the whole

trial except at the presentation of the full-screen scene, a black background was present around

the stimuli. Subjects answered by pressing one of two buttons on a hand-held response device

(as accurately and rapidly as possible) to indicate if the name corresponded to the object, which

235 occurred on 80% of the trials. The purpose of the task was to maintain the attention and

236 engagement of the subjects during the perception of the scenes and objects. A black screen was

237 displayed for an additional 1 s between trials.

238  On a third of the trials (*Valid* condition), the cue image was a scene associated with the

239 object following it (e.g., an airport and a suitcase); on another third (*Invalid* condition), it was

240 a scene not associated with the object following it (e.g., a church and a tennis racket); on the

241 final third (No-Prediction condition; *noPred*), it was a scrambled image (always a different

242 one). Each object was shown once in each of these conditions, for a total of 288 trials.

243  Trials were divided into three runs of 96 trials each. The order of the trials within each

244 run was predetermined randomly prior to the study and was constant across participants; the

245 order of the three runs was counterbalanced across subjects. Each functional run lasted between

246 10 and 12 mins (differences in length were due to the random inter-stimuli intervals), with short

247 breaks between them.

249 **Data Preprocessing and Analysis**

Figure 1. A) Example of one neutral and one affective scene, with their associated objects. See table S1 for a list of all contexts and associated objects. **B)** Example of a trial (Invalid Neutral condition). The object image and name have been enlarged for better viewing.

The SPM8 software (http://www.fil.ion.ucl.ac.uk/spm/), running in the MATLAB

environment (Mathworks Inc., Natick, MA, USA), was used. T1-weighted structural images

were segmented into white matter, gray matter and cerebrospinal fluid, and warped into MNI

space. Functional images were realigned, unwarped and corrected for geometric distortions

using the field map of each participant, slice time corrected, coregistered to the structural image

of the corresponding participant, and smoothed using an isotropic Gaussian kernel with a 6 mm

Full-Width Half-Maximum.

A standard General Linear Model (GLM) analysis was performed for each subject.

Three events were modelled on each trial: contexts (or scrambled images), objects and object

names. Object events (the regressors of interest) were modelled for each condition separately

(Valid-Aff, Valid-Neut, Invalid-Aff, Invalid-Neut and noPred); scene events (regressors of no

interest) were also modelled separately for each condition; one additional regressor was

included for the object names. All these events were modelled as Dirac delta functions (duration

of zero) convolved with SPM8's canonical hemodynamic response function. To get rid of

potential effects caused by differences in context-object associations, we included an additional

parametric regressor which consisted of the context-object association weights as determined

by our third validation study. This regressor was z-scored separately within Valid contexts and

Invalid contexts but not separately within each affective value subcondition so that differences

in context-object associations between affective and neutral contexts were accounted for, but

that differences between Valid and Invalid conditions remained; finally, we convolved it with

the hemodynamic response function. The six motion parameters were also included as

additional nuisance regressors.

A temporal high-pass filter (cut-off of 128 s) was used to remove low-frequency drifts,

and temporal autocorrelation across scans was modelled with an AR(1) process. Contrasts were

then computed at the subject level and used for group analyses using one-sample t-tests. All

voxels inside the brain were analyzed; we maintained the familywise error rate of $p < .05$, two-

tailed, at the cluster level (primary threshold of $p < .001$, uncorrected) using random field theory

(Friston et al., 1994). The Anatomy (Eickhoff et al., 2005) and WFU-PickAtlas (Maldjian et

al., 2003) toolboxes were used to identify activated brain regions based on peak Montreal

Neurological Institute (MNI) coordinates.

Data and code will be made available on the Open Science Framework repository

shortly after the publication of this manuscript.

283　　　　　　　　　　　　　　　**Results**

Behavioral results

Mean accuracy was 97.1% ($\sigma = 2.8\%$) for the Valid-Neut condition, 97.2% ($\sigma = 2.1\%$)

for the Valid-Aff condition, 96.9% ($\sigma = 2.6\%$) for the Invalid-Neut condition, 95.0% ($\sigma = 2.5\%$)

for the Invalid-Aff condition and 95.7% ($\sigma = 2.4\%$) for the noPred condition. When comparing

Valid, Invalid and noPred together (ANOVA, $n = 17$), there was no effect of condition on

accuracy ($F(2,16) = 2.17$, $p = .26$, $\eta^2_p = 0.12$). When comparing all subconditions except

noCont together in order to include affective value as a factor (ANOVA, $n = 17$, corrected for

multiple comparisons across both ANOVAs), there was a significant main effect of predictive

value ($F(1,16) = 10.36$, $p = .01$, $\eta^2_p = 0.13$), i.e. accuracy was higher when objects were

predicted. There was no significant main effect of affective value ($F(1,16) = 4.42$, $p = .10$, η^2_p

$= 0.08$), and no significant interaction between affective and predictive values ($F(1,16) = 3.97$,

$p = .13$, $\eta^2_p = 0.10$).

Mean response time was 640 ms ($\sigma = 121$ ms) for the Valid-Neut condition, 650 ms (σ

$= 120$ ms) for the Valid-Aff condition, 638 ms ($\sigma = 110$ ms) for the Invalid-Neut condition, 636

ms ($\sigma = 127$ ms) for the Invalid-Aff condition and 632 ms ($\sigma = 116$ ms) for the noPred

condition. When comparing Valid, Invalid and noPred (ANOVA, $n = 17$), there was no effect

of condition on response time ($F(2,16) = 1.53$, $p = .46$, $\eta^2_p = 0.09$). When comparing all

conditions except noPred together together in order to include affective value as a factor

(ANOVA, $n = 17$, corrected for multiple comparisons across both ANOVAs), there was no

main effect of affective or predictive value and no interaction (Fs$(1,16) = 1.67$, 0.25 and 0.64

respectively, $p > .40$, $\eta^2_p < .03$).

fMRI results

308   We first investigated which regions responded to the presentation of objects in general.

309   All object presentations (irrespectively of the specific condition) were contrasted against the

310   implicit baseline. Several areas were active, most notably the bilateral fusiform gyri and parts

311   of the left occipital cortex (see supplementary materials). These areas are part of the lateral

312   occipital complex, which is typically activated during object perception (Grill-Spector et al.,

313   2001).

Figure 2. A) Significant clusters for the noCont > (Pred + noPred) (in red) and the (Pred + noPred) > noCont (in cyan) contrasts. **B)** Beta values of individual subjects for noCont and (Pred + noPred) conditions in peak voxels of various significant clusters, along with the group means and standard errors.

To investigate the potential effect of explicit contextual expectations, irrespectively of

their validity, on brain activity during object recognition, we contrasted the Valid and Invalid

conditions with the noPred condition (paired t-test, $n = 17$). This contrast reveals areas where

expectations and sensory information are combined or integrated, i.e. areas where sensory

processing is modulated by expectations irrespectively of their validity (Summerfield &

Koechlin, 2008). Five clusters were significantly more activated in the Valid and Invalid

conditions than in the noPred condition ($p < .05$, two-tailed, corrected for family-wise error rate

(FWER); peak Cohen's $d_z = 1.91$; Figure 2; Table 1): one bilateral cluster in the precuneus

(which is part of the retrosplenial complex), one extending from the left precuneus and middle

occipital gyrus to the left angular gyrus, one in the left middle temporal gyrus, one in the left

middle and inferior frontal gyri and one in the right angular gyrus. The reverse contrast revealed

the specific activation of two clusters in the right superior and middle occipital gyri and in the

left middle occipital gyrus ($p < .05$, two-tailed, FWER-corrected; peak Cohen's $d_z = 1.73$;

Figure 2; Table 1). To confirm that our randomized jitters prevented contamination of object

responses by scene information, we also conducted supplementary analyses comparing the

same conditions but at the moment of context presentation instead of object presentation (i.e.

contrast of scenes to scrambled scenes). We observed the activation of occipital areas and most

notably, of the parahippocampal gyrus, a region typically associated to scene processing

(Epstein et al., 2003; see supplementary materials). Importantly, these regions were only partly

overlapping with those engaged at the moment of object presentation, and the scene-processing

parahippocampal place area was only implicated when directly contrasting scenes.

We then investigated whether there was a main effect of predictive value (Valid vs

Invalid), a main effect of the context's affective value (Aff vs Neut), and an interaction between

predictive and affective values at the moment of object recognition (paired t-tests, $n = 17$).

There were no significant main effects of predictive or affective values. However, there was a

significant interaction between predictive and affective values for two clusters: one in the right

cuneus and one overlapping the left cuneus, calcarine gyrus and lingual gyrus ($p < .05$, two-

Figure 3. A) Significant clusters for the interaction between affective and predictive values (in red). **B)** Beta values of individual subjects for each condition in peak voxels of significant clusters, along with the group means and standard errors.

tailed, FWER-corrected; peak Cohen's $d_z = 1.74$; Figure 3; Table 1). We then investigated the

simple effects specifically in the peak voxels (local maxima) of the clusters which had a

significant interaction effect. We observed that these voxels were more active in the Valid-Aff

condition than in the Invalid-Aff condition (left cuneus: $t(16) = 4.80$, $p_{Bonf} = .0008$, $d_z = 1.16$;

right cuneus: $t(16) = 4.56$, $p_{Bonf} = .001$, $d_z = 1.11$) and more active in the Invalid-Neut than in

the Valid-Neut condition (left cuneus: $t(16) = 4.41$, $p_{Bonf} = .002$, $d_z = 1.07$; right cuneus: $t(16)$

$= 4.24$, $p_{Bonf} = .003$, $d_z = 1.03$).

Next, we conducted a series of control analyses to ensure that the interaction could not

have been the result of undesirable confounds. First, we investigated whether the interaction

could have been caused by differences between the objects associated to neutral contexts and

those associated to affective contexts by assessing if there was any significant difference in

brain activity when they were perceived without a context (noPred condition). There was no

significant difference between the conditions ($p_{FWER} > .33$). We also analyzed the image

similarities directly: we used the HMAX model (Riesenhuber & Poggio, 1999; Serre et al.,

2007), a commonly used model of the early visual cortex, and we computed correlation

distances between the responses of the model to each image. We then verified if the between-

categories (affective context objects to neutral context objects) distances were larger than the

within-categories distances (two sample t-tests): no difference was observed (compared to

within-neutral distances: .498 vs .504, $t(3430) = .57$, $n = 1128$ and 2304, $p = .57$; compared to

within-affective distances: .498 vs .502, $t(3430) = .38$, $n = 1128$ and 2304, $p = .70$), suggesting

that the images in these two object categories are similar.

Finally, the possibility remained that attention could explain the interaction between

affective and predictive values: a similar interaction has indeed been previously reported with

attention as a factor instead of affective value (Kok et al., 2012b). A first objection to this claim

would be that our behavioral results actually trend ($p = .10$) toward an opposite effect. Although

we observe the same reversed prediction effect in the brain for affective contexts that Kok et

al. observed for task-relevant stimuli, the lower recognition accuracy in the affective condition

suggests that they are not attended more and that attention is not the cause of this interaction.

Nonetheless, we decided to conduct an additional behavioral experiment to isolate potential

attentional effects better. Twenty-four participants aged between 18 and 30 years (mean = 25.2)

performed a Gabor orientation discrimination task (vertical vs horizontal), in which the Gabor

patches (1 cycle per degree) were randomly following either a neutral context image or an

affective context image in the same way as in the fMRI experiment (contexts presented for 1s,

1.5-4 s jitter, patches presented during 133 ms). Subjects were instructed to respond as

accurately and rapidly as possible, and adaptive procedures were conducted separately in each

condition in order to find the contrast sensitivity threshold associated with each condition.

Again, no difference was observed ($\log_{10}$(contrast) of -2.10 vs -2.11; p = .94). Since we know

that contrast sensitivity is greatly enhanced by attention (see Carrasco, 2006, for a review), it

does not seem likely that affective contexts were attracting attention and maintaining it for up

to 4 seconds in order for it to alter object processing.

Table 1. Montreal Neurological Institute (MNI) coordinates and T values for significantly
activated brain regions.

Brain regions	Peak MNI coordinates			Nb of voxels	Peak T value
	x	**y**	**z**		
(Pred + noPred) > noCont					
L Middle Occipital	-30	-69	39	232	7.88
L Angular	-42	-63	27		6.63
L Middle Temporal	-54	-21	-9	76	6.92
R Angular	51	-63	36	90	6.16
L Middle Frontal	-48	18	39	94	5.79
L Inferior Frontal	-42	15	24		5.51
L Precuneus	-3	-66	54	224	5.59
R Precuneus	9	-57	42		5.32
noCont > (Pred + noPred)					
R Superior Occipital	27	-78	21	61	7.12
R Middle Occipital	36	-81	12		4.75
L Middle Occipital	-27	-84	6	90	6.76
Predict. x Affect.					

R Cuneus	15	-96	6	45	7.79
L Cuneus	-12	-90	3	43	6.08
	0	-87	-3		4.55
	-9	-84	-9		3.89

Discussion

Our first aim was to investigate how the generation of expectations about objects from

a preceding context might modulate the activity of brain areas involved in object perception.

We found significantly more activation in the precuneus, the left middle occipital gyrus, the left

middle temporal gyrus, the left frontal cortex and the parietal cortex, when (valid or invalid)

contextual expectations were generated prior to object perception, suggesting that these high-

level areas are mainly associated with object processing when expectations are generated. These

activations specifically represent an interaction between contextual expectations and object

bottom-up sensory information: activity related solely to object processing is cancelled out

because the objects are the same in both conditions, and activity related solely to the prior

presentation of the context is regressed out in the GLM.

To our knowledge, only Summerfield & Koechlin (2008) performed a similar analysis

before; however, they used lines as cues and gratings as stimuli, and the cue was directly related

to the task (the subjects had to indicate whether the cue and the grating matched). In their study,

they observed a significantly greater activation of the middle occipital and fusiform gyri when

there was an expectation. We also find a greater activation of the middle occipital gyrus, in

addition to many other brain regions. Since expectations in our study are about objects rather

than simple grating orientations, regions representing them are likely to be more numerous. The

interaction between object and context processing observed in the middle temporal gyrus (a

part of the inferotemporal cortex) supports a popular hypothesis according to which top-down

contextual predictions would be combined with bottom-up sensory information to facilitate

object recognition in the inferotemporal cortex (Bar, 2004). The precuneus and the parietal

cortex, which are also activated in this contrast, have previously been linked to episodic

memory retrieval and contextual associative processing (Lundstrom et al., 2005; Aminoff et al.,

2007; Livne and Bar, 2016; Brandman and Peelen, 2017) which both require the integration of

stored representations with incoming sensory information. Moreover, the precuneus of an

observer that views several objects simultaneously is more activated when these objects are

contextually related than when they are not (Livne and Bar, 2016); this suggests that the

contextual representations elicited by some of these objects are compared to other objects.

Recently, activity in the retrosplenial complex, a region comprising the precuneus, has been

shown to correlate with supra-additive decoding of objects embedded in scenes, suggesting that

the precuneus is responsible for a scene-based facilitation of object representations (Brandman

and Peelen, 2017). Interestingly, the interaction we observed between context and object

information in the precuneus is also supra-additive (i.e. there is a remaining positive activation

after considering the main effects of object and context). We extend previous results by showing

that the precuneus integrates object sensory information with valid or invalid scene-based

expectations generated prior to object presentation. The inferior and middle frontal gyri were

also active during object processing when expectations were generated. These regions have

previously been found to respond more to objects in non-congruent scenes than to objects in

congruent scenes (Rémy et al., 2014): it is thus likely that they are responsible of integrating

contextual information with perceived objects. The prefrontal cortex has also been linked to

object-related predictions in other studies (Bar, 2007; Bar et al., 2006) and has been found to

both maintain expectations and integrate them with sensory information (Summerfield et al.,

2006; Summerfield & Koechlin, 2008).

The reverse contrast, associated with visual processing of objects when no expectation

(neither valid nor invalid) had been generated from a context, yielded bilateral activation of

primary visual areas. Activated voxels may be part of areas primarily associated with the

processing of sensory information shared by a majority of objects (e.g., intermediate spatial

frequencies; Caplette et al., 2014), which is thus reduced when almost any object is expected.

We then investigated whether there was an effect of prediction error or match, i.e.

whether some areas were more active at the presentation of the object when the object followed

a valid context or when the object followed an invalid context. When neutral and affective

contexts were combined, there was no significant difference between valid and invalid

conditions; however, there was a significant interaction between predictive and affective values

in low-level occipital areas, specifically the left and right cunei. Looking at this cluster, the

classical prediction error effect was visible for neutral contexts, i.e. validly predicted objects

elicited a smaller BOLD signal; but, when contexts were affective, this effect was reversed, i.e.

validly predicted objects elicited a larger BOLD signal. Note that previous studies observing a

smaller signal for validly predicted objects have exclusively used affectively neutral cues,

making our results compatible with theirs.

These results are not compatible with the proposal that a subject's internal affective state

is altering the content of their predictions about object identities (Barrett and Bar, 2009).

According to this idea, the affective value of a preceding context (or even a simultaneous

context or the object itself; see Barrett and Bar, 2009) would alter the subject's bodily state and

bring additional information that could be used by the brain to predict the identity of perceived

objects. Consequently, a similar pattern of results should be visible for neutral and emotional

contexts, with only a greater difference in activation between validly predicted and invalidly

predicted objects for emotional contexts than for neutral contexts (due to the additional

emotional information).

Our results are compatible, however, with the general idea that affect interacts with

predictive processing (Barrett and Simmons, 2015; Miller and Clark, 2018). One possibility

recently put forward by some authors is that, rather than contributing to the content of the

predictions, a subject's internal affective state modulates the weight given to prediction errors

during perceptual inference (Miller and Clark, 2018). Specifically, this weight would increase

when the subject is experiencing affect. According to recent predictive coding models, such an

increased weighting should lead to a reversal of the classical prediction error effect, as we

observed (Feldman & Friston, 2010; Kok et al., 2012b).

Note that most affective contexts (11/15) used in our experiment had a positive valence.

This may have affected the results. However, because negative contexts were especially

negative, the median valence for affective contexts was still close to neutral (5.8, 0 being the

most negative and 10 the most positive). Moreover, Miller & Clark (2018) do not differentiate

between positive and negative stimuli in their proposal and, generally, the same brain network

seems to be implicated in the processing of all affective stimuli, irrespective of valence

(Lindquist et al., 2016).

Kok and colleagues (Kok et al., 2012b) reported a similar reversal of the prediction error

effect in the early visual cortex for task-relevant stimuli. They argued that this effect was caused

by endogenous attention increasing the weight of prediction errors (Friston, 2009; Feldman &

Friston, 2010; Rao, 2005). This cannot be the cause of the effect we observed however, since

attention was not manipulated in our study and our stimuli were all similarly task relevant.

Furthermore, exogenous attention was also similar between our conditions, as revealed by

behavioral results obtained in the scanner and in the control contrast sensitivity experiment.

This implies that the reversal of the prediction error effect in our study was not caused by an

increase in attention.

Notably, we observed significant main effects neither of predictive nor of affective

value. The absence of a main effect of prediction can be explained by the fact that the effect of

prediction is completely reversed depending on the affective value and so is cancelled when all

contexts are combined. The absence of a main effect of affect might be due at least partly to the

fact that our contrast concerns object processing and that affective value was at the level of the

context. However, we also did not observe the activation of several regions typically implicated

in affect processing during affective scene presentation (see supplementary materials). Our

scenes, which were for the most part everyday contexts, possibly did not have a sufficient

intensity to elicit such activations: the stimuli used in most fMRI studies are often of a much

higher average intensity (e.g., IAPS; Lang et al., 2005).

In summary, real-world expectations initiated by contexts, irrespectively of their degree

of validity, led to more activation of high-level areas (including parietal and frontal cortices)

during subsequent object recognition; notably, these regions were distinct from those

responsible of instantaneous context-object interactions. It is important however to note that

these prior expectations are not necessarily explicit and conscious: they are representations

preactivated by the perception of the scene, which will impact the processing of subsequent

stimuli. In addition, the context's affective value interacted with the validity of the prediction

it had initiated: classical prediction error effects were only observed with neutral contexts, and

a complete reversal of these effects was observed when contexts were emotional. This result is

not compatible with the idea that the affective value of a stimulus, and the ensuing internal

bodily state of the subject, are contributing to the creation of predictions (Barrett and Bar,

2009); but it is compatible with a modulatory role of affective value over the weight of sensory

evidence in perception (Miller and Clark, 2018). In conclusion, our results deepen our

understanding of predictive coding in an ecological setting by showing that the mere presence

of explicit expectations, and their affective content, modulate object recognition.

References

Alink A, Schwiedrzik CM, Kohler A, Singer W, Muckli L (2010) Stimulus predictability

reduces responses in primary visual cortex. J Neurosci 30(8):2960–2966.

Aminoff EM, Gronau N, Bar M (2007) The parahippocampal cortex mediates spatial and

nonspatial associations. Cereb Cortex 17(7):1493–1503.

Bar M (2003) A cortical mechanism for triggering top-down facilitation in visual object

recognition. J Cogn Neurosci 15(4):600–609.

Bar M (2004) Visual objects in context. Nat Rev Neurosci 5(8):617–629.

Bar M, Aminoff E (2003) Cortical analysis of visual context. Neuron 38(2):347–358.

Bar M, Kassam KS, Ghuman AS, Boshyan J, Schmid AM, Dale AM, Hämäläinen MS,

Marinkovic K, Schacter DL, Rosen BR, Halgren E (2006) Top-down facilitation of visual

recognition. Proc Natl Acad Sci U S A 103(2):449–454.

Bar M, Ullman S (1996) Spatial context in recognition. Perception 25:343–352.

Barrett LF, Bar M (2009) See it with feeling: affective predictions during object perception.

Philos Trans R Soc Lond B Biol Sci 364(1521):1325–1334.

Barrett LF, Simmons WK (2015) Interoceptive predictions in the brian. Nat Rev Neurosci

16:419-429.

Biederman I, Mezzanotte RJ, Rabinowitz JC (1982) Scene perception: Detecting and judging

objects undergoing relational violations. Cogn Psychol 14(2):143–177.

Brandman T, Peelen MV (2017) Interaction between scene and object processing revealed by

human fMRI and MEG decoding. J Neurosci 37(32):7700–7710.

Caplette L, West G, Gomot M, Gosselin F, Wicker B (2014) Affective and contextual values

modulate spatial frequency use in object recognition. Front Psychol 5:512.

Carrasco M (2006) Covert attention increases contrast sensitivity: psychophysical,
neurophysiological and neuroimaging studies. Prog Brain Res 154A:33–70.

Davenport JL, Potter MC (2004) Scene Consistency in Object and Background Perception.
Psychol Sci 15(8):559–564.

de Lange FP, Heilbron M, Kok P (2018) How do expectations shape perception? Trends Cogn
Sci 22(9):764–779.

den Ouden HEM, Daunizeau J, Roiser J, Friston KJ, Stephan KE (2010) Striatal prediction error
modulates cortical coupling. J Neurosci 30(9):3210–3219.

Eickhoff SB, Stephan KE, Mohlberg H, Grefkes C, Fink GR, Amunts K, Zilles K (2005) A new
SPM toolbox for combining probabilistic cytoarchitectonic maps and functional imaging
data. Neuroimage 25(4):1325–1335.

Epstein R, Graham KS, Downing PE (2003) Viewpoint-Specific Scene Representations in
Human Parahippocampal Cortex. Neuroimage 37(5):865–876.

Faivre N, Dubois J, Schwartz N, Mudrik L (2019) Imaging object-scene relations processing in
visible and invisible scenes. Sci Rep 9:4567.

Feldman H, Friston KJ (2010) Attention, uncertainty, and free-energy. Front Hum Neurosci
4:215.

Friston KJ (2005) A theory of cortical responses. Philos Trans R Soc Lond B Biol Sci
360(1456):815–836.

Friston KJ (2009) The free-energy principle: a rough guide to the brain? Trends Cogn Sci
13(7):293–301.

Friston KJ, Worsley KJ, Frackowiak RSJ (1994) Assessing the significance of focal activations
using their spatial extent. Hum Brain Mapp 1:214-220.

Goh JOS, Siong SC, Park D, Gutchess A, Hebrank A, Chee MWL (2004) Cortical areas
involved in object, background, and Object-Background Processing Revealed with
Functional Magnetic Resonance Adaptation. J Neurosci 24(45):10223–10228.

Grill-Spector K, Kourtzi Z, Kanwisher N (2001) The lateral occipital complex and its role in
object recognition. Vision Res 41(10–11):1409–1422.

Gronau N, Neta M, Bar M (2008) Integrated contextual representation for objects' identities
and their locations. J Cogn Neurosci 20(3):371–388.

Hindy NC, Ng FY, Turk-Browne NB (2016) Linking pattern completion in the hippocampus
to predictive coding in visual cortex. Nat Neurosci 19(5):665–667.

Jenkins LJ, Yang YJ, Goh J, Hong YY, Park DC (2010) Cultural differences in the lateral
occipital complex while viewing incongruent scenes. Soc Cogn Aff Neurosci 5:236–241.

Jiang J, Summerfield C, Egner T (2013) Attention sharpens the distinction between expected
and unexpected percepts in the visual brain. J Neurosci 33(47):18438–18447.

Kirk U (2008). The neural basis of object-context relationships on aesthetic judgment. PLoS
ONE 3(11):e3754.

Kok P, Failing MF, de Lange FP (2014) Prior expectations evoke stimulus templates in the
primary visual cortex. J Cogn Neurosci 26(7):1546–1554.

Kok P, Jehee JFM, de Lange FP (2012a) Less is more: expectation sharpens representations in
the primary visual cortex. Neuron 75(2) :265–270.

Kok P, Mostert P, de Lange FP (2017) Prior expectations induce prestimulus sensory templates.
Proc Natl Acad Sci U S A 114(39):10473–10478.

Kok P, Rahnev D, Jehee JFM, Lau HC, de Lange, FP (2012b) Attention reverses the effect of
prediction in silencing sensory signals. Cereb Cortex 22(9):2197–2206.

Kok P, Turk-Browne NB (2018). Associative prediction of visual shape in the hippocampus. J
Neurosci 38(31):6888–6899.

Lang PJ, Bradley MM, Cuthbert BN (2005) International affective picture system (IAPS):

Affective ratings of pictures and instruction manual. Technical report A-6. Gainesville:

University of Florida.

Lebrecht S, Bar M, Barrett LF, Tarr MJ (2012) Micro-valences: perceiving affective valence in

everyday objects. Front Psychol 3:107.

Lindquist KA, Wager TD, Kober H, Bliss-Moreau E, Barrett LF (2016) The brain basis of

emotion: A meta-analytic review. Behav Brain Sci 35(3): 121–143.

Livne T, Bar M (2016) Cortical integration of contextual information across objects. J Cogn

Neurosci 28(7):948–958.

Lundstrom BN, Ingvar M, Petersson KM (2005) The role of preuneus and left inferior frontal

cortex during source memory episodic retrieval. Neuroimage 27(4):824–834.

Maldjian JA, Laurienti PJ, Kraft RA, Burdette JH (2003) An automated method for

neuroanatomic and cytoarchitectonic atlas-based interrogation of fMRI data sets.

Neuroimage 19(3):1233–1239.

Miller M, Clark A (2018) Happily entangled: prediction, emotion, and the embodied mind.

Synthese 195(6):2559–2575.

Mumford D (1992) On the computational architecture of the neocortex: II. The role of cortico-

cortical loops. Biol Cybern 66:241.

Oliva A, Torralba A (2007) The role of context in object recognition. Trends Cogn Sci

11(12):520–527.

Palmer SE (1975) The effects of contextual scenes on the identification of objects. Mem Cogn

3(5):519–526.

Rao RPN (2005) Bayesian inference and attentional modulation in the visual cortex.

Neuroreport 16(16):1843–1848.

Rao RPN, Ballard DH (1999) Predictive coding in the visual cortex: a functional interpretation

of some extra-classical receptive-field effects. Nat Neurosci 2(1):79–87.

Rémy F, Vayssière N, Pins D, Boucart M, Fabre-Thorpe M (2014) Incongruent object/context

relationships in visual scenes: Where are they processed in the brain? Brain Cogn 84(1):34–

43.

Riesenhuber M, Poggio T (1999) Hierarchical models of object recognition in cortex. Nat

Neurosci 2:1019–1025.

Serre T, Wolf L, Bileschi S, Riesenhuber M, Poggio T (2007) Robust object recognition with

cortex-like mechanisms. IEEE Trans on Pattern Anal Mach Intell 29:411–426.

Summerfield C, Egner T, Greene M, Koechlin E, Mangels J, Hirsch J (2006) Predictive codes

for forthcoming perception in the frontal cortex. Science 314(5803):1311–1314.

Summerfield C, Koechlin E (2008) A neural representation of prior information during

perceptual inference. Neuron 59(2):336–347.

Summerfield C, Trittschuh EH, Monti JM, Mesulam MM, Egner T (2008) Neural repetition

suppression reflects fulfilled perceptual expectations. Nat Neurosci 11(9):1004–1006.

Todorovic A, de Lange F O (2012) Repetition suppression and expectation suppression are

dissociable in time in early auditory evoked fields. J Neurosci 32(39):13389–13395.

Ullman S (1995) Sequence seeking and counter streams: a computational model for

bidirectional information flow in the visual cortex. Cereb Cortex 5(1):1–11.