Hybrid Automata Library: A modular platform for efficient hybrid modeling with real-time visualization

December 17, 2018

Rafael Bravo[1,3], Etienne Baratchart[1], Jeffrey West[1], Ryan O. Schenck[1,2], Anna Miller[1], Jill Gallaher[1], Chandler Gatenbee[1], David Basanta[1], Mark Robertson-Tessi[1], Alexander R. A. Anderson [1,4]

1:Integrated Mathematical Oncology, Moffitt Cancer Center, Tampa, FL, 33612, USA

2:Wellcome Centre for Human Genetics, University of Oxford, Oxford, OX3 7BN, UK

3:rafael.bravo@moffitt.org,**4**:alexander.anderson@moffitt.org

Abstract

The Hybrid Automata Library (HAL) is a Java Library developed for use in mathematical oncology modeling. It is made of simple, efficient, generic components that can be used to model complex spatial systems. HAL's components can broadly be classified into: on- and off-lattice agent containers, finite difference diffusion fields, a GUI building system, and additional tools and utilities for computation and data collection. These components are designed to operate independently and are standardized to make them easy to interface with one another. As a demonstration of how modeling can be simplified using our approach, we have included a complete example of a hybrid model (a spatial model with interacting agent-based and PDE components). HAL is a useful asset for researchers who wish to build efficient 1D, 2D and 3D hybrid models in Java, while not starting entirely from scratch. It is available on github at https://github.com/torococo/HAL under the MIT License. HAL requires at least Java 8 or later to run, and the Java JDK version 1.8 or later to compile the source code.

1 Author Summary

In this paper we introduce the Hybrid Automata Library (HAL) with the purpose of simplifying the implementation and sharing of hybrid models for use in mathematical oncology. Hybrid modeling is used in oncology to create spatial models of tissue, typically by modeling cells using agent-based techniques, and by modeling diffusible chemicals using partial differential equations (PDEs). HAL's key components are designed to run agent-based models, PDEs, and visualization. The components are standardized and are completely decoupled, so models can be built with any combination of them. We first explore the philosophy behind HAL, then summarize the components. Lastly we demonstrate how the components work together with an example of a hybrid model, and a walk-through of the code used to construct it. HAL is open-source and will produce identical results on any machine that supports Java 8 and above, making it highly portable. We recommend HAL to modelers interested in spatial

dynamics, even those outside of mathematical oncology, as the components are general enough to facilitate a variety of model types. A community page that provides a download link and online documentation can be found at https://halloworld.org [1].

2   Introduction

The Hybrid Automata Library (HAL) was created to assist the growing mathematical oncology community with a common framework for efficiently building and visualizing hybrid models. Hybrid models in oncology usually represent cells (both of the tumor and of the surrounding tissue) using agent-based modeling (ABMs) and the concentrations of relevant chemicals (drugs, resources and signaling molecules) as continuous partial differential equations (PDEs). These models can simulate local interactions between cells with complex internal dynamics and decision-making processes while also allowing cells to interact with the PDE concentration fields in their local environment.

Hybrid models have been widely adopted within the Mathematical Oncology community to model many aspects of cancer [2–5]. A unique strength of the hybrid modeling approach is that it allows for a mechanistic understanding of the ecological feedback between the cancer cells and their tissue environment. Cancer cell agents can be modeled as a part of the surrounding tissue, and interact with the systems that normally maintain homeostasis. [6–11] Drugs may be subsequently introduced to add additional selective pressure to the model, and the long-term effects on the tumor evolution observed. A better understanding of these selection dynamics can be used to help develop more effective drug sequences to prevent cancer resistance to therapy and to develop evolutionary therapies to control cancers that cannot be cured with maximum tolerated dose [12–14]. Further realism can be incorporated by initializing spatial models with clinical or histological data [15, 16].

Whilst a number of agent-based modeling frameworks have been used for tissue modeling, including MASON, Repast, Physicell, CompuCell3D, Chaste, and Netlogo, we designed HAL to be simpler, more efficient, and more flexible.

Some of these frameworks facilitate model building under specific spatial interaction assumptions like PhysiCell [17], which treats cells as spheres under Newtonian adhesion-repulsion dynamics and is optimized for large cell populations, and CompuCell 3D [18], which models cells as contiguous composites of lattice positions, allowing cell deformation. HAL does not include the same depth in the domains specific to these frameworks, but uses a broader approach to provide the capacity for a variety of approaches.

Some of the most popular frameworks that also take a broad approach are Chaste, Repast, Mason, and Netlogo. Chaste uses an assumption based system for model building, in which modular rules are composed to define behavior, and behaviors that are not currently represented can be added as new modules [19]. This modular approach allows for very rapid prototyping, and increases the reproducibility of results. Repast uses a hierarchical nesting approach to group agents into sets that will all execute some action, and also features a highly customizable scheduling procedure to sequence these actions [20]. MASON is probably the most architecturally similar to HAL, as it also strives to be a modular agent-based modeling package, with built-in optional visualization tools and comparatively lax structure [21]. Netlogo uses a custom scripting language in order to simplify the coding process [22]. Netlogo also provides an accessible model development environment, making it a great choice for new modelers/coders. Each of these frameworks facilitates modeling under a different centralized scheduling structure, as mentioned in Table 1.

HAL shares many characteristics with these frameworks, but differentiates itself with a minimal, decentralized design made up of independent building blocks that are

Name	Language	Scheduling Structure	Spatial Representations
HAL	Java	For-Loop Iteration	On/Off-lattice, Newtonian Physics
PhysiCell	C++	Domain Specific	Newtonian Physics
CompuCell 3D	Python/XML	Domain Specific	On Lattice Composites
Chaste	C++	Modular Behavior Based	On/Off-lattice, Newtonian Physics, Voronoi
Repast	Java	Group-Based Scheduler	On/Off-lattice, Network
Mason	Java	Agent-Level-Scheduler	On/Off-lattice
Netlogo	Netlogo	Go Loop	On/Off-lattice, Spatial Networks

Table 1. Comparison of HAL with other agent-based Modeling Frameworks commonly used in tissue modeling

thematically similar. There is no centralized controller or scheduler, so the modeler   92
designs the logical flow and the scheduling of interactions between model components.   93
This removes common presuppositions or requirements made by schedulers in other   94
frameworks (eg. when models should be visualized, when their step logic should run,   95
when models should be created or destroyed, etc.) and leaves these decisions up to the   96
modeler. This cuts down on any unnecessary use of resources by the modeling system,   97
and increases model flexibility. These considerations have led to a lightweight   98
framework that is easy to use, highly flexible, and effective within the scope of hybrid   99
modeling, agent-based modeling, and the solving of reaction-diffusion PDEs using finite   100
differences. HAL was designed with mathematical oncology in mind, but is general   101
enough to facilitate modeling systems from many domains (eg. ecology [23],   102
development, population dynamics, and network theory). [17]. While some familiarity   103
with the Java programming language is recommended for new users of HAL, we imagine   104
that its simplicity and explicit nature could make it a useful educational platform.   105

The main components of HAL consist of n-dimensional (0D,1D,2D,3D) Grids that   106
hold Agents, 1D,2D, and 3D finite difference PDE fields, 2D and 3D visualization tools,   107
and methods for sampling distributions and data recording. In this paper we will   108
discuss the philosophy behind these components, then look at their design and   109
capabilities in more detail. See the manual for a complete reference on how to use these   110
components [24].   111

3 Design And Implementation   112

3.1 Design Philosophy   113

In the next section, we discuss some of the design decisions that have driven the   114
architecture of HAL.   115

3.1.1 Language Choice   116

In designing HAL we have tried to balance an adherence to speed, memory   117
management, simplicity, stability, modularity and extensibility. The Java language itself   118
balances these considerations very well, making it a suitable basis for HAL. High   119
performance languages such as C, C++, and Fortran, can be coded to run at speeds   120
comparable to or faster than Java, however these languages require more low-level   121
management. Moreover, they do not have the same security guarantes as they permit   122
out-of-bounds memory accesses and memory leaks. Higher level languages, such as   123
Python, while more flexible and syntactically intuitive than Java, are typically   124
significantly slower. Java is also one of the most commonly used and taught   125
programming languages today, which helps facilitate the adoption of HAL by new users.   126
The fact that Java is cross-platform is also ideal.   127

3.1.2 Modularity and Extensibility 128

HAL's components can each function independently. This permits any number of 129
components to be used in a single model, with the use of spatial queries to combine 130
components, as seen in Fig 1. This modularity also allows modelers to choose only the 131
components of HAL that are of interest for their project. These components can be 132
easily mixed and matched with other software, such as using the AgentGrids with a 133
different PDE solver, or using the GUI and Visualization components with a different 134
modeling system. Modularity also makes adding new components more manageable and 135
easier to test without adding bulk or heavy modifications to the core of the platform. 136

Figure 1. The modular design of HAL helps build complex models out of simple
components. The highlighted on-lattice agent in the topmost grid searches for local
overlaps with several other grids and PDEs. These overlaps can be used in a model to
generate spatial interactions.

Given the incremental nature of many scientific endeavors, we also wanted to allow 137
models and components to be extended and modified. Java's extension architecture 138
provides an excellent environment for layered development. As an example of the 139
extensibility of HAL, the built-in Spherical Agent types (SphericalAgent2D, 140
SphericalAgent3D) extend the Point Agent types (AgentPT2D, AgentPT3D). By 141
default, Point Agents have no radius and will not collide with each other. This behavior 142
can be useful for modeling phenomena such as the Brownian motion of small particles, 143
as visualized in Fig 2a. Spherical Agents extend Point Agents by adding an additional 144
radius variable and velocity component variables. These properties combined with 145
added functions for summing force vectors in response to overlap allow for a Newtonian 146
adhesion-repulsion spherical model of spatial agents. This behavior can be useful for 147
modeling tissue formation, as visualized in Fig 2b. 148

A   **B**

Figure 2. Off-lattice agent examples. Each example contains 1000 agents. **(A)** Example of 2D Point Agents modeling Brownian motion. The Point Agents move freely and cannot collide. **(B)** Example of 2D Spherical Agents modeling growing tissue. The agents will push apart from each other to a uniform density. Agent radii are shown as gray circles around their centers. Examples Displayed unsing the OpenGL2DWindow object.

It is also possible to extend completed models using the same approach. For example, grids and agents from published models can be used as a scaffold on which to do additional studies. This allows for followup studies to focus on implementing whatever additional assumptions and functionality they need, while leaving intact the base model code with all of its published assumptions.

3.1.3 Simplicity and Stability

An important design principle was to make HAL simple to use without sacrificing performance. Simplicity makes HAL easy to learn and forces the components to be more generic, meaning that the same components can be applied to a greater variety of modeling problems. There is also a consistency to each framework component, such that learning to use some components is often sufficient to grasp the others, and makes using them in combination intuitive.

Another key design principle is stability, which is achieved in three ways:

Encapsulation By providing safe interaction functions and preventing direct interaction with component internals. For example, modelers are not permitted to directly modify the position properties of agents. Instead, they must call the provided movement functions that also update the grid position of the agents for future spatial queries.

Defensive Programming By including checks in functions for invalid inputs. The program halts and throws an error message immediately when one of these problematic inputs occurs. This allows the user to see what caused the problem, rather than seeing its effects later down the line.

Unit Tests By testing HAL's components. HAL is very shallow by design, leaving little complexity for bugs to hide in. The more complex algorithms are tested in a series of small test programs. These tests help ensure confidence in the mathematics while also serving as simple tutorials.

3.1.4 Speed and Memory Management ₁₇₄

Much of the performance capability of HAL comes directly from its decentralized design. ₁₇₅
Having no built-in scheduler/underlying structure means that there is comparatively ₁₇₆
little work that the program does that the modeler is unaware of. This combined with ₁₇₇
the modular components and utilities allows modelers the flexibility to incorporate the ₁₇₈
functionality that they need, without the software sacrificing performance by implicitly ₁₇₉
doing unnecessary tasks. ₁₈₀

HAL also prioritizes performance in its algorithmic implementation. HAL includes ₁₈₁
efficient PDE solving algorithms, such as the ADI (alternating direction implicit) ₁₈₂
method, and uses efficient distribution samplers rather than naive approaches. The ₁₈₃
integrated visualization tools are also highly efficient, using Swing BufferedImages for ₁₈₄
lattice-based visualization, and lwjgl OpenGL for 2D and 3D polygon graphics. ₁₈₅
Whenever possible, primitives and arrays are used to store data rather than classes, ₁₈₆
which takes advantage of Java's optimization for these simpler data types. Java is also ₁₈₇
an inherently fast language, which helps efficiently execute agent behavioral logic. ₁₈₈

There is a memory footprint consideration with most of HAL's assets. A common ₁₈₉
criticism of Java applications is that they tend to use a lot of memory and are slowed ₁₉₀
down by Java's "garbage collector" which deletes objects that are no longer being used. ₁₉₁
To sidestep these memory issues, most of the objects generated internally by HAL are ₁₉₂
recycled rather than discarded. This reuse also has a performance benefit: if a function ₁₉₃
using the same object is called many times sequentially, the object will be faster to ₁₉₄
access in the computer's memory because it was already cached from the earlier calls. ₁₉₅

A key example of this reuse: when agents die and are removed from the model ₁₉₆
during a simulation run, the removed agents are kept internally and will be returned ₁₉₇
again for re-initialization when a new agent is requested. Agent recycling ensures that ₁₉₈
the number of agents that the model creates over a complete model run is capped to the ₁₉₉
maximum population that exists in the model at one time. ₂₀₀

3.2 Component Overview ₂₀₁

We now move from the abstract discussion of the unifying principles behind HAL to a ₂₀₂
look at its core components in more detail. Although it may seem that learning how to ₂₀₃
use these components would be a difficult task given their number and variety, all ₂₀₄
components were designed with a consistent API (Application Programming Interface), ₂₀₅
which makes changing between agent/grid types and learning their methods much easier. ₂₀₆

3.2.1 AgentGrids ₂₀₇

AgentGrids are used as spatial containers for agents. They come in 1D, 2D, 3D, and ₂₀₈
non-spatial types. An example usage of a 3D AgentGrid is shown in Fig 3. These ₂₀₉
objects hold populations of agents that exist either bound to a lattice, or are free to ₂₁₀
move continuously. Internally, AgentGrids are composed of two data-structures: an ₂₁₁
agent list for agent iteration, and an agent lattice for spatial queries (even off-lattice ₂₁₂
agents are stored on a lattice for quick access). The agent list can be shuffled at every ₂₁₃
iteration to randomize iteration order, and the list holds onto removed agents to ₂₁₄
facilitate object recycling. ₂₁₅

3.2.2 Agents ₂₁₆

There are 10 base types of agent, introduced in Table 2. The SQ and PT suffixes refer ₂₁₇
to whether the agents are imagined to exist as lattice bound squares/voxels, or as ₂₁₈
non-volumetric points in space. ₂₁₉

Name	Spatial Dimension	Lattice Bound	Stackable
Agent0D	0	N/A	N/A
AgentSQ1D	1	yes	yes
AgentSQ1Dunstackable	1	yes	no
AgentPT1D	1	no	yes
AgentSQ2D	2	yes	yes
AgentSQ2Dunstackable	2	yes	no
AgentPT2D	2	no	yes
AgentSQ3D	3	yes	yes
AgentSQ3Dunstackable	3	yes	no
AgentPT3D	3	no	yes

Table 2. The 10 base agent types in HAL. The differences between them are displayed in each column. Stackable refers to whether multiple agents can exist on the same lattice position

Agent objects are always bound to a grid. In their base class form, agents keep track of their position on the grid and their age. Newly created agents are not included in the same iteration loop in which they are created, to prevent infinite loops of "runaway proliferation." The base agent classes can be extended to include additional state properties and methods as needed.

Figure 3. An example of a 3D on-lattice hybrid model of tumor cells spreading through tissue. The red vertical lines represent vessels, and the blue dots represent tumor cells. The cell color goes from pink to blue depending on how much oxygen is locally available. Displayed using the OpenGL3DWindow object.

3.2.3   PDEGrids

The PDE Grids consist of either a 1D, 2D, or 3D lattice of concentrations. PDE grids contain functions that will solve reaction-diffusion equations. PDE function operations are accumulated on a separate lattice so they can be applied all at once in a simultaneous update. Currently implemented PDE solution methods include:

- Forward difference in time and 2nd order central difference in space diffusion
- ADI Diffusion [25]
- 1st order upwind finite difference advection for incompressible flows [26]
- 1st order finite volume upwind advection for compressible flows

- Modification of values at single lattice positions to facilitate reaction with agents or other sources/sinks. 234 235

Most of these methods are flexible, allowing for spatially heterogeneous diffusion rates and advection velocities as well as different boundary conditions such as periodic, Dirichlet, and zero-flux Neumann. 236 237 238

3.2.4 Graphical User Interface (GUI) 239

The GUI building system consists of the following components: 240

- UIWindow: a window that displays GUI sub-components which are added in columns. the UIWindow will automatically scale to the appropriate size to fit all sub-components. The following five sub-components can be added: 241 242 243

  - UIGrid: a grid of pixels whose values are set individually. These are typically used to plot agent positions and diffusible concentrations, and can be easily output in GIF or PNG formats. 244 245 246
  - UIPlot: an extension of the UIGrid, the UIPlot is used to create real-time plots. The UIPlot will automatically resize to fit points that fall out of its bounds. 247 248 249
  - UILabel: a label that presents modifiable text. 250
  - UIButton: a button that executes a function when clicked 251
  - UIInputFields: various fields that accept bounded input of Integers, Doubles, Strings, Booleans, File Creation/Selection, and Combo boxes 252 253

- Window2DOpenGL/Window3DOpenGL: visualization windows that use OpenGL to efficiently render polygon graphics. 254 255

- GridWindow: A shortcut to generate a UIWindow with a single UIGrid component embedded. This simple component is used in the results section example. 256 257 258

- GifMaker: An object that can turn UIGrid visualization snapshots into gifs (Original source code created by Patrick Meister [27]). 259 260

An example GUI that uses the UIWindow with embedded UIButtons, InputFields, UILabels, and a UIGrid is shown in Fig 4. 261 262

Figure 4. An example UIWindow GUI. When the "Run" UIButton (bottom left) is clicked, the UIGrid component (right) displays a running model that is parameterized with the given UIInputField settings (left). In this example model based on [28], the red cells are stem cells, and the blue cells are differentiated cells. Differentiated cells have a limited number of divisions and therefore can only spread a limited distance from the stem cells. UILabels (top) show the current timestep and population size.

3.2.5 Utilities

The Util and Rand classes are used with almost every project. The Util class consists of a collection of standalone functions that solve common problems such as: Generating colors for use with the visualization tools, array manipulation, generating coordinate neighborhoods (eg. VonNeumann, Moore, Hex, Triangular), spatial mathematical operations, multicore parallelization, functions to save and load model states, etc. The Rand class is used for generating random numbers and for sampling distributions (eg. Gaussian, Poisson, Binomial, Multinomial - created using code adapted from the Colt and Numpy open source libraries [29, 30]) See the manual for more information [24].

3.2.6 Tools

A set of miscellaneous tool objects are included to help with specific modeling tasks, these include:

- A FileIO object that is used to read input files and output results.

- A GenomeTracker object that internally stores phylogeny information in a searchable tree structure, and can be used to model branching processes.

- An ODESolver object that can solve ODEs numerically using Euler, Runge-Kutta 4, and Runge-Kutta Fehlberg 4,5 integration. ²⁷⁸ ²⁷⁹

- A Multi-Well Experiment object that uses multi-threading to run and display many models simultaneously. The modeler simply creates an array of initialized models, defines an update and draw step, and can then feed many models into the Multi-Well experiment object and observe divergences in dynamics. This allows modelers to intuitively seed different models or replicates of the same conditions and observe differences in their behavior over time, see Fig 5 ²⁸⁰ ²⁸¹ ²⁸² ²⁸³ ²⁸⁴ ²⁸⁵

Figure 5. Example of a 10x10 Multi-Well experiment where evolutionary competition of two phenotypes (red,green) shows divergent results with different random seeds. models are separated with red lines.

- An InteractiveModel object that embeds models in a graphical user interface from which the modeler can schedule modifications to parameters, such as treatment application, and interact with their model in real time. Modelers may also rewind execution to adjust settings, helping them to more quickly understand their model dynamics, and identify useful drug combinations and schedules. This tool exemplifies the power of modular design, and uses a UIPlot object for the timeline, as well as several UIGrids and UIButtons for other interactive components. This tool was used as part of the development of the Cancer Crusade game [31] to test ²⁸⁶ ²⁸⁷ ²⁸⁸ ²⁸⁹ ²⁹⁰ ²⁹¹ ²⁹² ²⁹³

the effects of therapy on a model by Tessi et al. [12], see Fig 6.

Figure 6. Example usage of the InteractiveModel object, allowing the modeler to experiment with treatment strategies using a model of the by Tessi et al. [12]. **(A)** A spatial visualization of the current model state. **(B)** A control panel of UIButtons allows the user to quickly restart the model, pause execution, clear all treatments, and undo previous changes. Hotkeys for these controls are in brackets. **(C)** A Speed Control option allows the user to easily adjust the execution speed of the model to range from evaluating as fast as possible to taking a second between time-steps, allowing for careful observation of model dynamics. **(D)** A timeline that will plot timestep information so that the user may observe aggregate changes over time in response to treatment. The user may also click anywhere in the timeline to backtrack to a previous timepoint and replay the model from there. The timeline will also automatically backtrack to recalculate any necessary frames when a treatment schedule change is made. **(E)** A set of sliders that allow the user to select different treatment intensities for each drug. **(F)** Each horizontal bar parallels the simulation timeline and displays the schedule of a different treatment. Modelers can click on regions within these bars to change regions to a new treatment intensity selected in (E). Modelers may also use the hotkeys presented in (E) to apply the selected intensities in real time as the model runs.

4 Results: Competitive Release Model

To demonstrate how the aforementioned principles and components of HAL are applied, we consider a simple but complete example of hybrid modeling. We implement the

model of pulsed therapy based on a recent publication by Gallaher et al. [14]. We also ²⁹⁸
showcase the flexibility that the modular component approach brings by displaying ²⁹⁹
three different parameterizations of the same model side by side. ³⁰⁰

4.1 Competitive Release Introduction ³⁰¹

The model in [14] describes two competing tumor-cell phenotypes: a rapidly dividing, ³⁰²
drug-sensitive phenotype and a slower dividing, drug-resistant phenotype. There is also ³⁰³
a diffusible drug that enters the system through the domain boundaries and is ³⁰⁴
consumed by the tumor cells over time. ³⁰⁵

Every timestep ("tick") each cell has a probability of death and a probability of ³⁰⁶
division. The division probability depends on phenotype (resistant cells divide less ³⁰⁷
frequently) and the availability of space (cells will divide only if there is an open space ³⁰⁸
in the nearest eight grid square neighborhood or moore neighborhood). Sensitive cells ³⁰⁹
have a death rate that increases when the cells are exposed to drug, while resistant cells ³¹⁰
have a constant death rate. ³¹¹

The modular design of HAL allows us to test 3 different treatment conditions, each ³¹²
with an identical starting tumor (no drug, constant drug, and pulsed drug). An ³¹³
interesting outcome of the experiment is that pulsed therapy is better at managing the ³¹⁴
tumor than constant therapy. Under pulsed therapy the sensitive population is kept in ³¹⁵
check, while still competing spatially with the resistant phenotype and preventing its ³¹⁶
expansion. The rest of the section describes in detail how this abstract model is ³¹⁷
generated. ³¹⁸

Fig 7 provides a high level look at the structure of the code. Red font indicates ³¹⁹
where a section of the coding example is called. Table 3 provides a quick reference for ³²⁰
the built-in HAL functions used in this example. Any functions that are used by the ³²¹
example but do not exist in the table are defined within the example itself and ³²²
explained in detail below the code. Those fluent in Java may be able to understand the ³²³
example just by reading the code and using Table 3. Built-in HAL functions and classes ³²⁴
are highlighted in red in the following source code to make identifying HAL's ³²⁵
components easier. ³²⁶

Figure 7. **(A)** Example program flow diagram. Red font indicates where coding example sections are first called. **(B)** CellStep function flow diagram.

Function	Object	Action
NewAgentSQ(INDEX)	AgentGrid2D	Returns a new agent, placed at the center of the square at the provided position INDEX.
ShuffleAgents(RNG)	AgentGrid2D	Usually called after every timestep to shuffle the order of agent iteration.
GetTick()	AgentGrid2D	Returns the current grid timestep.
ItoX(INDEX), ItoY(INDEX)	AgentGrid2D	Converts from a grid position INDEX into the x and y components that point to the same grid position.
MapHood(NEIGH-BORHOOD,X,Y)	AgentGrid2D	Finds all position indices in the provided neighborhood, centered around X,Y that don't fall out of bounds of the AgentGrid2D. Writes these indices into the NEIGHBORHOOD argument, and returns the number that were found.
MapEmptyHood(NEIGHBORHOOD)	AgentSQ2D	Finds all position indices in the provided neighborhood, centered around the agent, that do not have an agent occupying them. Writes these indices into the NEIGHBORHOOD argument, and returns the number that were found.
G	AgentSQ2D	Gets the grid that the agent occupies.
Isq()	AgentSQ2D	Gets the position index of the grid square that the agent occupies.
Dispose()	AgentSQ2D	Removes the agent from the grid and from iteration.
Get(INDEX)	PDEGrid2D	Returns the concentration of the PDE field at the given index.
Mul(INDEX, VALUE)	PDEGrid2D	Multiplies the concentration at the given INDEX by VALUE and adds the result to the current concentration when Update() is called
DiffusionADI(RATE)	PDEGrid2D	Applies diffusion using the ADI method with the rate constant provided. A reflective boundary is assumed. The result is applied when Update() is called.
DiffusionADI(RATE, BOUNDARY_COND)	PDEGrid2D	Applies diffusion using the ADI method with the RATE constant provided. The BOUNDARY_COND value diffuses from the grid borders. The result is applied when Update() is called.
Update()	PDEGrid2D	Applies all state changes simultaneously to the PDEGrid
SetPix(INDEX, COLOR)	GridWindow	Sets the color of a pixel.
TickPause(MILLISECONDS)	GridWindow	Pauses the program between calls to TickPause. The function automatically subtracts the time between calls from MILLISEC-ONDS to ensure a consistent timestep rate for visualization.
ToPNG(FILENAME)	GridWindow	Writes out the current state of the UIWindow to a PNG image file.
Close()	GridWindow	Closes the GridWindow.
RGB(RED, GREEN, BLUE)	Util	Returns an integer with the requested color in RGB format. This value can be used for visualization.
HeatMapRGB(VALUE)	Util	Maps the VALUE argument (assumed to be between 0 and 1) to a color in the heat colormap.
CircleHood(INCLUDE_ORIGIN, RADIUS)	Util	Returns a set of coordinate pairs that define the neighborhood of all squares whose centers are within the RADIUS distance of the center $(0, 0)$ origin square. The INCLUDE_ORIGIN argument specifies whether to include the origin in this set of coordinates.
MooreHood(INCLUDE_ORIGIN)	Util	Returns a set of coordinate pairs that define a Moore neighborhood around the $(0, 0)$ origin square. The INCLUDE_ORIGIN boolean specifies whether we intend to include the origin in this set of coordinates.
Write(STRING)	FileIO	Writes the STRING to the output file.
Close()	FileIO	Closes the output file.
Double()	Rand	Generates a random double value in the range $[0 - 1)$

Table 3. HAL functions used in the example. Each function is a method of a particular object, meaning that when the function is called it may use properties that pertain to the object that it is called from.

4.2 Main Function

We first examine the 'main' function for a bird's-eye view of how the program is
structured. Source code elements highlighted in red are built-in HAL functions and
objects, and can be referenced in Table 3.

```
1    public static void main(String[] args) {
2        //setting up starting constants and data collection
3        int x = 100, y = 100, visScale = 5, tumorRad = 10, msPause = 5;
4        double resistantProb = 0.5;
5        GridWindow win = new GridWindow("Competitive Release", x * 3, y,
             visScale);
6        FileIO popsOut = new FileIO("populations.csv", "w");
7        //setting up models
8        ExampleModel[] models = new ExampleModel[3];
9        for (int i = 0; i < models.length; i++) {
10           models[i] = new ExampleModel(x, y, new Rand());
11           models[i].InitTumor(tumorRad, resistantProb);
12       }
13       models[0].DRUG_DURATION = 0;//no drug
14       models[1].DRUG_DURATION = 200;//constant drug
15       //Main run loop
16       for (int tick = 0; tick < 10000; tick++) {
17           win.TickPause(msPause);
18           for (int i = 0; i < models.length; i++) {
19               models[i].ModelStep(tick);
20               models[i].DrawModel(win, i);
21           }
22           //data recording
23           popsOut.Write(models[0].Pop() + "," + models[1].Pop() + "," +
                 models[2].Pop() + "\n");
24           if ((tick) % 100 == 0) {
25               win.ToPNG("ModelsTick" + tick + ".png");
26           }
27       }
28       //closing data collection
29       popsOut.Close();
30       win.Close();
31   }
```

Lines 3-4: Defines all of the constants that will be needed to setup the model and
display.

5: Creates a GridWindow of RGB pixels for visualization and for generating timestep
PNG images. x*3, y define the dimensions of the pixel grid. the x variable is
multiplied by 3 so that 3 models can be visualized side by side in the same
window. The last argument is a scaling factor that specifies that each pixel on the
grid will be viewed as a 5x5 square of pixels on the screen.

6: Creates a file output object that will write to a file called populations.csv.

8: Creates an array with 3 entries that will be populated with models.

9-12: Fills the model list with models that are initialized identically. Each model will
hold and update its own cells and diffusible drug. See the Grid Definition and
Constructor section and the InitTumor Function section for more details.

13-14: Setting the DRUG_DURATION constant creates the only difference in the 3
models being compared. In models[0] no drug will be administered. In models[1]
drug administration will be constant (DRUG_DURATION is set equal to
DRUG_CYCLE). In models[2] drug will be administered periodically (the default

value of DRUG_DURATION is 40). See the ExampleModel Constructor and $_{382}$
Properties section for the default model initialization. $_{383}$

16: Executes the main loop for 10000 timesteps. $_{384}$

17: Requires every iteration of the loop to take a minimum number of milliseconds. $_{385}$
This slows down the execution and display of the model and makes it easier for $_{386}$
the viewer to follow. $_{387}$

18: Loops over all models to update them. $_{388}$

19: Advances the state of the agents and diffusibles in each model by one timestep. See $_{389}$
the Model Step Function for more details. $_{390}$

20: Draws the current state of each model to the window. See the Draw Model $_{391}$
Function for more details. $_{392}$

23: Writes the population sizes of each model every timestep to allow the models to be $_{393}$
compared. $_{394}$

24: Every 100 timesteps, writes the state of the model as captured by the GridWindow $_{395}$
to a PNG file. $_{396}$

29-30: After the main for loop has finished, the FileIO object and the visualization $_{397}$
window are closed, and the program ends. $_{398}$

4.3 ExampleModel Constructor and Properties $_{399}$

This section explains how the grid is defined and instantiated. $_{400}$

$_{401}$

```
1   public class ExampleModel extends AgentGrid2D<ExampleCell> {
2       //model constants
3       public final static int RESISTANT = RGB(0, 1, 0), SENSITIVE = RGB(0,
            0, 1);
4       public double DIV_PROB_SEN = 0.025, DIV_PROB_RES = 0.01,
5               DEATH_PROB = 0.001, DRUG_DIFF_RATE = 2, DRUG_UPTAKE = −0.09,
6               DRUG_TOXICITY = 0.2, DRUG_BOUNDARY_VAL = 1.0;
7       public int DRUG_START = 400, DRUG_CYCLE = 200, DRUG_DURATION = 40;
8       //internal model objects
9       public PDEGrid2D drug;
10      public Rand rng;
11      public int[] divHood = MooreHood(false);
12
13      public ExampleModel(int x, int y, Rand generator) {
14          super(x, y, ExampleCell.class);
15          rng = generator;
16          drug = new PDEGrid2D(x, y);
17      }
```

$_{402}$
$_{403}$
$_{404}$
$_{405}$
$_{406}$
$_{407}$
$_{408}$
$_{409}$
$_{410}$
$_{411}$
$_{412}$
$_{413}$
$_{414}$
$_{415}$
$_{416}$
$_{417}$
$_{418}$
$_{419}$
$_{420}$

1: The ExampleModel class, which is user defined and specific to this example, is built $_{421}$
by extending the generic AgentGrid2D class. The extended grid class requires an $_{422}$
agent type parameter, which specifies the type of agent that will live on the grid. $_{423}$
To meet this requirement, the <ExampleCell> type parameter is added to the $_{424}$
declaration. $_{425}$

3: Defines RESISTANT and SENSITIVE constants, which are created by the Util RGB $_{426}$
function. These constants serve as both colors for drawing and as labels for the $_{427}$
different cell types. $_{428}$

4-7: Defines all constants that will be needed during the model run. These values can ₄₂₉ be reassigned after model creation to test different parameter settings. In the ₄₃₀ main function, the DRUG_DURATION variable is modified for the ₄₃₁ Constant-Drug, and Pulsed Therapy experiment cases. ₄₃₂

9: Declares that the model will contain a PDEGrid2D, which will hold the drug ₄₃₃ concentrations. The PDEGrid2D can only be initialized when the x and y ₄₃₄ dimensions of the model are known, which is why we do not assign their values ₄₃₅ until the constructor function is called. ₄₃₆

10: Declares that the Grid will contain a Random number generator (the Rand object), ₄₃₇ but takes it in as a constructor argument to allow the modeler to seed the ₄₃₈ generator if desired for consistent output. ₄₃₉

11: Creates a neighborhood using the MooreHood function. The MooreHood function ₄₄₀ generates a set of coordinates that define the Moore Neighborhood (the 8 closest ₄₄₁ coordinates to a central origin), centered around $(0,0)$. The false argument ₄₄₂ declares that we do not want to include the origin in the neighborhood, just the 8 ₄₄₃ coordinates around that position. The neighborhood is stored in the format ₄₄₄ $[0_1 0_2, ..., 0_n, x_1, y_1, x_2, y_2, ..., x_n, y_n]$. The leading zeros are written to when ₄₄₅ MapHood is called, and will store the position indices that the neighborhood ₄₄₆ maps to. See the CellStep function for more information, and the InitTumor ₄₄₇ Function Line 3 for another example of the use of neighborhoods ₄₄₈

13: Defines the model constructor, which takes as arguments the x and y dimensions of ₄₄₉ the model and a random number generator (a Rand object). ₄₅₀

14: Calls the AgentGrid2D constructor with super, passing it the x and y dimensions of ₄₅₁ the model, and the ExampleCell Class. This Class is used by the Grid to generate ₄₅₂ a new cell when the NewAgentSQ function is called. ₄₅₃

15-16: The Rand argument is assigned and the drug PDEGrid2D is defined with ₄₅₄ matching dimensions. ₄₅₅

4.4 InitTumor Function ₄₅₆

The next segment of code is a function from the ExampleModel class that defines how ₄₅₇ the tumor is first seeded after the ExampleModel is created. ₄₅₈

₄₅₉
```
1      public void InitTumor(double radius, double resistantProb) {
2          //get a list of indices that fill a circle at the center of the
                grid
3          int[] tumorNeighborhood = CircleHood(true, radius);
4          int hoodSize = MapHood(tumorNeighborhood, xDim / 2, yDim / 2);
5          for (int i = 0; i < hoodSize; i++) {
6              if (rng.Double() < resistantProb) {
7                  NewAgentSQ(tumorNeighborhood[i]).type = RESISTANT;
8              } else {
9                  NewAgentSQ(tumorNeighborhood[i]).type = SENSITIVE;
10             }
11         }
12     }
```

1: The arguments passed to the InitTumor function are the approximate radius of the ₄₇₄ circular tumor being created and the probability that each created cell will be of ₄₇₅ the resistant phenotype. ₄₇₆

3: Sets the tumorNeighborhood array using the CircleHood function, which stores coordinates in the form $[0_1, 0_2, ..., 0_n, x_1, y_1, x_2, y_2, ...x_n, y_n]$. The x,y coordinate pairs define a neighborhood of all squares whose centers are within the radius distance of the center $(0,0)$ origin square. The leading 0s are used by the MapHood function to store the mapped indices. The boolean argument specifies that the origin will be included in this set of squares, thus making a completely filled circle of squares.

4: Uses the MapHood function to map the neighborhood defined above to be centered around xDim/2,yDim/2 (the dimensions of the AgentGrid). The results of the mapping are written as position indices to the beginning of the tumorNeighborhood array. MapHood returns the number of valid indices found, and this will be the size of the starting population.

5: Loops from 0 to hoodSize, allowing access to each mapped position index in the tumorNeighborhood.

6: Samples a random number in the range $[0 - 1)$ and compares to the resistantProb argument to set whether the cell should have the resistant phenotype or the sensitive phenotype.

7-9: Uses the NewAgentSQ function to place a new cell at each tumorNeighborhood position. In the same line we also specify that the phenotype should be either resistant or sensitive, depending on the result of the rng.Double() call.

4.5   ModelStep Function

This section looks at the model's step function which is executed once per timestep by each Model.

```
1      public void ModelStep(int tick) {
2          ShuffleAgents(rng);
3          for (ExampleCell cell : this) {
4              cell.CellStep();
5          }
6          int periodTick = (tick − DRUG_START) % DRUG_CYCLE;
7          if (periodTick > 0 && periodTick < DRUG_DURATION) {
8              //drug will enter through boundaries
9              drug.DiffusionADI(DRUG_DIFF_RATE, DRUG_BOUNDARY_VAL);
10         } else {
11             //drug will not enter through boundaries
12             drug.DiffusionADI(DRUG_DIFF_RATE);
13         }
14         drug.Update()
15     }
```

2: The ShuffleAgents function randomizes the order of iteration so that the agents are always looped through in random order.

3-4: Iterates over every cell on the grid, and calls the CellStep function on every cell.

6-7: The periodTick variable stores at what point in the drug delivery cycle the tick is, and the If statement checks whether the tick is in the right part of the drug cycle to apply drug, (See the Grid Definition and Constructor section for the values of the constants involved, the DRUG_DURATION variable is set differently for each model in the Main Function)

9: If it is time to add drug to the model, the DiffusionADI function is called. DiffusionADI uses the ADI method which is more stable than 2D Euler and allows us to take larger steps. The additional argument to the DiffusionADI function specifies the boundary condition value DRUG_BOUNDARY_VAL. This causes the drug to diffuse into the PDEGrid2D from the boundary. Here we assume that drug is only delivered from the boundaries of the domain

12: Without the second argument the DiffusionADI function assumes a zero-flux boundary, meaning that drug concentration cannot escape or enter through the sides of the model. Therefore the only way for the drug concentration to decrease is via uptake by the Cells. See the CellStep function section, line 6, for more information.

14: Update is called to apply the reaction and diffusion changes to the PDEGrid.

4.6   CellStep Function and Cell Properties

We next look at how the ExampleCell Agent is defined and at the CellStep function that runs once per Cell per timestep. The G property that is referenced many times in this section is a built-in agent property that gives access to the ExampleGrid object that the cell lives on.

```
1   class ExampleCell extends AgentSQ2Dunstackable<ExampleModel> {
2       public int type;
3
4       public void CellStep() {
5           //uptake of Drug
6           G.drug.Mul(Isq(), G.DRUG_UPTAKE);
7           double deathProb, divProb;
8           //Chance of Death, depends on resistance and drug concentration
9           if (this.type == RESISTANT) {
10              deathProb = G.DEATH_PROB;
11          } else {
12              deathProb = G.DEATH_PROB + G.drug.Get(Isq()) *
                    G.DRUG_TOXICITY;
13          }
14          if (G.rng.Double() < deathProb) {
15              Dispose();
16              return;
17          }
18          //Chance of Division, depends on resistance
19          if (this.type == RESISTANT) {
20              divProb = G.DIV_PROB_RES;
21          } else {
22              divProb = G.DIV_PROB_SEN;
23          }
24          if (G.rng.Double() < divProb) {
25              int options = MapEmptyHood(G.divHood);
26              if (options > 0) {
27                  G.NewAgentSQ(G.divHood[G.rng.Int(options)]).type =
                        this.type;
28              }
29          }
30      }
31  }
```

1: The ExampleCell class is built by extending the generic AgentSQ2Dunstackable class. The extended Agent class requires the ExampleModel class as a type argument, which is the type of Grid that the Agent will live on. To meet this requirement, we add the <ExampleModel> type parameter to the extension.

2: Defines a cell property called "type". Each Cell holds a value for this field. If the value is RESISTANT, the Cell is of the resistant phenotype, if the value is SENSITIVE, the cell is of the sensitive phenotype. The RESISTANT and SENSITIVE values are defined in the ExampleGrid as constants (See the ExampleModel Constructor and Properties, line 3).

6: The G property is used to access the ExampleGrid object that the Cell lives on. G is used often with agent functions as the AgentGrid is expected to contain any information that is not local to the individual agent. Here it is used to get the drug PDEGrid2D. The drug concentration at the index that the Cell is currently occupying (Isq()) is then multiplied by the drug uptake constant, thus modeling local drug uptake by the Cell.

7: Defines deathProb and divProb variables, these will be assigned different values depending on whether the ExampleCell is RESISTANT or SENSITIVE.

9-12: If the cell is resistant, the deathProb variable is set to the DEATH_PROB value alone, if the cell is sensitive, an additional term is added to account for the probability of the cell dying from drug exposure, using the concentration of drug at the cell's position (Isq())

14-16: Samples a random number in the range $[0 - 1)$ and compares to deathProb to determine whether the cell will die. If so, the built-in agent Dispose() function is called, which removes the agent from the grid, and then return is called so that the dead cell will not divide.

19-22: Sets the divProb variable to either DIV_PROB_RES for resistant cells, or DIV_PROB_SEN for sensitive cells.

24: Samples a random number in the range $[0 - 1)$ and compares to divProb to determine whether the cell will divide.

25: If the cell divides, the MapEmptyHood function is used, which checks the positions in the divHood (the Moore neighborhood as defined in the ExampleModel Constructor and Properties section, line 11) around the Cell, and writes the position indices that do not contain any agents into the divHood. MapEmptyHood returns the number of valid empty positions found.

26-27: If there are one or more valid division options, a new daughter cell is created using the NewAgentSQ function and its starting location is chosen by randomly sampling the divHood array to pull out one if its valid locations. The other daughter is assumed to occupy the same location as the mother cell. Finally with the .type=this.type statement, the phenotype of the newly placed daughter cell is inherited from the mother cell.

4.7 DrawModel Function

We next look at the DrawModel Function, which is used to display a summary of the model state on a GridWindow object. In this program, DrawModel is called once for each model per timestep; see the main function section for more information.

```
1    public void DrawModel(GridWindow vis, int iModel) {
2        for (int x = 0; x < xDim; x++) {
3            for (int y = 0; y < yDim; y++) {
4                ExampleCell drawMe = GetAgent(x, y);
5                if (drawMe != null) {
6                    vis.SetPix(x + iModel * xDim, y, drawMe.type);
```

```
 7                    } else {
 8                        vis.SetPix(x + iModel * xDim, y,
                             HeatMapRGB(drug.Get(x, y)));
 9                    }
10                }
11            }
12        }
```

2-3: Loops over every lattice position of the grid being drawn, xDim and yDim refer to the dimensions of the model.

4: Uses the GetAgent function to get the Cell that is at the x,y position.

5-6: If a cell exists at the requested position, the corresponding pixel on the GridWindow is set to the cell's phenotype color. To draw the models side by side, the pixel being drawn is displaced to the right by the model index.

7-8: If there is no cell to draw, then the pixel color is set based on the drug concentration at the same index, using the built-in heat colormap.

4.8   Imports

The final code snippet looks at the imports that are needed. Any modern Java IDE should generate import statements automatically.

```
1  package Examples._6CompetitiveRelease;
2  import Framework.GridsAndAgents.AgentGrid2D;
3  import Framework.GridsAndAgents.PDEGrid2D;
4  import Framework.Gui.GridWindow;
5  import Framework.GridsAndAgents.AgentSQ2Dunstackable;
6  import Framework.Tools.FileIO;
7  import Framework.Rand;
8  import static Examples._6CompetitiveRelease.ExampleModel.*;
9  import static Framework.Util.*;
```

1: The package statement specifies where the file exists in the larger project structure

2-7: Imports all of the classes that we will need for the program.

8: Imports the static fields of the model so that we can use the type names defined there in the Agent class.

9: Imports the static functions of the Util file, which adds all of the Util functions to the current namespace, so we can natively call them. Statically importing Util is recommended for every project.

4.9   Model Results

Table 4 displays the model visualization at timestep 0, timestep 400, timestep 1100, timestep 5500, and timestep 10,000 recorded from the GridWindow ToPNG function. The caption explores the notable trends visible in each image. Fig 8 displays the population sizes as recorded by the FileIO Write function at the end of every timestep.

Figure 8. FileIO population output. This plot summarizes the changes in tumor burden over time for each model. This plot was constructed in python using data accumulated in the program output CSV file. Displayed using Seaborn with Python.

This example illustrates the power of HAL's approach to model building. Writing relatively little complex code, we setup a three model experiment with nontrivial dynamics along with methods to collect data and visualize the models. We now briefly review the model results.

As can be seen in Table 4, at timestep 0 and timestep 400 (right before drug application starts), all 3 models are identical. At timestep 1100 the differences in treatment application show different effects: when no drug is applied, the rapidly dividing sensitive cells quickly fill the domain, while when drug is applied constantly, the resistant cells overtake the sensitive population. Pulsed drug kills some sensitive cells, but leaves enough alive to prevent growth of the resistant cells. At timestep 5500, the resistant cells have begun to emerge from the center of the pulsed drug model. At timestep 10000, all domains are filled. Interestingly, in the models with drug application, the sensitive cells are able to survive in the center of the domain because drug is consumed by cells on the outside. This creates a drug-free zone in which the sensitive cells out-compete the resistant cells even when drug is applied constantly.

As can be seen in Fig 8, the pulsed therapy is the most effective at preventing tumor growth, however the resistant cells ultimately succeed in breaking out of the tumor center and out-competing the sensitive cells on the fringes of the tumor. It may be possible to contain a population of sensitive and resistant cells for longer by using a different pulsing schedule or by modifying the treatment schedule in response to the tumor growth (adaptive therapy). As the presented model is primarily an example, we do not explore how to improve treatment further. For a more detailed exploration of the

potential of adaptive therapy for prolonging competitive release, see [14].

Timestep	No Drug / Constant Drug / Pulsed Drug
0

 |
400	
1100	
5500	
10000	

Table 4. Selected model visualization PNGs. Blue cells are drug sensitive, Green cells are drug resistant, background heatmap colors show drug concentration.

5 Availability And Future Directions ₆₉₃

5.1 How to Download and Contribute ₆₉₄

HAL is publicly available on GitHub, at https://github.com/torococo/HAL. A manual is ₆₉₅
included that walks the user through installation and serves as a coding reference. For ₆₉₆
those interested in using HAL, downloading and setting up the project is a good first ₆₉₇
start. From there running and examining the included examples is recommended, as ₆₉₈
they do a good job of summarizing HAL's capabilities. Modelers can contribute tools ₆₉₉
that they develop by making pull requests to the repository. ₇₀₀

5.2 Future Directions ₇₀₁

5.2.1 Additional agent-based Modeling Paradigms ₇₀₂

Currently the only paradigm implemented on top of the base agent types are the ₇₀₃
SphericalAgent2D/3D extension classes, which facilitate modeling cells as ₇₀₄
circles/spheres with Newtonian physics. In the future we hope to incorporate additional ₇₀₅
modeling paradigms that are commonly used in agent-based modeling of cells. A ₇₀₆
potential addition is a Delaunay Agent type, which would use Delaunay tessellation [32] ₇₀₇
to find the cell's nearest neighbors and determine cell volume. We are also considering ₇₀₈
including modeling paradigms that construct cells out of smaller subunits, such as ₇₀₉
Deformable Ellipsoid Cell Modeling [33], as this would allow us to model the mechanics ₇₁₀
of tissue formation and cell migration in more detail. ₇₁₁

5.2.2 Cross Model Validation ₇₁₂

Having many different paradigms to choose from adds several complications to ₇₁₃
modeling: It can take significant effort to build a model from scratch under one ₇₁₄
paradigm, and then significant additional effort to migrate the model to a different ₇₁₅
paradigm. By adding more modeling approaches with a consistent interface, HAL will ₇₁₆
lower the model migration barrier and allow modelers to test the merits of many ₇₁₇
paradigms in their investigation, and to validate their results by seeing whether they ₇₁₈
hold true across paradigms. Note that our goal is not to recreate all of the functionality ₇₁₉
of the pre-existing frameworks that support these paradigms, it is to provide their core ₇₂₀
algorithms so that users can easily choose from and compare them. ₇₂₁

5.2.3 Bridging Spatial Scales ₇₂₂

We also hope to explore the possibility of adjusting spatial scales for both our PDEs ₇₂₃
and Agents. For PDEs, this is a readily understood problem, and we intend to add ₇₂₄
scalable PDEGrids to HAL soon. However, for agent-based modeling the process of ₇₂₅
changing scales while preserving dynamics is not so well defined, though we imagine ₇₂₆
that it may be possible under certain assumptions. This would be useful for helping us ₇₂₇
bridge the divide between cell level and tissue/organ/tumor level dynamics, as the ₇₂₈
number of cells involved at these scales are orders of magnitude greater than what ₇₂₉
desktop machines can tractably model. ₇₃₀

5.2.4 Assumption Modules ₇₃₁

A common modeling task is exploring how combinations of different assumptions ₇₃₂
influence model behavior. The included ModuleSetManager object helps design models ₇₃₃
specifically with this in mind. The design entails providing code "hooks" so that code ₇₃₄
can be added to influence specific agent decisions and model events, (eg. whether an ₇₃₅

agent will reproduce). Modelers can then write assumption modules that will influence ₇₃₆
these events (eg. by altering the probability of reproduction based on an environmental ₇₃₇
factor that would otherwise be ignored). ₇₃₈

This approach allows modelers to combine and remove assumption modules without ₇₃₉
having to worry about breaking the model. This facilitates easy exploration of the space ₇₄₀
of assumptions until ones suitable for understanding biological phenomena are found. ₇₄₁
We are very excited about the potential of this approach for collaborative projects and ₇₄₂
for building increasingly complex models by encapsulating the complexity into ₇₄₃
manageable parts, and hope to improve on the tools for this paradigm as we explore its ₇₄₄
potential. ₇₄₅

5.2.5 Advanced Scheduling ₇₄₆

Taking inspiration from Repast, SWARM, and MASON, another expected extension is ₇₄₇
the inclusion of optional schedulers to facilitate more complex methods of iterating ₇₄₈
through agents than simply looping over each grid. This is not intended to replace the ₇₄₉
simple grid iteration approach, but instead should augment it with optional complex ₇₅₀
methods. An AgentList object is currently included to begin to address this. It allows ₇₅₁
modelers to make selective lists of agents for more flexible iteration. ₇₅₂

5.2.6 Building a Community ₇₅₃

HAL has already seen adoption within the labs at the Integrated Mathematical ₇₅₄
Oncology department of Moffitt Cancer Center and beyond. We certainly hope that ₇₅₅
more outside users will be interested in its potential. As the user-base for HAL grows, ₇₅₆
we plan to extend the base of resources around the platform. The current set of ₇₅₇
resources that exist for new users to get started are the manual 6, a website with an ₇₅₈
online version of the manual [1] and a playlist of YouTube videos [34]. We intend to ₇₅₉
increase HAL's online presence by including a website with a code repository to make ₇₆₀
sharing models and tools easier. ₇₆₁

6 Conclusion ₇₆₂

Cancer is a complex and heterogeneous disease whose mathematical study is still being ₇₆₃
developed. To make better progress in this endeavor, it is helpful to have a set of highly ₇₆₄
generic tools that encapsulate the key components of spatial modeling so that ₇₆₅
researchers can produce efficient models quickly without being constrained in their ₇₆₆
approach, nor in the complexity of the systems that they can produce. HAL is our ₇₆₇
attempt to achieve this. ₇₆₈

HAL was made easily extensible so that researchers can build models and more ₇₆₉
specific tools on top of HAL's generic base. The hope is that by this process HAL will ₇₇₀
grow into a powerful toolset that will help standardize and coordinate hybrid modeling ₇₇₁
in mathematical oncology. ₇₇₂

We recommend HAL to anyone building spatial models for oncology, as the tools ₇₇₃
presented are primarily geared toward this end. However, given the amount of overlap ₇₇₄
and cross talk between the approaches used in different modeling applications, we hope ₇₇₅
that modelers outside of mathematical oncology will also take interest and contribute, ₇₇₆
to our mutual benefit. ₇₇₇

Supporting information

S1 Fig.   HAL (Hybrid Automata Library) Manual. Includes setup
instructions, implementation details, and a function glossary.

References

1. Jeffrey West RB. Hybrid Automata Library; 2018. Available from:
   https://halloworld.org.

2. Rejniak KA, Anderson AR. Hybrid models of tumor growth. Wiley
   Interdisciplinary Reviews: Systems Biology and Medicine. 2011;3(1):115–125.

3. Anderson AR, Chaplain M. Continuous and discrete mathematical models of
   tumor-induced angiogenesis. Bulletin of mathematical biology.
   1998;60(5):857–899.

4. Gerlee P, Anderson AR. An evolutionary hybrid cellular automaton model of
   solid tumour growth. Journal of theoretical biology. 2007;246(4):583–603.

5. Nichol D, Robertson-Tessi M, Jeavons P, Anderson AR. Stochasticity in the
   genotype-phenotype map: implications for the robustness and persistence of
   bet-hedging. Genetics. 2016; p. genetics–116.

6. Basanta D, Anderson A. Homeostasis Back and Forth: An Ecoevolutionary
   Perspective of Cancer. Cold Spring Harbor perspectives in medicine. 2017;7(9).

7. Basanta D, Strand DW, Lukner RB, Franco OE, Cliffel DE, Ayala GE, et al. The
   Role of Transforming Growth Factor-β–Mediated Tumor-Stroma Interactions in
   Prostate Cancer Progression: An Integrative Approach. Cancer research.
   2009;69(17):7111–7120.

8. Kim E, Rebecca V, Fedorenko IV, Messina JL, Mathew R, Maria-Engler SS, et al.
   Senescent fibroblasts in melanoma initiation and progression: an integrated
   theoretical, experimental, and clinical approach. Cancer research. 2013;.

9. Anderson AR, Weaver AM, Cummings PT, Quaranta V. Tumor morphology and
   phenotypic evolution driven by selective pressure from the microenvironment.
   Cell. 2006;127(5):905–915.

10. Araujo A, Cook LM, Lynch CC, Basanta D. An integrated computational model
    of the bone microenvironment in bone-metastatic prostate cancer. Cancer
    research. 2014;74(9):2391–2401.

11. Scianna M, Bell C, Preziosi L. A review of mathematical models for the
    formation of vascular networks. Journal of theoretical biology. 2013;333:174–209.

12. Robertson-Tessi M, Gillies RJ, Gatenby RA, Anderson AR. Impact of metabolic
    heterogeneity on tumor growth, invasion, and treatment outcomes. Cancer
    research. 2015;75(8):1567–1579.

13. Zhang J, Cunningham JJ, Brown JS, Gatenby RA. Integrating evolutionary
    dynamics into treatment of metastatic castrate-resistant prostate cancer. Nature
    communications. 2017;8(1):1816.

14. Gallaher JA, Enriquez-Navas PM, Luddy KA, Gatenby RA, Anderson AR.
    Adaptive vs continuous cancer therapy: Exploiting space and trade-offs in drug
    scheduling. bioRxiv. 2017;.

15. Karolak A, Rejniak KA. Micropharmacology: an in silico approach for assessing drug efficacy within a tumor tissue. Bulletin of mathematical biology. 2018; p. 1–19.

16. Alfonso J, Talkenberger K, Seifert M, Klink B, Hawkins-Daarud A, Swanson K, et al. The biology and mathematical modelling of glioma invasion: a review. Journal of the Royal Society Interface. 2017;14(136):20170490.

17. Ghaffarizadeh A, Heiland R, Friedman SH, Mumenthaler SM, Macklin P. PhysiCell: an open source physics-based cell simulator for 3-D multicellular systems. PLoS Comput Biol. 2018;14(2):e1005991. doi:10.1371/journal.pcbi.1005991.

18. Swat MH, Thomas GL, Belmonte JM, Shirinifard A, Hmeljak D, Glazier JA. Multi-scale modeling of tissues using CompuCell3D. Methods in cell biology. 2012;110:325.

19. Mirams GR, Arthurs CJ, Bernabeu MO, Bordas R, Cooper J, Corrias A, et al. Chaste: an open source C++ library for computational physiology and biology. PLoS computational biology. 2013;9(3):e1002970.

20. Collier N. Repast: An extensible framework for agent simulation. The University of Chicagos Social Science Research. 2003;36:2003.

21. Luke S, Cioffi-Revilla C, Panait L, Sullivan K. Mason: A new multi-agent simulation toolkit. In: Proceedings of the 2004 swarmfest workshop. vol. 8. Department of Computer Science and Center for Social Complexity, George Mason University Fairfax, VA; 2004. p. 316–327. Available from: http://cobweb.cs.uga.edu/~maria/pads/papers/mason-SwarmFest04.pdf.

22. Tisue S, Wilensky U. Netlogo: A simple environment for modeling complexity. In: International conference on complex systems. vol. 21. Boston, MA; 2004. p. 16–21. Available from: https://ccl.northwestern.edu/papers/netlogo-iccs2004.pdf.

23. Anderson A, Sleeman B, Young I, Griffiths B. Nematode movement along a chemical gradient in a structurally heterogeneous environment: 2. Theory. Fundamental and applied nematology. 1997;20(2):165–172.

24. Bravo R. HAL Manual; 2018. Available from: https://github.com/torococo/HAL/blob/master/manual.pdf.

25. Peaceman DW, Rachford HH Jr. The numerical solution of parabolic and elliptic differential equations. Journal of the Society for industrial and Applied Mathematics. 1955;3(1):28–41.

26. Courant R, Isaacson E, Rees M. On the solution of nonlinear hyperbolic differential equations by finite differences. Communications on Pure and Applied Mathematics. 1952;5(3):243–255.

27. Meister P. gifAnimation processing library; 2015. Available from: https://github.com/extrapixel/gif-animation.

28. Poleszczuk J, Macklin P, Enderling H. Agent-based modeling of cancer stem cell driven solid tumor growth. In: Stem Cell Heterogeneity. Springer; 2016. p. 335–346.

29. Oliphant TE. A guide to NumPy. vol. 1. Trelgol Publishing USA; 2006.

30. CERN. Colt; 2004. Available from: `http://dst.lbl.gov/ACSSoftware/colt/`.

31. Bravo R, Robertson-Tessi M, West J, Anderson AR. Cancer Crusade; 2018. Available from: `https://cancercrusadegame.com`.

32. Bock M, Tyagi AK, Kreft JU, Alt W. Generalized voronoi tessellation as a model of two-dimensional cell tissue dynamics. Bulletin of mathematical biology. 2010;72(7):1696–1731.

33. Alexander Anderson KR Mark A J Chaplain. Single-Cell-Based Models in Biology and Medicine. illustrated ed. Springer Science & Business Media; 2007.

34. Bravo R. HAL Tutorial 1: Setup; 2018. Available from: `https://www.youtube.com/watch?v=yjTmH3qORFQ&t=43s`.

Acknowelgements

This work was possible through the generous support of NIH funding, Anderson and Robertson-Tessi acknowledge NCI U54CA193489, Anderson and Bravo acknowledge NCI UH2CA203781.