1 **Title:** Hippocampal-entorhinal transformations in abstract frames of reference
2

3 **Authors:** Raphael Kaplan[1,2] & Karl J Friston[1]
4
5 **Affiliations:**
6 1-Wellcome Centre for Human Neuroimaging, University College London, United Kingdom
7 2- Egil and Pauline Braathen and Fred Kavli Centre for Cortical Microcircuits, Kavli Institute for
8 Systems Neuroscience, Norwegian University of Science and Technology, Trondheim, Norway
9
Correspondence: raphael.s.m.kaplan@ntnu.no

Abstract: Knowing how another's preferences relate to our own is a central aspect of everyday

decision-making, yet how the brain performs this transformation is unclear. Here, we ask whether the

putative role of the hippocampal-entorhinal system in transforming relative and absolute spatial

coordinates during navigation extends to transformations in abstract decision spaces. During fMRI

scanning, subjects learned a stranger's preference for an everyday activity – relative to one of three

personally known individuals – and subsequently decided how the stranger's preference relates to the

other two individuals' preferences. We found that entorhinal cortex/subiculum signals exhibited

reference frame-sensitive responses to the absolute distance between the ratings of the stranger and

the familiar choice options. In contrast, striatal signals increased when accurately determining the

ordinal position of choice options in relation to the stranger. Paralleling its role in navigation, these

data implicate the entorhinal/subicular region in assimilating relatively coded knowledge within

abstract metric spaces.

Introduction

Learning other people's attributes is facilitated by expressing personal preferences *ordinally*–whether we prefer one thing to another–and *metrically*–how much more we prefer one thing over another. Ordinal and metric coding are particularly important when acquiring knowledge about new people. This type of learning involves relating a new person's attributes to prior beliefs about other people; either by adopting a relative or absolute frame of reference. For instance, imagine you are preparing dinner for a foreign visitor that says, "I like spicy food". If they are Vietnamese, their preference for spicy food is probably greater than Germanic tastes, despite everyone declaring the same preference.

On one hand, progress has been made in linking the hippocampus to the maintenance of an ordinal sequence or 'hierarchy' of personal attributes (Eichenbaum, 2015; Schiller et al., 2015; Kumaran et al., 2012, 2016) and, similarly, category learning (Zeithamova et al., 2008; Mack et al, 2017, 2018). Yet, the neural representation of metrically coded knowledge remains elusive, even though metric coding affords the transformation of knowledge learned via relative and absolute frames of reference.

Clues about the neural computations underlying the transformation of abstract knowledge among frames of reference may come from research on the role of the hippocampal formation in path integration: the process of calculating one's position by estimating the direction and distance one has travelled from a known point. During path integration, specific sub-regions of the hippocampal formation have been implicated in integrating relative and absolute spatial coordinates during navigation, in order to reach a desired location (McNaughton et al., 2006). In particular, grid cells in entorhinal/subicular areas are selectively active at multiple spatial scales when an animal encounters periodic triangular locations covering the entire environment (Hafting et al., 2005; Boccara et al., 2010), while hippocampal place cells code specific locations in an environment (O'Keefe & Dostrovsky, 1971). Working together with boundary vector cells in entorhinal/subicular areas – that code an environmental boundary at a particular direction and distance (O'Keefe & Burgess, 1996; Hartley et al., 2000; Burgess et al., 2000) – and head direction cells (Taube et al., 1990), spatially-

modulated neurons in the hippocampal formation are thought to serve collectively as a cognitive map

of the environment (O'Keefe & Nadel, 1978; McNaughton et al., 2006; Hartley et al., 2013).

Notably, recent findings have extended the idea of map-like coding in the entorhinal cortex

and subiculum to humans. Human entorhinal/subicular regions respond to both the distance of goal

locations (Howard et al., 2014; Chadwick et al., 2015) and discrete abstract relations (Garvert et al.,

2017), suggesting that entorhinal/subicular areas might represent abstract knowledge metrically along

multiple dimensions. Taken together, these results imply that neural computations in the hippocampal

formation related to spatial exploration, may also underlie the integration of information learned in

different reference frames during more abstract types of memory-guided decision-making (Kaplan et

al., 2017a).

We investigated whether specific brain regions, including sub-regions of the hippocampal

formation – like the entorhinal/subicular area – facilitate switching between relative and absolute

reference frames during memory-guided decisions. To test this hypothesis, we developed a novel

experimental task, where healthy volunteers were first asked to rate 1-9, on a 0-10 scale, how likely

(likelihood) they (*self*), a close friend (*friend*), and a typical person (*canonical*) were to partake in a

variety of everyday scenarios (e.g., eat spicy food, read a book, cycle to work; Fig. 1A). To allow for

strangers with more extreme ratings than the familiar individuals in the fMRI paradigm, subjects were

restricted to rating between 1-9. Subsequently, subjects performed a forced-choice fMRI task (Fig.

1B), where they judged the proximity of a *stranger's* rating relative to the ratings of the self, friend,

and canonical individuals, for a given everyday scenario (Fig. 1B). Specifically, on each (self-paced)

trial, subjects were shown the preference of a *stranger* on a 0-10 scale, relative to a known person

(*anchor*) and subjects had to select which of the two remaining (*non-anchor*) familiar individuals

were closest to the *stranger*. After making a decision, a jittered (mean=2.43s) intertrial interval (ITI)

period started, where a white fixation point overlaid on a black background appeared on the screen.

In our task, it was crucial that the *anchor* was always placed in the middle of the scale, to ensure that

subjects used their prior knowledge in order to infer the *stranger's* absolute preference and form an

appropriate mental number line of personal preferences (i.e., remembering the absolute positions of

the different preferences on the number line, instead of the visible relative position of the anchor in

the middle of the screen with a stranger presented somewhere between 0-10; see Fig. 1C-D). In other

words, subjects had to infer the *stranger's* position in relation to the *anchor's* 'true' rating for that

scenario (i.e., the rating they gave for that anchor and scenario during the training period) and

mentally rescale this information relative to the closest boundary (0 or 10). Note that this is a non-

trivial task because the preferences of *strangers* were not conserved over attributes.

In summary, training subjects to think of absolutely coded personal preferences in the form of

a mental number line allowed us to probe different everyday scenarios at various levels of

discriminability and use a well-characterized signal detection model of decision-making (Tanner &

Swets, 1954). Discriminability was determined by the absolute distance between individuals on a

scale and how confident subjects were about a particular preference. Furthermore, this modeling

approach allowed us to account for differing mnemonic demands related to the subject knowing their

ratings better for themselves (*self*) than their *friend* and *canonical* ratings (Fig. 1C). Casting our

paradigm in terms of coordinate transforms, we investigated how personal preferences are represented

in the brain in two complementary ways. First, how the stranger's rating is inferred by mentally

rescaling the *anchor* individual's rating from its perceived relative position on the screen, to its

absolute position (the participant's actual rating) on the preference scale (i.e., anchor rescaling).

Second, uncertainty in preference discrimination based on the absolute distance between the

stranger's rating and the ratings of the personally familiar individuals that the stranger is compared

with (i.e., choice discriminability). We subsequently refer to these two elements of representing

personal preferences in our task as anchor rescaling(Fig. 1D) and choice discriminability(Fig. 1C),

respectively.

Results

Behavior

Subjects' ratings of personally known individuals followed a consistent structure. As

expected, subjects tended to rate the *canonical* individual towards the middle of scale, 5, with the *self*

and *friend* ratings being more evenly dispersed between 1-9 (Fig. 2A-source Data 1). Subjects' ratings

for the *canonical* exemplar and their *friend* were generally consistent before and after scanning; after

scanning, subjects were on average within ±1 of their original ratings for 67.7% (SD=8.15%) of trials

and only made large deviations from their original ratings >=±3 on 8.54% (SD=6.2%) of occasions

(Fig. 2B-source data 2). Notably, there was a significant effect of *anchor* condition (*self*, *canonical*, or

friend) for the average absolute distance between the choice options and the stranger

$(F(2,22)=10.1;p=.001)$, where *self* (mean=2.34; SD=.412) and *friend* (mean=2.26; SD=.371) *anchor*

conditions had significantly smaller absolute distances than the *canonical* (mean=2.62; SD=.473)

anchor condition (Fig. 2C-source data 3). Additionally, there were overlapping ratings (the same

rating for two individuals on the same scenario) for a small subset of preferences, and there was a

significant effect of *anchor* condition in the number of overlapping ratings $(F(2,22)=6.74; p=.005)$,

such that there was higher overlap between *self* and *friend* ratings (the *canonical anchor* condition)

than between other pairings (Fig. 2-Figure Supplement 1-source data 7). Crucially, trials with

overlapping ratings were always considered correctly answered and not included in subsequent

behavioral and fMRI analyses. When relating subjective confidence to rating consistency, confidence

ratings significantly correlated with rating consistency $(t(23)=-4.11;p<.001)$, where higher confidence

ratings had more rating consistency. These results suggest a metacognitive validity of the subjective

ratings, relating to memory for specific personal preferences.

During the fMRI experiment, subjects made 72.6% of decisions correctly (SD=1.13%; n=24),

after eliminating trials for which answer was correct (i.e., same or equidistant ratings). The mean

reaction time (RT) was 4.07 s (SD=.803 s). There was a significant effect of condition $(p<.05)$ for RT

$(F(2,22)=4.57;P=.022;$ Fig. 2D-source data 4), but not performance $(F(2,22)=2.73 ;P=.087)$. The RT

effect was driven by significantly higher RT for *self* versus *friend anchor* conditions

$(t(23)=2.71;P=.012;$ Fig. 2D). Notably, there was a negative correlation between trial by trial RT and

accuracy $(t(23)=-5.51;p<.001)$, i.e., quicker RT for accurate choices. In parallel, RT and rating

consistency were also correlated $(t(23)=2.55; p=.015)$, where slower RT related to trials containing

inconsistently rated preferences (i.e., poorly remembered preferences),

We then related RT and accuracy to the absolute distance between the stranger's rating and

the ratings of the non-anchor individuals presented as choice options for each trial (i.e., choice

discriminability without the use of a model and confidence ratings). As expected, we found that this

distance negatively correlated with RT (t(23)=-5.42;p<.001) and positively correlated with accuracy

(t(23)=15.8;p<.001); i.e., larger distances related to quicker and more accurate decisions. Highlighting

how the metric nature of these absolute distances influenced behavior, we observed a steady increase

in the quickness (Fig. 2-Figure Supplement 2-source data 8) and accuracy (Fig. 2E-source data 5) of

the participant's responses when the stranger's rating was closer to one choice option versus another.

Further relating these absolute distances to subjects' behavior, we then used a signal detection model

fit to subjects' performance that was based on absolute rating distances and subjective confidence

ratings. Given the relationship between subjective confidence and rating consistency, subjective

confidence ratings also helped account for the different mnemonic demands induced by the different

conditions.

155
A computational model of latent preferences

We quantified the difficulty of discriminating a particular preference by fitting a formal signal

detection model (Tanner & Swets, 1954) based on the absolute distance between the two choice (*non-*

anchor) individuals on a scale and subjective confidence. Specifically, we characterized

discriminability using the entropy of decision probabilities based on a softmax function of likelihood

and confidence ratings (Fig. 1C). Using this modeling approach allowed us to characterize the

absolute distance between the ratings, along with the subjects' confidence ratings, in a single

measurement of trial-specific choice discriminability. Importantly, high entropy corresponds to lower

choice discriminability that is induced by similar ratings. To estimate the requisite softmax

(sensitivity or precision) parameter, we modeled performance in terms of entropy (H) over trials (and

subjects) using a simple linear regression model. The ensuing behavioral model provided an estimate

of the precision parameter (β) and associated measure of trial-specific choice discriminability for

each subject.

In detail, we want to score the difficulty of each trial. This difficulty is the entropy (H) of the

choice probability (p), based upon a softmax function of the log odds ratio of a target (*stranger*)

preference (*T*) being sampled from the distributions of (*non-anchor*) reference subjects A and B. Let

the preference of individual i have a mean μ_i and standard deviation σ_i, then the log probability of

sampling T, from the preference distribution of the i-th reference subject is (ignoring constants):

$$L_i = -\frac{1}{2}\frac{(T-\mu_i)^2}{\sigma_i^2}$$

Equation 1

If we assume a precision of β, then the probability of choosing subject A over B is a softmax

function of the log odds ratio:

$$P_A = \frac{\exp(\beta \cdot L_A)}{\sum_{i \subset \{A,B\}} \exp(\beta \cdot L_i)}$$

Equation 2

and the difficulty is the entropy:

$$H = \sum_{i \subset \{A,B\}} -P_i \ln P_i$$

Equation 3

This will give difficulties between 0 and ln(2) i.e., 0.6931. Given the mean and standard deviation

reported by subjects, we can evaluate the probability of choosing each (*non-anchor*) individual on

each trial, given the *stranger's* target preference. We used the Bayesian information criterion (BIC)

(Schwarz, 1978) to determine if a signal detection model including subjective confidence ratings – as

the standard deviation – outperforms a distance-only model. Notably, we found that the model

including confidence ratings (BIC=-39,056) outperformed a simpler distance-only model (BIC=-

38,387), where the lower BIC signifies the greater model evidence. In short, this provides strong

evidence for a model based on confidence ratings.

This model of choice behavior provided trial-specific measures of choice uncertainty (*H*) that

enabled us to identify its fMRI correlates. Following previous work (Daw et al., 2006; Glascher et al.,

2010; Daw, 2011), we used the mean precision parameter (β), evaluated over subjects to compute

trial-specific choice entropies as a predictor for our fMRI responses. We found that choice entropy

negatively correlated with performance over trials (t=-10.9; p <.001). As might be expected, we

observed a significant effect of condition for mean choice entropy (F(2,22)=17.6;P<.001; see Fig.2F-

source data 6), where choice entropy was significantly higher for *self* than *canonical*

(t(23)=6.06;*P*<.001) or *friend* (t(23)=4.23;p<.001) anchor trials (Fig. 2D). This was likely due to

lower confidence (i.e., memory demands) for *friend* and *canonical* ratings, relative to ratings of *self*

preferences, as well as the smaller mean absolute distances in *self anchor* trials in relation to

canonical anchor trials.

fMRI Analyses

Choice Discrimination

To test how strangers' preferences are compared to personally known people, we

characterized the brain's response to uncertainty in preference discrimination. Specifically, we were

interested in what brain regions related to choice discrimination in different reference frames.

In a whole-brain analysis – comparing differences in entropy effects between the three

conditions (*self, friend, canonical*) – the only significant effect of condition, and the strongest effect

of any area in the brain for this contrast, was in a right entorhinal/subicular area (x=24,y=-28,z=-22;

F-stat:9.87; Z-score=3.46; SVC peak-voxel p=.034; Fig. 3A-B), extending into anterior

parahippocampal cortex. In other words, the right entorhinal/subicular effect of discriminability

depended upon the *anchor* condition.

Subsequent t-tests on the entorhinal/subicular region exhibiting choice

discriminability/entropy effects indicated that there was a significant positive correlation with entropy

(i.e., less discriminable/ambiguous choices) for *canonical* (t(23)=2.75;p=.011) and *friend*

(t(23)=2.36;p=.027) *anchor* trials, while there was a significant negative correlation with entropy (i.e.,

more discriminable/straightforward choices) for *self anchor* trials (t(23)=-2.39;p=.025; Fig. 3B).

Contrasting *canonical* and *friend* versus *self anchor* trials, we observed that the right

entorhinal/subicular effect (right: Z-score=4.02; peak voxel p=.004 Fig. 3C) was the strongest effect

of any area in the brain for this contrast. Note that *canonical* and *friend* anchor trials involved choices

with *self* preferences. Subjects either decided whether a *stranger's* rating for a scenario was closer to

the *self* versus *canonical* individual (*friend anchor*), or the *self* versus the *friend* (*canonical anchor*).

Conversely, *self anchor* trials involved deciding whether a *stranger's* rating was closer to the *friend*

versus the *canonical* individual. In other words, the entorhinal/subicular region responded to more fine-grained/ambiguous choices involving self-comparisons, but readily discriminable choices otherwise.

We then investigated which brain regions responded to choice entropy (i.e., how discriminable the choices were). However, we did not find any significant regions responding to increasing (i.e., a positive correlation between the fMRI signal and choice entropy/less discriminable choices) or decreasing choice entropy (i.e., a negative correlation between the fMRI signal and choice entropy/more discriminable choices) anywhere in the brain.

Anchor Rescaling

In our task, reference frame transformations rely on flexibly relating different known individuals' ratings to each other. We wanted to capture the initial demands of mentally rescaling the anchor and, consequently, the corresponding stranger from its observed (relative) position on the screen to its actual rating (absolute position) on the scale. To test this, we investigated which regions responded to how far the *anchor's* preference deviated from the middle of the scale (Anchor Rescaling; |anchor rating-5|). In a whole-brain analysis, the only significant main effect of increased anchor rescaling towards the limits of the scale was in the superior parietal lobule (SPL) bilaterally (left: x=-57,y=-52,z=44; Z-score=4.09; FWE cluster p=.024; right: x=33,y=-64,z=54; Z-score=3.99; FWE cluster p=.005; Fig. 4-Figure Supplement 1).

However, we did not observe any significant effects for decreased anchor rescaling (maintaining the rating in the middle of the scale). Likewise, we did not observe any regions showing an interaction with anchor condition.

Accuracy

Further characterizing the functional contribution of different brain regions, we asked if regional responses during memory-guided decisions depended on whether subjects made a correct, or incorrect choice for each trial. In a whole-brain analysis, we observed significant activation for correct trials in the right ventral striatum (x=24,y=8,z=-6; Z-score=4.69; FWE cluster p<.001; Fig. 4A-B) and

left posterior parietal cortex (PPC) in the depth of intraparietal sulcus (x=-24,y=-64,z=42; Z-

score=4.30; FWE cluster p=.005; Fig. 4-Figure Supplement 2). We did not observe any significant

activation that preceded incorrect choices, nor significant interactions between anchor condition and

accuracy.

Finally, to test whether the right ventral striatum accuracy effect was driven by choices where

highest/lowest judgments between the two choice individuals needed to be made, we split decision-

making trials in terms of whether a choice required determining which choice option was

highest/lowest, instead of closest. Ignoring the three anchor conditions, we split the data into two

conditions; one where the target was between the two choice individuals, and the second where the

target was between either higher or lower than both choice individuals. We asked whether subjects

who performed better for the latter scenario, also recruited the ventral striatum when making

highest/lowest versus proximity judgments. We found a between-subject correlation between our right

ventral striatal effect for highest/lowest judgments and subject performance for highest/lowest versus

proximity judgments (r=.561;p=.004) (Fig. 4C).

Remaining fMRI analyses

Asking whether the time spent deliberating and trying to remember a particular choice

option's preferences influenced any neural responses during our task, we investigated whether any

fMRI signals during the social decision-making task correlated with RT. We observed signals in the

posterior parietal cortex/precuneus (left: x=-18,y=-58,z=44; Z-score=4.49; FWE cluster p<.001; right:

x=30,y=-73,z=42; Z-score=4.07; FWE cluster p=.001; Fig. 4-Figure supplement 3), left motor cortex

(x=-33,y=5,z=48; Z-score=4.35; FWE cluster p=.033), and lateral occipital cortex (left: x=-24,y=-

97,z=-6; Z-score=4.26; FWE cluster p<.001; right: x=27,y=-91,z=4; Z-score=4.35; FWE cluster

p=.033) that positively correlated with RT. However, we observed no significant negative correlation

with RT anywhere in the brain, nor significant interactions between *anchor condition* and RT. Lastly,

we also tested whether there were neural responses specifically linked to participants' subjective

confidence ratings for a given choice and did not observe significant responses in any brain region.

Discussion

Using fMRI, a signal detection model, and a novel memory-guided decision-making

paradigm, we asked how different brain regions integrate relatively coded knowledge of different

people's personal attributes within absolutely coded metric spaces (Fig. 1). Focusing on reference

frame-sensitive responses, we identified an entorhinal/subicular region that related to the absolute

distance between the stranger's rating and the ratings of choice options (Fig. 3). In parallel, superior

parietal lobule activity increased when the *anchor* required a mental shift from the middle of the scale

towards the periphery(Fig. 4-Figure supplement 1). Finally, we found that striatal responses also

preceded correct choices, which were partially driven by decisions about which individual had the

highest or lowest preference rating (Fig. 4). In what follows, we relate these memory-guided choice

findings to the wider literature – and to the different hippocampal formation responses we observed.

We then speculate on potential neural computations induced by our task.

Entorhinal-subicular representations of social knowledge along multiple scales

We observed entorhinal/subicular responses to more precise, fine-grained choices, if self-

comparisons were involved, but more straightforward choices otherwise. This result is partially a

consequence of lower confidence when rating the *friend* and *canonical* individual, as well as smaller

mean absolute distances between those two individuals and the stranger, which induced significantly

higher choice entropy for the *self anchor* condition; i.e., a more ambiguous/less discriminable choice

scenario. Despite the difference between the *anchor* conditions in mean choice entropy (potentially

due to an entropy ceiling effect in the *self anchor* condition), a similar distinction was not observed in

the hippocampal body, or other brain regions. Notably, in rodents, hippocampal place representations

are typically self-referenced and continuous (Buzsaki & Moser, 2013). In contrast,

entorhinal/subicular grid, as well as object and boundary vector representations use multiple reference

frames, and can either be continuously or discretely coded (Hartley et al., 2013; Diehl et al., 2017;

Høydal et al., 2018). This highlights a potential functional dissociation to memory-guided decision-

making involving different reference frames, where the body of the hippocampus could relate to self-

referenced sampling of prior experience (Ezzyat & Davachi, 2014; Bornstein & Norman, 2017;

Bakkour et al., 2018; Shadlen & Shohamy, 2016). While in contrast, we observe entorhinal/subicular

sensitivity to the depth of personal knowledge for different familiar individuals (i.e., how well we

know someone's personal preferences). Further support for this distinction stems from the putative

role of the entorhinal cortex (Buzsaki & Moser, 2013; Maas et al., 2015; Navarro et al., 2015) and

subicular region (Dalton & Maguire, 2017) in integrating incoming sensory input with learned

hippocampal representations. Building on recent studies of macaque and human entorhinal cortex in

spatial and non-spatial tasks, our results potentially speak to the organizational principles governing

metrically coded maps (Doeller et al., 2010; Chadwick et al., 2015; Constantinescu et al., 2016;

Lositsky et al., 2016; Vass et al., 2017; Julian et al., 2018; Meister et al., 2018; Nau et al., 2018),

along with the implicit encoding of discrete graphs (Garvert et al., 2017), which may be located

within the same brain region. This architecture portends a domain general role for entorhinal cortex in

memory-guided decision-making involving multiple reference frames.

Parietal rescaling of metrically coded preferences

In our task, participants retrieve and non-linearly rescale different mental number lines of

personal preferences. Following previous observations of posterior parietal involvement in

maintaining a mental number line (Dehaene et al., 1993, 2003) and manipulating the position of items

in spatial working memory (Koenigs et al., 2009), we observe bilateral superior parietal lobule

responses during trials when participants need to mentally rescale the anchor's relative position in the

center towards an absolute position on the periphery of the scale. Moreover, our observation of

superior parietal lobule involvement in mental rescaling of metrically scaled preferences meshes well

with the putative notion that parietal areas track magnitudes (Bueti & Walsh, 2009).

Striatal involvement in knowledge-guided social decision-making

We observed a ventral striatal signal corresponding to correct choices, which also related to

choices where highest/lowest–as opposed to proximity–judgments could be made. This distinction

between hippocampal-entorhinal versus striatal responses to different knowledge-guided decision-

making strategies closely follows spatial navigation strategies; where the subjects align themselves to

a single landmark, instead of a boundary, in order to infer the direction of a goal location (Doeller &

Burgess, 2008). The implicit functional neuroanatomy may parallel the dissociation between

hippocampal and striatal responses observed in the current study. This follows since boundary-

oriented navigation is linked to the hippocampus, whereas landmark-based navigation is related to the

striatum (Doeller et al., 2008). More generally, this striatal versus hippocampal dissociation highlights

a potential mechanism for how reinforcement/procedural learning could reduce metrically-coded

relational knowledge into more efficiently usable heuristics (Simon & Daw, 2011; Gershman & Daw,

2017), paralleling categorical versus coordinate-based judgments in spatial cognition (Kosslyn, 1987;

Baumann & Mattingley, 2014).

Allocentricity and the dimensionality of preferences

Our findings highlight the role of the hippocampal formation, namely the entorhinal cortex

and subiculum, in the functional anatomy of how we transform relative and absolute reference frames

during decision-making. However, since all of our conditions involve a transformation, it is unclear

whether humans ever preferentially use an absolute or 'allocentric' frame of reference during

decision-making without drawing upon their own frame of reference. Even in spatial and episodic

memory this question is difficult to resolve (see Filimon, 2015); since self-referencing helps us relate

past experience to our current environment (Vann et al., 2009). Useful clues about how we flexibly

transform relative and absolute reference frames come from the social psychology literature. A subset

of social psychology has focused on how individualized representations of others' preferences are

generated by anchoring to a known preference, and then adjusting accordingly, a phenomenon known

as 'anchoring and adjustment' (Epley & Gilovich, 2001; Epley et al., 2004; Tamir & Mitchell, 2013).

Given their similarities, jointly studying 'anchoring and adjustment' with boundary-oriented

navigation may offer a promising avenue for translational research across species and levels of

analysis.

We tested metrically-coded preferences along a single dimension (namely the likelihood of

people preferring things), but the true dimensionality of personal preferences is less clear. It is

plausible that we learn about others' preferences within a multi-dimensional trait space (Tamir &

Thornton, 2018). Yet we do not know the number of dimensions that support this trait space (Tavares

et al., 2015; Bellmund et al., 2018). Further work may help relate what we know about navigating

physical space with the mental exploration of more abstract spaces (Aronov et al., 2017; Kaplan et al.,

2017a).

Our study induces a spatial (metric) strategy, preventing us from asking whether humans must

use map-like coding in order to relate others' preferences to their own. Furthermore, decisions in our

task involve an abstract one-dimensional spatial discrimination, where subjects determine the relative

proximity of a stranger's rating to the non-anchor individuals. Future work can implicitly test

discrimination of metrically coded decision variables in different reference frames more implicitly

(i.e., without an explicit spatial element) to determine whether the spatial element is required for

hippocampal-entorhinal involvement. Still, theoretical work has provided support for the use of a

spatial strategy, where non-human primate research has investigated social cognition in terms of

coordinate transforms (Chang et al., 2013). Social coordinate transformation experiments have

captured how social variables are encoded in individual neurons – and how encoding changes over

different computational stages during social decision-making (Chang, 2013), like current versus long-

term frames of reference (Boorman et al., 2013). Extending such work to abstract knowledge can

potentially help us understand how coordinate transformations can generally guide everyday

decisions.

Conclusion

Metric coding of decision variables informs decisions by providing coordinates and

boundaries that can be translated between different frames of reference. We provide evidence that

neural computations – that integrate relative and absolute coordinates during spatial navigation – also

extend to relating others' personal attributes to our own. Consequently, these data provide important

clues about how hippocampal-entorhinal map-like coding may facilitate memory-guided decision-

making in a domain general manner.

Materials and Methods

Subjects

Twenty-four healthy adult subjects were studied and compensated (16 female; mean age in

25.5 y; SD of 5.38 y) and gave informed written consent to participate. This study was approved by

the local research ethics committee at University College London. The study was conducted in

accordance with Declaration of Helsinki protocols. All subjects were right-handed had normal or

corrected-to-normal vision and reported good health with no prior history of neurological disease.

Task

Stimuli were presented using the Cogent (http://www.vislab.ucl.ac.uk/cogent.php) toolbox

running in MATLAB (Mathworks, Natick, MA, USA). Subjects performed a self-paced (max 9s),

forced-choice, social decision making-task featuring 100 different personal preferences for 3

personally familiar individuals, which included themselves. Subjects viewed a personal preference for

a novel stranger, represented by an avatar (Fig. 1), that was presented on a scale relative to one of

three known individuals (*anchor*). Immediately prior to scanning, subjects were first trained to infer

the stranger's rating and then look below the scale in order to decide which of the two remaining

familiar individuals was closer to that rating. All of the information needed to perform the task was

presented at once on the screen and the only aspects of the task that varied from trial to trial were the

anchor and choice options.

All ratings were obtained from subjects approximately 45 minutes prior to fMRI scanning.

Subjects gave likelihood ratings about 110 everyday scenarios (e.g. eating spicy food; see Figure 1-

Source data 1 for all scenarios) from 1-9 on a 0-10 scale (0 being impossible to 10 being extremely

likely) for themselves and two other familiar individuals. For one of the familiar individuals (*friend*),

subjects were asked to choose their closest friend of the same gender that had the most distinct

personality from the subject and – unlike the subject – ideally lived outside of London, in order to

induce different ratings between individuals. The third individual was a typical/*canonical* individual

of the same gender named Mr/Ms. Normal. Mr/Ms. Normal was supposed to correspond with what

they thought a normal person/exemplar at their stage of life would do for each scenario (Fig. 1A).

During the rating period, subjects were instructed to keep track of how their ratings related to each

other for a given scenario (e.g., the participant being a bit more likely to have spicy food than their

friend). Crucially, subjects also gave confidence ratings for the *canonical* exemplar and their *friend* on

every scenario on a scale from 1-5 (No Idea to Very Sure) in order to assess the consistency of their

rating (Fig. 1A). As a second confirmation of rating consistency, subjects also rated the familiar

individuals for every scenario after the fMRI task.

425   Subjects then performed a brief practice version of the fMRI social decision-making task

outside of the scanner, where subjects viewed a personal preference for a *stranger* that was presented

on a 0-10 scale relative to one of the known individuals (*anchor*). Subjects had a maximum of 9

seconds to decide whether the *stranger's* rating was closer to the two remaining (*non-anchor*)

individuals. The *anchor* was indicated by presenting their initials, which would either be the friend's

initials, ME (Self), or MN, which was an abbreviation for Mr/Ms. Normal (*Canonical*). All

information related to the decision was presented at once, with the scenario being listed above the

stranger and anchor individual on the scale (Fig. 1B). Directly below the scale "closer to

self/friend/canonical individual (A) or self/friend/canonical individual (B)" was written. After making

a decision, there was then a jittered intertrial interval (ITI) period (mean=2.43s; range=0.25-9s) where

a white fixation point overlaid on a black background was presented.

436   Crucially, the anchor individual was always placed in the middle of the scale, so that subjects

needed to use prior social knowledge in order to infer the *stranger's* absolute preference and form a

mental number line of the *non-anchor* preferences. In other words, subjects had to infer the stranger's

true (absolute) position in relation to the anchor's rating for that scenario and the closest boundary (0

or 10). For example, if the stranger was ¾ to the right of an anchor individual that was rated a 9, the

participant would infer that the stranger's rating was ¾ of the way between 9 and 10 (the right

boundary of the scale). Consequently, the subject would indicate the stranger's rating would

approximately be near 10 (actual rating=9.75). We assumed that subjects represented people's

preferences on this number line, similar to a mental number line (Dehaene et al., 1993), thereby

enabling them to choose the *individual* (A or B) that was closest to the *stranger*. If both individuals in

the choice were the same or equidistant from the stranger, subjects were instructed that either answer

was counted as correct. Same/equidistant trials were not used in either behavioral or fMRI analyses.

Subjects then practiced the task using the last 10 scenarios they rated, which were repeated

three times each. On the first few practice trials, subjects verbally rehearsed transforming the anchor's

rating from the middle of the screen to its actual (absolute) position and then inferring the stranger's

rating with verbal feedback from the experimenter until they performed the transformation correctly.

Then during fMRI scanning, subjects performed the task for the remaining 100 scenarios in

three different self-paced runs (once for each anchor individual) each lasting approximately 10

minutes (a maximum of 15 minutes). From a relative viewpoint, the stranger was either ±1/4 or 3/4 of

the way between the anchor individual and the boundary ratings of 0 and 10, which was presented

equally by run and condition. Subjects were instructed that it was a different stranger on each trial, so

the stranger didn't conserve any preferences. To further emphasize the lack of conserved preferences,

the stranger avatar randomly alternated between five colors (red, green, yellow, magenta, and cyan).

Once again after completing the fMRI task, subjects gave likelihood ratings for the friend and

canonical individuals outside of the scanner.

Computational Model

We used a trial-by-trial computational model of subjects' performance in order to quantify

how subjects' individual ratings and confidence judgments determined subjects' choice

discriminability during social decision-making (see Fig. 1C). Choice discriminability (or inverse

precision) was measured using Shannon entropy (Shannon, 1948). Shannon entropy (*H*) was

calculated by estimating the distribution of choice probabilities using a softmax function of individual

ratings. This included the standard deviation (σ_i) derived from subject's confidence ratings (C_i) for

each scenario (σ_i=1 for all self ratings), where the constant term accommodated the assumed stability

(reduced memory demands) of self ratings, as well as the dynamic range of confidence ratings.

$$\sigma_i = 1 + \tfrac{1}{2}(5 - C_i) : C_i \subset \{1, \ldots, 5\}$$

Equation 4

Furthermore, the inverse temperature parameter (β) of the softmax function was optimized using

each subject's trial-by-trial performance. We constructed predictions of neuronal responses in terms

of the Shannon entropy (H) of the choice probability in each trial for fMRI (Kaplan et al., 2017b).

We optimized subject-specific parameters across trials using maximum likelihood estimation

and the optimization toolbox in MATLAB (MathWorks, Inc). We then calculated trial-by-trial

parameter estimates of H (choice discriminability) using the group average softmax (precision or

inverse temperature) parameter. The ensuing trial-by-trial choice entropy measures were then used to

predict BOLD responses in our neuroimaging analyses.

fMRI Acquisition

Functional images were acquired on a 3T Siemens Trio scanner. BOLD T2*-weighted

functional images were acquired using a gradient-echo EPI pulse sequence acquired obliquely at 45°

with the following parameters: repetition time, 3,360 ms; echo time, 30 ms; slice thickness, 2 mm;

inter-slice gap, 1 mm; in-plane resolution, 3×3 mm; field of view, 64×72 mm^2; 48 slices per

volume. A field-map using a double echo FLASH sequence was recorded for distortion correction of

the acquired EPI (Weiskopf et al., 2006). After the functional scans, a T1-weighted 3-D MDEFT

structural image (1 mm^3) was acquired to co-register and display the functional data.

fMRI Analysis

Functional images were processed and analyzed using SPM12 (www.fil.ion.ucl.uk/spm). The

first five volumes were discarded to allow for T1 equilibration. Standard preprocessing included bias

correction for within-volume signal intensity differences, correction for differences in slice

acquisition timing, realignment/unwarping to correct for inter-scan movement, and normalization of

the images to an EPI template (specific to our sequence and scanner) that was aligned to the T1

Montreal Neurological Institute (MNI) template. Finally, the normalized functional images were

spatially smoothed with an isotropic 8-mm full-width half maximum Gaussian kernel. For the model

described below, all regressors, with the exception of six movement parameters of no interest, were

convolved with the SPM hemodynamic response function. Data were also high-pass filtered (cut-off

period = 128 s). Statistical analyses were performed using a univariate GLM with an event-related

experimental design.

GLM1: There were two periods of interest, the self-paced (9s maximum) social decision-making and

jittered baseline inter-trial interval (ITI), which were modeled as boxcar functions and convolved with

a canonical hemodynamic response function (HRF) to create regressors of interest. For each social

decision-making regressor (*self*, *friend*, and *canonical* anchor trials), there were parametric regressors

based on accuracy (whether the choice was correctly answered; 1=incorrect choice; 2=correct choice),

anchor rescaling, choice entropy (discriminability), reaction time (RT), and subjective confidence

ratings. Inferences about these effects were based upon t- and F-tests using the standard summary

statistic approach for second level random effects analysis.

GLM2: In a follow-up analysis to assay whether the ventral striatum accuracy effect was driven by

choices where highest/lowest judgment between the two choice individuals needed to be made, we

split decision-making trials in terms of whether a choice required determining which choice option

was highest/lowest, instead of closest. Ignoring the three conditions, we split the data into two

conditions; one where the target was between the two choice individuals, and the second where the

target was either higher or lower than both choice individuals.

All initial analyses were whole-brain analyses. Subsequently, post hoc statistical analyses

were conducted using 10-mm radius spheres in MarsBar toolbox (Brett et al., 2002) within SPM12

around the respective peak voxel specified in the GLM analysis. This allowed us to compare the

effects of different parametric regressors of interest (e.g., to determine whether an accuracy effect was

present in a region defined by an orthogonal main effect of choice discriminability). This ensured we

did not make any biased inferences in our post hoc analyses. We used 10-mm radius spheres for post

hoc statistical analyses–instead of clusters–since our hippocampal-entorhinal effects were corrected

for multiple comparisons at the peak-voxel level.

Given the previously hypothesized role of the entorhinal/subicular region and hippocampus in

absolute versus relative coding of environmental cues, we report whether peak-voxels in these regions

survive small-volume correction for multiple comparisons ($p < 0.05$) based on bilateral ROIs in the

entorhinal/subicular region (mask used in Chadwick et al., 2015; Garvert et al., 2017) and the

hippocampus (mask created using Neurosynth, Yarkoni et al., 2011). For all analyses outside of the

ROIs, we report activations surviving an uncorrected statistical threshold of $p = 0.001$ and correction

for multiple comparisons at the whole-brain level (FWE $p < 0.05$). Coordinates of brain regions are

reported in MNI space.

Acknowledgments

The authors would like to thank Asaf Gilboa, Jochen Michely, Philipp Schwartenbeck, and Geert-Jan

Will for helpful discussion, along with Martin Chadwick and Mona Garvert for providing an

entorhinal/subicular mask. We thank Jacob Bellmund and Joshua Julian for helpful comments on a

previous version of this manuscript. The authors would also like to thank Megan Creasey and Clive

Negus for help with scanning and the Wellcome Centre for Human Neuroimaging for providing

facilities. This work was funded by a Wellcome Trust grant to KJF (Ref: 088130/Z/09/Z), and a Sir

Henry Wellcome Postdoctoral Fellowship awarded to RK (Ref: 101261/Z/13/Z). The funders had no

role in study design, data collection and analysis, decision to publish, or preparation of the

manuscript. The authors declare no competing interests.

544
545   **References**
546
547   Amunts K, Kedo O, Kindler M, Pieperhoff P, Mohlberg H, Shah NJ, Habel U, Schneider F, Zilles K
548   (2005) Cytoarchitectonic mapping of the human amygdala, hippocampal region and entorhinal cortex:
549   intersubject variability and probability maps. Anat Embryol (Berl) 210:343-52.
550
551   Aronov, D., Nevers, R., and Tank, D.W. (2017). Mapping of a non-spatial dimension by the
552   hippocampal-entorhinal circuit. Nature *543*, 719-22.
553
554   Baumann, O., Mattingley, J.B. (2014) Dissociable roles of the hippocampus and parietal cortex in
555   processing of coordinate and categorical spatial information. Front Hum Neurosci *8, 73*
556
557   Bellmund JLS, Gardenfors P, Moser EI, Doeller CF. (2018). Navigating cognition: Spatial codes for
558   human thinking. Science 362.
559
560   Boccara, C.N., Sargolini, F., Thoresen, V.H., Solstad, T., Witter, M.P., Moser, E.I., and Moser, M.B.
561   (2010). Grid cells in pre- and parasubiculum. Nat Neurosci. *13*, 987-94.
562
563   Boorman, E.D., Rushworth, M.F., Behrens, T.E. (2013) Ventromedial prefrontal and anterior
564   cingulate cortex adopt choice and default reference frames during sequential multi-alternative choice.
565   J Neurosci, 33:2242-53.
566

567   Brett, M., Anton, J.L., Valabregue, R., and Poline, J.B. (2002). Region of interest analysis using an
568   SPM toolbox; Sendai, Organization for Human Brain Mapping.
569
570   Bueti, D., Walsh V. (2009) The parietal cortex and the representation of time, space, number and
571   other magnitudes. Philos Trans R Soc Lond B Biol Sci *364*:1831-40.
572
573   Burgess, N., Jackson, A., Hartley, T., and O'Keefe, J. (2000). Predictions derived from modelling the
574   hippocampal role in navigation. Biological cybernetics *83*, 301-12.
575
576   Buzsaki, G. and Moser, E.I. (2013). Memory, navigation and theta rhythm in the hippocampal-
577   entorhinal system. Nat Neurosci. *16*, 130-8.
578
579   Chadwick, M.J., Jolly, A.E., Amos, D.P., Hassabis, D., and Spiers, H.J. (2015). A goal direction
580   signal in the human entorhinal/subicular region. Curr Biol. *25*, 87-92.
581
582   Chang, S.W. (2013). Coordinate transformation approach to social interactions. Front Neurosci. *7*,
583   147.
584
585   Chang, S.W., Gariepy, J.F., and Platt, M.L. (2013). Neuronal reference frames for social decisions in
586   primate frontal cortex. Nat Neurosci. *16*, 243-50.
587
588   Constantinescu, A.O., O'Reilly, J.X., and Behrens, T.E.J. (2016). Organizing conceptual knowledge
589   in humans with a gridlike code. Science *352*, 1464-68.
590
591   Dalton, M.A., and Maguire, E.A. (2017). The pre/parasubiculum: a hippocampal hub for scene-based
592   cognition? Curr Opin Behav Sci. *17*, 34-40.
593
594   Daw. N.D., O'Doherty, J.P., Dayan, P., Seymour B., Dolan, R.J. (2006) Cortical substrates for
595   exploratory decisions in humans. Nature. 441:876-9.
596
597   Daw, N.D. in Decision Making, Affect, and Learning: Attention and Performance XXIII,
598   eds:Delgado, M.R., Phelps, E.A., Robbins, T.W. (Oxford Univ Press, Oxford) (2011).
599
600   Diehl, G.W., Hon, O.J., Leutgeb, S., and Leutgeb, J.K. (2017). Grid and Nongrid Cells in Medial
601   Entorhinal Cortex Represent Spatial Location and Environmental Features with Complementary
602   Coding Schemes. Neuron *94*, 83-92.
603
604   Dehaene, S., Bossini, S., and Giraux, P. (1993). The mental representation of parity and number
605   magnitude. Journal of Experimental Psychology: General. *122*, 371-96.
606
607   Dehaene., S., Piazza, M., Pinel, P., Cohen, L. (2003) Three parietal circuits for number processing.
608   Cognitive Neuropsychology. 20, 487-506.
609
610   Doeller, C.F. and Burgess, N. (2008). Distinct error-correcting and incidental learning of location
611   relative to landmarks and boundaries. Proc Natl Acad Sci USA. *105*, 5909-14
612
613   Doeller, C.F., King, J.A., and Burgess, N. (2008). Parallel striatal and hippocampal systems for
614   landmarks and boundaries in spatial memory. Proc Natl Acad Sci USA. *105*, 5915-20
615
616   Doeller, C.F., Barry, C., and Burgess, N. (2010). Evidence for grid cells in a human memory network.
617   Nature *463*, 657-61.
618
619   Eichenbaum, H. (2015). The Hippocampus as a Cognitive Map … of Social Space. Neuron, *87*, 9-11.
620

621   Epley, N. and Gilovich, T. (2001). Putting adjustment back in the anchoring and adjustment heuristic:
622   Differential processing of self-generated and experimenter-provided anchors. Psychol Sci. *12*, 391-96.
623
624   Epley, N., Keysar, B., Van Boven, L., and Gilovich, T. (2004). Perspective tasking as egocentric
625   anchoring and adjustment. J Pers Soc Psychol. *87*, 327-39.
626
627   Ezzyat, Y, Davachi, L. (2014) Similarity breeds proximity: pattern similarity within and across
628   contexts is related to later mnemonic judgments of temporal proximity. Neuron, *81*:1176-89.
629
630   Filimon, F. (2015). Are all spatial reference frames egocentric? Reinterpreting evidence for
631   allocentric, object-centered, or world-centered reference frames. Front Hum Neurosci. *9*, 648.
632
633   Garvert, M.M., Dolan, R.J., and Behrens, T.E. (2017). A map of abstract relational knowledge in the
634   human hippocampal-entorhinal cortex. Elife 6.
635
636   Gershman, S.J. and Daw, N.D. (2017). Reinforcement learning and episodic memory in humans and
637   animals: an integrative framework. Ann Rev Psychol. *68*, 101-128.
638
639   Glascher, J., Daw, N., Dayan, P., O'Doherty, J.P. (2010) States versus rewards: dissociable neural
640   prediction error signals underlying model-based and model-free reinforcement learning. Neuron.
641   66:585-95.
642
643   Hafting, T., Fyhn, M., Molden, S., Moser, M.B. and Moser, E.I. (2005). Microstructure of a spatial
644   map in the entorhinal cortex. Nature *436*, 801-6.
645
646   Hartley, T., Burgess, N., Lever, C., Cacucci, F. and O'Keefe, J. (2000). Modeling place fields in terms
647   of the cortical inputs to the hippocampus. Hippocampus *10*, 369-79
648
649   Hartley, T., Lever, C., Burgess, N. and O'Keefe, J. (2013). Space in the brain: how the hippocampal
650   formation supports spatial cognition. Philos Trans R Soc Lond B. *369*, 20120510.
651
652   Howard, L.R., Javadi, A.H., Yu, Y., Mill, R.D., Morrison, L.C., Knight, R., Loftus, M.M., Staskute,
653   L., and Spiers, H.J. (2014). The hippocampus and entorhinal cortex encode the path and Euclidean
654   distances to goals during navigation. Curr Bio. *24*, 1331-40.
655
656   Høydal, Ø.A., Skytøen, E.R., Moser, M.B., and Moser, E.I. (2018) Object-vector coding in the medial
657   entorhinal cortex. bioRxiv
658
659   Julian, J.B., Keinath, A.T., Frazzetta, G., and Epstein, R.A. (2018). Human entorhinal cortex
660   represents visual space using a boundary-anchored grid. Nat Neurosci. *21*, 191-94.
661
662   Kaplan, R., Schuck, N.W., and Doeller, C.F. (2017a). The Role of Mental Maps in Decision-Making.
663   Trends Neurosci. *40*, 256-9.
664
665   Kaplan, R., King, J., Koster, R., Penny, W.D., Burgess, N., and Friston, K.J. (2017b). The neural
666   representation of prospective choice during spatial planning and decisions. PLoS Biol. *15*, e1002588.
667
668   Koenigs, M., Barbey, A.K., Postle, B.R., and Grafman, J. (2009) Superior parietal cortex is critical for
669   the manipulation of information in working memory. J Neurosci. *29*:14980-14986.
670
671   Kosslyn, S.M. (1987) Seeing and imagining in the cerebral hemispheres: A computational approach.
672   Psychological Review, 94:148-75.
673
674   Kumaran, D. (2012). What representations and computations underpin the contribution of the
675   hippocampus to generalization and inference? Front Hum Neurosci. *6*, 157

676
677 Kumaran, D., Melo, H.L., and Duzel, E. (2012). The emergence and representation of knowledge
678 about social and non-social hierarchies. Neuron *134*, 653-8.
679
680 Kumaran, D., Banino, A., Blundell, C., Hassabis, D., and Dayan, P. (2016). Computations Underlying
681 Social Hierarchy Learning: Distinct Neural Mechanisms for Updating and Representing Self-Relevant
682 Information. Neuron *92*, 1135-47.
683
684 Leutgeb, J.K., Leutgeb, S., Moser, M.B., and Moser, E.I. (2007). Pattern separation in the dentate
685 gyrus and CA3 of the hippocampus. Science *315*, 961-6.
686
687 Lositsky O, Chen J, Toker D, Honey CJ, Shvartsman M, Poppenk JL, Hasson U, Norman KA (2016)
688 Neural pattern change during encoding of a narrative predicts retrospective duration estimates. Elife
689 5.
690
691 Maass, A., Berron, D., Libby, L.A., Ranganath C, Duzel, E (2015). Functional subregions of the
692 human entorhinal cortex. Elife 4.
693
694 Mack ML, Love BC, Preston AR (2016) Dynamic updating of hippocampal object representations
695 reflects new conceptual knowledge. Proc Natl Acad Sci USA, 113:13203-13208.
696
697 Mack ML, Love BC, Preston AR (2017) Building concepts one episode at a time: The hippocampus
698 and concept formation. Neurosci Lett
699
700 Marr, D. (1971). Simple memory: a theory for archicortex. Philos Trans R Soc Lond B Biol Sci. *262*,
701 23–81
702
703 McNaughton, B.L., Battaglia, F.P., Jensen, O., Moser, E.I., and Moser, M.B. (2006). Path integration
704 and the neural basis of the 'cognitive map'. Nat Rev Neurosci. *7*, 663-78,
705
706 Meister, M.L.R. and Buffalo, E.A. (2018). Neurons in primate entorhinal cortex represent gaze
707 position in multiple spatial reference frames. J Neurosci. *38*, 2430-41.
708
709 Nau, M., Navarro Schroeder, T., Bellmund, J.L.S., and Doeller, C.F. (2018). Hexadirectional coding
710 of visual space in human entorhinal cortex. Nat Neurosci. *21*, 188-90.
711
712 Navarro Schroeder, T., Haak, K.V., Zaragoza Jimenez, N.I., Beckmann, C.F., and Doeller C.F.
713 (2015). Functional topography of the human entorhinal cortex. Elife 4.
714
715 O'Keefe, J. and Dostrovsky, J. (1971). The hippocampus as a spatial map: Preliminary evidence from
716 unit activity in the freely-moving rat. Brain Res. *34*, 171-5.
717
718 O'Keefe J and Nadel L. The Hippocampus as a Cognitive Map. 1978:114–52 (Oxford Univ Press)
719
720 O'Keefe, J., and Burgess, N. (1996). Geometric determinants of the place fields of hippocampal
721 neurons. Nature *381*, 425-28.
722
723 Schiller, D., Eichenbaum, H., Buffalo, E.A., Davachi, L., Foster, D.J., Leutgeb, S., and Ranganath, C.
724 (2015). Memory and Space: Towards an Understanding of the Cognitive Map. J Neurosci. *35*, 13904-
725 11.
726
727 Schwarz G (1978) Estimating the dimension of a model. Ann Stat **6**:461-64.
728
729 Shadlen, M.N. and Shohamy, D. (2016). Decision Making and Sequential Sampling from Memory.
730 Neuron *90*, 927-39.

731
732   Shannon, C.E. (1948). A mathematical theory of communication. The Bell System Technical Journal
733   *27*, 379-423.
734
735   Simon, D.A. and Daw, N.D. (2011). Neural correlates of forward planning in a spatial decision task in
736   humans. J Neurosci. *31*, 5526-39.
737
738   Tamir, D.I. and Mitchell, J.P. (2013). Anchoring and adjustment during social inferences. J Exp
739   Psychol Gen. *142*, 151-62.
740
741   Tamir, D.I. and Thornton, M.A. (2018). Modeling the Predictive Social Mind. Trends Cogn Sci. *22*,
742   201-12.
743
744   Tanner Jr., W.P. and Swets, J.A. (1954) A decision-making theory of visual detection. *Psychological
745   Review*, *61*,401-9.
746
747   Taube, J.S., Muller, R.U., and Ranck, J.B. (1990). Head-Direction Cells Recorded from the
748   Postsubiculum in Freely Moving Rats. I. Description and Quantitative Analysis. J Neurosci. *10*, 420-
749   35.
750
751   Tavares, R.M., Mendelsohn, A., Grossman, Y., Williams, C.H., Shapiro, M., Trope, Y., and Schiller,
752   D. (2015). A Map for Social Navigation in the Human Brain. Neuron *87*, 231-43.
753
754   Vann, S.D., Aggleton, J.P., and Maguire, E.A. (2009). What does the retrosplenial cortex do? Nat Rev
755   Neuro. *10*, 792-802.
756
757   Vass, L.K. and Epstein, R.A. (2017). Common Neural Representations for Visually Guided
758   Reorientation and Spatial Imagery. Cereb Cortex. *27*, 1457-71.
759
760   Weiskopf, N., Hutton, C., Josephs, O., and Deichmann, R. (2006). Optimal EPI parameters for
761   reduction of susceptibility-induced BOLD sensitivity losses: A whole-brain analysis at 3 T and 1.5
762   T. Neuroimage *33*, 493–504.
763
764   Yarkoni, T., Poldrack, R.A., Nichols, T.E., Van Essen, D.C., and Wager, T.D. (2011). Large-scale
765   automated synthesis of human functional neuroimaging data. Nat Methods. *8*, 665-70.
766
767   Zeithamova, D., Maddox, W.T., Schnyer, D.M. (2008) Dissociable prototype learning systems:
768   evidence from brain imaging and behavior. J Neurosci. 28:13194-201.
769

770
771
Figure 1. Experiment. *A*. Right before fMRI scanning, subjects were instructed to choose a friend with
a different personality of the same gender. Subsequently, subjects rated from 1-9, on a 0-10 scale,
how likely (likelihood) they (*self*), a close friend (*friend*), and the typical person (*canonical*) were to
partake in a variety of everyday scenarios (e.g., eat spicy food, read a book, cycle to work). To allow
for strangers with more extreme ratings than the familiar individuals in the fMRI paradigm, subjects
were restricted to rating between 1-9. Subjects also reported their confidence, on a 1-5 scale, for each
scenario. *B*. fMRI paradigm. During a forced-choice task, subjects made a decision on the relative
proximity of a *stranger*'s likelihood rating for an everyday scenario relative to the likelihood ratings
for the *self*, *friend*, and *canonical* individuals for that same scenario. On each self-paced trial (max.
allowed response time 9s), subjects viewed a personal preference for a new *stranger* presented
relative to one of the known individuals' initials (*anchor*) on a number line. Subjects had to determine
which one of the two remaining (i.e., non-anchor) familiar individuals was closer to the *stranger*'s
rating. Crucially, the anchor individual (e.g., ME=self; MN=canonical 'Mr./Ms. Normal'; JD=friend's
initial) was always placed in the middle of the scale, ensuring that subjects had to use memory of their

ratings made before fMRI scanning to infer the *stranger's* absolute preference relative to the *anchor's*
true rating and the ends of the number line. Additionally, subjects were instructed that the number line
ranged from 0 and 10. For example, if the stranger was ¾ to the right of the anchor with a rating of 9,
the participant would infer that the stranger's rating was ¾ of the way between 9 and 10 (the right
boundary of the scale). Consequently, the participant would indicate that the stranger's rating would
be approximately near 10. Notably, the numbers on the scale were not visible during the task. After
making a decision, an intertrial interval (mean=2.43s) screen with a white fixation point in the center
of a black screen appeared. *C*. Illustration of the behavioral model. Top illustration shows an
ambiguous, less discriminable choice, while the bottom illustration shows a straightforward, highly
discriminable choice. We quantified the difficulty of discriminating a particular choice by fitting a
formal signal detection model, based on the absolute distance between the two choice individuals on
the scale and how confident subjects were in their ratings (e.g., comparing the *stranger* rating,
represented by the blue avatar, with their rating for their *friend* and the *canonical* individual).
Subjective confidence was represented by the standard deviation for each rating (e.g., curve width in
the illustrations), where lower confidence entails higher standard deviations, and helped account for
the influence of memory on choice behavior. *D*. Anchor rescaling. Illustration of how the stranger's
rating is inferred by mentally rescaling the anchor individual's rating from its perceived relative
position on the screen (5), to its absolute position (participant's rating) on the preference scale.
804
Figure 2. Behavioral Results. *A*. Mean ratings across subjects for each familiar individual and every
scenario. Occurrences are out of the 100 total trials per condition. *B*. Rating Consistency. Difference
in ratings pre- and post-fMRI scanning for *friend* and *canonical* individuals *C*. Distribution of
absolute distances by condition. Mean amount of trials for each *anchor* and absolute distance.
Significant effect of condition for absolute distance between the two individuals' ratings and the
stranger's (p=0.001). Part of the x-axis is shaded in gray because only a fraction of subjects had trials
with absolute distances of 5 (*self*: 20/24; *friend*: 19/24; *canonical*: 24/24), 6 (*self*: 14/24; *friend*: 16/24;
canonical: 23/24), 7 (*self*: 6/24; *friend*: 7/24; *canonical*: 16/24), and 8 (*self*: 3/24; *friend*: 1/24;
canonical: 13/24, respectively for each *anchor* condition. Individuals being compared are listed in the
key with the corresponding anchor/condition name listed in parentheses. *D*. Reaction time: Significant
effect of condition for reaction time/decision speed (p=.022). Individuals being compared are listed
below each bar with the corresponding anchor condition listed in parentheses. *E*. Absolute distances
and performance: Significant relationship (p<.001) between accuracy and the absolute distance
between strangers' ratings and the non-anchor individuals for each trial. 50% represents chance level
of accuracy. 7 & 8 on the x-axis are shaded in gray because 18/24 and 13/24 of subjects had trials
with absolute distances of 7 & 8, respectively. *F*. Choice entropy: Significant effect of condition for
choice entropy (p<0.001). Individuals being compared listed below each bar, with corresponding
anchor listed in parentheses. All error bars showing mean ± SEM. For absolute distance plots, the
absolute value of each absolute distance was rounded to the closest integer and plotted from 1 to 8.
824
825
Figure 3. Entorhinal/Subicular Choice Discrimination Effects. *A*. Coronal image of right
entorhinal/subicular region exhibiting an effect of choice discriminability/entropy by condition circled
in turquoise. B.*:* Effect size for a 10-mm sphere around right entorhinal/subicular region exhibiting
effect of choice entropy by condition (mean ± SEM). Asterisk marks significance at p<.05. C.
Coronal image showing right entorhinal/subicular (circled in turquoise) correlation with choice
entropy for *f*riend and *canonical anchor* trials (i.e., choices involving self-comparisons) versus *self*
anchor trials (i.e., trials comparing canonical versus friend ratings). Portion of left
entorhinal/subicular region showing same effect is also visible. A positive effect size indicates a
positive BOLD correlation with choice entropy (i.e., ambiguous choices), whereas a negative effect
size indicates a negative BOLD correlation with choice entropy in the same comparison (i.e.,
straightforward choices). All highlighted regions survived FWE correction for multiple comparisons
at p< 0.05 and are displayed at an uncorrected statistical threshold of p<.005 for display purposes. For
visualization purposes, entorhinal/subicular (blue) and hippocampal body (red) probabilistic masks
from the Jülich SPM Anatomy toolbox are presented (Amunts et al., 2005).
840

Figure 4. Striatum and Decision Accuracy. *A*. Ventral striatal activity related to correct versus
incorrect choices. The ventral striatal cluster survived cluster-level FWE correction at p< 0.05 and is
displayed at an uncorrected statistical threshold of p<.001. *B*. Effect sizes for a 10-mm sphere around
right ventral striatum peak voxel (mean ± SEM). Individuals being compared list below with anchor
in parentheses. A positive effect size indicates a positive BOLD correlation with correct choices.
Asterisk marks significance at p<.05. *C*. Plot showing between-subject correlation for subjects'
ventral striatal fMRI signals with behavioral performance. Ventral striatal effects were for
highest/lowest judgments versus proximity judgment trials (GLM2). Behavioral performance was
taken from subjects' performance on trials, where highest/lowest judgments could be used, versus
their performance on trials where a proximity judgment could be used. Subjects who performed better
for highest/lowest judgments exhibited increased ventral striatal activity for the same contrast.

852
853 **Figure Supplements**

854
855 Figure 2-Figure supplement 1. Ratings and Overlap. Significant effect of condition for ratings overlap
856 (the same ratings) between the two individuals (p<0.001). Individuals being compared are listed
857 below each bar with the corresponding anchor/condition name listed in parentheses. Occurrences are
858 out of the 100 trials per condition.

859
Figure 2-Figure supplement 2. Absolute distances and reaction time: Significant relationship (p<.001)
between decision speed (reaction time) and the absolute distance between strangers' ratings and the
non-anchor individuals for each trial. The absolute value of absolute distances were rounded to the
closest integer and plotted from 1 to 8. 7 & 8 on the x-axis are shaded in gray, because only 18/24
and 13/24 subjects had trials with absolute distances of 7 & 8 respectively. Error bars showing mean ±
SEM.

866
867 Figure 4-Figure supplement 1. Superior Parietal Lobe Rescaling Effect. Sagittal image showing
868 superior parietal lobule effect of mentally rescaling anchor towards the periphery in either direction,
869 as seen in Figure 1D. Highlighted region survived cluster-level FWE correction at p< 0.05 and image
870 is displayed at an uncorrected statistical threshold of p<.001.

871
872 Figure 4-Figure supplement 2. Coronal image of increased intraparietal sulcus activity for correct
873 versus incorrect choices. Highlighted region survived cluster-level FWE correction at p< 0.05 and
874 image is displayed at an uncorrected statistical threshold of p<.001.

875
876 Figure 4-figure supplement 3. Images of increased posterior parietal cortex and precuneus activity for
877 slower reaction times (RTs). Highlighted region survived cluster-level FWE correction at p< 0.05 and
878 image is displayed at an uncorrected statistical threshold of p<.001.

879
Source Data
Figure 1-Source Data 1. List of Rated Scenarios. Last 10 were used during practice trials and first 100
were used for the fMRI task.
Figure 2-Source Data 1. Data used to make Figure 2A.
Figure 2-Source Data 2. Data used to make Figure 2B.
Figure 2-Source Data 3. Data used to make Figure 2C.
Figure 2-Source Data 4. Data used to make Figure 2D.
Figure 2-Source Data 5. Data used to make Figure 2E.
Figure 2-Source Data 6. Data used to make Figure 2F.
Figure 2-Source Data 7. Data used to make Figure 2-Figure supplement 1.
Figure 2-Source Data 8. Data used to make Figure 2-Figure supplement 2.

A

B

Parameter Estimates (a.u.)

Friend & Canonical (Self) | Canonical & Self (Friend) | Friend & Self (Canonical)

t statistic(23)

C

Ventral Striatal Parameter Estimates (a.u.)

Performance on highest/lowest v proximity judgments (fraction correct)

3.8   t statistic(23)   4.4

t statistic(23)   3.7   5.5

3.7 t statistic(23) 5.5