Generalized sample verification models to estimate ecological state variables with detection-nondetection data while accounting for imperfect detection and false positive errors

John D. J. Clare[1*], Benjamin Zuckerberg[1], and Philip A. Townsend[1]

[1]Department of Forest and Wildlife Ecology, University of Wisconsin – Madison, Madison, Wisconsin

[*]jclare2@wisc.edu; 1630 Linden Drive, Madison, Wisconsin 53706

Abstract

Spatially indexed repeated detection-nondetection data is widely collected in ecological studies

in order to estimate parameters such as species distribution, relative abundance, density, richness,

or phenology while accounting for imperfect detection. Given growing evidence that false

positive error is also present within most data, more recent model development has focused on

also explicitly accounting for this error type. To date, however, most modeling efforts have

improved occupancy estimation. We describe a generalizable structure for using verified samples

to estimate and account for false positive error in detection-nondetection data that can be flexibly

implemented within many existing model types. We use simulation to demonstrate that

estimators for relative abundance, arrival time, and density exhibit bias under realistic levels of

false positive prevalence, and that our modified estimators improve performance. As ecologists

increasingly use expedient but potentially error-prone techniques to classify growing volumes of

data, properly accounting for misclassification will be critical for sound ecological inference.

The generalized model structure presented here provides ecologists possessing even a small

amount of verified data a means to correct for false positive error and estimate several state

variables more accurately.

Introduction

Binary detection non-detection data is widely used in ecology because it directly describes many

variables of interest, can be used to derive many other variables, and is more reliably collected

and more easily modeled than continuous, count, or categorical types. Repeated detection-

nondetection data has a long history of use within ecology for the purposes of accounting for

zero-inflation, first within capture-recapture studies (e.g., Otis et al. 1978). The logistical

difficulties associated with marking or repeatedly identifying individual organisms across large

spatial or temporal domains are much greater than repeatedly identifying species or other

organism states across those domains. Unsurprisingly, there has been rapid recent adoption of

space or site-structured models that record species or other phenomena repeatedly at specific

locations to estimate parameters associated with species distribution, relative abundance, density,

or phenology (MacKenzie et a. 2002, Royle and Nichols 2003, Roth et al. 2014, Ramsey et al.

2015) or associated dynamics while still accounting for the imperfect detection that motivated

capture-recapture studies.

However, a growing body of evidence suggests that binary data are collected with both

false negative observation error and false positive error. Across a variety of protocols, false

positives interspecifically range from nearly negligible to constituting 20% of observations or

more (Simons et al. 2007, McClintock et al. 2010, Swanson et al. 2016, Norouzzadeh et al.

2018). This has motivated model extensions to account for false positive error as well as false

negative error in binary data using a variety of sampling techniques (e.g., Miller et al. 2011,

Chambert et al. 2015). Simulation and empirical studies indicate that ignoring false-positive error

can lead to severely biased inference regarding occupancy or occupancy dynamics, and that

using false positive extensions provides more reliable inference (e.g., Miller et al. 2015).

However, efforts to address false positives have largely been confined to occupancy estimation

even though any parameter that can be estimated with binary data is likely to be sensitive to un-

assumed error.

Here, we address this issue by first reformulating the sample-verification false positive

model for occurrence presented by Chambert et al. (2015) to make it more easily extensible to

other models. We use simulation to demonstrate that estimators using repeated binary data to

estimate relative abundance, density, and species arrival are sensitive to false positive error, and

to show that our model extensions permit more rigorous inference.

Methods

Chambert et al. (2015) assume that an investigator has recorded repeated detection-nondetection

data $\mathbf{y}$ of some species (or other phenomena of interest) at $i = 1, 2, \ldots R$ locations over $j = 1,$

$2 \ldots T$ discrete sampling intervals, where $y_{i,j} = 1$ if species is observed and 0 otherwise. The

purpose of the sampling is to estimate the binary occurrence state within a finite sample of sites

(z_i) or the population level probability of occurrence ψ, assuming $z_i \sim$ Bernoulli (ψ). Within some

number of sampling intervals at specific sites, observations ($v_{i,j}$) have been verified as either

containing only true positives ($v_{i,j} = 1$), only false positives ($v_{i,j} = 2$), both ($v_{i,j} = 3$), or no

observations ($v_{i,j} = 4$). These observations might include images, audio or video recordings, or

physical samples (hair or scat) that can subsequently be confirmed via expert evaluation,

laboratory analysis, or other means. Data from confirmed samples $v_{i,j} \sim$ Categorical ($\mathbf{\Omega}$), where

the elements of $\mathbf{\Omega}$ are conditional on whether the species occurs at site i or not. If $z_i = 1$ (species

occurs), then $\mathbf{\Omega} = [\{(s_1 \times (1 - s_0)\} \{s_0 \times (1 - s_1)\} \{s_1 \times s_0\} \{(1 - s_1) \times (1 - s_0)\}]$. If $z_i = 0$, the only

possible outcomes are a false positive detection or no detection, and $\mathbf{\Omega} = [\{0\} \{s_0\} \{0\} \{1 - s_0\}]$.

Here s_1 and s_0 represent the probabilities that a sampling interval contains > 0 true positive or

false positive observations conditional upon the occurrence state. A similar conditional statement

for unconfirmed data is $y_{i,j}|z_i \sim$ Bernoulli ($z_i \times p_{11} + (1 - z_i) \times p_{10}$). If present, a species can either

be truly or falsely detected with probability $p_{11} = s_1 + s_0 - (s_1 \times s_0)$, and if not it can only be

falsely detected with probability $p_{10} = s_0$.

Our initial description includes two alterations to the sampling protocols described by

Chambert et al. (2015) that we have previously shown to be valid (Clare et al. *in review).*

Chambert et al. (2015) describe v as including all sampling intervals at a subset of sites k such

that v and y are completely distinct and have different indexing. We imagine that it is more likely

that samples will be verified across any number of sites or intervals such that y and v share

consistent indexing: the only critical constraint is that specific samples cannot be included within

the likelihoods for both v and y. We also envision that most verification efforts will primarily

focus on intervals with > 0 observations (either true or false positive). That is, investigators may

never effectively evaluate sampling intervals with no detections (where $v_{i,j} = 4$), but Ω_4 must

remain within the likelihood for v because confirmed data share parameters with non-confirmed

data where nondetections are possible and may constitute the majority of outcomes.

Two further alterations make the sample verification model easier to generalize across

other model structures. First, we define s_1 as a derived parameter reflecting a combination of

state and observation processes that describe the *unconditional* probability of true detection

(Royle and Dorazio 2008), which will consequently vary (at least) across locations i. For an

occupancy model, $s_{1,i} = z_i \times p$, where p is the *conditional* probability of truly detecting a present

species (MacKenzie et al. 2002). As before, $\mathbf{\Omega_i} = [\{(s_{1,i} \times (1 - s_0)\} \{s_0 \times (1 - s_{1,i})\} \{ s_{1,i} \times s_0\} \{(1$

$- s_{1,i}) \times (1 - s_0)\}]$ and $v_{i,j} \sim$ Categorical ($\mathbf{\Omega_i}$). The difference is that $s_{1,i}$ here is derived from a

function of other parameters, and in the original treatment it is equivalent to the p of MacKenzie

et al. (2002). Secondly, we do not derive conditional parameters p_{11} and p_{10}, but instead consider

$y_{i,j} \sim$ Bernoulli ($1 - \Omega_{4,i}$): the species is detected truly, falsely, or both, or is not detected. The

hierarchical likelihood is then

88               $$z_i \sim \text{Bernoulli } (\psi)$$

89               $$s_{1,i} = z_i \times p$$

$$90 \qquad \mathbf{\Omega}_i = [\{(s_{1,i} \times (1 - s_0)\} \{s_0 \times (1 - s_{1,i})\} \{ s_{1,i} \times s_0\} \{(1 - s_{1,i}) \times (1 - s_0)\}]$$

$$91 \qquad v_{i,j} \sim \text{Categorical } (\mathbf{\Omega}_i)$$

$$92 \qquad y_{i,j} \sim \text{Bernoulli } (1 - \Omega_{4,i})$$

We emphasize that this is primarily a reorganization of derived parameters within Chambert et

al.'s (2015) model and the different parameterizations produce almost exactly the same results

(Figure S1). The sole difference in the likelihood is that the original description treats $y_{i,j} = 1$ as

constituting either a true or false positive detection, whereas here $y_{i,j} = 1$ may also reflect a

mixture of true and false observations (Figure 1). Conditioning $\mathbf{\Omega}$ upon the underlying state is

straightforward for models with two states, but burdensome for models with many possible states

or if the range of states has unknown dimension (i.e., population size). The general structure of

our reformulation instead conditions $s_{1,i}$ upon the underlying ecological state, and allows

extension to several models dependent on binary data simply by redefining $s_{1,i}$ as equivalent to

the applicable unconditional probability of (true) detection.

We use three models as examples. First, consider an occupancy model designed to

estimate the timing of some ephemeral phenomena such as migration arrival following Roth et

al. (2014). The model is exactly the same as presented above, except that organisms can only be

truly detected during sampling intervals after they have arrived and occupied sites. Let arrival

time at site i be denoted as x_i and assume that $x_i \sim \text{Poisson } (\varphi)$. To simplify presentation, we

define x_i in terms of sampling intervals j rather than specific dates. A hierarchical description is:

$$109 \qquad z_i \sim \text{Bernoulli}(\psi)$$

$$110 \qquad x_i \sim \text{Poisson } (\varphi)$$

$$s_{1,i,j} = z_i \times p \times I(j > x_i)$$

$$\mathbf{\Omega_{i,j}} = [\{(s_{1,i,j} \times (1 - s_0)\} \{s_0 \times (1 - s_{1,i,j})\} \{ s_{1,i,j} \times s_0\} \{(1 - s_{1,i,j}) \times (1 - s_0)\}]$$

The likelihoods for confirmed and unconfirmed observations are then $v_{i,j} \sim$ Categorical ($\mathbf{\Omega_{i,j}}$) and

$y_{i,j} \sim$ Bernoulli ($1 - \Omega_{4,i,j}$).

In the model presented by Royle and Nichols (2003), the unconditional probability of

detection $s_{1,i} = 1 - (1 - r)^{N_i}$, where r is the probability of detecting an individual during a

sampling interval, while $N_i \sim$ Poisson (λ) and denotes the abundance of a species at site i. The

false positive extension can be described hierarchically as:

$$N_i \sim \text{Poisson } (\lambda)$$

$$s_{1,i} = 1 - (1 - r)^{N_i}$$

$$\mathbf{\Omega_i} = [\{(s_{1,i} \times (1 - s_0)\} \{s_0 \times (1 - s_{1,i})\} \{ s_{1,i} \times s_0\} \{(1 - s_{1,i}) \times (1 - s_0)\}]$$

The statements for $v_{i,j}$ and $y_{i,j}$ follow the occupancy description.

As a final example, the spatially explicit variant of Royle and Nichols' (2003) model

(Ramsey et al. 2015) uses z_i to denote whether individuals $i = 1,2…M$ exist within a geographic

space $\|S\|$ with probability ψ. The state variable of interest, population size N in $\|S\|$ is estimated

as $\hat{N} = \sum_{i=1}^{M} z_i$, and population density is derived as $\hat{N}/Area_{\|S\|}$. Individuals have distinct activity

centers located within $\|S\|$ and the coordinates of these activity centers are denoted as s_i;

individuals are detected at any of j detectors on given sampling occasions k with probability $p_{i,j.}$

The unconditional probability of detection is a function of whether an individual exists, the

distance between an individual's latent activity center and the location of the detector, $d_{i,j}$, and

the parameters g_0 and σ that respectively relate to the probability of individual detection at $d_{i,j} = 0$

and the rate at which individual encounter probability decays. Individuals are not distinguished,

so these parameters are inferred by marginalizing across the latent individual encounter histories

at a specific detector such that the unconditional probability of detection $s_{1,j} = 1 - \prod_{i=1}^{M}(1 - p_{i,j})$.

$$z_i \sim \text{Bernoulli}(\psi)$$

$$p_{i,j} = g_0(-d_{i,j}/2\sigma^2) \times z_i$$

$$s_{1,j} = 1 - \prod_{i=1}^{M}(1 - p_{i,j})$$

$$\boldsymbol{\Omega_j} = [\{(s_{1,j} \times (1 - s_0)\} \{s_0 \times (1 - s_{1,j})\} \{s_{1,j} \times s_0\} \{(1 - s_{1,j}) \times (1 - s_0)\}]$$

139 Here, $v_{j,k} \sim$ Categorical $(\boldsymbol{\Omega_j})$ and $y_{j,k} \sim$ Bernoulli $(1 - \Omega_{4,j})$.

Simulation Study

141 We use simulation to demonstrate both that false-positive error influences estimates of arrival

142 time, relative abundance, and density, and that extensions to account for false positive error

143 provide better performance.

Royle-Nichols Model

We considered 8 different simulation scenarios of interest while holding simulated sampling

parameters constant: 200 sites, with 20 temporal replications each. For each scenario (Table 1)

we generated 300 replicate datasets with site-specific abundances $N_{i,sim} \sim$ Poisson $(\lambda_{i,\,sim})$ and log

$(\lambda_{i,sim}) = \beta_0 + \beta_1 X_{1,i,sim}$, where $X_{1,i,sim} \sim N(0, 1)$, $\beta_0 = 0$, and $\beta_1 = 0$ or 1. True detection data $y_{i,j,sim}$

was generated as Bernoulli $(p_{i,sim})$, where $p_{i,sim} = 1 - (1 - r_{i,sim})^{N_{i,sim}}$, logit $(r_{i,sim}) = \alpha_0 + \alpha_1 X_{2,i,sim}$,

$X_{2,i,sim} \sim N(0, 1)$, $\alpha_0 = -1.73$, and $\alpha_1 = 0$ or 1.

For each simulated encounter history, we generated false-positive detections as occurring

at random across all cells within a simulation. The probability of a false-positive detection within

a cell was derived such that the number of false-positive detections was 5 or 10% of the number

of true detections (with Binomial variance). These rates of false positive error are common

across a variety of sampling situations (Simons et al. 2007, McClintock et al. 2010, Norouzzadeh

et al. 2018) and have also been used as threshold definitions for accurate data (McShea et al.

2016, Swanson et al. 2016). Ten percent of positive detections were sampled to create the

verified data $v_{i,j,sim}$ (across simulation replicates and scenarios, $\bar{x} = 74.95$ verified detections, s =

15.22). Each of the 2400 generated datasets was used to fit both a standard Royle-Nichols model

and our false-positive extension. We evaluated the performance of both estimators by calculating

the mean error associated with the posterior mean of $\boldsymbol{\beta}$ and $\boldsymbol{\alpha}$, the relative bias of finite sample

population size point estimates ($\hat{N}^*$, derived as the posterior mode of $\sum_{i=1}^{R} \hat{N}_i$), and the frequentist

coverage of 95% CRI.

Phenology Model

Our subsequent simulation investigations were less thorough. To evaluate the sensitivity of the

Roth et al. (2014) model for arrival we considered a single scenario with 200 sites and 20

sampling occasions (each treated as analogous to a 10-day sampling period). Parameterization of

the simulated data was as follows: logit ($\psi_{i,sim}$) = $\beta_0 + \beta_1 X_{1,i,sim}$, $X_{1,i,sim} \sim$ N (0, 1), $\beta_0 = 0$, and $\beta_1 =$

0.5; logit ($p_{i,sim}$) = $\alpha_0 + \alpha_1 X_{2,i,sim}$, $X_{2,i,sim} \sim$ N (0, 1), $\alpha_0 = -2$, and $\alpha_1 = 0.5$; average arrival time φ

was simulated as day 60. True observations $y_{i,j,sim}$ were generated as Bernoulli ($z_{i,sim} \times p_{i,sim} \times$

I($a_{i,j,sim}$)), where $z_{i,sim} \sim$ Bernoulli ($\psi_{i,sim}$), and I($a_{i,j,sim}$) is an indicator function associated with

whether survey j falls after the site and simulation specific arrival time $a_{i,j,sim}$ itself is generated

as Poisson (φ_{sim}). We simulated 300 replicate dataset, with false positive detections and a 10%

verification sample v created as before (summarizing the size of the verification sample across

replicates, $\bar{x} = 20.57$, s = 4.57).

We evaluated 5 scenarios using the simulated data. We fit a standard arrival model

treating φ_{sim} as constant (1), a standard arrival model treating $\varphi_{i,sim}$ as a site-specific random

effect distributed as N ($\mu_{\varphi,sim}$, $\sigma_{\varphi,sim}$) (2). We fit the second model because we have observed that

sometimes random effects are operationally assumed to account for observation error. For

scenario 3 we fit an arrival model incorporating false positives and treating φ_{sim} as constant.

Scenario 4 also incorporated false positives and treated φ_{sim} as constant; here, we altered the

verification sample to constitute 20% of detections within the first 10 sampling intervals ($\bar{x} =$

26.79 verified samples, s = 5.34). As a fifth scenario, we used the extended model, and increased

the size of the verification sample to 20% across all time periods ($\bar{x} = 40.82$ verified samples, s =

7.22). We evaluated models on the basis of the relative bias and frequentist coverage of $\hat{\varphi}$ and

finite sample estimate of the proportion of occupied sites ($\widehat{PAO}$, derived for each simulation as

$\sum_{i=1}^{R} \hat{z}_i$), and the mean error and coverage associated with estimates of coefficients for

occurrence.

Spatial Royle-Nichols Model

Because the spatially-explicit extension of the Royle-Nichols model is computationally intensive

and typically used only to estimate one state variable of ecological interest (population size $\hat{N}$),

we simulated only 100 replicates within a single scenario to demonstrate proof of concept. Fixed

sampling parameters included a population size of 50 organisms; $\|S\|$ defined as a 20 × 20 unit

square; detection parameters $g_0 = 0.15$ and $\sigma = 0.5$; 196 detector locations within a 14 × 14

square grid with 1 unit spacing, and 20 sampling intervals: only the location of individual

activity centers varied across simulation replicates. False positive observations and a verification

sample were generated as before, although the lower number of simulated detections also

resulted in a much smaller verification sample ($\bar{x}$ = 12.56 verified samples, s = 3.30). We

compared the standard model and the false positive extension on the basis of relative bias and

frequentist coverage of $\hat{N}$.

Evaluating transferability of s_0

A potentially appealing property of generalizing the model as here is that the verification

outcomes that primarily contribute to the estimation of s_0 and its underlying generating process

are likely to be consistent regardless of how the unconditional probability of true detection is

formulated. This suggests that if data or computational resources are lacking, one might be able

to use an informative prior for s_0 given previous estimates of the parameter from a distinct (and

more quickly fit) model. To briefly explore transferability, we fit standard occupancy models to

the simulated data previously used to fit Royle-Nichols models, compared the congruency of s_0

estimates across model types, and refit an extended Royle-Nichols model to the simulated data

using an informed prior distribution for s_0 derived from the posterior distribution of the

occupancy estimator.

We fit models using JAGS (Plummer 2003) or Nimble (the spatial model, deAlpine et al.

2017) to perform Markov-Chain Monte Carlo simulation through R v 3.4 (R Core Team 2017).

Simulation settings are detailed further within Appendix SI2.

Results

Across all model types, estimators incorporating false positive error performed better than

standard implementations. The Royle-Nichols model exhibited positive-bias and permissive

coverage of finite-sample population size (relative bias ≥ 0.20, coverage ≤ 0.22) and the

abundance intercept parameter (mean error ≤ -0.16, coverage ≤ 0.49) even with relatively low

(5%) rates of false positive error. Overall performance was worse when site-specific abundance

varied in relation to simulated covariates although associations were estimated more accurately

than baseline prevalence (Table 1). False positive extensions were nearly unbiased and had

approximately nominal coverage across all parameters or state parameters considered.

Similar results held for the other models considered. Regardless of whether expected

arrival time was estimated as fixed or randomly varying across sites, phenological occupancy

models ignoring false positive error were biased estimators of the time of arrival (relative bias =

-0.44) and finite-sample occupancy (relative bias = 0.16, Table 2) and exhibited permissive

coverage (0.07 for estimates of arrival date, and 0.20 for estimates of finite-sample occurrence).

False positive extensions were less biased and had more nominal coverage (Table 2). However,

results suggested trade-offs between verifying samples randomly across the survey duration or

placing more focus on verifying samples during earlier sampling times around the time of

arrival. Focusing verification efforts on earlier sampling times reduced bias and provided more

nominal coverage of arrival date than verifying samples across all time periods (relative bias and

coverage respectively 0.01 vs 0.04 and 0.96 vs. 0.85), but resulted in poorer estimation of finite-

sample occupancy (relative bias and coverage probability respectively 0.18 vs. –0.08 and 0.33

vs. 0.80). When the verified sample was random but larger (scenario 5), bias was negligible and

coverage approximately nominal for all parameters considered.

Spatially explicit estimators of population size were severely biased (relative bias = 0.82)

and exhibited poor coverage (0.48) when false positive rates were 10%. Extended models

exhibited better performance (relative bias = 0.24, coverage probability = 0.89). One particular

simulation appeared to produce non-identifiable data, as the posterior mode fell along the

boundary of our data augmentation prior even after refitting models with a more diffuse prior

(Figure 2): excluding this outlier, the relative bias for the standard and modified estimator was

0.80 and 0.21, respectively. In a few other simulation replicates, the upper boundary of the

augmentation prior may have truncated posterior density (and the 95% CRI): because of this, we

likely overestimate coverage probability slightly (particularly for the standard estimator, which

appeared more prone to this issue).

Estimates of s_0 derived from occupancy models were correlated with—but greater than—

estimates of s_0 derived from the Royle-Nichols model (Figure S5). Despite this discrepancy,

using an informative prior distribution for false positive error within the Royle-Nichols model

derived from an occupancy model's estimates of s_0 resulted in model performance that barely

differed from when verification data was directly evaluated within the likelihood (Table 1,

Figure S5.).

Discussion

Because repeated detection-nondetection data are relatively easily to collect, such data is

extensively applied for monitoring and modeling purposes. As ecologists increasingly focus

upon addressing broad-scale questions that require collecting or collating massive amounts of

data (e.g., Sorrano and Schimel 2014), ease of collection plays an important role in study design.

Modeling advancements are often dependent upon data availability and amount, and the

parameters that can be estimated using detection-nondetection data continues to grow. While

model complexity has grown in conjunction with increases in data amount, whether the data

collected and used to fit these models are clean enough to permit accurate estimation is a

continued limitation. Indeed, "big data" efforts often depend upon fast but potentially error-prone

data collection or processing methods such as algorithms or crowdsourcing (e.g., Swanson et al.

2016, Tabak et al. 2018). As the scale of inquiry grows – either the sample itself or predictive

space – so too does the amount of potential absolute bias and the implications of biased

estimation. Previous efforts have repeatedly shown that occupancy estimators are biased under

realistic rates of false positive error (e.g., Miller et al. 2011, Chambert et al. 2015). Results here

demonstrate that this bias is general to many estimators reliant upon repeated binary detection

data. Bias associated with population size or the timing of arrival may be more problematic

because these metrics both cover a wider range of potential values (bias can be more

pronounced), and because they are more widely used to justify management decisions (e.g.,

timing of actions, quotas, recovery metrics) than occurrence or distribution.

Models are potentially sensitive to numerous violations of assumptions, but relative to

more nuanced assumptions such as the form of a given parametric function, the assumption that

an error type like false positives does not exist is particularly easy to evaluate, and as shown

here, not prohibitively difficult to correct for. One cost of incorporating validated data to

explicitly model false positive detections is to induce additional uncertainty associated with extra

parameters and to require additional effort associated with verification. Results indicate that even

very small number of verification samples (n = 15 – 20) can substantively improve inference

even when false positives are scarce. The sample size of many of the simulated verification

samples presented here is probably smaller than most investigators would prefer, particularly

when fitting models with a great deal of intrinsic uncertainty given multiple latent variables, like

the spatial Royle-Nichols model or a phenological occupancy model. Regardless, the size of the

verified sample need not be prohibitively large to permit unbiased and reasonably precise

estimation. Results here and elsewhere (Clare et al. *in* review) suggest that when s_0 is constant,

the sample verification model is generally unbiased when ~50 samples have been verified.

Increasing the size of a verification sample beyond this may further result in reduced bias as

investigators gain more power to approximate any underlying variability in s_0, but otherwise

primarily increases estimator precision (Miller et al. 2015, Chambert et al. 2018).

A second cost of using false positive-extensions is that they require slightly more

computational overhead. There are several ways to limit this cost. If there is no modeled

temporal variation in true or false positive detections, verified sampling occasions could be

aggregated across sites and treated as $v_i \sim$ Multinomial (Ω_i, k_i). Our results suggest that s_0 may be

transferable enough across different model structures that investigators operating under stringent

computational constraints could estimate s_0 using a simpler model and subsequently use an

informed prior for more intensive analyses. The primary benefit of including verified data within

the model likelihood rather than using an informed prior is that the verified data provide direct

information about particular latent variables (e.g., z_i or N_i), but these are rarely of direct interest,

and using an informed prior shrinks the dimensionality of the model matrix and may provide

substantive increases in speed if the verification sample is large. Finally, the concepts here need

not be implemented using MCMC simulation within a Bayesian framework. We describe the

extensions hierarchically using a complete data likelihood because all models considered have

been described in this fashion, but if a model can be fit using faster means such by maximizing a

marginalized likelihood, so too can the extensions presented here.

Further extensions are possible and deserve more investigation. The degree to which false

positive errors degrade dynamic or integrated extensions of the static models considered here

(i.e., provide biased estimates of trends) is a subject of ongoing research, but previous work

demonstrating that false positives induce biased estimates of occupancy dynamics (McClintock

et al. 2010b) and that integrated models are sensitive to misspecifications associated with any

constituent data type (Zipkin et al. 2017) suggests that such extensions are likely to be similarly

sensitive. False positive error may not always happen at random as in our simulations, and a

natural way to deal with heterogeneity between sites or sampling intervals is via the use of

random effects or covariates—e.g., logit $(s_{0,i}) = \boldsymbol{\beta X}$, where the vector or matrix $\boldsymbol{X}$ captures

covariates associated with, for example, the occurrence of a similar looking species, or a metric

associated with classification confidence. Additionally, sampling intervals may contain several

distinct observations that are classified separately (e.g., recordings, images) but aggregated

across a sampling interval for an analysis. In some cases, it may be easier to verify discrete

observations rather than verify complete sets of observations within defined sampling intervals,

and a larger number of observations within a sample suggests a greater probability that at least

one observation is true (Chambert et al. 2015, 2018). One way to deal with this is to model a

positive outcome within a sampling interval as arising from either > 0 true observations or all

misclassified observations, where the probability that all observations are misclassified within a

sampling interval $s_{0,i,j} = (1 - r_0)^{n_{i,j}}$, $n_{i,j}$ is the number of recorded observations within interval j at

site i, and r_0 is the probability that a single observation is false positive (Chambert et al. 2015,

Appendix SI3).

The sampling designs associated with verification effort may also deserve more attention.

Here, a verification sample targeting earlier sampling intervals where simulated false positives

were more prevalent than true positives permitted unbiased estimation of arrival time, but not

overall occurrence, while a random verification sample across all sampling intervals provided

better performance. For models in which observation is conditional upon multiple independent

latent variables (e.g., arrival time and occurrence), different verification schemes may provide

more information about one parameter than another. Detections verified as true during earlier

sampling periods provided more information about arrival time than detections verified at

random, but focusing a verification effort upon earlier sampling periods appears to have biased

the verification sample towards false positive detections prior to species arrival relative to true

detections. In turn, this appears to have negatively biased estimates of the true probability of

detection and led to a similar positive bias in the number of occupied sites as exhibited by

models ignoring false positives. More generally, targeting the verification sample towards

suspected false positives may require explicitly accounting for sampling bias within the

verification effort.

Recent studies focusing on species distribution or demographic parameters generally

acknowledge the existence of imperfect detection and use models that explicitly account for it.

Explicitly accounting for imperfect detection while assuming no false positive error makes many

of these models extremely sensitive to misclassification. As demonstrated here, accounting for

false positives is both surmountable and important for making rigorous ecological inference

across a broader class of models than previously recognized.

Acknowledgments

Support for this research was provided by NASA ESSF NNX16AO61H to JC and NASA

Ecological Forecasting grant NNX14AC36G to PT and BZ.

References

Chambert, T., D.A.W. Miller, and J. D. Nichols. 2015. Modeling false positive detections in

species occurrence data under different study designs. Ecology 96:332-339.

Chambert, T., J. H. Waddle, D.A.W. Miller, S. C. Walls, and J. D. Nichols. 2018. A new

framework for analyzing automated acoustic species-detection data: occupancy

estimation and optimization of recordings post-processing. Method ins Ecology and

Evolution 9:560-570.

de Valpine, P., D. Turek, C. Paciorek, C. Anderson-Bergman, D. T. Lang, and R. Bodik. 2017.

Programming with models: writing statistical algorithms for general model structures

with NIMBLE. Journal of Computational and Graphical Statistics 26:403-413.

MacKenzie, D. I., J. D. Nichols, G. B. Lachman, S. Droege, J. A. Royle, and C. A. Langtimm.

2002. Estimating site occupancy rates when detection probabilities are less than one.

Ecology 83:2248-2255.

McClintock, B. T., L. L. Bailey, K. H. Pollock, and T. R. Simons. 2010a. Experimental

investigation of observation error in anuran call surveys. Journal of Wildlife Management

74:1882-1893.

McClintock B.T., L.L. Bailey, K. H. Pollock, and T. R. Simons. 2010b. Unmodeled observation

error induces bias when inferring patterns and dynamics of species occurrence via aural

detections. Ecology 91: 2446–2454.

McShea, W. J., T. Forrester, R. Costello, Z. He, and R. Kays. 2016. Volunteer-run cameras as

distributed sensors for macrosystem mammal research. Landscape Ecology 31:55-66.

Miller, D. A., J. D. Nichols, B. T. McClintock, E. H. Campbell Grant, L. L. Bailey, and L. A.

Weir. 2011. Improving occupancy estimation when two types of observational error

occur: non-detection and species misidentification. Ecology 92: 1422-1428.

Miller, D.A.W., L. L. Bailey, E. H. C. Grant, B. T. McClintock, L. A. Weir, and T. R. Simons.

2015. Performance of species occurrence estimators when basic assumptions are not met:

a test using field data where true occupancy status is known. Methods in Ecology and

Evolution 6:557-565.

Norouzzadeh, M. S., A. Nguyen, M. Kosmala, A. Swanson, M. S. Palmer, C. Packer, and J.

Clune. 2018. Automatically identifying, counting, and describing wildlife animals in

camera-trap images with deep learning. Proceedings of the National Academy of

Sciences: 201719367.

Otis, D. L., K. P. Burnham, G. C. White, and D. R. Anderson. 1978. Statistical

inference from capture data on closed animal populations. Wildlife Monographs 62:3-

135.

Plummer, M. (2003). JAGS: a program for analysis of Bayesian graphical models using GIBBS

sampling. Proceedings of the 3[rd] international workshop on distributed statistical

computing.

Swanson, A., M. Kosmala, C. Lintott, and C. Packer. 2016. A generalized approach for

producing, quantifying, and validating citizen science data from wildlife images.

Conservation Biology 30:520-531.

R Core Team. 2017. R: a language and environment for statistical computing. R Foundation for

Statistical Computing, Vienna.

Ramsey, D. S. L., P. A. Caley, and A. Robley. 2015. Estimating population density from

presence-absence data using a spatially explicit model. Journal of Wildlife Management

79:491-499.

Roth, T., N. Strebel, and V. Amrhein. 2014. Estimating unbiased phenological trends by

adapting site-occupancy models. Ecology 95:2144-2154.

Royle, J.A., and R. D. Dorazio. 2008. Hierarchical modeling and inference in ecology. Academic

Press, London.

Royle, J. A., and J. D. Nichols. 2003. Estimating abundance from repeated presence-absence

data or point counts. Ecology 84:777-790.

Simons, T. R., M.W. Alldredge, K. H. Pollock, and J. M. Wettroth. 2007. Experimental analysis

of the auditory detection process on avian point counts. Auk 124:986-999.

Sorrano, P. A., and D. S. Schimel. 2014. Macrosystems ecology: big data, big ecology. Frontiers

in Ecology and the Environment 12:3-3.

Swanson, A., M. Kosmala, C. Lintott, and C. Packer. 2016. A generalized approach for

producing, quantifying, and validating citizen science data from wildlife images.

Conservation Biology 30:520-531.

Zipkin, E. F., S. Rossman, C. B. Yackulic, J. D. Wiens, J. T. Thorson, R. J. Davis, and E. H.

Campbell Grant. Integrating count and detection-nondetection data to model population

dynamics. Ecology 98:1640-1650.

Table 1. Simulation settings and model performance of the standard Royle-Nichols estimator and the false positive extension described herein either fit with verified data in the likelihood or using an informed prior. Dashes indicate value was not estimated.

Estimator	Scenario	True Values					Mean Error				Relative Bias	Coverage				
		β_0	β_1	α_0	α_1	FP	$\hat{\beta}_0$	$\hat{\beta}_1$	$\hat{\alpha}_0$	$\hat{\alpha}_1$	$\hat{N}^*$	$\hat{\beta}_0$	$\hat{\beta}_1$	$\hat{\alpha}_0$	$\hat{\alpha}_1$	$\hat{N}^*$
Standard	1	0	1	−1.73	1	0.1	0.71	−0.13	−0.57	−0.19	0.80	0	0.46	0.01	0.24	< 0.01
	2	0	0	−1.73	1	0.1	0.45	-	−0.38	−0.18	0.57	0.05	-	0.06	0.41	< 0.01
	3	0	1	−1.73	0	0.1	0.58	−0.11	−0.46	-	0.59	0	0.54	0.01	-	< 0.01
	4	0	0	−1.73	0	0.1	0.33	-	−0.27	-	0.37	0.11	-	0.14	-	0.01
	5	0	1	−1.73	1	0.05	0.43	−0.08	−0.36	−0.12	0.43	0.06	0.74	0.15	0.54	0.09
	6	0	0	−1.73	1	0.05	0.25	-	−0.21	−0.10	0.28	0.38	-	0.44	0.69	0.15
	7	0	1	−1.73	0	0.05	0.32	−0.06	−0.26	-	0.30	0.18	0.83	0.26	-	0.15
	8	0	0	−1.73	0	0.05	0.19	-	−0.16	-	0.20	0.49	-	0.54	-	0.22
False Positive Extension	1	0	1	−1.73	1	0.1	0.00	0.01	−0.01	0.01	< 0.01	0.95	0.92	0.94	0.95	0.94
	2	0	0	−1.73	1	0.1	−0.02	-	−0.11	0.01	−0.01	0.95	-	0.87	0.92	0.96
	3	0	1	−1.73	0	0.1	−0.02	0.02	−0.10	-	−0.02	0.96	0.95	0.91	-	0.95
	4	0	0	−1.73	0	0.1	−0.03	-	−0.08	-	−0.04	0.97	-	0.91	-	0.96
	5	0	1	−1.73	1	0.05	−0.02	< 0.01	<0.01	0.01	−0.02	0.97	0.94	0.96	0.94	0.97
	6	0	0	−1.73	1	0.05	−0.01	-	<0.01	< 0.01	−0.01	0.97	-	0.97	0.95	0.96
	7	0	1	−1.73	0	0.05	−0.01	0.01	<0.01	-	−0.01	0.94	0.96	0.93	-	0.95
	8	0	0	−1.73	0	0.05	0.00	-	<0.01	-	−0.01	0.95	-	0.91	-	0.93
	1[A]	0	1	−1.73	1	0.1	−0.06	0.03	<0.01	0.02	−0.03	0.95	0.92	0.95	0.94	0.95
	2[A]	0	0	−1.73	1	0.1	−0.04	-	−0.01	0.01	−0.03	0.96	-	0.98	0.92	0.97
	3[A]	0	1	−1.73	0	0.1	−0.06	0.02	0.02	-	−0.05	0.93	0.96	0.99	-	0.92
	4[A]	0	0	−1.73	0	0.1	−0.07	-	0.04	-	−0.07	0.90	-	0.98	-	0.87
	5[A]	0	1	−1.73	1	0.05	−0.04	0.01	0.01	0.01	−0.03	0.95	0.95	0.98	0.93	0.97
	6[A]	0	0	−1.73	1	0.05	−0.03	-	0.01	< 0.01	−0.03	0.97	-	0.99	0.95	0.95
	7[A]	0	1	−1.73	0	0.05	−0.07	0.02	0.04	-	−0.05	0.91	0.95	0.99	-	0.94
	8[A]	0	0	−1.73	0	0.05	−0.06	-	0.04	-	−0.06	0.94	-	0.98	-	0.92

[A]Model does not include verified data within the likelihood, but instead uses an informed prior for false positive error derived from posterior estimates of an occupancy model.

Table 2. Error, relative bias, and coverage of parameters associated with detection (α), occurrence (β), arrival time (φ), and the finite-sample proportion of occupied sites (PAO) for the 4 candidate phenological occupancy models described within the main text. The standard estimators (Models 1 and 2) overestimate overall occurrence, and underestimate arrival time and true detection probability. The modified estimators exhibit limited bias with respect to the timing of arrival, but also sub-optimally estimate overall occurrence. In particular, focusing the verification sample towards earlier time periods (Model 4) reduces the accuracy of occupancy estimation.

Model	Mean Error					Relative Bias	Coverage					
	β_0	β_1	α_0	α_1	φ	PAO	β_0	β_1	α_0	α_1	φ	PAO
1	0.35	0.03	–0.23	–0.05	–0.44	0.16	0.6	0.93	0.35	0.88	0.07	0.21
2	0.34	0.04	–0.23	–0.05	–0.44	0.16	0.61	0.93	0.36	0.87	0.07	0.21
3	–0.17	$>$ –0.01	0.17	–0.02	–0.04	-0.08	0.88	0.95	1	0.92	0.83	0.80
4	0.4	0.03	–0.04	–0.04	–0.01	0.17	0.58	0.96	0.93	0.91	0.96	0.39
5	$<$ 0.01	0.05	0.02	$<$ 0.01	0.01	$<$ 0.01	0.94	0.96	0.96	0.97	0.92	0.97

$S_{1,i}$ = *Unconditional* probability of (true) detection at a location during a given sampling interval = combination of state and observation processes
s_0 = Probability of false detection within a sampling interval
$\mathbf{\Omega_i}$ = [{$(s_{1,i} \times (1 - s_0))$} {$s_0 \times (1 - s_{1,i})$} { $s_{1,i} \times s_0$} {$(1 - s_{1,i}) \times (1 - s_0)$}]
$$v_{i,j} \sim \text{Categorical}(\mathbf{\Omega_{i,j}})$$
$$y_{i,j} \sim \text{Bernoulli}(1 - \Omega_{4,i,j})$$
$$\Pr(y_{i,j} = 0) = \Pr(v_{i,j} = 4)$$
$$\Pr(y_{i,j} = 1) = \Pr(v_{i,j} \neq 4)$$

Occupancy Model: $s_{1,i} = z_i \times p$
Royle-Nichols Model: $s_{1,i} = 1 - (1 - r)^{N_i}$
Spatial Royle-Nichols Model: $s_{1,j} = 1 - \prod_{i=1}^{N}(1 - g_0(-d_{i,j}/2\sigma^2) \times z_i$
Arrival Model: $s_{1,i,j} = z_i \times p \times I(j > x_i)$

Figure 1. Schematic for the generalizable sample-verification model for false positive error presented here. Unconfirmed outcomes are positive if the species has either been truly or falsely detected, or negative if neither true nor false detection has occurred. Confirmed data can either result in a true detection only, a false detection only, both, or no detection. The probability of > 0 false detections within a verified sampling interval is denoted s_0, while the probability of > 0 true detections, $s_{1,i}$, is treated as a combination of functions associated with state and conditional observation models.

Figure 2. Simulation-specific point estimates and 95% CRI from the standard spatial Royle-Nichols model (A), an extension to account for false-positives (B), and the overall distribution of point estimates (C). Dashed lines denote true values. In A, B, and C, one point estimate falls right at the boundary, potentially indicating a non-identifiable dataset; other simulated replicates exhibit nonnegligible posterior density along the boundary such that the upper CRI abuts it. This is more common for the standard estimator, and one additional consequence of ignoring false positive error may be added computational cost associated with using a larger data augmentation prior for *N*.

Supporting Information S1.

Figure S1. Point estimates (based upon the mode [top left] or mean of the posterior distribution) from Chambert et al.'s 2015 description of the sample verification model and our reformulation of the model are essentially equivalent: red dots indicate point estimates from specific simulate replicates, black dashed line is 1:1, blue line is fitted linear association. These estimates are derived from 18 simulation scenarios described in Clare et al. *in review*.

Figure S2. Abundance estimation using the Royle-Nichols model is biased under low to moderate rates of false positive error, particularly when abundance is modeled as spatially varying (A); in all scenarios, the false positive extension presented herein is nearly unbiased (B).

Figure S3. Root squared error (A) and bias (B) associated with the extended Royle-Nichols estimator exhibit little association with the size of the verification sample within the range considered: when false positive error is constant, gains in estimator precision may require much larger increases in sample size than considered here.

Figure S4. Point estimates from the extended spatial Royle-Nichols model (blue) exhibit sensitivity to the size of the verification sample and the empirical proportion of false positives within it appear more pronounced than for the non-spatial Royle-Nichols, likely because the simulated verification sample was very small. Regardless, the extended model exhibits better performance than the standard model (red, jittered).

Figure S5. Associations between false positive probabilities estimated using the Royle-Nichols and occupancy estimator suggests that the occupancy estimator tends to produce slightly larger estimates of s_0 (A). However, estimates of population size using an informed prior derived from occupancy-based estimates are practically equivalent to estimates of population size when confirmed data is included within the likelihood (B), and both appear nearly unbiased (C, D).