GRID-seq assisted prediction of transcription factor binding motifs

Werner Pieter Veldsman[1*]

1. School of Life Sciences, The Chinese University of Hong Kong, Shatin, New Territories, Hong Kong, China.

* To whom correspondence should be addressed.

Email: veldsman@link.cuhk.edu.hk

Abstract

Experimental validation of computationally predicted transcription factor binding motifs is desirable. Increased RNA levels in the vicinity of predicted protein-chromosomal binding motifs intuitively suggest regulatory activity. With this intuition in mind, the approach presented here juxtaposes publicly available experimentally derived GRID-seq data with binding motif predictions computationally determined by deep learning models. The aim is to demonstrate the feasibility of using RNA-sequencing data to improve binding motif prediction accuracy. Publicly available GRID-seq scores and computed DeepBind scores could be aggregated by chromosomal region and anomalies within the aggregated data could be detected using mahalanobis distance analysis. A mantel's test of matrices containing pairwise hamming distances showed significant differences between 1) randomly ranked sequences, 2) sequences ranked by non-GRID-seq assisted scores, and 3) sequences ranked by GRID-seq assisted scores. Plots of mahalanobis ranked binding motifs revealed an inversely proportional relationship between GRID-seq scores and DeepBind scores. Data points with high DeepBind scores but low GRID-seq scores had no DNAse hypersensitivity clusters annotated to their respective sequences. However, DNase hypersensitivity was observed for

high scoring DeepBind motifs with moderate GRID-seq scores. Binding motifs of interest were

recognized by their deviance from the inversely proportional tendency, and the underlying

context sequences of these predicted motifs were on occasion associated with DNAse

hypersensitivity unlike the most highly ranked motif scores when DeepBind was used in

isolation. This article presents a novel combinatory approach to predict functional protein-

chromosomal binding motifs. The two underlying methods are based on recent developments

in the fields of RNA sequencing and deep learning, respectively. They are shown to be suited

for synergistic use, which broadens the scope of their respective applications.

Introduction

To consider the effect that the presence of an increased concentration of RNA in the

vicinity of a promoter may have on a protein binding to a promoter, an approach that

combines an estimate of RNA affinity and transcription factor (TF) affinity for the same given

sequence is required. Two recent papers have each presented a new approach that have the

potential to be applied towards this goal in combination. Firstly, there is the global RNA

interactions with DNA by deep sequencing (GRID-seq) approach(1), which allows a user to

quantify genome wide binding of RNA to chromatin in a manner that results in data similar to

what might be obtained from model-based analysis of ChIP-Seq (MACS)(2). In other words, a

BED file is generated that contains chromosomal regions of an arbitrary length of 1000

nucleotides, annotated with a score that indicates the extent to which RNAs bind to a given

sequence. The second approach, called DeepBind(3), uses a deep learning approach to

discover TF binding motifs in a given sequence. The models with which DeepBind's binding

motif predictions are made were trained using either ChIP-seq, SELEX or RNA-binding protein

(RBP) experiments. This is a defining characteristic of DeepBind that diversifies the

provenance of the data that its models are derived from.

Although DeepBind and GRID-seq are new experimental techniques, the principals on

which they are based have already been validated by a significant amount of research. As an

example, the DeepBind method employs a specific type of deep learning neural network

called a convolution neural networks (CNNs). CNNs have been used to predict RNA secondary

structure(4) and impute DNA methylation(5) to name but a few. GRID-seq for its part has the

major advantage over previous methods in that it can be used to detect nascent RNA-

chromatin interaction on a genome wide scale. Analyzing nascent RNA is preferable over

analyzing total cellular RNA since it is believe to be a less biased approach that provides the

researchers with better resolution over cellular variables such as RNA stability and

transcription rate(6).

The aim of combining DeepBind and GRID-seq is to derive results that may assist

researchers in study target selection. The desired outcome is achieved by simultaneously

considering the influence that scores from of each of the respective methods (GRID-seq and

DeepBind) has as a single distance function based on the distribution of their scores, and then

ranking sequences that contain predicted binding motifs according to this new combined

score. The intention is to predict protein-chromatin binding motifs with an indication as to

whether the predicted motifs might be bound by proteins in an environment with heightened

levels of RNA, which could in turn indicate whether the binding motif is functional.

Results

Mahalanobis distance analysis reveals candidate binding motifs as outliers

GRID-seq scores in the top 60 mahalanobis ranking had a minimum value of 8.47 as compared to a minimum value of 2.03 in the entire GRID-seq score population. Similarly, DeepBind scores in the top 60 mahalanobis ranking had a minimum of -0.26 as compared to a minimum value of -1.97 in the entire DeepBind score population. Maximum values for GRID-seq and DeepBind scores were 905.06 and 6.77 in the mahalanobis subsets. Maximas in the subsets were identical to those in the entire populations. The minima and maxima properties therefore indicated that the top 1% mahalanobis ranked scores were qualitatively representative of their respective populations. Plotting the top 1% mahalanobis ranked scores by their constituent GRID-seq and DeepBind scores illustrated how mahalanobis ranking can be applied to increase the resolution of realistic candidate binding motifs (Fig 1)

Fig 1: Mahalanobis ranked binding motifs Two predicted binding motif scores in the green cluster, directly above and outside the confidence ellipse, are noticeably separated from both high DeepBind scores (blue cluster) and high GRID-seq scores (orange and yellow clusters). These two data points are separated from other high DeepBind scores in the blue cluster because moderate levels of RNA have been detected in the vicinity of their associated binding motifs.

RNA levels are associated with significantly dissimilar sequence ranking

A statistical test to determine whether the order of DNA sequences (and therefore the

order of predicted motifs) were significantly affected by choice of scoring method, revealed

that Mahalanobis ranked sequences were significantly different to DeepBind ranked

sequences (p=0.45). Mahalanobis ranked sequences were also significantly different to

randomly ranked sequences (p=0.75) and DeepBind ranked sequences were significantly

different to randomly ranked sequences (p=0.80). These results statistically confirm that the

ranking of DNA sequences (that contain predicted binding motifs) are significantly changed

by the choice of scoring method. The results are as expected; however, it validates the motif

prediction power of DeepBind for this specific case in that the sequences that are

hypothesized to contain binding motifs are statistically proven to be compositionally different

to random sequences. In addition, the lower p-value with which DeepBind-ranked and

Mahalanobis-ranked sequences were deemed to be statistically different from each other

suggests that the underlying sequence composition that leads to the prediction of a binding

motif is not disproportionally affected by either GRID-seq data or DeepBind data. If it had

been disproportionally affected, the p-value would have either shown an insignificant

difference (p < 0.05) or would have been similar to the p-values obtained by tests on randomly

ranked sequences.

GRID-seq and DeepBind scores have an inversely proportional property

A comparison of GRID-seq assisted transcription factor motif prediction scores for

model types against different sequence sets show that clustering of high DeepBind scores and

GRID-seq scores are dependent on the strength of the respective scores (Fig 2). From these

nine graphs, it seems in six out of the nine cases that the higher the average DeepBind scores

are, the higher the average GRID-seq scores are. However, when looking at the individual data

points, it becomes apparent that there is a tendency that the higher an individual GRID-seq

score is, the lower its accompanying DeepBind score is. In other words, an inversely

proportional relationship between GRID-seq scores and DeepBind scores seems to become

more pronounced as their respective values increase.

Fig 2: Permuted test of robustness using three models and three transcription factors GRID-

seq data plotted against DeepBind data for three transcription factors and three models

derived from different source data. There seems to be a general trend that the higher a

DeepBind score is, the lower the level of RNAs are in the vicinity of the motif predicted by

DeepBind. However, it is the outliers that deviate from this pattern that are of interest due to

their higher potential to represent functional binding motifs.

Discussion

Discovering transcription factor binding motifs *in silico* requires follow up work to

establish whether binding takes place *in situ*. This is the case because not all potential binding

sites are bound by transcription factors in the cellular environment. These motifs that are

compositionally valid but never bound are the false positives of computational motif

prediction. It has been suggested as early as 2002 that expression data can be used to validate

functional binding motifs(7). Employing GRID-seq data would therefore be a realization of

using such an approach. Many software solutions have already been developed for

computational prediction of binding motifs. A 2006 paper by Tompa *et al.* evaluated the

performance of thirteen of these tools(8). In Tompa's discussion, emphasize is placed on using

complementary tools for motif prediction and to investigate a "top few" predicted motifs

instead of just the most significantly predicted motif.

But the question as to how RNA levels may contribute to confirming a binding motif's

functional role has multiple answers. A protein's function can be changed when bound by

RNA. As a result, a transcription factor bound by RNA may promote, inhibit or completely

uplift transcription. Transcription factors (TFs) have the ability to bind to RNA as well as to

DNA. Binding of RNA to a nuclear protein can override the protein's localization signal, leading

to its export from the nucleus(9). It has also been shown that a well-known TF, p53, has two

distinct nucleotide binding domains: one with high specificity for motifs in the promoter

region of genes targeted by p53, and another domain that exhibits non-specific binding to,

amongst others, single stranded nucleotide sequences. TFIIIa is an example of a typical zinc-

fingered TF that binds both DNA and RNA(10). Given then that RNA has been demonstrated

to have the ability to interfere with the localization signal of a protein and to have the ability

to bind to transcriptional initiation factors in a non-specific manner, it is reasonable to assume

that there exists a large set of RNAs in the nucleus that can directly affect gene expression

that is in turn under the control of a TF. More specifically, the binding of a transcription factor

to a promoter region could therefore be under the regulation of an unknown number of RNAs.

And since the binding may be non-specific, it follows that if the concentration of RNA in the

vicinity of a promoter is high, there must be a higher probability that the binding of the TF

could be regulated. If not by the possibility that the given TF has non-specific RNA binding

affinity, or that increased RNA levels indicate 3d proximity of some sequentially distant

enhancer/repressor, then at least by the increased likelihood of physical obstruction arising

from the quantity of RNA molecules in the vicinity of the promoter. This rationale forms the

basis of the method that is presented in this paper. In this sense, the method purposed here

does not draw specific conclusions about the nature of the association between RNA and

predicted protein binding motifs but acts as a mechanism by which candidate binding motifs

can be selected for further study.

When switching around cause and effect, the proximity of RNA to a predicted binding

motif could instead be taken as an indication that transcription is taking place due to

regulatory activation of a downstream gene. In that case, the flow of information as described

by the central dogma(11) suggests that it is the presence rather than the mechanism of action

of RNA that gives a clue as to whether a binding motif is functional. The inverse proportional

relationship of GRID-seq scores and DeepBind scores that becomes apparent when viewing

Fig 2 seems to indicate that the more likely it is that a given sequence contains a binding motif,

the less RNA are bound to the chromatin in its vicinity. This does not support or reject the

central dogma notion of confirming binding motif validity by the presence of RNA, because

although most of the motifs predicted with high significance exhibit the inversely proportional

relationship, a few high significance motifs do not. It does however allow for a novel

categorization of the "top few" significant motifs – i.e. those that are associated with

heightened levels of RNA and those that are not.

The contribution that GRID-seq data can make when assessing the functionality of a

predicted binding motif becomes apparent in Table 1. This table lists the top 5 predicted

motifs ranked by their DeepBind scores (blue cluster on Fig 1), the top 5 ranked by their GRID-

seq scores (yellow cluster on Fig 1), and five other predicted motifs (green cluster on Fig 1)

that are discernable on Fig 1 as being separated from both the DeepBind and Grid-seq clusters.

What the table shows is that even though DeepBind might predict certain motifs with high

significance, when the DNAse I activity of these top 5 sequences ranked by DeepBind score is

examined, there appears to be no DNAse I cluster annotated to them (when viewed using the

UCSC Genome browser(12)). The DNAse cluster column in Table 1 is a binary field that either

confirm that cluster boxes have been observed when viewing the genomic regions in the UCSC

Genome browser or that cluster boxes have not been observed. DNAse hypersensitivity

typically indicates that chromatin is in an accessible state and has been extensively used to

identify regulatory elements including promoters(13).

Table 1: DNAse hypersensitivity characteristics of sequences containing predicted motifs							
	GRID-seq score	DeepBind score	Mahalanobis distance	Chromosome	Start	Stop	DNAse clusters
GRID-seq	905.056	1.338331	47.59	chr7	101994000	101995000	No
	890.99	1.038863	46.24	chr7	101993000	101994000	No
	886.461	1.186810	45.61	chr7	101991000	101992000	Yes
	871.941	1.448033	43.90	chr7	101992000	101993000	No
	861.87	1.423735	42.82	chr7	101990000	101991000	Yes
DeepBind	26.255	6.457482	27.66	chr7	100805000	100806000	No
	13.0953	6.356945	26.77	chr7	104937000	104938000	No
	17.6181	6.207847	25.23	chr7	103866000	103867000	No
	8.47069	6.174184	25.01	chr7	135598000	135599000	No
	10.5831	5.812598	21.56	chr7	93166000	93167000	No
Combined	583.454	4.531703	27.71	chr7	101816000	101817000	Yes
	570.183	3.386700	21.17	chr7	101891000	101892000	No
	552.997	3.548660	20.71	chr7	101815000	101816000	Yes
	549.316	6.183928	38.21	chr7	101940000	101941000	No
	374.84	6.767595	35.56	chr7	101927000	101928000	Yes

The above table has three main sections that indicate clusters on Fig 1 with high

GRID-seq data points (yellow cluster of Fig 1), high DeepBind data points (blue

cluster on Fig 1), and high DeepBind data points having significant GRID-seq scores

(green cluster on Fig 1). The last column of the table indicates whether the

sequence associated with a score has been annotated with DNAse activity. It

becomes apparent that a cluster of significant DeepBind scores in isolation do not

serve as a good indicator of whether a given motif is functional (by virtue of being

annoted with DNAse activity). However, when RNA activity is taken into

consideration, DNAse activity is also observed to be annotated to some of the

respective sequences.

Increased RNA levels in the vicinity of accessible chromatin makes intuitive sense if

they are involved in regulating a functional binding motif or are transcribed in close proximity

to a functional binding motif. In other words, since increased RNA levels are expected to be

observed in the vicinity of a functioning gene (and by consequence it's promoter and TF

binding motifs), it could indicate that a given binding motif is more likely to be functional than

a binding motif in a region that does not show increased RNA levels. It should be noted that

if regulatory interfering RNAs were to be a significant constituent of an observed increased

level of RNAs in a given chromosomal region, the assumption about the reason for their

presence would be the opposite of the assumption for the cause of their presence under the

central dogma.

Conclusion

The approach presented here demonstrates that RNA-seq data can be used to

substantiate binding motifs predicted by computational methods. It is shown that predicted

binding motifs that have some RNA bound in their vicinity also on occasion have DNAse

hypersensitivity annotated to their contextual sequences. This characteristic stood in contrast

to the most highly ranked predicted binding motifs by computational prediction, which had

no hypersensitivity annotated to their contextual sequences. DNAse hypersensitivity is widely

accepted as indicative of transcriptional activity. The ability to distinguish between true

positive and false positive binding motifs is therefore improved by this approach. In addition,

this approach allows simultaneous consideration of both RNA-seq and DeepBind data using a

novel statistical application of the mahalanobis distance function, which in turn allows binding

motif candidates to be ranked based on the contribution of multiple variables. Future work

could focus on experimenting with the inclusion of additional variables that may further

improve the accuracy and specificity of predicted binding motifs.

Methods

Sourcing GRID-seq data, DeepBind models, and related sequences

Candidate transcription factors were found in GRID-seq supplementary data by

manually filtering gene names published by Li *et al.* (1) The criteria for selecting a gene name

from the GRID-seq data was that a DeepBind model matching a gene name was available at

http://tools.genes.toronto.edu/deepbind/ Multiple matches were found using this approach.

An arbitrary decision was made to select *CUX1* related data for the purposes of illustrating

the method discussed in this paper. The first step after confirming that both GRID-seq data

and a DeepBind model existed for a gene of interest, was to retrieve GRID-seq genomic

intervals and accompanying RNA-binding scores from http://fugenome.ucsd.edu/gridseq/

This data was found by matching the gene identifier to file names in the MM.1S dataset. GRID-

seq results for *CUX1* were extracted from file gridseq.MM1S.ENSG00000257923.bdg The

actual DNA sequences were downloaded by concatenating these ranges to an http get

request directed at http://togows.org/api/ucsc/hg38/

Predicting protein-chromatin binding motifs using a DeepBind model

The sequences obtained in the previous step each had a length of 1000 nucleotides.

These sequences had to be cut into 20 shorter sequences of length 50 to comply with

DeepBind specifications. DeepBind was downloaded from

http://tools.genes.toronto.edu/deepbind/ The shortened sequences and the CUX1 model

identifier (D00329.002) were passed as input to the DeepBind modeler. A file by the name

README.txt file is bundled with the DeepBind modeler and contains usage guidelines and

handy examples. To keep scoring regimes comparable, the maximum DeepBind score in each

bin of 20 subsequences were used as the matching DeepBind score for each of the GRID-seq

scores associated with a 1000 base pair genomic region.

Score integration and sequence ranking

GRID-seq and DeepBind scores per genomic interval were recoded into single

variables using the multivariate mahalanobis distance method of the R package

anomalyDetection(14). GRID-seq and DeepBind scores together with their respective means

and co-variances were passed to *anomalyDetection's* mahalanobis function whilst leaving all

other parameters at their default values. To improve on the resolution of data points, an

arbitrary decision was made to keep 1% of the highest ranking Mahalanobis scores (60 out of

6069) for further analysis. A hamming distance matrix was created from sequences associated

with the top 60 mahalanobis scores using the R package *DECIPHER*(15). Similar matrices were

created for the top 60 sequences ranked by DeepBind scores and 60 randomly selected

sequences. These three matrices were then tested for correlation in turn using a Mantel test

implementation bundled with the R package *ade4*(16) with the default permutation value of

ade4's mantel.rtest method changed to 10,000. The null hypothesis for each paired test of

the three matrices were that there is no relationship between any two given matrices at α =

0.05 Data parsing was carried out using the R packages *data.table*(17) and *reshape2*(18). In

all cases scores were visualized using the R package *ggplot2*(19), and where applicable,

gridExtra(20).

Test for robustness

In the main example discussed in this paper (Fig 1), CUX1 transcription factor binding

motifs were predicted using a DeepBind model that was trained on SELEX data. To test the

robustness of GRID-seq assisted protein-chromatin binding motif prediction as well as the

approach's tolerance to changes in DeepBind model architecture, two further transcription

factors were analyzed. They were TBL1XR1 and MTR3. DeepBind models for these two TF's

were constructed using ChIP-seq and RBP assay data, respectively. Scores derived using each

of the three DeepBind models were visually compared to each of the GRID-seq associated

DNA sequences. The results of these further tests are illustrated in Fig 2.

Acknowledgements

300   This project was funded by the Chinese University of Hong Kong.

References

1.   Li X, Zhou B, Chen L, Gou LT, Li H, Fu XD. GRID-seq reveals the global RNA-chromatin

interactome. Nat Biotechnol. 2017;35(10):940–50.

2.   Zhang Y, Liu T, Meyer CA, Eeckhoute J, Johnson DS, Bernstein BE, et al. Model-based

analysis of ChIP-Seq (MACS). Genome Biol. 2008;9(9).

3.   Alipanahi B, Delong A, Weirauch MT, Frey BJ. Predicting the sequence specificities of

DNA- and RNA-binding proteins by deep learning. Nat Biotechnol. 2015;33(8):831–8.

4.   Budach S, Marsico A. pysster: Classification Of Biological Sequences By Learning

Sequence And Structure Motifs With Convolutional Neural Networks. bioRxiv

[Internet]. 2018;230086. Available from:

https://www.biorxiv.org/content/early/2018/02/06/230086

5.   Angermueller C, Lee HJ, Reik W, Stegle O. DeepCpG: Accurate prediction of single-cell

DNA methylation states using deep learning. Genome Biol. 2017;18(1).

6.   Friedel CC, Dölken L. Metabolic tagging and purification of nascent RNA: Implications

317   for transcriptomics. Vol. 5, Molecular BioSystems. 2009. p. 1271–8.

318 7. Halfon MS, Grad Y, Church GM, Michelson AM. Computation-based discovery of

319   related transcriptional regulatory modules and motifs using a experimentally

320   validated combinatorial model. Genome Res. 2002;12(7):1019–28.

321 8. Tompa M, Li N, Bailey TL, Church GM, De Moor B, Eskin E, et al. Assessing

322   computational tools for the discovery of transcription factor binding sites. Vol. 23,

323   Nature Biotechnology. 2005. p. 137–44.

324 9. Cassiday LA. Having it both ways: transcription factors that bind DNA and RNA.

325   Nucleic Acids Res [Internet]. 2002;30(19):4118–26. Available from:

326   https://academic.oup.com/nar/article-lookup/doi/10.1093/nar/gkf512

327 10. Burd CG, Dreyfuss G. Conserved structures and diversity of functions of RNA-binding

328   proteins. Science (80-). 1994;265(5172):615–21.

329 11. Crick F. Central dogma of molecular biology. Nature. 1970;227(5258):561–3.

330 12. Karolchik D, Hinrichs AS, Kent WJ. The UCSC genome browser. Curr Protoc Hum

331   Genet. 2011;(SUPPL. 71).

332 13. Crawford GE, Holt IE, Whittle J, Webb BD, Tai D, Davis S, et al. Genome-wide mapping

333   of DNase hypersensitive sites using massively parallel signature sequencing (MPSS)

334   Genome-wide mapping of DNase hypersensitive sites using massively parallel

335   signature sequencing (MPSS). Genome Res. 2006;16:123–31.

336 14. Gutierrez RJ, Boehmke BC, Bauer KW, Saie CM, Bihl TJ. anomalyDetection:

337   Implementation of Augmented Network Log Anomaly Detection Procedures. R J.

338   2017;9(2):354–65.

339 15. Wright ES. Using DECIPHER v2.0 to Analyze Big Biological Sequence Data in R. R J.

340   2016;8(1):352–9.

16. Dray S, Dufour A-B. The ade4 Package: Implementing the Duality Diagram for

Ecologists. J Stat Softw [Internet]. 2007;22(4). Available from:

http://www.jstatsoft.org/v22/i04/

17. Dowle M, Short T, Lianoglou S, Srinivasan A. R: data.table [Internet]. CRAN. 2014.

Available from: http://cran.r-

project.org/web/packages/data.table/data.table.pdf%5Cnhttp://cran.r-

project.org/web/packages/data.table/vignettes/datatable-faq.pdf%5Cnhttp://cran.r-

project.org/web/packages/data.table/vignettes/datatable-intro.pdf

18. Wickham H. R: Package 'reshape2' [Internet]. CRAN. 2017. p. 14. Available from:

https://cran.r-project.org/web/packages/reshape2/reshape2.pdf

19. Wickham H. Ggplot2 : elegant graphics for data analysis. Springer; 2009. 212 p.

20. Auguie B. gridExtra: Miscellaneous functions for "grid" graphics. R package version

2.2. 1. Google Sch. 2016;