D-GPM: a deep learning method for gene promoter methylation inference

Xingxin Pan[a], Biao Liu[a], Xingzhao Wen[b], Yulu Liu[a], Xiuqing Zhang[a], Shengbin Li[c,d*],

Shuaicheng Li[e,*]

[a]BGI Education Center, University of Chinese Academy of Sciences, Shenzhen, China

[b]School of Biological Science and Medical Engineering, Southeast University, Nanjing,

China

[c]Forensic Genomics International (FGI), BGI-Shenzhen, Shenzhen, China

[d]Shenzhen Key Laboratory of Forensics, BGI-Shenzhen, Shenzhen, China

[e]Department of Computer Science, City University of Hong Kong, Kowloon, Hong Kong

E-mail addresses

Xingxin Pan: panxingxin16@mails.ucas.ac.cn; Biao Liu: liubiao2@genomics.cn; Xingzhao

Wen: wenxingzhao1227@gmail.com; Yulu Liu: liuyulu@genomics.cn; Xiuqing Zhang:

zhangxq@genomics.cn; Shengbin Li: silkroad@genomics.cn; Shuaicheng Li:

shuaicli@gmail.com.

Corresponding author

Department of Computer Science, City University of Hong Kong, Kowloon, Hong Kong

E-mail address: shuaicli@gmail.com

Abstract

Background: Gene promoter methylation plays a critical role in a wide range of biological processes, such as transcriptional expression, gene imprinting, X chromosome inactivation, *etc*. Whole-genome bisulfite sequencing generates a comprehensive profiling of the gene methylation levels but is limited by a high cost. Recent studies have partitioned the genes into landmark genes and target genes and suggested that the landmark gene expression levels capture adequate information to reconstruct the target gene expression levels. Moreover, the methylation level of the promoter is usually negatively correlated with its corresponding gene expression. This result inspired us to propose that the methylation level of the promoters might be adequate to reconstruct the promoter methylation level of target genes, which would eventually reduce the cost of promoter methylation profiling.

Results: Here, we developed a deep learning model (D-GPM) to predict the whole-genome promoter methylation level based on the methylation profile of the landmark genes. We benchmarked D-GPM against three machine learning methods, namely, linear regression (LR), regression tree (RT) and support vector machine (SVM), based on two criteria: the mean absolute deviation (MAE) and the Pearson correlation coefficient (PCC). After profiling the methylation beta value (MBV) dataset from the TCGA, with respect to MAE and PCC, we found that D-GPM outperforms LR by 9.59% and 4.34%, RT by 27.58% and 22.96% and SVM by 6.14% and 3.07% on average, respectively. For the number of better-predicted genes, D-GPM outperforms LR in 92.65% and 91.00%, RT in 95.66% and 98.25% and SVM in 85.49% and 81.56% of the target genes.

Conclusions: D-GPM acquires the least overall MAE and the highest overall PCC on

MBV-te compared to LR, RT, and SVM. For a genewise comparative analysis, D-GPM

outperforms LR, RT, and SVM in an overwhelming majority of the target genes, with respect

to the MAE and PCC. Most importantly, D-GPM predominates among the other models in

predicting a majority of the target genes according to the model distribution of the least MAE

and the highest PCC for the target genes.

Keywords: promoter methylation, deep neural network, machine learning, prediction method

1 Background

By influencing the transcription factor's accessibility to DNA, the methylation of the

promoter of a gene regulates various biological process [1]. Enzymatic digestion, affinity

enrichment, and bisulfite conversion are methods to capture the DNA methylation level [2].

Despite technological advances, there are still limitations in existing wet-lab methods. The

resolution of enzymatic digestion-based approach is restricted to regions adjacent to the

methylation-sensitive restriction enzyme recognition sites [3]. The resolution of methylated

DNA immunoprecipitation is limited to 100-300 base pair long fragments, and it is also

biased towards the hypermethylated regions[4]. Illumina's 450K bead-chip is the most widely

used method for profiling DNA methylation in humans, but the chip only probes

approximately 450K CpG sites in the human genome and covers partial CpG islands and may

be biased towards the CpG dense contexts [5]. Whole-genome bisulfite sequencing is a

golden standard protocol. However, it is too costly because the genome-wide deep

sequencing of bisulfite-treated fragments needs to generate a compendium of gene

methylation level over a large number of conditions, such as retrovirus, DNMT activity

changes and drug treatments [6]. The community awaits more feasible and more economical

solutions.

Previous research suggests that there is a low-rank structure in the genome-wide gene

expression profile [7], i.e., by leveraging the inner correlation between genes, the expression

level of a few well-chosen landmark genes captures sufficient detail to reconstruct the

expression of the rest of genes, namely, the target genes across the genome. The above result

was achieved by studying the gene regulation networks and conducting a principal

component analysis on the whole-genome expression profile [8]. Consequently, scientists

created a new technology called L1000, which only acquires the expression profiling of the

landmark genes (~1000) to infer the expression profiling of the target genes (~21000) [7].

Inspired by L1000, we proposed a method according to the following rationale to

acquire the whole-genome promoter methylation level according to the promoter

mythylations of the landmark genes. First, latent associations exist between the expression of

these landmark genes and the target genes at the genome-wide level [9]; second, the

methylation in the promoters located upstream of the transcription start site is usually

negatively correlated with their corresponding gene expression levels [10]. Hence, it is likely

that strong associations are present among the methylation levels in the landmark genes and

target genes.

To predict the methylation panorama on the whole genome is a large-scale multitask

machine learning problem, with a high-dimensional aim (~21,000) and a low-dimensional

attribute (~1,000). Meanwhile, the deep learning method has shown its power in integrating

large-scale data and capturing the nonlinear complexity of input features. In biology,

extensive applications include predictions for the splicing activity of individual exons,

inferring chromatin marks from the DNA sequence, and the quantification of the effect of

SNVs on chromatin accessibility [11-13].

Here, we present a multilayer deep neural network named Deep-Gene Promoter

Methylation Inference (D-GPM). To evaluate our D-GPM model, we benchmarked its

performance against linear regression (LR), regression tree (RT) and support vector machine

(SVM), with regard to methylation profile data based on the Illumina Human Methylation

450k data from The Cancer Genome Atlas (TCGA) [14]. LR is used to infer the methylation

levels of the target genes based on the promoter methylation of the landmark genes using

linear regression models. However, the linear model may fail to capture the nonlinear

relations of the original data. The SVM reliably represents complex nonlinear patterns [15]

but is limited by poor scalability due to the large data size. The RT addresses the

interpretability of the biological data and prediction model despite its lower accuracy and

instability in some predictors.

According to Illumina Human Methylation 450k data, we accessed the methylation

information from 902 landmark genes and 21645 target genes. The experimental results show

that D-GPM consistently outperforms the other methods for the testing data, and this was

measured using the criteria of the mean absolute deviation (MAE) and the Pearson

correlation coefficient (PCC).

2 Results

Here, we introduced the methylation beta value (MBV) datasets from TCGA and

defined the methylation profile inferences as a multitask regression problem, with the

MBV-tr for training, MBV-va for validation and MBV-te for testing. We have also illustrated

our deep learning method D-PGM and the other three methods, including LR, RT and SVM,

to work out the regression problem. Next, we show the predictive performances of the above

methods on the MBV-te data based on the MAE and PCC criteria.

2.1 D-GPM performs the best for predicting promoter methylation

The back-propagation algorithm, mini-batch gradient descent, and other beneficial

deep learning techniques are adopted in training the D-GPM [16]. The detailed parameter

configurations are shown in Table 1.

Table 1. Detailed parameter configurations are given in D-GPM.

Parameters	
# of hidden layers	[1-8]
# of hidden units in each hidden layer	[1000,2000,3000,4000,5000,6000,7000,8000,9000]
Dropout rate	[0%,5%,10%,15%,20%,25%,30%,35%,40%,45%,50%]
Momentum coefficient	0.5
Initial learning rate	5E-4, 2E-4, 1E-4 or 8E-5
Minimum learning rate	1.00E-05
Learning rate decay factor	0.9
Learning scale	3.0
Mini-batch size	200
Training epoch	500
Weights initial range	$\left[-\dfrac{\sqrt{6}}{\sqrt{n_i + n_o}}, \dfrac{\sqrt{6}}{\sqrt{n_i + n_o}} \right]$

According to the parameter configurations, all the combinations of parameters are

made during the D-GPM training for predicting the promoter methylation of the target genes.

As Table 2 indicates, D-GPM acquires the best MAE performance on MBV-te, with

five hidden layers of 7000 units and a 15% dropout rate (D-GPM-15%-7000×5) among the

792 (8*9*11) various D-GPMs. Meanwhile, D-GPM has an extraordinary edge over MAE

compared with LR, SVM, and RT.

Table 2. The MAE-based overall errors of LR, RT, SVM, and D-GPM, with partially

different architectures and partially different dropout rates on MBV-te. The numbers after "±"

are the standard deviations of the prediction errors over all the target genes. The best

performance of D-GPM is underlined. SD refers to standard deviation.

hidden layers	hidden units MAE±SD dropout rate	6000	7000	8000
4	10%	0.03322±0.02527	0.03403±0.02597	0.03434±0.02634
4	15%	0.03328±0.02533	0.03402±0.02597	0.03436±0.02637
4	20%	0.03362±0.02548	0.03425±0.02608	0.03440±0.02622
5	10%	0.03441±0.02637	0.03373±0.02574	0.03464±0.02643
5	15%	0.03430±0.02596	<u>0.03285±0.02511</u>	0.03425±0.02612
5	20%	0.03502±0.02671	0.03430±0.02591	0.03472±0.02650
6	10%	0.03407±0.02592	0.03389±0.02575	0.03388±0.02575
6	15%	0.03392±0.02588	0.03336±0.02551	0.03314±0.02529
6	20%	0.03562±0.02690	0.03461±0.02606	0.03508±0.02645
Linear regression		0.036334±0.027738		
Support vector machine		0.034999±0.025837		
Regression tree		0.045360±0.036298		

Similarly, D-GPM also obtains the best PCC performance on MBV-te among the 792

prediction models, as shown in Table 3. The complete MAE, PCC evaluation of D-GPM

armed with the other architectures (hidden layer: from 1 to 8, with step size 1; hidden unit:

from 1000 to 9000, with step size 1000; dropout rate: from 0% to 50%, with step size 5%) on

the MBV-te is given in the Supplementary Material.

Table 3. The PCC of LR, RT, SVM and D-GPM, with partially different architectures and

partially different dropout rates on MBV-te. The numbers after "±" are the standard

deviations of the PCC over all the target genes. The best performance of D-GPM is

underlined. SD refers to standard deviation.

hidden layers	hidden units PCC±SD dropout rate	6000	7000	8000
4	10%	0.80806±0.09641	0.79721±0.09759	0.80580±0.09570
4	15%	0.80553±0.09681	0.79364±0.09888	0.80413±0.09610
4	20%	0.80770±0.09642	0.80322±0.09639	0.79684±0.09507
5	10%	0.77764±0.10222	0.80320±0.09841	0.79896±0.09435
5	15%	0.78415±0.10122	0.81859±0.09403	0.78281±0.10353
5	20%	0.78349±0.10011	0.81346±0.09432	0.79334±0.09970
6	10%	0.79192±0.09870	0.80074±0.09613	0.80103±0.09465
6	15%	0.78648±0.10022	0.80858±0.09232	0.81062±0.09144
6	20%	0.78793±0.10062	0.80824±0.09245	0.79523±0.09749
Linear regression		0.784622±0.106910		
Support vector machine		0.794183±0.105629		
Regression tree		0.665748±0.119239		

Based on the above MAE and PCC, we can conclude that D-GPM is the best model

for predicting promoter methylation among the prediction models.

2.2 Evaluation according to MAE criteria

D-GPM acquires the best MAE performance on the MBV-te, with a 15% dropout rate

(described as D-GPM-15%) among the eleven dropout rates, ranging from 0% to 50%, with a

step size of 5%. Fig. 1 shows the overall MAE performances of D-GPM-15% and SVM on

the MBV-te. The larger architecture of D-GPM-15% (five hidden layers with 7000 hidden

units in each hidden layer, described as D-GPM-15%-7000$\times$5) acquires the least MAE on the

MBV-te. The improvements of D-GPM-15%-7000$\times$5 is 9.59%, 27.58%, and 6.14% over LR,

RT, and SVM, respectively. A possible explanation is that deep learning can capture complex

features [17].

D-GPM also outperforms LR and RT for almost all the target genes on MAE. Fig. 2

shows the density plots of the MAE errors of all the target genes by LR, RT, SVM, and

D-GPM. On the whole, D-GPM occupies a larger proportion at the low MAE level and a

lower proportion at the high MAE level compared to the three machine learning methods,

especially for RT and LR, attesting to the prominent performance of D-GPM.

Fig. 3(a-c) displays a genewise comparative analysis between D-GPM and the other

three methods. In terms of MAE, D-GPM outperforms RT for 95.66% (20705 genes) of the

target genes, it outperforms LR for 92.65% (20054 genes) of the target genes, and it

outperforms SVM for 85.49% (18504 genes) of the target genes. These results can also be

viewed by the larger proportion of dots lie above the diagonal, and this better performance

may suggest that D-GPM can capture some intrinsic nonlinear features of the MBV data,

which LR, RT, and SVM did not accomplish.

RT performs significantly worse than the other methods in the MAE aspect. One

possible reason is that the model is oversimplified to capture the essential features between

the landmark and target genes based on the MBV-te [18].

According to the model distribution of the lowest MAE for each target gene, we find

the best model distribution, as shown in Fig. 4(a). RT accomplishes the best MAE

performance for 305 target genes (1.41%), including the genes *BRD2, GPI, MAF,* and *MICB*,

implying that there is a relatively simple methylation regulation mechanism and promoter

methylation of these genes that is dominantly regulated by a very few landmark genes. The

LR can predict 1,242 target genes (5.74%), at best, among the other three methods, including

the genes *ABCD1, HPD, AMH* and *ARAF*, laying a solid foundation for the pathogenesis of

diseases, such as Adrenoleukodystrophy, Hawkinsinuria, Persistent Mullerian Duct Syndrome

and Pallister-Killian Syndrome, using our LR [19-22]. Noticeably, SVM performs best for a

total of 2813 genes (13.00%), including *ACE2, A2M,* and *CA1*. One possible explanation for

this is that there seem to be intricate and complicated interactions among the promoter

methylation of the landmark genes and these 2813 target genes. Undoubtedly, D-GPM does

better than the other three methods, as far as 17,285 genes (79.86%) are concerned,

demonstrating the deep neural networks' powerful ability to capture the nonlinear

relationship of methylation profiling.

2.3 Evaluation according to PCC

D-GPM accomplishes the best PCC performance on the MBV-te, with a 15% dropout

rate. Fig. 5 shows the overall PCC performances of D-GPM-15% and the other methods on

MBV-te. Similar to the MAE, D-GPM-15%-7000×5 acquires the most significant PCC on

the MBV-te. The relative improvement of D-GPM-15%-7000×5 is 4.34% over the LR, 22.96%

over RT and 3.07% over SVM. Similar to MAE, almost all the combined architectures of

D-GPM-15% outperforms LR and RT in PCC performance.

In terms of the PCC, D-GPM also outperforms RT and LR for almost all the target

genes. Fig. 6 displays the density plots of the PCC of all the target genes by LR, RT, SVM,

and D-GPM. By and large, we can see that D-GPM possesses a larger proportion of the high

PCC and a lower proportion at the low PCC compared to the RT, LR, and SVM.

Fig. 7(a-c) shows a genewise comparative analysis between D-GPM and the other

three methods. For PCC, D-GPM outperforms RT in 98.25% (21266 genes) of the target

genes, outperforms LR in 91.00% (19696 genes) in of the target genes and outperforms SVM

in 81.56% (17653 genes) of the target genes. Therefore, D-GPM's powerful prediction for the

PCC of the overall target genes is preserved similar to its effective prediction for the MAE. It

is obvious that although the prediction property of the SVM is still modest in the PCC aspect,

its PCC for some of the target genes is significantly higher than D-GPM and behaves better

than the prediction for the same target genes in the MAE aspect. This finding is probably due

to the fact that SVM is based on the principle of the structural risk minimization, avoiding

overlearning problems and having a strong generalization ability.

According to the model distribution of the maximal PCC, we find the best model

distribution, as shown in Fig. 5(b). Surprisingly, RT only gains the best PCC performance for

19 target genes (0.09%), including the genes *ALG1* and *NBR2* falling far below the best 305

target genes in the MAE aspect. Considering RT's awful prediction power for PCC compared

with its better prediction power for MAE, it may be explained by the fact that RT makes

decisions based on an over simple assumption. LR predicts the best 1057 target genes (4.88%)

among other three methods, including the genes *AASS* and *ACE*, which is almost the same as

the 1242 in the MAE level. For PCC, SVM is on its best behavior for a total of 3613 genes

(16.69%), having an increasing number compared to that of the MAE, in contrast to RT.

Undoubtedly, D-GPM outperforms the other three methods, with regard to 16956 genes

(78.34%), but behaves badly relative to the 79.86% in the MAE level, suggesting an inability

to predict the PCC for the target genes.

Noticeably, the dropout regularization manages to improve the performance of

D-GPM-7000×5 on the MBV-te, as shown in Fig. 8. With a 15% dropout rate,

D-GPM-15%-7000×5 consistently achieves the best MAE performance on the MBV-te

among the models, with 0%, 15%, 20%, 25%, and 35% dropout rates, proving that overfitting

and underfitting both result in a bad influence on the prediction model.

3 Discussion

Comprehending intricate regulation modes of promoter methylation profiling under

numerous biological states needs robust inference frameworks and cost-effective profiling

tools. Despite the fact that whole genome bisulfite sequencing is thought of as the best

protocol, it is too costly because the genome-wide deep sequencing of the bisulfite-treated

fragments needs to be implemented.

Promoter methylation of a gene has been confirmed to be associated with DNA

accessibility and the binding of transcription factors that regulate gene expression.

Considering that there is an underlying relationship between ~1,000 landmark genes and

~21,000 target genes at the genome-wide level of expression and the fact that methylation

occurring in the promoters located in the promoter region is negatively associated with

expression of its corresponding gene, we can make good use of the methylation levels in the

promoter regions of landmark genes to characterize the cellular status of samples under

diverse conditions. Here, we also develop three machine learning methods, namely, LR, SVM

and RT, and a deep method called D-GPM for inferring the promoter methylation of target

genes based on only landmark genes.

The different methods have different advantages and disadvantages. RT provides us

with good interpretability and shows a relative lousy accuracy. LR offers a better

performance compared to RT, even though it ignores the nonlinearity within biological data.

SVM represents complex nonlinear patterns. Unfortunately, it suffers from poor scalability of

the large data size. To some extent, D-GPM manages to overcome the above drawbacks.

These prediction models are not perfect and behave better separately for different target genes.

It is instructive to interpret these prediction models and explain the inherent relationship

between the promoter methylation of the target genes and landmark genes according to our

results.

Although D-GPM is the best model for predicting most of the target genes, three

machine learning methods all have specific advantages when predicting some specific target

genes. Next, we will integrate multiple prediction models as an ensemble tool to ensure it is

suitable for predicting as many target genes as possible. In addition, we need to conduct a

verification experiment to judge whether the conclusion drawn from the relationship among

the promoter methylation of the target and landmark genes (such as *TDP1* and *CIAPIN1*) is

sound and persuasive. Furthermore, after obtaining the ensemble prediction model, we will

make the most of it to impute and revise methylation sites that are missing or have a low

reliability in realistic methylation profiling data.

4 Conclusions

In summary, D-GPM acquires the least overall MAE and the highest PCC on the

MBV-te among LR, RT, and SVM. For a genewise comparative analysis between D-GPM

and the above methods, D-GPM outperforms LR, RT, and SVM in an overwhelming majority

of the targets genes, concerning the MAE and PCC. In addition, according to the model

distribution of the least MAE and the highest PCC for the target genes, D-GPM predominates

among the other models for predicting a majority of the target genes, laying a solid

foundation for explaining the inherent relationship between the promoter methylation of

target genes and landmark genes via interpreting results from these prediction models.

5 Methods

In this section, we first specify the gene methylation datasets in this study and

formulate the gene promoter methylation inference problem. We then propose the D-GPM for

this problem and describe the relevant details. Finally, we introduce several machine learning

methods, which serve as benchmarks.

5.1 Datasets

The MBV datasets are acquired from TCGA [23]. Considering that the Illumina

Human Methylation 450k possess more probes and a higher coverage rate, we exclude

datasets from the Illumina Human Methylation 27k, and finally, 9756 records remain for the

later analysis [24]. After filtering out the records, we calculate the average beta value of all

the probes located in the promoter regions of a certain gene as its promoter methylation level.

For more information on the data preprocessing, please refer to the data preprocessing section

in the Supplementary Material.

We randomly partitioned the methylation data into 80% for training, 10% for

validation, and 10% for testing, which corresponded to 7,549 samples, 943 samples, and 943

samples, respectively. We denoted them as MBV-tr, MBV-va, and MBV-te in order.

5.2 Multitask regression model for gene expression inference

In the model, there are J landmark genes, K target genes and N training samples. We

denoted the training data as $\{x_i, y_i\}_{i=1}^{N}$, where $x_i \in \Re^{J}$ is the promoter methylation

profiles of the landmark genes and $y_i \in \Re^{K}$ represents the methylation profiles of the target

genes in the ith sample. Our task is to find a mapping $F : \Re^{J} \Rightarrow \Re^{K}$ that fits $\{x_i, y_i\}_{i=1}^{N}$

well, which can be viewed as a multitask regression problem.

Let us assume a sample of 9756 individuals, each represented by a 902-dimensional

input vector and a 21645-dimensional output vector. Let $\mathbf{X}$ denote the $N \times J$ input matrix,

whose column corresponds to the observations for the j-th input $x_j = \left\{x_j^1, ..., x_j^N\right\}^{T}$. In genetic

association mapping, each element x_j^i of the input matrix takes values from $\{0, 1, 2, 3\}$

according to the number of minor alleles at the j-th locus of the i-th individual. Let $\mathbf{Y}$ denote

the $N \times K$ output matrix, whose column is a vector of observations for the k-th output

$y_k = \{y_k^1, ..., y_k^N\}^T$. For each of the K output variables, we assume a linear regression model:

$y_k = X\beta_k + \varepsilon_k, \forall k = 1, ...K,$ (1)

where β_k is a vector of the J regression coefficients $\{\beta_k^1, ...\beta_k^J\}^T$ for the k-th output, and

ε_k is a vector of N independent error terms having a mean of 0 and a constant variance. We

center the y_k's and x_j's, such that $\sum_i y_k^i = 0$ and $\sum_i x_j^i = 0$, and consider the model

without an intercept.

The regression coefficients matrix β was used to take advantage of the relatedness

across all the input variables.

5.3 Assessment criteria

We adopted MAE and PCC as the criteria to evaluate models' performance at each

target gene t of the different samples. We formulated the overall error as the average MAE

over all the target genes. The PCC was used to describe the relationship between the real

promoter methylation and the predicted promoter methylation. Here, the definitions of MAE

and PCC for evaluating the predictive performance at each target gene t are as follows:

$MAE_{(t)} = \dfrac{1}{N'} \sum_{i=1}^{N'} | y_{i(t)} - \hat{y}_{i(t)} |,$ (2)

$Correlation_{(t)} = \dfrac{\sum_{i=1}^{N'} (y_{i(t)} - \overline{y}_{(t)})(\hat{y}_{i(t)} - \overline{\hat{y}}_{(t)})}{\sqrt{\sum_{i=1}^{N'} (y_{i(t)} - \overline{y}_{(t)})^2 \cdot \sum_{i=1}^{N'} (\hat{y}_{i(t)} - \overline{\hat{y}}_{(t)})^2}},$ (3)

where N' is the number of testing samples, $\hat{y}_{i(t)}$ is the predicted expression value for the

target gene t in sample i, and $\overline{\hat{y}}_{(t)}$ is the mean predicted expression value for the target gene t

in N' testing samples.

5.4 D-GPM

D-GPM is a fully connected multilayer perceptron with one output layer. All the

hidden layers consist of H hidden units. In this work, we had a set of Hs, ranging from 1000

to 9000, with a step size of 1000. A hidden unit j in layer l takes the sum of the weighted

outputs plus the bias from the previous layer l-1 as the input and produces a single output o_j^l.

$$o_j^l = f\left(\sum_{i=1}^{H} w_{i,j}^{l-1} o_i^{l-1} + b_j^{l-1}\right), \tag{4}$$

where f is a nonlinear activation function, H is the number of hidden units, and

$\left\{w_{i,j}^{l-1}, b_j^{l-1}\right\}_{i=1}^{H}$ are the weights and the bias of unit j to be found.

The loss function is the sum of the mean squared error at each output unit, which is:

$$\varsigma = \sum_{t=1}^{T}\left[\frac{1}{N}\sum_{i=1}^{N}\left(y_{i(t)} - \hat{y}_{i(t)}\right)^2\right]. \tag{5}$$

D-GPM contains 902 units in the input layer, corresponding to the 902 landmark

genes, and we also configured D-GPM with 21,645 units in the output layer analogous to the

21,645 target genes. Fig. 9 shows the various architectures of D-GPM.

Here, we briefly describe the training techniques and their significance in training

steps:

1. Dropout is a scheme used to perform model averaging and regularization for deep

neural networks [25]. Here, we utilize dropout to all the hidden layers of D-GPM, and the

dropout rate p, which steers the regularization intensity, is set at [from 0% to 50%, with step

size 5%], separately, to find the optimum architecture of D-GPM.

2. A normalized initialization can stabilize the variances of activation during epochs.

To initialize the parameters of deep neural networks, here, we set the initialized weights to

within the range of $\left[-1\times10^{-4}, \quad 1\times10^{-4} \right]$, according to the activation function.

3. The momentum method is also adopted in our work to speed the gradient

optimization and improve the convergence rate of the deep neural networks [26].

4. The learning rate is initialized to 5×10^{-4}, 2×10^{-4}, 1×10^{-4} or 8×10^{-5}, depending on

different architecture of D-GPM, and is tuned according to the training error on a subset of

MBV-tr.

5. Model selection is implemented based on the MBV-va. The models are assessed on

MBV-va after each epoch, and the model with the minimum loss function is saved. The

maximum epoch for training is set as 500 epochs.

Here, we implement D-GPM with the Theano and Pylearn2 libraries [27,28].

5.5 Benchmark methods

To evaluate the performance of the deep learning methods, we adopt LR, RT, and

SVM as benchmarks.

Here, we utilize the RT model with rpart [29]. The Gaussian RBF kernel function has

a high superiority for a large sample and for high dimension data, and it reduces the

computational complexity in our methylation profiling data efficiently [30]; , we adopt the

kernlab package to implement SVM for predicting promoter methylation [31].

When training the above three machine models, we harness the 5-fold cross-validation

method. Our models are modeled using 80% of the randomly sliced data, and the remaining

20% of the data re used for evaluation. After the process of training and evaluating the model

is repeated five times independently, we calculate the average performance during these five

processes as a final performance index.

Abbreviations

MAE: mean absolute deviation; PCC: Pearson correlation coefficient; LR: linear regression;

RT: regression tree; SVM: support vector machine; MBV: methylation beta value. SD:

standard deviation.

Declarations

Ethics approval and consent to participate

Not applicable.

Consent for publication

Not applicable.

Availability of data and materials

The datasets used and/or analyzed during the current study are available from the

corresponding author upon reasonable request.

Competing interests

The authors declare that they have no competing interests.

Funding

This research was supported by the Shenzhen Key Laboratory of Forensics (NO.

ZDSYS201507301424148) of the Shenzhen Municipal Government of China.

Authors' contributions

S.C.L. supervised the research and revised the manuscript; X.X.P. designed the study, did the

modeling, performed the experiments, carried out the data analyses, graphing and wrote the

manuscript; B.L. collected and prepossessed data; X.Z.W. participated in SVM, graphing,

manuscript writing and revision; X.X.P., B.L., X.Z.W., Y.L.L., X.Q.Z., and S.B.L.

participated in the literature review; all the authors contributed to the manuscript.

Acknowledgements

The authors acknowledge BGI-Shenzhen for the computing resources and TCGA project

organizers for the public datasets.

References

1.   Moore LD, Le T, Fan G. DNA methylation and its basic function.

Neuropsychopharmacology. 2013;38:23-38.

2.   Hammoud SS, Cairns BR, Carrell DT. Analysis of gene-specific and genome-wide

sperm DNA methylation. Methods Mol Biol. 2013;927:451-8.

3.   Krygier M, Podolak-Popinigis J, Limon J, Sachadyn P, Stanislawska-Sachadyn A. A

simple modification to improve the accuracy of methylation-sensitive restriction

enzyme quantitative polymerase chain reaction. Anal Biochem. 2016;500:88-90.

4.   Thu KL, Vucic EA, Kennett JY, Heryet C, Brown CJ, Lam WL, et al. Methylated

DNA immunoprecipitation. J Vis Exp. 2009:e935.

5.   Bibikova M, Le J, Barnes B, Saedinia-Melnyk S, Zhou L, Shen R, et al.

Genome-wide DNA methylation profiling using Infinium(R) assay. Epigenomics.

2009;1:177-200.

6.   Li Q, Hermanson PJ, Springer NM. Detection of DNA methylation by whole-genome

bisulfite sequencing. Methods Mol Biol. 2018;1676:185-96.

7.   Edgar R, Domrachev M, Lash AE. Gene expression omnibus: NCBI gene expression

416   and hybridization array data repository. Nucleic Acids Res. 2002;30:207-10.

417   8.   Bansal M, Belcastro V, Ambesi-Impiombato A, di Bernardo D. How to infer gene

418   networks from expression profiles. Mol Syst Biol. 2007;3:78.

419   9.   Daura-Oller E, Cabre M, Montero MA, Paternain JL, Romeu A. Specific gene

420   hypomethylation and cancer: new insights into coding region feature trends.

421   Bioinformation. 2009;3:340-3.

422   10.   Portela A, Esteller M. Epigenetic modifications and human disease. Nat Biotechnol.

423   2010;28:1057-68.

424   11.   Xiong HY, Alipanahi B, Lee LJ, Bretschneider H, Merico D, Yuen RK, et al. RNA

425   splicing. The human splicing code reveals new insights into the genetic determinants

426   of disease. Science. 2015;347:1254806.

427   12.   Kelley DR, Snoek J, Rinn JL. Basset: learning the regulatory code of the accessible

428   genome with deep convolutional neural networks. Genome Res. 2016;26:990-9.

429   13.   Zhou J, Troyanskaya OG. Predicting effects of noncoding variants with deep

430   learning-based sequence model. Nat Methods. 2015;12:931-4.

431   14.   Mclendon R, Friedman A, Bigner D, Meir EGV, Van Meir E, Brat D, et al.

432   Comprehensive genomic characterization defines human glioblastoma genes and core

433   pathways. Nature. 2008;455:1061-8.

434   15.   Ye G, Tang M, Cai JF, Nie Q, Xie X. Low-rank regularization for learning gene

435   expression programs. PLoS One. 2013;8:e82146.

436   16.   Tomczak K, Czerwińska P, Wiznerowicz M. The Cancer Genome Atlas (TCGA): an

437   immeasurable source of knowledge. Contemp Oncol (Pozn). 2015;19:A68-77.

438 17. Touleimat N, Tost J. Complete pipeline for Infinium((R)) Human Methylation 450K

439   BeadChip data processing using subset quantile normalization for accurate DNA

440   methylation estimation. Epigenomics. 2012;4:325-41.

441 18. Hinton GE, Srivastava N, Krizhevsky A, Sutskever I, Salakhutdinov RR. Improving

442   neural networks by preventing co-adaptation of feature detectors. arXiv preprint

443   arXiv:12070580. 2012.

444 19. Glorot X, Bengio Y. Understanding the difficulty of training deep feedforward neural

445   networks. J Mach Learn Res. 2010;9:249-56.

446 20. Sutskever I, Martens J, Dahl G, Hinton G: On the importance of initialization and

447   momentum in deep learning. In: *Proceedings of the 30th international conference on*

448   *international conference on machine learning: 2013; Atlanta, GA, USA*: ACM; 2013:

449   III-1139-III-47.

450 21. Goodfellow IJ, Warde-Farley D, Lamblin P, Dumoulin V, Mirza M, Pascanu R, et al.

451   Pylearn2: a machine learning research library. arXiv preprint arXiv:13084214. 2013.

452 22. Bergstra J, Breuleux O, Bastien F, Lamblin P, Pascanu R, Desjardins G, et al.: Theano:

453   A CPU and GPU math compiler in Python. In: *Proceedings of the python for scientific*

454   *computing conference (SciPy): 2010; Austin, TX*; 2010.

455 23. Therneau TM, Atkinson B. Rpart: recursive partitioning. R package version 3.1-51.

456   2012.

457 24. Steinwart I, Hush D, Scovel C. An explicit description of the reproducing kernel

458   hilbert spaces of gaussian RBF kernels. IEEE Trans Inf Theory. 2006;52:4635-43.

459   25.   Karatzoglou A, Smola A, Hornik K, Zeileis A. kernlab-an S4 package for kernel

460   methods in R. J Stat Softw. 2004;11:721-9.

461   26.   Bengio Y. Learning Deep Architectures for AI. Foundations and Trends® in Machine

462   Learning. 2009;2:1-127.

463   27.   Timofeev R. *Classification and regression trees (CART) theory and applications*.

464   Berlin: Humboldt University; 2004.

465   28.   Park JA, Jun KR, Han SH, Kim GH, Yoo HW, Hur YJ. A novel mutation in the

466   ABCD1 gene of a Korean boy diagnosed with X-linked adrenoleukodystrophy. Gene.

467   2012;498:131-3.

468   29.   Thodi G, Schulpis KH, Dotsikas Y, Pavlides C, Molou E, Chatzidaki M, et al.

469   Hawkinsinuria in two unrelated Greek newborns: identification of a novel variant,

470   biochemical findings and treatment. J Pediatr Endocrinol Metab. 2016;29:15-20.

471   30.   Wongprasert H, Somanunt S, De Filippo R, Picard JY, Pitukcheewanont P. A novel

472   mutation of anti-Mullerian hormone gene in Persistent Mullerian Duct Syndrome

473   presented with bilateral cryptorchidism: a case report. J Pediatr Urol. 2013;9:e147-9.

474   31.   Ticho BH. Iris transillumination defects associated with pallister-killian syndrome. J

475   Pediatr Ophthalmol Strabismus. 2010;47:58-9.

Figure legends

Fig. 1. The overall MAE errors of D-GPM-15%, with various architectures on the MBV-te.

Fig. 2. The density plots of the MAE by LR, RT, SVM, and D-GPM on the MBV-te.

Fig. 3. (a) The MAE errors of each target gene by D-GPM compared with RT on the MBV-te.

(b) The MAE errors of each target gene by D-GPM compared with LR on the MBV-te. (c)

The MAE errors of each target gene by D-GPM compared with SVM on the MBV-te. Among

(a), (b) and (c), each dot represents one out of the 21645 target genes. The x-axis is the MAE

of each target gene by D-GPM, and the y-axis is the MAE of each target gene by the other

machine learning method. The dots above the diagonal indicate that D-GPM achieves lower

error compared with the other method.

Fig. 4. (a) Distribution of the best model according to MAE for the target genes. (b)

Distribution of best model according to PCC for the target genes.

Fig. 5. The overall PCC performance of D-GPM-15% with various architectures on the

MBV-te.

Fig. 6. The density plots of the PCC of all the target genes by LR, RT, SVM and D-GPM on

MBV-te.

Fig. 7. (a) The PCC performance of each target gene by D-GPM compared with RT on the

MBV-te. (b) The PCC performance of each target gene by D-GPM compared with LR on the

MBV-te. (c) The PCC performance of each target gene by D-GPM compared with SVM on

the MBV-te. Among (a), (b) and (c), each dot represents one out of the 21645 target genes.

The x-axis is the PCC of each target gene by the abovementioned three machine learning

technique, and the y-axis is the PCC of each target gene by D-GPM. The dots above the

diagonal indicate that D-GPM achieves high PCC compared with the other method.

Fig. 8. The overall MAE decreasing the curves of D-GPM-7000×5 on the MBV-te, with

different dropout rates. The x-axis is the training epoch, and the y-axis is the overall MAE

error. The overall MAE error of SVM is also covered for comparison.

503 **Fig. 9**. The architecture of D-GPM. It is comprised of one input layer, one or multiple hidden

504 layers and one output layer. All the hidden layers have the same number of hidden units.

a The distribution of best model based on MAE

Linear regression(5.74%)
Regression tree(1.41%)
SVM(13%)
DNN(79.86%)

b The distribution of best model based on PCC

Linear regression(4.88%)
Regression tree(0.09%)
SVM(16.69%)
DNN(78.34%)

the overall correlation coefficient of D-PGM-15% with different architectures on test data