MITRE: predicting host status from microbiota time-series data

Elijah Bogart[1,2], Richard Creswell[1], Georg K. Gerber[1,*]

[1]Massachusetts Host-Microbiome Center, Department of Pathology, Brigham and

Women's Hospital, Harvard Medical School, 60 Fenwood Road, Boston, MA,

USA

[2]Present address: Kintai Therapeutics, Inc., 55 Cambridge Parkway Suite 800E,

Cambridge, MA 02142

*Corresponding author, ggerber@bwh.harvard.edu

Abstract

Longitudinal studies are crucial for discovering casual relationships between the

microbiome and human disease. We present Microbiome Interpretable Temporal

Rule Engine (MITRE), the first machine learning method specifically designed for

predicting host status from microbiome time-series data. Our method maintains

interpretability by learning predictive rules over automatically inferred time-periods

and phylogenetically related microbes. We validate MITRE's performance on

semi-synthetic data, and five real datasets measuring microbiome composition

over time in infant and adult cohorts. Our results demonstrate that MITRE performs

on par or outperforms "black box" machine learning approaches, providing a

powerful new tool enabling discovery of biologically interpretable relationships

between microbiome and human host.

Keywords: microbiome, time-series, longitudinal, machine learning

Introduction

The human microbiome is highly dynamic on multiple timescales, changing

dramatically during development of the gut in childhood, with diet, or due to

medical interventions [1]. Recently, a number of longitudinal studies have been

undertaken, seeking to link changes in the microbiota over time with medical

interventions such as delivery by Cesarean section [2], dietary changes [3], or

antibiotic treatment [4], or with disease outcomes in the host such as type 1

diabetes [5], dietary allergies [6], premature delivery [7, 8], necrotizing enterocolitis

[9, 10] and infection [11, 12].

Deriving maximally useful information from these studies requires computational

methods that can simultaneously identify patterns of change in the microbiome and

link these patterns to the host's status (e.g. disease outcome, presence or absence

of an intervention, etc.) Moreover, such computational methods must contend with

numerous challenges inherent to microbiome time-series data, including

measurement noise, sparse and irregular temporal sampling, and inter-subject

variability.

To overcome the challenges inherent in analyzing microbiome time-series data to

predict host status, we developed MITRE, a computational model that infers

human-interpretable predictive rules from high-throughput microbiome time-series

data, implemented in an open-source software package

(https://github.com/gerberlab/mitre/). MITRE falls into the general category of

Bayesian supervised machine learning classifiers: the algorithm uses a training

dataset of microbiota time-series and host statuses (supervised learning) to learn

a probability distribution (Bayesian inference) over a set of alternative models that

predict the status of a host from associated microbiome data (classification).

Bayesian approaches are powerful, because they provide principled estimates of

uncertainty throughout the model, which is an especially important feature in

biomedical applications where noisy inputs are the norm. We note that another

rule-based method, association rule mining (ARM), has recently been applied to

analyzing microbiome data in a different context (finding interaction patterns

among OTUs) [13]. Although ARM has some commonalities with Bayesian rule

learning approaches, ARM methods tend to employ user-based cut-offs and

heuristics, rather than principled probabilistic methods, as their primary function is

to mine large databases for putative interactions, rather than build predictive

models. Further, unlike Bayesian models, ARM methods do not incorporate prior

knowledge, as their focus is mining from large databases.

In previous work, we presented the MDSINE [14] algorithm, which infers dynamical

systems models from microbiome time-series data in order to predict population

dynamics of the microbiome over time. Our present work, MITRE, addresses a

different question: can we predict the status of the host *given* microbiome time-

series data. From the machine learning perspective, MDSINE is an unsupervised

model, whereas MITRE is a supervised model. The key distinction is that MDSINE

models the microbiome, whereas MITRE does not, and instead models host

outcomes. Like other supervised models, MITRE focuses on finding only the

essential features (in this case, microbial clades and relevant time-windows) to

explain the outcome, rather than attempting to explain the microbiome data itself.

This architecture is ideal for highly heterogeneous datasets with many

"distractors," which are the reality for longitudinal studies of the human

microbiome. Supervised machine learning classifiers are employed in many

biomedical predictive modeling applications, including forecasting (predicting a

future outcome, such as onset of disease, based on past data) and diagnosis or

subtyping (predicting which category a subject belongs to based on all available

data).

MITRE's unique contributions are its modeling of the special properties of

microbiome time-series data (phylogenetic and temporal relationships), and its

emphasis on producing human-interpretable predictors. This latter capability is in

contrast to various generic "black box" machine learning methods that have been

applied to analyzing static microbiome data, such as random forests [6, 15-17],

which may achieve high predictive accuracy but do not yield easily human-

interpretable models; interpretability is especially challenging for such models in

the context of time-series analyses, given repeated measurements and the fact

that relevant dynamics may occur at multiple time-scales. In the following sections,

we introduce the MITRE framework, then provide benchmarking results of MITRE

versus comparator methods on semi-synthetic data and five real microbiome time-

series datasets, and finally illustrate through examples MITRE's exploratory data

analysis capabilities and how these can help extract biological insights.

Results

Conceptual overview of the MITRE model and software

Figure 1 provides an overview of the MITRE framework. MITRE takes as input: (1)

tables of microbial abundances, typically operational taxonomic units (OTUs) from

16S rRNA amplicon sequencing or species mappings from metagenomic data,

measured over time for each host, (2) the status of each host (e.g., phenotype A

or phenotype B), (3) an optional set of static covariates for each host (e.g., gender),

and (4) placements of the microbes on a reference phylogenic tree [18]. MITRE

then automatically learns from the data predictive models that can be expressed

as a set of conditional statements, or human-readable rules, about time-localized

patterns of change in the abundances of groups of phylogenetically related

organisms. Weighted sums of the truth values of the rules are used to predict the

status of each host. The MITRE software package also provides a graphical user

interface (GUI) for interactive visualization of the output, which summarizes the

predictive models learned from the data.

To be more precise, a MITRE model consists of a baseline probability of a default

host status plus a set of zero or more rules. Each rule is a conjunction of one or

more *detectors*—conditional statements about bacterial abundances in the form

"between times t_0 and t_1, the average abundance of bacterial group j is

[above/below] threshold θ_l" or "between times t_0 and t_1, the slope of the abundance

of bacterial group j is [above/below] threshold θ_l"—together with a multiplicative

effect on the odds of the outcome of interest if all the detectors are satisfied.

As a simple example, a MITRE model predicting the odds of an infant developing

a disease in the first year of life might be:

• If, from month 2 to month 5, the average relative abundance of bacterial

126   clade A is above 4.0%, and from month 5 to month 8, the relative abundance

127   of bacterial clade B increases by at least 1.0% per month, the odds of

128   disease increase by a factor of 10;

129   • If, from month 3 to month 10, the average relative abundance of OTU C is

130   less than 9.5%, the odds of disease decrease by a factor of 2;

•   The baseline probability of disease is 22.0%.

Figure 1B schematically illustrates the application of a rule set to hypothetical data.

To predict the probability that an individual will develop the disease, the effects of

each rule satisfied by that individual's microbiome data are combined with the

baseline disease probability.

A comprehensive pool of possible detectors is generated automatically at the

beginning of a MITRE analysis, including detectors that apply to average values

and rates of change of clades at all levels on the phylogenetic tree of observed

bacteria at as many time windows as the temporal resolution of the data will allow

(see Methods.) By combining detectors from this pool, rules in a MITRE model can

capture rich temporal patterns, but still remain human-interpretable because each

component rule is easy to understand.

MITRE is a nonlinear model, which has a number of advantages over a linear

model. Most obviously, nonlinear models can capture effects such as

thresholds/saturation or interactions between variables. A more subtle issue,

particularly relevant to microbiome ratio-based data, is that linear models introduce

mathematical/statistical difficulties when analyzing compositional or proportional

data. While special constraints are needed for linear models to overcome these

difficulties [19], nonlinear models do not suffer from the same limitations because

they can inherently learn nonlinear transformations of the data. It is particularly

straightforward to understand the transformations produced by the MITRE

detectors described above: the learned thresholds effectively discretize ratio data

into distinct levels, a transformation that renders the data mathematically non-

compositional.

The MITRE framework is fully Bayesian, meaning it learns a distribution over

models, called the posterior probability distribution, which takes into account both

the input data as well as prior information provided. In the case of MITRE, this prior

information favors by default parsimonious explanations, i.e., short sets of simple

rules. Importantly, the default prior is designed to favor the empty rule set, or the

case in which the baseline odds only are used to predict host status, and the

microbiome data plays no role. This feature of the default prior is designed to guard

against over-fitting. Moreover, through the formalism of Bayes factors (see

Methods), MITRE provides a quantitative measure for the evidence favoring no

association between the microbiome data and host status or the alternative of any

rule sets that predict such a relationship; this feature allows the user to rigorously

evaluate whether sufficient signal is present in the microbiome data to predict host

status. Of note, this measure in effect incorporates multiple "hypotheses"

simultaneously (as the inference procedure explores the entire space of possible

rule sets at once.) Additional Bayes factors allow the user to assess the evidence

that each particular bacterial clade or OTU is associated with the host status, by

comparing the evidence for a model in which no detector in the rule set applies to

the clade of interest to a model in which at least one detector does apply to the

clade.

The MITRE software approximately infers the posterior probability distribution

using a custom Markov Chain Monte Carlo algorithm, and reports a *point estimate*

of the single best rule set as well as a summary of the distribution, which the user

may investigate interactively with the provided GUI. To make predictions for new

data, either the point estimate or an *ensemble* of multiple rule sets, weighted

according to their posterior probabilities, may be used.

Benchmarking against standard machine learning methods: semi-synthetic data

We used semi-synthetic data to compare the cross-validated predictive

performance of MITRE to two popular standard machine learning methods,

random forests and L1-regularized logistic regression, which have been widely

used to analyze data from static microbiome studies. We tested the performance

of MITRE and the comparator methods by training each method on a subset of the

available data and then classifying the remaining data according to the model

learned.   For each method, performance was evaluated using the F1-score

(harmonic mean of precision and recall) under crossvalidation, converting modeled

probabilities of outcomes to binary predictions by applying a threshold at

probability 0.5.

We simulated data from a real dataset using a parametric bootstrapping-type

procedure, in which models of microbiome dynamics were employed to interpolate

the real data and inject temporal perturbations into microbial clades to simulate a

"disease" host phenotype (see Methods for details). The real dataset [2] we

bootstrapped from tracked the gut microbiome composition from birth to two years

of age in a cohort of U.S. infants; we chose this dataset because it was among the

densest and most regularly sampled of available time-series datasets, and also

studied a relatively large number of subjects. To gain insight into the predictive

performance of the different methods, we simulated data with varying numbers of

subjects or time-points, and one or two temporal perturbations to microbial clades

to simulate subjects with a "disease." We assumed the perturbations occur over a

limited but unknown time-period during the study (~20% of the study duration),

which represents a challenging but biologically relevant scenario for analysis. The

ranges of subjects and time-points simulated correspond approximately to those

in real studies, and thus provide insight into the performance of the algorithms on

realistically sized studies. Note that MITRE is a supervised machine learning

method, which does not directly model the covariates (microbiome data.) Thus,

our data simulation procedure is unrelated to the underlying MITRE model and not

expected to introduce bias in favor of our method.

To provide as reasonable a comparison as possible, we used the average

abundance of each OTU in a series of time windows as input to the comparator

algorithms. It is important to note that there are no prior methods available that

were specifically designed for supervised learning from microbiome time-series

data. In fact, the comparator algorithms we implemented themselves represent an

advance over the state-of-the-art for many studies. To date, most studies have

employed an *ad hoc* strategy of manually identifying time windows of interest within

the experiment, and then testing for differential abundance of pre-specified groups

of taxa in each time window separately. Such an approach has significant

limitations. For example, effects occurring outside defined windows or across their

boundaries may not be detected; and, analyzing each time window/taxon pair

independently significantly reduces statistical power and precludes the discovery

of interactions across taxa or sequences of events across multiple time windows.

Our results on semi-synthetic data over a range of scenarios (Figure 2A-2D)

demonstrate superior cross-validated predictive performance of MITRE compared

to the other methods. Several interesting trends are also evident from these

results. First, the MITRE ensemble and point methods have similar performance,

except for in the setting of low numbers of subjects, which is likely simply a

stochastic effect since all the methods in that setting have poor performance. The

similar performance of the MITRE point and ensemble methods is very

encouraging from the interpretability perspective, since the point method yields a

single, human-interpretable rule set. Second as expected, all of the methods

improve in performance with increasing numbers of subjects, with eventual

plateauing of gains in performance at a level ultimately limited by noise in the data.

Third, there is also improvement in performance with increasing numbers of time-

points, but this improvement is less impressive. This phenomenon can be partially

explained by our assumption in generating the semi-synthetic data that

perturbations corresponding to the "disease" phenotype occur over a limited time-

period during the study. Thus, sampling of more time-points outside the

perturbation period provides only limited additional information useful for

prediction. Fourth and finally, we also see generally worse performance of all

methods in the more complex setting of two perturbations in the "disease" cases,

particularly with limited numbers of subjects or time-points. Interestingly, Random

Forests outperforms L1-regularized logistic regression in the two-perturbation case

in the setting of low numbers of subjects or time-points, while the opposite is true

in the one-perturbation case, which may be due to Random Forest's capacity to

handle non-linearities. In any event, MITRE, which models non-linearities through

conjunctions in rules, consistently outperforms the other two methods in this setting

as well. Overall, our results demonstrate that MITRE, a method specifically tailored

for analyzing microbiome time-series data, outperforms generic machine learning

methods. Moreover, we provide a simulation and testing platform for users to

investigate questions relevant to particular microbiome time-series datasets in the

future.

Benchmarking against standard machine learning methods: real data

We next evaluated the performance of MITRE on real experimental datasets with

16S rRNA amplicon and whole-genome-shotgun metagenomic sequencing data,

from five representative published studies with sufficiently dense temporal

sampling and numbers of subjects. Vatanen et al. [6] tracked gut microbiome

composition and life history data, including allergy diagnoses and serum IgE levels,

from birth to three years of age in cohorts of infants at high risk for autoimmune

disease in Finland, Estonia, and Russia. David et al. [3] tracked the gut microbiome

composition of healthy adults before, during and after a five-day period of

consuming exclusively plant-based or exclusively animal-based diets. Bokulich et

al. [2] tracked the gut microbiome composition from birth to two years of age in a

cohort of U.S. infants and examined the effects of mode of delivery, diet, and

antibiotic exposure. Kostic et al. [5] tracked the gut microbiome of Finnish and

Estonian infants at high risk for type 1 diabetes throughout the first years of life,

examining microbiome correlates of disease development. Finally, DiGiulio et al.

[7] tracked the composition of the vaginal microbiome in a cohort of pregnant

women, investigating an association with premature delivery.

Using the microbiome and outcome/class data from these five studies, we defined

a total of eleven representative microbiome-based prediction or classification tasks

(e.g., given the vaginal microbiome data of DiGiulio et al., predict which women in

the cohort experienced premature delivery; given the gut microbiome data of David

et al, determine which time series correspond to exclusively animal-based diets vs

exclusively plant-based diets; etc.) A full list of the tasks analyzed is given in

Supplementary Table 1. In five out of the eleven tasks, we found that at least one

of the methods performed well (F1-score > 0.7, indicating reasonably high

precision and recall.) These tasks represent scenarios in which true biological

signal may be present in the data, and thus serve as the most meaningful basis

for comparing performance of the different methods. Detailed results for all

methods on all tasks are given in Supplementary Table 1.

Both the MITRE point estimate and ensemble method achieved high accuracy on

all five of the relevant prediction or classification tasks (Figure 2E). In the case of

distinguishing infants fed formula-based diets from those predominantly breast-fed

(Bokulich *et al.*), predicting seroconversion to serum autoantibody positivity in

infants at high risk of T1D (Kostic *et al.*), and predicting premature delivery

(DiGiulio *et al.*), MITRE significantly outperformed the random forest and L1-

regularized logistic regression approaches; for Russian cohort membership

(Vatanen *et al.*) or plant-based diet (David *et al.*) prediction, MITRE performed on

par with the best comparator method (Random Forest). These results are

consistent with our semi-synthetic data simulations as well. Collectively our results

suggest that MITRE's phylogenetic aggregation approach and robust use of the

temporal structure of the data provide significant advantages for classification, and

the increased interpretability of the MITRE point estimate comes at little if any cost

in predictive accuracy.

Model interpretability and exploratory analysis capabilities

We illustrate here an example demonstrating MITRE's ability to achieve high

accuracy while maintaining interpretability. The best (point estimate) rule set

learned by MITRE to distinguish between predominantly formula-fed and

predominantly breast-fed infants in the study of Bokulich et al. [2] is "If, between

the 1st day of life and the 156th day of life, the average abundance of clade 13241

increases faster than 0.03% per day, the probability that the subject was

predominantly formula-fed is 79%; otherwise that probability is 5.4%." Though this

MITRE rule set is simple enough to express in a single sentence, it outperforms

Random Forest models that aggregate the predictions of over a thousand decision

trees (Figure 2E). Moreover, this MITRE rule set lends itself readily to biological

interpretation. Clade 13241 is a broad group of Firmicutes, including OTUs in the

dataset mapping to *Ruminococcus gnavus*, *Roseburia hominis*, and several

Clostridium and *Blautia* species. These species are generally viewed as more

representative of adult or at least more mature microbiomes, being strict

anaerobes with specialized carbon source utilization requirements and capabilities

(e.g., [20]), suggesting that the formula diet may shift infants toward more adult-

like gut microbiota. Of note, the expressiveness and interpretability of the MITRE

rule set format is retained even in cases of nonlinear interactions across multiple

clades and time windows; see the Supplementary Note for an example.

In addition to providing the point estimate, which can serve as a powerful predictive

model as described, MITRE also allows the user to explore the distribution of

probable rules learned by the framework. Such explorations can be useful for

further interpreting rule sets and generating biological hypotheses. Figure 3

illustrates MITRE's capabilities for interactive visualization of the distribution of

learned rules. Heat maps as shown in Figure 3A and 3D allow the user to examine

the time windows and regions of the phylogenetic tree where the temporal changes

in the microbiota are most strongly associated with the outcome of interest. In

Figure 3A-C, MITRE has been used to learn rules that distinguish the microbial

dynamics observed when the subjects in the study of David et al. [3] were fed an

exclusively plant-based diet for five days versus the dynamics observed when

subjects were fed an exclusively animal-derived diet. The user has clicked on two

areas on the heat map, revealing rules that apply to different time windows and

different groups of OTUs in the order Clostridiales. The first rule set pertains to a

clade containing *Roseburia* species, which are butyrate producers, whereas the

second rule set pertains to a clade containing *Dorea* species, which produce other

short-chain fatty acids including acetate and formate, but not butyrate. Thus, this

capability to explore the distribution of rule sets allows the user to find evidence

that the animal-based diet promotes two groups of phylogenetically distinct, and

likely functionally distinct, groups of microbes.

As another example, Figures 3D and 3E demonstrate exploration of the posterior

distribution of rule sets identifying temporal patterns that distinguish the microbiota

of predominantly formula-fed and predominantly breast-fed infants in the study of

Bokulich et al. [2], for which the point estimate described above performed well.

The heat map of Figure 3D shows that the high-posterior-probability rule sets are

strongly focused on a single group of OTUs in the first 156 days of life. Figure 3E

presents a particular detector, included in many such rule sets, that discriminates

effectively between diet types in the training data (which is the detector used by

MITRE to form the point estimate rule discussed above). Thus, in this case, the

user finds evidence that the posterior distribution is essentially unimodal, with the

point estimate alone characterizing temporal differences between the formula and

breast-milk fed infants well.

Discussion

MITRE offers a number of advantages over generic statistical or machine learning

methods. Incorporation of phylogenetic information readily allows for biological

interpretation of results, as discussed, whereas standard classification methods

that evaluate each taxon independently clearly do not have this advantage. MITRE

automatically learns time windows that are relevant to predicting host status, as

opposed to generic approaches that require the user to manually specify periods

of interest, which are generally unknown *a priori*. We have also highlighted the

utility of MITRE's human-readable rules. These rules can capture rich temporal

patterns and nonlinear relationships among microbes, but remain interpretable, as

they are composed of simple and understandable detectors. Indeed, as we have

shown, MITRE rule sets are not only easy to understand, but a single MITRE rule

can outperform black box machine learning methods that make predictions based

on collections of hundreds to thousands of components, which are difficult to

understand even individually.

Another important feature of the MITRE framework is that it is fully Bayesian.

Bayesian models are increasingly being adopted in a variety of fields, in particular

for biomedical applications (e.g., [21]), because they provide a unified framework

that handles a number of key modeling and inferential issues, including

incorporation of prior knowledge, accurate estimation of confidence in predictions,

and principled comparisons of multiple models. Bayesian methods for model

comparison have recently been highlighted as powerful alternatives [22] to

traditional *p*-value based hypothesis testing [23], because Bayesian approaches

allow direct comparison of multiple relevant alternative models, rather than just the

ability to reject a null model that is often of little interest in itself. In particular, MITRE

facilitates principled model comparisons by calculating Bayes factors [24], which

quantify the strength of the evidence provided by the data for each of a set of

competing models. We have also described how exploration of the posterior

distribution of rule sets using the provided GUI in the MITRE software package

allows the user to evaluate the possibility of multiple informative rule sets and

formulate biological hypotheses about the data set.

Although MITRE as currently implemented is primarily designed to use taxonomic

abundance profiles derived from 16S rRNA amplicon sequencing or WGS

metagenomics data as input–currently the most common data types in longitudinal

microbiome studies–the model and software can readily incorporate other time-

series of additional data types, e.g., host physiological measurements,

metabolomics, or metagenomics-derived functional profiles, as such data become

more widely available. Other model features that could be readily added in the

future include time-varying, continuous, and multiple host outcomes, e.g.,

multivariate host read-outs such as blood pressure, blood glucose, and body

weight.

Conclusion

We have demonstrated that our software package MITRE overcomes the unique

challenges of predicting host outcomes from microbiome time-series data, while

drawing on a well-established tradition of rule-based techniques in machine

learning and artificial intelligence [25-27], and can perform as well as or better than

"black box" machine learning methods while maintaining interpretability. This latter

feature is critical as microbiome analyses move into clinical applications, in which

patients and physicians necessarily place a premium on transparency and

interpretability of results. We have provided an open source and user-friendly

implementation of our method, which we expect will greatly aid investigators

analyzing longitudinal host-microbiome studies and ultimately provide novel

insights into the complex interplay between microbiome dynamics and host health

and disease.

Methods

Operation of the software and input data requirements

The MITRE software is implemented in Python 2.7.3. MITRE and its dependencies

are available through the Python Package Index, pypi.python.org, facilitating

installation across multiple platforms. The software is run from the command-line,

with parameters and other inputs specified using a straightforward configuration

file format.

Each MITRE run requires four input files (for the standard case of 16S rRNA

amplicon data): a table of OTU abundances in each sample, a table specifying the

subject and timepoint associated with each sample, a table specifying the outcome

(and optionally other data) associated with each subject, and phylogenetic

placements of the OTUs on a reference tree. The user provides the three tables in

comma-separated-value format, and phylogenetic placements in the .jplace format

produced by pplacer. Alternative input data types, including taxonomic abundance

profiles generated from WGS metagenomic data with Metaphlan, are described in

the MITRE manual online.

The output of the software, described in detail below, includes textual summaries

of a single best set of rules (the point estimate) and the distribution of probable

alternative rule sets, as well as an HTML file providing a graphical interface for

interactive visualization of the results.

MITRE model details

Mathematical basis of the MITRE model

MITRE can be expressed as a hierarchical generative model that generates sets

of rules of the form described above. The generative process, starting at the top of

the hierarchy, is as follows:

• Sample a length K for the rule set

• For each rule $k \in \{1,\ldots,K\}$, sample:

○ A weight β_k

○ A rule length L_k (number of detectors in the rule)

○ The detectors $d \in \{1,\ldots,L_k\}$, drawing from a pre-defined pool of

detectors (see below) according to a probability distribution which is

parameterized by the time window and bacterial group (phylogenetic

subtrees) to which each detector applies.

The rules are then weighted in a Bayesian logistic regression model to predict host

status. To be precise, assume we have observations x_{ijt} for i=1,2,…,$N_{subjects}$ of

relative abundances of bacterial OTUs j=1,2,…,N_{OTUs} sampled at time-points

t=1,2,…,$N_{samples,i}$, as well as a binary status variable y_i for each host. The MITRE

probability model can then be expressed as:

$$y_i \sim \mathrm{Bernoulli}(p_i)$$

$$p_i = \frac{1}{1 + e^{-\psi_i}}$$

$$\psi = \beta_0 + A(R, x)\vec{\beta}$$

$$\beta | R \sim \text{Normal}(0, \sigma_b^2 I)$$

$$\beta_0 \sim \text{Normal}(0, \sigma_b^2)$$

$$R \sim \pi(R, x)$$

Here, R is a set of rules, and $A(R,x)$ is the matrix whose entry A_{ik} is 1 if the data

from subject i satisfies the conditions of all detectors in the k-th rule in the set, and

zero otherwise. Conditional on R, this is a standard Bayesian logistic regression

model, whose covariates are the truth values of the rules in R (along with an offset

term modeling baseline odds). MITRE also allows the optional inclusion of static

non-microbiome covariates; see the Supplemental Note for complete details.

The prior probability distribution over rule sets, $\pi(R,x)$, is a mixture over the

probability Θ_{empty} for an empty rule set R_0, versus a truncated negative binomial

distribution for the length of a non-empty rule set. For a non-empty rule set, the

prior further models the distribution over detectors that comprise each rule, taking

into account the length of the time window for the detector and an associated

position on the phylogenetic tree. Hyperparameters for these priors, as well as

priors on other variables, complete the model. A full specification of priors in

MITRE, and a discussion of sensitivity to the choice of hyperparameters, are given

in the Supplementary Note.

Generation of pools of detectors from data

MITRE generates a comprehensive pool of detectors from the supplied data and

user-specified parameters t_{min}, t_{max}, N_w, and N_θ, as follows:

1. Divide the duration of the experiment/observations into N_w equal basic time

windows, and enumerate all combinations of 1 or more consecutive basic

time windows that are longer than t_{min} and shorter than t_{max} and during which

at least one sample was collected for every subject.

2. Within each such time window (t_0, t_1), for each bacterial group (phylogenetic

subtree) j, calculate the average abundance of the group in each subject i,

and sort those values, obtaining $v_1 \leq v_2 \leq \ldots \leq v_{Nsubjects}$. If $N_{subjects} < N_\theta + 1$,

for $l=1,2,\ldots,N_{subjects}-1$, let $\theta_l = (v_l + v_{l+1})/2$ and add the detectors "between

t_0 and t_1, the average abundance of group j is above θ_l and "between t_0

and t_1, the average abundance of group j is below θ_l" to the population. If

instead $N_{subjects} > N_\theta$, hierarchically cluster the values $v_0, \ldots , v_{Nsubjects}$ into N

$_\theta$ groups, let θ_l be the midpoint between cluster l and cluster $l+1$, for

$l=1,2,\ldots, N_\theta -1$, and add the detectors corresponding to those thresholds

instead.

3. Then repeat the process for all combinations of 1 or more consecutive basic

time windows longer than t_{min} and shorter than t_{max} during which at least two

samples were collected for every subject, calculating the slope of the

abundance of each group j in each subject i during each such window, and

adding the detectors "If, between t_0 and t_1, the slope of the abundance of

group j is [above/below] θ_i" to the population (again carrying out a

clustering process to reduce the number of threshold values to N_θ, if

needed.)

The runtime of the inference algorithm (described below) depends approximately

linearly on the size of the detector pool; thus the choice of parameters t_{min}, t_{max}, N_w,

and N_θ controls a tradeoff between high resolution (temporally, and in the space

of threshold values for OTU abundance/slope) and performance. It is

recommended to choose N_w as large as possible while ensuring that most basic

time windows include at least one observation from every subject, and to set $N_\theta =$

40; t_{min} should generally be set to 0 and t_{max} to either the duration of the study or

(to enforce temporal localization of the rules in cases where, e.g., dramatic

increases in abundance at a well-defined time also lead to notable increases in

average abundance over the period of the entire study) half that duration, but may

be adjusted if dynamics on a particular time scale are of *a priori* interest.

Model inference

We perform approximate Bayesian inference, to learn the posterior distribution

over model parameters including rule sets R and regression coefficients β. MITRE

employs a custom Markov Chain Monte Carlo (MCMC) algorithm, which alternates

efficient updates of the regression coefficients using a Polya-Gamma auxiliary

variable scheme [28], Metropolis-Hastings update steps that propose changes to

the rule set R, and updates to the hyperparameters governing the prior distribution

over rule sets. The MCMC algorithm is described in detail in the Supplementary

Note. Briefly, four types of updates to R are considered:

1. A randomly-chosen detector in R may be replaced by another detector from

the pool

2. A randomly-chosen detector in R may be removed from R (if it is the only

detector in a rule, the rule is removed as well)

3. A detector from the pool may be added to R, either to an existing rule

chosen at random, or to form a new rule of length 1

4. A detector may be moved from one rule in R to another

For the analyses presented here, 50,000 samples were drawn from the posterior

distribution (except for analyses of data from Vatanen et al. [6], where 25,000

samples were used, and Kostic et al. [5], where 100,000 samples were used.)

Mixing of the MCMC sampler was assessed using the diagnostics described in the

Supplementary Note; we recommend users employ these diagnostics to determine

the appropriate number of samples needed for their particular studies.

Run time depends on the size and complexity of the data set; using a single Intel

Xeon CPU (E5-2697 v3 2.60GHz), sampling took 45 minutes for the data of

DiGiulio et al. [7], 23 hours for the data of David et al. [3], 30 hours for the data of

Bokulich et al. [2], and 64.5 hours for the data of Vatanen et al. [6]. Cross-validation

was performed in parallel (1 fold/core) requiring similar total elapsed time for each

study.

Data simulation

We simulated from the Bokulich et al. [2] dataset using a parametric bootstrapping-

style procedure. Simulated subjects were sampled with replacement from the set

of control subjects in the real data. Equal numbers of simulated cases and control

subjects were generated for each scenario. In order to have sufficient real data to

bootstrap to evaluate the range of scenarios of interest, we excluded subjects with

fewer than 13 time-points sampled, who had no samples before 10 days, and who

were studied for less than 600 days; this yielded 20 subjects for bootstrapping. We

then truncated data to an interval between 10 and 600 days, since this contained

the densest sampling across subjects.

Perturbations of duration 120 days, in time windows randomly occurring

throughout the experiment, were introduced into randomly selected clade(s) to

simulate cases, with the magnitude of the perturbation distributed among clade

members according to the relative abundance of members in the original data. The

duration of the perturbation(s) was chosen to be approximately of the order of that

seen with the MITRE point rule on the real data set. Perturbations were introduced

randomly into clades with the following characteristics: minimum average relative

abundance of 0.1%, maximum average relative abundance of 20%, and a

maximum of 30 OTUs in the clade. These parameters were chosen so as to

provide a meaningful relative disturbance to other clades, but not to drastically

disrupt the entire microbiome (which would present less of a challenge to the

prediction algorithms.) The magnitude of perturbation(s) were sampled for each

subject from log-normal distributions, with mean and variance of the order of that

seen with the MITRE point rule on the real data set (control log mean = -6, control

std = 1.5, case log mean = -3, case log std = 1.5). When two perturbations were

applied, each control subject received only one perturbation, whereas case

subjects received both perturbations.

Note that MITRE is a supervised learning (conditional) method, meaning that the

microbiome data itself is not modeled; to simulate time-points not present in the

original data set, we therefore must introduce a model of microbiome dynamics.

We model the underlying microbiome data as arising from latent time-dependent

stochastic processes (Gaussian random walks):

$$x_{os}(t) \sim \mathrm{Normal}_+(x_{os}(t-1), \Delta t \tau^2)$$

Here, $x_{os}(t)$ is the latent trajectory for OTU o in subject s at time t, and τ^2 is the

process variance parameter, which is empirically estimated from the real data as

approximately the 75-percentile variance. We assume a Bayesian model and infer

the posterior latent trajectories using a 1-step ahead MCMC algorithm similar to

our previously described method [29], except in this case trajectories are assumed

to be independent of one another.

The observed data $c_s(t)$, consisting of sequencing counts, is assumed to arise

through a two-stage error model:

$$y_{os}(t) \sim \text{Normal}_+(x_{os}(t), \theta x_{os}(t))$$

$$m_s(t) = \sum_o y_{os}(t)$$

$$C_s(t) \sim \text{DMD}(y_s(t)/m_s(t), \alpha, N)$$

Here, DMD denotes the Dirichlet-Multinomial distribution with concentration

parameter α and number of simulated sequencing reads per sample N; we use

parameters estimated from data (a = 286; N = 50,000) as previously described

[14].

The model thus provides temporal coherence through the Gaussian random walk

latent trajectory, while modeling compositionality and over-inflation through the

two-stage error model. Posterior samples from the model capture temporal trends

seen in the real data (e.g., periods of time in which a particular OTU are

increasing), but with randomness introduced so that subjects sampled with

replacement look sufficiently different.

For each scenario simulated (e.g., a particular number of time-points or subjects),

10 independent simulations were performed. To investigate the effects of varying

the number of subjects, we fixed the simulation at an intermediate number of time-

points (18), and simulated different numbers of subjects. Similarly, to investigate

the effects of varying the number of time-points, we fixed the simulation at an

intermediate number of subjects (32), and simulated different numbers of time-

points. To facilitate comparisons, we sampled evenly spaced time-points in all

cases. The simulated data were then provided to MITRE and the other methods in

the same input format as for real data, as described below. Complete Python code

to reproduce the simulations is available in the MITRE online repository.

Output

MITRE generates several summaries from the posterior samples obtained from

the MCMC inference procedure described above. The *point estimate* is a single

rule set R^* (with coefficients β^*) that summarizes the mode of the posterior

distribution. If the posterior probability that R is empty is greater than 0.5, the point

estimate is the empty rule set. Otherwise, to obtain a representative non-empty

summary list, we determine the posterior mode d^* of the total number of detectors

in R, and take R^* to be the rule set with the highest posterior probability among all

sampled rule sets that contain d^* total detectors. The point estimate coefficients β^*

are the highest posterior probability sampled coefficients associated with R^*.

To provide an overview of the possible alternative rule sets learned by the model,

rule sets in the posterior samples are clustered and a summary of the highest-

probability clusters is produced. The clustering process first forms clusters of

detectors that apply to the average value or slope of the same variable in highly

overlapping time windows (ignoring threshold values), then clusters together rules

whose component detectors belong to the same clusters, and finally groups rule

sets whose rules belong to the same clusters (see the Supplementary Note for a

full description.) For each cluster, a representative rule set and the estimated

posterior probability that R^* belongs to the cluster are reported.

Calculation of the Bayes factor for the empty rule set R_0 (vs any non-empty R) and

two additional types of Bayes factors, indicating the relevance of phylogenetic

subtrees or time-windows, is described in the Supplementary Note.

Finally, MITRE generates an interactive graphical visualization of the posterior

distribution of rule sets. A heatmap of the Bayes factors for leaf variable/basic time

window combinations is rendered alongside the bacterial phylogeny (as in figure

3A, 3D); clicking on any cell allows the visualization of the detectors associated

with the cell with the largest Bayes factors (as in figure 3B-C and 3E.)

Data preprocessing and filtering

MITRE offers a number of user-configurable options for preprocessing and filtering

microbiome time-series data. The following procedure is recommended, and was

used for the results presented here (except as noted below):

1. To remove potentially spurious rare OTUs, discard all OTUs with less than
   $N_{counts,OTU}$ observed across all samples (typically $N_{counts,OTU}$ = 10.)

2. To exclude samples where coverage is so low that abundance estimates
   for uncommon OTUs may be unreliable, discard all samples with less than
   $N_{counts,sample}$ total counts observed across all remaining OTUs (typically
   $N_{counts,sample}$=5000 for HiSeq/MiSeq data.)

3. If desired, to analyze only a particular time period (because, e.g., samples
   are not available outside that period for the majority of subjects) discard all
   samples before time t_i and after time t_f (by default, t_i is the time of the earliest
   available sample, and t_f the time of the latest sample.)

4. To exclude subjects for whom microbiome dynamics cannot be resolved at
   the desired temporal resolution throughout the entire study, discard
   subjects with too few, or too sparse, observation points, by dividing the
   duration of the study into $N_{w,filter}$ equal pieces and keeping only subjects with
   at least N_s samples in any N_c consecutive such pieces. Default values are
   $N_{w,filter}$=10, N_s = 2, and N_c=1; note that for data with very inconsistent

sampling, these parameters must be chosen judiciously to maximize the

number of subjects included while allowing an acceptable level of temporal

resolution.

After these steps, counts data are converted to relative abundance data for each

sample, and, for each node in the phylogenetic tree, a relative abundance estimate

is obtained by summing the relative abundances of its children. The following

filtering steps are then applied to all taxa (both OTUs and higher nodes in the tree):

5. To exclude low abundance taxa (for which abundance estimates may be

inaccurate) or infrequently observed taxa (which we expect are unlikely to

be explanatory, though higher taxa including them may be), discard all taxa

except those that exceed a threshold abundance a in at least N_a

consecutive samples in at least N_i subjects. Typically, $N_a=2$. Appropriate

values for a and N_i depend on the number of subjects and typical reads per

sample; for studies with 10-150 subjects and average reads per sample on

the order of 10^4, we recommend $a=10^{-4}$ and $N_i=4$ or 10% of the number of

subjects, whichever is larger.

6. To minimize redundancy, discard all taxa corresponding to nodes in the

phylogenetic tree with exactly one remaining child taxon, as their temporal

patterns are often very similar to those of their children.

Note that, when a large number of taxa are considered, the detector pool becomes

large and the computational cost of the inference algorithm grows; if necessary, it

is recommended to increase the stringency of steps 5 and 6 to keep the total

number of taxa below 500.

Bioinformatics and preprocessing for analyzed datasets

For each 16S-based dataset to which MITRE was applied, the original 16S rRNA

amplicon sequencing data was reprocessed to obtain tables of OTU abundances

and phylogenetic placements for each OTU on a reference tree, using as

consistent an analysis process as possible given differences in sequencing

methodology and the nature of the available data. Where possible, DADA2 1.1.5

[30] was used to trim, quality filter, merge, and remove chimeras from the reads,

assign them to inferred true sequences, and classify the inferred sequences

taxonomically (such classification is not necessary for MITRE application, but is

helpful for interpretation of the results.) Inferred sequences were then placed on

a reference tree generated from full-length or near full-length (>1200 nt) 16S rDNA

sequences of type strains from the Ribosomal Database Project [31] using pplacer

[18]. When quality scores for sequences were not available and DADA2 could not

be used, sequences were instead processed using mothur 1.35.1 [32, 33] for

denoising, quality filtering, alignment against the ARB Silva 16S gene sequence

reference database, clustering into OTUs at 97% identity, and taxonomic

classification. For the WGS metagenomics data of Kostic et al [5], published

taxonomic abundance tables were used directly as input data to MITRE, exploiting

MITRE's built-in support for parsing Metaphlan result tables, described in the

MITRE manual. Full details regarding pre-processing of all datasets are described

in the Supplemental Note.

After reanalyzing sequencing data for each study and excluding subjects with

infrequent sampling (see description of filtering methods above) we applied MITRE

and the comparator methods to classify subjects according to relevant categories:

membership in the Russian cohort (n=30), elevated IgE levels (n=28), diagnosis

with any allergy (n=49), any dietary allergy (n=42), with dairy allergy (n=32), or with

egg allergy (n=25) in the data of Vatanen et al. (n=113 total for nationality; n=109

total for all other outcomes); formula-dominant diet (n=11) or Cesarean delivery

(n=13) in the data of Bokulich et al. (n=35 total); seroconversion (n=11) in the data

of Kostic et al. (n=19 total); premature delivery (n=6) in the data of DiGiulio et al.

(n=37 total); and plant-based diet (n=10) in the data of David et al. (n=20 total.)

Comparison methods

To compare MITRE's predictive performance to alternative methods, each OTU's

abundance data for each subject was averaged across all observations within each

of a set of time windows, defined by dividing the experiment into $N_{w,comparison}$ equal

intervals and taking any consecutive $N_{c,comparison}$ such intervals as a valid time

window. Parameters were chosen to maximize temporal resolution while ensuring

that each time window still contained at least one observation for each subject.

Note that the same subjects were used (i.e., those not excluded by the

preprocessing settings described above) for both MITRE and the comparison

methods. For David et al. [3], $N_{w,comparison}$=10 and $N_{c,comparison}$=3; for Vatanen et al.

[6], $N_{w,comparison}$=9 and $N_{c,comparison}$=4; for DiGiulio et al. [7],

$N_{w,comparison}$=$N_{c,comparison}$=1; for Bokulich et al. [2], $N_{w,comparison}$=12 and $N_{c,comparison}$=2;

for Kostic et al. [5], $N_{w,comparison}$=5 and $N_{c,comparison}$=2.

These averaged abundances were then used to train Random Forest or logistic

regression classifiers using the Python package scikit-learn [34]. Random Forest

classifiers included 1024 trees (as larger numbers of trees were not found to

improve classifier performance.) For logistic regression with L1 regularization, the

regularization strength parameter was chosen using 10-fold crossvalidation from

among a grid of logarithmically spaced options spanning the range 10^{-4} to 10^4.

Declarations

Acknowledgements: We thank Daniel DiGiulio for assistance with the data from

reference [7], and Travis Gibson for helpful comments on the manuscript.

Funding: This work was supported by the Brigham and Women's Hospital

Precision Medicine Initiative and NIH 5R01GM130777 to GKG. EB received

support from NIH grant T32HL007627.

Availability of data and materials:

The MITRE software package is available at: https://github.com/gerberlab/mitre/ .

All additional input files needed to reproduce the results presented here, and

detailed output from all MITRE simulations discussed, are available at

https://github.com/gerberlab/mitre_paper_results.

Datasets analyzed during the current study are available: data from Bokulich et

al. [2], from ENA (https://www.ebi.ac.uk/ena/data/view/PRJEB14529) and QIITA

(https://qiita.ucsd.edu, study 10249); data from David et al. [3], from MG-RAST

(http://metagenomics.anl.gov/linkin.cgi?project=mgp6248); data from Kostic et al.

[5], via the DIABIMMUNE project web site

(https://pubs.broadinstitute.org/diabimmune/t1d-cohort); data from Vatanen et al.

[6], via the DIABIMMUNE project web site

(https://pubs.broadinstitute.org/diabimmune/three-country-cohort); data from

DiGiulio et al. [7], on request from those authors.

Authors' contributions: EB and GKG conceived the method, developed the theory,

and wrote the manuscript. EB wrote the software, curated the relevant data, and

formally analyzed and validated the method and software. RC contributed to the

software and analysis and validation of the method.

Ethics approval and consent to participate: Not applicable

Consent for publication: Not applicable

Competing interests: GKG is a Strategic Advisory Board Member of Kaleido

Biosciences and has a sponsored research agreement with the company, and is

a Scientific Advisory Board Member, co-founder, and shareholder of ConsortiaTX.

No funding for the present work was provided by either company.

References

1. Gerber, G.K., *The dynamic microbiome.* FEBS Lett, 2014. **588**(22): p. 4131-9.
2. Bokulich, N.A., et al., *Antibiotics, birth mode, and diet shape microbiome*
maturation during early life. Sci Transl Med, 2016. **8**(343): p. 343ra82.
3. David, L.A., et al., *Diet rapidly and reproducibly alters the human gut*
microbiome. Nature, 2014. **505**(7484): p. 559-63.
4. Yassour, M., et al., *Natural history of the infant gut microbiome and impact of*
antibiotic treatment on bacterial strain diversity and stability. Sci Transl Med,
2016. **8**(343): p. 343ra81.
5. Kostic, A.D., et al., *The dynamics of the human infant gut microbiome in*
development and in progression toward type 1 diabetes. Cell Host Microbe,
2015. **17**(2): p. 260-73.
6. Vatanen, T., et al., *Variation in Microbiome LPS Immunogenicity Contributes to*
Autoimmunity in Humans. Cell, 2016. **165**(4): p. 842-53.
7. DiGiulio, D.B., et al., *Temporal and spatial variation of the human microbiota*
during pregnancy. Proc Natl Acad Sci U S A, 2015. **112**(35): p. 11060-5.
8. Romero, R., et al., *The vaginal microbiota of pregnant women who*
subsequently have spontaneous preterm labor and delivery and those with a
normal delivery at term. Microbiome, 2014. **2**: p. 18.
9. Raveh-Sadka, T., et al., *Gut bacteria are rarely shared by co-hospitalized*
premature infants, regardless of necrotizing enterocolitis development. Elife,
2015. **4**.
10. Zhou, Y., et al., *Longitudinal analysis of the premature infant intestinal*
microbiome prior to necrotizing enterocolitis: a case-control study. PLoS One,
2015. **10**(3): p. e0118632.
11. Pop, M., et al., *Individual-specific changes in the human gut microbiota after*
challenge with enterotoxigenic Escherichia coli and subsequent ciprofloxacin
treatment. BMC Genomics, 2016. **17**: p. 440.
12. van Rensburg, J.J., et al., *The Human Skin Microbiome Associates with the*
Outcome of and Is Influenced by Bacterial Infection. MBio, 2015. **6**(5): p.
e01315-15.

13. Tandon, D., M.M. Haque, and S.S. Mande, *Inferring Intra-Community Microbial*
Interaction Patterns from Metagenomic Datasets Using Associative Rule Mining
Techniques. PLoS One, 2016. **11**(4): p. e0154493.
14. Bucci, V., et al., *MDSINE: Microbial Dynamical Systems INference Engine for*
microbiome time-series analyses. Genome Biol, 2016. **17**(1): p. 121.
15. Subramanian, S., et al., *Persistent gut microbiota immaturity in malnourished*
Bangladeshi children. Nature, 2014. **510**(7505): p. 417-21.
16. Sze, M.A. and P.D. Schloss, *Looking for a Signal in the Noise: Revisiting Obesity*
and the Microbiome. MBio, 2016. **7**(4).
17. Teng, F., et al., *Prediction of Early Childhood Caries via Spatial-Temporal*
Variations of Oral Microbiota. Cell Host Microbe, 2015. **18**(3): p. 296-306.
18. Matsen, F.A., R.B. Kodner, and E.V. Armbrust, *pplacer: linear time maximum-*
likelihood and Bayesian phylogenetic placement of sequences onto a fixed
reference tree. BMC Bioinformatics, 2010. **11**: p. 538.
19. Lu, J., P. Shi, and H. Li *Generalized Linear Models with Linear Constraints for*
Microbiome Compositional Data. ArXiv e-prints, 2018.
20. Crost, E.H., et al., *The mucin-degradation strategy of Ruminococcus gnavus:*
The importance of intramolecular trans-sialidases. Gut Microbes, 2016. **7**(4):
p. 302-312.
21. Berry, D.A., *Bayesian clinical trials.* Nat Rev Drug Discov, 2006. **5**(1): p. 27-36.
22. Donald, B. and D. Rubin, *Fisher, Neyman, and Bayes at FDA.* Journal of
Biopharmaceutical Statistics, 2016. **26**: p. 1020-1024.
23. Wasserstein, R. and N. Lazar, *The ASA's Statement on p-Values: Context,*
Process, and Purpose. The American Statistician, 2016. **70**: p. 129-133.
24. Kass, R. and A. Raftery, *Bayes Factors.* J. Am. Stat. Assoc., 1995. **90**: p. 773-
795.
25. Friedman, J. and B. Popescu, *Predictive learning via rule ensembles.* Ann. Appl.
Stat., 2008. **2**: p. 916–954.
26. Letham, B., et al., *Interpretable classifiers using rules and Bayesian analysis:*
Building a better stroke prediction model. Ann. Appl. Stat., 2015. **9**: p. 1350–
1371.
27. Urbanowicz, R. and J. Moore, *Learning Classifier Systems: A Complete*
Introduction, Review, and Roadmap. J. Artif. Evol. Appl. , 2009: p. 1-25.
28. Polson, N., J. Scott, and J. Windle, *Bayesian Inference for Logistic Models Using*
Pólya–Gamma Latent Variables. J. Am. Stat. Assoc. , 2013. **108**: p. 1339–1349.
29. Gibson, T. and G. Gerber, *Robust and Scalable Models of Microbiome Dynamics*,
in *Thirty-fifth International Conference on Machine Learning*. 2018:
Stockholm.
30. Callahan, B.J., et al., *DADA2: High-resolution sample inference from Illumina*
amplicon data. Nat Methods, 2016. **13**(7): p. 581-3.
31. Cole, J.R., et al., *Ribosomal Database Project: data and tools for high*
throughput rRNA analysis. Nucleic Acids Res, 2014. **42**(Database issue): p.
D633-42.
32. Schloss, P.D., et al., *Introducing mothur: open-source, platform-independent,*
community-supported software for describing and comparing microbial
communities. Appl Environ Microbiol, 2009. **75**(23): p. 7537-41.

33.   Kozich, J.J., et al., *Development of a dual-index sequencing strategy and*
874   *curation pipeline for analyzing amplicon sequence data on the MiSeq Illumina*
875   *sequencing platform.* Appl Environ Microbiol, 2013. **79**(17): p. 5112-20.
876   34.   Pedregosa, F., et al., *Scikit-learn: Machine Learning in Python.* J. Mach. Learn.
877   Res., 20122. **12**: p. 2825-2830.

Figures

Figure 1: MITRE learns human-interpretable rule-based models predicting

host status from microbiota time-series data. Rules operate on automatically

learned time-periods and groups of phylogenetically related microbes. **(A)**

Schematic of the MITRE analysis pipeline, resulting in a single best predictive

model as well as a distribution over alternative models that can be interactively

explored. **(B)** Schematic of example rule in **(A)** applied to hypothetical data. Here,

two subjects satisfy both the condition on the average abundance of microbe group

A and the rate of change of abundance of group B.

Figure 2: Cross-validated predictive performance of MITRE and comparator

methods on semi-synthetic and real data. **(A-D)** Results on semi-synthetic

data. A parametric bootstrapping-type method was used to generate simulated

data from an underlying real dataset. Simulated cases were generated by

randomly selecting and perturbing bacterial clades over a randomly selected

limited time-window (~20% of the duration of the study); an equal number of

control subjects were simulated. For the one clade perturbation scenarios, the

clade remained unperturbed for the simulated cases; for the two clade

perturbation scenarios, one clade was perturbed in the simulated control

subjects, and both were perturbed in the simulated cases. **(A-B)** One or two

clades randomly perturbed in simulated subjects, 18 time-points, varying

numbers of subjects. **(C-D)** One or two clades randomly perturbed in simulated

subjects, 32 subjects, varying numbers of time-points. **(E)** Results on real data.

The different methods were used to predict the indicated categories in the

datasets shown. F1-score is the harmonic mean of precision and recall; higher

scores indicate superior results.

Figure 3. MITRE supports exploratory analyses through an interactive visualization interface. The interface allows the user to explore the distribution of learned rules. MITRE was applied to predict diet type from data from David et al. [3] **(A-C)** or Bokulich et al. [2] **(D-E)**. In **(A)** and **(D)**, cell colors indicate the strength of evidence that the dynamics of an OTU, or one of its ancestors, during a time window is associated with diet. Panels **(B)**, **(C)**, and **(E)** show high-probability detectors and phylogenetic subtrees to which they apply. **(B-C)** Analyses reveals

dynamic behaviors of two different clades, one with butyrate producers and the

other without, which distinguish subjects on plant or animal-based diets. The

animal-based diet thus promotes two groups of phylogenetically distinct microbes

which are also likely functionally distinct. **(E)** Analyses reveal dynamic behavior of

a clade of bacteria, associated with a more mature microbiome, which is increased

in the predominantly formula-fed infants, suggesting the formula diet may shift

infants toward more adult-like gut microbiota. Red lines, threshold

slopes/abundances; black lines, median slopes/abundances. Median effect =

median over all rules containing the detector.