Studying Human Behaviour with Virtual Reality: The Unity Experiment Framework

Jack Brookes*[1], Matthew Warburton[1], Mshari Alghadier[1], Mark Mon-Williams[1,2], & Faisal Mushtaq*[1,2]

[1]School of Psychology, University of Leeds, Leeds, West Yorkshire, United Kingdom

[2]Centre for Immersive Technologies, University of Leeds, Leeds, West Yorkshire, United Kingdom

*Correspondence can be addressed to Jack Brookes or Faisal Mushtaq at School of Psychology, University of Leeds, Leeds, United Kingdom. Email: jbrookes187@gmail.com; f.mushtaq@leeds.ac.uk

Article Type: Original Research Article

Number of Figures: 7

Total Word Count: 5248

Keywords: Virtual reality, Unity, Software, Experiment, Behaviour, Toolkit

Abstract

Virtual Reality systems offer a powerful tool for human behaviour research. The ability to create three-dimensional visual scenes and measure responses to the visual stimuli enables the behavioural researcher to test hypotheses in a manner and scale that were previously unfeasible. For example, a researcher wanting to understand interceptive timing behaviour might wish to violate Newtonian mechanics, so objects move in novel 3D trajectories. The same researcher may wish to collect such data with hundreds of participants outside the laboratory (e.g. in a museum), and the use of a VR headset makes this a realistic proposition. The difficulty facing the researcher is that sophisticated 3D graphics engines (such as Unity) have been created for game designers rather than behavioural scientists. In order to overcome this barrier, we have created a set of tools and programming syntaxes that allow logical encoding of the common experimental features required by the behavioural scientist. The Unity Experimental Framework (UXF) allows the researcher to readily implement several forms of data collection, and provides researchers with the ability to easily modify independent variables. UXF does not offer any stimulus presentation features, so the full power of the Unity game engine can be exploited. We use a case study to show how UXF can support behavioural research and remote deployment of experiments (where data are streamed over the internet and accessed later by researchers). In summary, UXF presents an opportunity to simplify and speed up development of virtual reality experiments created in commercial VR software.

Introduction

Virtual Reality (VR) systems are opening up new opportunities for behavioural research as they allow visual (and auditory) stimuli to be displayed in 3D computer generated environments that can correspond to the participant's normal external Cartesian space, but which do not need to adhere to the rules of Newtonian mechanics(Wann & Mon-Williams, 1996). Moreover, VR systems support naturalistic interactions with virtual objects and can provide precise measures of the kinematics of the movements made by adults and children in response to displayed visual stimuli. In addition, the relatively low cost and portability of these systems lowers the barriers to performing research in non-laboratory settings.

The potential advantages of VR in behavioural research have been recognised for at least two decades (e.g. Loomis, Blascovich, & Beall, 1999) but recent advantages in technology and availability of hardware and software are making VR a feasible tool for all behavioural researchers (rather than a limited number of specialist VR labs). For example, researchers can now access powerful software engines that allow the creation of rich 3D environments. One such popular software engine is Unity (alternatively called Unity3D) (Unity Technologies, 2018). Unity is a widely used 3D game engine for developing video games, animations and other 3D applications and it is growing in its ubiquity. It is increasingly being used in research settings as a powerful way of creating 3D environments for a range of applications (e.g. psychology experiments, surgical simulation, rehabilitation systems). The recent popularity of virtual reality head-mounted displays has meant that Unity has become widely used by games developers for the purpose of crating commercial virtual reality (VR) content. Unity has well developed

systems in place for rich graphics, realistic physics simulation, particles, animations and

more. Nevertheless, it does not contain any features specifically designed for the needs

of human behaviour researchers. We set out to produce an open source software

resource that would empower researchers to exploit the power of Unity for behavioural

studies.

A literature search of human behavioural experiments reveals that experiments

are often defined by a common model, one that more easily allows researchers to

exercise the scientific method. Experiments are often composed of trials, where trials

can be defined as an instance of a scenario. Trials are usually composed of a stimulus

and a human response and are a basic unit of behavioural experiments. Trials can be

repeated many times for a single participant, increasing the signal-to-noise ratio of

measurements, or allowing the study of human behaviour over time (e.g. adaptation and

learning). Blocks can be defined as a grouping of trials that share something in

common; comparing measures between blocks allows the examination of how

substantial changes to the scenario affect the response. A session is a single iteration

of the task with a participant. Defining an experiment in such a session-block-trial model

(**Figure 1**) allows the definition and communication of an experimental design without

ambiguity.

Figure 1. Structure of typical human behaviour experiments, in the session-block-trial model. Many experiments comprise multiple repetitions of trials. Between trials, only minor changes are made. A substantial change of content in the trial is often described as creating a new "block". A single iteration of a task by a participant is called a session.

The use of this session-block-trial model in computer-based experiments affords a

certain type of system design structure that mirrors the model itself. Typically, the code

produced for an experimental task consists of a loop, where the process of presenting a

stimulus and measuring a response is repeated many times, sometimes changing the

parameters between loop iterations. The popularity of this experimental architecture

means that researchers have attempted to provide tools that allow the development of

tasks without the need to 'reinvent the wheel'. Relatedly, development of the stimuli for

software experiments is often difficult without knowledge of low-level computer

processes and hardware. Thus, several software packages have been released which

aim to make the stimuli themselves easier to specify in code. There is some crossover

between these two types of packages, some focus only on stimuli whilst others also

provide high-level ways to define the trials and blocks of the experiment.

PsychToolbox (Brainard, 1997) is a software package for MATLAB that allows

researchers to program stimuli for vision experiments, providing the capability to

perform low-level graphics operations but retaining the simplicity of the high-level

interpreted MATLAB language. PsychoPy (Peirce, 2007) is an experimental control

system that provides a means of using the Python programming language to

systematically display stimuli to a user with precise timing. It consists of a set of

common stimulus types, built-in functions for collection and storage of user

responses/behaviour, and means of implementing various experimental design

techniques (such as parameter staircases). PsychoPy also attempts to make research

accessible for non-programmers with its 'builder', a GUI that allows development of

experiments with little to no computer programming requirements.

The graphics processes for immersive technologies are significantly more

complex than those required for two dimensional displays. In VR, it is difficult to think of

stimuli in terms of a series of coloured pixels. The additional complexity includes a need

for stimuli to be displayed in apparent 3D to simulate the naturalistic way objects appear

to scale, move and warp according to head position. Unity and other game engines

have the capacity to implement the complex render pipeline that can accurately display

stimuli in a virtual environment; current academic focused visual display projects may

not have the resources to keep up with the evolving demands of immersive technology

software.

The Unity Experiment Framework (UXF)

In order to provide behavioural researchers with the power of Unity but the convenience

of programmes such as PsychoPy, we created the Unity Experiment Framework (UXF).

UXF is a software framework for the development of human behaviour experiments with

Unity. UXF takes common programming concepts and features that are widely used,

and often re-implemented for each experiment, and implements them in a generic

fashion (**Table 1**). This gives researchers the tools to create their experimental software

without the need to re-develop this common set of features. UXF aims to specifically

solve this problem, and overtly excludes any kind of stimulus presentation system, with

the view that Unity (and its large asset developing community) provides all the

necessary means to implement any kind of stimulus or interaction system for an

experiment. In summary, UXF provides the 'nuts and bolts' that work behind the scenes

of an experiment developed within Unity.

Table 1. Common experiment concepts and features which are represented in UXF

Concept	Description
Trial	The base unit of experiments. A trial is usually a singular attempt at a task by a participant after/during the presentation of a stimulus.
Block	A set of trials – often used to group consecutive trials that share something in common.
Session	A session encapsulates a full "run" of the experiment. Sessions are usually separated by a significant amount of time and could be within subjects (for collection of data from a singular participant over several sessions) and/or between subjects (for collection of data from several participants each carrying out a single session).
Settings	Settings are parameters or variables for an experiment, block, or trial, usually predetermined, that quantitatively define the experiment. Settings are useful for defining the experimental manipulation (i.e. the independent variables).
Behavioural data	We perform an experiment to measure the effect of an independent variable on a dependent variable. Behavioural data collection allows for the collection of measured values of dependent variables on a trial-by-trial basis. For example, we may wish to collect the response to a multiple-choice question, or the distance a user throws a virtual ball.

Continuous data	Within a trial, we may want to measure a value of one or more parameters over time. Most commonly we want to record the position and rotation of an object within each trial. This could be an object that is mapped to a real-world object (e.g. participant head, hands) or a fully virtual object (virtual ball in a throwing experiment). Position and rotation of an object is the main use case but UXF supports measurement of any parameter over time (e.g. pressure applied to a pressure pad).
Participant information	There may be other variables that we cannot control within the software which we may wish to measure to record to examine its relationship to the result. For example, age or gender of the participant.

Experiment structure

UXF provides a set of high-level objects that directly map onto how we describe

experiments. The goal is to make the experiment code more readable and avoid the

temptation for inelegant if-else statements in the code as the complexity increases.

Session, blocks, trials are our 'objects' which we can be represented within our code.

The creation of a session, block or trial automatically generates properties we would

expect them to have – for example each block has a block number, each trial has a trial

number. These numbers are automatically generated as positive integers based on the

order in which they were created. Trials contain functionality such as 'begin' and 'end'

which will perform useful tasks implicitly in the background, such as recording the

timestamp when the trial began or ended.

Measuring dependent variables

While the trial is ongoing, at any point we can add any observations to the results of the

trial, which will be added to the behavioural data output file at the end of the session.

Additionally, we can continuously log a variable over time. The main use case of this is

where the position and rotation of any object in Unity can be automatically recorded on

a per-trial basis, saving a single file for each trial of the session. This allows for easy

cross-referencing with behavioural data. All data files (behavioural, and continuous) are

stored in a directory structure organised by *experiment > participant > session number*.

Setting independent variables

Settings can be used to attach values of an independent variable to an experiment,

session, block, or trial. Settings have a cascading effect, whereby one can apply a

setting to the whole session, a block or a single trial. When attempting to access a

setting, if it has not been assigned in the trial, it will attempt to access the setting in the

block. If it has not been assigned in the block, it will search in the session (Figure 2).

This allows users to very easy implement features common to experiments, such as

"10% of trials contain a different stimulus". In this case, one could assign a "stimulus"

setting for the whole session, but then assign 10% of the trials with a different value for

a "stimulus" setting.

Settings are also a useful feature for allowing for changing experimental parameters

without modifying the source code. A simple text file can be placed in the experiment

directory which will be read upon the start of a session, and its settings applied to that

session. This system speeds up the iteration time during the process of designing the

experiment; the experimenter can change settings from this file and see their immediate

effect without changing any of the code itself.

It also allows multiple versions of the same experiment (e.g. different experimental

manipulations) to be maintained within a single codebase using multiple settings files.

Using the UI, the experimenter can select one of these settings profiles on launching the

experiment.

Figure 2. The UXF Settings system. Independent variables that we change in order to iterate a design of
an experiment, or to specify the experimental manipulation itself, can be written in a human-readable .json
file. Settings can also be programmatically accessed or created at trial, block or session level. Where a
setting has not been specified, the request cascades up and searches the in the next level above. This
allows both "gross" (e.g. to a whole session) or "fine" (e.g. to a single trial) storage of parameters within the
same system.

Experimenter UI

UXF includes an (optional) experimenter user interface (UI) to allow selection of a

settings profile, and inputting additional participant information, such as demographics.

Information the experimenter wishes to collect is fully customisable. The UI includes

support for a "participant list" system, whereby participant demographic information is

stored in its own CSV file. As new participants perform the experiment, their

demographic information is stored in the list. This allows participant information to be

more easily shared between sessions or even separate experiments – instead of having

to input the information each time, the experimenter can select any existing participant

found in the participant list via a drop-down menu.

Figure 3. Screenshot of the experimenter user interface.

Example

Below is an example of the code used to create a simple 2 block, 10 trial experiment

where the participant is presented with a number x and they must input the doubled

value $(2x)$.

```
198   // create variable: block 1, containing 5 trials
199   var block1 = session.CreateBlock(5);
200   // apply a setting 'manipulation' as false to the whole block
201   block1.settings['manipulation'] = false;
202   // loop over the trials and assign the setting 'x' to a random value
203   foreach (var trial in block1.trials)
204       trial.settings['x'] = Random.Range(1, 10);
205
206   // create variable: block 2, containing 5 trials
207   var block2 = session.CreateBlock(5);
208   // apply a setting 'manipulation' as true for the whole block
209   block2.settings['manipulation'] = true;
210   // loop over the trials and assign a the setting 'x' to a random value
211   foreach (var trial in block2.trials)
212       trial.settings['x'] = Random.Range(1, 10);
213
214   // apply a setting to only the first trial of block 1
215   block1.firstTrial.settings['show_instructions'] = true;
216
217   // begin the first trial...
218   session.firstTrial.Begin();
219
```

Elsewhere in our project, we can define what happens when we begin the trial (such as

making the value of x appear for the participant), and mechanisms to retrieve the

participant's response for the trial (participant's calculated value of $2x$). These are to be

created with standard Unity features for making objects appear in the scene, collecting

user response via keyboard input, etc. The resulting behavioural data .CSV file would

be automatically generated and saved (**Table 2**). A typical structure of a task developed

with UXF is shown in **Figure 4**.

Table 2. Example behavioural data output. Columns not shown include participant ID, session number,
and experiment name.

trial_num	block_num	start_time	end_time	manipulation	x	response
1	1	0.000	1.153	FALSE	8	16
2	1	1.153	2.112	FALSE	3	6
3	1	2.112	2.950	FALSE	4	8
4	1	2.950	3.921	FALSE	7	14
5	1	3.921	4.727	FALSE	4	8
6	2	4.727	5.826	TRUE	9	18
7	2	5.826	6.863	TRUE	5	10

8	2	6.863	7.693	TRUE	10	20
9	2	7.693	8.839	TRUE	6	12
10	2	8.839	9.992	TRUE	3	6

230
231

Figure 4. Structure of a typical task developed with UXF. The left panel shows functionality present in UXF, with functionality a researcher is expected to implement shown on the right panel. The framework features several "events" (shown in red) which are invoked at different stages during the experiment; these allow developers to easily add behaviours that occur at specific times, for example presenting a stimulus at the start of a trial.

Multithreading file I/O

Continuous capture of data requires large amounts of data to be collected over the

course of the experiment. When using a VR head-mounted display, it is essential to

maintain a high frame rate and keep stutters to a minimum to minimise the risk of

inducing sickness or discomfort on the participant. Handling of tasks such as reading

and writing to file may take several milliseconds or more depending on operating

system background work. Constant data collection (particularly when tracking the

movement of many objects in the scene) and writing these data to file therefore poses a

risk of dropping the frame rate below acceptable levels. The solution is to create a multi-

threaded application which allows the virtual environment to continue to be updated

whilst data are being written to files simultaneously in a separate thread. Designing a

stable multithreaded application imparts additional technical requirements on the

researcher. UXF abstracts file I/O away from the developer, performing these tasks

automatically, with a multithreaded architecture working behind the scenes.

Cloud-based experiments

UXF is a standalone, generic project, and so it does not put any large design constraints

on developers using it. This means that UXF does not have to be used in a traditional

lab-based setting, with researchers interacting directly with participants; it can be used

for data collection opportunities outside of the lab, by embedding experiments within

games or apps that a user can partake in at their discretion. Data are then sent to a web

server where it is later downloaded and analysed by researchers (Figure 5). Recently

these cloud-based experiments have become a viable method of performing

experiments on a large scale.

Figure 5. Experiment in the cloud. A piece of software developed with UXF can be deployed to an
internet connected device. Researchers can modify experiment settings to test different experimental
manipulations over time, which are downloaded from the web by the client device upon running a UXF
experiment. As the participant partakes in the experiment, they are presented with stimuli, and their
movements are recorded in the form of behaviours/responses or continuous measurement of parameters
like hand position. Their results are automatically and securely streamed up to a server on the internet, of
which the researcher can periodically retrieve data from.

UXF can be used in cloud-based experiments (**Figure 5**) using two independent pieces

of software that accompany UXF:

1. UXF S3 Uploader allows all files that are saved by UXF (behavioural data,

continuous data, logs) to be additionally uploaded to a location in Amazon's

Simple Storage Service as setup by a researcher. This utilizes existing UXF

functionally of setting up actions for after a file has been written; and so a

developer could potentially implement uploading the files to any other storage

service.

2. UXF Web Settings replaces the default UXF functionality of selection of

experiment settings via a user interface, to the settings being accessed

automatically from a web URL by the software itself. This allows a deployed

experiment (e.g. via an app store, or simply transferring an executable file), to be

remotely altered by the researcher, without any modification to the source code.

Settings files are stored in json format and would usually be of a very small file

size so can be hosted online cheaply and easily.

A developer can implement neither, either, or both, depending on the needs of the

research. For lab-based experiments, neither are required. For experiments without any

need to modify settings afterwards, but with the requirement of securely backing up data

in the cloud, (1) can be used. If a researcher wants to remotely modify settings but has

physical access to the devices to retrieve data, (2) can be used. For a fully cloud-based

experiment without direct researcher contact with the participant both (1) and (2) can be

used. This has been successfully used in the context of a museum exhibition, where

visitors could take part in virtual reality experiments, with the recorded data being

uploaded to the internet. Both UXF S3 Uploader and UXF Web Settings are available as

open source Unity packages.

298 Case study

One classic question in human behavioural research has related to the information used

by adults and children when maintaining posture. There are two possible sources of

information that allow a human to maintain balance when standing – kinaesthetic

information and vision (Wann, Mon-Williams & Rushton 1998). The fact that humans

can maintain standing balance with their eyes closed indicates that kinaesthetic

information is sufficient for postural control (Thomas & Whitney 1959). Nevertheless, it

has been established for well over half a century that posture is more stable when the

eyes are open (Edwards 1946). This phenomenon indicates that visual information

contributes towards postural balance, and raises the issue of how kinaesthetic

information and vision are combined when both are available. This question was

addressed four decades ago by Lee and Aronson (1975) who used a physical 'swinging'

room to perturb the visual information provided by the walls and ceiling whilst leaving

the kinaesthetic information unaffected (only the walls and ceiling swung and the floor

did not move). This experimental manipulation was able to demonstrate the influence of

vision on posture but the scale of the apparatus meant that the experiment could only

ever be implemented in a laboratory setting. The experiment was also subject to

measurement errors and researcher bias (Wann, Mon-Williams & Rushton 1998). In

more recent years, scientists have used conventional computer displays to explore the

impact of vision on posture (e.g. Villard et al 2008). This approach has addressed the

issues of measurement error and researcher bias but still remains confined to the

laboratory.

The ability to create a virtual swinging room in a Virtual Reality environment

provides a test case for the use of UXF in supporting behavioural research. The

implementation of the swinging room inside a Virtual Reality headset can provide a

proof-of-concept demonstration of how large laboratory experiments can be placed

within a non-laboratory setting (such as a museum). The deployment of such a system

in such a setting can also provide proof-of-concept of the usefulness of Virtual Reality in

the provision of behavioural measures. In this test case, we decided to use the head

tracking function as a proxy measure of postural stability (as decreased stability would

be associated with more head sway (Flatters et al., 2014)). In order to test the UXF

software we decided to construct a simple experiment with a within-participant

component (whether the virtual room was stationary or oscillating) and a between-

participant factor (adults vs children). We then deployed the experiment in a museum

with a trained demonstrator and remotely collected data on a hundred participants.

The task was developed in the Unity game engine with UXF handling several

aspects of the experiment including; Participant information collection, Settings,

Behavioural data and Continuous data. *Participant information collection*: The UXF built-

in user interface was used to collect a unique participant ID as well as the participant's

age and gender. This information was stored in a CSV participant list. This list was

subsequently updated with participant height and arm-span as they were collected in

the task. *Settings*: A settings file accompanied the task that allowed modification of the

assessment duration as well as the oscillation amplitude and period without modifying

the code. Settings for each trial were used to construct the environment to facilitate the

requested trial condition. *Behavioural data*: While there were no dependant variables

that were directly measured on each trial, the UXF behavioural data collection system

output a list of all trials that were run in that session, as well as the vision condition for

that trial. *Continuous data*: UXF was configured to automatically log the HMD position

over time within each trial, which was then used offline for the stability measure

calculation. UXF split the files with one file per trial which was designed to make it easy

to match each file with the trial condition the file was collected under.

Methods

Fifty children (mean age: 9.6 years; sd: 2.0 years) and 50 adults (mean age: 27.5 years;

sd: 13.2 years) took part in the study (children defined here as under 16 years old).

Participants were recruited from either the University of Leeds participant pool (adults),

or were attendees at the Eureka! Science museum (children and adults) and gave full

consent for their data to be collected. A gaming-grade laptop (Intel Core i5-7300HQ,

Nvidia GTX 1060) in addition to a VR HMD (Oculus Rift CV1) were used to present

stimuli and collect data. The HMD was first calibrated using the built-in procedure, which

additionally sets the virtual floor level to match the physical floor.

After explaining the requirements of the task, the demonstrator put the HMD on

the participant's head (over spectacles if necessary) and adjusted it until the participant

reported it was comfortable and they could see clearly. Participants were given an

Oculus Touch hand controller to hold in each hand and were then placed in the centre

of a simple virtual room (height: 3m, width: 6m, depth: 6m) with textured walls and floors

(Figure 6). First, participants were told to stand up straight and look directly forward,

stretching their arms out horizontally as wide as possible. At this point the demonstrator

pushed a button on the laptop to record the participant's height and arm span. Height

was measured as vertical distance from the floor to the "centre eye" of the participant

(as reported by the SteamVR API). Arm span was measured as the absolute distance

between the two hand controllers. The height was used to place a fixation cross on the

wall at the participant's height; arm-span was not used within the experiment.

Figure 6. Screenshot from inside the virtual room. Arrows indicate the three axes as well as the origin.
The red fixation cross is shown on the wall.

The task consisted of two trials, each lasting 10 seconds, performed in a random

order. The *normal* condition asked participants to stand still and look at a fixation cross

placed on the wall. In the *oscillating* condition, the participants were given the same

instructions, but we made the virtual room oscillate in a sinusoidal fashion (rotating

around the x axis) with an amplitude of 5° and a frequency of 0.25 Hz. The oscillation

was performed about the point on the floor at the centre of the room, in effect keeping

the participant's feet fixed in-place. Participants were not explicitly informed about the

room oscillation. The position of the HMD inside the virtual room was logged at a rate of

90Hz during each of the two trials. The path-length of the head was used as a proxy

measure of postural stability (sum of all point-to-point distances over a trial).

Results

No participants reported any feelings of sickness or discomfort during or after taking

part in the task. The UXF software enabled the experiment to be designed and the data

collected with ease. A mixed-model design ANOVA was carried out, with postural

stability (head path length) as the dependent variable, vision condition as a within-

participant factor and age group as a between- participant factor. There were significant

main effects of both vision condition, $F(2, 98) = 7.35$, $p = .008$, $\eta^2_G = .016$ and age

group, $F(1, 98) = 9.26$, $p = .003$, $\eta^2_G = .068$ (Figure 7). There was no reliable interaction,

$F(2, 98) = 0.34$, $p = .562$, $\eta^2_G = .001$.

Figure 7. Postural stability as a function of vision condition. The two conditions were 'normal' (static virtual
room) and 'oscillating' (oscillating virtual room). Postural stability was indexed by the path length of head
movement in meters (measured over a 10 second period). Adults showed significantly different path length
overall compared to children (shorter – indicating greater stability). Error bars represent +/- 1 SEM.

Summary

We have created an open source resource that enables researchers to use the powerful

games engine of Unity when designing experiments. We tested the usefulness of UXF

by designing an experiment that could be deployed within a museum setting. We found

that UXF simplified the development of the experiment and produced measures in the

form of data files that were in a format that made subsequent data analysis straight

forward. The data collected were consistent with the equivalent laboratory-based

measures (reported over many decades of research) whereby children showed less

postural stability than adults, and where both adults and children showed greater sway

when the visual information was perturbed. There are likely to be differences in the

postural responses of both adults and children within a virtual environment relative to a

laboratory setting and we would not suggest that the data are quantitatively similar

between these settings. Nonetheless, these data do show that remotely deployed VR

systems can capture age differences and detect the outcomes of an experimental

manipulation.

Our planned work includes maintaining the software for compatibility with future

versions of Unity, and refactoring UXF so that it works on a wider range of platforms

(e.g. mobile devices, web browsers, augmented reality devices, standalone VR

headsets). Features may be added or modified if a clear need for a feature arises. The

project is open source, thus allowing researchers in the field to implement and share

such additions.

Availability

UXF is freely available to download via GitHub (**github.com/jackbrookes/unity-**

experiment-framework), and currently can be integrated into Unity tasks built for

Windows PCs. The package is open sourced under the MIT licence.

Acknowledgements: The authors would like to thank Almanzo McConkey and Andrea

Loriedo for their feedback on earlier versions of the software. Authors F.M and M.M-W

hold Fellowships from the Alan Turing Institute. M.W., F.M. and M.M-W are supported

by a Research Grant from the EPSRC (EP/R031193/1).

References

Brainard, D. H. (1997). The Psychophysics Toolbox. *Spatial Vision*, *10*(4), 433–436.

Flatters, I., Mushtaq, F., Hill, L. J. B. L. J. B., Rossiter, A., Jarrett-Peet, K., Culmer, P., … Mon-Williams, M.

(2014). Children's head movements and postural stability as a function of task. *Experimental Brain*

Research, *232*(6), 1953–1970. https://doi.org/10.1007/s00221-014-3886-0

Loomis, J. M., Blascovich, J. J., & Beall, A. C. (1999). Immersive virtual environment technology as a basic

research tool in psychology. *Behavior Research Methods, Instruments, & Computers*, *31*(4), 557–

564. https://doi.org/10.3758/BF03200735

Peirce, J. W. (2007). PsychoPy—Psychophysics software in Python. *Journal of Neuroscience Methods*,

162(1–2), 8–13. https://doi.org/10.1016/j.jneumeth.2006.11.017

Unity Technologies. (2018). Unity. Retrieved from https://unity3d.com/

Wann, J., & Mon-Williams, M. (1996). What does virtual reality NEED?: human factors issues in the design

of three-dimensional computer environments. *International Journal of Human-Computer Studies*,

44(6), 829–847. https://doi.org/10.1006/ijhc.1996.0035

445