AUTOMAGIC: Standardized Preprocessing of Big EEG Data

Andreas Pedroni[1], Amirreza Bahreini[1], Nicolas Langer[1]

Methods for Plasticity Research, Psychological Institute, University of Zurich

1. Abstract

Electroencephalography (EEG) recordings have been rarely included in large-scale neuropsychiatric biomarker studies. This is arguably not due to a lack of information that lies in EEG recordings but mainly on account of methodological issues. In many cases, particularly in clinical or pediatric populations, the EEG has a high degree of artifact contamination and the quality of EEG recordings often substantially differs between subjects. Although there exist a variety of standardized preprocessing methods to clean EEG from artifacts, currently there is no method to objectively quantify the quality of preprocessed EEG. This makes the commonly accepted procedure of excluding subjects from analyses due to exceeding contamination of artifacts highly subjective. As a consequence, P-hacking is fostered, the replicability of results is decreased, and it is difficult to compare data from different study sites. In addition, in large-scale studies, data are collected over years or even decades, requiring software that controls and manages the preprocessing of ongoing and dynamically growing studies. To address these two challenges, we developed AUTOMAGIC, an open-source MATLAB toolbox that acts as wrapper to run currently available preprocessing methods and offers objective standardized quality assessment for growing studies. In the present paper we outline the functionality of AUTOMAGIC and examine the effect of applying combinations of methods on a sample of resting EEG data. This examination suggests that a applying a pipeline of algorithms to detect artifactual channels in combination with Multiple Artifact Rejection Algorithm (MARA), an independent component analysis (ICA)-based artifact correction method, is sufficient to reduce a large extent of artifacts.

Keywords: EEG, artifacts, preprocessing, quality control,

2. Introduction

Major breakthroughs in translating insights from research in neuroscience to diagnose or treat mental disorders have been rare (Kapur, Phillips, and Insel 2012). To foster advances, several suggestions have been made to change paradigms and practices in research. This includes reconceptualizing the definition of mental disorders with concepts that are closer to their biological underpinnings and searching for diagnostic markers at this level (Cuthbert and Insel 2013). Furthermore, it has been suggested to move away from studying disorders in isolation and rather investigate disorders in the natural co-occurence of multiple disorders. At last, it is proposed that study samples should cover a heterogeneous composition of symptoms in various degrees of severity, facilitating the generalization and application of results to broader populations.

To implement these suggestions, studies with vast sample sizes are needed. This has become manifest in an increasing number of large-scale research initiatives, such as the IMAGEN study, the 1000 functional connectomes project or the Alzheimer's Disease Neuroimaging Initiative (ADNI). These biomarker initiatives have assessed various sets of neuropsychological, lifestyle phenotypes and brain-imaging measures, predominantly using structural and functional magnetic resonance imaging (s/fMRI). One aspect, which is at first sight surprising, is that with the exception of one notable initiative, the Healthy Brain Network study (Alexander et al. 2017; Langer, Ho, Alexander, et al. 2017), electroencephalography (EEG) measures have not been included in any large biomarker initiative.

We believe that the current paucity of EEG measures in large-scale studies is not due to a lack of information about neuronal processes that can be gained from EEG. Complementing the rather static view of the brain that is offered by MRI with information at the speed of the actual brain processes, a wealth of studies has shown that the EEG in various mental disorders deviates from healthy controls.

EEG recorded during rest is highly reliable (Näpflin, Wildi, and Sarnthein 2007; Lund et al. 1995) and is altered in various mental diseases, such as ADHD (N. Boutros, Fraenkel, and Feingold 2005), autism spectrum disorders (Wang et al. 2013), schizophrenia (N. N. Boutros et al. 2008), depression and anxiety disorders (Thibodeau, Jorgensen, and Kim 2006), and dementia and mild cognitive impairment (Jelic and Kowalski 2009). There are also abundant studies showing that task-related EEG parameters differ between healthy controls and patients suffering from various disorders (Pfefferbaum et al. 1984; Cecchi et al. 2015; Duncan et al. 2009). Furthermore, specific event-related potentials are suggested to reflect endophenotypes, for instance for anxiety disorders, depression, and substance abuse (Olvet and Hajcak 2008). Task-related EEG additionally offers insights into the processing steps that are required to perform tasks, thus allowing insights into *why* a person performs more or less well in a cognitive task (Langer, Ho, Pedroni, et al. 2017). This reflects an aspect, which complements neuropsychological testing (often included in large-scale studies), that typically only provides information about performance in the form of a single score. Finally, EEG measures also favorable from an economic point of view: If EEG-based biomarkers are identified, the financial burden of implementing widespread screening for such markers is low compared to MRI-based screening.

One major challenge that has hindered the large-scale application of EEG is the difficulty of obtaining EEG recordings that are comparable in their quality between subjects. The EEG signal is influenced by technical factors and by characteristics of the recorded subject. For instance, the EEG signal is delicately influenced by environmental factors such as temperature and air humidity and these factors interact with sources of noise, such as line noise, or other sources of electromagnetic noise (Kappenman and Luck 2010). Furthermore, it is reasonable to assume that these signals further interact with subject-related characteristics, such as the composition of skin, the skull and scalp thickness, or characteristics of the hair. In addition, subject-related artifacts, typically reflecting unwanted

physiological signals (such as eye movements, eye blinks, muscular noise, heart signals and sweating), may differ from subject to subject and may interact in a complex manner with non-physiological artifacts. The resulting artifact signals in the EEG are typically more prominent than the signal of interest (i.e. brain activity) and hence require preprocessing in the form of artifact cleaning or artifact correction (Keil et al. 2014).

Various automated artifact preprocessing pipelines have been developed to preprocess EEG data. They apply methods of source separation techniques (Jung et al. 2000; Delorme, Sejnowski, and Makeig 2007; Gabard-Durnam et al. 2018), regression methods, and linear decomposition (Parra et al. 2005) to clean EEG data. In addition, there exist various methods of detecting and removing artifactual channels and segments from EEG (Nolan, Whelan, and Reilly 2010; Mognon et al. 2011; Hatz et al. 2015; Winkler, Haufe, and Tangermann 2011; Chaumon, Bishop, and Busch 2015). A number of processing pipelines combine parts of these methods and/or extend them. The PREP pipeline (Bigdely-Shamlo et al. 2015) offers standardized early-stage EEG processing, includes sophisticated methods to remove line-noise (using Clean Line, (T. Mullen 2012) and robust average referencing by iteratively detecting and interpolating artifactual channels. The Harvard Automated Processing Pipeline for EEG (HAPPE) (Gabard-Durnam et al. 2018) reflects a standardized pipeline that additionally offers artifact correction using Wavelet-enhanced independent component analysis (ICA), ICA and Multiple Artifact Rejection Algorithm (MARA, (Winkler, Haufe, and Tangermann 2011)). The Computational Testing for Automated Preprocessing (CTAP) toolbox (Cowley, Korpela, and Torniainen 2017; Cowley and Korpela 2018) has a similar goal but additionally offers functions to optimize the different preprocessing methods by allowing the user to compare different pipelines. More recently, the Batch Electroencephalography Automated Processing Platform (BEAPP, (Levin et al. 2018)) reflects a platform for batch processing of EEG that allows the creation of preprocessing pipelines with a variety

of options that can be re-applied to new datasets, hence facilitating the exact methodological replication of studies.

Although all of these preprocessing pipelines do a remarkably good job in removing artifacts from EEG, arguably none of them would claim to be able to do this perfectly. Therefore, the extent to which a subject produces artifacts, such as moving the eyes or blinking, not only influences the signal in the raw EEG but may leave spurious traces in the preprocessed EEG. As a consequence, preprocessed EEG may vary to large extent between subjects. In some cases where the EEG signal is highly contaminated with noise, which is often the case in heterogenous study populations such as developmental studies with children and elderly subjects or in clinical studies, artifact correction cannot recover the EEG signal from the noise in a satisfactory way. It is then often unavoidable common practice to dismiss a selection of EEG recordings due to inferior quality from the analyses that enter a study.

The decision of whether a recording has acceptable quality to be submitted to further analysis is highly subjective and depends on many factors such as the recording length (i.e. number of trials), sample size, the effect sizes of interest and, foremost, the specific research question. In studies with small sample sizes it is manageable for one researcher to perform this classification, which is typically based on the visual inspection of the preprocessed EEG. Even in the case that one person assesses an entire dataset, the classification within the dataset might vary as a function of his/her motivation, tiredness and on the previously reviewed datasets. Moreover, it can be highly problematic if the data are not blinded and is classified with knowledge about the hypotheses. Things may become even more intricate in large-scale studies with thousands of datasets, where it is not feasible for one person to classify all data sets and the classification sensitivity may change from researcher to researcher, and thus may introduce biases in the study sample that lower the generalizability of results.

Recently, the HAPPE (Gabard-Durnam et al. 2018) processing pipeline has been introduced; it offers standardized metrics of the data quality, allowing objective classification of datasets. Quality metrics are the the number of interpolated channels, the number of epochs that survive epoch-wise artifact rejection after preprocessing, the number of independent components (IC) that are rejected as artifact components and the retained variance of the EEG data after IC rejection. Although these metrics are helpful to assess the quality of data they rely on how well the preprocessing was able to identify artifacts. For instance, the percentage of interpolated channels (i.e. channels that are contaminated by artifacts) depends on how well a bad-channel detection algorithm is capable to detect noisy channels. Since the noise may vary between subjects, the bad-channel detection algorithm may vary in the sensitivity to identify a noisy channel. Therefore, the quality metrics are only valid if the preprocessing is equally capable of identifying artifacts in each recording, an assumption on which our experience casts doubt. We propose additional quantitative quality metrics that are not dependent on the identification of artifacts or bad channels on which to base inclusion/exclusion criteria for EEG recordings in a more standardized way.

A further practical problem that hinders the implementation of EEG measurements in large-scale studies is a lack of software that allows the handling of large and, in particular, growing datasets. Large-scale studies and longitudinal studies typically run over many years and it is impractical to hold back data preprocessing until the end of a study. Often, research questions can be addressed in subsamples of a large study and therefore scientific progress would be slowed if data are not released until the endpoint of a study. This requires that preprocessing software is capable of handling growing studies by keeping track of the already preprocessed datasets and by freezing preprocessing settings (and software versions) to assure a standardized procedure. To the best of our knowledge no such software solution exists so far in the realm of EEG.

In the present paper we aim to address these two challenges, by presenting a software solution that implements a selection of currently available artifact correction procedures in addition to a novel quality assessment tool that relies on standardized and quantitative quality metrics that are independent from the preprocessing. In addition, the software is capable of handling growing studies and facilitates exact methodological replication of studies by providing a detailed logging of all processings steps with the applied parameters (in accordance with (Pernet et al. 2018). The software, called AUTOMAGIC, is based on MATLAB, open source and freely available under the terms of the GNU General Public License. It is available from https://github.com/methlabUZH with a user manual https://github.com/methlabUZH/automagic/wiki.

3. The AUTOMAGIC processing pipeline for big EEG data

3.1. Overview

AUTOMAGIC has been developed with the intention of offering a user-friendly preprocessing software for big (and small) EEG datasets. One major focus of the software lies in the standardization of the preprocessing and quality control and the transparent reporting to facilitate open science practices. The software can be fully controlled by command line or with a graphical user interface (GUI) and therefore does not require any knowledge of programming. It runs with MATLAB (from Version 2016b) and can be installed with a few clicks. Due to the fact that AUTOMAGIC is compiled of several MATLAB functions that are compatible with EEGLAB (Delorme and Makeig 2004), one of the most used open-source frameworks for EEG analysis), more experienced users can readily modify

AUTOMAGIC to their specific needs. In addition, AUTOMAGIC can be used as an EEGLAB extension.

AUTOMAGIC contains three basic sections, the *project section*, the *configuration section*, and the *quality assessment section*. A typical workflow involves the following steps: In the project section, the user defines the input and output folders of the processing and information about the EEG data, such as the format, channel locations, and electrooculogram (EOG)-channels. The configuration section allows the selection of various preprocessing steps with their settings that are applied to the EEG. After preprocessing of the data and the interpolation of bad channels, the user can review the quality of the preprocessing in the quality section. Here, EEG datasets can be displayed as heatmaps (with dimensions of channels and time) or classical EEG channel plots (using the eegplot function of EEGLAB), allowing the user to obtain a comprehensive overview of the data quality. In addition, various quality criteria are computed such as the ratio of interpolated channels and time windows of high voltage amplitudes. Finally, the user can define cutoffs for these quality criteria to objectively include datasets of good quality and exclude datasets of too poor quality. For each dataset, the exact sequence of the preprocessing steps are stored in a log-file and all the parameters of the preprocessing and the quality measures are stored in a MATLAB structure that is stored along the preprocessed data.

In the following sections, we will walk through the processing steps (see Figure 1 for an overview) of AUTOMAGIC and provide detailed information.

Figure 1. Typical workflow of AUTOMAGIC. The raw EEG data are organized in a project. Each dataset within a project enters the bad channel identification routines chosen by the user, detecting noisy, flat or outlier channels. These channels (red arrow) are subsequently removed from the original EEG. When choosing Artifact Subspace Reconstruction (ASR), the EEG is additionally corrected for corrupt segments at this point. In a next step, the EEG can be filtered and the user can choose to apply the artifact correction methods of EOG-regression and MARA or rPCA. In a next step, the bad channels are interpolated and the quality of each dataset is assessed using a number of objective criteria. Finally, the user can categorize the quality of each dataset into "Good", "OK" and "Bad", by applying cutoffs to the quality criteria. In addition, a visual summary of the preprocessing for each dataset and a log-file with the applied methods are saved.

3.1.1. Project

The basic idea behind a *project* is that the user defines a *data folder,* which is the source of preprocessing, along with a *results folder,* which is the target for the preprocessed data, and a list of *configurations* for the preprocessing, which is stored in the results folder in a so-called *project file (project_state.mat)*. Once the configurations have been defined and a project has been created, all the configurations are fixed and can no longer be changed, thus assuring that all datasets are processed in an identical fashion. In contrast to having the configurations fixed, the input files are not; hence, it is always possible to add (or to delete) datasets to a data folder and AUTOMAGIC detects these changes whenever the application is restarted. This guarantees that all EEG files are preprocessed in a standardized way.

3.1.2. EEG data import

AUTOMAGIC supports the EEG files types that can be imported with EEGLAB (see https://sccn.ucsd.edu/wiki/EEGLAB_Extensions_and_plug-ins). In addition, the EGI HCGSN "raw." file format is supported for 128 and 256 (or 129 and 257 if reference electrode is included respectively), with included channel locations.

3.2. The Processing steps of AUTOMAGIC

3.2.1. Bad channel identification

In a first step, so-called "bad channels" are identified[1]. Generally, bad channels are those with low recording signal-to-noise ratio (SNR) or very low or no signal throughout a considerable span of time of the EEG recording. If there are only few channels affected by such noise/low signal it is impractical to reject/correct entire time windows of the EEG for this reason. Instead, it is more sensible to interpolate the signal of bad channels by the combined signal of channels with adequate SNR.

AUTOMAGIC creates a copy from the original raw EEG data, which is submitted to algorithms whose purpose is to detect bad channels. In this way, the original data are unaffected by the high-pass filtering with a cutoff of 1 Hz that is performed by default for the currently supported bad channel removal algorithms. Note that the bad channel identification procedures only detect bad channels and do *not* modify (e.g. interpolate channels) the EEG data. Bad channels are interpolated after the preprocessing.

3.2.2. Bad channel identification and robust average referencing using the PREP pipeline

By default, AUTOMAGIC uses the PREP pipeline (Bigdely-Shamlo et al. 2015) that offers four sophisticated bad channel identification algorithms and a method to estimate a robust average reference. The specific processing steps are described in detail in (Bigdely-Shamlo et al. 2015) and on http://vislab.github.io/EEG-Clean-Tools/. Here, we only outline the key steps. In a first step, the copy of the original EEG data are high-pass filtered with a cutoff of 1 Hz. Next, power line noise is removed, using the cleanLine EEGLAB plugin developed by Mullen (2012), which estimates the amplitude and

---

[1] Note that it is possible to skip bad channel identification, but it is advisable to identify and later exclude bad channels before applying artifact correction routines because methods such as the ICA applied in MARA or the rPCA may not work properly if bad channels are not excluded beforehand.

size of a deterministic sinusoid at a specified frequency embedded in locally white noise. The algorithm requires approximate indications of the frequencies to be removed, which are by default multiples from the frequency of the line power filter input, up to half of the Nyquist frequency.

After these two initial steps, PREP iteratively estimates a robust average reference. The robust average reference method subtracts the average of all "good" (i.e. not "bad") channels from each channel. Specifically, the algorithm iteratively detects and interpolates bad channels to arrive at an average reference that is not affected by artifacts. It uses four measures for this: extreme amplitudes (deviation criterion), lack of correlation with any other channel (correlation criterion), lack of predictability by other channels (predictability criterion), and unusual high frequency noise (noisiness criterion). Note that the estimated robust average reference is only computed but not applied to the EEG data. Therefore, the data remain referenced to the initial reference. Note that the PREP pipeline is quite computationally expensive, especially on datasets with many EEG channels, and it is advisable to allow PREP using the parallel processing offered by MATLAB, which is done by default.

3.2.3. Bad channel identification using clean_rawdata()

A computationally less expensive and faster alternative (or an addition) to the bad channel identification algorithms offered by PREP, are the three bad channel identification algorithms of the EEGLAB plugin clean_rawdata() (http://sccn.ucsd.edu/wiki/Plugin_list_process). The first algorithm detects channels that have no signal variation for a duration of longer than 5 s. The EEG of the remaining channels is then filtered with a forward–backward (non-causal) filter (with transition band of 0.5 - 1Hz and stop-band attenuation of 80 db) to remove slow-wave drifts. The second algorithm (equivalent to the predictability criterion of PREP) searches for channels with a lower correlation to its robust estimate (based on other channels) than a given threshold. Specifically, (using the default

settings) it calculates the correlation of each channel in a time window of 5 s of the EEG to its random

sample consensus (RANSAC) reconstruction (with 50 samples derived from a subset of 25% of all

channels). If the correlation is below 0.85 in more than 40% of times, the respective channel is

identified as bad. The third algorithm removes EEG channels with excessive line noise. It extracts the

signal above 50 Hz from the raw EEG, which is considered line noise. Then the median absolute

deviation (MAD) of the difference between raw EEG and the line noise is calculated and divided by the

MAD of the line noise, which gives a relative noise-to-signal estimate for each channel. This estimate

is z-transformed and channels with a z-value above 4 (i.e. 4 standard deviations above the channel

population mean) are marked as bad channels.

In addition to these algorithms, we found it helpful to identify channels that show exceedingly

high variance over time. Bad channels are identified by searching for channels with a standard

deviation exceeding a certain threshold (by default 25 mV). Note that this residual channel

identification algorithm is applied after the entire preprocessing. The reason for applying this step after

preprocessing is to identify whether residual noisy channels also remain after the artifact correction,

which we have observed in some cases.

In addition to the bad channel identification algorithms, clean_rawdata() offers a function that

automatically detects and repairs artifacts using the Artifact Subspace Reconstruction (ASR) method

(Tim Mullen et al. 2013). This method does not identify bad channels, but detects "bad" time windows

(with pronounced bursts of noise) in the data and attempts to interpolate this data based on the rest of

the EEG signal during these time periods. A second function identifies and removes time periods that

could not be recovered by ASR (with abnormally high power from the data). Note that the selection of

these two additional processing steps has consequences for the original EEG as the EEG dataset might

be shortened by the time periods that could not be adequately recovered. In a limited set of tests with

small data sets, we observed that the time periods rejected by ASR varied and hence were not perfectly

replicable. Therefore, we suggest testing the use of ASR with respective data sets.

3.2.4. Bad channel removal

After having run either (or both) of the bad channel identification pipelines (clean_rawdata()

and/or the PREP pipeline) the selection of identified bad channels is excluded from the original EEG

data (see Fig. 1). This is done because, for instance, the ICA used in a later processing step in many

cases does not work with bad channels (e.g. flat channels). Note that from this point on, the

downstream processing changes the EEG signals but thus far no channels are interpolated.

3.2.5. Filtering

In this step, EEG data can be filtered using low-pass, high-pass and or notch-filter, implemented

in EEGLAB's pop_eegfiltnew().

3.3. Artifact correction

Although bad channel identification methods have the goal of identifying a distinct set of

channels with low SNR throughout a considerable span of time of the EEG recording, many artifacts

span multiple channels, while being more temporally isolated, such as eye-blinks and movement

muscle artifacts. One simple approach to handle such artifacts is to detect them (e.g. EOG data with

amplitudes ±75 V) and delete these time segments. However, this can potentially lead to a large loss of

data, consequently reducing the SNR and the quality of downstream analyses (i.e. too few trials for an

ERP). To avoid loss of data, various methods exist that remove the artifacts while preserving the

underlying neural activity. In AUTOMAGIC three such artifact correction methods are implemented, with the EOG regression, MARA, an ICA-based correction method, and a robust principal component analysis (rPCA) method.

3.3.1. EOG regression (EOGr)

In this step, artifacts that are caused by eye movements are separated from the EEG signal, using the subtraction method that relies on linear transformation of the EEG activity (see (Parra et al. 2005). This method is similar to the classical regression approach, where EOG electrodes are used as a reference signal that is subtracted in proportion to their contribution to each EEG channel (Croft and Barry, 2000). The main difference to the classical approach is that EEG channels are also used to construct an optimal estimate of the EOG activity as reference for subtraction.

3.3.2. Multiple Artifact Rejection Algorithm (MARA)

The Multiple Artifact Rejection Algorithm (MARA) (Winkler, Haufe, and Tangermann 2011; Winkler et al. 2014), used as a default, is an open-source EEGLAB plug-in which automatizes the process of hand-labeling independent components (ICs) for artifact rejection. In short, ICs of the EEG are separated by independent component analysis (ICA) using the runica() algorithm implemented in EEGLAB. MARA classifies ICs into ones that reflect artifacts and those that reflect EEG. This classification is based on a supervised learning algorithm that has learned from expert ratings of 1290 components considering six features from the spatial, the spectral and the temporal domain. The ICs that are classified as artifacts are removed and their activities are subtracted from the data. Note that prior to the ICA, a copy of the data is made and high-pass filtered with a cutoff of 1 Hz. This is done

because the ICs classified as artifacts are removed from the original data, allowing the data to be filtered with lower cutoff frequencies than those optimal for running the ICA in MARA.

3.3.3. Noise removal using robust PCA (rPCA)

An alternative (and faster) way of removing artifacts is the use of robust principal component analysis (rPCA). The implemented algorithm (Lin, Chen, and Ma 2010) estimates a low-dimensional subspace of the observed data, reflecting the signal that is cleaned from sparse corruptions. In contrast to the classical PCA, the rPCA is able to efficiently estimate true low-dimensional subspace even when the observations are grossly corrupted. We advise using the ICA instead of the rPCA, as previously suggested by Jung and colleagues (2000) because we have observed that in some cases oscillatory signals that are for example induced in steady state visual evoked potential (SSVEP) paradigms are removed by the rPCA.

3.3.4. DC offset removal

As a final preprocessing step, the DC offset is removed by subtracting the channel-wise mean from each data point.

3.3.5. Preprocessed data and auxiliary outputs

The preprocessed data are then saved.[2] AUTOMAGIC saves preprocessed data as a MATLAB MAT-file (Version 7.3). After preprocessing the prefix *"p"* (for preprocessed) is added to the filename. The MAT-file contains two structures, a structure named *EEG* that corresponds to the EEG structure of EEGLAB (see EEGLAB https://sccn.ucsd.edu/wiki/A05:_Data_Structures) and a structure named

---

[2] Note that the data, which is the input to preprocessing, are not modified at any time.

automagic. Saving the preprocessed data in an EEGLAB *EEG* structure makes it possible to readily use EEGLAB for further analyses by simply loading the MAT-files to MATLAB workspace.[3] The *Automagic* structure contains all parameters of the preprocessing and quality measures. The two structures *EEG* and *automagic* can be selectively loaded (using *load(filename,structure)*), which saves time when loading data, for instance if one wants to inspect the information in the (small in byte-size) *automagic* structure.

For each preprocessed dataset, a jpg. file is saved (in the same folder), providing a visual representation of the effects of the applied preprocessing methods. In addition, a log-file is saved for each dataset, describing the exact order and the used parameters of the preprocessing steps. This logfile can be readily used to precisely communicate the preprocessing of an EEG project in a publication.[4]

3.3.6. Data Viewer

The user can now review the data in the *Data Viewer,* where each dataset is plotted as a heatmap and bad channels are marked with blue lines. The preprocessed datasets can be furthermore visually compared to the raw 1 Hz high-pass filtered data. Furthermore, it is possible to manually select bad channels that have not been detected by the applied methods; however, for the sake of replicability we discourage this.

---

[3] EEGLAB functions can be directly applied to the loaded EEG structure. Alternatively, by starting EEGLAB and calling the command eeglab -redraw the EEG structure in MATLAB's workspace becomes accessible in the EEGLAB GUI.

[4] Users may have observed a reduced_*.mat file in the results folders. This file is a downsampled version of the EEG data and is used for faster displaying in the data viewer.

3.3.7. Bad channel interpolation

3.4. In a next step all the channels that have been detected as bad channels can be interpolated using the eeg_interp() function of EEGLAB with the "spherical" interpolation method as a default. After interpolation the EEG data are saved and the prefix "i" (for interpolated) is added to the filename.

3.5. Quality assessment

The goal of the quality assessment module is to provide objective measures of the data quality after preprocessing. Because datasets in a project may be differently contaminated by artifacts, more or less channels may have been detected and interpolated. Similarly, the artifact correction methods may have been more or less successful in cleaning the data from artifacts. This can lead to a large variability in data quality within a project and often requires the researcher to exclude overly contaminated datasets from downstream analyses. Obviously, the decision about which datasets to exclude from an analysis leaves many degrees of freedom and hence may lead to an increase in Type I errors (Simmons, Nelson, and Simonsohn 2011) in the statistical inference of downstream analyses. Automagic offers a number of objective quality measures with which datasets can be compared within a project and objective exclusion criteria can be determined. These criteria can be used to facilitate the exact replication of a project or can be included in the pre-registration of an entire methodological workflow in an EEG analysis.

3.5.1. Quality measures

One indicator of the quality of the data is the ratio of identified bad and consequently interpolated channels (RBC). The more channels that are interpolated the more of the signal of interest is lost, hence the worse the data quality. To assess the extent of signal loss is not straightforward because the signal loss depends on the spatial configuration of interpolated channels. If many bad channels are located in clusters the signal loss is greater than bad channels that are spatially scattered across the scalp. Therefore, this quality measure should be considered together with the scalp distribution of interpolated channels and clustered bad channels should be considered as more negatively affecting the quality of the data than scattered bad channels.

The quality of each dataset is furthermore assessed using three types of quality measures that are based on the magnitude of the voltage amplitudes. A range of thresholds can be defined for these measures, resulting in quality measures of different sensitivity.

The quality measure of the overall high amplitude (OHA) is defined by calculating the ratio of data points (i.e. channels c x timepoints t) that have a higher absolute voltage magnitude v of x mV,

$$OHA(x) = \frac{1}{N} \sum_{ct}^{N} v_{ct} < |x| \tag{1}$$

where x reflects a vector of voltage magnitude thresholds (e.g. $x = 10$ mV, 20 mV, 30 mV, 50 mV, 60 mV, 70 mV) and N reflects the number of data points. Thus, each OHA(x) threshold results in a quality measure that differs in its sensitivity.

Similarly, the ratio of time points t is identified, where the standard deviation σ of the voltage measures v across all channels c exceeds x mV, where x reflects a vector of standard deviation thresholds and T the number of time points. The ratio of timepoints that exceeds such a threshold reflects the timepoints of high variance (THV) criterion for a given threshold x:

$$THV(x) = \frac{1}{T} \sum_{t}^{T} \sigma_t(v_c) \ < |x| \tag{2}$$

The same logic applies to the ratio of channels, for which the standard deviation σ of the

voltage v measures across all time points t exceeds x mV. This ratio is reflected in the channels of high

variance (CHV) criterion:

$$CHV(x) = \frac{1}{C} \sum_{c}^{C} \sigma_c(v_t) \ < |x| \tag{3}$$

Therefore, after preprocessing and interpolating the datasets of a project, quality measures with

varying sensitivity (i.e. by applying variable thresholds) for high-amplitude noise are calculated. The

effect of the different thresholds is illustrated in Figure 2. The choices of the quality measure thresholds

should serve to optimize the sensitivity of high amplitude noise. We found the amplitude threshold of

30 mV and the standard deviation thresholds of 15 mV to be a good starting point to quantify

remaining artifacts when data are high-pass filtered with bandpass of 0.5 Hz[5]. For data filtered with a

higher bandpass, higher thresholds may be more suitable and can be changed by selecting the

respective threshold in the respective dropdown menus in the *Quality Classification* panel (see below).

---

[5] Note that this recommendation is based on data recorded with an 128 channels Netamps system (Electrical
Geodesics, Eugene, Oregon) and may not apply to other recording systems.

Figure 2. Effect of applying different thresholds to the quality measures. Panel A shows an exemplary EEG dataset with considerable artifacts. A) Applying rather strict thresholds of 20 mV results in large values for OHA (20%), THV (25%), and CHV (45%), indicating strong contamination of artifacts. B) and C) show the effects of applying more liberal thresholds of 40 mV and 90 mV, resulting in smaller values for OHA (8%, 2%), THV (10%, 4%), CHV (26%, 3%). Green lines indicate channels marked in accordance with the CHV criterion, red time windows indicate epochs marked in accordance with the THV criterion, blue areas indicate data points marked by the OHA criterion.

We would like to emphasize that the rationale behind assessing quality with multiple measures

is that the quality of a dataset strongly depends on the goal and specifics of the analysis. For instance, if

a researcher is only interested in ERPs of very specific channels, it is may be not important that the CHV criterion or the RBC criterion is in a reasonable range, as long as the channels of interest are free of artifacts. Alternatively, if there are many trials available in a dataset the THV criterion could be relaxed. Therefore, the user can select the thresholds and the criteria, upon which the quality assessment is based. However, importantly, the thresholds are applied to all datasets of one project and therefore the quality standards are the same for all datasets.

3.5.2. Quality classification

Using a selection of the quality measures (OHA, THV, CHV, RBC) and specified thresholds, the user can classify the datasets of one project into three categories "Good", "OK", "Bad", by applying cutoffs for each quality measure. We provide three categories in order to test whether effects of interest that can be delineated in very clean EEG data (i.e. "Good" category) also hold in noisier ("OK" category) data. By equating the thresholds of "OK" to the thresholds of the "Bad" category, the data can be included/excluded in a deterministic way for later analyses.

All the default values for thresholds and category cutoffs can be modified and therefore the user can compile samples in accordance with his/her own purposes. However, to restrict oneself in compiling categories and running analyses until effects become true (i.e. P-hacking), the user can commit selected a categorical assignment by pressing "commit classification", which appends the letters "g" for "Good", "o" for "OK", and "b" for "Bad" to the file name of the preprocessed EEG dataset. The application of such quantitative quality measures and cutoffs makes it possible to compare the ratio of "Good", "OK", "Bad" categories between projects, providing insights into the comparability of the data quality of different projects/recording sites or recording apparatus.

4. Validation

Automagic utilizes mainly preprocessing methods that have been previously published and most of the methods have been validated (Winkler, Haufe, and Tangermann 2011; Winkler et al. 2014; Bigdely-Shamlo et al. 2015; T. Mullen 2012; Parra et al. 2005). The main aim of this section is to validate the effect of *combining* methods on the resulting preprocessed data to provide recommendations on the choice of preprocessing steps when using Automagic.

The goal of preprocessing is to separate and clean artifacts (i.e. signal of no interest) from physiological signals of interest; hence, our validation aims to delineate to what extent noise can be separated from the signal of interest. Since it is not possible to determine the ground-truth for the signal of interest (i.e. EEG signal with neuronal source) because the neural sources cannot be fully determined by the EEG signal (i.e. the inverse problem), we follow an indirect validation strategy. We will later provide details but first outline the basic idea behind this strategy: Considering the EEG of one person, we assume that the underlying neuronal activity during rest is relatively similar during periods of time where artifacts occur and periods of time with clean EEG. The EEG signals in the clean and artifact-contaminated time windows should to a great extent differ due to artifactual noise and not due to underlying differences in neuronal activity; hence, a valid preprocessing method should remove the artifactual noise and increase the similarity of key characteristics of periods of time where artifacts occur and periods of time without artifacts.

To test this, we used 52 EEG datasets (128 channels Netamps system (Electrical Geodesics, Eugene, Oregon), Cz recording reference, sampling rate: 500 Hz, 1 Hz high-pass filtered) of 26 healthy elderly subjects (mean age 71.5, SD ±5.1) during a passive resting task with opened eyes. The channels that were placed in the most ventral ring of the cap (E32, E48, E49, E56, E63, E68, E73, E81, E88,

E94, E99, E107, E113, E119) were discarded. EOG channels were E1, E32, E8, E14. E17, E21, E25, E125, E126, E127, E128.

The data of each subject, consisting of five 16s epochs (=40000 time frames (TFs)), were first scanned for artifacts by identifying the TFs where the standard deviation across channels is larger than 25 mV. Then, the EEG was epoched into 2 s segments. If a TF with a standard deviation greater than 25 mV was within an epoch, the epoch was marked as a bad epoch (i.e. epoch with artifact); otherwise, a good epoch (i.e. epoch without artifact).

Good and bad epochs were then concatenated to separate datasets. To avoid datasets with exceedingly small number of time points, datasets with fewer than 10,000 TFs of either good or bad epochs were discarded for the further analysis. To make the good and bad datasets of a subject comparable, the length of the dataset with more TFs was reduced to the length of the dataset with shorter length, by randomly choosing the corresponding number of epochs. This resulted in 52 datasets (for each subject one good and one bad dataset) with on average 22,000 TFs (min: 10,000 TFs, max: 30'000 TFs, std = 6,112 TFs).

In a next step, we set up and ran 18 different variations of preprocessing in Automagic. In a first set of variations, we preprocessed the datasets by only interpolating bad channels that were identified by PREP and/or clean_rawdata(), using the respective default settings (see section Bad channel identification and Bad channel interpolation). These bad channel interpolating methods were then combined with artifact correction methods of either MARA or rPCA and with a combination with EOG regression (with their default settings, see section Artifact correction).

4.1. Results

4.1.1. Quantitative characteristics

The results of the preprocessing are summarized in Figure 3. The quality measures of the good and bad datasets were calculated and serve as comparison of the extent to which artifacts are present in the data before and after the respective preprocessing variation. Before preprocessing (Figure 3, leftmost column), the bad epochs show substantially more noise in all quality measures than the good epochs. In general, the more preprocessing methods are applied, the more noise and arguably overall signal of interest (see Figure 3 panel B) is removed. Thus, from this information alone it is not possible to assess an optimal preprocessing variation that balances removal of noise and signal. We will turn to this later.

Considering the ratio of identified bad channels, clean_rawdata() detected on average 19% bad channels in the bad datasets and 15% in the good datasets, compared to fewer bad channels identified PREP (15% in bad datasets, 13% in good datasets). The combination of bad channel identification methods together yielded 22% of bad channels in the bad dataset and 18% of bad channels in the good datasets. Therefore, both bad channel identification pipelines identify to a great extent similar but not identical bad channels.

Panel G shows the retained variance after MARA. The retained variance indicates how much variance is retained after back-projecting only the non-artifactual (clean) ICs. Note that retained variance is influenced by how clean the data are when entering the ICA of MARA. Therefore, more retained variance does not *per se* indicate less noisy data. If MARA is used without a preceding EOG regression, substantially more variance is removed from the data in the bad datasets (on average 52% retained variance in good datasets, 27% retained variance in bad datasets) whereas this difference is substantially smaller when MARA is used after EOG regression (on average 52% retained variance in

good datasets, 42% retained variance in bad datasets). This indicates that the EOG regression and

MARA may to some extent remove similar artifacts.

In addition to these rather global quality measures, we computed for the data before

preprocessing (high-pass filtered at 1 Hz) and the 18 variations of preprocessing power spectral

densities (PSDs) for a frequency range of 1 Hz to 45 Hz (using the spectopo() function of EEGLAB

with 2 times oversampling) for the channels Fz, Cpz, and Oz. Panel (H) shows to what extent the good

and bad PSDs differ when aggregating spectral power bands (mean of "Fz", "Cpz", "Oz", delta: 1.5 - 6

Hz, theta: 6.5 - 8 Hz, $alpha_1$: 8.5 - 10 Hz, $alpha_2$: 10.5 - 12 Hz, $beta_1$: 12.5 - 18 Hz, $beta_2$: 18.5 - 21 Hz,

$beta_3$: 21.5 - 30 Hz, gamma: 30 - 45 Hz). Overall it becomes evident that the bad datasets have overall

higher PSDs compared to the good datasets. Considering the different preprocessing variations, those

with bad channel interpolation only and bad channel interpolation in combination with rPCA leave

large differences between good and bad data in lower frequency bands, which are substantially smaller

when at least EOG regression or MARA is applied.

To further quantify these findings, we statistically compared the "good" and "bad" PSDs of

each subject. Recall that a valid preprocessing method should remove the artifactual noise and remove

differences in PSDs in the good and bad epochs of subjects. To test this, we used paired-permutation

tests, where we count how many times for each frequency the sum of the differences between "good"

and "bad" PSDs is larger than the sum of the differences when the "good" and "bad" PSDs are 10,000

times pairwise randomly shuffled. The ratio of randomly exceeding the actual sum of differences

reflects the empirical probability p that the actually observed sum of differences is observed by chance.

The permutation tests are performed for each frequency bin (1 - 45 Hz) for the channels Oz, Cpz and

Fz. The results of these tests are illustrated in Figure 3 panel I, where the frequency bins (x-axis), in

which the PSD differs significantly ($p < 0.001$) between the good and bad datasets are drawn in black

for the channels Oz, Cpz and Fz (in rows) and for each preprocessing variation. The results suggest that

after applying any bad channel rejection method in combination with artifact correction using MARA,

no significant differences in the PSD across the frequencies of 1 - 45 Hz are observable. In contrast,

using bad channel rejection only or a combination thereof with rPCA and EOG regression leaves

substantially more frequency bins that differ significantly.

Figure 3. Validation results. Panel A shows the combinations of selected (black) preprocessing methods. The first column of the figure reflects the quality measures of the EEG data before the preprocessing. The combinations are sorted with respect to mean absolute voltage shown in panel B with blue bars for the good datasets and red bars for the bad datasets; hence, the order indicates how much signal is subtracted by the preprocessing variations. Panels C-E depict the results of applying the quality measures of overall high amplitude data points (OHA), time points with high variance (THV), and channels with high variance (CHV) (see section Quality measures for details on the calculation). Panel F shows the ratio of bad channels, as identified by the bad channel identification methods. In panel G the percentage of retained variance after the back-projection of non-artifactual ICs in MARA is shown. The difference between the spectra power in frequency bands of the bad minus the good datasets is shown in panel H. Panel I illustrates in which frequencies the power differs significantly (black bars: $p < 0.001$) in the channels Fz, Cpz, and Oz.

4.1.2. Qualitative characteristics

To assess to what extent signal (and not only artifacts) are removed, we consider qualitative

characteristics of the PSDs. Figure 4 panel A shows PSDs in the channels Fz, Pcz and Oz with only 1

Hz filtered data. Figure 4 panel B shows the PSD after having applied PREP, Figure 4 panel C PREP

and EOGr, and Figure 4 panel D PREP and MARA. The full set of plots of all variations are shown in

Appendix A.

It is evident that only applying bad channel identification (i.e. PREP and clean_rawdata()) and

interpolation leaves substantial differences between good and bad datasets in frequency ranges from 1

to 20 - 30 Hz (see also Appendix A. Figure 1 B-D). Considering the different combinations of artifact

correction methods (i.e. EOGr, MARA, rPCA) and bad channel identification methods demonstrates

that MARA is able to correct for most artifacts in contrast to EOGr and rPCA, which leave substantial

differences between good and bad datasets (see also Appendix A. Figure 1 E-S). Furthermore, the

results suggest that a combination of PREP (or clear_rawdata()) and MARA is sufficient to remove

(almost) all significant differences in the PSDs.

To estimate to what extent the preprocessing variations balance the removal of noise compared

to retaining the signal of interest, we consider the characteristic alpha peak in Oz. We estimated the

alpha peak power amplitude using the method by Haller et al. (2018), where we calculate the mean

alpha peak power from the mean (across subjects) PSD in the frequency range of 8.5 Hz to 12 Hz for each preprocessing variation. Even if the amplitude of the alpha peak is smaller with opened eyes compared to closed eyes (Klimesch 1999), the results show that before the preprocessing the alpha peak power is more than double in the good datasets compared to the alpha peak power in the bad datasets (see Figure 4E). With additional preprocessing, the alpha peak power in Oz in the bad datasets increases (Figure 4E, red bars) whereas the alpha peak in the good dataset (blue bars) does not substantially decrease, as it would if the signal of interest were removed by the preprocessing. This suggests that the preprocessing (for instance using a variation of bad channel identification), MARA (and EOGr) removes to a great extent artifactual signal and not signal of interest (i.e. signal in the alpha band).

Figure 4. PSDs with different preprocessing variations. The PSDs of good (blue lines) and bad (red lines) datasets are shown for the channels Fz, Pcz, and Oz. The asterisks indicate significantly (p < 0.001) differing PSD at the specific frequency bin. Panel E shows the alpha peak power in Oz in good (blue) and bad (red) data after the preprocessing variations (in identical order as in Figure 2). The black boxes point to the respective preprocessing variation shown in panels A-F above. (P = PREP, C = clean rawdata(), M = MARA, R = rPCA, E = EOGr)

5. Discussion

The number of large-scale studies using EEG is limited compared to large-scale MRI and fMRI studies. As we argue, this is not because the EEG signals offers less informative insights into brain (dys-)functioning, but is manifest mainly in two unresolved issues. First, the quality of EEG recordings often substantially differs between subjects and currently there is no objective way of quantifying the quality and hence these differences. This renders the typically inevitable process of excluding subjects from analyses due to exceeding contamination of artifacts highly subjective. This not only impedes a precise methodological replication but also seduces researchers into trying out various combinations (i.e. P-hacking), further decreasing the chance of replication. The second reason is technical. Currently no software solution exists that controls and manages the preprocessing of ongoing and dynamically growing studies. To address these two challenges, we developed Automagic, an open-source MATLAB toolbox that wraps currently available preprocessing methods and offers standardized quality assessment for growing studies. We introduced the functionality of Automagic and investigated the effect of applying combinations of methods on a sample of resting EEG data. This validation revealed that a combination of applying a pipeline of bad channel identification algorithms and MARA, an ICA-based artifact correction method, is sufficient to reduce a large number of artifacts.

There are several limitations to the presented validation and also to the use of Automagic. First, the ratio between the duration of the data and the number of channels used for the validation is rather

low and may be suboptimal for an ICA decomposition. However, we believe that the result of the validation—namely, that a combination of MARA and a bad channel identification pipeline successfully removes noise while preserving the characteristics of resting EEG PSDs (e.g. alpha peak)—still holds. With more data, the ICs would be estimated more robustly and hence the results should improve. Yet, it is also possible that the performance of correcting artifacts with the rPCA and EOGr improves with more data.

The results of the validation are furthermore limited to testing the effects of preprocessing on the PSDs of resting EEG with eyes open. Other signals of interests (such as characteristics of event related potentials (ERP), features in time-frequency decomposition, source localization and connectivity measures) may favor different combinations of preprocessing and should be tested on the respective datasets. We chose resting EEG with open eyes because we aimed to use realistic EEG data with a similar number of clean segments and segments of EEG that were clearly contaminated with artifacts. Under the assumption that the true underlying neuronal activity is similar in the artifactual and clean epochs, we assessed the effectiveness of the methods by considering the extent of increase in the similarity of key characteristics of the good and bad datasets.

6. References

Alexander, Lindsay M., Jasmine Escalera, Lei Ai, Charissa Andreotti, Karina Febre, Alexander Mangone, Natan Vega-Potler, et al. 2017. "An Open Resource for Transdiagnostic Research in Pediatric Mental Health and Learning Disorders." *Scientific Data* 4 (December): 170181.

Bigdely-Shamlo, Nima, Tim Mullen, Christian Kothe, Kyung-Min Su, and Kay A. Robbins. 2015. "The PREP Pipeline: Standardized Preprocessing for Large-Scale EEG Analysis." *Frontiers in Neuroinformatics* 9 (June): 16.

Boutros, Nash, Liana Fraenkel, and Alan Feingold. 2005. "A Four-Step Approach for Developing Diagnostic Tests in Psychiatry: EEG in ADHD as a Test Case." *The Journal of Neuropsychiatry and Clinical Neurosciences* 17 (4): 455–64.

Boutros, Nash N., Cynthia Arfken, Silvana Galderisi, Joshua Warrick, Garrett Pratt, and William Iacono. 2008. "The Status of Spectral EEG Abnormality as a Diagnostic Test for Schizophrenia." *Schizophrenia Research* 99 (1-3): 225–37.

Cecchi, Marco, Dennis K. Moore, Carl H. Sadowsky, Paul R. Solomon, P. Murali Doraiswamy, Charles D. Smith, Gregory A. Jicha, Andrew E. Budson, Steven E. Arnold, and Kalford C. Fadem. 2015. "A Clinical Trial to Validate Event-Related Potential Markers of Alzheimer's Disease in Outpatient Settings." *Alzheimer's & Dementia: The Journal of the Alzheimer's Association* 1 (4): 387–94.

Chaumon, Maximilien, Dorothy V. M. Bishop, and Niko A. Busch. 2015. "A Practical Guide to the Selection of Independent Components of the Electroencephalogram for Artifact Correction." *Journal of Neuroscience Methods* 250 (July): 47–63.

Cowley, Benjamin U., and Jussi Korpela. 2018. "Computational Testing for Automated Preprocessing 2: Practical Demonstration of a System for Scientific Data-Processing Workflow Management for High-Volume EEG." *Frontiers in Neuroscience* 12 (April): 236.

Cowley, Benjamin U., Jussi Korpela, and Jari Torniainen. 2017. "Computational Testing for Automated Preprocessing: A Matlab Toolbox to Enable Large Scale Electroencephalography Data Processing." *PeerJ Computer Science* 3 (March): e108.

Cuthbert, Bruce N., and Thomas R. Insel. 2013. "Toward the Future of Psychiatric Diagnosis: The Seven Pillars of RDoC." *BMC Medicine* 11 (May): 126.

Delorme, Arnaud, and Scott Makeig. 2004. "EEGLAB: An Open Source Toolbox for Analysis of Single-Trial EEG Dynamics Including Independent Component Analysis." *Journal of Neuroscience Methods* 134 (1): 9–21.

Delorme, Arnaud, Terrence Sejnowski, and Scott Makeig. 2007. "Enhanced Detection of Artifacts in EEG Data Using Higher-Order Statistics and Independent Component Analysis." *NeuroImage* 34 (4): 1443–49.

Duncan, Connie C., Robert J. Barry, John F. Connolly, Catherine Fischer, Patricia T. Michie, Risto Näätänen, John Polich, Ivar Reinvang, and Cyma Van Petten. 2009. "Event-Related Potentials in Clinical Research: Guidelines for Eliciting, Recording, and Quantifying Mismatch Negativity, P300, and N400." *Clinical Neurophysiology: Official Journal of the International Federation of Clinical Neurophysiology* 120 (11): 1883–1908.

Gabard-Durnam, Laurel J., Adriana S. Mendez Leal, Carol L. Wilkinson, and April R. Levin. 2018. "The Harvard Automated Processing Pipeline for Electroencephalography (HAPPE): Standardized Processing Software for Developmental and High-Artifact Data." *Frontiers in Neuroscience* 12 (February): 97.

Haller, Matar, Thomas Donoghue, Erik Peterson, Paroma Varma, Priyadarshini Sebastian, Richard Gao, Torben Noto, Robert T. Knight, Avgusta Shestyuk, and Bradley Voytek. 2018. "Parameterizing Neural Power Spectra." *bioRxiv*. https://doi.org/10.1101/299859.

Hatz, F., M. Hardmeier, H. Bousleiman, S. Rüegg, C. Schindler, and P. Fuhr. 2015. "Reliability of Fully Automated versus Visually Controlled Pre- and Post-Processing of Resting-State EEG." *Clinical Neurophysiology: Official Journal of the International Federation of Clinical Neurophysiology* 126 (2):

268–74.

Jelic, Vesna, and Jan Kowalski. 2009. "Evidence-Based Evaluation of Diagnostic Accuracy of Resting EEG in Dementia and Mild Cognitive Impairment." *Clinical EEG and Neuroscience: Official Journal of the EEG and Clinical Neuroscience Society* 40 (2): 129–42.

Jung, T. P., S. Makeig, C. Humphries, T. W. Lee, M. J. McKeown, V. Iragui, and T. J. Sejnowski. 2000. "Removing Electroencephalographic Artifacts by Blind Source Separation." *Psychophysiology* 37 (2): 163–78.

Kappenman, Emily S., and Steven J. Luck. 2010. "The Effects of Electrode Impedance on Data Quality and Statistical Significance in ERP Recordings." *Psychophysiology* 47 (5): 888–904.

Kapur, S., A. G. Phillips, and T. R. Insel. 2012. "Why Has It Taken so Long for Biological Psychiatry to Develop Clinical Tests and What to Do about It?" *Molecular Psychiatry* 17 (12): 1174–79.

Keil, Andreas, Stefan Debener, Gabriele Gratton, Markus Junghöfer, Emily S. Kappenman, Steven J. Luck, Phan Luu, Gregory A. Miller, and Cindy M. Yee. 2014. "Committee Report: Publication Guidelines and Recommendations for Studies Using Electroencephalography and Magnetoencephalography." *Psychophysiology* 51 (1): 1–21.

Klimesch, W. 1999. "EEG Alpha and Theta Oscillations Reflect Cognitive and Memory Performance: A Review and Analysis." *Brain Research. Brain Research Reviews* 29 (2-3): 169–95.

Langer, Nicolas, Erica J. Ho, Lindsay M. Alexander, Helen Y. Xu, Renee K. Jozanovic, Simon Henin, Agustin Petroni, et al. 2017. "A Resource for Assessing Information Processing in the Developing Brain Using EEG and Eye Tracking." *Scientific Data* 4 (April): 170040.

Langer, Nicolas, Erica J. Ho, Andreas Pedroni, Lindsay M. Alexander, Enitan T. Marcelle, Kenneth Schuster, Michael P. Milham, and Simon P. Kelly. 2017. "A Multi-Modal Approach to Decomposing Standard Neuropsychological Test Performance: Symbol Search." *bioRxiv*. https://doi.org/10.1101/200998.

Levin, April R., Adriana S. Méndez Leal, Laurel J. Gabard-Durnam, and Heather M. O'Leary. 2018. "BEAPP: The Batch Electroencephalography Automated Processing Platform." *Frontiers in Neuroscience* 12 (August): 513.

Lin, Zhouchen, Minming Chen, and Yi Ma. 2010. "The Augmented Lagrange Multiplier Method for Exact Recovery of Corrupted Low-Rank Matrices." *arXiv [math.OC]*. arXiv. http://arxiv.org/abs/1009.5055.

Lund, T. R., S. R. Sponheim, W. G. Iacono, and B. A. Clementz. 1995. "Internal Consistency Reliability of Resting EEG Power Spectra in Schizophrenic and Normal Subjects." *Psychophysiology* 32 (1): 66–71.

Mognon, Andrea, Jorge Jovicich, Lorenzo Bruzzone, and Marco Buiatti. 2011. "ADJUST: An Automatic EEG Artifact Detector Based on the Joint Use of Spatial and Temporal Features." *Psychophysiology* 48 (2): 229–40.

Mullen, T. 2012. "CleanLine EEGLAB Plugin." *San Diego, CA: Neuroimaging Informatics Toolsand Resources Clearinghouse (NITRC)*.

Mullen, Tim, Christian Kothe, Yu Mike Chi, Alejandro Ojeda, Trevor Kerth, Scott Makeig, Gert Cauwenberghs, and Tzyy-Ping Jung. 2013. "Real-Time Modeling and 3D Visualization of Source Dynamics and Connectivity Using Wearable EEG." *Conference Proceedings: ... Annual International Conference of the IEEE Engineering in Medicine and Biology Society. IEEE Engineering in Medicine and Biology Society. Conference* 2013: 2184–87.

Näpflin, Markus, Marc Wildi, and Johannes Sarnthein. 2007. "Test–retest Reliability of Resting EEG Spectra Validates a Statistical Signature of Persons." *Clinical Neurophysiology: Official Journal of the International Federation of Clinical Neurophysiology* 118 (11): 2519–24.

Nolan, H., R. Whelan, and R. B. Reilly. 2010. "FASTER: Fully Automated Statistical Thresholding for EEG Artifact Rejection." *Journal of Neuroscience Methods* 192 (1): 152–62.

Olvet, Doreen M., and Greg Hajcak. 2008. "The Error-Related Negativity (ERN) and Psychopathology: Toward an Endophenotype." *Clinical Psychology Review* 28 (8): 1343–54.

Parra, Lucas C., Clay D. Spence, Adam D. Gerson, and Paul Sajda. 2005. "Recipes for the Linear Analysis of EEG." *NeuroImage* 28 (2): 326–41.

Pernet, Cyril R., Marta Garrido, Alexandre Gramfort, Natasha Maurits, Christoph Michel, Elizabeth Pang, Riitta Salmelin, Jan Mathijs Schoffelen, Pedro A. Valdes-Sosa, and Aina Puce. 2018. "Best Practices in Data Analysis and Sharing in Neuroimaging Using MEEG." https://doi.org/10.31219/osf.io/a8dhx.

Pfefferbaum, A., B. G. Wenegrat, J. M. Ford, W. T. Roth, and B. S. Kopell. 1984. "Clinical Application of the P3 Component of Event-Related Potentials. II. Dementia, Depression and Schizophrenia." *Electroencephalography and Clinical Neurophysiology* 59 (2): 104–24.

Simmons, Joseph P., Leif D. Nelson, and Uri Simonsohn. 2011. "False-Positive Psychology: Undisclosed Flexibility in Data Collection and Analysis Allows Presenting Anything as Significant." *Psychological Science* 22 (11): 1359–66.

Thibodeau, Ryan, Randall S. Jorgensen, and Sangmoon Kim. 2006. "Depression, Anxiety, and Resting Frontal EEG Asymmetry: A Meta-Analytic Review." *Journal of Abnormal Psychology* 115 (4): 715–29.

Wang, Jun, Jamie Barstein, Lauren E. Ethridge, Matthew W. Mosconi, Yukari Takarae, and John A. Sweeney. 2013. "Resting State EEG Abnormalities in Autism Spectrum Disorders." *Journal of Neurodevelopmental Disorders* 5 (1): 24.

Winkler, Irene, Stephanie Brandl, Franziska Horn, Eric Waldburger, Carsten Allefeld, and Michael Tangermann. 2014. "Robust Artifactual Independent Component Classification for BCI Practitioners." *Journal of Neural Engineering* 11 (3): 035013.

Winkler, Irene, Stefan Haufe, and Michael Tangermann. 2011. "Automatic Classification of Artifactual ICA-Components for Artifact Removal in EEG Signals." *Behavioral and Brain Functions: BBF* 7 (August): 30.

Q

1 Hz + PREP + rPCA + EOGr

R

1 Hz + Clean rawdata() + rPCA + EOGr

S

1 Hz + PREP + Clean rawdata() + rPCA + EOGr