# Mouse Academy: high-throughput automated training and trial-by-trial behavioral analysis during learning

Mu Qiao[1], Tony Zhang[1], Cristina Segalin[2], Sarah Sam[1], Pietro Perona[2,3] & Markus Meister[1,3*]

[1]Division of Biology and Biological Engineering, California Institute of Technology, Pasadena, CA 91125, USA

[2]Division of Engineering and Applied Sciences, California Institute of Technology, Pasadena, CA 91125, USA

[3]Tianqiao and Chrissy Chen Institute for Neuroscience, California Institute of Technology, Pasadena, CA 91125, USA

*Correspondence: meister@caltech.edu

**ABSTRACT**

Progress in understanding how individual animals learn will require high-throughput standardized methods for behavioral training but also advances in the analysis of the resulting behavioral data. In the course of training with multiple trials, an animal may change its behavior abruptly, and capturing such events calls for a trial-by-trial analysis of the animal's strategy. To address this challenge, we developed an integrated platform for automated animal training and analysis of behavioral data. A low-cost and space-efficient apparatus serves to train entire cohorts of mice on a decision-making task under identical conditions. A generalized linear model (GLM) analyzes each animal's performance at single-trial resolution. This model infers the momentary decision-making strategy and can predict the animal's choice on each trial with an accuracy of ~80%. We also introduce automated software to assess the animal's detailed trajectories and body poses within the apparatus. Unsupervised analysis of these features revealed unusual trajectories that represent hesitation in the response. This integrated hardware/software platform promises to accelerate the understanding of animal learning.

## INTRODUCTION

Learning – the change of neural representation and behavior that results from past experience and the consequences of actions – is important for animals to survive and forms a central topic in neuroscience[1]. Different individuals may apply different strategies to the learning process, reflecting their individual personalities. Indeed, substantial differences in sensory biases, locomotion, motivation, and cognitive competence have been observed in populations of fruit flies[2,3], rodents and primates[4-6]. Thus, it is critical to investigate learning at the individual level.

Rodents, especially the mouse, have become popular experimental animals in studying associative learning and decision-making, because of the wide availability of transgenic resources[7-10]. They can learn to perform complex decision-making tasks that probe cognitive components such as working memory and selective attention[11-13]. However, differences in learning strategies across individuals have rarely been addressed, partly owing to the limitations of data gathering and analysis.

Studying differences among individuals requires training and collecting data from multiple animals in a standardized and high-throughput fashion. The training procedures are often time-consuming, requiring several days to many weeks[8,9], depending on the task. Although there have been advances in training automation, existing systems either require an experimenter to move animals from the home cage to the training apparatus[14-16], or training animals within their own cages[17-19]. The former introduces additional sources of variability[20,21], and the latter precludes tasks that require a large training arena. Following data acquisition, the analysis of behavior aims at understanding the learning process. Present approaches tend to focus on the averaged performance over many trials[22]. However, changes in behavior may happen at a single trial, and thus the modeling of behavior should similarly offer a time resolution of single trials to assess each animal's individual approach to learning.

To address these challenges, we present Mouse Academy, an integrated platform for automated training of group-housed mice and analysis of behavioral changes in learning a decision-making task. We designed hardware that makes use of implanted radio frequency identification (RFID) chips to identify each mouse, and guides the animal into a behavior training box. Synchronized video recordings and decision-making sequences are acquired during animal learning. To analyze the decision-making sequences, we developed an iterative generalized linear model (GLM). This model makes a prediction of the animal's choice in each trial and gets updated based on the animal's actual choice. This iterative GLM model achieves a prediction accuracy of ~80%, and also reveals the decision-making strategy of the animal and how it changes over time. To analyze the animal's behavior during the task in greater detail, we developed automated software that tracks the animal in video recordings and extracts its location and body pose using deep convolutional neural networks (CNNs). These features allowed us to perform an unsupervised analysis of each animal's behavior, and discover individual traits of behavioral learning that were not apparent from the simple choice sequences.

**RESULTS**
The Mouse Academy platform consists of three components (**Fig. 1**): an automated RFID sorting and animal training system, an iterative GLM to analyze decision-making sequences, and behavior assessment software that extracts animal trajectories from video data.

**Automated RFID sorting supports individual training programs**
We designed the equipment in the following manner (**Fig. 1a**): RFID-tagged mice are grouped in a common home cage where food and bedding is supplied. The home cage connects to a behavior training box through a gated tunnel. The gates are controlled by a home-made RFID animal sorting system[23]: three RFID antennas are placed along the tunnel, with one near the home cage, one near the training box and one between the two; the motorized gates are placed between the RFID sensors, separating the tunnel into three compartments. An Arduino microcontroller integrates information from the RFID readers to open and shut the gates, allowing only one animal at a time to pass through the tunnel (**Supplementary Figs. 1a, 1c, 1d** and **Supplementary Videos 1-4**). The behavior box is outfitted with three ports, each of which contains a photo-transistor to detect snout entry, a solenoid valve to deliver water reward, and a light emitting diode (LED) to present visual cues. To maintain a controlled environment, the training box is isolated from the outside by a light- and sound-proof chamber (**Supplementary Fig. 1b**).

Once a mouse enters the training box, a protocol is set up to train the mouse to perform a certain
task. In the experiments reported here, the animal must nose-poke the center port to initialize a
trial and then hold the position for a short period. Visual or auditory stimuli are delivered, and
based on these stimuli, the animal must choose to poke one of the side ports. If the correct
response is chosen, the animal gets water reward from a lick tube in the response port, otherwise
a timeout punishment is applied. This training process is controlled by Bpod, an Arduino
microcontroller that interfaces with the three ports. Data from the response ports as well as video
recordings from an overhead camera are acquired simultaneously as the animal is trained.

The entire apparatus is orchestrated by a master program that coordinates the RFID sorting
device, the Bpod system, synchronized video recording, data management and logging
(**Supplementary Fig. 1e**). The program monitors the amount of water each animal consumes per
day and regulates the time each animal can spend in the training box per session. In addition, the
software updates the training protocol for each animal based on its performance, for example
switching to a harder task once a simpler one has been mastered (**Supplementary Fig. 2**). This
lets each animal learn at its own pace.

The apparatus can be assembled at a materials cost of $1500-2500, with the cheaper option using
a Raspberry Pi computer as the controller (**Supplementary Fig. 1f** and **Supplementary Table
1**). Compared with designs in which each animal is automatically trained in its own home
cage[15,17], the system saves considerable space. Because housing and training are independent
modules, the same system can be used for diverse training environments.

We tested the automated RFID sorting and animal training system by training group-house mice
to learn a variety of decision tasks, following similar procedures as reported previously[11,12]
(**Supplementary Fig. 2** and Online methods). The training period lasted 28 days, with up to five
mice in the common home cage. Each animal occupied the training box for 3-4 hours per day
(13-15% of the 24 hours) throughout the entire training period (**Figs. 2a**, **2b** and **Supplementary
Fig. 3**). For a sample cohort of four animals trained in sessions of 90 trials each, we found that
the behavior box was occupied most of the time, with brief empty intervals of <10 min (**Figs. 2c,
2d** and **2e**). Each animal was trained for over 900 trials (10 sessions), and consumed more than
1.9 mL of water per day (**Fig. 2f**). Interestingly there was no circadian pattern to the animals'
training activity, even though the setup was illuminated on a daily light cycle (12 h on / 12 h off)
(**Fig. 2g**). As observed previously, it appears that animals working for a goal can avoid circadian
modulation of the locomotor pattern[24,25].

**A generalized linear model accurately predicts decision-making during training**
In a decision-making task, an animal is asked to associate distinct stimuli with distinct responses.
Although this is the ultimate goal, during learning, it is often observed that the animal begins by
basing its decisions on unrelated input variables and gradually switches to using the stimulus
variables that actually predict reward. We define a policy as a mapping of these variables to the
animal's decisions. A fundamental goal in the study of learning is to infer what policy the animal
follows at any given time and to determine how the policy evolves with experience.

We applied a generalized linear model (GLM) to map factors relevant to the animal's decision-
making to its choices through logistic regression. A common way to build such a GLM is by
fitting data of an entire session[16,26]. However, this loses resolution in single trials within the
session. During learning, a change of policy can happen at each trial. Thus, we developed the
model to make trial-by-trial choice predictions based on various factors the animal might
plausibly use. The model works in an iterative two-step process (**Fig. 1b**). In the prediction step,
the model makes a prediction for the next decision based on the input factors. Once the outcome
of the animal's decision is observed, an error term between the model's prediction and the
observation is computed. This error, after weighting by a reward factor and a temporal discount
factor, is fed back to the loss function. In the update step, the model is updated by minimizing
the regularized loss function. This iteration happens after every trial. The temporal discount
factor accounts for the possibility that the most recent trials impact the current decision more
than remote trials. The reward factor accounts for the fact that water rewards and timeout
punishments may have effects of different magnitude on the updates of the animal's policy.
152
We illustrate the utility of this model by fitting results from an easy visual task, in which one of
the two choice ports lights up to indicate the location of the reward, and the optimal policy is to
simply poke the port with the light (**Supplementary Fig. 2a, 2a'** and **2a''**). All the mice
eventually reached a >83% performance level, comparable to what mice achieve in similar
tasks[19,27]. The GLM makes a prediction for the outcome of each trial based on a weighted
combination of several input variables: the current visual stimulus, a constant bias term, and
three terms representing the history of previous trials (**Fig. 3a**). These inputs from a previous
trial include the port choice, whether that choice was rewarded, and a term indicating the
multiplicative interaction between the choice and reward (Choice x Reward). This term supports
a strategy called win-stay-lose-switch (WSLS), which chooses the same port if it was rewarded
previously and the opposite one if not. Since a GLM cannot multiply two inputs, we provided
this interaction term explicitly. Each of the above terms has a weight coefficient that can be
positive or negative. For instance, a positive weight for the visual stimulus supports turning
towards the light, and a negative weight away from the light.
167
To determine the extent of trial history that affects the animal's behavior, we fitted the model to
the response data including history-dependent terms up to three previous trials. We found that
only the immediately preceding trial had an appreciable effect on the prediction accuracy, and
thus restricted further analysis to those inputs (**Fig. 3b**). The model also has three
hyperparameters (the temporal discount factor $\alpha$, the reward factor $r$, and the regularization
factor $\lambda$), and we optimized them for each animal by grid search. We found that each animal
had a different set of hyperparameters, reflecting differences in the learning process across
individuals (**Fig. 3c**). Among the four sample mice, Animal 2 had the lowest temporal discount
factor, suggesting that it weighed recent trials more heavily and updated the policy more quickly.
Indeed, this is the animal that learned the fastest among the four (**Fig. 3d**).
178
Predictions from the iterative GLM matched ~80% of the animals' actual choices (**Fig. 3f**), and
the predicted accuracy of each animal captured the actual fluctuations of its learning curve (**Fig.
3e** and **Supplementary Fig. 4**). We compared the performance of the GLM with two other
modeling approaches (Online methods). The first model was fit to the animal's average
performance in the task; its trial-by-trial match of the animal's actual choices was only ~59%

(**Fig. 3g**). The second model was a logistic regression fitted to data in a sliding window of $N$
trials. This sliding window model performed worse than the iterative GLM when the window
size was small ($N = 20$ and $30$ trials, **Fig. 3h**); for larger windows the performance was
comparable. Overall, the iterative model is advantageous because it makes predictions online as
every trial occurs and adapts dynamically to the growing data set.
189
**Individual learning policies can be inferred from iterative GLM fitting**
The iterative GLM serves to infer what policy the animal follows in making decisions. The linear
weight of each input term reflects its relative importance for the decision. By following this
weight vector across trials one obtains a policy matrix that documents how the animal's policy
changes during learning (**Figs. 1b** and **4c**). To test that the model can correctly capture a time-
varying policy, we simulated decision-making data from a ground truth policy that changed at a
certain frequency, including a certain level of noise in the behavioral output (**Fig. 4a**). Over a
wide range of policy change frequencies and noise levels, the GLM was able to capture the
ground truth policy (**Figs. 4a** and **4b**). In addition, different values of policy change frequency
and noise levels led to different sets of hyperparameters fitted from the model, showing that the
GLM can adapt to individuals with diverse learning characteristics (**Supplementary Figs. 5a-e**).
201
We then recovered the policy matrix of each animal from the GLM fits. All four animals started
with the non-optimal policy of WSLS. Subsequently each animal followed its own learning
process (**Fig. 4c**): Animal 2 had a clear bias towards the right port at the beginning but it rapidly
found the optimal policy of following the light. The other three animals were slower learners.
Animal 3 and Animal 4 followed similar processes to converge to the optimal policy. Animal 1
was distinct from the others. At the early stages, it had a strong bias towards the left port and it
made decisions based on whether the previous choice was rewarded.
209
We further validated the transition between policies during learning by analyzing the first and
last sessions of each animal and counting how many choices could be explained by each policy
(**Fig. 4d**). Indeed, we found a clear switch from the (non-optimal) WSLS policy to the (optimal)
stimulus-based policy (**Fig. 4e** and **Supplementary Fig. 5f**). The animals might have been
biased towards the WSLS strategy by a shaping method we used during training, which offered
the animal a repeat of the same stimulus every time it made a mistake (Online methods). To test
whether these correlations in the trial sequence influenced the final policy we performed two
additional analyses. First, we only included trials following a correct trial, and performed logistic
regression on these trials for each session. This analysis showed that at least on these trials, all
the animals based their decisions on the light stimulus by the end of learning (**Supplementary
Fig. 6a**). Second, we compared the error rate on trials following an incorrect choice with that
following a correct one. We found no significant difference between the two error rates during
the last session (**Supplementary Figs. 6b** and **6c**), suggesting that the animals treated these two
types of trials identically.
224
**Automated movement tracking reveals fine structure of behavioral responses**
Thus far the report has focused on the animal's responses only as sensed by the nose pokes into
response ports. The GLM fits of those responses already revealed differences in policy across
individuals. To gain further insight into these individual preferences, it is essential to track each
animal's behavior along the way from stimuli to responses[10]. We thus developed software that

uses deep learning to automatically, quantitatively and accurately assess each animal's behavior
during decision-making (**Figs. 1c** and **5a**).
232
To track the animal location and body coordinates, we recorded videos of the animal from above,
and analyzed them with a sequence of two deep convolutional neural networks (CNNs) that were
pre-trained on annotated pose data (**Fig. 5a** and **Supplementary Videos 5-7**). The first CNN was
based on the multi-scale convolutional (MSC) Multibox detector[28] (**Supplementary Fig. 7a**).
For each frame of the video it computed a crop frame around the body of the mouse. The second
CNN was a Stacked Hourglass Network[29] that used the cropped video frame to locate seven
body landmarks: the nose, the ears, the neck, the body sides and the tail of the animal
(**Supplementary Figs. 7a** and **7b**). These landmarks allowed precise identification of the
animal's position and body pose (**Supplementary Fig. 7c**), from which we further extracted two
features: the body centroid (average position of the seven landmarks) and the orientation (angle
of the line connecting the centroid and the nose).
244
To illustrate use of these behavioral trajectories, we focus on the period of the visual choice task
where the animal reports its decision: from the time it leaves the center port to when it pokes one
of the side ports. The trials fall into four groups based on location of the stimulus and the
response. As expected, the trajectories of position and orientation clearly distinguish left from
right choices (**Figs. 5b** and **5d**). Interestingly, the trajectories also reveal whether the decision
was correct: On incorrect decision, the trajectories reversed direction after ~0.5 s, because the
animal quickly turned back to the center after finding no reward in the chosen port (**Figs. 5c, 5e**
and **Supplementary Video 5**). A linear kernel support vector machine (SVM), trained to predict
the category of each trial from a 1 s trajectory, was able to correctly distinguish correct and
incorrect choices with an accuracy of over 90% (**Supplementary Fig. 8**). In addition, many of
the trajectories were highly asymmetric and again revealed differences across individuals. For
instance, Animal 2 and Animal 4 started from a location close to the right port, Animal 1 closer
to the left port (**Fig. 5c**). This asymmetry correlates with the bias revealed by the iterative GLM:
each animal prefers to select the port closer to its body location.
259
260 **Unsupervised behavioral analysis reveals moments of hesitation**
261 Whereas the supervised learning discussed above relies on prior classification of stimuli and
262 responses, an unsupervised analysis has the potential to discover unexpected structures in the
263 animal's behavior[30]. We thus performed an unsupervised classification of the behavioral
264 trajectories.
265
After subjecting all the trajectories of a given animal to principal component analysis (PCA) we
projected the data onto the top three components, which explained over 95% of the variance
(**Figs. 6a, 6b** and **Supplementary Fig. 9a**). Importantly, without any labels from trial types,
these three PCs captured meaningful features that differentiated the animal's responses. The first
PC separated movements to the left from those to the right (**Figs. 6a** and **6b**). The third PC
captured the turning-back behavior after an incorrect choice (**Fig. 6b** and **Supplementary Fig.
9a**). The second PC captured different baseline positions (**Fig. 6b**). Each animal has its own
preference for a baseline position somewhere off the midline of the chamber (**Supplementary
Fig. 9b**).
275

We also projected the trajectories into 2 dimensions using a non-linear embedding method, t-
distributed stochastic neighbor embedding[31,32] (t-SNE). Unlike PCA, this graph prioritizes the
preservation of local structures within the data instead of the global structure[32]. In the t-SNE
space the trajectories formed clear clusters (**Fig. 6c**). Most of the clusters are dominated by one
of the decision categories (**Fig. 6c** and **Supplementary Fig. 9c**). Interestingly, we found clusters
in Animals 2, 3, and 4, in which the centroid trajectories were flat, unlike the trajectories of the
four decision categories (**Fig. 6d**), suggesting that animals hesitated in these trials and made
decisions only after a delay. Indeed, in trials flagged by these clusters, the animals had longer
reaction times (**Fig. 6e**). Furthermore, such hesitating responses were more common following
an incorrect trial (**Fig. 6f**); they may reflect a behavioral adjustment to prevent further mistakes[33].
286
**DISCUSSION**
Despite the fact that rodents can be trained to perform interesting decision-making tasks[7-10], the
learning progress of individual animals has rarely been addressed. Doing so requires training and
observing many animals in parallel under identical conditions, and the ability to analyze the
decision policy of each animal on a trial-by-trial basis. To meet these demands, we developed
Mouse Academy, an integrated platform for automated training and behavior analysis of
individual animals.
294
We demonstrate here that Mouse Academy can train group-housed mice in an automated and
highly efficient manner while simultaneously acquiring decision-making sequences and video
recordings. Automated animal training has been of great interest in recent years and efforts have
focused on two directions. In one design, multiple animals are trained in parallel within stacks of
training boxes. This requires a technician to transfer animals from their home cages to the
behavior boxes[14-16]. Such animal handling has been reported to introduce additional
variability[20,21], and even the mere presence of an experimenter can influence behavioral
outcomes[34]. Thus, eliminating the requirement for human intervention, as in Mouse Academy,
likely reduces experimental variation. In another design, a training setup is incorporated within
the animals' home cage[17-19]. By contrast, Mouse Academy separates the functions of housing and
training, and that modular design allows easy adaptation to a different purpose. For instance, one
can replace the 3-port discrimination box with a maze to study spatial navigation learning[35,36], or
with an apparatus for training under voluntary head-fixation[37]. In each case, a single training
apparatus can serve many mice, potentially from multiple home cages.
309
To understand how an animal's decision-making policies change in the course of learning, we
developed a trial-by-trial iterative GLM. The evolution of the model is similar to online machine
learning[38] in which the data are streamed in sequentially, rather than in batch mode. The linear
nature of the model supports a straightforward definition of the animal's decision policy, namely
as the vector of weights associated with different input variables. In addition, the simple linear
structure allows rapid execution of the algorithm, which favors its use in real-time closed-loop
behavior experiments. The model also allows several parametric adjustments. One specifies how
much the recent trials are weighted over more distant ones in shaping the animal's policy.
Another rates the relative influence of reward versus punishments. Fitting these parameters to
each animal already revealed differences in learning style. This model can have a broader use
beyond mouse decision-making, for instance to track the progress of human learners from their
answers to a series of quizzes[39].

322
Finally we presented software for automated assessment of behaviors based on video recordings
within Mouse Academy. Largely extending existing methods, the software uses deep
convolutional neural networks for animal tracking and pose estimation. Because the animal's
movements are unconstrained, we performed the tracking in two stages: the first finds the animal
within the video frame and the second locates the body landmarks. Compared to a single-shot
procedure, this split approach requires fewer learning examples and less computation in the
second stage[38]. The resulting behavioral trajectories can reveal intricate aspects of the animal's
decision process that are hidden from a mere record of the binary choices. The large data volume
again calls for automated analysis, and both supervised machine learning methods[30,40,41] and
unsupervised classification[30-32,42] have been employed for this purpose. Unsupervised analysis is
not constrained by class labels, and can identify hidden structure in the data in an unbiased
manner. In the present case, we discovered a motif wherein the animal hesitates on certain trials
before taking action.
336
337 Mouse Academy can be combined with chronic wireless recording[43,44], to allow synchronized
338 data acquisition of neural responses. Researchers can seek correlations between neural activity
339 and the policy matrix or even the behavioral trajectories. This will open the door to a mechanistic
340 understanding of how neural representations and dynamics change in the course of animal
341 learning.
342
343 **ONLINE METHODS**
344 **Animals**
345 Subjects were C57BL/6J male mice aged 8-12 weeks. All experiments were conducted in
346 accordance with protocols approved by the Institutional Animal Care and Use Committee of the
347 California Institute of Technology.
348
349 **Hardware setup**
350 The hardware setup comprises a behavioral training box, an engineered home cage, and a radio
351 frequency identification (RFID) sorting system, which allows animals to move between the
352 home cage and the training box. These components are coordinated by customized software.
353
The design file for the behavior box was modified from that of Sanworks LLC
(https://github.com/sanworks/Bpod-CAD) using Solid-Works computer-aided design software
and the customized behavioral training box was manufactured in the lab. The behavior box is
controlled by a Bpod state machine (r0.8, Sanworks LLC). To monitor the animal's behavior, an
IR webcam (Ailipu Technology or OpenMV Camera M7) is installed above the behavior box.
The behavior box and the webcam are placed within a light- and sound-proof chamber. The
chamber is made of particle board with walls covered by acoustic foam. A tunnel made of red
plastic tubes connects the behavior box to a home cage (**Supplementary Fig. 1b**).
362
363 For the RFID access control system, an Arduino Mega 2560 microcontroller is connected with
364 three RFID readers (ID-12LA, Sparkfun) with custom antenna coils spaced along the access
365 tunnel. The microcontroller controls two generic servo motors fitted with plastic gates to grant
366 individual access to the training box (**Supplementary Fig. 1a**).
367

The microcontroller identifies each animal by its implanted RFID chip and permits only one
animal to go through the tunnel connecting the home cage and the behavioral training box
(**Supplementary Fig. 1c)**. It also communicates the animal's identity to a master program
running on a PC or Raspberry Pi (Matlab or Python). The master program coordinates the
following programs: Bpod (https://github.com/sanworks/Bpod), synchronized video recording,
data management and logging. A repository containing the design files, the firmware code for the
microcontroller, and the software can be found in
https://github.com/muqiao0626/Mouse_Academy.
376
**Behavior training**
The training procedures of mice to perform a selective attention task are similar to those
previously reported[11,12]. Mice were water restricted for seven days before training, and
habituated in the automated training system to collect reward freely for several sessions. Then
the mice were trained in sessions, each of which was made of 90 trials, to collect water rewards
by performing two alternative forced choice tasks. Briefly, the animal had to nose-poke one of
two choice ports based on the presented stimuli. If the decision was correct, 10% sucrose-
sweetened water (3 µL) was delivered to the animal. For incorrect responses, the animal was
punished with a five-second timeout. Following an incorrect response, the animal was presented
with the identical trial again; this simple shaping procedure helps counter-act biases in the
behavior.
Over 28 days of training the animals learned increasingly complex tasks, from visual
discrimination to a two-modality cued attention switching task[11,12]. The training progressed
through six stages (**Supplementary Fig. 2**):
1. A simple visual task: In this task, the animal initiates a trial by poking the center port and
holding the position for 100 ms. Then either the left or right side port light up briefly until
the animal moves away from the center port. The animal must then poke one of the two
side ports within the decision period of 10 s. Choice of the port flagged by the light leads
to a water reward, and choice of the other port leads to a time-out period during which no
trials can be initiated. Data presented in the main text are from this stage of training only.
2. A simple auditory task: As Stage 1, except that the stimulus was white noise sound either
the left or the right side to flag the reward port.
3. A cued single-modality (visual or auditory) switching task: Blocks of 15 trials consisting
of single-modality (visual or auditory) stimulus presentation. Each block was like stages
1 or 2, except that the trial type was indicated by a 7 kHz (visual) or 18 kHz (auditory)
pure tone.
4. A cued single- and double-modality switching task: Like stage 3, but distracting trials
were introduced in which both visual and auditory stimuli were present, but only one of
the modalities was relevant to the decision. The relevant modality was again indicated by
the pure tone cues. In repeating blocks, four types of trials were presented: a. five visual-
only trials; b. ten 'attend to vision' trials with auditory distractors; c. five auditory-only
trials; d. ten 'attend to audition' trials with visual distractors. During the training, the time
that the animal had to hold in the center port was gradually increased to 0.5 s, and the
duration of the stimuli was gradually shortened to 0.2 s.
5. A cued double-modality switching task: Like stage 4 except that the single-modality trials
were removed, and the block length was gradually shortened to three trials.

6.  A selective attention task: Like stage 5, but the block structure was abandoned and all
eight possible trial types were randomized: (audition vs vision) x (sound left or right) x
(light left or right).
416

**Iterative generalized linear model**

417   
418 We modeled the animal's choice probability by a logistic regression. At each trial number $t$, the
419 choice probability is defined as

$$p\left(y_t = 1 \middle| \mathbf{w}_{t-1}\right) = \frac{1}{1 + \exp\left(-\mathbf{w}_{t-1}^T \mathbf{x}_t\right)} \tag{1}$$

$$p\left(y_t = -1 \middle| \mathbf{w}_{t-1}\right) = 1 - p\left(y_t = 1 \middle| \mathbf{w}_{t-1}\right)$$

421
422 where $y_t$ indicates the binary choice of the animal ($1$ = right, $-1$ = left), $\mathbf{x}_t$ is the vector of input
423 factors on trial $t$, and $\mathbf{w}_{t-1}$ is the vector of weights for these factors obtained from fitting up to the
424 preceding trial.

425 The prediction $y_t^*$ for the animal's choice is simply that with the higher model probability:

$$y_t^* = \underset{y \in \{-1,+1\}}{\arg\max} \, p\left(y \middle| \mathbf{x}_t, \mathbf{w}_{t-1}\right) \tag{2}$$

427 After observing the animal's actual choice $z_t$, the cross-entropy error $E_t$ between the
428 observation and model prediction is calculated as

$$E_t = -\log p\left(z_t \middle| \mathbf{x}_t, \mathbf{w}_{t-1}\right) \tag{3}$$

430 We weight the error term by a reward factor $R_t$, and apply exponential temporal smoothing to
431 get the loss function $L_t$:

$$L_t = R_t E_t + \alpha L_{t-1} \tag{4}$$

433 where $\alpha$ is the smoothing discount factor accounting for the effect that distant trials have less
434 impact on decision-making than immediately preceding trials, and $R_t$ is defined as

$$R_t = \begin{cases} 1, \text{if the choice is rewarded} \\ r, \text{otherwise} \end{cases} \tag{5}$$

436 The values of $R_t$ for rewarded and unrewarded trials may be different, accounting for the fact
437 that rewards and punishments may have different effects on learning. For each time point, the
438 weights in the model are determined by minimizing the loss function subject to L1 (lasso)
439 regularization, namely

$$\mathbf{w}_t = \underset{\mathbf{w}}{\arg\min}\left(L_t + \lambda \|\mathbf{w}\|_1\right) \tag{6}$$

441 Then $\mathbf{w}_t$ is used for prediction of the next trial. For subsequent analysis, we only used
442 predictions starting at the 15th trial. The three hyperparameters for the temporal discount factor
443 $\alpha$, the reward factor $r$, and the regularization factor $\lambda$ were selected by grid search.
444

To fit the decision-making sequences of the simple visual task, we included the following terms
in the input vector $\mathbf{x}_t$:
1. Visual_stimulus: +1 = light on right, –1 = light on left.
2. Bias: A constant value of +1. The associated weight determines whether the animal
favors the left (negative) or the right (positive) port.
3. Choice_back_n: The choice the animal made *n* trials ago (+1 = right, –1 = left).
4. Reward_back_n: The reward the animal received *n* trials ago (+1 = reward, –1 =
punishment).
5. Choice x Reward_back_n: The product of terms 4 and 5. This term corresponds to the
win-stay-lose-switch (WSLS) strategy of repeating the last choice if it was rewarded and
switching if it was punished.
456
457 To determine the extent of history-dependence of the animal's decisions, we fitted the model
458 including terms 3-5 from up to three previous trials ($n = 1, 2, 3$), and found that only the
459 immediately preceding trial had an appreciable effect on the model's prediction accuracy. For the
460 subsequent analysis, we therefore included terms 3-5 for the preceding trial ($n = 1$).
461
462 We compared the iterative generalized linear model (GLM) with two other models. The first
463 only captures the animal's average performance over all trials. If the fraction of the correct
464 responses is $z$, then the model simply predicts a correct response with probability $z$, and an error
465 with probability $1-z$. Thus, the fraction of trials where the prediction matches the observation is
466 $z^2 + \left(1 - z\right)^2$.
467
468 The second model is a sliding window logistic regression. To make a prediction for trial $t$, we
469 fitted the logistic model presented above (Eqns 1-2) to the preceding $n$ trials. The loss function is

470
$$L_t = -\sum_{i=t-n}^{t-1} \log p\left(z_t \middle| \mathbf{x}_t, \mathbf{w}_{t-1}\right) \tag{7}$$

471 and the weights are again optimized as in Eqn 6.
472
**Recovering policy matrices from simulated data**
To test the model's ability in recovering policy matrices, we trained the model on data generated
from pre-defined ground truth policies. The ground truth policies changed every 10 trials, 30
trials, or 90 trials. Binary choices were simulated with different noise levels using the algorithm
'epsilon-greedy': with a probability of epsilon, the simulator made a random choice and with a
probability of 1-epsilon it chose the action indicated by the ground truth policy. The noise levels
(epsilon values) ranged from 0 to 0.6. The similarity between the recovered policy and the
ground truth policy was evaluated by the cosine between the recovered weight vector and the
ground truth weight vector.
482
**Automated behavior assessment software**
In this section we describe each part of the software that constitutes the system we developed to
track the mouse. The software is primarily made of two parts: mouse detection and pose
estimation, each of which is implemented by a deep convolutional neural network (CNN) trained
on annotated video data (**Supplementary Fig. 7a**). We collected a set of videos using red or IR

light illumination from the top of the arena. From these videos we extracted randomly a set of
15,000 frames and asked Amazon Mechanical Turk (AMT) workers to click on body landmarks
which give a representation of the skeleton of the mouse (**Supplementary Fig. 7b**).
491
**Mouse detection**
The architecture used for detection is the multi-scale convolutional (MSC) Multibox network[28],
which computes a list of bounding boxes along with a single confidence score for each box,
corresponding to its likelihood of containing the object of interest, in this case a mouse. Each
bounding box is encoded by 4 scalars, representing the coordinates of the upper-left and lower-
right coordinates. The coordinates of each box are normalized with respect to image dimensions
to deal with different image sizes, and their associated confidence score is encoded by an
additional node (which ouputs a value from 0 to 1). The loss function is the weighted sum of
two losses: confidence and location[28]. We trained the MSC-Multibox deep CNN to predict
bounding boxes that are spatially closest to the ground truth boxes while maximizing the
confidence of containing the mouse.
503
In order to reach better and faster detection, we used prior bounding boxes whose aspect ratios
closely match the distribution of the ground truth. As proposed previously by Erhan et al[28], these
priors were selected because their Intersection over Union (IoU) with respect to the ground truth
was over 0.5. In the following matching process, each ground truth box is best matched to a
prior, and the algorithm learns a residual between the two. At inference time, 100 bounding
boxes are proposed, from which the best one is selected based on the highest score and non-
maximum suppression.
511
We split the dataset into 12,750 frames for training, 750 for validation and 1,500 for testing.
During training, we augmented data with random cropping and color variation. Using the
Inception-ResNet-V2 architecture initialized with ImageNet pre-trained weights[45], we finetuned
the network with our training samples by updating the weights using stochastic gradient descent.
For the optimizer, we used RMPSProp, with the batch size set to 4, the initial learning rate set to
0.01, and the momentum and the decay both set to 0.99[46]. Images were resized to 299 x 299. We
trained the detector on a machine with a 8-core Intel i7-6700K CPU, 32GB of RAM, and a 8GB
GTX 1080 GPU. The model was trained for 288k iterations. A single instance of the forward
pass took on average 15 ms.
521
522   We evaluated the models using the detection metric Intersection over Union (IoU). Thresholding
523   the IoU defines matches between the ground truth and predicted boxes and allows computing
524   precision-recall curves. The precision-recall curve at different threshold of IoU is shown in
525   **Supplementary Fig. 7d**. In **Supplementary Table 2**, we report mean averaged precision (mAP)
526   and recall (mAR).
527
**Pose estimation**
With the bounding box generated from the MSC-Multibox deep CNN, we wish to determine the
precise pixel location of the keypoints that would describe the body features of the mouse. As a
well established problem in computer vision, a good pose estimation system must be robust to
occlusion, deformation, successful on rare and novel poses, invariant to changes in appearance
from differences in lighting and backgrounds.

The keypoints we chose are the nose, the ears, the neck, the body sides, and the base of the tail
(**Supplementary Fig. 7b**). These features were chosen because they are best recognized
regardless of the size of the animal, and one can deduce from them secondary features, such as
orientation of the animal. We used Stacked Hourglass Network[29] to estimate the keypoints. This
architecture has the capacity to learn all seven features and and output pixel-level predictions.
The output of the network is a set of heatmaps, one for each keypoint, representing the
probability of the keypoint's presence every pixel (**Supplementary Fig. 7a**). We estimated the
location of the keypoint by the maximum of its heatmap. A mean squared error (MSE) loss was
used to compare the predicted heatmap to the ground truth.

During training, cropped frames with the mouse centered in the bounding box were resized to a
resolution of 256 x 256. We also augmented the training data as follows (p is the probability of
applying a type of augmentation):
- rotation with $p = 1$: angles were selected uniformly between 0° and 180°
- translation
- horizontal and vertical flips
- scaling with $p = 1$: scaling factors were chosen from a pool of 0.10 to 0.65, uniformly
- color variation: adjusted brightness/contrast/gamma with $p = 0.5$ in order to emulate the
effects of poor lighting/setup
- Gaussian blur with $p = 0.15$: frames were blurred either by a $\sigma = 1$ or $\sigma = 2$ (chosen
uniformly).
- Gaussian Noise added independently across image with $p = 0.15$
- JPEG artifact with $p = 0.15$: added artifacts of JPEG compression onto the image
Extreme augmentations (with multiple types of augmentations) were examined to make sure that
the transformed data looked reasonable. Using original and augmented keypoint annotations, we
trained a pose estimator from scratch.

Training started from randomly initialized weights, and continued until validation accuracy
plateaued, taking approximately 6 days. This training process was performed for 749k iterations.
The network was trained using TensorFlow (Google) on a machine with 8-core Intel Xeon CPU,
24GB of RAM, and a 12GB Titan XP GPU. For optimization, we used RMPSProp optimizer
with momentum and decay both set to 0.99, batch size of 8 and a learning rate of 0.00025. We
dropped the learning rate once by a factor of 5 after validation accuracy plateaus (after 33
epochs). Batch normalization was used to improve training.

Evaluation was done using the standard Percentage of Correct Keypoint (PCK) metric which
reports the fraction of detections that fall within a distance of the ground truth[29]. More than 85%
of the keypoints of the nose, ears, and neck are inferred within an error radius of 0.5 cm, and
more than 80% of the keypoints of the body sides and tail lie within an error error radius of 1 cm
(as a reference, the distance between two ears is ~3 cm). The averaged PCK of all the seven
keypoints is ~80% within a radius of less than 0.5 cm  (**Supplementary Fig. 7c**). Overall the
system's performance can be characterized as high-human, significantly exceeding the typical
annotator, but less precise than the absolute best possible.

**Supervised and unsupervised analysis of behavioral trajectories**

From the pose estimation, we extracted two features to describe an animal's behavioral trajectories: the centroid was defined as the average position of the seven body landmarks; and the angular orientation of the line from the centroid to the nose. For each trial, these two features were extracted for $n$ frames ($n = 30$ (1 s) in most cases), thus the data dimension for each trial is $3n$ (the two centroid coordinates and the orientation).

To determine whether the behavioral trajectories contain information about the decision categories, a support vector machine (SVM) with a linear kernel was trained for each decision category. The training set was labelled with the decision category based on information about the visual stimulus and the animal's choice (for example, "Stim: R, Choice: L" means that the light is on the right and the animal chooses the left port). Performance of the trained SVM was examined by prediction accuracy on the test set, and the F1 score, which is the harmonic mean of precision and recall:

$$F_1 = 2 \cdot \frac{precision \cdot recall}{precision + recall} = \frac{2 \cdot true\_positive}{2 \cdot true\_positive + false\_positive + false\_negative} \quad (8)$$

The performance was computed as the average across 10 repeated analyses (**Supplementary Fig. 8**).

We performed a non-linear embedding method, t-distributed stochastic neighbor embedding (t-SNE) analysis as previously described[31,32]. Briefly, the trajectory data of each trial were projected into a 2D t-SNE space. Point clouds on the t-SNE map represented candidate clusters. Density clustering identified these regions. We then plotted trajectories and reaction time distributions to confirm that the clusters were distinct from each other. A repository of the analysis scripts can be found in https://github.com/tonyzhang25/MouseAcademyBehavior.

**AUTHOR CONTRIBUTIONS**

M.Q. and M.M. designed the study; M.Q. and S.S. constructed the hardware setup and wrote the controlling software; M.Q. performed experiments and collected data for analysis; M.Q. developed the iterative generalized linear model with input from P.P. and M.M; C.S. developed the automated tracking software; T.Z. implemented animal tracking and behavioral trajectory analysis with input from M.Q., P.P. and M.M; M.Q. and M.M. wrote the manuscript with comments from all authors.

**ACKNOWLEDGEMENT**

We thank Joshua Sanders for technical assistance in incorporating Bpod into our system. We thank Ann Kennedy for insightful comments and suggestions on analysis of the behavioral trajectories. We thank Oisin Mac Adoha and Yuxin Chen for helpful comments and discussions. This work was supported by a grant from the Simons Foundation (SCGB 543015, M.M. and P.P.) and a postdoctoral fellowship from the Swartz Foundation (M.Q.).

**COMPETING FINANCIAL INTERESTS**

The authors declare no competing financial interests.

**DATA AVAILABILITY**

The datasets analyzed during the current study are available in
https://drive.google.com/open?id=1gkPbqGYKPGs7Rx1WNmubQW0dKyYE5YVR

**REFERENCES**

Spear, N. E., Miller, J. S. & Jagielo, J. A. Animal memory and learning. *Annu Rev Psychol* **41**, 169-211, doi:10.1146/annurev.ps.41.020190.001125 (1990).

Branson, K., Robie, A. A., Bender, J., Perona, P. & Dickinson, M. H. High-throughput ethomics in large groups of Drosophila. *Nature methods* **6**, 451-457, doi:10.1038/nmeth.1328 (2009).

Honegger, K. & de Bivort, B. Stochasticity, individuality and behavior. *Current biology : CB* **28**, R8-R12, doi:10.1016/j.cub.2017.11.058 (2018).

Matzel, L. D. & Sauce, B. Individual differences: Case studies of rodent and primate intelligence. *J Exp Psychol Anim Learn Cogn* **43**, 325-340, doi:10.1037/xan0000152 (2017).

Atkinson, J. W. & Raphelson, A. C. Individual differences in motivation and behavior in particular situations. *J Pers* **24**, 349-363 (1956).

Stern, E. Individual differences in the learning potential of human beings. *Npj Science of Learning* **2** (2017).

Luo, L., Callaway, E. M. & Svoboda, K. Genetic Dissection of Neural Circuits: A Decade of Progress. *Neuron* **98**, 865, doi:10.1016/j.neuron.2018.05.004 (2018).

Carandini, M. & Churchland, A. K. Probing perceptual decisions in rodents. *Nature neuroscience* **16**, 824-831, doi:10.1038/nn.3410 (2013).

Gomez-Marin, A., Paton, J. J., Kampff, A. R., Costa, R. M. & Mainen, Z. F. Big behavioral data: psychology, ethology and the foundations of neuroscience. *Nature neuroscience* **17**, 1455-1462, doi:10.1038/nn.3812 (2014).

Juavinett, A. L., Erlich, J. C. & Churchland, A. K. Decision-making behaviors: weighing ethology, complexity, and sensorimotor compatibility. *Current opinion in neurobiology* **49**, 42-50, doi:10.1016/j.conb.2017.11.001 (2018).

Schmitt, L. I. *et al.* Thalamic amplification of cortical connectivity sustains attentional control. *Nature* **545**, 219-223, doi:10.1038/nature22073 (2017).

Wimmer, R. D. *et al.* Thalamic control of sensory selection in divided attention. *Nature* **526**, 705-709, doi:10.1038/nature15398 (2015).

Akrami, A., Kopec, C. D., Diamond, M. E. & Brody, C. D. Posterior parietal cortex represents sensory history and mediates its effects on behaviour. *Nature* **554**, 368-372, doi:10.1038/nature25510 (2018).

Uchida, N. & Mainen, Z. F. Speed and accuracy of olfactory discrimination in the rat. *Nature neuroscience* **6**, 1224-1229, doi:10.1038/nn1142 (2003).

Scott, B. B., Brody, C. D. & Tank, D. W. Cellular resolution functional imaging in behaving rats using voluntary head restraint. *Neuron* **80**, 371-384, doi:10.1016/j.neuron.2013.08.002 (2013).

Busse, L. *et al.* The detection of visual contrast in the behaving mouse. *The Journal of neuroscience : the official journal of the Society for Neuroscience* **31**, 11351-11361, doi:10.1523/JNEUROSCI.6689-10.2011 (2011).

Poddar, R., Kawai, R. & Olveczky, B. P. A Fully Automated High-Throughput Training System for Rodents. *PloS one* **8**, doi:ARTN e83171
10.1371/journal.pone.0083171 (2013).

669 18 Silasi, G. *et al.* Individualized tracking of self-directed motor learning in group-housed
670   mice performing a skilled lever positioning task in the home cage. *Journal of*
671   *Neurophysiology* **119**, 337-346, doi:10.1152/jn.00115.2017 (2018).
672 19 Erskine, A. B., T.; Herb, J. T.; Schaefer, A. AutonoMouse: High throughput automated
673   operant conditioning shows progressive behavioural impairment with graded olfactory
674   bulb lesions. https://www.biorxiv.org/content/early/2018/03/29/291815 (2018).
675 20 Crabbe, J. C., Wahlsten, D. & Dudek, B. C. Genetics of mouse behavior: interactions
676   with laboratory environment. *Science* **284**, 1670-1672 (1999).
677 21 Hurst, J. L. & West, R. S. Taming anxiety in laboratory mice. *Nature methods* **7**, 825-
678   826, doi:10.1038/nmeth.1500 (2010).
679 22 Daw, N. D. in *Decision Making, Affect, and Learning: Attention and Performance XXIII*
680   (Oxford University Press, 2011).
681 23 Winter, Y. & Schaefers, A. T. A sorting system with automated gates permits individual
682   operant experiments with mice from a social home cage. *J Neurosci Methods* **196**, 276-
683   280, doi:10.1016/j.jneumeth.2011.01.017 (2011).
684 24 Daan, S. *et al.* Lab mice in the field: unorthodox daily activity and effects of a
685   dysfunctional circadian clock allele. *J Biol Rhythms* **26**, 118-129,
686   doi:10.1177/0748730410397645 (2011).
687 25 Hut, R. A., Pilorz, V., Boerema, A. S., Strijkstra, A. M. & Daan, S. Working for food
688   shifts nocturnal mouse activity into the day. *PloS one* **6**, e17527,
689   doi:10.1371/journal.pone.0017527 (2011).
690 26 Seidemann, E. Neuronal mechanisms mediating conversion of visual signals into
691   perceptual decisions in a direction discrimination task. *Ph.D. dissertation, Stanford*
692   *University.* (1998).
693 27 Burgess, C. P. *et al.* High-Yield Methods for Accurate Two-Alternative Visual
694   Psychophysics in Head-Fixed Mice. *Cell Rep* **20**, 2513-2524,
695   doi:10.1016/j.celrep.2017.08.047 (2017).
696 28 Erhan, D. S., D.; Toshev, A.; Anguelov, D. Scalable Object Detection using Deep Neural
697   Networks. https://arxiv.org/abs/1312.2249 (2014).
698 29 Newell, A. Y., K.; Deng, J. Stacked Hourglass Networks for Human Pose Estimation.
699   https://arxiv.org/abs/1603.06937 (2016).
700 30 Gris, K. V., Coutu, J. P. & Gris, D. Supervised and Unsupervised Learning Technology
701   in the Study of Rodent Behavior. *Front Behav Neurosci* **11**, 141,
702   doi:10.3389/fnbeh.2017.00141 (2017).
703 31 Berman, G. J., Choi, D. M., Bialek, W. & Shaevitz, J. W. Mapping the stereotyped
704   behaviour of freely moving fruit flies. *J R Soc Interface* **11**, doi:10.1098/rsif.2014.0672
705   (2014).
706 32 Todd, J. G., Kain, J. S. & de Bivort, B. L. Systematic exploration of unsupervised
707   methods for mapping behavior. *Phys Biol* **14**, 015002, doi:10.1088/1478-
708   3975/14/1/015002 (2017).
709 33 Botvinick, M. M., Braver, T. S., Barch, D. M., Carter, C. S. & Cohen, J. D. Conflict
710   monitoring and cognitive control. *Psychol Rev* **108**, 624-652 (2001).
711 34 Sorge, R. E. *et al.* Olfactory exposure to males, including men, causes stress and related
712   analgesia in rodents. *Nature methods* **11**, 629-632, doi:10.1038/nmeth.2935 (2014).
713 35 Barnes, C. A. Memory deficits associated with senescence: a neurophysiological and
714   behavioral study in the rat. *J Comp Physiol Psychol* **93**, 74-104 (1979).

36     Olton, D. S., Walker, J. A. & Gage, F. H. Hippocampal connections and spatial
discrimination. *Brain Res* **139**, 295-308 (1978).
37     Aoki, R., Tsubota, T., Goya, Y. & Benucci, A. An automated platform for high-
throughput mouse behavior and physiology with voluntary head-fixation. *Nat Commun* **8**,
1196, doi:10.1038/s41467-017-01371-0 (2017).
38     Shalev-Shwartz, S. Online Learning and Online Convex Optimization. *Foundations and*
*Trends in Machine Learning* **4**, 107-194 (2012).
39     Piech, C. S., J.; Huang, J.; Ganguli, S.; Sahami, M.; Guibas, L.; Sohl-Dickstein, J. Deep
Knowledge Tracing. https://arxiv.org/abs/1506.05908 (2015).
40     Hong, W. *et al.* Automated measurement of mouse social behaviors using depth sensing,
video tracking, and machine learning. *Proc Natl Acad Sci U S A* **112**, E5351-5360,
doi:10.1073/pnas.1515982112 (2015).
41     Egnor, S. E. & Branson, K. Computational Analysis of Behavior. *Annu Rev Neurosci* **39**,
217-236, doi:10.1146/annurev-neuro-070815-013845 (2016).
42     Wiltschko, A. B. *et al.* Mapping Sub-Second Structure in Mouse Behavior. *Neuron* **88**,
1121-1135, doi:10.1016/j.neuron.2015.11.031 (2015).
43     Szuts, T. A. *et al.* A wireless multi-channel neural amplifier for freely moving animals.
*Nature neuroscience* **14**, 263-269, doi:10.1038/nn.2730 (2011).
44     Ziv, Y. *et al.* Long-term dynamics of CA1 hippocampal place codes. *Nature*
*neuroscience* **16**, 264-266, doi:10.1038/nn.3329 (2013).
45     Szegedy, S. I., S.; Vanhoucke, V.; Alemi, A. Inception-v4, Inception-ResNet and the
Impact of Residual Connections on Learning. https://arxiv.org/abs/1602.07261 (2016).
46     Ruder, S. An overview of gradient descent optimization algorithms.
https://arxiv.org/abs/1609.04747 (2017).
739

# Figure 1

## a

IR camera

RFID antennas

Behavior training box with three ports

Mouse implanted with a RFID chip

Home cage

Motorized gates

**RFID-tagged mice group housed in the home cage**

**RFID based animal sorting**

**Animal training and behavior profiling**

## b

At each trial

Relevant factors x

w

Iterative GLM

Update

Prediction y

Loss function L    α

Observed choice and whether it is rewarded

Weight vector over time

Policy matrix

| Trial: | 1 | 2 | 3 | ... | N |
|---|---|---|---|---|---|
| Factor 1 | 0.8 | 0.8 | 0.8 | | 1 |
| Factor 2 | 0.2 | 0 | 0 | | 0 |
| Factor 3 | 0.3 | 0.25 | 0.2 | | 0 |
| ... | ... | ... | ... | ... | ... |
| Factor n | 0.5 | 0.5 | 0.25 | | 0 |

## c

Video data

Deep convolutional neural nets

Body Landmarks

Features: centroid and orientation

Correlate with decision-making

Animal's behavioral trajectories

Feature

Time

**Fig. 1: Components of Mouse Academy**
**(a)** An automated RFID sorting and animal training system. Mice implanted with RFID chips are group-housed in the home cage. The RFID sorting system identifies each mouse by its implanted chip. One animal at a time gains access to a behavioral training box. As the animal learns a task, its decision sequences and video recordings are acquired. **(b)** An iterative generalized linear model. For each trial, the model predicts the animal's choice based on the relevant factors and then evaluates the difference from the actual choice. This difference, after temporal weighting, is fed back to the loss function, which gets minimized by updating the weights of the input factors. The model produces a policy matrix in which the rows indicate the weights of the relevant factors and the columns are the trials. **(c)** An automated behavior assessment program using deep convolutional neural networks to extract the location and pose information of an animal.

# Figure 2

**Fig. 2: Performance of the automated training system on a sample cohort**
**(a)** Fraction of time the behavior box was occupied by each of the four animals. **(b)** Activity trace of each animal in the behavior box for the entire training period of 28 days. Shadow indicates the dark cycle from 8pm to 8am. **(c)** Distribution of time intervals during which the behavior box is occupied or empty. **(d)** Box plot of intervals between each animal's sessions (median, quartiles, and range). **(e)** Box plot of the time spent in a session for each animal. **(f)** Averaged daily water consumption of each animal. Error bars indicate standard errors. **(g)** Circadian histograms of each animal's activity in the behavior box.

# Figure 3

**Fig. 3: Iterative generalized linear model and its prediction accuracy**
**(a)** Illustration of the GLM as applied to a visual discrimination task. The model's prediction is based on the output of a logistic function whose input is the weighted sum of a visual stimulus term, a bias term, and three history-dependent terms. The stimulus can be on the left or right and the choice can be rewarded (consistent with the stimulus, indicated by a green dot) or unrewarded (opposite to the stimulus, indicated by a red dot). **(b)** Selection of the history-dependent terms based on the model prediction accuracy. Error bars indicate standard errors. **(c)** Hyperparameters for each of the animals: reward factor, discount factor, and regularization factor. The optimal values are marked with a star. **(d)** The actual performance of each animal over time in the visual task. **(e)** Performance as predicted by the GLM. **(f)** Fraction of choices predicted correctly by the GLM. **(g)** Fraction of choices predicted correctly by a simple model based on the animal's average performance in the task. **(h)** Fraction of predictions matched by the iterative GLM and the sliding window logistic regression model. Error bars indicate standard errors. **\*\***, **\*** indicate $P < 0.01, 0.05$. Random prediction would give 50% match.

# Figure 4

**Fig. 4: Interpretation of policies during learning**
**(a)** Policy vectors recovered by the iterative GLM capture the ground truth policies. The policy matrix plots in each trial (horizontal) the weights associated with each of 5 factors (vertical), encoded with a color scale (see panel c). The factors are: A = Visual_stimulus, B = Choice×Reward_back_1, C = Choice_back_1, D = Reward_back_1, E = Bias. Two examples are shown of ground truth policies used to simulate data and the corresponding trial-by-trial estimates from the GLM. Blanks in the ground truth matrix indicate instances where the simulated choice is opposite to the policy. **(b)** Similarity between the recovered policy and the ground truth, measured by the cosine between the two policy vectors. Error bars indicate standard deviation. **(c)** Policy matrices recovered for the four animals show distinct individual learning processes. Dashed rectangles highlight the first and last sessions of each animal, as enlarged in **d**. **(d)** Recovered policy matrices for the first and last sessions of each animal. **(e)** Fraction of trials explained by two candidate policies (win-stay-lose-switch and following the stimuli) in the first and last sessions. Error bars indicate standard errors. ** indicates $P < 0.01$.

# Figure 5

**a** CNN1 Multibox detector → Bounding box → CNN2 Pose estimation → Body landmarks → Feature extraction → Orientation, Centroid, Nose

**b** Animal1

Distance (cm)

Legend:
- Stim:L,Choice:L (blue)
- Stim:L,Choice:R (green)
- Stim:R,Choice:R (orange)
- Stim:R,Choice:L (red)

**c** Animal1    Animal2    Animal3    Animal4

**d** Orientation (°)

**e** Animal1    Animal2    Animal3    Animal4

Time (s)

**Fig. 5: Supervised analysis using features extracted by automated behavior assessment**
**(a)** Two deep convolutional neural networks (CNNs) extract relevant features of mouse behavior. The first CNN generates for each video frame a bounding box that encloses the animal. The second CNN operates on the bounding box and generates seven body landmarks for nose, ears, neck, body sides, and tail. The centroid is the average of the seven body landmarks and the orientation is the angle between the horizontal axis and the line connecting the centroid and the nose. **(b)** Centroid distance along the left-right axis vs time during the movement, for animal 1. The starting position is set to zero, positive values indicate movement to the left, negative to the right. The 4 trial types are indicated by different colors. **(c)** Average centroid trajectory for each animal. Shaded region indicates standard error. **(d-e)** Orientation vs time, displayed as in panels b-c. Positive angle points to the left, negative to the right.

# Figure 6

**Fig. 6: Unsupervised analysis of the behavior trajectories**
**(a)** Principal component projections onto PC1 and PC2 of the centroid-vs-time trajectories from Fig 5. The 4 trial types are indicated by different colors. **(b)** The centroid trajectories corresponding to the first three principal components (PCs). The variance explained by each PC is shown in the plot legend. **(c)** Clustering trials by their trajectories using t-SNE analysis. Distinct clusters are marked with different colors for use in subsequent panels. **(d)** Averaged centroid distance vs time for each cluster, plotted as in Fig 5b. **(e)** Box plot of the reaction time for each cluster. **(f)** The error rate on the preceding trial for each cluster. Error bars indicate standard errors.

1    **Supplementary Materials**

3    **Supplementary Table 1. Cost Analysis of Mouse Academy Hardware**

4    **PC version**

| Parts | Quantity | Supplier | Cost |
|---|---|---|---|
| Bpod State Machine | 1 | Sanworks | $495.00 |
| Custom behavior box (Plastic, ports with LEDs and photo-gates, valves, etc.) | 1 | Port breakout boards from Sanworks | $500.00 |
| IR Webcam | 1 | Ailipu Technology | $47.99 |
| Custom light- and sound-proof chamber | 1 | NA | $75.00 |
| Arduino Mega 2560 R3 | 1 | Sparkfun | $45.95 |
| RFID Reader ID-12LA | 3 | Sparkfun | $29.95 |
| Servo - Generic | 2 | Sparkfun | $8.95 |
| Custom tunnel (Plastic, holders, antennas etc.) | 1 | NA | $150.00 |
| Engineered home cage | 1 | Caltech animal facility | $76.10 |
| PC | 1 | Hewlett-Packard | $1000.00 |
| **Total cost** | | | $2428.94 |

6    **Raspberry Pi version**

| Parts | Quantity | Supplier | Cost |
|---|---|---|---|
| Bpod State Machine | 1 | Sanworks | $495.00 |
| Custom behavior box (Plastic, ports with LEDs and photo-gates, valves, etc.) | 1 | Port breakout boards from Sanworks | $500.00 |
| OpenMV Camera M7 | 1 | OpenMV | $65.00 |
| Custom light- and sound-proof chamber | 1 | NA | $75.00 |
| Arduino Mega 2560 R3 | 1 | Sparkfun | $45.95 |
| RFID Reader ID-12LA | 3 | Sparkfun | $29.95 |
| Servo - Generic | 2 | Sparkfun | $8.95 |
| Custom tunnel (Plastic, holders, antennas etc.) | 1 | NA | $150.00 |
| Engineered home cage | 1 | Caltech animal facility | $76.10 |
| Raspberry Pi 3 Model B | 1 | Raspberry Pi | $35.10 |
| **Total cost** | | | $1481.05 |

8 **Supplementary Table 2: mean averaged precision (mAP) and recall (mAR) at different**
9 **threshold of Intersection over Union (IoU) (related to mouse detection)**

|  | mAP | mAR |
|---|---|---|
| $0.75 < IoU < 0.95$ | 0.81 | 0.82 |
| $IoU = 0.5$ | 0.99 | 0.99 |
| $IoU = 0.75$ | 0.95 | 0.98 |

# Supplementary Figure 1

**Supplementary Fig. 1: Technical details of the hardware design**
**(a-b)** Side view of the setup (**a**) packed into a light- and sound-proof box (**b**). **(c)** RFID sorting
process. For an animal to enter the behavior box, only when the left and the middle detectors
detect the same RFID chip, the left gate is closed and the right gate is open so that the animal can
access the behavior box. For an animal to return to the home cage, only when the right and the
middle detectors detect the same RFID chip, the right gate is closed and the left gate is open so
that the animal can go back to the home cage. In the entry and the return processes, if the left and
the middle detectors detect different RFID chips, the animals have to leave the tube and the
detectors get reset afterwards. **(d)** Schematic of RFID access control circuit. **(e)** Schematic of the
software controlling the devices. A master program receives input from the RFID sorting device
and controls four other modules including Bpod, synchronized video recording, data
management, and logging. **(f)** Top view of a Raspberry Pi version of the setup.

# Supplementary Figure 2

**Supplementary Fig. 2: Illustration of training procedures**

Training proceeds through six stages (Online methods). The design, learning curves, and animal performance of the simple visual task **(a, a', a'')**, the simple auditory task **(b, b', b'')**, the cued single-modality (visual or auditory) switching task **(c, c', c'')**, the cued single- (visual or auditory) and double-modality (attend to vision or audition) switching task **(d, d', d'')**, the cued double-modality (attend to vision or audition) switching task **(e', e'')**, and the final selective attention task **(f, f', f'')** are shown here. **a'** displays performance data as in **Fig. 3e**. Brown and gray dashed lines indicate the performance thresholds for upgrading to the next stage and downgrading to the previous stage respectively.

# Supplementary Figure 3

32  **Supplementary Fig. 3: Automated training system allows efficient use of the behavior box**
33  For a sample cohort of five animals, this shows the fraction of time each animal used the
34  behavior box (**a**) and the activity trace of each animal throughout one month.

# Supplementary Figure 4

**Supplementary Fig. 4: Additional analysis on the iterative generalized linear model's prediction accuracy**

The actual performance and the performance predicted by the model, for each of the four animals. Note that the predictions recapitulate the more prominent fluctuations in the actual learning curves. Error bars indicate standard errors.

# Supplementary Figure 5

**Supplementary Fig. 5: Iterative generalized linear model captures differences between**
**individuals and policy changes**
**(a-b)** Hyperparameter selection for the GLMs fitted to the simulated data generated from the
ground truth policies. Different values of policy change frequency and noise level (epsilon) lead
to different landscapes of the hyperparameters. **(c-e)** Selected temporal discount factor (**c**),
reward factor (**d**) and regularization factor (**e**) for different values of policy change frequency
and noise level (epsilon). **(f)** Fraction of the trials explained by the two policies (win-stay-lose-
switch or WSLS, and following the stimuli) in the first and last sessions, for each of the four
animals.

# Supplementary Figure 6

## a

## b

## c

**Supplementary Fig. 6: Additional analyses of policy changes during learning**
**(a)** Policy matrices over sessions of the four animals. Here the policy matrices are recovered
from logistic regression using only the trials following a correct response. Because the reward of
the last trial is always +1, the term Reward_back_1 is the same as Bias, and the term
RewardxChoice_back_1 is equal to Choice_back_1, so we drop them to avoid redundancy. **(b-c)**
Quantification of the error rate during the last session, comparing trials following a correct
response to those following a mistake. Averaged over all four animals (**b**) and for each of the
four animals (**c**). n.s. indicates not significant.

# Supplementary Figure 7

a

Video frames | Preprocess: resize, normalize | Multibox detector | Postprocess: Filter good bboxes | Preprocess bboxes: crop bboxes, pad, normalize | Pose estimation | Postprocess heatmaps: keypoints coords | Pose

b

c

Nose Tip

Left Ear

Right Ear

Neck

Left Side Body

Right Side Body

Tail Base

All keypoints averaged

d

**Supplementary Fig. 7: Technical details of the automated behavior assessment software**
**(a)** Detailed illustration of the automated behavior assessment software as presented in **Fig. 5a**.
Video frames are first preprocessed (resized and normalized) and then passed through the MSC-
Multibox detector (the first deep neural network (DNN)) to generate bounding boxes covering
the mouse body. Then images of the mouse around the bounding box are cropped, padded and
normalized for pose estimation. Pose estimation is done by Stacked Hourglass Network (the
second DNN), which produces seven keypoint coordinates for body landmarks as shown in **b**.
**(b)** The seven body landmarks of the nose, the ears, the neck, the body sides, and the tail. **(c)**
Percentage of Correct Keypoint (PCK) curves. The fraction of inferred keypoints that lie within a
specified pixel radius of the true location (10 pixels = 0.25 cm). On average over all seven
keypoints ~80% lie within an error radius of 0.5 cm. **(d)** Precision-Recall curves at different
thresholds of Intersection over Union (IoU) w.r.t ground truth bounding box. An IoU of 75%
already detects mice very effectively, with precision and recall above 95% .

# Supplementary Figure 8

70  **Supplementary Fig. 8: Performance of the support vector machine to infer trial category**
71  **from mouse trajectories**
72  **(a)** Prediction accuracy of the SVMs for individual animals. **(b)** F1 score of the SVM fitted for
73  the decision categories of each animal. Shaded region denotes standard error.

# Supplementary Figure 9

**Supplementary Fig. 9: Additional information on the unsupervised analysis of behavior**
**trajectories**
**(a)** Projection of trajectories onto PC1 and PC3. Different decision categories are indicated by
different colors, which is the same for **b** and **c**. **(b)** Scatter plot of starting positions along the left-
right axis against PC2 shows correlation between the two. Starting positions are normalized to
range from 0 (the leftmost position) and 1 (the rightmost position). **(c)** t-SNE plots with colors
indicating different decision categories.

**Supplementary Video 1:**
https://drive.google.com/open?id=1Ng5s1UhlFRdV4mZ5b1Ot7EUpaEiUXN2_
83
84  **Supplementary Video 2:**
85  https://drive.google.com/open?id=15qgqM5qOd30kajT-IQkCf8flcF80U2qV
86
87  **Supplementary Video 3:**
88  https://drive.google.com/open?id=1zqja6_3bA2jO9ap0EWd5t_Z_dVOA8FmA
89
90  **Supplementary Video 4:**
91  https://drive.google.com/open?id=1wiaaBD-sfZTudDbpRM0ByB2n9bTKyaid
92
93  **Supplementary Video 5:**
94  https://drive.google.com/open?id=1yjaZXDUS3TKzDR4YGHYUlbwbq0OfUmI4
95
96  **Supplementary Video 6:**
97  https://drive.google.com/open?id=1ISELpiyI0Yh_EoiGn7aX1GLSoUaFtjKa
98
99  **Supplementary Video 7:**
100 https://drive.google.com/open?id=1dILuZRlwAU48RwLEEkt1CBzmPQnqF95r
101