Human online adaptation to changes in prior probability

Elyse H. Norton[1], Luigi Acerbi[1,2,†], Wei Ji Ma[1,2], Michael S. Landy[1,2,*]

1 Psychology Department, New York University, New York, NY, USA
2 Center for Neural Science, New York University, New York, NY, USA

†Current Address: Département des neurosciences fondamentales, Université de Genève, CMU, 1 rue Michel-Servet, 1206 Genève, Switzerland
* Corresponding author, email: landy@nyu.edu

Abstract

Optimal sensory decision-making requires the combination of uncertain sensory signals with prior expectations. The effect of prior probability is often described as a shift in the decision criterion. Can observers track sudden changes in probability? To answer this question, we used a change-point detection paradigm that is frequently used to examine behavior in changing environments. In a pair of orientation-categorization tasks, we investigated the effects of changing probabilities on decision-making. In both tasks, category probability was updated using a sample-and-hold procedure. We developed an ideal Bayesian change-point detection model in which the observer marginalizes over both the current run length (i.e., time since last change) and the current category probability. We compared this model to various alternative models that correspond to different strategies – from approximately Bayesian to simple heuristics – that the observers may have adopted to update their beliefs about probabilities. We find that probability is estimated following an exponential averaging model with a bias towards equal priors, consistent with a conservative bias. The mechanism underlying change of decision criterion is a combination of on-line estimation of prior probability and a stable, long-term equal-probability prior, thus operating at two very different timescales.

Author summary

We demonstrate how people learn and adapt to changes to the probability of occurrence of one of two categories on decision-making under uncertainty. The study combined psychophysical behavioral tasks with computational modeling. We used two behavioral tasks: a typical forced-choice categorization task as well as one in which the observer specified the decision criterion to use on each trial before the stimulus was displayed. We formulated an ideal Bayesian change-point detection model and compared it to several alternative models. We found that the data are best fit by a model that estimates category probability based on recently observed exemplars with a bias towards equal probability. Our results suggest that the brain takes multiple relevant time scales into account when setting category expectations.

Introduction

Sensory decision-making involves making decisions under uncertainty. Furthermore, optimal sensory decision-making requires the combination of uncertain sensory signals

with prior expectations. Perceptual models of decision-making often incorporate prior expectations to describe human behavior. In Bayesian models, priors are combined with likelihoods to compute a posterior [1]. In signal detection theory, the effect of unequal probabilities (signal present vs. absent) is a shift of the decision criterion [2].

The effects of prior probability on the decision criterion have been observed in detection [2–4], line tilt [5], numerosity estimation [6, 7], recognition memory [8], and perceptual categorization [9] tasks, among others. These studies generally use explicit priors, assume a fixed effect, and treat learning as additional noise. However, there are many everyday tasks in which the probability of a set of alternatives needs to be assessed based on one's past experience with the outcomes of the task. The importance of experience has been demonstrated in studies examining differences between experience-based and description-based decisions [10, 11] and in perceptual-categorization tasks with unequal probability, in which response feedback leads to performance that is closer to optimal than observational feedback [12, 13]. While these studies demonstrate the importance of experience on decision-making behavior, they do not describe how experience influences expectation formation. The influence of experience on the formation of expectations has been demonstrated for learning stimulus mean [14–17], variance [14, 18], higher-order statistics [19], likelihood distributions [20], the rate of change of the environment [15–17, 21–23], and prior probability [24, 25]. Here, we add to previous work by investigating how one's previous experience influences probability learning in a changing environment.

In the previous work on probability learning by Behrens et al. [24], participants tracked the probability of a reward to learn the value of two alternatives. This is a classic decision-making task that involves combining prior probability and reward. In contrast, we are interested in perceptual decision-making under uncertainty, in which prior probability is combined with uncertain sensory signals. We might expect differences in strategy between cognitive and perceptual tasks, as cognitive tasks can be susceptible to additional biases. For example, participants often exhibit base rate neglect (i.e., they ignore prior probability when evaluating evidence) in cognitive tasks [26] but not in perceptual tasks [2]. On the other hand, Behrens et al. [24] found that participants' behavior was well described by an optimal Bayesian model, in that observed learning rates quantitatively matched those of a Bayesian decision-maker carrying out the same task. Although it is important to note that behavior was not compared to alternative models. A more recent study by Zylberberg et al. [25] examined probability learning under uncertainty in a motion-discrimination task. In this study, probability was estimated from a confidence signal rather than explicit feedback. Additionally, probability was changed across blocks, allowing participants to infer a change had occurred. Here, we examine probability learning when feedback is explicit and changes are sudden.

To investigate probability learning in uncertain and changing conditions, we designed a perceptual-categorization task in which observers need to learn category probability through experience. To prevent the use of external cues (e.g., the start of a new block indicating a change in probability) probabilities were changed using a sample-and-hold procedure. This approach has been used in decision-making [21, 22, 24] and motor domains [18] to examine behavior in dynamic contexts. Observers completed both a covert- and overt-criterion task, in which the decision criterion was implicit or explicit, respectively. The overt task, previously developed by Norton et al. [16], provided a richer dataset upon which to compare models of human behavior. We determined how observers tracked category probability in a changing environment by comparing human behavior to both Bayesian and alternative models. We find that a number of models qualitatively describe human behavior, but that, quantitatively, all models are outperformed by an exponential

averaging model with a bias towards equal priors. Our results suggest that changes in the decision criterion are the result of both probability estimates computed on-line and a more stable, long-term prior.

Results

Experiment

During each session, observers completed one of two orientation-categorization tasks. On each trial in the *covert-criterion* task, observers categorized an ellipse as belonging to category A or B by key press (Fig 1A). On each trial in the *overt-criterion* task, observers used the mouse to rotate a line to indicate their criterion prior to the presentation of an ellipse (Fig 1B). The observer was correct if the ellipse belonged to category A and was clockwise of the criterion line or if the ellipse belonged to category B and was counter-clockwise of the criterion line. The overt-criterion task is an explicit version of the covert-criterion task developed by Norton et al. [16]. The overt-criterion task provides a richer dataset than the covert-criterion task in that it affords a continuous measure and allows us to see trial by trial changes in the reported decision criterion, at the expense of being a more cognitive task. In both tasks, the categories were defined by normal distributions on orientation with different means ($\mu_\mathrm{B} = \mu_\mathrm{A} + \Delta\theta$) and equal standard deviation (σ_C); the mean of category A was set clockwise of the the mean of category B and a neutral criterion would be located halfway between the category means (Fig 1C). The difficulty of the task was equated across participants by setting $\Delta\theta$ to a value that predicted a d' value of 1.5 based on the data from the initial measurement session (see Methods). All data are reported relative to the neutral criterion, $z_\mathrm{neutral} = (\mu_\mathrm{A} + \mu_\mathrm{B})/2$.

Prior to testing, observers were trained on the categories. Only the covert-criterion task was used for training (see Section 6 in S1 Appendix). During training, category probability was equal ($\pi = 0.5$) and observers received feedback on every trial that indicated both the correctness of the response (tone) and the generating category (visual). As a measure of category learning, we compute the probability of being correct in the training block and averaged across sessions. All observers learned the categories to the expected level of accuracy ($p(\mathrm{correct}) = 0.74 \pm 0.01$; mean $\pm$ SEM across observers), given that the expected fraction of correct responses for an ideal observer with $d' = 1.5$ and equal priors over categories is 0.77. As an additional test of category learning, immediately following training observers estimated the mean orientation of each category by rotating an ellipse. Each category mean was estimated once and no feedback was provided. There was a significant correlation between the true and estimated means for each category (category A: $r = 0.82$, $p < 0.0001$; category B: $r = 0.97$, $p < 0.0001$), suggesting that categories were learned. However, on average mean estimates were repelled from the category boundary (average category A error of $11.3° \pm 6.3°$ and average category B error of $-8.0° \pm 2.6°$; mean $\pm$ SEM across observers) suggesting a systematic repulsive bias.

To determine how category probability affects decision-making, during testing category A probability π_t was determined using a sample-and-hold procedure (Fig 1D; category B probability was $1 - \pi_t$). For $t = 1$, category A probability was randomly chosen from a set of five probabilities $S_\pi = \{0.2, 0.35, 0.5, 0.65, 0.8\}$. On most trials, no change occurred ($\Delta_t = 0$), so that $\pi_{t+1} = \pi_t$. Every 80-120 trials there was a change point ($\Delta_t = 1$), with change point sampled uniformly. At each change point, category probability was randomly selected from the S_π excluding the current probability. On each trial t, a category C_t was randomly selected (with $P(\text{category A}) = \pi_t$) and a stimulus s_t was drawn from the stimulus distribution corresponding to the selected

category. We assume that the observer's internal representation of the stimulus is a noisy measurement x_t drawn from a Gaussian distribution with mean s_t and standard deviation σ_v, which represents visual noise (v). The generative model of the task is summarized in Fig 1E.

Fig 1. Experimental design. A: Trial sequence in the covert-criterion task. After stimulus offset, observers reported the category by key press and received auditory feedback indicating the correctness of their response. In addition, the fixation cross was displayed in the color of the generating category. B: Trial sequence in the overt-criterion task. Prior to stimulus onset, observers rotated a line to indicate their criterion by sliding the mouse side-to-side. When the observer clicked the mouse, a stimulus was displayed under the criterion line and auditory feedback was provided. C: Example stimulus distributions for category A (green) and category B (red). Note that numbers on the x-axis are relative to the neutral criterion (i.e., 0 is the neutral criterion). D: Example of random stepwise changes in probability across a block of trials. Change points occurred every 80-120 trials and are depicted above by the black arrows. Category A probabilities π_t were sampled from a discrete set, $S_\pi = \{0.2, 0.35, 0.5, 0.65, 0.8\}$. E: Generative model for the task in which category probability π is updated following a sample-and-hold procedure, a category C is selected based on the category probability, a stimulus s is drawn from the category distribution and is corrupted by visual noise resulting in the noisy measurement x. Note that this diagram omits the dependency that leads to change points every 80-120 trials.

Bayesian models

To understand how decision-making behavior is affected by changes in category probability, we compared observer performance to several Bayesian models. To compute the behavior of a Bayesian observer, we developed a Bayesian change point-detection algorithm, based on Adams and MacKay [27], but which also accounts

for Markov dependencies in the transition distribution after a change. Specifically, the
Bayesian observer estimates the posterior distribution over the current run length
(time since the last change point), and the state (category probability) before the last
change point, given the data so far observed (category labels until trial t,
$C_t = (C_1, \ldots, C_t)$). We denote the current run length at the end of trial t by r_t, the
current state by π_t, and the state before the last change point by ξ_t, where both
$\pi_t, \xi_t \in S_\pi$. That is, if a changepoint occurs after trial t (i.e., $r_t = 0$), then the new
category A probability will be π_t and the previous run's category probability
$\xi_t = \pi_{t-1}$. If no changepoint occurs, both π and ξ remain unchanged. We use the
notation $C_t^{(r)}$ to indicate the set of observations (category labels) associated with the
run r_t, which is $C_{t-r_t+1:t}$ for $r_t > 0$, and $\emptyset$ for $r_t = 0$. The range of times with a colon,
e.g., $C_{t':t}$, indicates the sub-vector of C with elements from t' to t included.

Both of our tasks provide category feedback, so that at the end of trial t the
observer has been informed of $C_{1:t}$. In S1 Appendix we derive the iterative Bayesian
ideal-observer model. After each trial, the model calculates a posterior distribution
over possible run lengths and previous probability states, $P(r_t, \xi_t | C_{1:t})$. The
generative model makes it easy to calculate the conditional probability of the current
state for a given run length and previous state, $P(\pi_t | r_t, \xi_t, C_{1:t})$. These two
distributions may be combined, marginalizing (summing) across the unknown run
length and previous states to yield the predictive probability distribution of the
current state, $P(\pi_t | C_{1:t})$. Given this distribution over states, in both tasks the
observer needs to determine the probability of each category. In particular,

$$P(C_{t+1} = \mathrm{A} | C_{1:t}) = \mathbb{E}[\pi_t] = \sum_{\pi_t \in S_\pi} \pi_t P(\pi_t | C_{1:t}). \tag{1}$$

In the overt task, the ideal observer sets the current criterion to the optimal value
z_t^{opt} based on the known category orientation distributions and the current estimate of
category probabilities. Further, in the ideal and all subsequent models of the overt
task, in addition to early sensory noise (σ_v) we assume the actual setting is perturbed
by adjustment noise ($z_t = z_t^{\mathrm{opt}} + \varepsilon_t$, where $\varepsilon_t \sim \mathcal{N}(0, \sigma_a^2)$).

In the covert task, the observer views a stimulus and makes a noisy measurement
x_t of its true orientation s_t with noise variance σ_v^2. The prior category probability is
combined with the noisy measurement to compute category A's posterior probability
$P(C_{t+1} = \mathrm{A} | x_{t+1}, C_{1:t})$. The observer responds "A" if that probability is greater than
0.5.

We consider the ideal-observer model (Bayes$_{\mathrm{ideal}}$) and three (suboptimal) variants
thereof, which deviate from the ideal observer in terms of their beliefs about specific
features of the experiment (Bayes$_r$, Bayes$_\pi$, and Bayes$_\beta$). Two further variants of the
Bayesian model (Bayes$_{\mathrm{bias}}$ and Bayes$_{r,\beta}$) are described in S1 Appendix. Crucially, all
these models are "Bayesian" in that they compute a posterior over run length and
probability state, but they differ with respect to the observer's assumptions about the
generative model.

Bayes$_{\mathrm{ideal}}$ The ideal Bayesian observer uses knowledge of the generative model to
maximize expected gain. This model assumes knowledge of sensory noise, the category
distributions, the set of potential probability states, and the run length distribution.
Because observers were trained on the categories prior to completing each
categorization task, assuming knowledge of the category distributions seems
reasonable. Further, it is reasonable to assume knowledge of sensory noise as this is a
characteristic of the observer. However, since observers were not told how often
probability would change, nor were they told the set of potential probability states,
observers may have had incorrect beliefs about the generative model. Thus, we

developed additional Bayesian models (described below), in which observers could have potentially incorrect beliefs about different aspects of the generative model.

Bayes$_r$ The Bayes$_r$ model allows for an observer to have an incorrect belief about the run length distribution. For a given discrete r, the observer believes that the run length distribution is drawn from a discrete uniform distribution, $\sim \mathrm{Unif}\left[\left\lfloor\frac{2}{3}r\right\rfloor, r\right]$. We chose this particular interval rather than a more general one, because it is simple and includes the true generative distribution. For the ideal observer, $r = 120$.

Bayes$_\pi$ The Bayes$_\pi$ model allows for an observer to have an incorrect belief about the set of probability states. The veridical set of experimental states is five values of π ranging from 0.2 to 0.8. The Bayes$_\pi$ model observer also assumes five possible values of π evenly spaced, but ranging from π_{min} to $\pi_{\mathrm{max}} = 1 - \pi_{\mathrm{min}}$, where π_{min} is a free parameter.

Bayes$_\beta$ While incorrect assumptions about parameters of the generative model result in suboptimal behavior, suboptimality can also arise from prior biases (that is, incorrect hyper-parameters). The Bayes$_\beta$ model, like the Bayes$_{\mathrm{ideal}}$ model, assumes knowledge of the generative model, but also includes a hyperprior $\mathrm{Beta}(\beta, \beta)$ that is applied after a change-point. Thus, as β increases, the posterior belief over category probabilities is biased toward equal probability. For the ideal observer, $\beta = 1$ (a uniform distribution).

Heuristic models

In addition to the Bayesian models described above, we tested the following heuristic models that do not require the observer to compute a posterior over run length and probability state. In each of the following models, assumptions vary about whether and how probability is estimated. In the Fixed Criterion (Fixed) model the observer assumes fixed probabilities. In the Exponential-Averaging (Exp), Exponential-Averaging with Prior Bias (Exp$_{\mathrm{bias}}$), and the Wilson et al. (2013) models, probability is estimated based on the recent history of categories. Finally, in the Reinforcement-Learning (RL) model, the decision criterion is updated following an error-driven learning rule with no assumptions about probability. We also tested three additional heuristic models that are described in the Supplementary material (see S1 Appendix).

Each of the following models, other than the RL model, computes an estimate of category probability ($\hat{\pi}_{\mathrm{A},t}$) on each trial and the estimated probability of the alternative is $\hat{\pi}_{\mathrm{B},t} = 1 - \hat{\pi}_{\mathrm{A},t}$. On each trial, the optimal criterion z_{opt} is computed based on these estimated probabilities in the identical manner as for the Bayesian models. To make a categorization decision in the covert-criterion task, the criterion is applied to the noisy observation of the stimulus. In the overt-criterion task, the observer reports the criterion, which we again assume is corrupted by adjustment noise.

Fixed   While incorporating category probability into the decision process maximizes expected gain, an alternative strategy is to ignore changes in probability and fix the decision criterion throughout the block. In the fixed-criterion model, we assume equal category probability and the criterion is set to the neutral criterion:

$$z = \frac{1}{2}(\mu_{\mathrm{B}} + \mu_{\mathrm{A}}). \tag{2}$$

This model is equivalent to a model in which the likelihood ratio, $\frac{P(x_t|C_t=\text{A})}{P(x_t|C_t=\text{B})}$, is used to make categorization decisions rather than the posterior odds ratio in the covert-criterion task. This is a reasonable strategy for an observer who wants to make an informed decision, but is unsure about the current probability state and its rate of change.

Exp The exponential-averaging model computes smoothed estimates of category probability by taking a weighted average of previously experienced category labels, giving more weight to recently experienced labels:

$$\hat{\pi}_{\text{A},1} = 0.5$$
$$\hat{\pi}_{\text{A},t+1} = \alpha_{\text{Exp}}C_t + (1 - \alpha_{\text{Exp}})\hat{\pi}_{\text{A},t},$$

(3)

where α_{Exp} is the smoothing factor, $0 < \alpha_{\text{Exp}} < 1$, and $C_t = 1$ if category A is observed on trial t and $C_t = 0$ otherwise. The time constant of memory decay for this model is $\tau = \frac{-1}{\log(1-\alpha_{\text{Exp}})}$. Mathematically this model is equivalent to a delta-rule [28] model based on an "error" that is the difference between the current category and the current probability estimate: $\hat{\pi}_{\text{A},t+1} = \hat{\pi}_{\text{A},t} + \alpha_{\text{Exp}}(C_t - \hat{\pi}_{\text{A},t})$. The criterion z is then set to the optimal value based on this category-probability estimate.

Exp$_{\text{bias}}$ The Exp$_{\text{bias}}$ model is identical to the Exp model, while also incorporating a common finding in the literature [2] known as conservatism (i.e., observers are biased towards the neutral criterion). On each trial an estimate of probability is computed as described in (Eq 3), and averaged with a prior probability of 0.5:

$$\tilde{\pi}_{\text{A},t} = w\hat{\pi}_{\text{A},t} + \frac{1}{2}(1 - w),$$

(4)

where w is the weight given to the probability estimate $\hat{\pi}_{\text{A},t}$ and $(1 - w)$ is the weight given to $\pi_{\text{A}} = 0.5$. The criterion z is also set to the optimal value based on this category-probability estimate.

Wilson et al. (2013) Due to the complexity of the full Bayesian change-point detection model, Wilson et al. [29] developed an approximation to the full model using a mixture of delta rules. In their reduced model, the full run-length distribution is approximated by maintaining a subset of all possible run lengths. These are referred to as nodes $\{l_1, ..., l_i\}$. On each trial, an estimate of probability is computed for each node,

$$\hat{\pi}_{\text{A},1}^{l_i} = 0.5$$
$$\hat{\pi}_{\text{A},t+1}^{l_i} = \hat{\pi}_{\text{A},t}^{l_i} + \frac{1}{l_i + \nu_{\text{p}}}\left(C_t - \hat{\pi}_{\text{A},t}^{l_i}\right),$$

(5)

where ν_{p} is a model parameter that represents the strength of the observer's prior towards equal category probability (pseudocounts of a Beta prior; larger ν_{p} corresponds to stronger conservatism) and C_t is the category label. The learning rate for each node is thus $\alpha_{\text{Wilson},l_i} = \frac{1}{l_i + \nu_{\text{p}}}$. For a single-node model, this is identical to the Exp model described above (Eq 3). To obtain an overall estimate of probability in a multiple-node model, estimates (Eq 5) are combined by taking a weighted average. The weights, $p(l_i|C_{1:t})$, are updated on every trial. The update is dependent on an approximation to the change-point prior, which in turn depends on the hazard rate h (for details see Wilson et al. [29], Eqs 25-31, along with the later correction [30]). In other words, when the probability of a change is high, more weight is given to l_1, which results in a greater change in the overall probability estimate. But when the

probability of a change is low, more weight is given to nodes greater than l_1 and the probability estimate is more stable. For a three-node model probability is estimated as

$$\hat{\pi}_{A,t+1} = p(l_1|C_{1:t})\hat{\pi}_{A,t+1}^{l_1} + p(l_2|C_{1:t})\hat{\pi}_{A,t+1}^{l_2} + p(l_3|C_{1:t})\hat{\pi}_{A,t+1}^{l_3}. \quad (6)$$

For the purpose of the current experiment, we used a three-node model in which the first node was fixed ($l_1 = 1$) and l_2 and l_3 were allowed to vary. In addition, the prior strength parameter, ν_p, which modulates the learning rate, was also free. By allowing ν_p to vary, this model is equivalent to the three-node model described by Wilson and colleagues [29] in which all nodes were free and $\nu_p = 2$ was fixed. The hazard rate was set to 0.01 and we assumed a change occurred at $t = 1$, so that all the weight was given to l_1. We also tested an alternative model with a fixed value of $\nu_p = 2$, but it resulted in a worse fit.

RL   While the models described above make assumptions about how probability is estimated, it is also possible that observers simply update the decision criterion without estimating the current probability state. Reinforcement-learning is a model-free approach that assumes the observer does not use knowledge of the environmental structure. Instead, the decision criterion, rather than an estimate of category probability, is updated. The observer updates the internal criterion (z) on each trial according to the following delta rule:

$$z_{t+1} = \begin{cases} z_t, \text{if correct} \\ z_t + \alpha_{RL}(x_t - z_t), \text{if incorrect.} \end{cases} \quad (7)$$

Thus, the criterion is updated when negative feedback is received by taking a small step in the direction of the difference between the noisy observation (x_t) and current criterion (z_t), where the step size is scaled by the learning rate α_{RL}. Nothing is changed after a correct response. Assuming effective training, we initialize the RL model by setting $z_1 = \frac{1}{2}(\mu_B + \mu_A)$.

Raw data

Fig 2 shows raw data for single observers in the covert (Fig 2A) and overt (Fig 2C) tasks. For visualization in the covert task, the 'excess' number of A responses is plotted as a function of trial (gray line in Fig 2A). To compute the 'excess' number of A responses, we subtracted $\frac{t}{2}$ from the cumulative number of A responses. Thus, 'excess' A responses are constant for an observer who reported A and B equally often, increase when A is reported more, and decrease when A is reported less. To get a sense of how well the observer performed in the covert task, the number of 'excess' A trials (based on the actual category on each trial rather than the observer's response) is shown in black (Fig 2A, top). For reference, π_A is shown as a function of trial (Fig 2A, bottom). From visual inspection, the observer reported A more often when $\pi_{A,t} > 0.5$ and B more often when $\pi_{A,t} < 0.5$.

In the overt task, the orientation of the observer's criterion setting, relative to the neutral criterion, is plotted as a function of trial (gray circles). For visualization, a running average was computed over a five-trial moving window (gray line). Here (Fig 2C, top), the black line represents the criterion on each trial, given perfect knowledge of the categories, sensory uncertainty, and category probability. While this is impossible for an observer to attain, we can see that the observer's criterion follows the general trend. This suggests that observers update their criterion appropriately in response to changes in probability. That is, the criterion is set counter-clockwise from the neutral criterion when $\pi_{A,t} > 0.5$, and clockwise of neutral when $\pi_{A,t} < 0.5$. Fig 2C (bottom) shows π_A as a function of trial.

Fig 2. Behavioral data and model fits. A: Behavioral data from a representative observer (CWG) in the covert-criterion task. Top: The number of 'excess' A responses (i.e., the cumulative number of A responses minus $\frac{t}{2}$) across trials. Gray line: Observer data. Black line: The true number of 'excess' A's. Bottom: The corresponding category probability. B: Model fits (colored lines) for observer CWG in the covert-criterion task. Shaded regions: 68% CI for model fits. Gray: Observer data. C: Behavioral data from a representative observer (GK) in the overt-criterion task. Top: The orientation of the criterion line relative to the neutral criterion as a function of trial number. Gray circles: raw settings. Gray line: running average over a 5-trial moving window. Black line: ideal criterion for an observer with perfect knowledge of the experimental parameters. Bottom: Category probability across trials. D: Models fits (colored lines) for observer GK in the overt-criterion task. A running average was computed over a 5-trial window for visualization. Shaded regions: 68% CI on model fits. These are generally smaller than the model-fit line. Gray line: the running average computed from the observer's data.

Modeling results

Model predictions

A qualitative comparison of the behavioral data to the ground truth suggests that observers updated their criterion in response to changes in probability. However, it does not tell us how. To explore the mechanism underlying these changes, we compared the observers' data to multiple models. For each task and model, the mean model response for a representative subject is plotted in Fig 2B (covert task) and 2D (overt task). Shaded regions indicate 68% CIs computed from the posterior over model parameters. Specifically, we sampled parameters from the posterior over model parameters and computed the model response for the given set of parameters. We then computed the standard deviation across model responses for a large sample (see Model visualization). Shaded regions computed on overt fits are generally narrower than the data line. Qualitatively, most models captured observers' changing criteria, with the fixed model being much worse. Differences across models are especially pronounced in the overt task. Specifically, we see that the Exp, Exp_{bias}, and Wilson et al. (2013) models capture changes in criterion that occur between change points that the Bayesian models fail to capture.

Model comparison

We quantitatively compared models by computing the log marginal likelihood (LML), also known as log Bayes factor, for each subject, model, and task. The marginal likelihood is the probability of the data given the model, marginalized over model parameters (see Methods). Here, we report differences in log marginal likelihood (ΔLML) from the best model, so that larger ΔLML correspond to worse models. We compare models both by looking at average performance across subjects (a fixed-effects analysis), and also via a Bayesian Model Selection approach (BMS; [31]) in which subjects are treated as random variables. With BMS, we estimate for each model its posterior frequency f in the population and its protected exceedance probability ϕ, which is the probability that a given model is the most frequent model in the population, above and beyond chance [32].

Model comparison (Fig 3) favored the Exp_{bias} model, which outperformed the second best model Bayes_r (covert task: ΔLML $= 9.27 \pm 2.86$; overt task: ΔLML $= 8.96 \pm 4.01$; mean and SEM across observers) in the two tasks (covert task: $t(10) = 3.99$, $p = 0.003$; overt task: $t(10) = 2.37$, $p = 0.04$). Similarly, Bayesian model comparison performed at the group level also favored the Exp_{bias} model (covert task: $f = 0.46$ and $\phi = 0.96$; overt task: $f = 0.38$ and $\phi = 0.84$). These results suggests that observers estimate probability by taking a weighted average of recently experienced categories with a bias towards $\pi = 0.5$.

Fig 4A shows the number of observers that were best fit by each model for each task. To compare LML scores across tasks, and for the purpose of this analysis only, we standardized model scores for each observer and task. Standardized LML scores in the overt task are plotted as a function of standardized LML scores in the covert task in Fig 4B. We found a significant positive correlation, $r = 0.62$, $p < 0.01$, indicating that models with higher LML scores in the covert task were also higher in the overt task. This result suggests that strategy was fairly consistent across tasks. In addition, there was more variance in model scores for worse-fitting models.

Model parameters

We examine here the parameter estimates of the best-fitting model, Exp_{bias}, recalling that the two model parameters α_{Exp} and w represent, respectively, the exponential

Fig 3. Model comparison. A: Average log marginal likelihood (LML) scores relative to the winning model, Exp_{bias} (top: covert task; bottom: overt task). Lower scores indicate a better fit. Error bars: 95% CI (bootstrapped). B: Bayesian model selection at the group level. The protected exceedance probability (ϕ) is plotted for each model. Models are stacked in order of decreasing probability.

smoothing factor and the degree to which observers exhibit conservatism. The
maximum a posteriori (MAP) parameter estimates are plotted in Fig 5. Converting
the smoothing factor to a time constant, we found that the time constant in both tasks
was well below the true rate of change (covert: $\tau = [4.24, 7.18]$; overt: $\tau = [3.48, 4.75]$).
We conducted paired-sample t-tests to compare the raw parameter estimates in the
covert and overt tasks. We found a significant difference in w ($t(10) = -2.55$,
$p = 0.03$), suggesting that observers were more conservative in the covert than the
overt task. No significant difference was found for α_{Exp} ($t(10) = -0.98$, $p = 0.35$).

To investigate whether there was bias in the parameter-estimation procedure when
fitting the Exp_{bias} model, we also conducted a parameter-recovery analysis. Most
parameters could be recovered correctly, except for adjustment variability (σ_{a}) in the
overt task, which we found to be overestimated on average (see Section 4 in
S1 Appendix for details). Note that this bias in estimating σ_{a} in the overt task does
not affect our model comparison, which is based on LMLs and not on point estimates.

While we might expect performance to be similar across tasks and observers (i.e., a
correlation between the parameter fits in each task), no significant correlations were
found (α_{Exp}: $r = -0.14$, $p = 0.67$; w: $r = 0.16$, $p = 0.64$). Parameter estimates for all

Fig 4. Modeling results for individual observers. A: Model frequency. The number of observers best fit by each model plotted for each task. Models are stacked in order of decreasing frequency. B: Comparison of LML scores across tasks. LML scores were standardized for each observer and task. Standardized LML scores in the overt task are plotted as a function of standardized LML scores in the covert task (colored data points). Black dashed line: identity line.

models are shown in Tables 1 and 2.

Table 1. Maximum a posteriori parameter estimates $\pm$S.E. in the covert-criterion task.

Model	$\sigma_{\mathbf{v}}$	r	π	β	α	w	l_2	l_3	$\nu_{\mathbf{p}}$
Bayes$_{\text{ideal}}$	9.7 ± 0.6	-	-	-	-	-	-	-	-
Bayes$_r$	9.9 ± 0.8	51.5 ± 11.8	-	-	-	-	-	-	-
Bayes$_\pi$	10.5 ± 0.8	-	0.32 ± 0.02	-	-	-	-	-	-
Bayes$_\beta$	10.2 ± 0.7	-	-	18.4 ± 8.2	-	-	-	-	-
Fixed	10.9 ± 0.8	-	-	-	-	-	-	-	-
Exp	9.4 ± 0.7	-	-	-	0.04 ± 0.01	-	-	-	-
Exp$_{\text{bias}}$	10.0 ± 0.8	-	-	-	0.17 ± 0.04	0.58 ± 0.05	-	-	-
Wilson et al. (2013)	9.4 ± 0.7	-	-	-	-	-	12.2 ± 2.8	118.5 ± 23.3	43.3 ± 14.4
RL	9.2 ± 0.7	-	-	-	0.26 ± 0.03	-	-	-	-

Table 2. Maximum a posteriori parameter estimates $\pm$S.E. in the overt-criterion task.

Model	$\sigma_{\mathbf{a}}$	r	π	β	α	w	l_2	l_3	$\nu_{\mathbf{p}}$
Bayes$_{\text{ideal}}$	17.2 ± 1.1	-	-	-	-	-	-	-	-
Bayes$_r$	16.4 ± 1.1	70 ± 15	-	-	-	-	-	-	-
Bayes$_\pi$	16.7 ± 1.1	-	0.17 ± 0.03	-	-	-	-	-	-
Bayes$_\beta$	17.0 ± 1.1	-	-	13.2 ± 8.2	-	-	-	-	-
Fixed	19.4 ± 1.1	-	-	-	-	-	-	-	-
Exp	16.7 ± 1.1	-	-	-	0.09 ± 0.02	-	-	-	-
Exp$_{\text{bias}}$	16.0 ± 1.0	-	-	-	0.22 ± 0.03	0.74 ± 0.06	-	-	-
Wilson et al. (2013)	16.4 ± 1.1	-	-	-	-	-	10.8 ± 2.0	46.4 ± 18.4	9.2 ± 5.1
RL	18.1 ± 1.2	-	-	-	0.21 ± 0.03	-	-	-	-

Fig 5. Parameter estimates for the best fitting model. A: Mean α_{exp} (top) and w (bottom) MAP values across observers. The * denotes significance at the $p < 0.05$ level. Error bars: $\pm$SEM. B: Individual α_{exp} (top) and w (bottom) MAP values from fits in the overt task as a function of MAP values from fits in the covert task. Black dashed lines: identity line.

Discussion

Although we know that people update decision criteria in response to explicit changes in prior probability, the effects of implicit changes in prior probability on decision-making behavior are less well known. In the present study, we used model comparison to investigate the mechanisms underlying decision-making behavior in an orientation-categorization task as prior probability changed. We tested a set of models that varied in both computational and memory demands. Models were tested on data from both a covert- and overt-criterion task. A comprehensive approach, consisting of both qualitative and quantitative analysis, was performed to determine the best fitting model. We found that observers updated their decision criterion following changes in probability. Additionally, we observed systematic changes in the decision criterion during periods of stability, which was clearly evident in the overt-criterion data. Model comparison favored an exponential-averaging model with a bias towards equal probability. This suggests that observers update the decision criterion by combining on-line estimation of probability with an equal-probability prior. Ultimately, our results help explain decision-making behavior in situations in which people need to assess the probability of an outcome based on previous experience.

Criterion updates in response to implicit changes in category probability

To determine the influence of prior probability on decision-making behavior, we examined changes in the decision criterion. First, we found that no participant was best fit by a fixed-criterion model. This finding suggests that observers update decision criteria in response to implicit changes in probability. This result is consistent with previous studies in which prior probability was explicit [2–9]. Further, this finding complements recent studies suggesting that individuals can learn and adapt to statistical regularities in changing environments [14–17, 24, 25, 33, 34]. Although this finding suggests that observers dynamically adjust decision criteria in response to changes in prior probability, it does not tell us how they do this (e.g., do observers compute on-line estimates of probability?). To uncover the mechanisms underlying changes in decision-making behavior, we compared multiple models ranging from the full Bayesian change-point detection model to a model-free reinforcement-learning (RL) model.

Systematic criterion fluctuations

How is the decision criterion set? Qualitatively, most models appear to fit the data reasonably well in the covert task. However, when we look at data from the overt task, while Bayesian models captured the overall trend, they failed to capture local fluctuations in the decision criterion observed during periods of stability (i.e., time intervals between change points). In other words, the criterion predicted by the Bayesian models stabilized whereas the observers' behavior did not. In contrast to the Bayesian models, the exponential models continually update the observer's estimate of probability based on recently experienced categories. How quickly observers updated this estimate is determined in the model by the decay-rate parameter. From our model fits to the data, we found that observers had an average decay rate that was substantially smaller than the true run length distribution (4.5 vs. 100 trials, respectively), leading to frequent, systematic fluctuations in decision criteria. Although we cannot directly observe these fluctuations in the covert task, because the estimated decay rate was not significantly different across tasks we can assume the fluctuations occurred in a similar manner. Like the exponential models, the RL model was also able to capture local fluctuations in the decision criterion. However, the amplitude of the changes in criterion predicted by the RL model was generally too low compared to the data. This discrepancy was especially clear in the overt task; no participant was best fit by the RL model. These results have two important implications. (1) It is important to test alternatives to Bayesian models: observers' behavior might be explained without requiring an internal representation of probability. (2) Using multiple tasks can provide additional insight into behavior. Here, the fluctuations in decision criteria between change points led to suboptimal behavior. Overall, our findings suggest that suboptimality arose from an incorrect, possibly heuristic inference process, that goes beyond mere sensory noise [35–37].

A dual mechanism for criterion updating

While a number of the models captured local fluctuations in the decision criterion, we found that the Exp_{bias} model fit the data best according to a quantitative model comparison. This result suggests that observers compute on-line estimates of category probability based on recent experience. Further, the bias component of the model suggests that observers are conservative, as reflected in a long-term prior that categories are equally likely. The degree to which observers weight this prior varied across individuals and tasks. Taken together, these results suggest a dual mechanism for learning and incorporating prior probability into decisions. That is, there are (at

least) two components to decision making that are acquired and updated at very   419
different timescales.   420

Multiple-mechanism models have been used to describe behavior in   421
decision-making [29] and motor behavior [38]. A model that combines delta rules   422
predicts motor behavior better than either delta rule alone [38]. Using a combination   423
of delta rules [29], we were able to capture the local fluctuations in criterion that the   424
full Bayesian model missed. However, we found that a constant weight on $\pi = 0.5$ fit   425
better than the multiple-node model described by Wilson and colleagues [29].   426
Temporal differences between their task and ours might explain some of the differences   427
we observed, as changes occurred much more slowly in our experiment. Additionally,   428
while fitting Wilson et al.'s model we set the hazard rate to 0.01 (the average rate of   429
change), but observers had to learn this value throughout the experiment and may   430
have had incorrect assumptions about the rate of change [21, 22].   431

Explanations of conservatism   432

While we observed conservatism in both the covert- and overt-criterion tasks, we   433
found that, on average, observers were significantly more conservative in the covert   434
task. To understand why conservatism differs across tasks, we need to understand the   435
differences between the tasks. While the generative model was identical across tasks,   436
the observer's response differed. In the covert task, observers chose between two   437
alternatives. In the overt task, observers selected a decision criterion. This is an   438
important difference because it allows us to potentially rule out previous explanations   439
of conservatism, such as the use of subjective probability [4], misestimation of the   440
relative frequency of events [39, 40], and incorrect assumptions about the sensory   441
distributions [41, 42]; these explanations predict similar levels of conservatism across   442
tasks. On the other hand, conservatism may be due to the use of suboptimal decision   443
rules. Probability matching is a strategy in which participants select alternatives   444
proportional to their probability, and has been used to explain suboptimal behavior in   445
forced-choice tasks in which observers choose between two or more   446
alternatives [6, 43–46]. Thus, the higher levels of conservatism in the covert task may   447
have been due to the use of a suboptimal decision rule like probability matching,   448
which would effectively smooth the observer's response probability across trials.   449
Probability matching is not applicable to responses in the overt task. Thus, the use of   450
different decision rules may result in different levels of conservatism. These differences   451
may also arise from an increase in uncertainty in the covert task due to less explicit   452
feedback. An observer with greater uncertainty will rely more on the prior. Thus,   453
conservatism may be the result of having a prior over criteria that interacts with task   454
uncertainty. This can be tested by manipulating uncertainty over the generative model   455
and measuring changes in conservatism. It is also possible that conservatism is the   456
result of both the use of suboptimal decision rules and one or more of the previously   457
proposed explanations.   458

Incorrect assumptions about the generative model   459

While we tested a number of Bayesian models that explored an array of assumptions   460
about the generative model, clearly one could propose even more variants. In   461
particular, we only analyzed one such assumption at a time. A simple way to expand   462
the model space is via a factorial comparison [36, 47], which we did not consider here   463
due to computational intractability and the combinatorial explosion of models. Most   464
notably, for all except the RL model we assumed knowledge of the category   465
distributions. However, Norton et al. [16] found that for the same   466
orientation-categorization task, category means were estimated dynamically, even after   467

prolonged training. Similarly, Gifford et al. [48] observed suboptimality in an
auditory-categorization task and found that the data were best explained by a model
with non-stationary categories and prior probability that was updated using the recent
history of category exemplars. This occurred despite holding categories and
probability constant within a block. In fact, similar effects of non-stationarity have
been observed in several other studies [49–51]. In addition to non-stationary category
means, observers may also have misestimated category variance [52], especially since
learning category variance takes longer than learning category means [14].

Conclusion

In sum, our results provide a computational model for how decision-making behavior
changes in response to implicit changes in prior probability. Specifically, they suggest
a dual mechanism for learning and incorporating prior probability that operate at
different timescales. Importantly, this helps explain behavior in situations in which
assessment of probability is learned through experience. Further, our results
demonstrate the need to compare multiple models and the benefit of using tasks that
provide a richer, more informative dataset.

Materials and methods

Participants

Eleven observers participated in the experiment (mean age 26.6, range 20-31, 8
females). All observers had normal or corrected-to-normal vision. One of the observers
(EHN) was also an author. The Institutional Review Board at New York University
approved the experimental procedure and observers gave written informed consent
prior to participation.

Apparatus and stimuli

Stimuli were presented on a gamma-corrected Dell Trinitron P780 CRT monitor with
a 31.3 x 23.8° display, a resolution of 1024 x 768 pixels, a refresh rate of 85 Hz, and a
mean luminance of 40 cd/m^2. Observers viewed the display from a distance of 54.6 cm.
The experiment was programmed in MATLAB [53] using the Psychophysics
Toolbox [54, 55].

Stimuli were 4.0 x 1.0° ellipses presented at the center of the display on a mid-gray
background. In both the orientation-discrimination and covert-criterion tasks, trials
began with a central white fixation cross (1.2°). In the overt-criterion task, a yellow
line with random orientation was presented at the center of the display (5.0 x 0.5°).

Procedure

Categories In the 'categorization' sessions described below, stimulus orientations
were drawn from one of two categories (A or B). Category distributions were Gaussian
with different means ($\mu_{\mathrm{B}} > \mu_{\mathrm{A}}$) and equal variance ($\sigma_{\mathrm{A}}^2 = \sigma_{\mathrm{B}}^2 = \sigma_{\mathrm{s}}^2 = 100\,\mathrm{deg}^2$). The
mean of category A was chosen randomly from all possible orientations at the
beginning of each session and the mean of category B was set so that d' was
approximately 1.5, which was determined for each observer based on the estimates of
sensory uncertainty obtained during a 'measurement session' (Fig 1C).

Sessions   All observers participated in three 1-hour sessions. Observers completed a   509
'measurement' session first followed by two 'categorization' sessions. Observers   510
completed the covert-criterion task in the first 'categorization' session followed by the   511
overt-criterion task in the second, or vice versa (chosen randomly). At the beginning   512
of each 'categorization' session, observers completed 200 trials of category training   513
followed by 800 experimental trials. Prior to training, observers were provided with a   514
detailed explanation of the category distributions and training task. After training,   515
observers were provided with additional instructions about the subsequent   516
'categorization' task and told that the categories would remain constant for the   517
remainder of the session but that category probability may change. Observers were not   518
told how often category probability would change or the range of probability states.   519

Measurement task   520

During the 'measurement' session, sensory uncertainty (σ_v) was estimated using a   521
two-interval, forced-choice, orientation-discrimination task in which two black ellipses   522
were presented sequentially on a mid-gray background. The observer reported the   523
interval containing the ellipse that was more clockwise by keypress. Once the response   524
was recorded, auditory feedback was provided and the next trial began. An example   525
trial sequence is shown in Fig S3A in S1 Appendix.   526
    The orientation of the ellipse in the first interval was chosen randomly on every   527
trial from a uniform distribution ranging from -90 to 90°. The orientation of the   528
second ellipse was randomly oriented clockwise or counter-clockwise of the first. The   529
difference in orientation between the two ellipses was selected using an adaptive   530
staircase procedure. The minimum step-size was 1° and the maximum step-size was   531
32°. Each observer ran two blocks. In each block, four staircases (65 trials each) were   532
interleaved (two 1-up, 2-down and two 1-up, 3-down staircases) and randomly selected   533
on each trial. For analyses and results see S1 Appendix.   534

Category training   535

Each training trial was identical to a covert-criterion trial (Fig 1A). During training   536
there was an equal chance that a stimulus was drawn from either category. To assess   537
learning of category distributions, observers were asked to estimate the mean   538
orientation of each category following training. The mean of each category was   539
estimated exactly once. The order in which category means were estimated was   540
randomized. For estimation, a black ellipse with random orientation was displayed in   541
the center of the display. Observers slid the mouse to the right and left to rotate the   542
ellipse clockwise and counterclockwise, respectively and clicked the mouse to indicate   543
they were satisfied with the setting. No feedback was provided. We computed the   544
proportion correct for each observer to ensure category learning by comparing it to the   545
expected proportion correct ($p(\mathrm{correct}) = 0.77$) for $d' = 1.5$. Mean estimates are   546
plotted in Fig S4C in S1 Appendix as a function of the true category means. We   547
computed the average estimation error for each category and observer by subtracting   548
the estimate from the true mean. From visual inspection, it appears that training was   549
effective with the exception of one outlier, which we assume was a lapse.   550

Categorization tasks   551

Covert-criterion task   In the covert-criterion task, observers categorized ellipses   552
based on their orientation. The start of each trial ($N_\mathrm{trials} = 800$) was signaled by the   553
appearance of a central white fixation cross (500 ms). A black oriented ellipse was   554
then displayed at the center of the screen (300 ms). Observers categorized the ellipse   555

as A or B by keypress. Observers received feedback as to whether they were correct on every trial. Observers received a point for every correct response and aggregate points were displayed at the top of the screen to motivate observers. In addition, the fixation cross was displayed at the center of the screen in the color corresponding to the true category (category A: green; category B: red). The next trial began immediately. An example trial sequence is depicted in Fig 1A.

Overt-criterion task   In the overt-criterion task, observers completed an explicit version of the categorization task described above that was developed by Norton et al. [16]. At the beginning of each trial ($N_{\text{trials}} = 800$), a line was displayed at the center of the screen. The orientation of the line was randomly selected from a uniform distribution ranging from -90 to 90°. The observers' task was to rotate the line to indicate the criterion for that trial. Observers rotated the line clockwise or counterclockwise by sliding the mouse to the right or left and clicked the mouse to indicate their setting. Next, an ellipse was displayed under the criterion line in the color corresponding to the true category for 300 ms. Auditory feedback indicated whether the set criterion correctly categorized the ellipse. That is, observers were correct when a category A stimulus was clockwise of the criterion line or a category B stimulus was counterclockwise of the line. Observers received a point for a correct response and aggregate points were displayed at the top of the screen. The next trial began immediately. An example trial sequence is depicted in Fig 1B.

Model fitting

For fitting, all models had one free noise parameter. In the covert-criterion task, this was sensory noise (σ_{v}). In the overt-criterion task, sensory noise was fixed and set to the value obtained in the 'measurement' session, but we included a noise parameter for the adjustment of the criterion line (σ_{a}). Fixing one noise parameter in the overt-criterion task ameliorated potential issues of lack of parameter identifiability [56], and ensured that models had the same complexity across tasks. The Bayes$_{\text{ideal}}$ and Fixed models had no additional parameters. Each suboptimal Bayesian model had one additional parameter: Bayes$_r$ (r); Bayes$_\pi$ (π_{min}); Bayes$_\beta$ (β). The Exp and RL models also only had one additional parameter (α). The Exp$_{\text{bias}}$ had two additional parameters (α_{exp} and w), and the Wilson et al. (2013) model had three (l_2, l_3, and ν_{p}).

To fit each model, for each subject and task we computed the logarithm of the *unnormalized* posterior probability of the parameters,

$$\log p^* (\boldsymbol{\theta}|\text{data}) = \log p(\text{data}|\boldsymbol{\theta}, \text{M}) + \log p(\boldsymbol{\theta}|\text{M}), \qquad (8)$$

where data are category decisions in the covert-criterion task and criterion orientation in the overt-criterion task, M is a specific model, and $\boldsymbol{\theta}$ represents the model parameters (generally, a vector). The first term of Eq 8 is the log likelihood, while the second term is the prior over parameters (see below).

We evaluated Eq 8 on a cubic grid, with bounds chosen to contain almost all posterior probability mass. The grid for all models, except Wilson et al. (2013), consisted of 100 equally spaced values for each parameter. Due to the computational demands of the Wilson et al. (2013) model, we reduced the grid to 50 equally spaced values. The grid allowed us to approximate the full posterior distribution over parameters, and also to evaluate the normalization constant for the posterior, which corresponds to the evidence or marginal likelihood, used as a metric of model comparison (see Model comparison). We reported as parameter estimates the best-fitting model parameters on the grid, that is the maximum-a-posteriori (MAP) values (see Tables 1 and 2). We used the full posterior distributions to compute

posterior predictive distributions, that is, model predictions for visualization (see Model visualization), and to generate plausible parameter values for our model-recovery analysis.

Priors over parameters   We chose all priors to be uninformative. For noise parameters, inspired by the Jeffreys prior for scale parameters, we used uniform priors in log space over a reasonably large range ($[0°, 3.4°]$) [57]. For $\alpha_{\exp}$, α_{RL}, and w we used a uniform prior from 0 to 1. For κ we used a uniform prior from 2 to 200 trials. For $\pi_{\min}$ we used a uniform prior from 0 to 0.5. For β, we used a uniform prior on the square root of the parameter value, ranging from 0 to 10. Instead of fitting the individual nodes in the Wilson et al. (2013) model, we fit the difference between nodes, i.e., $\delta_1 = l_2 - l_1$ and $\delta_2 = l_3 - l_2$. We used a uniform prior on the square root of δ_1 ranging from 1.01 to 5 and on the square root of δ_2 ranging from 1.01 to 14. Finally, for ν_{p} we used a uniform prior in log space from 0 to 5.

Response probability

Covert-criterion task   For each model, parameter combination, observer, and trial in the covert-criterion task, we computed the probability of choosing category A on each trial given a stimulus, s_t, and all previously experienced categories, $\boldsymbol{C}_{1:t-1}$. In all models, the observer's current decision depends on the noisy measurement, x_t, so the probability of responding A for a given stimulus s_t is

$$p(\hat{C}_A|s_t, \boldsymbol{C}_{1:t-1}, \mathrm{M}, \theta) = \int p(\hat{C}_A|x_t, \boldsymbol{C}_{1:t-1}, \mathrm{M}, \theta)\mathcal{N}(x_t|s_t, \sigma_v^2)dx_t. \tag{9}$$

Because the current criterion setting in the RL model depends on the vector of all previous stimulus measurements, $\boldsymbol{x}_{1:t}$, the probability could not be computed analytically for this model. As an approximation, we used Monte Carlo simulations with 5000 sample measurement vectors. For each measurement vector, we applied the model's decision rule and approximated the probability by computing the proportion of times the model chose A out of all the simulations. For all models, we included a fixed lapse rate, $\lambda = 10^{-4}$, that is the probability of a completely random response. The probability of choosing category A, $\hat{C}_A$, in the presence of lapses was then

$$p(\hat{C}_A|s_t, \boldsymbol{C}_{1:t-1}, \mathrm{M}, \theta) = (1 - \lambda)p(\hat{C}_A|s_t, \boldsymbol{C}_{1:t-1}, \mathrm{M}, \theta) + \frac{\lambda}{2}. \tag{10}$$

Effectively, the lapse rate acts as a regularization term that avoids excessive penalties to the likelihood of a model for outlier trials.

Next, assuming conditional independence between trials, we computed the log likelihood across all of the observer's choices, given each model and parameter combination

$$\log p(\mathrm{data}|\mathrm{M}, \theta) = \sum_{t=1}^{N_{\mathrm{trials}}} \log p(\hat{C}_A|s_t, \boldsymbol{C}_{1:t-1}, \mathrm{M}, \theta), \tag{11}$$

where t is the trial index and N_{trials} is the total number of trials.

Overt-criterion task   For each model, parameter combination, observer, and trial in the overt-criterion task, we computed the decision criterion on each trial. For all models except the RL model, the criterion was computed as in S1 Appendix. For the RL model, the criterion was computed as in Eq 7 for 5000 sample measurement vectors. For all models in the overt-criterion task, the criterion was corrupted by adjustment noise with variance σ_a^2, so that $\hat{z}_t \sim \mathcal{N}(z_t, \sigma_a^2)$, where z_t was the observer's

chosen criterion at trial t, and $\hat{z}_t$ was the actual reported criterion after adjustment noise. In addition, the observer had a chance of lapsing (e.g., a misclick), in which case the response was uniformly distributed in the range. Therefore, the probability that the observer reports the criterion $\hat{z}_t$ was

$$p(\hat{z}_t|\boldsymbol{C}_{1:t-1}, \mathrm{M}, \theta) = (1-\lambda)p(\hat{z}_t|\boldsymbol{C}_{1:t-1}, \mathrm{M}, \theta) + \frac{\lambda}{180}, \tag{12}$$

with $\lambda = 5 \times 10^{-5}$. As in the covert-criterion task, we computed the log likelihood across all trials by summing the log probability

$$\log p(\mathrm{data}|\mathrm{M}, \theta) = \sum_{t=1}^{T} \log p(\hat{z}_t|\boldsymbol{C}_{1:t-1}, \mathrm{M}, \theta). \tag{13}$$

Model comparison

To obtain a quantitative measure of model fit, for each observer, model, and task we computed the log marginal likelihood (LML) by integrating over the parameters in Eq 8,

$$\log p(\mathrm{data}|\mathrm{M}) = \log \int p(\mathrm{data}|\theta, \mathrm{M})p(\theta|\mathrm{M})d\theta. \tag{14}$$

To approximate the integral in Eq 14, we marginalized across each parameter dimension using the trapezoidal method. Assuming equal probability across models, the marginal likelihood was proportional to the posterior probability of a given model and thus represents a principled metric for comparison that automatically accounts for both goodness of fit and model complexity via Bayesian Occam's razor [58]. Penalizing for model complexity is a desirable feature of a model-comparison metric to reduce overfitting.

In addition to the Bayesian model-comparison metric described above, we computed the Akaike Information Criterion (AIC) [59] for each of our models. AIC is one of many information criteria that penalize the maximum log likelihood by a term that increases with the number of parameters. LML and AIC results were consistent (see S1 Appendix for model comparison using AIC scores).

For comparison purposes, we report relative model-comparison scores, ΔLML and ΔAIC. We used bootstrapping to compute confidence intervals on the mean difference scores. Specifically, we simulated 10,000 sample data sets. For each simulated dataset we sampled, with replacement, 11 difference scores (the same number of difference scores as observers) and calculated the mean. To determine the 95% CI, we sorted the mean difference scores and determined the scores that corresponded to the 2.5 and 97.5 percentiles.

For an additional analysis at the group level, we used the random-effects Bayesian model selection analysis (BMS) developed by Stephan et al. [31] and expanded on by Rigoux et al. [32]. Specifically, using observers' LML scores we computed the protected exceedance probability ϕ and the posterior model frequency for each model. Exceedance probability represents the probability that one model is the most frequent decision-making strategy in the population, given the group data, above and beyond chance. This analysis was conducted using the open-source software package Statistical Parametric Mapping (SPM12; http://www.fil.ion.ucl.ac.uk/spm).

Model visualization

For each model, observer, and task, we randomly sampled 1000 parameter combinations from the joint posterior distribution with replacement. For each

parameter combination, we simulated model responses using the same stimuli that were presented to the observer. Because the model output in the covert task was the probability of reporting category A, for each trial in a simulated dataset we simulated 10,000 model responses (i.e., category decisions), calculated the cumulative number of A's for each simulated dataset, and averaged the results. The mean and standard deviation were computed across all simulated datasets in both tasks. Model fit plots show the mean response (colored line) with shaded regions representing one standard deviation from the mean. Thus, shaded regions represent a 68% confidence interval on model fits.

Model recovery

To ensure that our models were discriminable, we performed a model-recovery analysis, details of which can be found in S1 Appendix. In addition to the model-recovery analysis, we also performed a parameter-recovery analysis for the winning model (Exp_{bias}). This was done to determine whether our parameter estimation procedure was biased for each parameter and task.

Supporting information

S1 Appendix. Supplementary Information. Ideal observer model derivation; additional models; model comparison with AIC; model recovery analysis; measurement task; category training.

Acknowledgments

We would like to thank Chris Grimmick for helping with data collection. This work utilized the NYU IT High Performance Computing resources and services.

References

1. Bernardo J, Smith A. Bayesian theory. New York: Wiley; 1994.

2. Green D, Swets JA. Signal detection theory and psychophysics. New York: Wiley; 1966.

3. Tanner Jr WP. Theory of recognition. J Acoust Soc Am. 1956;28:882–888.

4. Ackermann JF, Landy MS. Suboptimal decision criteria are predicted by subjectively weighted probabilities and rewards. Atten Percept Psychophys. 2015;77:638–658.

5. Ulehla ZJ. Optimality of perceptual decision criteria. J Exp Psychol. 1966;71:564.

6. Healy AF, Kubovy M. Probability matching and the formation of conservative decision rules in a numerical analog of signal detection. J Exp Psychol Hum Learn. 1981;7:344.

7. Kubovy M, Healy AF. The decision rule in probabilistic categorization: What it is and how it is learned. J Exp Psychol Gen. 1977;106:427.

8. Healy AF, Kubovy M. The effects of payoffs and prior probabilities on indices of performance and cutoff location in recognition memory. Mem Cognit. 1978;6:544–553.

9. Maddox WT. Toward a unified theory of decision criterion learning in perceptual categorization. J Exp Anal Behav. 2002;78:567–595.

10. Barron G, Erev I. Small feedback-based decisions and their limited correspondence to description-based decisions. J Behav Decis Mak. 2003;16:215–233.

11. Hertwig R, Barron G, Weber EU, Erev I. Decisions from experience and the effect of rare events in risky choice. Psychol Sci. 2004;15:534–539.

12. Bohil CJ, Wismer AJ. Implicit learning mediates base rate acquisition in perceptual categorization. Psychon Bull Rev. 2015;22:586–593.

13. Wismer AJ, Bohil CJ. Base-rate sensitivity through implicit learning. PloS ONE. 2017;12(6):e0179256.

14. Berniker M, Voss M, Kording K. Learning priors for Bayesian computations in the nervous system. PloS ONE. 2010;5(9):e12686.

15. Summerfield C, Behrens TE, Koechlin E. Perceptual classification in a rapidly changing environment. Neuron. 2011;71:725–736.

16. Norton EH, Fleming SM, Daw ND, Landy MS. Suboptimal criterion learning in static and dynamic environments. PLoS Comput Biol. 2017;13(1):e1005304.

17. Nassar MR, Wilson RC, Heasly B, Gold JI. An approximately Bayesian delta-rule model explains the dynamics of belief updating in a changing environment. J Neurosci. 2010;30:12366–12378.

18. Landy MS, Trommershäuser J, Daw ND. Dynamic estimation of task-relevant variance in movement under risk. J Neurosci. 2012;32:12702–12711.

19. Acerbi L, Wolpert DM, Vijayakumar S. Internal representations of temporal statistics and feedback calibrate motor-sensory interval timing. PLoS Comput Biol. 2012;8(11):e1002771.

20. Sato Y, Kording KP. How much to trust the senses: Likelihood learning. J Vis. 2014;14(13):13.

21. Glaze CM, Kable JW, Gold JI. Normative evidence accumulation in unpredictable environments. Elife. 2015;4. doi:10.7554/eLife.08825.

22. Wilson RC, Nassar MR, Gold JI. Bayesian online learning of the hazard rate in change-point problems. Neural Comput. 2010;22:2452–2476.

23. Meyniel F, Schlunegger D, Dehaene S. The sense of confidence during probabilistic learning: A normative account. PLoS Comput Biol. 2015;11(6):e1004305.

24. Behrens TE, Woolrich MW, Walton ME, Rushworth MF. Learning the value of information in an uncertain world. Nat Neurosci. 2007;10:1214.

25. Zylberberg A, Wolpert DM, Shadlen MN. Counterfactual reasoning underlies the learning of priors in decision making. Neuron. 2018;99(5):1083–1097.

26. Tversky A, Kahneman D. Judgment under uncertainty: Heuristics and biases. Science. 1974;185:1124–1131.

27. Adams RP, MacKay DJ. Bayesian online changepoint detection. arXiv preprint arXiv:07103742. 2007;.

28. Rescorla RA, Wagner AR. A theory of Pavlovian conditioning: Variations in the effectiveness of reinforcement and nonreinforcement. In: Black AH, Prokasy WF, editors. Classical conditioning II: Current research and theory. New York: Appleton-Century-Crofts; 1972. p. 64–99.

29. Wilson RC, Nassar MR, Gold JI. Correction: A mixture of delta-rules approximation to Bayesian inference in change-point problems. PLoS Comput Biol. 2013;9(7):e1003150.

30. Wilson RC, Nassar MR, Gold JI. A mixture of delta-rules approximation to Bayesian inference in change-point problems. PLoS Comput Biol. 2018;14(6):e1006210.

31. Stephan KE, Penny WD, Daunizeau J, Moran RJ, Friston KJ. Bayesian model selection for group studies. Neuroimage. 2009;46:1004–1017.

32. Rigoux L, Stephan KE, Friston KJ, Daunizeau J. Bayesian model selection for group studies—revisited. Neuroimage. 2014;84:971–985.

33. Burge J, Ernst MO, Banks MS. The statistical determinants of adaptation rate in human reaching. J Vis. 2008;8(4):20.

34. Qamar AT, Cotton RJ, George RG, Beck JM, Prezhdo E, Laudano A, et al. Trial-to-trial, uncertainty-based adjustment of decision boundaries in visual categorization. Proc Natl Acad Sci USA. 2013;110:20332–20337.

35. Beck JM, Ma WJ, Pitkow X, Latham PE, Pouget A. Not noisy, just wrong: the role of suboptimal inference in behavioral variability. Neuron. 2012;74(1):30–39.

36. Acerbi L, Vijayakumar S, Wolpert DM. On the origins of suboptimality in human probabilistic inference. PLoS Comput Biol. 2014;10(6):e1003661.

37. Drugowitsch J, DeAngelis GC, Angelaki DE, Pouget A. Tuning the speed-accuracy trade-off to maximize reward rate in multisensory decision-making. Elife. 2015;4:e06678.

38. Izawa J, Shadmehr R. Learning from sensory and reward prediction errors during motor adaptation. PLoS Comput Biol. 2011;7(3):e1002012.

39. Attneave F. Psychological probability as a function of experienced frequency. J Exp Psychol. 1953;46:81.

40. Varey CA, Mellers BA, Birnbaum MH. Judgments of proportions. Exp Psychol Hum Percept Perform. 1990;16:613.

41. Maloney LT, Thomas EA. Distributional assumptions and observed conservatism in the theory of signal detectability. J Math Psychol. 1991;35:443–470.

42. Kubovy M. A possible basis for conservatism in signal detection and probabilistic categorization tasks. Percept Psychophys. 1977;22:277–281.

43. Lee W, Janke M. Categorizing externally distributed stimulus samples for unequal molar probabilities. Psychol Rep. 1965;17:79–90.

44. Murray RF, Patel K, Yee A. Posterior probability matching and human perceptual decision making. PLoS Comp Biol. 2015;11(6):e1004342.

45. Thomas EA, Legge D. Probability matching as a basis for detection and recognition decisions. Psychol Rev. 1970;77:65.

46. Wozny DR, Beierholm UR, Shams L. Probability matching as a computational strategy used in perception. PLoS Comp Biol. 2010;6(8):e1000871.

47. van den Berg R, Awh E, Ma WJ. Factorial comparison of working memory models. Psychol Rev. 2014;121:124.

48. Gifford AM, Cohen YE, Stocker AA. Characterizing the impact of category uncertainty on human auditory categorization behavior. PLoS Comp Biol. 2014;10(7):e1003715.

49. Petzschner FH, Glasauer S. Iterative Bayesian estimation as an explanation for range and regression effects: a study on human path integration. J Neurosci. 2011;31:17220–17229.

50. Raviv O, Ahissar M, Loewenstein Y. How recent history affects perception: the normative approach and its heuristic approximation. PLoS Comp Biol. 2012;8(10):e1002731.

51. Fischer J, Whitney D. Serial dependence in visual perception. Nat Neurosci. 2014;17:738–743.

52. Zylberberg A, Roelfsema PR, Sigman M. Variance misperception explains illusions of confidence in simple perceptual decisions. Conscious Cogn. 2014;27:246–253.

53. MATLAB. version 7.10.0 (R2010a). Natick, Massachusetts: The MathWorks Inc.; 2010.

54. Brainard DH, Vision S. The psychophysics toolbox. Spat Vis. 1997;10:433–436.

55. Pelli DG. The VideoToolbox software for visual psychophysics: Transforming numbers into movies. Spat Vis. 1997;10:437–442.

56. Acerbi L, Ma WJ, Vijayakumar S. A framework for testing identifiability of bayesian models of perception. In: Advances in neural information processing systems; 2014. p. 1026–1034.

57. Jaynes ET. Probability theory: the logic of science. Cambridge, England: Cambridge University Press; 2003.

58. MacKay DJ, Mac Kay DJ. Information theory, inference and learning algorithms. Cambridge, England: Cambridge university press; 2003.

59. Akaike H. Information theory and an extension of the maximum likelihood principle. In: Proceedings of the 2nd international symposium on information; 1973. p. 267–281.