Estimating statistical significance of local protein profile-profile alignments

Mindaugas Margelevičius[*]

Institute of Biotechnology, Life Sciences Center, Vilnius University, Vilnius, 10257, Lithuania

Alignment of sequence families described by profiles provides a sensitive means for establishing homology between proteins and is important in protein evolutionary, structural, and functional studies. In the context of a steadily growing amount of sequence data, estimating the statistical significance of alignments, including profile-profile alignments, plays a key role in alignment-based homology search algorithms. Still, it is an open question as to what and whether one type of distribution governs profile-profile alignment score, especially when profile-profile substitution scores involve such terms as secondary structure predictions. This study presents a methodology for estimating the statistical significance of this type of alignments. The methodology rests on a new algorithm developed for generating random profiles such that their alignment scores are distributed similarly to those obtained for real unrelated profiles. We show that improvements in statistical accuracy and sensitivity and alignment quality result from statistically characterizing alignments by establishing the dependence of statistical parameters on various measures associated with both individual and pairwise profile characteristics. Implemented in the COMER software, the proposed methodology yielded an increase of up to 34.2% in the number of true positives and up to 61.8% in the number of high-quality alignments with respect to the previous version of the COMER method. A new version (v1.5.1) of the COMER software is available at https://sourceforge.net/projects/comer. The COMER software is also available on Github at https://github.com/minmarg/comer and as a Docker image (https://hub.docker.com/r/minmar/comer).

1 Introduction

Establishing homology between proteins is essential in evolutionary and highly important in structural and functional studies of proteins and their complexes. Alignment, in general, represents the most fundamental way to deduce homology directly or indirectly. Sequence alignment has proved indispensable in annotating uncharacterized proteins and paved the way for alignment of sequence families described by profiles, constituting the basis for inferring protein structure and function by homology.

In the presence of a large and steadily growing amount of sequence data, estimating the statistical significance of alignments plays a prominent role in alignment-based homology search algorithms (Karlin, 2005). For an alignment with a particular similarity score, it provides a probability or related quantity indicating how likely a chance alignment with the same or greater score is to be observed.

The limiting distribution of the ungapped local alignment score S (nonlattice) for large sequence lengths m

and n has been proved (Karlin *et al.*, 1990; Karlin and Altschul, 1990; Karlin and Brendel, 1992; Dembo *et al.*, 1994) to be the type 1 (Gumbel-type) extreme value distribution (EVD) (Kotz and Nadarajah, 2000)

$$P(S \le x) \approx \exp(-Kmne^{-\lambda x}), \tag{1}$$

where λ and K ($K = e^{\lambda\mu}/[mn]$; μ, the location parameter under the standard parametrization) are parameters calculable from the score matrix used to align sequences and satisfying the conditions of the negative expected score and existence of at least one positive score.

Ample empirical evidence (e.g., Mott, 1992; Altschul and Gish, 1996; Pearson, 1998; Waterman and Vingron, 1994b,a) has suggested that the statistical theory for ungapped alignments applies to gapped alignments, provided gap penalties, or costs, lead to alignment scores in the (local) region of logarithmic growth (Arratia and Waterman, 1994).

Importantly, factors, such as the length of sequences being compared (Altschul and Gish, 1996; Spang and Vingron, 1998; Altschul *et al.*, 2001) and their compositional similarity (Mott, 1992, 2000), affect the distribution of alignment scores. While solutions to take them into account exist for sequence and profile-to-sequence

---

[*]mindaugas.margelevicius@bti.vu.lt

alignments (Mott, 1992; Yu *et al.*, 2006) (we provide an overview in Supplementary Section S1), there is no established procedure for addressing them in profile-profile alignment (Sadreyev and Grishin, 2003; Poleksic, 2009; Margelevičius and Venclovas, 2010; Sadreyev and Grishin, 2008).

This study aims at characterizing the distribution of profile-profile alignment scores to improve statistical accuracy and remote homology detection. The profile achieves its highest potential in recognizing related proteins when its record at each position combines information components obtained by independent numerical methods or sources of information, e.g., secondary structure (SS) assignment, structure/sequence context predictions, contact propensities, and others. We consider this type of profiles, i.e., supplemented with composite data. To the best of our knowledge, studies dedicated to the distribution of scores produced by aligning such profiles have not been reported in the literature, although the characterization of profile-profile alignments assisted at least with SS predictions has attracted much interest.

Our focus is local alignment scores and the specification of their distribution. Hence, we assume that the expected profile-profile alignment score per aligned pair is negative and the probability for a positive score is positive. These assumptions are satisfied in part when the score for a pair of positions of two profiles is (implicitly) log-odds (Karlin, 2005; Meng *et al.*, 2011). Importantly, the score preserves the form of log-odds when it linearly combines different components (e.g., the similarity of two amino acid frequency vectors with that of SSs) as long as each component itself represents a log-odds score. Such a construction of composite scores is typical, and, given appropriate gap penalties, we can expect that the assumptions will hold for most profile-profile alignment methods.

Here, we use the COMER method (Margelevičius, 2016) as a means for producing profile-profile alignment scores the algorithms developed in this work employ. The COMER profile at each position encapsulates the transition probabilities of moving to and from the states of insertion and deletion, which for a pair of profiles transform to position-specific gap penalties. Comparing two COMER profiles also includes scoring predicted secondary structure and sequence contexts (Margelevičius, 2018). These properties make the characterization of the distribution of alignment scores a challenging task.

We aim at proposing a general procedure for estimating the statistical significance of profile-profile alignments. Therefore, we do not consider any modifications to the profile model, such as introducing additional HMM states and their transitions for more reliable alignment statistics (Eddy, 2008), which, however,

affect alignments and their scores not necessarily leading to increased sensitivity. This fits the procedure's objective to specify an alignment score distribution for profiles representing as much as possible real unrelated proteins.

The importance of the null model of random protein sequences has long been recognized (Mott, 2000; Yu and Hwa, 2001; Metzler, 2006; Eddy, 2008; Meng *et al.*, 2011). Real sequences do not conform to the canonical (and simplest) model, in which the amino acids in the sequence are iid, and exhibit a more complex structure with short- and long-range amino acid correlations. It has been proved that in the limit of infinitely long sequences, ungapped alignment scores for random Markov-dependent sequences are still distributed according to the EVD (Karlin and Dembo, 1992). Gapped alignments of random correlated sequences accounted for by a null model have been shown numerically to correspond to an EVD too (Messer *et al.*, 2007). Notably, the values of the statistical parameters differed substantially from those obtained for iid sequences.

In this work, the null model of protein sequence family does not explicitly incorporate correlations between families and leaves the profile-profile scoring function unchanged. Instead, we randomly generate profiles with properties of real unrelated profiles and take into account the correlations between them by establishing the dependence of statistical parameters on the compositional similarity between the profiles. The null model affects the probability of a score of a pair of profile positions, yet the change in composition does not alter the type of alignment score distribution but values of statistical parameters. The approach proposed here predicts differences in these values.

Overall, this work purposes a procedure for estimating the statistical significance of profile-profile alignments, regarding the effects and factors that influence alignment score distribution, such as edge effects, compositional similarity, and profile attributes (length and the effective number of observations). The procedure builds on an algorithm proposed for generating profiles that resemble real sequence families. The results of the implemented procedure give rise to an analysis of its impact on sensitivity and alignment quality, which we also provide in this paper.

2 Methods

The concept of estimating the statistical significance of profile-profile alignments, as proposed here, is illustrated in Figure 1. The significance of the alignment between a profile of length l_1 and effective number of observations (ENO) n_1 and another profile of length l_2

Figure 1. Concept of estimating the statistical significance of profile-profile alignments.

and ENO n_2 follows from combining the significance of the alignment score and that of the number of positive substitution scores in the alignment. The distribution of alignment scores depends on both the length of profiles being compared and their ENOs (Sadreyev and Grishin, 2008) (Supplementary Section S2.1 defines ENO). It also depends on the compositional similarity of profiles. Therefore, the significance of the alignment score of profiles 1 and 2 is calculated using statistics obtained from aligning unrelated profiles of the same length and ENO and having the same mutual compositional similarity.

The questions related to the proposed concept are the following: 1. How is the compositional similarity between profiles calculated? 2. What types of distributions govern alignment score and the number of positive substitution scores? 3. How are unrelated profiles generated? 4. How are statistics that are obtained from different simulations combined? 5. How are statistics derived for any values of length, ENO, and compositional similarity? 6. How are dependent p-values combined?

We consider them in detail below. More details can be found in Supplementary Section S4.

2.1 Compositional similarity

The statistical parameter $\lambda_u \equiv \lambda$ of the limiting distribution of sequence alignment scores (1) has several related meanings (Karlin and Altschul, 1990; Altschul et al., 1997; Schäffer et al., 2001). λ_u can also be regarded as a measure of compositional similarity (Yu et al., 2006). The value of λ_u found as the positive

solution to

$$\sum_k p(s_k) \exp(\lambda_u s_k) = 1, \qquad (2)$$

where $\{s_k\}_k$ represent different values of scores in the substitution matrix and $p(s_k)$ is the probability of s_k, will decrease as the number of positive substitution scores increases ($p(s_k)$ increases for all $k : s_k > 0$). Therefore, low values of λ_u may indicate an increased probability for a high-scoring alignment to occur by chance due to compositionally biased regions in two sequences.

The parameter λ_u calculated for a pair of profiles (Sadreyev and Grishin, 2003; Margelevičius and Venclovas, 2010) has the same dependence on composition. We take into account compositional similarity between profiles by specifying the dependence of the distribution of profile-profile alignment scores on it.

2.2 Alignment scores of real unrelated profiles

We analyze the distribution of alignment scores of real unrelated profiles (constructed from multiple sequence alignments, MSAs, of real sequences) for two reasons. One is to determine the type of distribution that describes them. The other reason is that these data provide a reference point for generating random profiles whose alignment scores would follow the same type of distribution and be similarly distributed.

We found that alignment scores of real unrelated profiles follow an EVD and 85% of goodness-of-fit tests do not reject the null hypothesis. Supplementary Sections S2.3 and S3.1, respectively, describe how real unrelated profiles were obtained and detail the comparison of profiles of different length, ENO, and compositional similarity.

2.3 Profile simulation

It is impractical to use real unrelated profiles to produce sufficient data for any values of profile length, ENO, and compositional similarity. Instead, random profiles are generated.

It has been shown that using a null model to generate realistic random profiles improves remote homology detection (Sadreyev and Grishin, 2008). Therefore, the aim is to develop an algorithm for generating random profiles that exhibit properties of real profiles, and the degree of correlation between the random profiles can be controlled.

We achieve that by using a modest number of "seed" profiles constructed for a diverse set of real sequences. Random profiles then result from adding noise to profiles/MSAs generated using these seed profiles as a model. Seeds provide properties of real profiles,

whereas noise and randomization represent a means of controlling correlation between random profiles. However, Supplementary Section S3.2 demonstrates the complications that arise when the comparison of generated profiles includes the scoring of SSs predicted for profiles.

Hence, an important feature of the algorithm that we propose (Algorithm 1) is that random profiles result from concatenating fixed-length fragments sampled randomly from a set of generated MSAs regardless of SS predictions the fragments entail. Supplementary Section S4.1 provides additional details, and Supplementary Algorithm S2 defines how MSAs with added noise are produced using a profile model in step 2 of Algorithm 1.

Algorithm 1 Generating random profiles of length l and ENO n given noise level r and fragment length s

---

Input: S sequences.
Output: R random profiles.

1. Make profiles (seeds) for S diverse sequences chosen at random for which profiles are obtained to be of a sufficiently large ENO (e.g., 12).

2. Using each of the S seed profiles as a model, generate M MSAs of ENO n with noise r.

3. Using each set of $S \times M$ generated MSAs of ENO n as source MSAs, generate a set of R random MSAs of length l in the following way:

    (a) choose a number j at random uniformly between 1 and $S \times M$;

    (b) randomly select a fragment of length s of source MSA j;

    (c) copy and add the selected fragment to a random MSA being generated;

    (d) repeat steps (3a)–(3c) until the length of the random MSA becomes l.

4. Construct profiles from the R generated random MSAs.

Algorithm 1 shows that the fragment length s and the level r of noise added to $S \times M$ generated MSAs are the parameters that determine the degree of similarity among resulting random profiles. Too large s and/or too small r lead to highly correlated random profiles, while too small s or too large r result in divergent profiles and useless alignment statistics.

2.4 Optimizing s and r

Based on the results reported in Section 2.2, we find the optimal s and r using two criteria: (1) the goodness of fit of the EVD to the empirical distribution of alignment scores and (2) the distance between the distribution function obtained for real unrelated profiles and the distribution function obtained from simulations. In this way, profiles generated using the optimal s and r possess features characteristic to real profiles and correlations between them do not dominate.

We calculate the supremum class upper tail Anderson-Darling statistic AD_{up} (Chernobai $et\ al.$, 2015) (Supplementary Section S5.1) for testing the goodness of fit of the EVD to the data (the first criterion). We normalize it, $AD_{\mathrm{up}}^{\star} = AD_{\mathrm{up}}/\sqrt{N}$, by the square root of the number of alignment scores, $\sqrt{N}$, to make it independent of sample size. The distance between two empirical distribution functions (the second criterion) is measured by the two-sample Kolmogorov-Smirnov statistic D.

The whole procedure for finding the optimal s and r can be described as follows. 1. Choose values for s and r. 2. Using Algorithm 1, generate random profiles of all ENOs and lengths considered. 3. Align simulated profiles. 4. Fit the EVD in the right tail of alignment score distributions. 5. Calculate the $AD_{\mathrm{up}}^{\star}$ statistic for each alignment score distribution. 6. Train models for predicting the statistical parameters for profiles with given attributes (ENO and length) and compositional similarity. 7. Predict the statistical parameters and calculate the p-value of each alignment of real unrelated profiles. 8. For each combination of pair values of profile ENO and length, calculate the distance D between the empirical distribution function obtained for real unrelated profiles and the distribution function obtained in step 7. 9. Repeat steps 1–8 until the optimal s and r with respect to $AD_{\mathrm{up}}^{\star}$ and D have been found.

We discuss prediction of statistical parameters (step 7) below. Here we note that predictions are used to incorporate compositional similarity into the statistical model of profile-profile alignments.

The results (Figure 2A) obtained using $S = 1012$ seed profiles ($M = 1$) suggest that considering a small number of different values suffices to find the optimal s and r: Large s increases correlation between profiles, whereas large r makes them unalignable. Figure 2A shows that the best balance between the two criteria is achieved for $s = 9$ and $r = 0.03$.

Sections S6.1 and S6.2 present additional results from simulation experiments. They also show that seeding from three different profiles representing different SCOPe (Fox $et\ al.$, 2013) classes leads to similar results (Figure 2B). Using one seed facilitates profile simulation.

Figure 2. Distance between distributions against goodness of fit for different values of s and r. Each point represents the average over all distributions obtained for different pair values of profile attributes. Vertical bars represent one standard deviation. Gray and black colors show the results obtained with and without considering the compositional similarity between profiles, respectively. (A): Results obtained using $S = 1012$ seed profiles. (B): Results for three different seed profiles ($S = 1$) used to generate $M = 1000$ source MSAs with $s = 9$ and $r = 0.03$. In this case, the results obtained with and without considering compositional similarity coincide.

Figure 3. Complete procedure of estimating the statistical significance of profile-profile alignments.

2.5 Combining statistics

Consider two profiles, one of length l_1 and ENO n_1 and another one of length l_2 and ENO n_2. The profiles share compositional similarly λ_u. Then, the significance of their alignment score is determined from combining statistics obtained (1) from aligning simulated profiles of length l_1 and ENO n_1 against profiles of length l_2 and ENO n_2 and (2) from aligning profiles of length l_1 against profiles of length l_2 with mutual compositional similarly λ_u, as shown in Figure 1. Here we define this statistical combination.

Let A and B index two distributions. The first is obtained for profiles described by the set of attributes $\{n_1, l_1; n_2, l_2\}$ (i.e., profiles of length l_1 and ENO n_1 have been aligned against profiles of length l_2 and ENO n_2) and the other for profiles characterized by the set of attributes $\{\lambda_u; l_1; l_2\}$. Assume that distributions A and B belong to the family of EVDs. Let $\hat{\mu}^A$ and $\hat{\sigma}^A$ respectively denote the estimates of the location and scale parameters of the EVD corresponding to distribution A. Similarly, let $\hat{\mu}^B$ and $\hat{\sigma}^B$ be the estimates of the statistical parameters of distribution B. Then, the conditional mean estimator of the location parameter given two sets of parameters specifying its distribution in settings A and B is

$$\hat{\mu} = a\hat{\mu}^A + (1-a)\hat{\mu}^B \quad (0 < a < 1), \qquad (3)$$

and the corresponding conditional mean estimator of the scale parameter is

$$\hat{\sigma} = b\hat{\sigma}^A + (1-b)\hat{\sigma}^B \quad (0 < b < 1), \qquad (4)$$

where a and b are parameters that depend on the parameters specifying the distributions of the location and scale parameters, respectively, in settings A and B (see Supplementary Appendix A for details and a proof).

2.6 Prediction of statistical parameters

In simulations (Section 2.4), random profiles are generated of predefined lengths $l \in \mathsf{L}$ and ENOs $n \in \mathsf{N}$ and discretized values of mutual compositional similarity λ_u rounded to the nearest multiple of 0.1. The sets $\mathsf{L} = \{50, 100, 200, 400, 600, 800\}$ and $\mathsf{N} = \{2, 4, 6, \dots, 14\}$ represent these predefined values.

Statistical significance for profiles of any length l, ENO n, and λ_u has to be estimated based on the statistics obtained from the observed distributions. As the statistics depend non-linearly on l, n, and λ_u (Supplementary Section S6), we use low-complexity artificial neural network (NN) models to predict statistical parameters. The models are trained on the estimates obtained (1) from aligning simulated profiles of length $l_1 \in \mathsf{L}$ and ENO $n_1 \in \mathsf{N}$ against profiles of length $l_2 \in \mathsf{L}$ and ENO $n_2 \in \mathsf{N}$ ($n_2 < n_1$) and (2) from aligning profiles of length $l_1 \in \mathsf{L}$ against profiles of length $l_2 \in \mathsf{L}$ with λ_u discretized. We denote the predictions of the location parameter in these two settings by $\hat{\mu}^A(n_1, l_1; n_2, l_2)$ and $\hat{\mu}^B(\lambda_u; l_1; l_2)$, respectively. The notation for the scale parameter is similar. (See also Supplementary Section S4.4.)

2.7 Adjustment of predictions

Statistical accuracy does not necessarily correlate with increased sensitivity and alignment quality (Yu et al., 2006; Sadreyev and Grishin, 2008). Therefore, to simultaneously improve all these qualities, we introduce simple adjustments to the predicted location $\hat{\mu}^v(\cdot)$ and scale parameters $\hat{\sigma}^v(\cdot)$ ($v = A, B$), as shown in Figure 3.

Observing a high correlation between the scale and the location parameters (Supplementary Section S6.3), we adjust the scale parameters as follows:

$$\tilde{\sigma}^A = g_s\hat{\mu}^A + g_i, \quad \tilde{\sigma}^B = g_c(\exp(\hat{\sigma}^B) - 1). \qquad (5)$$

The first equation eliminates the need to predict $\hat{\tilde{\sigma}}^{A}$. The second equation, although expressed non-linearly in $\hat{\tilde{\sigma}}^{B}$, employs one coefficient whose optimal value implies almost the same result as in the case of expressing the scale parameter linearly in $\hat{\tilde{\mu}}^{B}$.

We adjust the location parameters similarly:

$$\tilde{\mu}^{A} = h_s \hat{\tilde{\mu}}^{A} + h_i, \quad \tilde{\mu}^{B} = \hat{\tilde{\mu}}^{B} + h_c. \tag{6}$$

Note that the adjustments $\tilde{\mu}^v$ and $\tilde{\sigma}^v$ ($v =$ A, B) retain the dependence of the statistical parameters on the profile length and ENO and compositional similarity. They only scale and shift predictions made by the trained models.

Conditional mean estimators (3) and (4) are used to combine $\tilde{\mu}^v$ and $\tilde{\sigma}^v$ ($v =$ A, B). The parameters a and b and the coefficients $W = \{g_s, g_i, g_c, h_s, h_i, h_c\}$ in (5) and (6), which we refer to as the adjustment parameters, are optimized with respect to statistical accuracy and alignment quality and sensitivity (Supplementary Section S6.5). Here we note that the optimal balance is achieved with the compositional similarity between profiles having a large impact ($a = b = 0.35$) on conditional mean estimates.

2.8 Number of positive substitution scores

The number of positive profile-profile substitution scores in the alignment provides additional information to the alignment score. For example, the same alignment score can be the result of many weakly positive substitution scores or a few high scores. Therefore, it can be a useful indicator for estimating the significance of profile-profile alignments.

The distribution of the number of positive substitution scores can be accurately approximated by the negative binomial distribution (NBD) (Supplementary Section S6.4). However, aiming to reduce the overall complexity of the calculation of statistical significance, we propose a derived statistic ω_n. It depends on the lengths of profiles being compared and its value (consequently, its significance) decreases as the alignment search space (the product of the profile lengths) increases:

$$\omega_n = \left\lfloor \frac{c_0 \omega}{(l_1 l_2)^{\frac{3}{2}}} \right\rceil. \tag{7}$$

Here $\lfloor \cdot \rceil$ denotes rounding to the nearest integer, l_1 and l_2 are the lengths of two profiles compared, ω is the number of positive substitution scores in the alignment, and $c_0 = 10^5$ is the constant that is equal to the value of the denominator when l_1 and l_2 are slightly less than 50. Hence, the ω_n statistic corresponds to the number of positive substitution scores when the search space approximately equals that of two profiles of length 50. The number of positive substitution scores becomes less

informative as the search space increases, and, consequently, the value of the ω_n statistic decreases. The distribution of ω_n is approximately negative binomial (Supplementary Section S6.4).

The complete procedure for statistical significance estimation is shown in Figure 3. p-values of alignment score and ω_n, P_a and P_o, are combined using the empirical Brown's method (Poole et al., 2016) (Supplementary Section S4.5).

2.9 E-value and its correction

The expected number of local alignments with a score greater than or equal to x, $E = K l_1 l_N e^{-\lambda x}$, increases as the size of the search space increases (Karlin and Altschul, 1990; Dembo et al., 1994; Waterman and Vingron, 1994b; Spang and Vingron, 2001). (E-value and p-value P are related by the equation $P = 1 - \exp(-E)$.) Let E_N be the E-value of an alignment with score x obtained from searching a database of size l_N. Let also $E_{N'}$ be the E-value of an alignment with the same score x (and profile composition) obtained by searching a database of size $l_{N'}$ with the same query. Then, the relationship between E_N and $E_{N'}$ is (Yu et al., 2006)

$$E_N = \frac{l_N}{l_{N'}} E_{N'}. \tag{8}$$

We use this relationship when compensating for a limited number of randomly generated profiles used in simulations. We refer to the results obtained by calculating the corrected E-value as the alternative model.

3 Results

This section presents results from the application of the proposed procedure (Figure 3) for estimating the statistical significance of profile-profile alignments. The NN models predicting statistical parameters were trained on the estimates obtained for profiles generated by Algorithm 1 with a noise level $r = 0.03$ and a fragment length $s = 9$, as determined in Section 2.4.

3.1 Statistical accuracy

We used COMER to search and align the profiles constructed for 5000 simulated Pfam (Finn et al., 2016) (v30.0) MSAs against the database of simulated profiles representing 4931 SCOPe (v2.03) domains. The profiles were randomized using Algorithm 1 to preserve length, ENO, and composition inherent in each of the Pfam MSAs and profiles constructed for the SCOPe domains (see Supplementary Section S5.2). Then, we calculated the fraction of queries with a p-value reported by COMER for their best match less than the specified p-value.

Figure 4. Statistical accuracy of the COMER method using different models for statistical significance estimation. Shown are the results of comparing the profiles constructed for 5000 randomized Pfam families to the profiles constructed for 4931 randomized SCOPe domains. The figure plots the fraction of queries with a p-value reported for their best match less than the p-value indicated on the x-axis. The dashed line indicates the highest accuracy. These models are represented in the figure: the new model (new) proposed, the alternative model with E-value correction (new (alt.)), the statistical model used in the previous COMER version (previous), a model based on the statistics obtained for profiles generated with $s = 1$ and $r = 0.01$, and the model excluding the number of positive substitution scores (w/o ω_n).

The results are shown in Figure 4. The new model for statistical significance estimation is more accurate than the model (Margelevičius and Venclovas, 2010) implemented in the previous version (Margelevičius, 2018) of the COMER method. The results also show that the statistics obtained from aligning profiles generated by randomly permuting MSA columns ($s = 1$, $r = 0.01$) lead to overestimation of statistical significance. This result can be accounted for by unrealistic representation of protein sequence families (profiles).

Finally, although the models with and without the ω_n statistic taken into consideration achieve comparable statistical accuracy, the sensitivity and alignment quality obtained using the latter model (w/o ω_n) are lower.

3.2 Sensitivity and alignment quality

We compared the performance of the new COMER version with that of its previous version (Margelevičius, 2018), where the new and previous versions differed only in how they estimated the statistical significance of alignments. For reference, we also provide results for two other profile-profile alignment methods, HHsearch (Söding, 2005) (v3.0.0) and FFAS (Jaroszewski et al., 2011).

4900 protein domains of the test dataset from the SCOPe database (v2.03) filtered to 20% sequence identity was used to evaluate performance. The test and training datasets shared no common folds.

Profiles were constructed using two categories of

MSAs. The MSAs for each domain sequence were obtained by running PSI-BLAST (Altschul et al., 1997) (v2.2.28+) for six iterations and HHblits (Remmert et al., 2012) for three iterations, respectively, against a filtered UniProt database (Suzek et al., 2015).

A pair of aligned domains (profiles) that belonged to the same SCOPe superfamily or shared statistically significant structural similarity (DALI (Holm et al., 2008) Z-score ≥ 2) was considered a true positive (TP). Aligned pairs that did not meet the above criteria but belonged to the same SCOPe fold were considered to have an unknown relationship and were ignored. Other aligned pairs were considered false positives (FPs). The sensitivity was also summarized using the ROC_n score, which is the normalized area under the ROC curve up to n FPs.

Alignment quality was evaluated by generating, using MODELLER (Šali and Blundell, 1993) (v9.4), protein structural models for each produced alignment. Statistically significant similarity between a model and the real structure, TM-score ≥ 0.4 (Zhang and Skolnick, 2004), was considered to correspond to a high-quality alignment (HQA). An alignment with a TM-score < 0.2, a characteristic value for a random pair, was assumed to be of low-quality (LQA).

Two evaluation modes were used to evaluate alignment quality. The local mode penalizes alignment overextension, whereas the global mode penalizes too short alignments (e.g., a few amino acids in length). These evaluation modes were also used to evaluate the quality of maximally extended alignments produced by COMER and HHsearch (option -mact set to 0). The evaluation of maximally extended alignments reveals how the quality of local alignments changes with their extension. It provides an indication of the quality of the match between the query and a database protein, which is also important in protein homology modeling.

(Details about the evaluation setting can be found in Supplementary Section S5.3.)

Figure 5 and Table 1 reveal that the new statistical model lead to consistent improvement in both sensitivity and alignment quality and that most of the improvements are statistically significant.

Using the developed statistical model yielded an increase of up to 34.2% and 27.4% in the number of TPs and up to 43.9% and 61.8% in the number of HQAs. Table 2 shows that these percentage increases were achieved at a low false discovery rate (FDR). Hence, the largest relative improvements are expected for relationships detected at a high confidence level.

Table 2 also shows that the relative increases were greater when the profiles were constructed from the PSI-BLAST MSAs. A similar trend was also observed for the number of HQAs examined as a function of the number of alignments of inferior quality (IQAs) (Sup-

Figure 5. Performance of profile-profile alignment methods. (A,B): Sensitivity. (C–J): Alignment quality evaluated in the (C,E,G,I) local and (D,F,H,J) global evaluation modes. Maximally extended (max ext) COMER and HHsearch alignments are evaluated in (E,F,I,J). Profiles were constructed from (A,C–F) HHblits and (B,G–J) PSI-BLAST MSAs. COMER new (alt.) represents the COMER method using the model with E-value correction. COMER v1.4 represents the previous version of the COMER method. The color coding matches that of Figure 4. HQA, high-quality alignment. LQA, low-quality alignment.

Input	Evaluation	x	COMER new		COMER new (alt.)		COMER v1.4
			ROC_x	Z (p-value)	ROC_x	Z (p-value)	ROC_x
HHblits MSAs	Sensitivity	6000	0.837	0.9 (0.350)	0.836	0.6 (0.571)	0.835
PSI-BLAST MSAs	Sensitivity	6000	0.705	5.6 (1.7×10^{-8})	0.698	2.6 (0.009)	0.690
HHblits MSAs	Local	150	0.782	0.9 (0.350)	0.753	-0.9 (0.352)	0.768
	Global	10000	0.456	8.6 ($<3\times10^{-16}$)	0.456	7.3 (3.8×10^{-13})	0.438
	Local (max ext)	1000	0.628	9.0 ($<3\times10^{-16}$)	0.624	7.1 (1.7×10^{-12})	0.591
	Global (max ext)	1700	0.603	7.6 (3.9×10^{-14})	0.598	7.2 (7.7×10^{-13})	0.574
PSI-BLAST MSAs	Local	400	0.642	1.6 (0.103)	0.623	0.2 (0.874)	0.621
	Global	22000	0.330	3.7 (2.2×10^{-4})	0.334	4.9 (1.2×10^{-6})	0.321
	Local (max ext)	2500	0.496	5.3 (1.2×10^{-7})	0.499	6.3 (2.8×10^{-10})	0.477
	Global (max ext)	5000	0.471	5.1 (3.0×10^{-7})	0.474	5.6 (2.1×10^{-8})	0.457

Table 1. Area under the ROC curve and improvement of the COMER method. The sensitivity and alignment quality (Local and Global evaluation modes) of versions of the COMER method are evaluated. Maximally extended (max ext) COMER alignments are included in the evaluation. Profiles were constructed from HHblits and PSI-BLAST MSAs. ROC_x is the ROC score calculated up to x false positives (FPs; Sensitivity) or low-quality alignments (LQAs; alignment quality in the Local and Global modes). The number of FPs or LQAs, x, depends on the evaluation mode (see also Figure 5). Z is the difference between the areas (ROC_x scores) obtained for a new and the previous (v1.4) versions of the COMER method, divided by the estimated standard error. The statistical significance of Z is indicated in parentheses.

Input	Evaluation	COMER new			COMER new (alt.)		
		TPs (+%)	$\text{TPs}_{v1.4}$	FDR	TPs (+%)	$\text{TPs}_{v1.4}$	FDR
HHblits MSAs	Sensitivity	34902 (7.4)	32483	0.001	33474 (3.1)	32483	0.001
PSI-BLAST MSAs	Sensitivity	27666 (34.2)	20612	0.002	26266 (27.4)	20612	0.002
HHblits MSAs	Local	75622 (2.9)	73526	0.002	0 (0)	0	0
	Global	16699 (15.9)	14414	0.001	18670 (29.5)	14414	0.001
	Local (max ext)	46608 (8.8)	42857	0.005	38090 (10.8)	34367	0.001
	Global (max ext)	43603 (7.6)	40531	0.008	42165 (8.9)	38704	0.006
PSI-BLAST MSAs	Local	61222 (4.4)	58627	0.004	13423 (13.4)	11842	0.001
	Global	10248 (43.9)	7123	0.001	11523 (61.8)	7123	0.001
	Local (max ext)	25208 (8.9)	23146	0.004	28819 (24.5)	23146	0.004
	Global (max ext)	25161 (7.3)	23453	0.007	15588 (24.6)	12515	0.003

Table 2. Increase in the number of true positives or high-quality alignments. Shown are the results of the evaluation of the sensitivity and alignment quality (Local and Global evaluation modes) of versions of the COMER method using profiles constructed from HHblits and PSI-BLAST MSAs. TPs stands for the number of true positives (Sensitivity) or high-quality alignments (in the Local and Global evaluation modes) at a specified false discovery rate (FDR) for a new version of the COMER method. $\text{TPs}_{v1.4}$ represents the same number for the previous COMER version. The percentage improvement with respect to $\text{TPs}_{v1.4}$ is given in parentheses. 0 indicates no improvement.

plementary Section S7.1). In this evaluation setting, the developed statistical model showed an increase of up to 102.8% and 193.3% in the number of HQAs.

MSAs obtained from a PSI-BLAST search contain more alignment errors than those built using HHblits. Larger relative improvements in performance achieved when using PSI-BLAST MSAs for profile construction, therefore, show a certain degree of robustness that the new model exhibit. We attribute this characteristic to the combination of statistical parameters dependent upon both profile length and ENO and compositional similarity. If a high alignment score of two unrelated profiles arises due to false positives in the corresponding MSAs, a high compositional similarity between the profiles counterbalances the statistical significance estimated solely based on profile length and ENO.

3.3 Application to pairwise profile HMM alignments

We applied the methodology for estimating statistical significance (Figure 3) to pairwise profile HMM alignments produced by HHsearch. An improvement in both statistical accuracy and sensitivity and alignment quality (Supplementary Section S7.2) confirms the effectiveness of the developed methodology.

3.4 Example of reduced significance for a false positive

Reranking alignments using the proposed estimation of statistical significance has been shown to increase sensitivity and the rate of HQAs. This is demonstrated by an example.

Two domains d2hi7b1 (a.29.15.1) and d2cfqa_ (f.38.1.2) are alpha-helical proteins but represent different SCOPe classes. They have different topology and do not share statistically significant structural similarity.

Alpha-helical structure implies a high compositional similarity $\lambda_u = 0.296$ between the profiles constructed for the two domains (low values of λ_u correspond to high compositional similarity; Supplementary Sections S6.1 and S6.2). Significance estimation dependent upon compositional similarity allowed the new COMER version to correctly remove the alignment from the list of statistically significant alignments. In contrast, the alignment was considered significant by the previous COMER version. Note that both versions estimated the significance of the same alignment with the same score.

4 Discussion

Profiles represent sequence families, and this fact alone suggests that a profile contains information whose content largely depends on the family the profile describes. It means that the degree of (dis)similarity (distance) between unrelated sequence families strongly affects the distribution of scores of alignments between profiles that represent these families. The challenging aspects of characterizing the distribution of profile-profile alignment scores, however, are not limited to diversity across unrelated profiles. Similarity between SS, context and other predictions that accompany profiles complicate the characterization of alignment score distribution too.

The importance of a null model of profiles motivated us to develop an algorithm for generating random profiles. According to the algorithm, profiles are generated by concatenating fixed-length fragments sampled randomly from real unrelated profiles (seeds) with added noise. Controlling the noise level and fragment length allows to produce random profiles that are neither overly divergent nor share an excessive similarity. In this way, random profiles possess features characteristic to real profiles, but correlations that do not allow them to be considered unrelated do not dominate. Alignments between randomly generated profiles allowed us to determine the dependence of statistical parameters on profile length and ENO and also on compositional similarity between profiles.

The results suggest two important implications. First, profiles generated using long fragments (fragment length 9) represent real unrelated profiles much more accurately than do those obtained by randomly sampling profile columns. Statistics obtained from their alignments lead to higher statistical accuracy. On the other hand, randomly sampling of columns destroys higher-order dependencies inherent in real proteins and leads to the opposite result.

Second, the compositional similarity between profiles has a large impact on estimating the statistical significance of alignments. Improvements in sensitivity and alignment quality can be accounted for in part by that a high compositional similarity may indicate that the proteins share common structural elements or the profiles involve false positives. Significance estimation dependent upon compositional similarity, therefore, has a positive effect.

In fact, the issues of profile composition and random profile model are factors that hinder the application of techniques such as importance sampling (Park *et al.*, 2009) to accurately estimating statistical parameters. While composition can be measured in different ways, choosing a random profile model is more complicated because every profile represents a model. For example, the composition of two profiles, one of them obtained by randomly rearranging the positions of the other, will be the same. However, the distribution of alignment scores of profiles generated using the profile with rearranged positions as a seed (model) will differ from that obtained for profiles generated using the other profile as a seed. In this study, close match to the distribution of alignment scores of real unrelated reference profiles constituted one of the criteria for random profile model selection. However, a supplementary approach might be beneficial.

Based on the above considerations and the results obtained by generating random profiles using one seed profile, we suspect that further improvements may result from introducing a new measure of profile "sequence affinity" (as opposed to the quantitative measure of the effective number of observations). The benefit may come from including into the model the statistical parameters dependent upon the new measure through, e.g., the application of the conditional mean estimator. The present study already demonstrated the conditional mean estimator to be effective when the calculation of compositional similarity or divergence between profiles was in use. And it provides possibilities for further improvements.

Funding

This research was funded by the European Regional Development Fund according to a supported activity under Measure No. 01.2.2-LMT-K-718 (Grant No. 01.2.2-LMT-K-718-01-0028).

References

Altschul, S. and Gish, W. (1996). Local alignment statistics. *Methods Enzymol*, **266**, 460–480.

Altschul, S., Madden, T., Schäffer, A., Zhang, J., Zhang, Z., Miller, W., *et al.* (1997). Gapped BLAST and PSI-BLAST: a new generation of protein database search programs. *Nucleic Acids Res*, **25**(17), 3389–3402.

Altschul, S., Bundschuh, R., Olsen, R., and Hwa, T. (2001). The estimation of statistical parameters for local alignment score distributions. *Nucleic Acids Res*, **29**(2), 351–361.

Arratia, R. and Waterman, M. (1994). A phase transition for the score in matching random sequences allowing deletions. *Ann Appl Probab*, **4**(1), 200–225.

Chernobai, A., Rachev, S., and Fabozzi, F. (2015). Composite goodness-of-fit tests for left-truncated loss samples. In C. Lee and J. Lee, editors, *Handbook of Financial Econometrics and Statistics*, pages 575–596. Springer, New York.

Dembo, A., Karlin, S., and Zeitouni, O. (1994). Limit distribution of maximal non-aligned two-sequence segmental score. *Ann Probab*, **22**(4), 2022–2039.

Eddy, S. (2008). A probabilistic model of local sequence alignment that simplifies statistical significance estimation. *PLoS Comput Biol*, **4**(5), e1000069.

Finn, R., Coggill, P., Eberhardt, R., Eddy, S., Mistry, J., Mitchell, A., *et al.* (2016). The Pfam protein families database: towards a more sustainable future. *Nucleic Acids Res*, **44**(D1), D279–D285.

Fox, N., Brenner, S., and Chandonia, J. (2013). SCOPe: Structural classification of proteins–extended, integrating SCOP and ASTRAL data and classification of new structures. *Nucleic Acids Res*, **42**(D1), D304–D309.

Holm, L., Kääriäinen, S., Rosenström, P., and Schenkel, A. (2008). Searching protein structure databases with DaliLite v.3. *Bioinformatics*, **24**(23), 2780–2781.

Jaroszewski, L., Li, Z., Cai, X. H., Weber, C., and Godzik, A. (2011). FFAS server: novel features and applications. *Nucleic Acids Res*, **39**, W38–W44.

Karlin, S. (2005). Statistical signals in bioinformatics. *Proc Natl Acad Sci USA*, **102**(38), 13355–13362.

Karlin, S. and Altschul, S. (1990). Methods for assessing the statistical significance of molecular sequence features by using general scoring schemes. *Proc Natl Acad Sci USA*, **87**(6), 2264–2268.

Karlin, S. and Brendel, V. (1992). Chance and statistical significance in protein and dna sequence analysis. *Science*, **257**(5066), 39–49.

Karlin, S. and Dembo, A. (1992). Limit distributions of maximal segmental score among markov-dependent partial sums. *Adv Appl Probab*, **24**(1), 113–140.

Karlin, S., Dembo, A., and Kawabata, T. (1990). Statistical composition of high-scoring segments from molecular sequences. *Ann Stat*, **18**(2), 571–581.

Kotz, S. and Nadarajah, S. (2000). *Extreme value distributions: theory and applications*. Imperial College Press, London.

Margelevičius, M. (2016). Bayesian nonparametrics in protein remote homology search. *Bioinformatics*, **32**(18), 2744–2752.

Margelevičius, M. (2018). A low-complexity add-on score for protein remote homology search with COMER. *Bioinformatics*, **34**(12), 2037–2045.

Margelevičius, M. and Venclovas, Č. (2010). Detection of distant evolutionary relationships between protein families using theory of sequence profile-profile comparison. *BMC Bioinformatics*, **11**, 89.

Meng, L., Sun, F., Zhang, X., and Waterman, M. (2011). Sequence alignment as hypothesis testing. *J Comput Biol*, **18**(5), 677–691.

Messer, P., Bundschuh, R., Vingron, M., and Arndt, P. (2007). Effects of long-range correlations in DNA on sequence alignment score statistics. *J Comput Biol*, **14**(5), 655–668.

Metzler, D. (2006). Robust E-values for gapped local alignments. *J Comput Biol*, **13**(4), 882–896.

Mott, R. (1992). Maximum-likelihood estimation of the statistical distribution of smith-waterman local sequence similarity scores. *Bull Math Biol*, **54**(1), 59–75.

Mott, R. (2000). Accurate formula for P-values of gapped local sequence and profile alignments. *J Mol Biol*, **300**(3), 649–659.

Park, Y., Sheetlin, S., and Spouge, J. (2009). Estimating the Gumbel scale parameter for local alignment of random sequences by importance sampling with stopping times. *Ann Stat*, **37**(6A), 3697–3714.

Pearson, W. (1998). Empirical statistical estimates for sequence similarity searches. *J Mol Biol*, **276**(1), 71–84.

Poleksic, A. (2009). Island method for estimating the statistical significance of profile-profile alignment scores. *BMC Bioinformatics*, **10**, 112.

Poole, W., Gibbs, D., Shmulevich, I., Bernard, B., and Knijnenburg, T. (2016). Combining dependent p-values with an empirical adaptation of Brown's method. *Bioinformatics*, **32**(17), i430–i436.

Remmert, M., Biegert, A., Hauser, A., and Söding, J. (2012). HHblits: lightning-fast iterative protein sequence searching by HMM-HMM alignment. *Nat Methods*, **9**(2), 173–175.

Sadreyev, R. and Grishin, N. (2003). Compass: a tool for comparison of multiple protein alignments with assessment of statistical significance. *J Mol Biol*, **326**(1), 317–336.

Sadreyev, R. and Grishin, N. (2008). Accurate statistical model of comparison between multiple sequence alignments. *Nucleic Acids Res*, **36**(7), 2240–2248.

Schäffer, A., Aravind, L., Madden, T., Shavirin, S., Spouge, J., Wolf, Y., *et al.* (2001). Improving the accuracy of PSI-BLAST protein database searches with composition-based statistics and other refinements. *Nucleic Acids Res*, **29**(14), 2994–3005.

Söding, J. (2005). Protein homology detection by HMM-HMM comparison. *Bioinformatics*, **21**(7), 951–960.

Spang, R. and Vingron, M. (1998). Statistics of large-scale sequence searching. *Bioinformatics*, **14**(3), 279–284.

Spang, R. and Vingron, M. (2001). Limits of homology detection by pairwise sequence comparison. *Bioinformatics*, **17**(4), 338–342.

Suzek, B., Wang, Y., Huang, H., McGarvey, P., Wu, C., and the UniProt Consortium (2015). UniRef clusters: a comprehensive and scalable alternative for improving sequence similarity searches. *Bioinformatics*, **31**(6), 926–932.

Šali, A. and Blundell, T. L. (1993). Comparative protein modelling by satisfaction of spatial restraints. *J Mol Biol*, **234**(3), 779–815.

Waterman, M. and Vingron, M. (1994a). Rapid and accurate estimates of statistical significance for sequence data base searches. *Proc Natl Acad Sci USA*, **91**(11), 4625–4628.

Waterman, M. and Vingron, M. (1994b). Sequence comparison significance and poisson approximation. *Stat Sci*, **9**(3), 367–381.

Yu, Y. and Hwa, T. (2001). Statistical significance of probabilistic sequence alignment and related local hidden markov models. *J Comput Biol*, **8**(3), 249–282.

Yu, Y., Gertz, E., Agarwala, R., Schäffer, A., and Altschul, S. (2006). Retrieval accuracy, statistical significance and compositional similarity in protein sequence database searches. *Nucleic Acids Res*, **34**(20), 5966–5973.

Zhang, Y. and Skolnick, J. (2004). Scoring function for automated assessment of protein structure template quality. *Proteins*, **57**(4), 702–710.