PhyloSuite: an integrated and scalable desktop platform for streamlined molecular sequence data management and evolutionary phylogenetics studies

Dong Zhang[1,2], Fangluan Gao[3], Wen X. Li[1], Ivan Jakovlić[4], Hong Zou[1], Jin Zhang[4] and Gui T. Wang[1,]*

[1]Key Laboratory of Aquaculture Disease Control, Ministry of Agriculture, and State Key Laboratory of Freshwater Ecology and Biotechnology, Institute of Hydrobiology, Chinese Academy of Sciences, Wuhan, P. R. China,

[2]University of Chinese Academy of Sciences, Beijing, P. R. China,

[3]Institute of Plant Virology, Fujian Agriculture and Forestry University, Fuzhou 350002, Fujian, P. R. China,

[4]Bio-Transduction Lab, Wuhan Institute of Biotechnology, Wuhan, P. R. China

* Corresponding author: gtwang@ihb.ac.cn (GTW)

Abstract

Multi-gene and genomic datasets have become commonplace in the field of phylogenetics, but many of the existing tools are not designed for such datasets, which makes the analysis time-consuming and tedious. We therefore present PhyloSuite, a user-friendly workflow desktop platform dedicated to streamlining molecular sequence data management and evolutionary phylogenetics studies. It employs a plugin-based system that integrates a number of useful phylogenetic and

bioinformatic tools, thereby streamlining the entire procedure, from data acquisition

to phylogenetic tree annotation, with the following features: (i) point-and-click and

drag-and-drop graphical user interface, (ii) a workspace to manage and organize

molecular sequence data and results of analyses, (iii) GenBank entries extraction and

comparative statistics, (iv) a phylogenetic workflow with batch processing capability,

(v) elaborate bioinformatic analysis for mitochondrial genomes. The aim of

PhyloSuite is to enable researchers to spend more time playing with scientific

questions, instead of wasting it on conducting standard analyses. The compiled binary

of   PhyloSuite   is   available   under   the   LGPL   license   at

https://github.com/dongzhang0725/PhyloSuite/releases, implemented in Python and

runs on Windows, Mac OSX and Linux.

Introduction

Advancements in next-generation sequencing technologies (Metzker, 2009) have

resulted in a huge increase in the amount of genetic data available through public

databases. While this opens a multitude of research possibilities, retrieving and

managing such large amounts of data may be difficult and time-consuming for

researchers who are not computer-savvy. A standard analytical procedure for

phylogenetic analysis is: selecting and downloading GenBank entries, extracting

target genes (for multi-gene datasets, such as organelle genomes) and/or mining other

data, sequence alignment, alignment optimization, concatenation of alignments (for

multi-gene datasets), selection of best-fit partitioning schemes and evolutionary

models, phylogeny reconstruction, and finally visualization and annotation of the

phylogram. This can be very time-consuming if different programs have to be

employed for different steps, especially as they often have different input file format

requirements, and sometimes even require manual file tweaking. Therefore,

multifunctional, workflow-type software packages are becoming increasingly needed

by a broad range of evolutionary biologists (Smith, 2015). Specifically, as single-gene

datasets are rapidly being replaced by multi-gene or genomic datasets as a tool of

choice for phylogenetic reconstruction (Degnan and Rosenberg, 2009; Rivera-Rivera

and Montoya-Burgos, 2016), automated gene extraction from genomic data and batch

manipulation in some of the above steps, like alignment, are becoming a necessity.

Although there are several tools in existence, designed to streamline this process

by incorporating some or all of the steps mentioned above, none of these

incorporate all of the above functions in a manner suitable for current trends in

phylogenetic analyses (see detailed comparison in Supplementary data). Therefore,

we present PhyloSuite, a versatile tool designed to incorporate all of the functions

described above, including a series of different phylogenetic analysis algorithms, into

a single workflow that does not require programming skills, has an intuitive graphical

user interface (GUI), workspace, batch mode, extensive plugins support, inbuilt

updating function, etc. (Fig. 1). This tool aims to be accessible to all scientists,

streamline the phylogenetic analysis procedure, and allow scientists to focus on

solving scientific questions rather than waste time on toying with different scientific

software programs.

Fig. 1. The interface and the main functions of PhyloSuite

Implementation

PhyloSuite is a user-friendly stand-alone GUI-based software written in Python 3.6.7

and packaged and tested on Windows, Mac OSX and Linux. The functions are (Fig. 1,

Supplementary data): (i) retrieving, extracting, organizing and managing molecular

sequence data, including GenBank entries, nucleotide and amino acid sequences, and

sequences annotated in Word documents; (ii) batch alignment of sequences with

MAFFT (Katoh and Standley, 2013), for which we added a codon alignment

(translation align) mode; (iii) batch optimization of ambiguously aligned regions

using Gblocks (Talavera and Castresana, 2007); (iv) batch conversion of alignment

formats (FASTA, PHYLIP, PAML, AXT and NEXUS); (v) concatenation of multiple

alignments into a single dataset and preparation of a partition file for downstream

analyses; (vi) selection of the best-fit evolutionary model and/or partitioning scheme

using ModelFinder (Kalyaanamoorthy, et al., 2017) or PartitionFinder (Lanfear, et al.,

2017); (vii) phylogeny reconstruction using IQ-TREE (maximum likelihood) (Nguyen,

et al., 2015) and/or MrBayes (Bayesian inference) (Ronquist, et al., 2012); (viii)

linking the functions from (ii) to (vii) into a workflow; (ix) annotating phylogenetic

trees in the iTOL webtool (Letunic and Bork, 2016) using datasets generated by the (i)

function; (x) comprehensive bioinformatic analysis of mitochondrial genomes

(mitogenomes); (xi) visualization and editing of sequences using a MEGA-like

sequence viewer; (xii) storing, organizing and visualizing data and results of each

analysis in the PhyloSuite workspace.

Genetic data management

PhyloSuite provides a flexible GenBank entries processing function (see

Supplementary data). GenBank files can be imported either directly, or via a list of

IDs, which PhyloSuite will automatically download from the GenBank. Almost all of

the information in the annotation section of a GenBank record can be extracted and

displayed in the GUI. Additionally, the information can be standardized in batch using

a corresponding function or edited manually in the GUI, ambiguously annotated

mitogenomic tRNA genes can be semi-automatically reannotated using ARWEN

(Laslett and Canback, 2008), and taxonomic data can be automatically retrieved from

WoRMS and NCBI Taxonomy databases. The 'extract' function allows users to

extract genes in batches, as well as generate an assortment of statistics and dataset

files (iTOL datasets). The extracted results can be used for downstream analyses

without additional manipulation. The nucleotide and amino acid sequences can be

visualized and edited in a MEGA-like explorer equipped with common functions

(reverse complement, etc.). Importantly, PhyloSuite can parse the sequence

annotations recorded in a Word document via the inbuilt 'comment' function, and

generate a GenBank file and an *.sqn file for direct submission to the GenBank. This

function provides a novel and simple way to annotate genetic sequences, which shall

benefit researchers who are not computer-savvy.

Phylogenetic analysis workflow

By allowing users to combine seven plugin programs/functions and execute them

sequentially, PhyloSuite streamlines the evolutionary phylogenetics analysis (see

Supplementary data). The standard execution order of these functions is: MAFFT,

Gblocks, Concatenation, ModelFinder or PartitionFinder2, MrBayes and/or IQ-TREE.

The results of upstream functions are directly prepared as the input for downstream

functions, so only the first function of each workflow requires an input file(s).

Functions can also be used in a non-standard order and/or separately, in which case

PhyloSuite will automatically search for available input files (results of other tools) in

the workspace. Before starting the workflow, PhyloSuite will summarize the

parameters of each function, allowing the user to check and modify them, or

autocorrect conflicting parameters, such as sequence types. Once a workflow is

finished, PhyloSuite will describe the settings of each function as well as present the

references for each plugin program in the GUI.

Bioinformatics analysis for mitogenomic data

PhyloSuite was originally designed for, and its major comparative advantages are in,

the mitochondrial genomics analyses. There is a specialized configuration available

for the extraction of mitogenomic features. In addition to gene extraction, PhyloSuite

will generate a dozen of statistics and dataset files useful for downstream analyses

(see Supplementary data). The 'itol' dataset can be used to annotate the obtained

phylogram (colorize lineages, map gene orders, etc.). The gene order file can be used

to conduct gene order analysis with CREx (Bernt, et al., 2007) or treeREx (Bernt, et

al., 2008). The tables generated include the list of mitogenomes and overall statistics,

annotation, nucleotide composition and skewness, relative synonymous codon usage

(RSCU) and amino acid usage. The RSCU figure (see Fig. 3 in Zhang, et al. (2017))

can be drawn using the RSCU table and 'Draw RSCU figure' function. The

annotation table can be used to compare genomic annotations and calculate pairwise

similarity of homologous genes with 'Compare table' function (see Table 1 in Zhang,

et al. (2018)). In the future, PhyloSuite aims to gradually extend these analyses to

other small genomes (organelles, viruses, etc.).

141 **Discussion**

PhyloSuite links the management of genetic sequence data and a series of

phylogenetic analysis tools, thereby simplifying and speeding up multi-gene based

phylogenetic analyses, from data acquisition to phylogram annotation. In summary,

highlights of PhyloSuite include: (i) a user-friendly workspace to visualize, organize,

manipulate and store sequence data and results; (ii) flexible GenBank entries

processing (standardization, reannotation, etc.); (iii) batch data processing capability

and workflow; (iv) a state of the art mitogenomic bioinformatics analysis. Although

PhyloSuite is designed primarily to allow non-computer-savvy users to drag-and-drop

and point-and-click their way through the phylogenetic analysis, experienced

scientists will also find it useful to streamline their research, store and manage results,

and increase productivity. It will especially benefit evolutionary biologists who wish

to test the effects of different datasets and analytical methods on the phylogenetic

reconstruction.

Acknowledgements

The authors would like to thank Dr. Xiao-Qin Xia for modifying the manuscript and

Mr. Cheng-En Zheng for technical assistance in the software development.

Funding

This work was supported by the National Natural Science Foundation of China

[31872604]; the Earmarked Fund for China Agriculture Research System

[CARS-45-15]; and the Major Scientific and Technological Innovation Project of

Hubei Province [2015ABA045].

Conflict of Interest: none declared.

References

Bernt, M., Merkle, D. and Middendorf, M. (2008) An algorithm for inferring
mitogenome rearrangements in a phylogenetic tree. In Nelson, C.E. and Vialette, S.,
(eds.), *Comparative Genomics, International Workshop, RECOMB-CG 2008,*
Proceedings of Lecture Notes in Bioinformatics. Springer, Berlin, Vol. 5267, pp.
143-157.
Bernt, M.*, et al.* (2007) CREx: inferring genomic rearrangements based on common

intervals. *Bioinformatics*, 23(21), 2957-2958.

Degnan, J.H. and Rosenberg, N.A. (2009) Gene tree discordance, phylogenetic
inference and the multispecies coalescent. *Trends Ecol Evol*, 24(6), 332-340.

Kalyaanamoorthy, S*., et al.* (2017) ModelFinder: fast model selection for accurate
phylogenetic estimates. *Nat Methods*, 14(6), 587-589.

Katoh, K. and Standley, D.M. (2013) MAFFT multiple sequence alignment software
version 7: improvements in performance and usability. *Molecular biology and*
evolution, 30(4), 772-780.

Lanfear, R*., et al.* (2017) PartitionFinder 2: new methods for selecting partitioned
models of evolution for molecular and morphological phylogenetic analyses. *Mol Biol*
Evol, 34(3), 772-773.

Laslett, D. and Canback, B. (2008) ARWEN: a program to detect tRNA genes in
metazoan mitochondrial nucleotide sequences. *Bioinformatics*, 24(2), 172-175.

Letunic, I. and Bork, P. (2016) Interactive tree of life (iTOL) v3: an online tool for the
display and annotation of phylogenetic and other trees. *Nucleic Acids Res*, 44(W1),
W242-245.

Metzker, M.L. (2009) Sequencing technologies — the next generation. *Nature*
Reviews Genetics, 11(1), 31-46.

Nguyen, L.T*., et al.* (2015) IQ-TREE: a fast and effective stochastic algorithm for
estimating maximum-likelihood phylogenies. *Mol Biol Evol*, 32(1), 268-274.

Rivera-Rivera, C.J. and Montoya-Burgos, J.I. (2016) LS(3): A Method for Improving
Phylogenomic Inferences When Evolutionary Rates Are Heterogeneous among Taxa.
Mol Biol Evol, 33(6), 1625-1634.

Ronquist, F*., et al.* (2012) MrBayes 3.2: efficient Bayesian phylogenetic inference and
model choice across a large model space. *Systematic biology*, 61(3), 539-542.

Smith, D.R. (2015) Buying in to bioinformatics: an introduction to commercial
sequence analysis software. *Brief Bioinform*, 16(4), 700-709.

Talavera, G. and Castresana, J. (2007) Improvement of phylogenies after removing
divergent and ambiguously aligned blocks from protein sequence alignments.
Systematic Biology, 56(4), 564-577.

Zhang, D*., et al.* (2018) Three new Diplozoidae mitogenomes expose unusual
compositional biases within the Monogenea class: implications for phylogenetic
studies. *BMC Evol Biol*, 18(1), 133.

Zhang, D*., et al.* (2017) Sequencing of the complete mitochondrial genome of a
fish-parasitic flatworm *Paratetraonchoides inermis* (Platyhelminthes: Monogenea):
tRNA gene arrangement reshuffling and implications for phylogeny. *Parasites &*
Vectors, 10(1), 462.

Supplementary Information

We merged our two older beta tools, MitoTool

(https://github.com/dongzhang0725/MitoTool) and BioSuite

(https://github.com/dongzhang0725/BioSuite), into a single plugin-based software

program designed to streamline the multi-gene evolutionary phylogenetic analysis -

PhyloSuite (Fig. S1).

Fig. S1. The workflow diagram of PhyloSuite.

Comparison with extant software programs

Although the extant software programs possess some of the abilities of PhyloSuite, none of them incorporate all functions necessary for a streamlined multi-gene phylogenetic analysis, from data retrieval to the phylogenetic tree annotation (click here to access the attached Table S1). For example, FeatureExtract (Wernersson, 2005) and Geneious (Kearse, et al., 2012) can extract the annotations from GenBank files, but downstream analysis is not fully automated, so some manual data handling is required, especially for multi-gene datasets. Armadillo (Lord, et al., 2012), EPoS (Griebel, et al., 2008) and MEGA (Kumar, et al., 2016) do not possess the batch processing capability, which is indispensable for multi-gene datasets. Additionally, data partitioning and best-fit partitioning scheme estimation are also pivotal for multi-gene dataset-based phylogenetic analyses (Blair and Murphy, 2011; Lanfear, et al., 2012), but most other software programs lack this function, including Geneious, MEGA, Galaxy Workflow (Oakley, et al., 2014), etc. Although, MEGA and EPoS possess the ability to use the output of one tool directly as the input for another tool, they cannot link several functions into a single run (workflow). Probably the closest to meeting the described requirements is Geneious, but this is a commercial bioinformatics software, so it may not be an ideal option (i.e. too expensive) for all scientists, especially for students.

Functions and capabilities

Taking a recently published mitogenomic paper (Zhu, et al., 2018) as an example, using the 'extract' function user can quickly conduct most of the analyses reported in

that paper, and generate similar tables and figures: (i) mitogenome list and overall

statistics table (Table 1 in Zhu et al.), (ii) annotation table (Table 2), (iii) nucleotide

composition and skewness table (Table 3), (iv) relative synonymous codon usage

(RSCU) table and figure (Fig. 2B), (v) amino acid usage statistics file used to draw

Fig. 2A, and (vi) reconstruct and annotate (in iTOL) phylogenetic trees (Fig. 5) using

the extracted genes. In comparison, most of the tables in that paper were made

manually by the author, which is time-consuming, tedious and error-prone. Beyond

these, several additional analyses are available: (i) gene order file is generated, which

can be used to map gene orders of mitogenomes onto the phylograms in iTOL (Fig.

S2, also see Fig. 6 in Zhang, et al. (2018)), (ii) statistics for individual genes,

including size, start and terminal codons, base composition and skews (click here to

access the attached Table S2), (iii) general statistics table, which can be used to draw

skewness and base content figure (Fig. S3, also see Fig. 1 in Zhang, et al. (2018)), (iv)

comparison of genomic annotations and pairwise similarity calculation for

homologous genes, such as Table 1 in Zhang, et al. (2018).

Fig. S2 Mapping gene orders of monogenean mitogenomes onto the phylogenetic

tree.

Fig. S3 Skewness and base content of some flatworm mitogenomes.

References

Blair, C. and Murphy, R.W. (2011) Recent trends in molecular phylogenetic analysis:

where to next? *J Hered*, 102(1), 130-138.

Griebel, T., Brinkmeyer, M. and Bocker, S. (2008) EPoS: a modular software

framework for phylogenetic analysis. *Bioinformatics*, 24(20), 2399-2400.

Kearse, M.*, et al.* (2012) Geneious Basic: an integrated and extendable desktop

software platform for the organization and analysis of sequence data. *Bioinformatics*,

28(12), 1647-1649.

Kumar, S., Stecher, G. and Tamura, K. (2016) MEGA7: Molecular Evolutionary

Genetics Analysis Version 7.0 for Bigger Datasets. *Mol Biol Evol*, 33(7), 1870-1874.

Lanfear, R.*, et al.* (2012) PartitionFinder: combined selection of partitioning schemes

and substitution models for phylogenetic analyses. *Molecular biology and evolution*,

29(6), 1695-1701.

Lord, E.*, et al.* (2012) Armadillo 1.1: an original workflow platform for designing and

conducting phylogenetic analysis and simulations. *PLoS One*, 7(1), e29903.

Oakley, T.H.*, et al.* (2014) Osiris: accessible and reproducible phylogenetic and

phylogenomic analyses within the Galaxy workflow management system. *BMC*

Bioinformatics, 15(1), 230.

Wernersson, R. (2005) FeatureExtract--extraction of sequence annotation made easy.

Nucleic Acids Res, 33(Web Server issue), W567-569.

Zhang, D.*, et al.* (2018) Three new Diplozoidae mitogenomes expose unusual

compositional biases within the Monogenea class: implications for phylogenetic

studies. *BMC Evol Biol*, 18(1), 133.

Zhu, H.F.*, et al.* (2018) Complete mitochodrial genome of the crab spider Ebrechtella

tricuspidata (Araneae: Thomisidae): A novel tRNA rearrangement and phylogenetic

implications for Araneae. *Genomics*.

295