Genome analysis

Improved representation of sequence Bloom trees

Robert S. Harris [1] and Paul Medvedev [1,2,3,4,*]

[1] Department of Biology, The Pennsylvania State University, USA
[2] Department of Computer Science and Engineering, The Pennsylvania State University
[3] Department of Biochemistry and Molecular Biology, The Pennsylvania State University
[4] Center for Computational Biology and Bioinformatics, The Pennsylvania State University

*To whom correspondence should be addressed.

Abstract

Algorithmic solutions to index and search biological databases are a fundamental part of bioinformatics, providing underlying components to many end-user tools. Inexpensive next generation sequencing has filled publicly available databases such as the Sequence Read Archive beyond the capacity of traditional indexing methods. Recently, the Sequence Bloom Tree (SBT) and its derivatives were proposed as a way to efficiently index such data for queries about transcript presence. We build on the SBT framework to construct the HowDe-SBT data structure, which uses a novel partitioning of information to reduce the construction and query time as well as the size of the index. We evaluate HowDe-SBT by both proving theoretical bounds on its performance and using real RNA-seq data. Compared to previous SBT methods, HowDe-SBT can construct the index in less than 36% the time, and with 39% less space, and can answer small-batch queries at least five times faster. HowDe-SBT is available as a free open source program on `https://github.com/medvedevgroup/HowDeSBT`.

1 Introduction

Public read databases such as the Sequence Read Archive (SRA) contain a treasure trove of biological information and have the potential to become a ubiquitous community resource by enabling broad exploratory analyses. For example, given a long nucleotide sequence, which experiments in the database contain reads matching it? More concretely, which human RNA-seq experiments from the SRA contain a transcript of interest? Unfortunately, there does not exist a way for today's biologist to answer such a question in a reasonable amount of time. Tapping into the potential of these databases is hampered by scalability challenges and will require novel approaches from the algorithm community.

The computational problem falls into the widely-studied category of string alignment problems (Gusfield, 1997; Mäkinen *et al.*, 2015). However, it differs in several regards. The strings to be matched are rarely present in the database in their entirety. Instead, sequencers produce many highly fragmented copies of the desired string, each subjected to potential sequencing error. Furthermore, the scale of the databases makes traditional sequence alignment methods, such as SRA-BLAST (Camacho *et al.*, 2009), inadequate (Solomon and Kingsford, 2016).

The seminal paper of Solomon and Kingsford (2016) demonstrated that the above transcript question can be simplified to a question of approximate k-mer membership. Each experiment can be viewed as a collection of its constituent k-mers, and the biological question can be answered by finding all experiments which contain a high percentage of the k-mers in the query transcript. They demonstrated that this approach, even if only done approximately, is a good proxy for the answer to the transcript question. It also lends itself to answering a more broad range of questions, such as SNP presence, viral contamination, or gene fusion (Bradley *et al.*, 2017). Their work has opened the door to a slew of data structures implementing various k-mer indices, roughly falling into two categories.

The first category of approaches are based on the Bloofi (Crainiceanu and Lemire, 2015) data structure. Each experiment's k-mers are first stored in a Bloom filter (Bloom, 1970), an efficient but lossy data structure for storing sets. The experiments are then grouped into a hierarchical structure (i.e. tree) based on their similarity, where each leaf corresponds to the k-mers in an experiment. Each internal node represents the union of the k-mers in its descendants. The tree allows an efficient search for experiments matching a given k-mer profile by pruning non-promising branches. Bloofi was first adapted to the sequencing context by the Sequence Bloom Tree (SBT) data structure (Solomon and Kingsford, 2016), and further work improved the representation of the internal nodes (Sun *et al.*, 2017;

Solomon and Kingsford, 2017) and the clustering of the tree topology (Sun *et al.*, 2017).

The SBT approaches aggregate k-mer information at the level of an experiment. The second category of approaches aggregate experiment information at the level of the k-mers. In such an approach, each query k-mer is independently looked up in an index to retrieve information about which experiments contain the k-mer (Holley *et al.*, 2015; Muggli *et al.*, 2017; Almodaresi *et al.*, 2017; Mustafa *et al.*, 2018; Pandey *et al.*, 2018; Yu *et al.*, 2018; Bradley *et al.*, 2017; Almodaresi *et al.*, 2018). In this context, experiments are referred to as colors, and such a data structure is sometimes called a colored de Bruijn graph. These approaches are complementary to the SBT and the best choice depends on the particular properties of the queries and the dataset, such as the sharedness of k-mers between experiments.

In this paper, we develop an alternative way to partition and organize the data in an SBT such that it becomes much more compressible and faster to query. Our method is called HowDe-SBT. We prove theoretical bounds on the performance of HowDe-SBT and also demonstrate its performance advantages on real data by comparing it to the previous SBT methods and to Mantis, a representative from the second category of indexing methods. Finally, we propose and explore a culling procedure to remove non-informative nodes from the tree and create a non-binary forest (Supplementary Section 1).

2 Preliminaries

Let x and y be two bitvectors of the same length. A bitvector can be viewed as a set of the positions that are set to 1, and in this view, the set union (intersection, respectively) of x and y is equivalent to bitwise OR (AND, respectively). We write the bitwise AND between x and y as $x \cap y$, and the bitwise OR as $x \cup y$. The bitwise NOT operation on x is written as $\overline{x}$. The set difference of x and y is written as $x \setminus y$ and can be defined as $x \setminus y = x \cap \overline{y}$. The empty set is represented as a bitvector of zeros. The universal set, denoted by $\mathscr{E}$, is represented as a bitvector of ones. Given that the percentage of 1s in x is p, the *empirical entropy* of x is defined as $H(p) = -(p \log_2 p + (1 - p) \log_2(1 - p))$.

A *Bloom filter* (BF) is a bitvector of length b, together with q hash functions, $h_1, \ldots, h_q$, where b and q are parameters. Each hash function maps a k-mer to an integer between 0 and $b - 1$. To add a k-mer x to the set, we set the position $h_i(x)$ to 1, for all i. To check if a k-mer x is in the set, we check that the position $h_i(x)$ is 1, for all i. In this paper, we assume that the number of hash functions is 1.

Next, consider a rooted binary tree T. The parent of a non-root node u is denoted as $parent(u)$, and the set of all the leaves of the subtree rooted at a node u is denoted by $leaves(u)$. Let $children(u)$ refer to the child nodes of a non-leaf node u. Define $ancestors(u)$ as $\emptyset$ if node u is the root, and $parent(u) \cup ancestors(parent(u))$ otherwise. That is, $ancestors(u)$ are all the nodes on the path from u to the root, except u itself.

Suppose that there is a Bloom filter associated with each leaf of T. Then, define $B_\cup(u)$ for a leaf node u as its associated BF and $B_\cup(u)$ for an internal node as $\bigcup_{i \in leaves(u)} B_\cup(i)$. Note that $B_\cup(u)$ of an internal node u can be equivalently defined as $B_\cup(u) = \bigcup_{i \in children(u)} B_\cup(i)$. Define the intersection of leaf BFs in the subtree rooted at a node u as $B_\cap(u) = \bigcap_{i \in leaves(u)} B_\cup(i)$. Equivalently, $B_\cap(u) = \bigcap_{i \in children(u)} B_\cup(i)$.

In this paper, we solve the following problem:

Database input: A database $D = \{D_1, \ldots, D_n\}$, where each D_i is a BF of size b that represents experiment i.

Query input: A multi-set of k-mers Q (called the query), and a threshold

$0 < \theta \leq 1$.

Query output: The set of experiments that contain at least a fraction θ of the query k-mers, i.e. $\{i \ : \ |\{x \in Q \ : \ x \text{ exists in } D_i\}| \geq \theta \cdot |Q|\}$

Note that in this formulation, we assume that D (along with parameter b) is already given to us. How to choose b and construct D from raw reads was already described in Solomon and Kingsford (2016).

3 Representation and querying

Let us assume we are given a binary tree T and a bijection between the leaves and the experiment BFs in our database. We refer to this as a *topology*, to underscore that the internal nodes are not yet assigned any bitvectors. We now show how to assign these bitvectors — B_{det} and B_{how} — and how they can be used to answer a query.

Conceptually, each node u represents the set of experiment BFs corresponding to $leaves(u)$. We observe that some positions are *determined* in u: they have the same value in each of $leaves(u)$. Moreover, for the positions that are determined, we know exactly *how* they are determined. Formally, we define

$$B_{\text{det}}(u) \triangleq B_\cap(u) \cup \overline{B_\cup(u)} \qquad B_{\text{how}}(u) \triangleq B_\cap(u) \qquad (1)$$

Note that B_{how} is intended to only be informative for those positions that are in B_{det}.

Having B_{det} and B_{how} at each node can enable the following efficient query search; it is essentially the same strategy as in Sun *et al.* (2017) and Solomon and Kingsford (2017), but adapted to the HowDe-SBT tree. When we receive the set of query k-mers Q, we hash each one to determine the list of BF positions corresponding to Q. We call this list the *unresolved* positions. We also maintain two counters: the number of positions that have been determined to be 1 (*present*), and the number of positions determined to be 0 (*absent*). These counters are both initially 0. We then proceed in a recursive manner, starting at the root of the tree. When comparing Q against a node u, each unresolved position that is 1 in $B_{\text{det}}(u)$ is removed from the unresolved list, and the corresponding bit in $B_{\text{how}}(u)$ determines which counter, present or absent, is incremented. If the present counter is at least $\theta|Q|$, we add $leaves(u)$ to the list of matches and terminate the search of u's subtree. If the absent counter exceeds $(1 - \theta)|Q|$, Q cannot match any of the descendant leaves so we terminate the search of u's subtree. If neither of these holds, we recursively pass the two counters and the list of unresolved positions down to u's children. When we reach a leaf, the query unresolved list will become empty because B_{det} is all ones at a leaf, and the algorithm will necessarily terminate. Figure 1 shows an example of a tree and a query execution.

We observe that some bit positions will never be looked at during a search, as follows. First, if a position is determined at a node v, it will be removed from the query unresolved list (if it was even there) after node v is processed. We say that this position is inactive in v's descendents, since a search will never query that position. Formally, a position is *active in $B_{det}(u)$* if it is not determined at its parent (equivalently, at any of its ancestors). Second, the only positions that are queried in $B_{\text{how}}(u)$ are those that are active and set to one in $B_{\text{det}}(u)$. We say these positions are *active in $B_{how}(u)$*. Formally, we can define

$$B_{\text{det}}^{\text{active}}(u) \triangleq \begin{cases} \overline{B_{\text{det}}(parent(u))} & \text{if } u \text{ has a parent} \\ \mathscr{E} & \text{if } u \text{ is the root} \end{cases} \qquad (2)$$

$$B_{\text{how}}^{\text{active}}(u) \triangleq B_{\text{det}}(u) \cap B_{\text{det}}^{\text{active}}(u) \qquad (3)$$

Bits that are inactive are wasteful, since they take space to store but are never queried. We remove these bits from the bitvectors, as in Solomon and

Fig. 1. Example HowDe-SBT on $D = \{1110\,0011\,1000\,0000,\ 1110\,1111\,0000\,0000,\ 1111\,1100\,0000\,0000,\ 1001\,0001\,1100\,1000,\ 1001\,0000\,1111\,0000,\ 1001\,0000\,0000\,1111\}$. Each box represents a node of the tree, with leaves shown in blue and internal nodes in gray. For conciseness, the boxes show B_{det}, B_{how}, $B_{\cup}$, and $B_{\cap}$, but do not show $B_{\text{det}}^{\text{sqz}}$ and $B_{\text{how}}^{\text{sqz}}$. The yellow boxes demonstrate the processing of an example nine k-mer query with $\theta = 0.5$. The initial query is shown at the top, with the bits corresponding to the query k-mers shown with a U. The query flows down the tree. The query state presented to a node is Q_{in} and the result from the node is Q_{out}. Some bits are resolved as either present (P) or absent (A) across the subtree. Such bits are counted in the corresponding totals and removed from further processing (hyphen) in descendants. Processing along a branch halts if either total reaches the threshold needed to determine the outcome — which in this case is 5. In this example, Q matches the first two experiments.

Kingsford (2017). Formally, let $B_{\text{det}}^{\text{sqz}}(u)$ be $B_{\text{det}}(u)$ with all the inactive bits removed, and we let $B_{\text{how}}^{\text{sqz}}(u)$ be $B_{\text{how}}(u)$ with all the inactive bits removed. $B_{\text{det}}^{\text{sqz}}$ and $B_{\text{how}}^{\text{sqz}}$ are further compressed with the general purpose RRR compression algorithm (Raman *et al.*, 2007), and these compressed bitvectors are what, in the end, constitute our index. We note that since the removal of inactive bits changes the indices into the bitvectors, the query algorithm has to be modified accordingly by using rank and select. Since this is done in essentially the same way as in Solomon and Kingsford (2017), we omit the details here.

4 Construction algorithm

In this section, we describe how to build the tree from D. Initially, we determine a tree topology using the clustering algorithm of Sun *et al.* (2017) as a black-box. We will now describe the algorithm to compute $B_{\text{det}}^{\text{sqz}}$ and $B_{\text{how}}^{\text{sqz}}$ for this topology and prove its correctness. Our algorithm makes a pass through the tree using a postorder traversal. At each node u, it 1) computes B_{det} and B_{how} of u, and 2) computes $B_{\text{det}}^{\text{sqz}}$ and $B_{\text{how}}^{\text{sqz}}$ of each of its children using their B_{det} and B_{how}. As the final step, $B_{\text{det}}^{\text{sqz}}$ and $B_{\text{how}}^{\text{sqz}}$ are computed for the root node.

The base case of the algorithm is, for each leaf u, to set $B_{\text{det}}(u) \leftarrow \mathscr{E}$ and $B_{\text{how}}(u) \leftarrow B_{\cup}(u)$. For an internal node u, we first construct $B_{\cap}(u)$ and $B_{\cup}(u)$ using the operations:

$$B_{\cap}(u) \leftarrow \bigcap_{c\in children(u)} B_{\text{how}}(c)$$

$$B_{\cup}(u) \leftarrow \bigcup_{c\in children(u)} \left(\overline{B_{\text{det}}(c)} \cup B_{\text{how}}(c) \right)$$

Then, $B_{\text{det}}(u)$ and $B_{\text{how}}(u)$ are constructed by directly applying their definitions (Equation (1)). Once $B_{\text{det}}(u)$ and $B_{\text{how}}(u)$ have been computed, we compute the active bits in $B_{\text{det}}(c)$ and $B_{\text{how}}(c)$, for each child c of u:

$$B_{\text{det}}^{\text{active}}(c) \leftarrow \overline{B_{\text{det}}(u)} \qquad B_{\text{how}}^{\text{active}}(c) \leftarrow B_{\text{det}}(c) \cap \overline{B_{\text{det}}(u)}$$

Next, we make a linear scan through $B_{\text{det}}(c)$ and $B_{\text{how}}(c)$ and use $B_{\text{det}}^{\text{active}}(c)$ and $B_{\text{how}}^{\text{active}}(c)$ as a mask to remove all the inactive bits, thus generating $B_{\text{det}}^{\text{sqz}}(c)$ and $B_{\text{how}}^{\text{sqz}}(c)$. These are finally RRR compressed and written to disk.

After the postorder traversal completes, we make the final step to compute the $B_{\text{det}}^{\text{sqz}}$ and $B_{\text{how}}^{\text{sqz}}$ for the root u. It is essentially the same process

as for the internal nodes, but the active bits are set as:

$$B_{\text{det}}^{\text{active}}(u) \leftarrow \mathscr{E} \qquad\qquad B_{\text{how}}^{\text{active}}(u) \leftarrow B_{\text{det}}(u)$$

$B_{\text{det}}^{\text{sqz}}$ and $B_{\text{how}}^{\text{sqz}}$ are then computed as before, removing the inactive bits during a linear scan followed by RRR compression.

We note that the $B_{\cup}$, $B_{\cap}$, B_{det}, B_{how}, $B_{\text{det}}^{\text{active}}$, and $B_{\text{how}}^{\text{active}}$ bitvectors are not stored after construction is complete. To save memory, these can be discarded right after their use; however, it is necessary to save some of the B_{det} and B_{how} vectors. Specifically, we must save $B_{\text{det}}(u)$ and $B_{\text{how}}(u)$ between the visit to u and the visit to u's parent. During this interval they can be saved in memory or, in order to save memory, they can be written to disk and reloaded to memory as needed. When u's parent is visited, $B_{\text{det}}^{\text{sqz}}(u)$ and $B_{\text{how}}^{\text{sqz}}(u)$ are computed and $B_{\text{det}}(u)$ and $B_{\text{how}}(u)$ are no longer needed.

The following theorem shows that our algorithm is correct and that its runtime is linear in the total size of the input bitvectors.

Theorem 1. *Given a database of n Bloom filters, each of size b, and a tree topology, our method constructs B_{det}^{sqz} and B_{how}^{sqz} for all nodes in $\mathcal{O}(nb)$ time.*

Proof. We first prove the runtime. Our bitvector construction algorithm operates on each node twice — once when the node is visited, and a second time to finish the node when its parent is visited. (The root is a special case — its finishing stage occurs at the end of the algorithm.) At each stage, it performs a constant number of bitwise operations which each takes $\mathcal{O}(b)$ time. Similarly, the linear scan to remove inactive bits can be done in $\mathcal{O}(b)$ time by simply copying the active bits to a new vector.

Next, we prove correctness. We will need the following technical lemma:

Lemma 1. *The following properties are true:*

$$B_{\cap}(u) = B_{\cup}(u) \qquad\qquad \textit{if } u \textit{ is a leaf} \qquad (4)$$

$$B_{\cup}(u) = \overline{B_{det}(u)} \cup B_{how}(u) \qquad\qquad (5)$$

Proof. Equation (4) trivially follows from the definition of $B_{\cap}$. For Equation (5), first observe that $B_{\cap}(u)$ and $\overline{B_{\cup}(u)}$ are disjoint (since $B_{\cap}(u) \subseteq B_{\cup}(u)$). Combine this with the definition of $B_{\text{det}}(u)$, and we get $\overline{B_{\cup}(u)} = B_{\text{det}}(u) \setminus B_{\cap}(u) = B_{\text{det}}(u) \cap \overline{B_{\cap}(u)}$. Negating both sides, we get $B_{\cup}(u) = \overline{B_{\text{det}}(u)} \cup B_{\cap}(u) = \overline{B_{\text{det}}(u)} \cup B_{\text{how}}(u)$ □

We first show the correctness of computing B_{det} and B_{how} when we visit u. For a leaf u,

$$\begin{aligned} B_{\text{det}}(u) &= B_{\cap}(u) \cup \overline{B_{\cup}(u)} & \text{(by definition)} \\ &= B_{\cup}(u) \cup \overline{B_{\cup}(u)} & \text{(from Equation (4))} \\ &= \mathscr{E} \\ B_{\text{how}}(u) &= B_{\cap}(u) & \text{(by definition)} \\ &= B_{\cup}(u) & \text{(from Equation (4))} \end{aligned}$$

If u is an internal node, then it is enough to show that $B_{\cap}$ and $B_{\cup}$ are computed correctly.

$$\begin{aligned} B_{\cap}(u) &= \bigcap_{c \in children(u)} B_{\cap}(c) & \text{(by definition)} \\ &= \bigcap_{c \in children(u)} B_{\text{how}}(c) & \text{(from def. of } B_{\text{how}}) \\ B_{\cup}(u) &= \bigcup_{c \in children(u)} B_{\cup}(c) & \text{(by definition)} \\ &= \bigcup_{c \in children(u)} \left(\overline{B_{\text{det}}(c)} \cup B_{\text{how}}(c) \right) & \text{(from Equation (5))} \end{aligned}$$

To show the correctness of computing $B_{\text{det}}^{\text{active}}(c)$ and $B_{\text{how}}^{\text{active}}(c)$, recall their definitions from Section 3. It is straightforward to see that our algorithm computes $B_{\text{det}}^{\text{active}}$ and $B_{\text{how}}^{\text{active}}$ exactly according to these definitions, both for the case of children and for the case of the root. Finally, the algorithm correctly computes $B_{\text{det}}^{\text{sqz}}$ and $B_{\text{how}}^{\text{sqz}}$ because it simply applies their definitions. □

We note that the complexity of constructing the tree topology was not studied in Sun *et al.* (2017), but the obvious implementation would take $\Omega(n^2)$ time. Though it takes negligible time on currently tested datasets, it may become the bottleneck in the future if n increases by several orders of magnitude.

5 Analysis of savings compared to previous work

In this section, we show the connection of our representation to previous approaches and analyze the theoretical improvements. The structuring of our bitvectors can be viewed as an extension of the approach in Solomon and Kingsford (2017), which is called SSBT. The SSBT representation approach subsumes the representation of Sun *et al.* (2017), so we focus our comparison on SSBT. Briefly, SSBT uses the same approach of having a tree where the bitvectors at a node u represent, for each bit position x, whether x is 1 in all, none, or some of the $leaves(u)$. It also marks a bit position as inactive if it can never be reached during a query. The SSBT bitvectors are called u_{sim} and u_{rem}. The topology of the SSBT is computed differently from HowDe-SBT, and, as was shown in Sun *et al.* (2017), it leads to a much less compressible tree. However, since we want to focus on the improvements solely due to bitvector representation, we will assume that the SSBT is constructed using the same topology as HowDe-SBT. In this case, the relationship of SSBT to HowDe-SBT can be summarized as a one-to-one relationship between all possible bitvector states, shown in Figure 2.

The intuition which guided our design of HowDe-SBT, relative to SSBT, was 1) minimizing the number of active positions and 1 bits (to improve space), and 2) minimizing the number of bit lookups performed during a query (to improve speed). To try to theoretically quantify this improvement, we derive a savings rate per bit position x, in terms of 1) n_x, the number of nodes where x is active in B_{det}, and 2) s_x, the percentage of nodes where x is active in B_{how} that have a 1.

Let T be the tree topology. We are not able to directly derive the savings rate for T after RRR compression, but we instead rely on Shannon's information compression bound. For a bitvector a that is generated by a 0^{th} order Markov model and that has a fraction p of 1s, the best that a lossless compression algorithm can achieve is $|a|H(p)$ bits. While in practice this bound might be beaten because our bitvectors are not generated by a 0^{th} order Markov chain, it is still a useful proxy for the compressability. Let I_x^{howde} (respectively, I_x^{ssbt}) denote Shannon's information bound for

Fig. 2. The left tables show the correspondence between the possible states of SSBT and HowDe-SBT bitvectors. A dash represents an inactive bit. The tree is an example of a bit position x and its values in both representations. In this example, $n_x = 5$, $\ell_x = 3$, and $s_x = 1/3$. The nodes of T_x have a double border.

storing all the bit values at x in T using HowDe-SBT's representation (respectively, SSBT's representation).

Theorem 2. *Let $0 \leq x < b$ be a bit position. Then,*

$$I_x^{howde} = \frac{3n_x + 1}{2} H\left(\frac{(n_x + 1)(1 + s_x)}{3n_x + 1}\right)$$

$$I_x^{ssbt} = \frac{n_x(4 - s_x) + 1}{2} H\left(\frac{n_x(1 + s_x) + s_x - 1}{n_x(4 - s_x) + 1}\right)$$

Proof. Let T_x be the subtree of T containing all nodes where x is active in B_{det}. Observe that T_x is indeed a subtree and it contains exactly the nodes where x is determined and their ancestors. The total number of nodes in T_x is n_x. Let ℓ_x be the number of leaves of T_x. Note that since every internal node of T has two children, $\ell_x = (n_x + 1)/2$, for all x. Note that the nodes at which the B_{how} bits are active are exactly the leaves of T_x, and s_x is the percentage of these that are 1.

Now, the nodes for which x is active in B_{det} are exactly the nodes of T_x, and thus x contributes n_x active B_{det} bits. The only time B_{how} is active at x is when B_{det} is set to 1, which is exactly at the leaves of T_x. Hence, the total number of active bits is $n_x + \ell_x = (3n_x + 1)/2$. Next, we count the number of active bits that are set to 1. The B_{det} bits set to one are exactly at the leaves of T_x. There are ℓ_x active B_{how} bits, of which a fraction s_x are set to one. Hence, the number of active bits set to one is $\ell_x(1 + s_x) = (n_x + 1)(1 + s_x)/2$.

To prove the statement about I_x^{ssbt}, we use the equivalences in Figure 2 as a guide. The number of active positions in the u_{sim} vectors is n_x and in the u_{rem} vectors is $n_x - s_x\ell_x$. In sum, the number of active positions is $2n_x - s_x\ell_x = \frac{n_x(4 - s_x) + 1}{2}$. The number of active bits in u_{sim} that are set to 1 is $\ell_x s_x$ and the number of active bits in u_{rem} that are set to 1 is $n_x - \ell_x$. Hence the number of 1 bits in S is $n_x - \ell_x(1 - s_x) = \frac{n_x(1 + s_x) + s_x - 1}{2}$. □

Theorem 3. *Suppose both the SSBT and HowDe-SBT are built from the same tree topology T. Then the number of bit lookups necessary to resolve a bit position x is $(3n_x + 1)/2$ in HowDe-SBT, and $(n_x(4 - s_x) - s_x)/2$ in SSBT.*

Proof. Consider HowDe-SBT. For every internal node of T_x, we only make one lookup to B_{det}, resulting in $n_x - \ell_x$ lookups. At the leaves of T_x, we must also look at B_{how}, resulting in $2\ell_x$ lookups. The total number of lookups is then $n_x + \ell_x = (3n_x + 1)/2$. For SSBT, we must always check both u_{sim} and u_{rem} at every node, with one exception: at a leaf of T_x, we do not need to check u_{rem} if u_{sim} is 1. Hence, the number of lookups is $2n_x - \ell_x s_x = (n_x(4 - s_x) - s_x)/2$. □

We can measure the percent improvement in the space bound as $\Delta I_x = (I_x^{ssbt} - I_x^{howde})/I_x^{ssbt}$, shown in Figure 3(a). The curves behave differently for different values of s_x, with a change in concavity between $s_x = 0.75$ and $s_x = 0.5$. In the limit, ΔI_x approaches between 9% and 14% for

(a)   (b)

Fig. 3. (a) ΔI_x as a function of n_x, for various values of s_x. (b) The distributions of and dependencies between s_x and n_x on the real data. We use a random subsample of 1 mil bit positions for the plot, but omit those positions that are determined at the root (i.e. $n_x = 1$). These make up 15% of all values, and they all have $s_x = 0$. Each of the remaining positions are shown as a gray dot in the background. The s_x values are binned and the distribution of n_x within each bin is shown as a box plot. On the top (respectively, right) of the plot is the histogram of s_x (respectively, n_x).

$s_x \leq 0.75$. The percentage improvement in the number of lookups is $1 - \frac{3n_x + 1}{(4 - s_x)n_x - s_x}$, which in the limit goes to $\frac{1 - s_x}{4 - s_x}$. The improvement in lookups is thus between 0 (for $s_x = 1$) and 25% (for $s_x = 0$); for $s_x = 0.5$, it is 14%.

In large scale applications, our theoretical analysis can be simplified by assuming that n_x goes to the limit. However, HowDe-SBT can be applied in different settings, and some of these setting (like a private patient cohort) may in fact not be very large. Our detailed analysis can be used to determine at which point a dataset is large enough for the asymptotic effects to kick in; e.g. Figure 3(a) indicates that the space savings reaches a stable point roughly at $n_x = 50$.

We caution, however, that our analysis does not automatically translate to total improvements when all the positions are considered jointly. The total data structure size depends a lot on the structure of the input. That is reflected by the distribution of n_x and s_x in the real data, whether or not they are correlated, the entropy of all the bits together, rather than separated by position, and the higher-order entropy of the bitvectors. These effects can be analyzed using real data, which we do in the next section.

6 Results

6.1 Experimental setup

To evaluate HowDe-SBT, we compared it against three other tools. The first are its two predecessors, AllSome-SBT (Sun *et al.*, 2017) and SSBT (Solomon and Kingsford, 2017). The third is Mantis (Pandey *et al.*, 2018), a representative from the second category of approaches to k-mer indexing, which was previously shown to outperform SBT approaches in some cases (Pandey *et al.*, 2018). All experiments were run on an Intel Xeon CPU with 512 GB of RAM and 64 cores (at 2.10 GHz). Our tool is open source and available for free through `https://github.com/medvedevgroup/HowDeSBT`. All details about how the tools were run, including parameters, together with datasets needed to reproduce our results, are available on `https://github.com/medvedevgroup/HowDeSBT/tree/master/reproduce`.

We used the same data for evaluation as Solomon and Kingsford (2016), except that we removed experiments that did not have reads longer than k. This contained 2,585 human RNA-seq runs from blood, brain, and breast tissues, compromising all relevant human RNA-seq datasets in the SRA at the time of Solomon and Kingsford (2016). For each file, we filtered out any k-mers that occurred less than than a file-dependent threshold. We used the thresholds from Pandey *et al.* (2018), since we were unable to successfully run Mantis for thresholds inferred from Solomon and Kingsford (2016). We used $k = 20$, as in previous work. For the SBT approaches, we used a Bloom filter size of $b = 2 \cdot 10^9$, and k-mer counting was done using Jellyfish (Marçais and Kingsford, 2011), as in previous work. For Mantis, we used slot counts estimated as per section 4.1 of Pandey *et al.* (2018).

To study query performance, we created four types of queries: a single transcript, a batch of ten transcripts, a batch of 100, and a batch of 1000. Transcripts were picked arbitrarily from Gencode (ver. 25) transcripts that are at least k nt long. We created 100, 10, 3, and 3 replicates for each type of query, respectively. We include batches of multiple transcripts in our tests because SBT performance is known to depend on batch size (Solomon and Kingsford, 2016). We also test the effect of having a cold or warm cache on the query speed. For the test of a cold cache, we cleared the cache prior to each query. For the warm cache test, we ran each query two consecutive times, and then reported the run time for the second run.

Table 1. File sizes (in GiB) and build times. The intermediate space refers to the initial experiment Bloom filters for the SBT approaches and to the Squeakr files for Mantis. The construction time is the time to build the index from either the BFs or Squeakr files, and does not including k-mer counting. All times shows are on one processor.

	HowDe-SBT	AllSome-SBT	SSBT	Mantis
construction time	9h	25h	57h	22h
intermediate space	602	602	602	3,524
index size	14	142	23	32

6.2 Performance comparison

Table 1 shows the time and space taken to construct the index. The index could be created in less than 36% of the time and with 39% less space for HowDe-SBT than for all other approaches. One downside of Mantis compared to SBT methods is that it requires 5x the intermediate space (> 3 TB). The faster construction time of HowDe-SBT over AllSome-SBT was due a combination of having to handle much smaller bitvectors during construction (as reflected by the smaller index size) and software engineering improvements. Otherwise, the construction algorithms of the two methods only differ by the specific bitvector operations applied during the tree traversal.

It is important to note that the construction times in Table 1 do not include the pre-processing time of converting the SRA read files to the initial experiment Bloom filters (for SBT approaches) or to Squeakr files (for Mantis). This is a time-consuming process, which took us several days using multiple threads. We did not obtain reliable timing results since we did the conversion on the fly while streaming the data from the SRA over a network connection.

Table 2 show the query speed for all tools. On the cold cache, HowDe-SBT was faster than other SBT approaches, with over a 5x speedup on single-transcript batches. HowDe-SBT is more than 9 times faster than Mantis on single-transcript batches, but is slower for hundred-transcript and thousand-transcript batches, by 3x and 8x, respectively. Warming the cache prior to querying led to improved query times for all tools, but their relative performance remained similar. Peak RAM usage was < 1.3 GiB for all batches for all SBT tools, while it was 38 GiB for Mantis for all batches (Table 3).

Table 2. Query times (seconds). Values shown are the median over all the replicates.

	cache state	HowDe-SBT	AllSome-SBT	SSBT	Mantis
single		5.4	36.7	29.4	52.1
ten	cold	44.5	353.7	159.6	52.4
hundred		171.3	817.8	400.8	56.1
thousand		719.7	1168.6	3509.4	85.8
single		1.2	27.3	24.9	32.9
ten	warm	6.5	16.2	28.8	33.1
hundred		41.8	50.0	245.6	35.6
thousand		501.2	172.6	3226.6	64.2

6.3 Tree properties

First, we investigate how many positions are active and how saturated the active bits are. The fraction of active B_{det} positions decreases going down the tree (by definition), with a median of .006 at internal nodes and 0.002 at leafs. The saturation of B_{det}^{sqz} (i.e. the % of the active bits that are determined) is 100% at the leaves (by definition) and has a median of 41% at the internal nodes. The saturation of B_{how}^{sqz} (i.e. the % of the active B_{how}

Table 3. Peak resident RAM (in GiB) observed during queries. Values shown are the maximum over all the replicates.

	HowDe-SBT	AllSome-SBT	SSBT	Mantis
single	0.8	0.3	1.3	38
ten	0.8	0.3	1.1	38
hundred	0.8	0.3	1.1	38
thousand	0.8	0.6	1.1	38

bits that are 1) has a median of 51% at the leaves and 12% at the internal nodes. It decreases with the height of a node, meaning that at higher levels of the tree, the vast majority of positions that are determined are found to be absent rather than present. Figure 4 shows the saturation distributions. In terms of final space on disk, after RRR compression, the leaves account for only 18% of the total index size.

In Section 5, we derived the reduction in space and query time for a bit position x in terms of the number of nodes where it is active in B_{det} (denoted by n_x) and the fraction of nodes where it is set to one in B_{how} (denoted by s_x). Figure 3(b) shows the distribution of these values on our tree. The median value for s_x is 0.14 and for n_x is 31, which corresponds to $\Delta I_x \approx 14\%$ in Figure 3(a). However, we also see a correlation between n_x and s_x (Spearman coefficient of $r = 0.67$). Any future extension of our theoretical analysis per bit position to one of all bit positions jointly should take this complexity into account. We note that the total reduction in index size of HowDe-SBT over SSBT on our data (38%) is due not only to the improved bit representation but also due to the better tree topology that HowDe-SBT constructs; thus, a direct comparison to our theoretical predictions is challenging.

7 Conclusion

In this paper, we presented a novel approach for the representation of Sequence Bloom Trees and studied its performance from both a theoretical and experimental perspective. The main intuition behind our representation is that it reduces the number and entropy of the active bits. Compared to previous SBT approaches, HowDe-SBT is an improvement on all fronts: it constructs the index in less than 36% of the time and with 39% less the space, and can answer small-batch queries five times faster. The biggest advantage of HowDe-SBT over Mantis is that the construction algorithm is much faster and uses much less space, the final index is less than half the size, and queries require 30 times less memory. However, in terms of query time, there is no clear winner, with Mantis faster on larger batches while HowDe-SBT faster on smaller batches. The other advantage of Mantis is that, unlike the SBTs, it solves the query problem exactly; i.e., the SBT approaches use BFs to represent the k-mers, which can result in false positives, while Mantis uses an exact representation of the k-mers. There are therefore scenarios where Mantis is a more appropriate tool than an SBT, making the two approaches complementary.

With the improvements in this paper, the SBT can already be deployed for small and mid-size databases, such as a private patient cohort or all the sequencing data in `flybase.org`. Such a deployment will need to provide an automated way to update the database; while our method naturally supports insertions in $\mathcal{O}(height \cdot b)$ time (we have omitted the details), a quality assurance step will be necessary prior to automating database updates. It will also be necessary to provide a front-end interface (e.g. Galaxy or similar to Bradley *et al.* (2017)) for easy access. Such front-ends should also provide wrappers for more biologically-oriented queries (i.e. to convert "which sample has a SNP" into a k-mer query).

Acknowledgements: We are thankful to Ayaan Hossain and Natasha Stopa for helping prototype some aspects of this project. This work has been supported in part by

Fig. 4. The distribution of nodes' bitvector saturations, as a function of a node's height. The top panel shows barplots for the percentages of positions in the B_{det} vector that are active, the middle panel shows barplots for the percentages of those positions that are set to 1 (i.e. determined), and the bottom panel shows barplots for the percentage of active B_{how} positions that are set to 1. Above each plot is the histogram of height values, and to the right of each plot is the density plot of the percentages being measured in that plot.

NSF awards DBI-1356529, CCF-551439057, IIS-1453527, and IIS-1421908 to PM and partially supported by PSU's College of Engineering Multidisciplinary Seed Grant Program. Research reported in this publication was supported by the National Institute Of General Medical Sciences of the National Institutes of Health under Award Number R01GM130691. The content is solely the responsibility of the authors

and does not necessarily represent the official views of the National Institutes of Health.

References

Almodaresi, F., Pandey, P., and Patro, R. (2017). Rainbowfish: A succinct colored de Bruijn graph representation. In *LIPIcs-Leibniz International Proceedings in Informatics*, volume 88. Schloss Dagstuhl-Leibniz-Zentrum fuer Informatik.

Almodaresi, F., Pandey, P., Ferdman, M., Johnson, R., and Patro, R. (2018). An efficient, scalable and exact representation of high-dimensional color information enabled via de Bruijn graph search. *bioRxiv*, page 464222.

Bloom, B. H. (1970). Space/time trade-offs in hash coding with allowable errors. *Communications of the ACM*, **13**(7), 422–426.

Bradley, P., den Bakker, H., Rocha, E., McVean, G., and Iqbal, Z. (2017). Real-time search of all bacterial and viral genomic data. *bioRxiv*, page 234955.

Camacho, C., Coulouris, G., Avagyan, V., Ma, N., Papadopoulos, J., Bealer, K., and Madden, T. L. (2009). BLAST+: architecture and applications. *BMC bioinformatics*, **10**(1), 421.

Crainiceanu, A. and Lemire, D. (2015). Bloofi: Multidimensional Bloom filters. *Information Systems*, **54**, 311–324.

Gusfield, D. (1997). *Algorithms on strings, trees and sequences: computer science and computational biology*. Cambridge University Press.

Holley, G., Wittler, R., and Stoye, J. (2015). Bloom filter trie–a data structure for pan-genome storage. In *International Workshop on Algorithms in Bioinformatics*, pages 217–230. Springer.

Mäkinen, V., Belazzougui, D., Cunial, F., and Tomescu, A. I. (2015). *Genome-scale algorithm design*. Cambridge University Press.

Marçais, G. and Kingsford, C. (2011). A fast, lock-free approach for efficient parallel counting of occurrences of k-mers. *Bioinformatics*, **27**(6), 764–770.

Muggli, M. D., Bowe, A., Noyes, N. R., Morley, P. S., Belk, K. E., Raymond, R., Gagie, T., Puglisi, S. J., and Boucher, C. (2017). Succinct colored de Bruijn graphs. *Bioinformatics*, **33**(20), 3181–3187.

Mustafa, H., Schilken, I., Karasikov, M., Eickhoff, C., Raetsch, G., and Kahles, A. (2018). Dynamic compression schemes for graph coloring. *Bioinformatics*, page bty632.

Pandey, P., Almodaresi, F., Bender, M. A., Ferdman, M., Johnson, R., and Patro, R. (2018). Mantis: A fast, small, and exact large-scale sequence-search index. *Cell Systems*.

Raman, R., Raman, V., and Satti, S. R. (2007). Succinct indexable dictionaries with applications to encoding k-ary trees, prefix sums and multisets. *ACM Transactions on Algorithms (TALG)*, **3**(4), 43.

Solomon, B. and Kingsford, C. (2016). Fast search of thousands of short-read sequencing experiments. *Nature biotechnology*, **34**(3), 300âĿ"–302.

Solomon, B. and Kingsford, C. (2017). Improved search of large transcriptomic sequencing databases using split sequence Bloom trees. In *International Conference on Research in Computational Molecular Biology*, pages 257–271. Springer.

Sun, C., Harris, R. S., Chikhi, R., and Medvedev, P. (2017). AllSome sequence Bloom trees. In *International Conference on Research in Computational Molecular Biology*, pages 272–286. Springer.

Yu, Y., Liu, J., Liu, X., Zhang, Y., Magner, E., Lehnert, E., Qian, C., and Liu, J. (2018). SeqOthello: querying RNA-seq experiments at scale. *Genome biology*, **19**(1), 167.

Supplementary Section 1 Culling of nodes

In this section, we propose and explore a culling technique for allowing the tree to be non-binary, something was explored in the original Bloofi paper but was not supported by subsequent SBT approaches. The technique is applied during construction, right after the baseline binary tree topology is constructed but before the bitvector representations are computed.

For a node u, let $saturation(u)$ be the number of bits set to one and active in $B_{\text{det}}(u)$ divided by the number of bits that are active in $B_{\text{det}}(u)$. For example, in Figure 1, the left child of the root has saturation of $9/15$. Since at this stage B_{det} and B_{how} are not yet computed, we estimated the saturation by a sub-sampling technique, similar to that used to estimate node similarity Third, we identify the *culling threshold* as two standard deviations below the mean of the saturation value in the internal nodes. This was 20% on our dataset. Fourth, we scan the baseline topology to identify internal nodes u for which $saturation(u)$ is below the threshold. These nodes are then removed from the topology, with their children reassigned as children of the removed node's parent; if no parent exists, these nodes become roots of a new tree in the forest. We call this process *culling*. The result of culling is that the binary tree potentially becomes a non-binary forest. This does not change the query algorithm in any substantial way.

We investigate the effect of culling on the tree, as a function of the culling threshold (Table S1). At the threshold of 20%, we remove about 4% of the nodes, with a negligible decrease in total index size. The query times fluctuate (Table S2), showing a slight increase or decrease depending on the batch size.

Overall, we conclude that culling did not have a substantial effect on the SBT. It is interesting to observe that when the threshold is high (40%), 45% of the nodes are removed but the index size actually increases by 62%. This is due to the fact that a single active bit in $B_{\text{det}}(u)$ is replaced by two active bits in u's children, if u is removed.

Table S1. The effect of culling on the tree.

Culling threshold	total n. nodes	n. nodes culled	max depth	n. trees in forest	tree size (GiB)
0%	5169	0	26	1	14.3
10%	5157	12	25	1	14.3
20%	5056	113	23	2	14.3
30%	4679	490	19	8	14.9
40%	3997	1172	16	407	23.2

Table S2. The effect of culling on query time. A cold cache was used.

Culling threshold	median query time (s)			
	singles	tens	hundreds	thousands
0%	5.4	45	171	720
10%	5.1	43	170	713
20%	6.1	39	137	712
30%	7.7	44	155	636
40%	7.4	44	154	625