**gencore: An Efficient Tool to Generate Consensus Reads for**

**Error Suppressing and Duplicate Removing of NGS data**

Shifu Chen[1,2†*], Yanqing Zhou[1†], Yaru Chen[1], Tanxiao Huang[1], Wenting Liao[1,] Yun

Xu[1], Zhicheng Li[2], and Jia Gu[2]

[1]HaploX Biotechnology, Shenzhen, China
[2]Shenzhen Institutes of Advanced Technology, Chinese Academy of Sciences,
Shenzhen, China
†These authors have contributed equally to this work

**\* Correspondence:**
Corresponding Author
Shifu Chen: chen@haplox.com

# Abstract

**Background**

Removing duplicates might be considered as a well-resolved problem in next-generation sequencing (NGS) data processing domain. However, as NGS technology gains more recognition in clinical applications (i.e. cancer testing), researchers start to pay more attention to its sequencing errors, and prefer to remove these errors while performing deduplication operations. Recently, a new technology called unique molecular identifier (UMI) has been developed to better identify sequencing reads derived from different DNA fragments. Most existing duplicate removing tools cannot handle the UMI-integrated data. Some modern tools can work with UMIs, but are usually slow and use too much memory, making them not suitable for cloud-based deployment. Furthermore, existing tools rarely report rich statistical results, which are very important for quality control and downstream analysis. These unmet requirements drove us to develop an ultra-fast, simple, little-weighted but powerful tool for duplicate removing and sequence error suppressing, with features of handling UMIs and reporting informative results.

**Results**

This paper presents an efficient tool *gencore* for duplicate removing and sequence error suppressing of NGS data. This tool clusters the mapped sequencing reads and merges reads in each cluster to generate one single consensus read. While the consensus read is generated, the random errors introduced by library construction and sequencing can be removed. This error-suppressing feature makes *gencore* very suitable for the application of detecting ultra-low frequency mutations from deep sequencing data. When unique molecular identifier (UMI) technology is applied, *gencore* can use them to identify the reads derived from same original DNA fragment. *gencore* reports statistical results in both HTML and JSON formats. The HTML format report contains many interactive figures plotting statistical coverage and duplication information. The JSON format report contains all the statistical results, and is interpretable for downstream programs.

**Conclusions**

Comparing to the conventional tools like Picard and SAMtools, *gencore* greatly

reduces the output data's mapping mismatches, which are mostly caused by errors.

Comparing to some new tools like UMI-Reducer and UMI-tools, *gencore* runs much

faster, uses less memory, generates better consensus reads and provides simpler

interfaces. To our best knowledge, *gencore* is the only duplicate removing tool that

generates both informative HTML and JSON reports. This tool is available at:

https://github.com/OpenGene/gencore

# Keywords

next-generation sequencing; unique molecular identifier; consensus reads;

deduplication

## Introduction

High-depth next-generation sequencing (NGS) has been widely used for precision cancer diagnosis and treatment [1]. From such deep sequencing data, somatic mutations can be detected to guide personalized targeted therapy or immunotherapy. Recently, circulating tumor DNA (ctDNA) sequencing has been recognized as a promising biomarker for cancer treatment and monitoring. Since the tumor-derived DNA is usually a small part of the total blood cell-free DNA, the mutant allele frequency (MAF) of a variant detected from ctDNA sequencing data can be very low (as low as 0.1%). To detect such low-frequency variants, we usually increase the sequencing depth (can be higher than 10,000x). However, the processes of making NGS library and sequencing are not error-free. Particularly, the library amplification using PCR technology can lead to particular sequences becoming overrepresented [2], and consequently cause some false positive mutations in the result of NGS data analysis.

As a result of library amplification, NGS data can have many duplicates. Especially for the high-depth data generated by sequencing low-input DNA, the duplication level can be much higher. Traditionally, we just mark the duplicated reads and remove them before downstream analysis. For low-depth paired-end NGS data, the read pairs of same start and end mapping positions can be treated as duplicated reads derived from a same original DNA fragment [3]. Then, the reads clustered together can be merged to be a single read. Due to the nature that errors usually happen randomly, the inconsistent mismatches in the clustered read group can be removed to generate a consensus read.

However, for ultra-deep sequencing, it's possible that two read pairs with same positions are derived from different original DNA fragments. This possibility can be higher when the DNA fragments are shorter. For example, cell-free DNA usually has a peak length of ~167 bp, which is much shorter than the peak length of normally fragmented genomic DNA. To better identify sequencing reads derived from different DNA fragments, a technology called unique molecular identifier (UMI) has been

developed. It has been adopted by various sequencing methods such as Duplex-Seq [4]

and iDES [5]. With UMI technology, each DNA fragment is ligated with unique

random barcodes before any DNA amplification process. The UMIs can be then used

for accurate clustering of sequencing reads. UMIs may be applied to almost any

sequencing method where confident identification of PCR duplicates by alignment

coordinates alone is not possible and/or an accurate quantification is required,

including DNA-seq karyotyping [6] and antibody repertoire sequencing [7].

Some tools, like SAMtools [8] and Sambamba [9], are commonly used to remove

duplicates, but cannot process data with UMIs. Samtools is not efficient since it has to

sort the data twice for marking duplicate alignments. Sambamba runs faster, but opens

a lot of files (much more than 1024), and may introduce problems when multiple

instances are run concurrently. The conventional tool Picard markDuplicates

(http://broadinstitute.github.io/picard) is able to handle UMIs, but cannot process bam

data with unmapped reads. UMI-Reducer [10] and UMI-tools [11] are two new tools

designed for processing UMI-integrated NGS data. However, UMI-Reducer is only

suitable for RNA data, and UMI-tools cannot deal with data without UMI-integrated.

Furthermore, these tools are usually relative slow and use too much memory, which

make them cost ineffective for cloud-based deployment. These unmet requirements

drove us to develop a new tool called *gencore*, which is fast and memory efficient,

with functions to eliminate errors and remove duplicates by generating consensus

reads for NGS data with or without UMIs. Table 1 shows a brief comparison of

features of different deduplication or consensus read generating tools.

**Table 1 Features comparison of different deduplication or consensus read**

**generating tools.**

|  | SAMtools | Picard | *gencore* | Picard | UMI-tools | *gencore* |
|---|---|---|---|---|---|---|
|  | **Non-UMI mode** | | | **UMI mode** | | |
| No need to sort by read name |  | + | + |  | + | + |
| No need to sort clean up flags |  | + | + |  | + | + |
| No need to sort add UMI tag | + | + | + |  | + | + |
| No need to sort by position again |  | + | + |  | + | + |

| | | | | | | |
|---|---|---|---|---|---|---|
| JSON Report | + | + | + | + | | + |
| HTML Report | | | | | | + |

110 In Table 1, the input for these five tools is a sorted bam. SAMtools cannot handle

111 UMIs, whereas UMI-tools is only applicable for UMI-integrated data. Only

112 UMI-tools and *gencore* needn't any extra BAM preporcessing before performing the

113 deduplication. *gencore* reports metrix in JSON and HTML formats whereas

114 UMI-tools doesn't.

## Implementation

*gencore* requires an input of position sorted BAM file and a reference genome

FASTA file. If the FASTQ data has UMIs, it can be preprocessed using fastp [12] to

move the UMIs from read sequences to read identifiers. The main workflow of

*gencore* is described in Fig.1.

**Fig.1 The brief workflow of *gencore*.** Besides the input BAM/SAM file, this tool

accepts a reference genome input to assist consensus reads generation. If the data is

from targeted sequencing, a BED file can also be provided to describe the capturing

regions. In this case, the coverage statistics in BED regions will also be reported in the

HTML/JSON reports.

Simply put, *gencore* clusters read pairs by their mapping positions and UMIs (if

applicable), and then generates a consensus read for each cluster. The main algorithm

of *gencore* can be briefly introduced as following steps:

(1)  Position clustering: all mapped read pairs are grouped by mapping position first.

The reads with same mapping chromosome, start position and end position will be

grouped together. A multi-level map [*chr*]:[*left_pos*]:[*right_pos*]:[*read_pairs*], is used

to store the clusters being processed, while [*left_pos*] and is [*right_pos*] the read pair's

leftmost and rightmost mapping position in the chromosome respectively. [*read_pairs*]

is a group of read pairs that share the same mapping positions. To reduce the memory

usage, *gencore* implements a processing-while-reading strategy, which means

processing one group immediately when its all possible reads are collected. For

example, when *gencore* finds that the mapping position of current inputting read is

greater than [*right_pos*] of one group, it will perform following step 2 to step 7 for

this group and release the group immediately.

(2)  UMI clustering: for each group of same mapping positions, read pairs are then

clustered by their UMIs with one base difference tolerance. If the data has no UMIs,

this step is skipped. Due to the principle of Illumina paired-end sequencing, if the data

has dual UMIs from forward and reverse reads, the read pairs with reciprocal UMIs

will be clustered together. For instance, two read pairs with UMI *ATGC_GCAA* and

*GCAA_ATGC* will be considered as derived from different strands of same original

DNA fragment, and will be clustered together.

(3)  Cluster filtering: each cluster will be filtered by comparing its supporting reads

number with the threshold (default = 1, which means no threshold). If it passes,

*gencore* will start to generate a consensus read for this cluster. For ultra-deep

sequencing (i.e. ctDNA sequencing with 10,000× or higher depth), it's recommended

to increase the threshold to 2 to discard part of reads that without any PCR duplicates.

(4) Pair scoring: a default score number (default = 6) will be initially assigned to

every base in the read. For each read pair in a cluster, the overlapped region of the

paired reads is computed. For each base in the overlapped region, its score is adjusted

according to its consistence with its paired base, with the consideration of their quality

scores. The default scoring schema is presented in the project repository, and can be

configured through options.

(5) Cluster scoring: in this step, the total scores are computed by summarizing the

scores computed in previous step. For each position in the mapping region, *gencore*

queries the base presented in the cluster's different reads, and summarizes them to

compute the score of different bases (A/T/C/G).

(6) Consensus read generating: for each position in a cluster, its base diversity is

computed according to the scores of different bases computed in last step. If *gencore*

finds one dominant base, this base will also be presented in the consensus read.

Otherwise if exists one or more reads are concordant with reference genome with high

quality, or all reads at this positions are with low quality, the corresponding base in

the reference genome will be used. The using of reference genome is one of the major

differences between *gencore* and other tools. Since a base is more likely an error

when it's not concordant with reference, *gencore* assigns lower weight to them when

computing the consensus reads.

(7) Buffered reads outputting: when one consensus read is generated, it will be

buffered in a position-sorted queue to be written to output. To minimize the memory

used by this queue, *gencore* implements a writing-while-processing strategy. With

this strategy, *gencore* maintains a pointer that always points to the unprocessed read

with least mapping position, and periodically outputs the reads in queue with mapping

position less than it.

After the processing is done, *gencore* will generate a summary of the data before and

after processing. Some metrics like coverage, duplication histogram, mapping rate,

duplication rate, passing filter rate and mismatch rate are reported in HTML/JSON

format reports. The HTML report contains no image figures but some interactive

figures, which are built based on Plotly.js. Comparing to conventional HTML reports

with static images, this single-page standalone JavaScript-based HTML report is

much more interactive and easier to transfer. Fig. 2 shows a demonstration of the

coverage statistics in both genome scale and capturing regions in the HTML reports.

a. coverage in genome scale, with a window selected in chr2

b. coverage of the enlarged window selected in a.

c. coverage of capturing regions in given BED file

**Fig. 2 The coverage statistics figures in the HTML report.** In this interactive

HTML report, a region is selected in a), and then enlarged in b). While a) and b) are

coverage in genome scale, c) is the coverage only in the capturing regions. The BAM

file of this report was generated by targeted sequencing using a panel with hundreds

of genes. So the coverage in genome scale is very sparse, whereas the coverage in

capturing regions is high and dense.

**Application**

Since *gencore* can be used to reduce sequencing errors, it is very useful for the

application of detecting low-frequency somatic mutations from cancer sequencing

data, particularly in liquid biopsy technology [16]. When the samples are from blood,

urine or malignant effusion, the MAF of variants can be even much lower than 1%.

The detection of such low-frequency variants can be seriously affected by the errors,

which are usually introduced by library preparation and sequencing. *gencore* can

significantly reduce the sequencing errors of deep sequencing data, and consequently

reduce the false positive calling rate.

To evaluate how *gencore* can help the variant detection, we conducted two evaluation

experiments using 8 DNA samples, obtained from the National Center for Clinical

Laboratories (NCCL) in China. The dataset #1 (1801, 1802, 1803 and 180N) was

generated by sequencing plasma cell-free DNA samples, and each data contains ~55G

bases. Sample 1801, 1802 and 1803 were DNA extracted from blood of one lung

adenocarcinoma patient at different time, whereas sample 180N was DNA from a

healthy control. The dataset #2 (1811, 1812, 1813 and 181N) was generated by

sequencing tissue DNA samples, and each data contains ~10G bases. Sample 1811

and 1812 were DNA of tumor tissues collected from two breast cancer patients,

whereas sample 1813 was DNA of a biopsy tissue collected from a lung

adenocarcinoma patient, and sample 181N was DNA from a healthy control. These

DNA samples are publicly provided by NCCL as reference materials for conducting

inter-lab quality assessments. The golden standard mutations of all samples were also

provided by NCCL. Among all the mutations, the lowest frequency was about 0.15%.

In our experiment, all samples sequencing libraries were prepared using IDT xGen

Dual Index Adapters, captured with a 451-gene cancer panel, and then sequenced

using an Illumina NovaSeq 6000 sequencer. UMI adapters were used for 1801, 1802,

1803 and 180N samples. The detailed file sizes and commands of experiments are

provided in Supplementary file 1.

The FASTQ files were preprocessed by fastp, and then mapped to reference genome

hg19 using BWA [13]. After the mapped bam file was sorted using Samtools, the

sorted bam files were then processed by different tools. VarScan2 [14] was used to

call SNVs from the processed bam files, and ANNOVAR [15] was then used to

annotate the VCF files. The missense variants detected in the coding sequences were

then filtered with conditions (dataset #1: supporting reads $\geqslant$ 5; dataset #2: supporting reads $\geqslant$ 8 and variant allele frequency $\geqslant$ 2%). The variant calling results were evaluated by comparing to the golden standard results provided by NCCL, and the speed and memory performance were also compared. The comparison result is shown in Fig 3.

**Fig. 3 Comparison of speed, memory peak and processing results of different tools in both UMI and non-UMI modes.** a) memory peak and execution time of different tools. Samtools and Picard (in UMI mode) need to prepare the data before performing deduplication, whereas *gencore* and UMI_tools needn't. b) average depth of output BAM. For the cfDNA samples (1801, 1802 and 1803), the depths of UMI mode results are much higher than non-UMI mode, indicating that over-deduplication may happen when performing deduplication without UMI for ultra-deep sequencing data. c) specificity of downstream variant calling results comparing to the golden standard results provided by NCCL.

From Fig. 3, we can learn that *gencore* runs much faster than all other tools. For the

comparison of memory peak, *gencore* uses much less memory than Picard and

UMI_tools. Due to *gencore* consumes extra memory to load reference genome and

performs more processing, *gencore* uses more memory than Samtools. But, as shown

on Fig. 3a, its memory peak is still less than 8GB. This result shows that *gencore* is

littleweight and fast, and is much more cost-effective to be deployed on the cloud.

The comparison of downstream variant calling results also shows that *gencore*

outperforms other tools. From Fig. 3c, we can learn that *gencore* achieved higher

specificity in both UMI and non-UMI modes.

For the cfDNA samples (1801, 1802 and 1803), we applied a filter with condition

(supporting reads≥5). The results showed all tools successfully detected all true

positive variants for 1801 and 1802, but non-UMI mode tools missed one true positive

variant for 1803 due to its variant allele frequency was too low (VAF = 0.15%).

Moreover, we evaluated the detected variants by comparing their VAFs to the golden

results, and considered a variant as unacceptable if its VAF exceeded 2 standard

deviations. The results showed all non-UMI mode tools resulted in two variants with

unacceptable VAFs. For UMI mode, UMI_tools detected one variant with

unacceptable VAF, while all variants detected by Picard and *gencore* were acceptable.

For the tissue DNA samples (1811, 1812 and 1813), we applied a filter with condition

(supporting reads $\geqslant$ 8 and VAF $\geqslant$ 2%). The results showed that all tools could

detect true positive variants at 100% sensitivity. But for sample 1811, both Picard and

Samtools reported one false positive variant, while *gencore* achieved 100% specificity

for all three samples.

These results suggest that UMI technique is important for detecting variants with

ultra-low VAFs, and *gencore* is one of the best tools to process UMI-enabled data due

to its superior accuracy and performance.

**Results and discussion**

By analysing the output data using downstream tools, *gencore* outperforms other tools

in both non-UMI and UMI modes. By carefully exploring the data generated by these

different tools, we found the major difference was that *gencore* applied reference

genome based correction, whereas Picard and UMI-tools didn't. Utilization of a

reference genome is important for eliminating sequencing noises. When an

inconsistent position is found when making a consensus read, the reference base

should be taken into account since the base different from the reference may have

higher probability to be a sequencing error.

To explore how *gencore* eliminates the sequencing errors, we manually compared

some the alignment files before and after *gencore* processing. In the case of sample

1802, NM_005228.3(EGFR): c.2369C>T, p.T790M variant was one true positive

variant. Fig. 4 shows the alignment visualization illuminated by Integrated Genome

Viewer (IGV) for the files before and after processing. In Fig. 4a, which is the

original alignment file generated by mapping by BWA [13], the double-line marked

mismatch T base is the true positive variant EGFR p.T790M. However, there are also

some other mismatch bases, which are false positive mismatches caused by

sequencing errors. In Fig. 4b, which is the alignment file after *gencore* processing, we

can find these false positive mismatches are gone, while the true positive variant is

kept. This result suggests that *gencore* not only removes duplicates, but also

eliminates sequencing errors.

**Fig. 4 Comparison of the alignment files before and after *gencore* processing.** In

this figure, the position marked by double lines is NM_005228.3(EGFR): c.2369C>T,

p.T790M variant. a) visualizes the mapped reads of original alignment file, b)

visualizes the mapped reads after *gencore* processing. We can find that the false

positive mismatches, which appear randomly in the original alignment file, are

corrected by *gencore*.

## Conclusion

We introduced a tool *gencore*, which is useful for performing deduplication and

consensus read generation for deep next-generation sequencing data. We conducted

several experiments to evaluate the performance of *gencore*, with comparisons to

Picard, Samtools and UMI-tools. The result shows that *gencore* is much faster and

more memory efficient, while providing similar or better results. This tool generates

interactive HTML reports and informative JSON reports that can help manually

checking and programmatically downstream analysis. According to our estimation,

this tool has been used to process more than 10,000 samples in the authors' institution,

and is now suitable to be adopted by community users.

**List of abbreviations**

ctDNA: cell-free tumor DNA; NGS: next generation sequencing; IGV: integrative

genome viewer; MAF: mutated allele frequency; INDEL: insertion and deletion; SNP:

single-nucleotide polymorphism; SNV: single-nucleotide variation; EGFR: epidermal

growth factor receptor; UMI: unique molecular identifier; HTML: Hypertext Markup

Language; JSON: JavaScript Object Notation; NCCL: National Center for Clinical

Laboratories;

## Declarations

***Ethics approval and consent to participate***

Not applicable.

***Consent to publish***

Not applicable.

**Availability and requirements**

Project name: gencore

Project home page: https://github.com/OpenGene/gencore

Operating system(s): Linux or Mac OS X

Programming language: C++

Other requirements: htslib and zlib

License: MIT License.

***Competing interests***

The authors declare that they have no competing interests.

***Funding***

The presented study was funded by Shenzhen Science and Technology Innovation
Committee Technical Research Project (Grant No. JSGG20180703164202084) and
Shenzhen Strategic Emerging Industry Development Special Fund (Grant No.
20170922151538732).

***Authors' contributions***

SC designed the algorithm, developed the software and wrote the paper. YZ
co-designed the algorithm, YC, YX, WL and TH conducted the testing work and
evaluation experiments, ZL and JG contributed to data analysis and paper revision.
All authors read and approved the final manuscript.

***Acknowledgments***

We'd like to thank HaploX Biotechnology for supporting the publication cost. We'd
like to express our thanks to the *gencore* community users for testing and reporting

issues. We'd like to thank the OpenGene members for their suggestions of *gencore*'s

design.

# References

[1] Shendure J, Ji H. Next-generation DNA sequencing. *Nat Biotechnol* 2008, 26: 1135–45.

[2] Aird D, G Ross M, Chen W, Danielsson M, Fennell T, Russ C, et al. Analyzing and minimizing PCR amplification bias in Illumina sequencing libraries. *Genome biology* 2011, 12: p.R18.

[3] Sims D, Sudbery I, Ilott NE, Heger A, Ponting CP. Sequencing depth and coverage: key considerations in genomic analyses. Nat Rev Genet 2014, 15: 121–32.

[4] Kennedy SR, Schmitt MW, Fox EJ, Kohrn BF, Salk JJ, Ahn EH, et al. Detecting ultralow-frequency mutations by Duplex Sequencing. Nat Protoc 2014, 9: 2586-2606.

[5] Newman AM, Lovejoy AF, Klass DM, Kurtz DM, Chabon JJ, Scherer F, et al. Integrated digital error suppression for improved detection of circulating tumor DNA. *Nat Biotechnol* 2016, 34: 547-555.

[6] Karlsson K, Sahlin E, Iwarsson E, Westgren M, Nordenskjöld M, Linnarsson S. Amplification-free sequencing of cell-free DNA for prenatal non-invasive diagnosis of chromosomal aberrations. *Genomics* 2015, 105: 150–8.

[7] Vollmers C, Sit RV, Weinstein JA, Dekker CL, Quake SR. Genetic measurement of memory B-cell recall using antibody repertoire sequencing. *Proc Natl Acad Sci U S A* 2013, 110: 13463–8.

[8] Li H, Handsaker B, Wysoker A, Fennell T, Ruan J, Homer N, et al. The Sequence Alignment/Map format and SAMtools. *Bioinformatics* 2009, 25: 2078-2079.

[9] Tarasov A, Vilella AJ, Cuppen E, Nijman IJ, Prins P. Sambamba: fast processing of NGS alignment formats. *Bioinformatics* 2015, 31: 2032-4.

[10] Mangul S, Driesche SV, Martin LS, Martin KC, Eskin E. UMI-Reducer: Collapsing duplicate sequencing reads via Unique Molecular Identifiers. *bioRxiv* 2017, 103267.

[11] Smith T, Heger A, Sudbery I. UMI-tools: Modelling sequencing errors in Unique Molecular Identifiers to improve quantification accuracy. *Genome Res* 2017, 27: 491-499.

[12] Chen S, Zhou Y, Chen Y, Gu J. fastp: an ultra-fast all-in-one FASTQ

preprocessor. Bioinformatics 2018, 34: 884-890.

[13] Li H, Durbin R. Fast and accurate short read alignment with Burrows-Wheeler

transform. Bioinformatics 2009, 25: 1754-1760.

[14] Koboldt DC, Zhang Q, Larson DE, Shen D, McLellan MD, Lin L, et al. VarScan

2: somatic mutation and copy number alteration discovery in cancer by exome

sequencing. Genome Res 2012, 22: 568-576.

[15] Wang K, Li M, Hakonarson H. ANNOVAR: functional annotation of genetic

variants from high-throughput sequencing data. Nucleic Acids Res 2010, 38: e164.

[16] Esposito A, Criscitiello C, Trapani D, Curigliano G. The Emerging Role of

"Liquid Biopsies," Circulating Tumor Cells, and Circulating Cell-Free Tumor DNA in

Lung Cancer Diagnosis and Identification of Resistance Mutations. Curr Oncol Rep

2017, 19: 1.