The validity and consistency of continuous joystick response in perceptual decision-making

Maciej J. Szul, Aline Bompas, Petroc Sumner, Jiaxiang Zhang

Cardiff University Brain Research Imaging Centre, School of Psychology, Cardiff University, Cardiff CF24 4HQ, United Kingdom

Abbreviated title: Validity of joystick response in perceptual decision-making

Text pages: 37

Figures: 4

Table: 1

Correspondence should be addressed to:

Maciej Szul (SzulMJ@cardiff.ac.uk)

Cardiff University Brain Research Imaging Centre, School of Psychology, Cardiff University, Cardiff CF24 4HQ, United Kingdom

Acknowledgements

MJS was supported by a PhD studentship from Cardiff University School of Psychology. JZ was supported by a European Research Council Starting grant (716321). The authors declare no competing financial interests.

Abstract

A computer joystick is an efficient and cost-effective response device for recording continuous movements in psychological experiments. Movement trajectories and other measures from continuous responses have expanded the insights gained from discrete responses (e.g. button presses) by providing unique insights in how cognitive processes unfold over time. However, few studies have evaluated the validity of joystick responses with reference to conventional key presses, and response modality can affect cognitive processes. Here, we systematically compared human participants' behavioural performance of perceptual decision-making when they responded with either joystick movements or key presses in a four-alternative motion discrimination task. We found evidence that the response modality did not affect raw behavioural measures including decision accuracy and mean reaction time (RT) at the group level. Furthermore, to compare the underlying decision processes between the two response modalities, we fitted a drift-diffusion model of decision-making to individual participant's behavioural data. Bayesian analyses of the model parameters showed no evidence that switching from key presses to continuous joystick movements modulated the decision-making process. These results supported continuous joystick actions as a valid apparatus for continuous movements, although we highlight the need for caution when conducting experiments with continuous movement responses.

Keywords

Joystick trajectory, decision-making, computational modelling, behavioural experiments, drift-diffusion model

Introduction

Discrete key presses on a keyboard or button box have been the long-standing response modality in computer-based experiments in psychology, from which on/off responses and response time (RT) are commonly measured. Developments in computer and technology have improved the accessibility of other devices that are capable of recording continuous responses, e.g., joystick, computer mouse, motion sensor and robotic arm (Koop & Johnson, 2011; O'Hora, Dale, Piiroinen, & Connolly, 2013). In addition to the standard behavioural measures available from key presses, continuous responses enable further inferences from movement trajectories. However, to utilize the full capacity of continuous response recording, we need to ensure that experimental results from these devices are consistent with, or generalizable to, the findings from conventional response modalities such as key presses. The current study addressed this issue by comparing the behavioural performance between joystick movements and key presses in a perceptual decision-making task. Using computational modelling of behavioural data, we further compared the decision-making processes from the two response modalities.

Continuous and discrete responses in experimental psychology

Continuous responses can offer theoretical and practical advantages in experiments. First, although a discrete response is consistent with the assumption of sequential stages of cognition and motor outputs, a growing number of studies suggest a continuous and parallel flow of information between brain systems involved in sensory, cognitive and motor processes (Cisek & Kalaska, 2005; Spivey, Grosjean, & Knoblich, 2005). Continuous responses can capture the dynamics of these multiple mental processes, as well as the transitions between them (Resulaj, Kiani, Wolpert,

& Shadlen, 2009). Second, in experiments involving clinical populations, it can be difficult for

patients to make discrete responses accurately on a keyboard, especially in patients with dementia

or parkinsonism. Patients with motor function impairments (e.g., tremor, apraxia or loss of

dexterity) often omit button presses, press the button too early or too late, press wrong buttons

accidentally or are confused with response-button mapping. This limitation may result in a

significant amount of experiment data being rejected in some studies (Wessel, Verleger,

Nazarenus, Vieregge, & Kömpf, 1994), while continues response with natural movements can be

well tolerated in patients (Limousin et al., 1997; Strafella, Dagher, & Sadikot, 2003)

The trajectories of continuous movements contain rich spatiotemporal information of the action,

and provide unique insights into how cognitive processes unfold in time (Freeman, Dale, &

Farmer, 2011; Song & Nakayama, 2009). For example, in continuous reaching, movement

trajectories showed that human participants can initiate a reaching action prior to when the target

becomes fully available, and select from competing action plans at a later stage (e.g. Chapman et

al., 2010; Gallivan & Chapman, 2014). In perceptual decision-making, movement trajectories from

joysticks and other similar devices have been successfully used to investigate the cognitive

processes underlying changes of mind (Resulaj et al., 2009), error correction (Acerbi,

Vijayakumar, & Wolpert, 2017) and subjective confidence (Berg et al., 2016) that are otherwise

difficult to study with key presses.

A comparison between response modalities

To extend experimental findings to other apparatuses, it is necessary to assess the consistency of

performance between response modalities. More importantly, characterising the consistency

between response modalities may help us understand the interdependence of cognitive processes

and motor systems. For example, in decision-making tasks, comparisons between saccadic eye

movements and manual responses has suggested a domain general decision mechanism regardless

of response modality (Gomez, Ratcliff, & Childers, 2015; Ho, Brown, & Serences, 2009), and the

apparent difference in response speed is accounted for by the neuroanatomical distinctions in

saccadic and manual networks (Bompas, Hedge, & Sumner, 2017).

The current study aimed to examine the validity and consistency of continuous joystick responses

versus discrete button presses in perceptual decision-making. Participants performed a four-

alternative motion discrimination task (Churchland, Kiani, & Shadlen, 2008) with two levels of

perceptual difficulty. The task was to indicate the coherent motion direction from random dot

kinematogram, a standard psychophysical stimulus for visual perceptual decision (Fredericksen,

Verstraten, & Van De Grind, 1994; Lappin & Bell, 1976; Pilly & Seitz, 2009; Ramachandran &

Anstis, 1983; Watamaniuk, Sekuler, & Williams, 1989). In two counterbalanced sessions, the

participants indicated their decisions with either joystick movements or key presses. The joystick

response was to move the lever from its neutral position towards one of the four cardinal directions,

aligned to the coherent motion direction, and the corresponding key press was one of the four

arrow keys on the keyboard. We compared raw behavioural performance (decision accuracy and

mean RT) between the two response modalities and between the two levels of task difficulty. From

continuous movement trajectories, we also examined whether joystick-specific measures (i.e.,

trajectory length, peak velocity and acceleration time) were consistent between movement

directions.

To assess whether the response modality affected the decision-making process, we fitted a drift-

diffusion model (DDM) (Gold & Shadlen, 2007; Ratcliff, Smith, Brown, & McKoon, 2016) to

individual participant's behavioural data and compared model parameters derived from the

joystick and keyboard sessions. The DDM belongs to a family of sequential sampling models of

reaction time. These models assume that the decision process is governed by the accumulation of

noisy sensory evidence over time until a threshold is reached (Bogacz, Brown, Moehlis, Holmes,

& Cohen, 2006; Ratcliff & Smith, 2004), consistent with the electrophysiological (Britten,

Shadlen, Newsome, & Movshon, 1992; Churchland et al., 2008; Hanks, Kiani, & Shadlen, 2014;

Huk & Shadlen, 2005; Shadlen & Newsome, 2001) and neuroimaging (Heekeren, Marrett, &

Ungerleider, 2008; Ho, Brown, & Serences, 2009; Zhang, Hughes, & Rowe, 2012) evidence on

the identification of neural accumulators in the frontoparietal cortex. The current study used the

DDM to decompose the observed RT distributions and accuracy into three model components:

decision threshold for the amount of evidence needed prior to a decision, drift rate for the speed of

evidence accumulation, and non-decision time to account for the latencies of stimulus encoding

and action initiation (Ratcliff & McKoon, 2008; Wagenmakers, 2009). The latter parameter is of

interest in particular, because one may expect a difference in the latency distribution of action

initiation between joystick movements and key presses.

Our findings demonstrated that when human participants used ballistic movements to respond with

a joystick, their behavioural performance was modulated by task difficulty and similar to that from

key presses on the same perceptual task. Further computational modelling analysis showed no

evidence of a change in any model parameter when switching between response modalities. As

such, we concluded that joystick movement is a valid response modality for extending discrete

actions to continuous behaviour in psychological experiments, although participants may exhibit

differences in movement trajectory measures towards different directions.

Method

Participants

Twenty-one participants (7 males, aged range 18-24 years; M = 20.43 years, SD = 2.91 years) took part in the study following written informed consent. All but three were right-handed. All the participants had normal or corrected-to-normal vision, and none reported a history of motor impairments or neurological disorders. The study was approved by the Cardiff University School of Psychology Ethics Committee.

Apparatus

The experiment was conducted in a behavioural testing room with dimmed light. Stimuli were displayed on a 22-inch CRT monitor with 1600x1200 pixels resolution and 85 Hz refresh rate. A chin rest was used to maintain the viewing distance and position. A joystick (Extreme 3D Pro Precision, Logitech International S.A., Switzerland) was used to record movement trajectories at 85 Hz in the joystick session. The joystick handle could move nearly freely, with little resistance from its neutral position within the 20% movement radius. Beyond the 20% radius, the resistance during joystick movement was approximately constant. A standard PC keyboard was used to record key presses. The experiment was written using PsychoPy 1.85.4 library (Peirce, 2008).

Stimuli

In both the joystick and keyboard sessions, a random-dot kinematogram was displayed within a

central invisible circular aperture with 14.22° diameter. White dots were presented on a black

background (100% contrast) with a dot density of 27.77 dots per deg^2 per second and a dot size of

0.14°. Similar to previous studies (Britten et al., 1992; Pilly & Seitz, 2009; Roitman & Shadlen,

2002; Shadlen & Newsome, 2001; Zhang & Rowe, 2014), we introduced coherent motion

information by interleaving three uncorrelated sequences of dot positions across frames at 85 Hz.

In each frame, a fixed proportion (i.e., the motion coherence) of dots was replotted at an

appropriate spatial displacement in the direction of the coherent motion (51.195°/s velocity),

relative to their positions three frames earlier, and the rest of the dots were presented at random

locations within the aperture. Signal dots had a maximum lifetime of three frames, after which

they were reassigned to random positions. The coherent motion direction in each trial was set in

one of the four cardinal directions (0°, 90°, 180° or 270°).

Task and procedure

Each participant took part in two experimental sessions using keyboard or joystick as a response

modality. The order of response modality was counterbalanced across participants. In both

sessions, participants performed a four-alternative motion discrimination task, indicating the

coherent motion direction from four possible choices (0°, 90°, 180° or 270°). Each session

comprised 960 trials, which were divided into 8 blocks of 120 trials. Each block had 15 repetitions

of each of the four motion directions and two difficulty conditions. The motion coherence was

10% in the "Difficult" condition and 20% in the "Easy" condition. Feedback on the mean decision

accuracy was provided after each block. The order of the conditions was pseudo-randomized

across sessions and participants, ensuring that the same direction and difficulty condition did not

occur in four consecutive trials. In the keyboard session, the participants responded with four arrow

keys corresponding to the coherent motion direction (right - 0°, up - 90°, left - 180° and down -

270°). In the joystick session, the participants were instructed to indicate the motion direction with

an appropriate joystick movement from the joystick's central position to one of the four edges

(right - 0°, up - 90°, left - 180° and down - 270°).

Every trial started with a 400 ms fixation period (Figure 1a). The random dot kinematogram

appeared after the fixation period for a maximum of 3000 ms or until response. In the keyboard

session, stimuli disappeared after a button press. In joystick condition, stimuli disappeared when

the participants stopped joystick movement. The chosen stopping rule was when the joystick

position did not change in the last four sampling points, and its position was outside of the 20%

motion radius. After response, a blank screen was presented as the intertrial interval, with a

duration uniformly randomized between 1000 and 1400 ms.

The response time (RT) in the keyboard session was defined as the latency between the onset of

random-dot kinematogram and the time of key press. In the joystick session, the RT was defined

as the duration between the onset of the random-dot kinematogram and the first time when the

joystick's position left the 20% movement radius from its neutral position. It coincided with first

noticeable increase in velocity from stationary position. Participants' choice in the joystick session

was measured as the last position of the joystick was binned to the closest cardinal directions (i.e.,

0°, 90°, 180° and 270°).

Drift-diffusion model (DDM) analysis

We fitted the DDM to each participant's response time distributions and accuracy. The DDM

decomposes the behavioural data into four key model parameters (Ratcliff & McKoon, 2008). (1)

The decision threshold (a) denotes the distance between the two decision boundaries. (2) The mean

drift rate (v) denotes the strength of sensory information. (3) The starting point (z) denotes the

response bias towards one of the two alternatives. (4) The non-decision time (T_{er}) denotes the

latencies of stimulus encoding and response initiation. In addition, the DDM can be extended to

include trial-by-trial variability in drift rate s_v and non-decision time s_t, which improves model fit

to the data (Ratcliff & McKoon, 2008). The DDM predicts the decision time as the duration of the

accumulation process and the observed RT as the sum of the decision time and T_{er} (Figure 1B).

Similar to previous studies (Churchland et al., 2008) , we simplified the four-alternative forced

choice task in the current study to a binary decision problem for model fitting. This was achieved

by separately grouping trials with correct responses and trials with incorrect responses. The

behavioural task was then reduced to a binary choice between a correct and an incorrect alternative.

We used the hierarchical drift-diffusion model (HDDM) toolbox to fit the behavioural data

(Wiecki, Sofer, & Frank, 2013). The HDDM implemented a hierarchical Bayesian model

(Vandekerckhove, Tuerlinckx, & Lee, 2011) for estimating the DDM parameters, which assumes

that the model parameters for individual participants are sampled from group-level distributions at

a higher hierarchy. Given the observed experimental data, the HDDM used Markov chain Monte

Carlo (MCMC) approaches to estimate the joint posterior distribution of all individual- and group-

level parameters. The posterior parameter distributions can be used directly for Bayesian inference

(Gelman et al., 2014), and this Bayesian approach has been shown to be robust in recovering model

parameters when limited data are available (Ratcliff & Childers, 2015; Wiecki et al., 2013; Zhang

et al., 2016).

We applied a few constraints to the model parameters based on our task design. First, we allowed

all the model parameters ($a, v, Ter, s_v,$ and s_t) to vary between the two response modalities. Second,

the mean drift rate v was further allowed to vary between task difficulties (easy, difficult) and

correct directions (up, down, left and right). Third, the starting point z was fixed at 0.5, suggesting

that there was no bias towards the two decision boundaries and the equal amount of evidence was

required for a correct and incorrect decision. This was because the participants did not have *a*

priori knowledge about the correct alternative at the beginning of each trial.

We generated 15,000 samples from the joint posterior distribution of all model parameters by using

MCMC sampling (Gamerman & Lopes, 2006). The initial 7,000 samples were discarded as burn-

in for stable posterior estimates. Geweke diagnostic (Cowles & Carlin, 1996) and autocorrelation

were used to assess the convergence of the Markov chains in the last 8,000 samples. All parameter

estimates were converged after 15,000 samples.

Data analysis

First, we used both Bayesian and frequentist repeated-measures ANOVA to make inferences on

behavioural measures (JASP Team, 2018). For frequentist ANOVAs, Greenhouse-Geisser

correction was applied when the assumption of sphericity was violated. For Bayesian ANOVAs,

we followed the standard heuristic to characterize the strength of evidence based on the Bayes

factor (BF_{10}) (Wagenmakers, Lee, Lodewyckx, & Iverson, 2008), which can provide evidence

supporting either null ($BF_{10} < 1$) or alternative ($BF_{10} > 1$) hypotheses. A BF_{10} between [1, 3] (or [0,

1/3]) suggests week evidence for the alternative (or null) hypothesis. A BF_{10} between [3, 10] (or

[1/10, 1/3]) suggests moderate or compelling evidence for the alternative (or null) hypothesis. A

BF_{10} larger than 10 (or smaller than 1/10), suggests strong evidence for the alternative (or null)

hypothesis.

Second, to quantify the difference of RT distributions between response modalities, we used the

Kolmogorov-Smirnov test (Pratt & Gibbons, 1981), a non-parametric statistical measure of

difference between two one-dimensional empirical distributions.

Third, to compare a fitted DDM parameter between two conditions (e.g., between response

modalities or between task difficulties), we used Bayesian hypothesis testing (Bayarri & Berger,

2004; Gelman et al., 2014; Kruschke, 2015; Lindley, 1965) to make inferences from the posterior

parameter distributions, under the null hypothesis that the parameter value is equal between the

two conditions.

More specifically, we first calculated the distribution of the parameter difference from the two

MCMC chains of the two conditions, and we obtained the 95% highest density interval (HDI) of

that difference distribution between the two conditions. We then set a region of practical

equivalence (ROPE) around the null value (i.e., 0 for the null hypothesis), which encloses the

values of the posterior difference that are deemed to be negligible from the null value 0 (Kruschke,

2013). In each Bayesian inference, the ROPE was set empirically from the two MCMC chains of

the two conditions under comparison. For each of the two conditions, we calculated the 95% HDI

of the difference distribution between odd and even samples from that condition's MCMC chain.

This 95% HDI from a single MCMC chain can be considered as negligible values around the null,

because posterior samples from different portions of the same chain are representative values of

the same parameter. That is, we accepted that the null hypothesis is true when comparing the

difference between odd and even samples from the same MCMC chain. The ROPE was then set

to the widest boundaries of the two 95% HDIs of the two conditions.

From the 95% HDI of the difference distribution and the ROPE, a Bayesian P-value was

calculated. To avoid confusion, we used p to refer to classical frequentist p-values, and $P_{p|D}$ to refer

to Bayesian P-values based on posterior parameter distributions. If ROPE is completely contained

within 95% HDI, $P_{p|D} = 1$ and we accept the null hypothesis (i.e., the parameter values are equal

between the two conditions). If ROPE is completely outside 95% HDI, $P_{p|D} = 0$ and we reject the

null hypothesis (i.e., the parameter values differ between the two conditions). If ROPE and 95%

HDI partially overlap, $P_{p|D}$ equals to the proportion of the 95% HDI that falls within the ROPE,

which indicates the probability that the parameter value is *practically* equivalent between the two

conditions (Kruschke & Liddell, 2018).

Results

Behavioural results

The behavioural performance of the four-alternative motion discrimination task was quantified by

accuracy (proportion of correct responses, Figure 2A) and mean reaction time (RT, Figure 2B).

We compared the behavioural performance between response modalities (joystick or keyboard),

task difficulties (easy or difficult) and motion directions (up, down, left or right) using three-way

Bayesian and frequentist repeated-measure ANOVAs. Across the two response modalities,

participants showed decreased accuracy ($BF_{10} = 5.112 \times 10^{30}$; $F(1,20) = 292.709$, $p < 0.001$) and

increased mean RT ($BF_{10} = 1.458 \times 10^{18}$; $F(1,20) = 63.163$, $p < 0.001$) in the more difficult

condition. There was compelling evidence against the main effect of response modality on

accuracy ($BF_{10} = 0.124$; $F(1,20) = 0.083$, $p = 0.776$) and weak evidence against the main effect of

response modality on mean RT ($BF_{10} = 0.560$; $F(1,20) = 0.495$, $p = 0.490$). These results indicated

similar behavioural performance between joystick and keyboard responses.

When comparing the behavioural performance between motion directions, there was compelling

evidence against the main effect on accuracy ($BF_{10} = 0.185$; $F(2.248, 44.961) = 0.107$, $p = 0.357$).

On mean RT, the frequentist ANOVA suggested a significant main effect of motion direction

($F(2.853, 57.052) = 3.021$, $p = 0.039$), but this results was supported by neither post-hoc tests

($p > 0.139$ in all post-hoc comparisons, Bonferroni corrected) or Bayesian ANOVA ($BF_{10} = 0.305$).

Furthermore, there was a significant interaction on accuracy between task difficulty and motion

direction ($F(2.586, 51.718) = 6.317$, $p = 0.002$), although this was again not supported by Bayesian

analysis ($BF_{10} = 0.299$). There was evidence against all the other interactions on accuracy ($BF_{10} <$

0.179; $p > 0.228$) and mean RT ($BF_{10} < 0.199$; $p > 0.083$).

The results above suggested no systematic bias at the group level when comparing responses from

a joystick and a keyboard. However, the consistency of behavioural performance between response

modalities could vary between participants. For experiments with multiple response modalities,

the researcher may want to confirm whether the consistency between response modalities is

maintained across experimental conditions. This would allow, for example, a pre-screening

procedure to identify participants with high response consistency to be recruited for further

experiments. Here, we used Kolmogorov-Smirnov (K-S) statistics to quantify the difference of

individual participant's RT distributions between the joystick and keyboard sessions in each

difficulty condition, separately for correct and incorrect trials. There was strong evidence of a

positive correlation between the K-S statistics of the easy and difficult conditions (correct trials:

$BF_{10} = 3.647 \times 10^6$, $R = 0.92$, $p < 0.001$; incorrect trials: $BF_{10} = 4526.00$, $R = 0.82$, $p < 0.001$)

(Figure 2C). Therefore, the difference in behavioural performance between response modalities

was consistent within participants across difficulty levels.

Hierarchical drift-diffusion model analyses

To compare the underlying decision-making process between joystick and keyboard responses, we

simplified the four-alternative motion discrimination task to a binary decision task (Churchland et

al., 2008; see also "Drift-diffusion model" section) and fitted the drift-diffusion model (DDM) to

the behavioural data using the hierarchical DDM (HDDM) toolbox (Wiecki et al., 2013). The

DDM decomposed individual participant's behavioural data into model parameters of latent

psychological processes, and the HDDM toolbox allowed to estimate the joint posterior estimates

of model parameters using hierarchical Bayesian approaches. To evaluate the model fit, we

generated model predictions by simulations from the posterior estimates of the model parameters.

There was a good agreement between the observed data and the model simulations across response

modalities, task difficulties and motion direction (Figure 3).

With no *a priori* knowledge on the effect of response modality on the decision-making process,

we allowed all model parameters to vary between joystick and keyboard responses: the boundary

separation a, the mean drift rate v, the mean non-decision time T_{er}, the trial-by-trial variability of

drift rate s_v, and the trial-by-trial variability of non-decision time s_t (Table 1). The mean drift rate

was further allowed to vary between task difficulties and motion directions. We performed

Bayesian hypothesis testing on the posterior parameter estimates between response modalities

(Bayarri & Berger, 2004; Gelman et al., 2014; Kruschke, 2015; Lindley, 1965). This analysis

yielded 95% HDI of the parameter difference between the joystick and keyboard sessions, as well

as Bayesian P-values $P_{P/D}$ (see "Data analysis" section for details).

For all the model parameters, we could not reject the null hypothesis that the posterior parameter

estimates are practically equal between the joystick and keyboard sessions. The $P_{P/D}$, which

quantifies the probability that the model parameter is practically equal between the two conditions,

ranged from 0.641 to 0.964 (Table 1). Therefore, there was no evidence to support that switching

from keyboard to joystick altered the decision-making process. Next, because the mean drift rate

is often assumed to increase with decreased task difficulty (Ratcliff & McKoon, 2008), we

compared the drift rate averaged from the joystick and keyboard sessions between easy and

difficult conditions. As expected, the drift rate was larger in the easy compared with the difficult

condition in all motion directions (up: 95% HDI = [0.589, 1.613], $P_{P/D}$=0; down: 95% HDI =

[0.930, 1.958], $P_{P/D}$=0; left: 95% HDI = [1.204, 2.227], $P_{P/D}$=0; right: 95% HDI = [1.185, 2.214],

$P_{P/D}$=0).

Additional measures from joystick trajectories

In the joystick session, the participants' movement trajectories were close to the four cardinal

directions (Figure 4A). Continuous movements with the joystick enabled to acquire additional

trial-by-trial behavioural measures beyond that possible from simple key presses. We examined

three such measures: peak velocity (Figure 4B), acceleration time (Figure 4C) and trajectory length

(Figure 4D). These additional joystick measures were subsequent to accuracy and RT. In the

current study, we did not expect them to have critical influence on the two primary behavioural

measures. Hence our analyses were focused on the effects of movement direction and task

difficulty on the trajectory measures. However, we acknowledged that, in experiments with more

complex movement trajectories, decisions may be more directly coupled to continuous motor

responses (Song & Nakayama, 2009).

We calculated the action velocity as the rate of changes of joystick position. There was a single

peak of action velocity in each trial, consistent with the ballistic nature of the movement. There

was strong evidence for the main effect of response direction on the peak velocity (Figure 5B, BF_{10}

$= 3.900 \times 10^{24}$, $F(2.000, 40.002) = 39.25$, $p < 0.001$), moderate evidence for the main effect of

difficulty ($BF_{10} = 4.612$, $F(1,20) = 22.70$, $p < 0.001$) and strong evidence for the interaction

between direction and difficulty ($BF_{10} = 58.433$, $F(2.841,56.813) = 30.58$, $p < 0.001$).

We calculated the acceleration time as the latency between the RT and the time of peak velocity

(Figure 5C). There was strong evidence for the main effect of response direction ($BF_{10} = 1147.376$,

$F(2.253, 45.05) = 4.741$, $p = 0.011$). We found moderate evidence against difficulty level ($BF_{10} =$

0.172, $F(1,20) = 0.178$, $p = 0.677$). Frequentist ANOVA showed a significant interaction between

the response direction and difficulty levels ($F(2.853, 57.053) = 4.470$, $p = 0.008$), which was not

supported by the Bayes factor ($BF_{10} = 0.256$).

We calculated the trajectory length as the sum of the Euclidean distance between adjacent joystick

positions in each trial (Figure 5D). There was no compelling evidence for the main effect of

response direction on trajectory length ($BF_{10} = 1.759$; $F(3, 60) = 1.944$, $p = 0.151$), nor the main

effect of task difficulty ($BF_{10} = 0.450$, $F(1, 20) = 3.171$, $p = 0.09$). The evidence against the

interaction between direction and difficulty was strong ($BF_{10} = 0.090$, $F(3, 60) = 0.978$, $p = 0.409$).

In summary, the peak action velocity of joystick movements was affected by both action direction

and task difficulty, and acceleration time was affected only by trajectory direction. There was no

compelling evidence to support that trajectory length was affected by action direction or task

difficulty.

Discussion

The current study systematically compared the consistency between continuous and discrete

responses during rapid decision-making. In a four-alternative motion discrimination task, joystick

movements and key presses led to similar accuracy and mean RT. Further modelling analysis with

hierarchical DDM showed no evidence in supporting a change of any model parameters between

response modalities. Together, our findings provide evidence for the validity of using continuous

joystick movement as a reliable response modality in behavioural experiments.

Behavioural measures

In both joystick and keyboard sessions, participants had lower accuracy and longer mean RT in

the more difficult condition (i.e., lower motion coherence), in line with previous findings with

similar tasks (Britten et al., 1992; Pilly & Seitz, 2009; Ramachandran & Anstis, 1983; Roitman &

Shadlen, 2002). Using Bayesian statistics, we found evidence that response modality (joystick

motion or key press) did not affect either accuracy or mean RT, confirming the validity of using

joystick as a response device in decision-making tasks. Importantly, across participants, the

difference in the RT distributions between response modalities was positively correlated between

easy and difficult conditions. Therefore, participants with similar behavioural performance

between response modalities maintained their consistency between experimental conditions.

Joystick positions estimated at a high sampling rate enabled additional behavioural measures

beyond on/off key presses. In the current study, most of the movement trajectories were along the

four cardinal directions (Figure 5A). The averaged trajectory length was close to 1 (Figure 5D),

which was the shortest distance from the joystick's neutral position to the maximum range,

suggesting that the participants were able to make accurate and ballistic movements following the

task instruction. Nevertheless, it is worth noting that the movement direction affected the peak

velocity and acceleration time. This may be due to the difference in upper limb muscle contractions

when moving the joystick towards different directions (Oliver, Northey, Murphy, MacLean, &

Sexsmith, 2011). Therefore, for future behavioural experiments relying on sensitive trajectories

measures, we suggest extra cautious on the effects of ergonomics and human motor physiology,

especially for rapid movements as in the current study. One potential solution would be to acquire

baseline recordings of the movement to be expected during the experiment, which can then be used

to compensate measurement biases.

Model-based measures

The DDM and other sequential sampling models are commonly used to investigate the cognitive

processes underlying rapid decision-making (Bogacz et al., 2006; Smith & Ratcliff, 2004). In the

current study, the mean drift rate increased in the easier task condition, consistent with previous

modelling results (Ratcliff & McKoon, 2008). The combination of posterior parameter estimation

and Bayesian inference allowed us to obtain the probability of the parameter being practically

equal, a more informative measure than frequentist *p*-values (Kruschke, 2015). Although our

results suggested that most parameter values had high probabilities to remain the same between

response modalities (Table 1), we could not accept the null hypothesis for certain (which requires

$P_{P/D} = 1$) and need more data to confirm the inference.

We highlighted two model parameters with low $P_{P/D}$ values, which indicate that, with additional

observed data from future experiments, the posterior model parameters might be in favour of the

alternative hypothesis (i.e., a difference between response modalities). First, when switching from

key presses to joystick movements, there was a small increase in the mean non-decision time ($P_{P/D}$

= 0.658). Second, responding with a joystick resulted in a slightly decreased decision threshold

($P_{P/D}$ = 0.872). Several previous studies showed that instructing to respond faster or more

accurately could efficiently modulate participants' behaviour (Beersma et al., 2003; Schouten &

Bekker, 1967; Wickelgren, 1977). The decision threshold plays a substantial role under such

speed-accuracy instructions (Mulder et al., 2013; Rae, Heathcote, Donkin, Averell, & Brown,

2014; Ratcliff & McKoon, 2008; Starns & Ratcliff, 2014; Zhang & Rowe, 2014): a decrease of

threshold is accompanied with faster reaction speed and lower accuracy. If participants do

implicitly trade accuracy for speed when switching from keyboard to joystick movements, this

cognitive discrepancy needs to be considered when conducting experiments involving continuous

responses. One hypothesis for this potential behavioural change is that continuous joystick

movements allow participants to change or correct their responses later in a trial (Albantakis &

Deco, 2009; Gallivan & Chapman, 2014; Gallivan, Logan, Wolpert, & Flanagan, 2016; Selen,

Shadlen, & Wolpert, 2012), and this response flexibility may lead to reduced deliberation in initial

movements.

Future directions

Three issues require further consideration. First, we only used a joystick to record movement

trajectories, which is commonly used and widely available in behavioural testing labs. There are

many other devices capable for recording continuous responses, such as computer mouse (e.g.

Koop & Johnson, 2011), optic motion sensor (e.g. Chapman et al., 2010) and robotic arms

(Abrams, Meyer, & Kornblum, 1990; Archambault, Caminiti, & Battaglia-Mayer, 2009; Berg et

al., 2016; Burk, Ingram, Franklin, Shadlen, & Wolpert, 2014; Resulaj et al., 2009). The current

study offered a comprehensive comparison between key presses and joystick movements, but the

measures from other devices are yet to be validated. We also offered a practical solution to measure

RT from joystick movement comparable to that from key presses, taking in to account the small

resistive forces near the joystick's neural position. To facilitate future research, we have made our

data and analysis scripts openly available (https://osf.io/6fpq4).

Second, we instructed participants to make directional movements in the joystick session, which

allows for intra-individual comparisons between response modalities. Motion trajectories

suggested that the participants mainly made ballistic actions towards one of the four cardinal

directions (Figure 5A). One could explore the further potential of continuous responses in

behavioural tasks, such as in response to the change of mind (Berg et al., 2016; Burk et al., 2014;

Resulaj et al., 2009) or external distractions (Gallivan & Chapman, 2014).

Third, the DDM required the behavioural data to be presented as binary choices (Ratcliff &

McKoon, 2008). To meet this constraint, we simplified our four-choice task data into correct and

incorrect decisions, and incorrect responses contained errors towards three different directions

from the correct motion direction. Although our modelling results provided a good fit to the

observed data, it would be useful to extend the analysis using other models that are designed for

decision problems with multiple alternatives (Brown & Heathcote, 2008; Usher & McClelland,

2001; Wong & Wang, 2006), although a hierarchical Bayesian implementation of those more

complex models is beyond the scope of the current study.

In conclusion, our results validated the joystick as a reliable device for continuous responses during

rapid decision-making. Compared with key presses, the additional complexity and continuity

associated with joystick movements did not affect raw behavioural measures such as accuracy and

mean RT, as well as underlying decision-making processes. However, we highlighted the effects

of movement direction on continuous trajectory measures. Researchers should be cautious when

adopting experimental designs that require complex movement trajectories.

References

Abrams, R. A., Meyer, D. E., & Kornblum, S. (1990). Eye-hand coordination: Oculomotor control in rapid aimed limb movements. *Journal of Experimental Psychology: Human Perception and Performance*, *16*, 248–267.

Acerbi, L., Vijayakumar, S., & Wolpert, D. M. (2017). Target Uncertainty Mediates Sensorimotor Error Correction. *PLOS ONE*, *12*, e0170466.

Albantakis, L., & Deco, G. (2009). The encoding of alternatives in multiple-choice decision making. *Proceedings of the National Academy of Sciences*, *106*, 10308–10313.

Archambault, P. S., Caminiti, R., & Battaglia-Mayer, A. (2009). Cortical Mechanisms for Online Control of Hand Movement Trajectory: The Role of the Posterior Parietal Cortex. *Cerebral Cortex*, *19*, 2848–2864.

Bayarri, M. J., & Berger, J. O. (2004). The Interplay of Bayesian and Frequentist Analysis. *Statistical Science*, *19*, 58–80.

Beersma, B., Hollenbeck, J. R., Humphrey, S. E., Moon, H., Conlon, D. E., & Ilgen, D. R. (2003). COOPERATION, COMPETITION, AND TEAM PERFORMANCE: TOWARD A CONTINGENCY APPROACH. *Academy of Management Journal*, *46*, 572–590.

Berg, R. van den, Anandalingam, K., Zylberberg, A., Kiani, R., Shadlen, M. N., & Wolpert, D. M. (2016). A common mechanism underlies changes of mind about decisions and confidence. *ELife*, *5*, e12192.

Bogacz, R., Brown, E., Moehlis, J., Holmes, P., & Cohen, J. D. (2006). The physics of optimal decision making: A formal analysis of models of performance in two-alternative forced-choice tasks. *Psychological Review*, *113*, 700–765.

489   Bompas, A., Hedge, C., & Sumner, P. (2017). Speeded saccadic and manual visuo-motor

490   decisions: Distinct processes but same principles. *Cognitive Psychology*, *94*, 26–52.

491   Britten, K. H., Shadlen, M. N., Newsome, W. T., & Movshon, J. A. (1992). The analysis of visual

492   motion: a comparison of neuronal and psychophysical performance. *The Journal of*

493   *Neuroscience*, *12*, 4745–4765.

494   Brown, S. D., & Heathcote, A. (2008). The simplest complete model of choice response time:

495   Linear ballistic accumulation. *Cognitive Psychology*, *57*, 153–178.

496   Burk, D., Ingram, J. N., Franklin, D. W., Shadlen, M. N., & Wolpert, D. M. (2014). Motor Effort

497   Alters Changes of Mind in Sensorimotor Decision Making. *PLOS ONE*, *9*, e92681.

498   Chapman, C. S., Gallivan, J. P., Wood, D. K., Milne, J. L., Culham, J. C., & Goodale, M. A.

499   (2010). Reaching for the unknown: Multiple target encoding and real-time decision-

500   making in a rapid reach task. *Cognition*, *116*, 168–176.

501   Churchland, A. K., Kiani, R., & Shadlen, M. N. (2008). Decision-making with multiple

502   alternatives. *Nature Neuroscience*, *11*, 693–702.

503   Cisek, P., & Kalaska, J. F. (2005). Neural Correlates of Reaching Decisions in Dorsal Premotor

504   Cortex: Specification of Multiple Direction Choices and Final Selection of Action. *Neuron*,

505   *45*, 801–814.

506   Cowles, M. K., & Carlin, B. P. (1996). Markov Chain Monte Carlo Convergence Diagnostics: A

507   Comparative Review. *Journal of the American Statistical Association*, *91*, 883–904.

508   Fredericksen, R. E., Verstraten, F. A. J., & Van De Grind, W. A. (1994). Temporal integration of

509   random dot apparent motion information in human central vision. *Vision Research*, *34*,

510   461–476.

Freeman, J. B., Dale, R., & Farmer, T. A. (2011). Hand in Motion Reveals Mind in Motion.

Frontiers in Psychology, *2*.

Gallivan, J. P., & Chapman, C. S. (2014). Three-dimensional reach trajectories as a probe of real-

time decision-making between multiple competing targets. *Frontiers in Neuroscience*, *8*.

Gallivan, J. P., Logan, L., Wolpert, D. M., & Flanagan, J. R. (2016). Parallel specification of

competing sensorimotor control policies for alternative action options. *Nature*

Neuroscience, *19*, 320–326.

Gamerman, D., & Lopes, H. F. (2006). *Markov chain Monte Carlo stochastic simulation for*

Bayesian inference. Boca Raton: Taylor & Francis.

Gelman, A., Carlin, J. B., Stern, H. S., Dunson, D. B., Vehtari, A., & Rubin, D. B. (2014). *Bayesian*

data analysis.

Gold, J. I., & Shadlen, M. N. (2007). The neural basis of decision making. *Annual Review of*

Neuroscience, *30*, 535–74.

Hanks, T., Kiani, R., & Shadlen, M. N. (2014). A neural mechanism of speed-accuracy tradeoff in

macaque area LIP. *ELife*, *3*, e02260.

Heekeren, H. R., Marrett, S., & Ungerleider, L. G. (2008). The neural systems that mediate human

perceptual decision making. *Nature Reviews Neuroscience*, *9*, 467–479.

Ho, T. C., Brown, S., & Serences, J. T. (2009). Domain General Mechanisms of Perceptual

Decision Making in Human Cortex. *Journal of Neuroscience*, *29*, 8675–8687.

Huk, A. C., & Shadlen, M. N. (2005). Neural Activity in Macaque Parietal Cortex Reflects

Temporal Integration of Visual Motion Signals during Perceptual Decision Making. *The*

Journal of Neuroscience, *25*, 10420–10436.

JASP Team. (2018). *JASP (Version 0.8.6)*.

Koop, G. J., & Johnson, J. G. (2011). Response dynamics: A new window on the decision process.

Judgment and Decision Making, *6*, 750.

Kruschke, J. K. (2013). Bayesian estimation supersedes the t test. *Journal of Experimental*

Psychology: General, *142*, 573–603.

Kruschke, J. K. (2015). *Doing Bayesian data analysis: a tutorial with R, JAGS, and stan* (2E

[edition]). Boston: Academic Press.

Kruschke, J. K., & Liddell, T. M. (2018). The Bayesian New Statistics: Hypothesis testing,

estimation, meta-analysis, and power analysis from a Bayesian perspective. *Psychonomic*

Bulletin & Review, *25*, 178–206.

Lappin, J. S., & Bell, H. H. (1976). The detection of coherence in moving random-dot patterns.

Vision Research, *16*, 161–168.

Limousin, P., Greene, J., Pollak, P., Rothwell, J., Benabid, A.-L., & Frackowiak, R. (1997).

Changes in cerebral activity pattern due to subthalamic nucleus or internal pallidum

stimulation in Parkinson's disease. *Annals of Neurology*, *42*, 283–291.

Lindley, D. V. (1965). *Introduction to probability and statistics from a Bayesian point of view,*

Part 2, Inference.

Mulder, M. J., Keuken, M. C., Maanen, L., Boekel, W., Forstmann, B. U., & Wagenmakers, E.-J.

(2013). The speed and accuracy of perceptual decisions in a random-tone pitch task.

Attention, Perception, & Psychophysics, *75*, 1048–1058.

O'Hora, D., Dale, R., Piiroinen, P. T., & Connolly, F. (2013). Local dynamics in decision making:

The evolution of preference within and across decisions. *Scientific Reports*, *3*.

555 Oliver, M. L., Northey, G. W., Murphy, T. A., MacLean, A., & Sexsmith, J. R. (2011). Joystick

556   stiffness, movement speed and direction effects on upper limb muscular loading.

557   *Occupational Ergonomics*, *10*, 175–187.

558 Peirce, J. W. (2008). Generating stimuli for neuroscience using PsychoPy. *Frontiers in*

559   *Neuroinformatics*, *2*.

560 Pilly, P. K., & Seitz, A. R. (2009). What a difference a parameter makes: A psychophysical

561   comparison of random dot motion algorithms. *Vision Research*, *49*, 1599–1612.

562 Pratt, J. W., & Gibbons, J. D. (1981). Kolmogorov-Smirnov Two-Sample Tests. In J. W. Pratt &

563   J. D. Gibbons, *Concepts of Nonparametric Theory* (pp. 318–344). New York, NY: Springer

564   New York.

565 Rae, B., Heathcote, A., Donkin, C., Averell, L., & Brown, S. (2014). The hare and the tortoise:

566   Emphasizing speed can change the evidence used to make decisions. *Journal of*

567   *Experimental Psychology: Learning, Memory, and Cognition*, *40*, 1226–1243.

568 Ramachandran, V. S., & Anstis, S. M. (1983). Displacement thresholds for coherent apparent

569   motion in random dot-patterns. *Vision Research*, *23*, 1719–1724.

570 Ratcliff, R., & Childers, R. (2015). Individual differences and fitting methods for the two-choice

571   diffusion model of decision making. *Decision*, *2*, 237–279.

572 Ratcliff, R., & McKoon, G. (2008). The diffusion decision model: theory and data for two-choice

573   decision tasks. *Neural Computation*, *20*, 873–922.

574 Ratcliff, R., & Smith, P. L. (2004). A Comparison of Sequential Sampling Models for Two-Choice

575   Reaction Time. *Psychological Review*, *111*, 333–367.

576 Ratcliff, R., Smith, P. L., Brown, S. D., & McKoon, G. (2016). Diffusion Decision Model: Current

577   Issues and History. *Trends in Cognitive Sciences*, *0*.

Resulaj, A., Kiani, R., Wolpert, D. M., & Shadlen, M. N. (2009). Changes of mind in decision-

making. *Nature*, *461*, 263–266.

Roitman, J. D., & Shadlen, M. N. (2002). Response of Neurons in the Lateral Intraparietal Area

during a Combined Visual Discrimination Reaction Time Task. *The Journal of*

Neuroscience, *22*, 9475–9489.

Schouten, J. F., & Bekker, J. A. M. (1967). Reaction time and accuracy. *Acta Psychologica*, *27*,

143–153.

Selen, L. P. J., Shadlen, M. N., & Wolpert, D. M. (2012). Deliberation in the Motor System: Reflex

Gains Track Evolving Evidence Leading to a Decision. *Journal of Neuroscience*, *32*, 2276–

2286.

Shadlen, M. N., & Newsome, W. T. (2001). Neural Basis of a Perceptual Decision in the Parietal

Cortex (Area LIP) of the Rhesus Monkey. *Journal of Neurophysiology*, *86*, 1916–1936.

Smith, P. L., & Ratcliff, R. (2004). Psychology and neurobiology of simple decisions. *Trends in*

Neurosciences, *27*, 161–168.

Song, J.-H., & Nakayama, K. (2009). Hidden cognitive states revealed in choice reaching tasks.

Trends in Cognitive Sciences, *13*, 360–366.

Spivey, M. J., Grosjean, M., & Knoblich, G. (2005). Continuous attraction toward phonological

competitors. *Proceedings of the National Academy of Sciences of the United States of*

America, *102*, 10393–10398.

Starns, J. J., & Ratcliff, R. (2014). Validating the unequal-variance assumption in recognition

memory using response time distributions instead of ROC functions: A diffusion model

analysis. *Journal of Memory and Language*, *70*, 36–52.

Strafella, A. P., Dagher, A., & Sadikot, A. F. (2003). Cerebral blood flow changes induced by subthalamic stimulation in Parkinson's disease. *Neurology*, *60*, 1039–1042.

Usher, M., & McClelland, J. L. (2001). The time course of perceptual choice: The leaky, competing accumulator model. *Psychological Review*, *108*, 550–592.

Vandekerckhove, J., Tuerlinckx, F., & Lee, M. D. (2011). Hierarchical diffusion models for two-choice response times. *Psychological Methods*, *16*, 44–62.

Wagenmakers, E.-J. (2009). Methodological and empirical developments for the Ratcliff diffusion model of response times and accuracy. *European Journal of Cognitive Psychology*, *21*, 641–671.

Wagenmakers, E.-J., Lee, M., Lodewyckx, T., & Iverson, G. J. (2008). Bayesian versus frequentist inference. In *Bayesian evaluation of informative hypotheses* (pp. 181–207). Springer.

Watamaniuk, S. N. J., Sekuler, R., & Williams, D. W. (1989). Direction perception in complex dynamic displays: The integration of direction information. *Vision Research*, *29*, 47–59.

Wessel, K., Verleger, R., Nazarenus, D., Vieregge, P., & Kömpf, D. (1994). Movement-related cortical potentials preceding sequential and goal-directed finger and arm movements in patients with cerebellar atrophy. *Electroencephalography and Clinical Neurophysiology/Evoked Potentials Section*, *92*, 331–341.

Wickelgren, W. A. (1977). Speed-accuracy tradeoff and information processing dynamics. *Acta Psychologica*, *41*, 67–85.

Wiecki, T. V., Sofer, I., & Frank, M. J. (2013). HDDM: Hierarchical Bayesian estimation of the Drift-Diffusion Model in Python. *Frontiers in Neuroinformatics*, *7*.

Wong, K.-F., & Wang, X.-J. (2006). A Recurrent Network Mechanism of Time Integration in Perceptual Decisions. *The Journal of Neuroscience*, *26*, 1314–1328.

Zhang, J., Hughes, L. E., & Rowe, J. B. (2012). Selection and inhibition mechanisms for human

voluntary action decisions. *NeuroImage*, *63*, 392–402.

Zhang, J., Rittman, T., Nombela, C., Fois, A., Coyle-Gilchrist, I., Barker, R. A., … Rowe, J. B.

(2016). Different decision deficits impair response inhibition in progressive supranuclear

palsy and Parkinson's disease. *Brain*, *139*, 161–173.

Zhang, J., & Rowe, J. B. (2014). Dissociable mechanisms of speed-accuracy tradeoff during visual

perceptual learning are revealed by a hierarchical drift-diffusion model. *Frontiers in*

Neuroscience, *8*.

Table 1. Posterior estimates of the hierarchical drift-diffusion model parameters (decision threshold a, mean drift rate v, non-decision time T_{er}, trial-by-trial drift rate variability s_v, trial-by-trial non-decision time variability s_t). The first two data columns showed the posterior means and standard deviations of the parameters in the joystick and keyboard sessions. 95% HDI denoted the 95% highest density intervals for the parameter difference between the joystick and keyboard sessions. $P_{P|D}$ denoted the Bayesian P-value for the parameter difference being equal between response modalities.

			Joystick (mean ± sd)	Keyboard (mean ± sd)	95% HDI	$P_{P|D}$
a			1.508 ± 0.072	1.572 ± 0.073	[-0.270, 0.120]	0.872
v	Easy	Up	1.694 ± 0.263	1.269 ± 0.260	[-0.300, 1.144]	0.720
		Down	1.765 ± 0.264	1.454 ± 0.261	[-0.460, 0.999]	0.810
		Left	2.169 ± 0.267	1.906 ± 0.260	[-0.450, 1.020]	0.789
		Right	2.351 ± 0.267	2.187 ± 0.262	[-0.580, 0.880]	0.863
	Difficult	Up	0.477 ± 0.257	0.291 ± 0.263	[-0.526, 0.896]	0.866
		Down	0.144 ± 0.262	0.202 ± 0.256	[-0.822, 0.603]	0.932
		Left	0.441 ± 0.261	0.216 ± 0.257	[-0.529, 0.909]	0.854
		Right	0.533 ± 0.263	0.597 ± 0.261	[-0.769, 0.685]	0.964
T_{er}			0.613 ± 0.028	0.556 ± 0.028	[-0.025, 0.130]	0.658
s_v			0.992 ± 0.047	0.916 ± 0.042	[-0.039, 0.203]	0.669
s_t			0.268 ± 0.007	0.283 ± 0.007	[-0.035, 0.004]	0.641

Figure 1.

Figure 1. Behavioural paradigm and the drift-diffusion model (DDM). (**A**) The structure of a single trial of the experiment. A fixation screen was presented for 400 ms, after which the random-dot kinematogram was presented for a maximum of 3000 ms or until response. The inter-trial interval was randomised between 1000 and 1400 ms. Participants were instructed to indicate the direction of the coherent motion direction (0°, 90°, 180° or 270°) using joystick or keyboard in two counterbalanced sessions. (**B**) The drift-diffusion model and examples of evidence accumulation trajectories. The parameter (*a*) indicates the distance between the correct and incorrect decision thresholds. The drift rate (*v*) represents the speed of evidence accumulation and its magnitude is determined by the quality of the evidence. A positive *v* indicates that, on average, the accumulation of sensory evidence is towards the correct decision threshold. The starting point (*z*) represents the response bias towards one of the two thresholds. The non-decision time (T_{er}) represents the latencies of non-decision processes, which is illustrated besides the decision time distribution in the figure. The diffusion process starts at the starting point (*z*) until the accumulated evidence reaches one of the two thresholds. If the accumulated evidence reaches the correct (upper)

threshold (blue trajectories), the model predicts a correct response. Because of noise, the

accumulated evidence may reach the incorrect (lower) threshold (red trajectories) and the model

predicts an incorrect response. The predicted single-trial RT is the sum of the duration of the

evidence accumulation (decision time) and the non-decision time T_{er}.

Figure 2.

Figure 2. Behavioural results in joystick and keyboard sessions. (**A**) Average decision accuracy

(proportion of correct) across participants. Error bars denote standard errors of the means. (**B**)

Average mean RT across participants. Error bars denote standard errors of the means. (**C**) The

Kolmogorov-Smirnov (K-S) statistics when comparing the RT distributions between response

modalities. The scatter plot showed the K-S statistics in the difficult condition as a function of the

that in the easy condition. Each data point represents the correct (filled data point) or incorrect

(open data point) trials of one participant. Linear regression lines were illustrated for correct (solid

line) and incorrect (dashed line) trials.

Figure 3.

A. Stimuli direction: up (90º)

B. Stimuli direction: down (270º)

C. Stimuli direction: left (180º)

D. Stimuli direction: right (0º)

Figure 3. Posterior predictive RT distributions from the fitted DDM. Each panel shows the

normalized histograms of the observed data (blue bars – correct responses, red bars – incorrect

responses) and the model prediction (black lines) across participants. The RT distribution along

the positive x-axis is from correct responses, and the areas under the curve on the positive x-axis

corresponds to the observed and predicted accuracy. The RT distribution along the negative x-axis

is from error responses, and the areas under the curve on the negative x-axis corresponds to the

observed and predicted error. The posterior predictions of the model were generated by averaging

500 simulations of the same amount of model predicted data as observed in the experiment using

posterior parameter estimates.

Figure 4.

Figure 4. Measures from joystick trajectories. (A) The summary of movement trajectories and

final positions. The heat map in the centre represents the proportion of the total joystick position

across trials and participants. The histogram on the edge represents the distribution of final

positions. (B) The peak velocity of joystick movements averaged across participants. (C) The mean

acceleration time of joystick movements averaged across participants (D) The mean trajectory

length averaged across participants. The error bars denote the standard errors of the means.