Natural selection subsumes and unites multiple theories of perceptual optimization

Victor Quintanar-Zilinskas*

*Address correspondence to: vquintanar@hotmail.com

Perceptual processing is thought to occur in two stages[1,2]: compression of the environment's information, followed by inference of the environment's state. While inference is believed to be Bayes-optimal[3-5], the model for optimal compression is comparatively less well-established: multiple signal processing frameworks have been used to explain empirical outcomes[1,2,6-8] and hypothesized to align with Darwinian fitness[1,2,7-9]. Here I endeavor to constrain the model space by framing fitness as a function of the compression scheme and optimizing fitness directly. I find that signal processing and fitness objectives often deviate; for example, in a finite game where risk-avoidant bet-hedging[10] beats maximization of average performance. However, when average performance determines fitness, then both are maximized by minimized cost-weighted signal distortion. Meanwhile, the signal processing metrics of estimation error and mutual information align with these latter objectives only under very specific circumstances. Taken together, my results establish a Darwinian (nested) hierarchy of perceptual compression objectives, which extends the existing understanding of optimal compression by incorporating not just signal processing but also economic frameworks, and reconciles the extant usages of the former by clarifying their respective domains of applicability. The cost-weighted distortion objective's evolutionary importance is additionally intriguing because this objective is potentially congruent with a broad set of experimental findings.

To evaluate the fitness of perceptual compression schemes, I employ a framework in which an organism: is presented with n items, perceives them through its perceptual interface[11], chooses one, and adds the item's utility value to its total lifetime utility score. Not all interfaces are equally fit: their fitness hinges on their effective mapping of high- and low-utility items to different percepts, thereby enabling low-utility choices to be avoided. Also, the interface represents a compression: multiple items are mapped to the same percept, possible real-world items outnumber the possible percepts, and the mapping does not fully preserve the details of an item's real-world attributes (Fig. 1A). Notably, this framework's discretization of choice options renders the compression amenable to formal mathematical parameterization, while its discretization of choice instances and utilities renders the compression's fitness consequences measureable. Despite these abstractions, the framework retains perception's fundamental relationship to fitness: the information it transmits to the organism informs actions[12].

In the present study, I apply the above framework across several decision-making environments, each characterized by a set of selection pressures and distribution of item utilities. In each environment, certain interface parameters, cast as alleles that are subject to selection, are shown to be more adaptive than others, and perhaps even optimal in that particular environment. The various congruencies revealed between selected-for parameterizations and well-known compression and decision strategies collectively provide an expanded understanding of perceptual processing in the natural world.

In environment one, fitness is linearly proportional to average decision utility, item utilities are a function of a subset of their real-world attribute values, and the values of each utility-relevant attribute are contained within the interval $[0,b_{a,1}]$, where a is the index of a specific attribute. In a version of this environment simplified even further, utility depends linearly on just one attribute

(in which case, I write $b_{a,1}$ as b_1), and item probability is uniform over the attribute space. In such a one-dimensional utility landscape, it is adaptive to associate percept boundaries with specific values of the utility-determining attribute, and assign all items between boundaries b_i and b_{i+1} to the same percept. Thus, an interface with β output bits divides the item space into $m = 2^\beta$ percepts P_i ($i = 1{:}m$), whose index indicates both the percept's ordinal desirability (relative to other percepts) and its upper boundary b_i. While b_1 is a constant, the other b_i ($i=2{:}m$) can be regarded as the alleles subject to selection.

In this environment, there is congruence between the utility maximization objective and the minimization of signal distortion, with the loss function being the compression's utility cost (details in Supplementary Equations, Part 1). These objectives are demonstrably equivalent in the general case of a β-bit interface and n item choices (Supplementary Equations, Part 2). They are also equivalent, when $\beta = 1$ and $n = 2$, on utility landscapes exhibiting simple deviations from the assumptions of 1) a linear attribute-utility relationship 2) uniformly probable item attribute values (Fig. 1b1 and 1b2; Supplementary Equations, Parts 3 and 4; respectively). Moreover, these results straightforwardly extend to multidimensional utility landscapes. The extension is trivial for an organism with an idealized interface[11] that can map items to percepts with infinite flexibility. If utilities are unitary (e.g. a weighted sum of attribute values), then the interface will in effect rearrange the items onto a unidimensional utility continuum (Fig. 1c, left). Alternatively, if the organism experiences a variety of situations, each corresponding to a different utility-determinative attribute, then each dimension individually can be optimally divided (Fig. 1c, right). Granted, real-world interfaces are often composites whose individual components (e.g., vision and olfaction) are constrained to processing a subset of item attributes (e.g., reflected wavelengths and emitted chemical compounds). Under such circumstances, the

utility and distortion loss objectives will dictate equivalent segmentations of individual

dimensions and, at least for a two-bit interface making binary decisions between items from a

two-dimensional utility space (Fig. 1d; Supplementary Equations, Part 5), an equivalent

assignment of interface bits to the available dimensions.

Notably, when I set $\beta = 1$ and $n > 2$, the utility and distortion loss objectives demonstrably

(Supplementary Equations, Part 6) diverge from the frequently-studied objectives of mutual

information maximization and utility estimation error minimization[13]. The latter two are favored

by selection with respect to neither items perceived nor items chosen; stated alternatively,

selection favors neither the optimization of perceptual accuracy nor of action outcome

prediction. Still, optimized action outcome prediction has been previously shown[3] to provide a

lower bound on utility obtained.

Environment two is mostly similar to environment one; the main differences, seemingly subtle,

are that fitness is determined by utility accumulated over a finite lifespan (duration measured in

decisions) rather than by average decision utility, and that after every generation, the fixed-size

population undergoes a membership refresh during which the lowest-utility members leave no

offspring. Additional key features of this environment: individual decisions depend on just one

attribute, the utility landscape is two-dimensional, and although $b_{1,1} \ll b_{2,1}$, decisions contingent

on attribute 2 are so rare that mean utility maximization dictates the allocation of both perceptual

bits to attribute 1. Organisms interact with this environment via a 2-bit interface configured to

either maximize mean utility ("optimal", Fig. 1d, right) or avoid large utility-harvesting failures

during those few decisions contingent on attribute 2 ("risk averse", Fig. 1d, left).

Simulations of competition between these interface strategy alleles (details in Methods) mostly

favor "optimal"; notably, all observed fixations of "risk averse" occur when reproduction is

restricted to the best-performing 20%, and this outcome is also favored by short organism

lifetimes (Table 1). Thus, the victories of "risk averse" can best be understood as successful bet-

hedges[10,14], defined as the sacrifice of maximized average performance in order to avoid

unacceptable risks (such as falling into the population's non-reproductive 80%), or as

demonstrations of the advantageousness of risk-taking in competitions that reward relative

standing[15,16]. These results show that when reproductive fitness deviates from linear dependence

on average decision utility, strong correspondence between distortion loss and fitness objectives

is still possible, but cannot be assumed.

In environments three through six, item utilities are not fixed in evolutionary memory; instead,

they must be experienced and learned. It is assumed that percept utilities are learned, and that

percept preference order is established, rapidly. It is further assumed, except when otherwise

noted, that average post-learning decision utility determines fitness. Environments three and four

consist of 100 items with randomly sampled utilities; the expected value derived from a

particular item-percept assignment is computed as described in Methods and Fig. 2.

Fitness in environment three is determined by the interface's extraction of value from

uncorrelated, randomly-valued items. The top plots of Fig. 2a reveal (for n > 9) that in this

endeavor there is a trade-off between pursuing large gains (black line) and steady gains (blue

line). (The bottom plots show that if mean item utility is high, then reward is reliably available

and the trade-off is mitigated or even eliminated.) Fig. 2b illustrates the genesis of this trade-off;

it clarifies why the pursuit of large gain potential from one percept comes at the cost of

decreased gain potential from the other, and in turn suggests that unbalanced percepts deliver

low geometric mean utility because their pursuit of utility is undiversified[17]. The ultimate

advantageousness of these alternative reward pursuit strategies depends on whether the

environment selects for arithmetic or geometric mean utility maximization; thus, as in environment two, bet-hedging perception is potentially favored over utility-maximizing perception.

In environment four, meanwhile, item utilities are correlated: specifically, they belong to one of two clusters. I find (Fig. 2c) that even when within-cluster utility variation appreciably exceeds between-cluster variation, assigning the clusters to distinct percepts (red lines) delivers greater mean utility, arithmetic and geometric, than does splitting each cluster's items evenly between the percepts (black lines). The latter strategy is potentially advantageous only if items from one of the clusters are very rarely encountered (blue lines), in which case environment four approximates environment three.

Environment five's similarities to the simplest version of the first are that one attribute determines utility and that utility declines linearly from the peak-utility attribute value; what differs is that the utility peak, instead of being fixed, now assumes a random value within the interval $[0,b_1]$, or else within $[-\pi,\pi]$ if the attribute space is radial rather than linear. Notably, the randomization of the utility peak can bring the estimation error objective into alignment with the utility and distortion loss objectives. More specifically, the three objectives align in the linear attribute space when $\beta = 1$ or $n = 2$ and in the radial attribute space for general β and n (Supplementary Equations, Part 7), and remain aligned in the radial attribute space (if $n = 2$) even when the probability distribution of items across the utility space is non-uniform (Supplementary Equations, Part 8).

The significance of these results comes into focus upon considering a more biologically realistic formulation of environment five (and four), in which the organism encounters a multiplicity of decision situations, each with a unique utility-maximizing attribute value (or, unique item cluster

utilities). If environment one demonstrated that natural selection favors the selective recognition of an environment's highest-utility items, then these results demonstrate that natural selection favors estimation accuracy across all items when all items have the potential to (sometimes) be the environment's highest-utility item. On that note (Supplementary Equations, Part 8), efficient coding of the attribute space may sometimes be more adaptive than efficient coding of the environment's item distribution; just because certain items are common doesn't mean that differentiating amongst them is particularly important to organismal performance.

The principle that unites all of the present study's findings is that natural selection favors perceptual interfaces revelatory of utility gradients that inform decisions. My formalization of this seemingly simple notion, which has enjoyed decades[7,18,19] of acceptance, advances understanding in several important and unanticipated ways. First, it differentiates it from the notion[7,8] that selection maximizes total utility harvesting, and shows that instead, interfaces calibrated to maximize total decision utility are a subset of all gradient-revelatory interfaces potentially favored by natural selection. Environments two and three, for example, showcase the adaptiveness of interfaces calibrated to avoid an environment's lowest-utility outcomes (and arguably, by propagating interfaces specialized for the processing of risk-indicative stimuli[20,21], so too does nature). Second, it differentiates it from the notion, also enjoying decades of acceptance[1,3,22] (despite being incorrect), that selection favors maximally-informative (i.e. error-minimizing) interfaces, and instead shows that these are adaptive only to the extent that they abet the exploitation of utility gradients. This latter result further clarifies that maximally-informative interfaces are favorable under decision conditions similar to those faced by task-general interfaces that process low-level stimulus features[1]. Third, it presents cost-weighted distortion minimization as a broadly useful framework that can account for perceptual adaptation to several

types of environmental variation, such as task structure (e.g. selective identification of one vs. multiple peak-utility items), utility gradients (e.g. Fig 1b1), and environmental item probabilities (e.g. Supplementary Equations, Part 8). Though this framework's experiment interpretation utility is already established[6-8], future studies may bridge it with an expanded set of empirical findings, such as categorical color perception[23,24] and the effects of reward-associated plasticity on sensory cortex stimulus tuning[25,26]; after all, that plasticity is induced by previously-unencoded environmental utility gradients.

Methods

Interface allele competition. Three populations are simulated in parallel. The size of each is fixed at 100 individuals. Individuals differ according to whether their perceptual interface is "risk averse" (RA) or "optimal" (O). At simulation initialization, the prevalence of O is either 20%, 50%, or 80%; all three populations are initialized equivalently. Then, within each population, a lifetime of decisions is simulated for each member (the nth member of each population faces the same life decisions), the members are ranked by their lifetime's accrued utility, and the membership of the next generation is generated according to rules specific to each population. Lifetime simulation and population refresh procedures repeat until each population converges to fixation for one of the two alleles.

The first and second sets of refresh rules are simple: the bottom 80% and 50% (respectively) of the utility accumulators are eliminated, and the set remaining is copied until the population size is restored to 100. The third set eliminates the bottom 10% and replaces each member thereof with an individual whose probability of exhibiting each allele is proportional to the allele's prevalence in the top 90%.

The decisions made within a lifetime involve choosing between two items sampled (with uniform probability) from the utility landscape in Fig. 1d, with $b_{1,1} = 100$ and $b_{2,1} = 1100$. Most decision utilities are contingent upon attribute 1; those contingent upon attribute 2 are deemed "high stakes" (HS), and arise with probability p(HS). In these simulations, p(HS) = .02 or .015; the result in Supplementary Equations, Part 5 indicates that the O interface (Fig. 1d, right) achieves higher average decision utility than the RA interface (Fig. 1d, left) when p(HS) < .022.

Statistics. In Table 1, the parameterization conditions A-F were each simulated 10 times. Then, the "risk averse" fixation probability was compared (Fisher's exact test, two-sided, n=20) across various pairs of conditions differentiated by just one parameter.

Expected utility computation. Because percepts are composed of items whose utilities are drawn from normal distributions, the distributions of mean percept values are also normal. Also, once percept utilities are learned, the organism will preferentially select items mapped to higher-utility percepts; a percept's expected value, therefore, is related to its position in the percept preference order. If it is further specified that the interface has N percepts, and that a particular sampling of item utilities results in percept 1 being the highest-utility percept, then the expected value of percept 1, $E(P_1)$, can be expressed as

$$\int_{-\infty}^{\infty} N_{PDF}(0, \sigma_1^2) * \prod_{i=2}^{N} N_{CDF}(0, \sigma_i^2) * x dx$$

Alternatively, if $E(P_1) < E(P_2)$ and $E(P_1) > E(P_i) \; \forall \; i > 2$, then

$$E(P_1) = \int_{-\infty}^{\infty} \left(1 - N_{CDF}(0, \sigma_2^2)\right) * N_{PDF}(0, \sigma_2^2) * \prod_{i=3}^{N} N_{CDF}(0, \sigma_i^2) * x dx$$

The expressions for all expected percept values across all preference orderings are constructed similarly. In the present study, these expressions are evaluated by numerical integration. The

results in Fig. 2a and 2c are obtained by integrating over [-5,5] with dx = .001, those in Fig. 2b are obtained by integrating over [-6,6] with dx = .01.

A notable feature of the above expressions is that each percept has an associated σ-value. These are computed individually for every percept across all item-percept assignments, using standard methods. For example, for a 25-item percept with utilities drawn from $N(0,1)$, $\sigma = 1/5$.

Upon computing the ordering-specific expected percept values, it becomes possible to combine them to compute the mean utility obtained by a particular assignment of 100 items to the available percepts. Specifically, the respective arithmetic and geometric mean utilities are $(E(O_1)+E(O_2))/2$ and $(E(O_1)*E(O_2))^{1/2}$ (in Fig. 2, when some $E(O_2)*E(O_2) < 0$, I report the square of the geometric mean), where the O_j represent different percept preference orderings. Letting O_j denote the ordering in which j is the preferred percept, defining $E(P_{j,i})$ as the expected value of percept i in ordering j, and defining S_i as the size (in items) of percept i,

$$100^n*E(O_1) = E(P_{1,1})*(100^n-(S_2)^n)+E(P_{1,2})*(S_2)^n$$

$$100^n*E(O_2) = E(P_{2,2})*(100^n-(S_1)^n)+E(P_{2,1})*(S_1)^n$$

References

Wei, X.-X. & Stocker, A. A. A Bayesian observer model constrained by efficient coding can explain 'anti-Bayesian' percepts. *Nat Neurosci* **18**, 1509–1517 (2015).

Polanía, R., Woodford, M. & Ruff, C. C. Efficient coding of subjective value. *Nature Neuroscience* **22**, 134-142 (2018).

Friston, K. The free-energy principle: a unified brain theory? *Nat. Rev. Neurosci.* **11**, 127-138 (2010).

Moreno-Bote, R., Knill, D. C. & Pouget, A. Bayesian sampling in visual perception. *Proc. Natl. Acad. Sci.* **108**, 12491-12496 (2011).

Knill, D. C. & Pouget, A. Bayesian brain: the role of uncertainty in neural coding and computation. *Trends Neurosci.* **27**, 712-719 (2004).

Sims, C. R. Rate-distortion theory and human perception. *Cognition* **152**, 181-198 (2016).

Sims, C. R. Efficient coding explains the universal law of generalization in human perception. *Science* **360**, 652-656 (2018).

Marzen, S. E. & DeDeo, S. The evolution of lossy compression. *J R Soc Interface* **14**, 20170166 (2017).

Linsker, R. Self-organization in a perceptual network. *IEEE Computer* **21**, 105-117 (1988).

Frank, S. A. Natural selection. I. Variable environments and uncertain returns on investment. *J Evol Biol* **24**, 2299–2309 (2011).

Mark, J. T., Marion, B. B. & Hoffman, D. D. Natural selection and veridical perceptions. *J Theor Biol* **256**, 504-515 (2010).

Singh, M. & Hoffman, D. in *Shape Perception in Human and Computer Vision*   (eds Sven J Dickinson & Zygmunt Pizlo) Ch. 12, 171-186 (Springer Verlag, 2013).

Wei, X.-X. & Stocker, A. A. Lawful relation between perceptual bias and discriminability. *Proc. Nat. Acad. Sci.* **114**, 10244-10249 (2017).

King, O. D. & Masel, J. The evolution of bet-hedging adaptations to rare scenarios. *Theoretical Population Biology* **72**, 560-575 (2007).

Rtischev, D. Risk-bearing in a winner-take-all contest. *Gakushuin Economic Papers* **45**, 65-79 (2008).

Dekel, E. & Scotchmer, S. On the evolution of attitudes towards risk in winner-take-all games. *J Econ Theory* **87**, 125-143 (1999).

Markowitz, H. M. *Portfolio Selection: Efficient Diversification of Investments*. 2nd edn, (Blackwell Publishers Ltd, 1991).

Wehner, R. J. 'Matched filters' — neural models of the external world. *Comp. Physiol. A* **161**, 511-531 (1987).

Shepard, R. N. Toward a universal law of generalization for psychological science. *Science* **237**, 1317-1323 (1987).

DeLoache, J. S. & LoBue, V. The narrow fellow in the grass: human infants associate snakes and fear. *Developmental Science* **12**, 201-207 (2009).

Hein, A. M., Gil, M. A., Twomey, C. R., Couzin, I. D. & Levin, S. A. Conserved behavioral circuits govern high-speed decision-making in wild fish shoals. *Proc. Nat. Acad. Sci.* **115**, 12224-12228 (2018).

Barlow, H. B. in *Sensory Communications*   (ed W A Rosenblith) 217-234 (MIT Press, 1961).

Caves, E. M. *et al.* Categorical perception of colour signals in a songbird. *Nature* **560**, 365-367 (2018).

Komarova, N. L. & Jameson, K. A. Population heterogeneity and color stimulus heterogeneity in agent-based color categorization. *J Theor Biol* **253**, 680-700 (2008).

Gdalyahu, A. *et al.* Associative fear learning enhances sparse network coding in primary sensory cortex. *Neuron* **75**, 121-132 (2012).

Berlau, K. M. & Weinberger, N. M. Learning strategy determines auditory cortical plasticity. *Neurobiol Learn Mem* **89**, 153-166 (2008).

Author Information V.Q.-Z. declares no competing interests. Correspondence and requests for materials should be addressed to V.Q.-Z. (vquintanar@hotmail.com).

Code and Data are accessible at github.com/victorqz1/PerceptualCompression1.

Table 1. Simulations of competition between "risk averse" and "optimal" interface alleles

Condition	Lifetime Decisions	Probability of high-stakes (HS) scenario	Risk averse allele, initial prevalence	Instances of "risk averse" allele fixation
A	1000	.02	80%	8
B	1000	.015	80%	0
C	100	.015	80%	7
D	100	.015	50%	1
E	100	.02	50%	9
F	100	.02	20%	1
Comparison	**P**[1]	**Parameter**		
A vs. B	.0007	p(HS)		
B vs. C	.0031	Lifetime length		
C vs. D	.0198	Initial prevalence		
D vs. E	.0011	p(HS)		
E vs. F	.0011	Initial prevalence		

[1]Fisher's exact test, two-sided

Figure 1. Illustration of utility-maximizing assignment of real-world items to percepts. a, Individual real-world items (1 and 2) have quantifiable attributes. Perceptual interfaces inevitably compress this information; here, an interface with a 1-bit output perceives items as blue or red, based on one particular attribute value being above or below a boundary. The organism favors blue options when choosing an item. **b**, Each pair of plots illustrates how (for a 1-bit interface making binary decisions) a particular deviation from a simple baseline utility landscape shifts the optimal perceptual boundary. **c**, The boxes in this panel (and the next) show the optimal division, by a 2-bit interface that makes binary decisions, of an item landscape in which utilities are determined by two uncorrelated attributes. Right and left boxes respectively segment items whose utilities exhibit situation-specific single-attribute dependency or are determined by their attribute sum. These interfaces are free from item-percept assignment constraints. **d**, These landscape divisions are optimal subject to the constraint that attributes are perceived separately. The right-box division is "optimal" (e.g., in environment 2) when utility hinges on attribute 1 far more than on attribute 2. The left-box division is favored evolutionarily when utility is similarly dependent on both attributes, or even in versions of environment 2 (where $b_{2,1} \gg b_{1,1}$) in which this "risk averse" division benefits from avoidance of rare, but large, utility-harvesting failures.

Figure 2. Optimizing the assignment of unknown-utility items to percepts whose utilities are learnable. a, Displays mean (arithmetic and geometric) decision utilities obtained using a 1-bit interface to distinguish amongst 100 items with utilities drawn independently from N(μ,4). **b**, When percept variances are similar (A vs. B), the low-variance percept's high-utility random values are more likely than its low-utility random values to become learned preferences (dotted red line). However, this likelihood distinction mostly disappears (solid red line) when percept variances differ significantly (A vs. C), because the high-variance percept's value almost wholly determines which percept is preferred. **c**, Here, item utilities belong to one of two clusters, $\mu+x_1+N(0,b^2)$ and $\mu+x_2+N(0,b^2)$; x_1 and x_2 are themselves drawn from N($0,a^2$). Line labels indicate either the sizes of percept-assigned clusters, or that each cluster's members are "split" between percepts.

Supplementary Equations

Note: in these analyses, the range of utility values is assumed to be spanned by a density of items sufficient to justify an integral approximation for the calculation of: utility estimation error, item-percept mutual information, expected utility, and distortion loss.

Part 1: derivation of the objective function for distortion loss minimization

Distortion during a single decision: given a set of n items available during a particular decision round, one can label their utilities x_1:x_n, indexed in order of descending utility. A perceptual system that transmits environmental information perfectly would obtain utility x_1, as would a perceptual system that assigns the x_1-utility item to a category of its own. However, if there are k items that appear to be of the same, most-preferred percept, then the expected utility of the decision round is $\sum_{i=1}^{k} x_i / k$. The distortion loss is the expected magnitude of the utility loss that results from the perceptual system's compression of the world's information; it's magnitude is $x_1 - \sum_{i=1}^{k} x_i / k$.

Total distortion (TD), then, is simply the sum of the distortion losses over all possible utility value sets $X = \{x_1,…,x_n\}$ when the interface uses the boundaries $B = \{b_2,…,b_m\}$. As an illustration of how boundaries affect the distortion, consider the set Q of all item sets $\{x_1,…,x_n\}$ that satisfy $b_i < x_1$:$x_k < b_{i+1} < x_{k+2}$:x_n. The contribution of Q to TD is

$$Q = \int_{b_{i+1}}^{b_i} \int_{b_{i+1}}^{x_1} … \int_{b_{i+1}}^{x_{k-1}} \left(x_1 - \frac{\sum_{i=1}^{k} x_i}{k} \right) \int_{0}^{b_{i+1}} \int_{0}^{x_{k+1}} … \int_{0}^{x_{n-1}} p(X) dx_n dx_{n-1} … dx_1$$

Note that the limits of integration reflect the ordinal arrangement of the x_i, and their position relative to the b_i. Note also that the distortion depends on p(X). Generalizing this expression across all boundaries i and best-percept item counts k, and noting that $Q_{i1} = 0$, yields $TD = \sum_{i=1}^{m} \sum_{k=2}^{n} Q_{ik}$.

Part 2: proof that for the general game with m percepts, n choices, a linearly increasing and unidimensional utility continuum, and a uniform distribution of item probabilities over that continuum, the perceptual category boundaries that optimize total distortion (TD) and utility (U) are equivalent

Approach: the optima of U and TD are equivalent if ∀ i, $dU/db_i = C*dTD/db_i$, C constant.

2.1: expression for dU/db_i

Recall from main text that: b_i and b_{i+1} are the upper and lower boundaries of P_i; note also that $b_{m+1} = 0$, $E(P_i) = (b_i+b_{i+1})/2$, and

$$p(P_i) = P(\text{no items from percept } x < i)*P(\text{at least one item from percept i})$$

$$= (b_i/b_1)^n*(1-(b_{i+1}/b_i)^n) = ((b_i)^n-(b_{i+1})^n)/(b_1)^n$$

Thus, utility can be written as

$$U = \sum_{i=1}^{m} E(P_i)P(P_i) = \sum_{i=1}^{m} (b_i + b_{i+1})(b_i^n - b_{i+1}^n)/2b_1^n$$

$$= (\ldots + (b_{i-1} + b_i)(b_{i-1}^n - b_i^n) + (b_i + b_{i+1})(b_i^n - b_{i+1}^n) + \cdots)/2b_1^n$$

Setting dU/db$_i$ = 0 and solving yields

$$b_i = \left(\frac{b_{i-1}^n - b_{i+1}^n}{n(b_{i-1} - b_{i+1})} \right)^{1/(n-1)}$$

2.2: simplifying Q$_{ik}$

$$Q_{ik} = \int_{b_{i+1}}^{b_i} \int_{b_{i+1}}^{x_1} \ldots \int_{b_{i+1}}^{x_{k-1}} \left(x_1 - \frac{\sum_{i=1}^{k} x_i}{k} \right) \int_0^{b_{i+1}} \int_0^{x_{k+1}} \ldots \int_0^{x_{n-1}} p(X)dx_n dx_{n-1} \ldots dx_1$$

First, set aside the p(X) term; in this environment, it is constant $\forall$ X
Second,

$$\int_0^{b_{i+1}} \int_0^{x_{k+1}} \ldots \int_0^{x_{n-1}} 1 dx_n \ldots dx_{k+1} = b_{i+1}^{n-k}/(n-k)!$$

Third,

$$x_1 - \sum_{i=1}^{k} x_i /k = \left((k-1)x_1 - \sum_{i=2}^{k} x_i \right)/k$$

Fourth, define C$_1$ = (b$_{i+1}$)$^{n-k}$/k(n-k)! These four steps allow Q$_{ik}$ to be re-written as

$$C_1 \int_{b_{i+1}}^{b_i} (k-1)x_1 \int_{b_{i+1}}^{x_1} \ldots \int_{b_{i+1}}^{x_{k-1}} 1 dx_k \ldots dx_1 - C_1 \int_{b_{i+1}}^{b_i} \int_{b_{i+1}}^{x_1} \ldots \int_{b_{i+1}}^{x_{k-1}} \sum_{i=2}^{k} x_i \, dx_k \ldots dx_1$$

Fifth,

$$\int_{b_{i+1}}^{x_1} \ldots \int_{b_{i+1}}^{x_{k-1}} 1 dx_k \ldots dx_2 = (x_1 - b_{i+1})^{k-1}/(k-1)!$$

Sixth,

$$\int_{b_{i+1}}^{x_1} \cdots \int_{b_{i+1}}^{x_{k-1}} \sum_{i=2}^{k} x_i \, dx_k \ldots dx_2 = (b_{i+1} + x_1) * (x_1 - b_{i+1})^{k-1}/(2 * (k-2)!)$$

Therefore,

$$Q_{ik} = C_1/(k-2)! \int_{b_{i+1}}^{b_i} (x_1 - b_{i+1})^k/2 \, dx_1 = \frac{b_{i+1}^{n-k}(k-1)(b_i - b_{i+1})^{k+1}}{2(k+1)!\,(n-k)!}$$

2.3: deriving and simplifying TD$_i$

Defining TD$_i$ as $\sum_{k=2}^{n} Q_{ik}$ leads to the expression given in TD$_{i1}$, expansion of the binomial exponential reveals DL$_{i2}$, and expansion of the double summation followed by the grouping of terms by exponent of b$_i$ reveals DL$_{i3}$.

$$TD_{i1} = \sum_{k=2}^{n} \frac{b_{i+1}^{n-k}(k-1)(b_i - b_{i+1})^{k+1}}{2(k+1)!\,(n-k)!}$$

$$TD_{i2} = \frac{1}{2} * \sum_{k=2}^{n} \frac{(k-1)\sum_{j=0}^{k+1}\binom{k+1}{j}(-1)^j b_i^{k+1-j} b_{i+1}^{n-k+j}}{(k+1)!\,(n-k)!}$$

$$TD_{i3} = \frac{1}{2} * \sum_{L=0}^{n+1} C_L b_i^L b_{i+1}^{n+1-L}$$

In TD$_{i3}$, the coefficients C$_L$ can be derived from noting that in TD$_{i2}$, for all powers of b$_i$, there is a one-to-one correspondence between the outer sum's k values and the inner sum's j values. Thus,

$$C_L = \sum_{k=2}^{n} \frac{(-1)^{k+1-L}\binom{k+1}{k+1-L}(k-1)}{(k+1)!\,(n-k)!} \rightarrow \frac{1}{L!} \sum_{k=\max(2,L-1)}^{n} \frac{(-1)^{k+1-L}(k-1)}{(k+1-L)!\,(n-k)!}$$

The rightmost expression is the consequence of observing that k+1-L is potentially negative for certain combinations of (k,L), and that in DL$_{i2}$ there is no b_i^L term in the inner sum while L < k+2. This formulation yields

$$C_0 = \sum_{k=2}^{n} \frac{(-1)^{k+1}(k-1)}{(k+1)!\,(n-k)!} = \frac{\sum_{k=0}^{n}(-1)^k(k-2)T_{k,n+1} - \sum_{k=0}^{2}(-1)^k(k-2)T_{x,n+1}}{(n+1)!} = \frac{1-n}{(n+1)!}$$

$$C_1 = \sum_{k=2}^{n} \frac{(-1)^k(k-1)}{(k)!\,(n-k)!} = \frac{1}{n!} * \left(\sum_{k=0}^{n} (-1)^k(k-1)T_{k,n} - \sum_{k=0}^{1} (-1)^k(k-1)T_{k,n} \right) = 1/n!$$

$$C_2 = \frac{1}{2} \sum_{k=2}^{n} \frac{(-1)^{k-1}}{(k-2)!\,(n-k)!} = \sum_{k=0}^{i} (-1)^k T_{k,i} = 0$$

$$C_{2<L<n-1} = \frac{1}{6} \sum_{k=L-1}^{n} \frac{(-1)^{k-2}(k-1)}{(k-L+1)!\,(n-k)!} = \sum_{k=0}^{i} (-1)^k(L-2+k)T_{k,i} = 0$$

$$C_n = -1/n!$$

$$C_{n+1} = (n-1)/(n+1)!$$

Combining all of the terms derived yields

$$TD_i = \frac{b_i^{n+1}(n-1)}{2(n+1)!} - \frac{b_i^n b_{i+1}}{2n!} + \frac{b_i b_{i+1}^n}{2n!} - \frac{b_{i+1}^{n+1}(n-1)}{2(n+1)!}$$

In the above expressions, $T_{k,i} = \binom{i}{k}$ and represents the kth term of the ith row of Pascal's triangle. In Part 2.3.1 it is shown that certain sums over $T_{k,i}$ terms equal 0.

2.3.1: $0 = \sum_{x=0}^{i}(-1)^x T_{x,i} = \sum_{x=0}^{i}(-1)^x(X+x)T_{k,i}$ (X is an arbitrary integer)

A well-known feature of Pascal's triangle is that $T_{k,i} = T_{k-1,i-1} + T_{k,i-1}$ ($T_{-1,i} = T_{i+1,i} = 0$). Therefore, the $T_{k,i}$ terms in the sum $\sum_{k=0}^{i}(-1)^k T_{k,i}$ can be replaced with $T_{k,i-1}$ terms; additionally decomposing the sum itself into its positive and negative components yields

$$\sum_{k=-1}^{i} T_{k,i-1} - \sum_{k=0}^{i-1} T_{k,i-1} = T_{-1,i-1} + T_{i,i-1} + \sum_{k=0}^{i-1} T_{k,i-1} - \sum_{k=0}^{i-1} T_{k,i-1} = 0$$

It is also true that $T_{k,i} = T_{k-2,i-2} + 2*T_{k-1,i-2} + T_{k,i-2}$. Proposing that $\sum_{k=0}^{i}(-1)^k(X+k)T_{k,i}$ can be expressed as $\sum_{k=-2}^{i} D_k T_{k,i-2}$ the coefficients D_k can be derived by noting first that individual $T_{k,i-2}$ terms only contribute to $T_{n,i}$ for $n \in [k:k+2]$; within $[k:k+2]$, observe that

(X+k)*T_{k,i}-(X+k+1)*T_{k+1,i}+(X+k+2)*T_{k+2,i}
= (X+k)*(T_{k-2,i-2}+2*T_{k-1,i-2}+T_{k,i-2})
- (X+k+1)*(T_{k-1,i-2} + 2*T_{k,i-2}+T_{k+1,i-2})
+ (X+k+2)*(T_{k,i-2}+2*T_{k+1,i-2}+T_{k+2,i-2})
= Constant+T_{k,i-2}*(X+k-2*(X+k+1)+X+k+2) = Constant+T_{k,i-2}*0

Since the individual $D_k = 0$, $\sum_{k=-2}^{i} D_k T_{k,i-2} = 0 = \sum_{k=0}^{i}(-1)^k(X+k)T_{k,i}$

2.4: Expression for dTD/db_i

$$TD = \ldots + TD_i + TD_{i+1} + \ldots$$

$$= \cdots + \frac{b_{i-1}^{n+1}(n-1)}{2(n+1)!} - \frac{b_{i-1}^n b_i}{2n!} + \frac{b_{i-1}b_i^n}{2n!} - \frac{b_i^{n+1}(n-1)}{2(n+1)!}$$
$$+ \frac{b_i^{n+1}(n-1)}{2(n+1)!} - \frac{b_i^n b_{i+1}}{2n!} + \frac{b_i b_{i+1}^n}{2n!} - \frac{b_{i+1}^{n+1}(n-1)}{2(n+1)!} + \cdots$$

Setting $dTD/db_i = 0$ and solving yields

$$b_i = \left(\frac{b_{i-1}^n - b_{i+1}^n}{n(b_{i-1} - b_{i+1})} \right)^{1/(n-1)}$$

Finally, rewriting TD and U as shown below reveals that they vary in opposite directions with respect to $b_{i-1}(b_i)^n$-$b_i(b_{i-1})^n$. So, the b_i that maximize utility will minimize distortion.

$$TD = C_1 b_1^{n+1} + C_2 \sum_{i=2}^{m} (b_{i-1}b_i^n - b_{i-1}^n b_i)$$

$$U = C_3 b_1^{n+1} + C_4 \sum_{i=2}^{m} (b_{i-1}^n b_i - b_{i-1}b_i^n)$$

Part 3: proof that, for two-item decisions on the attribute-utility landscape in Figure 1b1, the perceptual boundary that optimizes utility also optimizes distortion

In this decision environment, setting a > 1, utility as a function of attribute value x is

$$u(x) = \begin{cases} x, x < b_1/2 \\ b_1/2 + a_1(x - b_1/2), x > b_1/2 \end{cases}$$

From Part 2.1, for a 1-bit interface, U = p(P$_1$)E(P$_1$)+p(P$_2$)E(P$_2$). Also, assuming (reasonably) that $b_2 > b_1/2$,

$$p(P_1) = ((b_1)^2 - (b_2)^2)/(b_1)^2, \quad p(P_2) = (b_2/b_1)^2$$

$$E(P_1) = (b_1/2 + a_1*(b_2 - b_1/2) + (1+a_1)*b_1/2)/2 = (b_1 + a_1*b_2)/2$$

$$E(P_2) = \left(\int_0^{b_1/2} x\,dx + \int_{b_1/2}^{b_2} b_1/2 + a_1(x - b_1/2)\,dx \right)/b_2$$

Setting $dU/db_2 = 0$ and solving yields $b_2 = b_1*(5/8 - a^{-1}/8)$.

Considering now the optimization of TD, the present decision environment affords three simplifications to the integrand, $p(X)(x_1 - \sum_{i=1}^{k} x_i /k)$. First, p(X) is a constant. Second, $x_1 - \sum_{i=1}^{k} x_i /k$ simplifies to $(x_1\text{-}x_2)/2$. Third, when x_1 and x_2 correspond to different percepts, the integrand is zero. Therefore,

$$TD = \int_0^{b_2} \int_0^{x_1} \frac{x_1 - x_2}{2} dx_2 dx_1 + a_1 \int_{b_2}^{b_1} \int_{b_2}^{x_1} \frac{x_1 - x_2}{2} dx_2 dx_1$$

Here, it is illuminating to split the first double integral into the following components:

$$\int_0^{b_1/2} \int_0^{x_1} \frac{x_1 - x_2}{2} dx_2 dx_1 + \int_{b_1/2}^{b_2} \int_0^{b_1/2} \frac{b_1/2 + a_1(x_1 - b_1/2) - x_2}{2} dx_2 dx_1$$
$$+ a_1 \int_{b_1/2}^{b_2} \int_{b_1/2}^{x_1} \frac{x_1 - x_2}{2} dx_2 dx_1$$

Setting dTD/db$_2$ = 0 and solving yields b$_2$ = b$_1$*(5/8-1/(8*a$_1$)).

Part 4: proof that, for two-item decisions on the attribute-utility landscape in Figure 1b2, the perceptual boundary that optimizes utility also optimizes distortion

In this decision environment, with a$_2$∈[0,1/b$_1$], the item PDF as a function of attribute value x, and the resulting utility function, are given below:

$$p(x) = \begin{cases} 1/b_1 - a_2, x < b_1/2 \\ 1/b_1 + a_2, x > b_1/2 \end{cases}$$

$$U = \left(1 - \left(\int_0^{b_2} p(x)\right)^2\right) \left(\frac{\int_{b_2}^{b_1} p(x)u(x)}{\int_{b_2}^{b_1} p(x)}\right) + \left(\int_0^{b_2} p(x)\right)^2 \left(\frac{\int_0^{b_2} p(x)u(x)}{\int_0^{b_2} p(x)}\right)$$

U reduces to a more familiar form when a$_2$ = 1. For a$_2$∈[0,1/b$_1$], $\int_{b_2}^{b_1} p(x)u(x) / \int_{b_2}^{b_1} p(x)$ simplifies to (b$_1$+b$_2$)/2 because p(x) is constant in [b$_2$,b$_1$]. Also, for specificity's sake:

$$\int_0^{b_2} p(x) = \int_0^{b_1/2} 1/b_1 - a_2 dx + \int_{b_1/2}^{b_2} 1/b_1 + a_2 dx$$

$$\int_0^{b_2} p(x)u(x) = \int_0^{b_1/2} x(1/b_1 - a_2)dx + \int_{b_1/2}^{b_2} x(1/b_1 + a_2)dx$$

Setting dU/db$_2$ = 0 and solving yields b$_2$ = b$_1$*(1/2+a$_2$*b$_1$/4), which is a linear function of a$_2$ with range [b$_1$/2,3*b$_1$/4].

Meanwhile, letting $p_1(x_1,x_2) = (1/b_1-a_2)^2$, $p_2(x_1,x_2) = (1/b_1-a_2)*(1/b_1+a_2)$, and $p_3(x_1,x_2) = (1/b_1+a_2)^2$,

$$TD = \int_0^{\frac{b_1}{2}} \int_0^{x_1} p_1(x_1,x_2)\frac{x_1-x_2}{2}dx_2dx_1 + \int_{b_1/2}^{b_2} \int_0^{b_1/2} p_2(x_1,x_2)\frac{x_1-x_2}{2}dx_2dx_1$$

$$+ \int_{b_1/2}^{b_2} \int_{b_1/2}^{x_1} p_3(x_1,x_2)\frac{x_1-x_2}{2}dx_2dx_1 + \int_{b_2}^{b_1} \int_{b_2}^{x_1} p_3(x_1,x_2)\frac{x_1-x_2}{2}dx_2dx_1$$

Setting $dTD/db_2 = 0$ and solving yields $b_2 = b_1*(1/2+a_2*b_1/4)$.

Part 5: demonstration that the bit-attribute assignments that maximize utility are the same as those that minimize distortion (2 bits, 2 independent and independently-perceived attributes, 2 item choices, uniform item probabilities over attribute values)

5.1: definition of problem and notation

The ranges of attributes 1 and 2 are $[0,b_{1,1}]$ and $[0,b_{2,1}]$, respectively. If item utilities are the sum of attribute values, utility and distortion are abbreviated U_s and D_s, respectively. Alternatively, if utility is situationally-determined, depending on attributes 1 and 2 with probabilities p and 1-p (respectively), I use the abbreviations U_p and D_p. These abbreviations are in turn superscripted according to the attributes in which perceptual bits are invested.

Thus, if both bits are invested in differentiation along attribute 1,

$$U_s^{11} = \frac{b_{2,1}}{2} + \sum_{i=1}^{4}(b_{1,i} + b_{1,i+1})(b_{1,i}^n - b_{1,i+1}^n)/2b_{1,1}^n$$

$$U_p^{11} = (1-p)\frac{b_{2,1}}{2} + p\sum_{i=1}^{4}(b_{1,i} + b_{1,i+1})(b_{1,i}^n - b_{1,i+1}^n)/2b_{1,1}^n$$

$$D_s^{11} = \sum_{i=1}^{4}\sum_{k=2}^{n} Q_{ik}^{(1)} + \int_0^{b_{2,1}}\int_0^{x_1} \cdots \int_0^{x_{n-1}} \left(x_1 - \frac{\sum_{i=1}^n x_i}{n}\right)$$

$$D_p^{11} = p\sum_{i=1}^{4}\sum_{k=2}^{n} Q_{ik}^{(1)} + (1-p)\int_0^{b_{2,1}}\int_0^{x_1} \cdots \int_0^{x_{n-1}} \left(x_1 - \frac{\sum_{i=1}^n x_i}{n}\right)dx_n \ldots dx_1$$

$$Q_{ik}^{(1)} = \int_{b_{1,i+1}}^{b_{1,i}}\int_{b_{1,i+1}}^{x_1} \cdots \int_{b_{1,i+1}}^{x_{k-1}} \left(x_1 - \frac{\sum_{i=1}^k x_i}{k}\right)\int_0^{b_{1,i+1}}\int_0^{x_{k+1}} \cdots \int_0^{x_{n-1}} dx_n dx_{n-1} \ldots dx_1$$

If one bit is invested in differentiation along each attribute,

$$U_s^{12} = \frac{(b_{1,1} + b_{1,2})(b_{1,1}^n - b_{1,2}^n) + b_{1,2}^{n+1}}{2b_{1,1}^n} + \frac{(b_{2,1} + b_{2,2})(b_{2,1}^n - b_{2,2}^n) + b_{2,2}^{n+1}}{2b_{2,1}^n}$$

$$U_p^{12} = p * \frac{(b_{1,1} + b_{1,2})(b_{1,1}^n - b_{1,2}^n) + b_{1,2}^{n+1}}{2b_{1,1}^n} + (1 - p) * \frac{(b_{2,1} + b_{2,2})(b_{2,1}^n - b_{2,2}^n) + b_{2,2}^{n+1}}{2b_{2,1}^n}$$

$$D_s^{12} = Q^{(2)} + Q^{(3)}$$

$$D_p^{12} = p * Q^{(2)} + (1 - p) * Q^{(3)}$$

$$Q^{(2)} = \int_0^{b_{1,2}} \int_0^{x_1} \cdots \int_0^{x_{n-1}} \left(x_1 - \frac{\sum_{i=1}^n x_i}{n} \right) dx_n \ldots dx_1$$
$$+ \sum_{k=2}^n \int_{b_{1,2}}^{b_{1,1}} \int_{b_{1,2}}^{x_1} \cdots \int_{b_{1,2}}^{x_k} \left(x_1 - \frac{\sum_{i=1}^k x_i}{k} \right) \int_0^{b_{1,2}} \int_0^{x_{k+1}} \cdots \int_0^{x_{n-1}} dx_n \ldots dx_1$$

To obtain $Q^{(3)}$ from $Q^{(2)}$, respectively replace $b_{1,1}$ and $b_{1,2}$ with $b_{2,1}$ and $b_{2,2}$.

5.2: along attribute a, for a particular n and boundaries b_i, $U_a = C_1 * b_{a,1}$ and $D_a = C_2 * b_{a,1}$; so, if $b_{a,1}$ is scaled by f, so are U_a and D_a.

First, from Parts 2.1 and 2.4, $b_i = \left(\frac{b_{i-1}^n - b_{i+1}^n}{n(b_{i-1} - b_{i+1})} \right)^{1/(n-1)}$. If b_1 is scaled by f, and all other b_i are also scaled by f, then this formula still holds true:

$$\left(\frac{f^n b_{i-1}^n - f^n b_{i+1}^n}{n(f * b_{i-1} - f * b_{i+1})} \right)^{1/(n-1)} = \left(\frac{f^n}{f} * \frac{b_{i-1}^n - b_{i+1}^n}{n(b_{i-1} - b_{i+1})} \right)^{1/(n-1)} = f * b_i$$

Second, from Part 2.1, $U = \sum_{i=1}^m (b_i + b_{i+1})(b_i^n - b_{i+1}^n)/2b_1^n$; scaling all b_i by f gives

$$\sum_{i=1}^m (f * b_i + f * b_{i+1})(f^n b_i^n - f^n b_{i+1}^n)/(2f^n b_1^n) = f \sum_{i=1}^m (b_i + b_{i+1})(b_i^n - b_{i+1}^n)/2b_1^n = f * U$$

Third, from Parts 1 and 2.4,

$$TD = \frac{p(X)}{2n!} \left(b_1^{n+1}(n - 1) + \sum_{i=2}^m b_{i-1}b_i^n - b_{i-1}^n b_i \right)$$

Assuming uniform item probability over each attribute's span, $p(X) = 1/(b_{a,1})^n$. Thus, substituting $f * b_{a,1}$ for $b_{a,1}$,

$$\frac{1}{f^n b_1^n} * \frac{1}{2n!} * \left(f^{n+1} b_1^{n+1}(n-1) + \sum_{i=2}^{m} f^{n+1} b_{i-1} b_i^n - b_{i-1}^n b_i \right) = f * TD$$

5.3: for all U^{11} and D^{11} vs. U^{12} and D^{12}, the optimal bit-attribute allocations are analogous

Knowing that utilities and distortions are linear functions of $b_{a,1}$ allows several simplifications to be made to the U^{xx} and D^{xx} expressed in Part 5.1. The simplifications make use of the following expressions (which correspond to n = 2; when $\beta > 1$, closed-form expressions are not obtainable for n > 2; see Part 5.3.1):

$$U_{\beta=k} = \sum_{i=1}^{k}(b_i + b_{i+1})(b_i^2 - b_{i+1}^2)/2b_1^2 = b_1*(1/2,5/8,21/32) \text{ for k=(0,1,2)}$$

$$D_{\beta=k} = \frac{2^k}{b_1^2} \int_0^{b_1/2^k} \int_0^{x_1} \frac{x_1 - x_2}{2} dx_2 dx_1 = b_1*(1/12,1/48,1/192) \text{ for k=(0,1,2)}$$

The above solutions use the result from Part 2.4 to determine that $b_2 = b_1/2$ when $\beta = 1$, and that $(b_2,b_3,b_4) = (.75b_1,.5b_1,.25b_1)$ when $\beta = 2$. For further simplicity, $b_{1,1} = 1$ and $b_{2,1}/b_{1,1} = R$; now, the U^{xx} and D^{xx} become:

$$U_s^{11} = \frac{R}{2} + \frac{21}{32}, \ U_s^{12} = \frac{5}{8} + \frac{5}{8}R, \ U_s^{22} = \frac{1}{2} + \frac{21}{32}R$$

Thus, $U_s^{11} > U_s^{12}$ ($U_s^{22} > U_s^{12}$) when R < .25 (R > 4)

$$U_p^{11} = (1-p)\frac{R}{2} + p\frac{21}{32}, \ U_p^{12} = p\frac{5}{8} + (1-p)\frac{5}{8}R, \ U_p^{22} = \frac{(1-p)}{2} + pR\frac{21}{32}$$

Thus, $U_p^{11} > U_p^{12}$ ($U_p^{22} > U_p^{12}$) when R*(1-p)/p < .25 (R*(1-p)/p > 4)

$$D_s^{11} = \frac{1}{192} + \frac{R}{12}, \ D_s^{12} = \frac{1}{48} + \frac{R}{48}, \ D_s^{22} = \frac{R}{192} + \frac{1}{12}$$

Thus, $D_s^{11} > D_s^{12}$ ($D_s^{22} > D_s^{12}$) when R < .25 (R > 4)

$$D_p^{11} = \frac{p}{192} + (1-p)\frac{R}{12}, \ D_p^{12} = \frac{p}{48} + (1-p)\frac{R}{48}, \ D_p^{22} = \frac{pR}{192} + \frac{1-p}{12}$$

Thus, $D_p^{11} > D_p^{12}$ ($D_p^{22} > D_p^{12}$) when R*(1-p)/p < .25 (R*(1-p)/p > 4)

The bit allocation optimality transitions are equivalent for U_s vs. D_s, and for U_p vs. D_p.

5.3.1: derivation of b_i, from formula in Part 2.4

For $\beta = 0$ and $\beta = 1$, the derivations are trivial. For $\beta = 2$, $b_4 = b_3*n^{-1/(n-1)}$, which leads to $b_2 = \left(\frac{b_1^n - b_3^n}{n(b_1 - b_3)}\right)^{1/(n-1)}$, which leads to an expression for b_3 that is intractable in general but is exactly solvable when n = 2.

$$b_3 = \left(\frac{\left(\frac{b_1^n - b_3^n}{n(b_1 - b_3)} \right)^{n/(n-1)} - b_3^n * n^{-n/(n-1)}}{n \left(\left(\frac{b_1^n - b_3^n}{n(b_1 - b_3)} \right)^{1/(n-1)} - b_3 * n^{-1/(n-1)} \right)} \right)^{1/(n-1)}$$

$$\xrightarrow[n=2]{} \frac{1}{4} * \frac{\left(\frac{b_1^2 - b_3^2}{(b_1 - b_3)} \right)^2 - b_3^2}{\left(\frac{b_1^2 - b_3^2}{(b_1 - b_3)} - b_3 \right)} = \frac{1}{4} * \frac{(b_1 + b_3)^2 - b_3^2}{(b_1 + b_3 - b_3)} = \frac{b_1 + 2b_3}{4} \rightarrow b_3 = b_1/2$$

Part 6: proof that the percept boundary placement that maximizes evolutionary utility differs from those which either maximize percept-item mutual information or minimize utility estimation error

6.1: utility

From Part 2.1, the 1-bit interface is optimized when $b_2 = b_1/n^{1/(n-1)}$.

6.2: mutual information

If the items spanning $0:b_1$ are chosen at random, their differential entropy (H) is $-\int_0^{b_1} p_i \log(p_i) di$ ($p_i = 1/b_1$).

In the case of the one-bit interface, the conditional differential entropy (H_c), conditioned on the low- and high-utility percepts (labeled L and H, respectively), equals

$$-p(L) \int_0^{b_2} p_{i|L} \log(p_{i|L}) di - p(H) \int_{b_2}^{b_1} p_{i|H} \log(p_{i|H}) di$$

Here, $p_{i|L} = 1/b_2$ and $p_{i|H} = 1/(b_1 - b_2)$.

Mutual information (MI) = $H - H_c$, and this holds true whether one is considering the mutual information between percepts and items perceived (MI_P) or between percepts and items chosen (MI_C); it should be specified, however, that in the MI_P (MI_C) case, $p(L)$ and $p(H)$ are respectively equal to b_2/b_1 and $1 - b_2/b_1$ (($b_2/b_1)^n$ and (($b_1)^n - (b_2)^n)/(b_1)^n$).

It is clear by inspection that maximizing MI_P with respect to b_2 is not equivalent to maximizing utility because only the latter depends on n.

Deviation between dMI_C and utility is demonstrated in Part 6.4.

6.3: estimation error

The following expression serves as a generalized mean error function:

$$p(L) \int_0^{b_2} p_{x|L} f(x, b_2/2)dx + p(H) \int_{b_2}^{b_1} p_{x|H} f(x, (b_1 + b_2)/2)dx$$

In the absolute and squared error cases, f(a,b) = |a-b| and (a-b)^2, respectively.

Analogously with Part 6.2, $p_{x|L}$ = 1/b_2 and $p_{x|H}$ = 1/(b_1-b_2); furthermore, when considering the utility estimate error of items perceived (chosen), E_P (E_C), the values of p(L) and p(H) are equivalent to those for MI_P (MI_C). It is therefore still clear by inspection that the maxima of utility and E_P are not equivalent.

In Part 6.4 it is confirmed that the maxima of utility and E_C are not equivalent either.

6.4: further study of MI_C and E_C

Setting dMI_C/db_2 = 0 and simplifying yields

$$((b_1)^n - b_1*(b_2)^{n-1})/(b_1 - b_2) = n*(b_2)^{n-1}*\log((b_1 - b_2)/b_2)$$

This does not afford an analytic solution for all n; it does not reduce to $b_2 = b_1/n^{1/(n-1)}$.

$$E_C, \text{ squared} = \left(\frac{b_2}{b_1}\right)^n \int_0^{b_2} \left(x - \frac{b_2}{2}\right)^2 /b_2 dx + \left(\frac{b_1^n - b_2^n}{b_1^n}\right) \int_{b_2}^{b_1} \left(x - \frac{b_1 + b_2}{2}\right)^2 /(b_1 - b_2)dx$$

Setting dE_C/db_2 = 0 and simplifying yields

$$b_1*(1+n)*(b_2)^{n+1} + (b_2)^2*(b_1)^n - b_2*(b_1)^{n+1} - n*(b_2)^n*(b_1)^2/2 = 0$$

This does not afford an analytic solution for all n; it does not reduce to $b_2 = b_1/n^{1/(n-1)}$. (Illustratively, for the case n = 2, it reduces to $b_2 = b_1/3^{1/2}$.)

$$E_C, \text{ absolute} = \left(\frac{b_2}{b_1}\right)^n * \frac{1}{b} * \left(\int_0^{b_2/2} \left(\frac{b_2}{2} - x\right) dx + \int_{b_2/2}^{b_2} \left(x - \frac{b_2}{2}\right) dx\right)$$
$$+ \left(\frac{b_1^n - b_2^n}{b_1^n}\right) * \frac{1}{b_1 - b_2} * \left(\int_{b_2}^{(b_1 + b_2)/2} \left(\frac{b_1 + b_2}{2} - x\right) dx + \int_{(b_1 + b_2)/2}^{b_1} (x - \frac{b_1 + b_2}{2})dx\right)$$

Setting dE_C/db_2 = 0 and simplifying yields $2*(n+1)*(b_2)^{n+1} - n*b_1*(b_2)^n - b_2*(b_1)^n = 0$.

This does not afford an analytic solution for all n; it does not reduce to $b_2 = b_1/n^{1/(n-1)}$. (Illustratively, for the case n = 2, it reduces to $b_2 = (1+7^{1/2})*b_1/6$.)

Part 7: proof that the percept boundaries that minimize estimation error across all percepts correspond to an optimum of the distortion loss and utility objectives when 1) attribute probabilities are uniform 2) max-utility attribute values are uniformly probable 3) utility varies linearly with attribute value 4) choices are binary in a linear attribute space (spanning $[0,b_1]$) OR the attribute space is radial (spanning $[-\pi,\pi]$)

Let point p ($p \in [0,b_1]$) emerge as the randomly-determined peak utility attribute value; denote the corresponding distortion and utility functions as D_p and U_p, respectively.

The objective function corresponding to the interface's overall utility is $OU = \int_0^{b_1} U_p \, dx$. To optimize the boundary placement of a 1-bit interface, set $dOU/db_2 = 0$ and solve.

$$\frac{dOU}{db_2} = \int_0^{b_1/2} \frac{dU_p}{db_2} dx + \int_{b_1/2}^{b_1} \frac{dU_p}{db_2} dx + \frac{dU_{.5*b1}}{db_2}$$

Estimation error is minimized when $b_2 = .5*b_1$; fortuitously, at this value of b_2, the integral terms are additive inverses and $dU_{.5*b1}/db_2 = 0$. Moreover, this result is independent of n (the number of item choices presented).

To construct an optimal 2-bit interface, it is instructive to assume that $b_1/2$ is the optimal placement for b_3 and to define OU_1 and OU_2 such that $U_p \in OU_1$ (OU_2) when $p \in [0,b_1/2]$ ($p \in [b_1/2,b_1]$). Within the interval $[b_3,b_1]$,

$$\frac{dOU_2}{db_2} = \int_{b_3}^{(b_1+b_3)/2} \frac{dU_p}{db_2} dx + \int_{(b_1+b_3)/2}^{b_1} \frac{dU_p}{db_2} dx + \frac{dU_{(b_1+b_3)/2}}{db_2}$$

By analogy with the 1-bit interface, the optimal placement of b_2 with respect to OU_2 is midway between b_1 and b_3. This analogy extends to β-bit interfaces as follows: the optimal placement of b_i with respect to OU_i, $U_p \in OU_i$ when $p \in [b_{i+1},b_{i-1}]$, is $(b_{i-1}+b_{i+1})/2$.

Meanwhile, within the interval $[b_3,b_1]$, all $U_p \in OU_1$ reduce to c-x (c constant); the division of these linear utility gradients is therefore equivalent and as described in Part 2. Thus, the placement of b_2 at $(b_3+b_1)/2$ is optimal uniquely when n = 2. This result extends to β-bit interfaces as follows: with n = 2, the optimal placement of b_i with respect to OU_x, $U_p \in OU_x$ when $p \neg\in [b_{i+1},b_{i-1}]$, is $(b_{i-1}+b_{i+1})/2$.

All of these constructions generalize to the radial attribute space, with one exception. Consider, in a linear attribute space, the placement of b_i within $[b_{i+1},b_{i-1}]$. If $b_{i-1} \leq b_1/2$ (an analogous argument can be made if $b_{i+1} \geq b_1/2$), then define: $b_{m+1} = 0$, dh = $b_{i+1}+b_{i-1}$, $U_p \in OU_1$ (OU_2, OU_3, OU_4) when $p \in [b_{m+1},b_{i+1}]$ ($[b_{i+1},b_{i-1}]$, $[b_{i-1},b_{dh}]$, $[b_{dh},b_1]$). Furthermore, assume uniform spacing of all existing boundaries prior to the insertion of b_i. Under these conditions, for any n, at $b_i = (b_{i-1}+b_{i+1})/2$, $dOU_1/db_i = -dOU_3/db_i$ and $dOU_2/db_i = 0$; however, $dOU_4/db_i = 0$ only if n = 2. In a radial attribute space, meanwhile, rotational symmetry allows boundary labels to be rotated arbitrarily; so, let the boundary placement problem be framed as the placement of b_0 between b_1 and b_m, b_i (i = 1:m)

spaced evenly. It is optimal to place b_0 midway between b_1 and b_m; $\forall\ k \in [0,b_m\text{-}b_1]$, $dU_{1+k}/db_0 = \text{-}dU_{m\text{-}k}/db_0$.

Finally, the above expressions continue to hold true if D_p is substituted for U_p, and so do the corresponding conclusions.

Part 8: proof that in a radial attribute space, when 1) utility varies linearly with attribute value 2) max-utility attribute values are uniformly probable 3) attribute probabilities belong to a particular but not special non-uniform distribution, utility is optimized by efficient coding of the item probability distribution specifically when decisions are binary, i.e. when n = 2, and that as n increases, utility optimization converges to the efficient coding of the attribute space. (Here, efficient coding is defined as the minimization of attribute value estimation error.)

8.1: n = 2

The expression for the total estimation error (TE) can be constructed as follows. First, consider that $\forall\ x \in [\text{-}\pi,\pi]$, expected error E(x) can be computed, and the E(x) can then be summed; symbolically, $TE = \int_{-\pi}^{\pi} p(x) * E(x)dx$. Next, denoting x's assigned percept P_x, E(x) is the product of $|x\text{-}E(P_x)|$ times the probability that errors of this magnitude will be realized. The latter of these multiplied quantities can be written as $\int_{-\pi}^{\pi}[x,y]p(y)dy$, where [x,y] = 1 (0) if x and y are (not) assigned to the same percept. Combining these ideas yields

$$E(P_x) = \int_{-\pi}^{\pi} y[x,y]p(y)dy \Big/ \int_{-\pi}^{\pi} [x,y]p(y)dy$$

$$TE = \int_{-\pi}^{\pi} p(x)|x - E(P_x)| \int_{-\pi}^{\pi} [x,y]p(y)dy\, dx$$

Next, note that $|x - E(P_x)| \int_{-\pi}^{\pi}[x,y]p(y)dy$ expands as follows:

$$\left| \int_{-\pi}^{\pi} x * p(y) * [x,y]dy - \frac{\int_{-\pi}^{\pi} y[x,y]p(y)dy}{\int_{-\pi}^{\pi}[x,y]p(y)dy} * \int_{-\pi}^{\pi} [x,y]p(y)dy \right|$$

Simplifying the above expression yields an integrand over y of |x-y|p(y)[x,y]; if p(x) and p(y) are further combined into p(x,y), then

$$TE = \int_{-\pi}^{\pi}\int_{-\pi}^{\pi} |x - y|[x,y]p(x,y)dy\, dx$$

An expression for utility can be constructed similarly. First, $\forall\ p \in [\text{-}\pi,\pi]$, expected utility U_p can be computed, and the U_p can then be summed; symbolically, $U = \int_{-\pi}^{\pi} p(p)U_p dp$. Second, the peak value can be denoted as M. Third, denoting the utility obtained from

the sampling of item pair (x,y) as U_{pxy}, $U_p = \int_{-\pi}^{\pi} \int_{-\pi}^{\pi} p(x,y) * U_{pxy} dy\, dx$. Finally, if x and y are assigned to different percepts, then $U_{pxy} = \min(|p\text{-}x|,|p\text{-}y|)$; otherwise, U_{pxy} is the average of $\min(|p\text{-}x|,|p\text{-}y|)$ and $\max(|p\text{-}x|,|p\text{-}y|)$. Combining these ideas yields

$$U = \int_{-\pi}^{\pi} p(p) \int_{-\pi}^{\pi} \int_{-\pi}^{\pi} M - p(x,y) * \left(\min(p-x, p-y) + [x,y] \frac{|x-y|}{2} \right) dy\, dx\, dp$$

$$= \int_{-\pi}^{\pi} \int_{-\pi}^{\pi} M - p(x,y) * \min(p-x, p-y) - p(x,y) * [x,y] \frac{|x-y|}{2} \int_{-\pi}^{\pi} p(p) dp\, dy\, dx$$

$$= \int_{-\pi}^{\pi} \int_{-\pi}^{\pi} M - p(x,y) * \min(p-x, p-y)\, dy\, dx - \int_{-\pi}^{\pi} \int_{-\pi}^{\pi} p(x,y) * [x,y] \frac{|x-y|}{2} dy\, dx$$

$$= C - TE/2.$$

In the above expressions, note that $\int_{-\pi}^{\pi} p(p) dp = 1$ and that C is a constant. This simplification clarifies that TE and U depend equally and oppositely on the values of [x,y], which are determined by the item-percept assignment; thus, they are optimized by the same assignment.

8.2: large n

For every potential peak utility attribute value p, let $p(P_p)$ be the probability that, from a set of n sampled items, at least 1 belongs to the same percept assignment group as p. Also, let $E(P_p)$ $E(\neg P_p)$ respectively be the expected values derived when at least one and when none of the sampled items belong to P_p. Then,

$$E(P_p) = \int_{-\pi}^{\pi} (M - |p-y|)[p,y]p(y)dy \Big/ \int_{-\pi}^{\pi} [p,y]p(y)dy$$

$$p(P_p) = 1 - \left(1 - \int_{-\pi}^{\pi} [p,y]p(y)dy \right)^n$$

$$U = \int_{-\pi}^{\pi} p(P_p)E(P_p) + E(\neg P_p)(1 - p(P_p))dp$$

$E(P_p)$ is unaffected by n, while as n grows, $p(P_p)$ converges to 1. This convergence allows U to be approximated as

$$U = \int_{-\pi}^{\pi} \frac{\int_{-\pi}^{\pi}(M - |p-y|)[p,y]p(y)dy}{\int_{-\pi}^{\pi}[p,y]p(y)dy} dp$$

$$= \int_{-\pi}^{\pi} \frac{M \int_{-\pi}^{\pi}[p,y]p(y)dy}{\int_{-\pi}^{\pi}[p,y]p(y)dy} dp - \int_{-\pi}^{\pi} \frac{\int_{-\pi}^{\pi}|p-y|[p,y]p(y)dy}{\int_{-\pi}^{\pi}[p,y]p(y)dy} dp$$

The first of these integrals is a constant, while the minimization of the second maximizes U. In fact, for optimization purposes, the quotient of integrals (Q) can be considered in isolation.

To illustrate the value of efficiently encoding the attribute space, I assume β = 2 and

$$p(y) = \begin{cases} .1/2\pi, [-\pi, \pi/2] \\ 3.7/2\pi, [\pi/2, \pi] \end{cases}$$

Q is straightforwardly minimized by placing boundaries at −π/2, 0, π/2, and π; this boundary placement diverges obviously from the efficient coding of p(y), which would make distinctions within the interval [π/2,π].