LEMMI: A continuous benchmarking platform for metagenomics classifiers

Mathieu Seppey[1]   ORCID: 0000-0003-3248-011X

Mosè Manni[1]   ORCID: 0000-0002-4146-6523

Evgeny M. Zdobnov[1]*

[1]Department of Genetic Medicine and Development, University of Geneva Medical School and Swiss Institute

of Bioinformatics, Geneva, Switzerland

*Corresponding author: E-mail: evgeny.zdobnov@unige.ch

Keywords

Metagenomics, taxonomic classification, read binning, reference database, benchmarking, continuous

evaluation, reproducibility, containers, bioinformatics, pipeline.

Abstract

Studies of microbiomes are booming, as well as the diversity of computational tools to make sense out of the sequencing data and the volumes of accumulated microbial genotypes. LEMMI (https://lemmi.ezlab.org) is a novel concept of a benchmarking platform of computational tools for metagenome composition assessments that introduces: a continuous integration of tools, their multi-objective ranking, and an effective distribution through software containers. Here, we detail the workflow and discuss the evaluation of some recently released methods. We see this platform eventually as a community-driven effort: where method developers can showcase novel approaches and get unbiased benchmarks for publications, while users can make informed choices and obtain standardized and easy-to-use tools.

Introduction

Metagenomics has made possible the study of previously undiscovered uncultured microorganisms. To probe the vast hidden microbial landscape, we need effective bioinformatics tools, notably taxonomic classifiers for binning the sequencing reads (i.e. grouping and labeling) and profiling the corresponding microbial community (i.e. defining the relative abundance of taxa). This is computationally challenging, requiring time and resources to query shotgun sequencing data against rapidly expanding genomic databases. Users have to choose a solution among the plethora of methods that are being developed in a quest for accuracy and efficiency, for instance lowering the runtime and memory usage by reducing the reference material while maintaining the representative diversity[1,2]. To date, at least one hundred published methods can be identified[3], and new developments that may revolutionize the field cohabit with re-implementations of already explored strategies, complicating methods selection, fragmenting the community of users, and hindering experimental reproducibility. Papers describing these methods fall in the "self-assessment trap"[4], in which all published methods are the best on carefully selected data, giving no indication to potential users about general performances, which should be a prerequisite before considering any case-specific improvements or novel features. Independent comparative benchmarking studies[5–9] and challenges[10] are a major step towards a fair assessment of methods. They can also promote developments dedicated to specific technologies or problems[11] and have brought valuable benchmarking resources[12–14]. While results in such publications are extensively discussed by the authors upon release, their content cannot be reinterpreted according to specific individual needs. More importantly, tools that were overlooked or made available after the list of methods was finalized cannot be added, maintaining a permanent uncertainty about the true state of the art and delaying the benefits that innovative developments bring in a fast-evolving field. To overcome these limitations, there is a need for a different workflow that enables continuous and generalizable comparisons of individual methods or multi-step pipelines while considering multiple objectives and their computational costs (e.g. accuracy versus memory usage).

Recommendations for efficient "omics" tool benchmarking[15–17] include using containers (i.e. isolated software packages) to allow reproducibility and long-term availability of tools[18], reporting computational resources consumption (available hardware limits the choice to otherwise less efficient

methods), exploring parameters, and avoiding rankings based on a unique metric. In the particular

case of taxonomic classification, a benchmark that uses the same reference for all methods is

necessary to perform a valid evaluation of their respective algorithms, in addition to evaluating the

variety of available databases. In line with this, we introduce LEMMI, standing for "A Live Evaluation

of Computational Methods for Metagenome Investigation" (Figure 1), a web-based platform that hosts

in its infrastructure, currently, a semi-automated benchmarking pipeline whose first available

component presented here focuses on assessing taxonomic profilers and binners. Its novel workflow

explicitly addresses key problems for the community: (i) closing the time gap between benchmarking

publications by continuously evaluating new methods, (ii) allowing heterogeneous tools and pipelines

to be evaluated together with a multi-objective exploration and ranking of their performances, (iii)

reporting computational resources, (iv) exploring parameters and references, (v) facilitating the

dissemination of easy-to-use software packages, and (vi) producing evaluations in a neutral and

controlled environment to ensure published methods have a reliable benchmark on generic problems

and unified hardware. Our solution can complement and support analyses of specific cases usually

discussed in self-evaluations or discussed periodically in comparative studies. We describe below the

advantages of the LEMMI workflow and discuss novel results from which conclusions about several

methods released recently can be drawn.

Results

A fully containerized evaluation

LEMMI inputs consist of methods wrapped in containers resembling a previously suggested format, bioboxes[14], that can be prepared by the LEMMI development teams, and envisioned to be contributed by method developers themselves. In the latter case, containers can be exchanged through public channels (e.g. https://hub.docker.com) to be loaded and run on the platform. In addition, evaluated containers can be downloaded by users from the LEMMI website along with their building sources, unless the method is commercialized and/or not under open source licensing. LEMMI is the first solution in its field to compel containerization to manage a benchmarking workflow (Supplementary Figure 1a) and therefore favor a simple access to evaluated tools. The benefits of such an approach regarding systematic re-evaluation (Supplementary Figure 1b) and re-usability are likely greater in the long term than the flexibility offered by mere results submission. As solutions that facilitate automated conversion between distribution channels are being explored (for instance from BioConda to biocontainers[19]), establishing standardized benchmarking processes that rely exclusively on these channels to obtain all methods ensure that the otherwise subjective question of installability is addressed unambiguously.

A dynamic interface to explore alternative objectives

Making informed decisions when designing analyses or pipelines requires a thorough exploration of the parameter space of available algorithms. Multiple runs of a container enable such exploration within the platform. LEMMI does not segregate methods into profilers and binners by conducting separate evaluations, as many tools now provide both features or have extra scripts that blur the demarcation (e.g. kraken[20,21] is a read classifier that can be associated with its companion tool bracken[22] to produce a valid taxonomic abundance profile). Instead, LEMMI is "results-oriented", so comparisons can be made between multi-functional tools or their combinations to generate profiles, bins, or both, in a single run that informs on the full potential of a method. These two-dimensional results can be visualized from different perspectives through a dynamic multi-criteria ranking where

104 users can put the emphasis on the metric they recognize as important (Figure 2-3, Supplementary

105 Figure 2-3, 5-9). Tradeoffs can be found to maximize the efficiency of a single tool or pipeline for both

106 tasks.

Pre-packaged and built reference databases

Some method implementations provide pre-packaged reference databases while others provide

scripts to generate them. LEMMI evaluates these pre-packaged references to include methods whose

value lies in providing a curated database (e.g. marker genes[23]) and to keep track of reference

genome catalogs available to method users. However, as the use of different reference databases is

likely a major source of result discrepancies, methods accepting any nucleotide or protein files to

construct their database can integrate the corresponding scripts in the container to be used as part of

the benchmark. This enables LEMMI to report the resources (i.e. memory, runtime) required to build a

reference in addition to those of the analysis, and assess the algorithm underlying the method

independently from the taxa that constitute its default reference database. To provide a continuous

evaluation that is unaffected by the publication of new genomic sequences, LEMMI maintains an in-

house repository currently based on all bacterial and archaeal RefSeq[24] assemblies. However, only

entries having both nucleotide and corresponding protein files are kept to offer the two types of

molecules as a possible reference with equal representation (hereafter, the LEMMI/RefSeq

repository). It can be subsampled by publication date, assembly states, or a fixed number of

representatives per taxonomic identifier (taxid). As for parameters, this enables for each method the

exploration of references, for instance by restraining the source material to what was available at a

given date (Supplementary Figure 3) or to specific criteria (e.g. assembly states being only "Complete

Genome"). Not every method can process the 125,000 genomes included in LEMMI/RefSeq with the

resources provided (245 GB of RAM, representing a medium-scale environment). It is therefore

relevant both to assess which subsets constitute good tradeoffs in terms of runtime, memory use, and

accuracy of the predictions, and to track the impact of continuous database growth on different

methods[25].

In-silico datasets and genome exclusion

LEMMI uses its repository not only as source material provided to each method to create their

reference database, but also for sampling mock microbial communities to generate in-silico paired-

end short reads used to measure the accuracy of predictions made by each method. It implements a

genome exclusion[26] approach to simulate unknown organisms at various taxonomic ranks and to

prevent overfitting by excluding the source of the analyzed reads from the reference (Supplementary

Figure 4, see Online Methods). Simulating taxa that have no corresponding organisms in the

reference also makes LEMMI datasets good proxies to real life scenarios and creates a challenging

problem that can be useful to spot methods producing an excess of false positive matches (Figure

3C). Datasets generated in-house by LEMMI contain randomly sampled bacteria and archaea,

representing generic communities of variable complexity in terms of number of species, abundance

distribution (i.e. absence or presence of taxa below 100 reads), and k-mers content. Their description

is presented in Supplementary Table 1. Their detailed taxonomic compositions remain private as long

as they are in use in the platform and will be published when LEMMI moves to its next major release.

A demo dataset is available to exemplify their typical composition and help preparing a method

container for evaluation. LEMMI datasets are complemented by others used in previously published

benchmarking studies (CAMI1[10] and mockrobiota[27]). This enables comparisons with past results and

introduces variety in the dataset creation methods, which is useful to identify behaviors inherent to the

benchmarking design (Supplementary Note). Detailed evaluation results using up to 17 metrics are

presented individually in interactive plots for each dataset and taxonomic rank, namely genus and

species (Figure 3, Supplementary Figure 2-3, 5-9, Supplementary Table 2).

Two benchmarking categories

To allow a separate interpretation of evaluations conducted with pre-processed databases (meaning

no genome exclusion and thus potential overfits of some references) from those conducted under an

identical set of genomes absent from the source of in-silico reads, LEMMI distinguishes two

benchmarking categories (Figure 2). When choosing "TOOLS & REFERENCES", users can get an

overview of all tools and references that exist, giving an outline of the ability of currently available

approaches to capture the known microbial diversity, strongly influenced by the database sampling

strategy and creation date, but reflecting what practitioners will encounter when using ready-to-use

solutions. The second category, "METHOD ALGORITHMS", considers only methods and datasets

that permit the creation of a reference, using genome exclusion, that will be identical for each run.

This is the best possible benchmark for developers to support their algorithm improvement claims,

and for advanced user interested in producing their own reference database after selecting the most

efficient method.

164 Evaluation of recent methods

The release of the LEMMI benchmarking platform described here (beta01.20191002) includes the

well-established methods Centrifuge[1], Kraken1[20] and Kraken2[21] associated with Bracken[22], Kaiju[28],

and Metaphlan2[2]. They are a good representation of the field as it is today, as they stand among

methods evaluated together recently[6]. This allows LEMMI users to judge additional methods never

evaluated before side-by-side with tools they are already familiar with. We highlight on Figure 2,

Figure 3, and Supplementary Figure 2, 5-8 a glimpse of the performances of the novel algorithms

implemented by Ganon[29], Metacache[30], and CCMetagen[31], which are described in their supporting

publications but currently absent from comparative benchmarks. We report overall very good

performances in recall and precision at the species level for Metacache and Ganon, which make them

worth considering as alternatives to older solutions if their specific innovations, for instance the ability

to update the database provided by Ganon, are beneficial to the user. These tools perform well when

compared to other solutions using a freely selected references (Figure 2, Figure 3AB) as well as when

compared to other tools using an identical built reference (Figure 3C, Supplementary Figure 5). They

are also top scorers when taxonomic binning objectives are considered (Supplementary Figure 6).

CCMetagen shows very good precision but suffers from a poor recall, except when analyzing the two

datasets having a lower number of species (Figure 3ABC, Supplementary Figure 7). As LEMMI minor

releases are continuously produced, the current list of methods and databases (Supplementary Table

3) will rapidly be enriched. To appreciate the full extent of the results through detailed plots, we invite

readers to visit the LEMMI web platform (https://lemmi.ezlab.org).

Evaluation of different references with Kraken2

Taking advantage of LEMMI flexible reference construction, we appreciated the improvement of the

Kraken algorithm in its second version[21] regarding its ability to build comprehensive references

without using a considerable amount of memory. It is the most efficient to that aspect among the

methods evaluated in LEMMI so far (Figure 3D, Supplementary Figure 8) and it remains among the

top scoring methods when combined with Bracken 2.0, being the top scorer in relative abundance

estimation (Figure 2-3, Supplementary Figure 2). This lower memory usage enables LEMMI to run

Kraken2 using of all entries in LEMMI/RefSeq to be compared to using the pre-built MiniKraken

database, a reference intended for low memory environments and created by subsampling k-mers on

"Complete genomes" (CG) sequences only. The diversity of datasets offered by LEMMI shows that

good performances of Minikraken depend almost entirely on the source of the in-silico reads being

CG sequences. This way of limiting source genomes, unrelated to the Minikraken k-mers

subsampling strategy, ignores the large part of the diversity proxied by NCBI species taxids that have

no CG representatives (Supplementary Note). This can be observed when analyzing CAMI1 datasets,

in which a large proportion of taxa is overlooked while it could actually be recovered using

LEMMI/RefSeq as reference (Supplementary Figure 9).

Discussion

Here, we introduce the first of its kind continuous integration benchmarking platform for metagenomics

classifiers to enable immediate and independent evaluation of any newly published method using

datasets of various compositions that can be generated or reused from previous effort. In addition, we

highlight the high potential of some recently published methods unevaluated independently before, and

ensure that future promising developments will join the ranking soon after they are identified as such.

We also show the importance of considering all assembly states issued from RefSeq to avoid missing

most of the diversity produced by year of microbial genome sequencing. Therefore, better subsampling

strategies than simply keeping CG sequences should be explored by database creators to mitigate the

problem of insufficient computational resources when conducting analyses. Moreover, future

benchmarking efforts should not rely exclusively on CG to evaluate methods in order to assess the true

ability of methods to scale with the ever-growing diversity of sequenced taxa.

LEMMI envisions a sustainable life cycle (Supplementary Figure 1b), encouraging feedback from the

community of method developers and users. It ensures a traceable archive of past rankings through

the use of unique "fingerprints" to be reported in publications. While the current major release of LEMMI

uses the NCBI taxonomy[32] and has put the focus on evaluating the lowest supported ranks, i.e. genus

and species, it is designed to integrate alternative ranks or taxonomies. There are calls to revise NCBI

taxonomy[33,34] and future method implementations could be more agnostic regarding taxonomic

authority (i.e. configuring the ranks and identifiers, instead of having the NCBI taxonomy entangled with

the core classification algorithm). This would enable the exploration of new approaches meant to

improve the classification resolution (e.g. reaching bacterial strains, viral operational taxonomic units[35]).

New LEMMI datasets (e.g. also including long read technologies) will be produced for the next major

release to replace those in use today, integrating newly discovered taxon or covering currently

unsupported clades. Having all methods containerized will facilitate a systematic re-evaluation of all

valuable ones. Developers interested in submitting their tools can visit https://lemmi.ezlab.org, where

documentation, support, a discussion board, and evaluated containers are available. Future extensions

of LEMMI may also include a standalone version to allow private assessment and help with

development before submitting to the public platform for an independent evaluation.

Benchmarking has become a must-have requirement for publishing novel methods. To bring credibility

and facilitate the adoption by their target audience, it is essential that methods appear side-by-side with

established competitors in a trusted independent ranking. The technology of containerization has a

strong future in the bioinformatics community. Therefore, LEMMI will encourage developers to consider

biocontainers to disseminate their work and to standardize the results formats so users will obtain easy-

to-use and stable implementations of up-to-date methods as they appear in the benchmark.

Online Methods

Release strategy

LEMMI rankings are identified by the major release version of the platform (e.g beta01) and the minor release date (e.g. 20191002). Until the next major release, the content of the LEMMI/RefSeq repository, the version of the NCBI taxonomy, and the datasets are frozen to a specific version that guarantees exact comparisons. Continuous additions or withdrawals of an entry in the rankings generate a new minor release date, while previous rankings remain accessible by requesting old fingerprints (e.g. https://lemmi.ezlab.org/#/rankings/SD.DEFAULT.beta01.20191002).

Structure of the pipeline

An in-house python3-based[36,37] controller coordinates the many subtasks required to generate datasets, run the candidate containers, and compute the statistics. Snakemake 5.3.1[38] is used to supervise individual subtasks such as generating a dataset or running one evaluation. The process is semi-automated through configuration files, designed to allow a potential full automation through a web application. To be easily deployable, the benchmarking pipeline itself is wrapped in a Docker container. The plots presented on the user interface are generated with the mpld3 library[39]: https://mpld3.github.io.

LEMMI containers

The LEMMI containers are implemented for Docker 18.09.0-ce. They partially follow the design[40] introduced by http://bioboxes.org/ as part of the first CAMI challenge effort. The required output files are compatible with the profiling and binning format created for the CAMI challenge. Two tasks have to be implemented in order to generate a reference and conduct an analysis. To take part in the benchmark, a method developer has to build the container on their own environment, while ensuring that both tasks can be run by an unprivileged user and return the desired outputs. A tutorial is available on https://gitlab.com/ezlab/lemmi/wikis/user-guide. The containers or the sources to recreate

260 them are made available to the users. The sources of all method containers presented as results in

261 this study are available on https://gitlab.com/ezlab/lemmi/tree/beta01.20191002/containers.

Computing resources

263 During the benchmarking process, the container is loaded on a dedicated server and given 245 GB of

264 RAM and 32 cores. Reaching the memory limit will cause the container to be killed ending the

265 benchmarking process unsuccessfully. All inputs and outputs are written on a local disk and the

266 container is not given access to the Internet.

Taxonomy

268 The NCBI taxonomy is used to validate all entries throughout the process and unknown taxids are

269 ignored (unclassified). The framework etetoolkit[41] (ETE3) is used to query the taxonomy. The

270 database used in beta01 was downloaded on 03/09/2018 and remains frozen to this version until a

271 new major release of the LEMMI platform.

RefSeq repository

All RefSeq assemblies for bacteria, archaea, and viruses were downloaded from

ftp.ncbi.nlm.nih.gov/refseq/release (download date for the beta01 release was 08/2018) with the

conditions that they contained both a protein and a nucleotide file and that their taxid has a

corresponding entry in the ETE3 NCBI taxonomy database, for a total of 132,167 files of each

sequence type. The taxonomic lineage for the seven main levels was extracted with ETE3

(superkingdom, phylum, class, order, family, genus, species). Viruses were not used for generating

references and datasets in this proof of concept study and the number of genomes in the reference

RefSeq/08.2018/All is 124,289. To subset the repository and keep one representative per species as

inputs for the reference construction (for entries labelled as RefSeq/08.2018/1rep.), the list of bacterial

and archaeal genomes was sorted according to the assembly states (1:Complete Genome,

2:Chromosome, 3:Scaffold, 4:Contig) and the first entry for each species taxid was retained, for a total

of 18,907 files. When subsampling the repository in the genome exclusion mode (i.e. for the

METHOD ALGORITHMS category, Supplementary Figure 4), if the entry to be selected was part of

the reads, the next representative in the list was used instead when available.

LEMMI datasets

To sample the genomes included in the LEMMI datasets, a custom python script was used to

randomly select representative genomes in the LEMMI/RefSeq assembly repository, among bacterial

and archaeal content (Supplementary Table 1). Their abundance was randomly defined following a

lognormal distribution (mean=1, standard deviation in Supplementary Table 1). In the case of

LEMMI_LOWDIV datasets, additional low coverage species (abundance corresponding to < 100

reads) were manually defined while in LEMMI_MEDDIV datasets, low coverage species were

produced as part of the random sampling procedure. Each species abundance was normalized

according to the species average genome size (as available in the LEMMI/RefSeq repository) to get

closer to organisms' abundance (considering one genome copy per cell), and the total was

normalized to one to constitute a relative abundance profile. Therefore, both tools classifying all reads

and those using markers genes can normalize their output to provide a unified answer. BEAR[42] was

used to generate paired-end reads, 2x150 bp, and DRISEE[43] was used to extract an error profile from

the SRA entry ERX2528389 to be applied onto the generated reads. The ground truth profile for the

seven taxonomic ranks, and taxonomic bins for species and genus were kept. The non-unique 50-

mers and 31-mers diversity of the obtained reads were generated with Jellyfish 2.2.8[44] on the

concatenated pair of reads using the following parameters: jellyfish count -m 31 -s 3G --bf-size 5G -t 8

-L 1 reads.fq.

Additional datasets

The CAMI1 datasets were obtained from https://data.cami-challenge.org/ (accessed 09/2018) along

with the metadata describing their content, already in the expected file format. The binning details

were reprocessed to obtain distinct lists at the species and genus rank. The mockrobiota-17 dataset[45]

was obtained through https://github.com/caporaso-lab/mockrobiota and reprocessed to obtain a

taxonomic profile in the appropriate format. No binning detail is available for this dataset, therefore no

assessment of this aspect is based on this dataset. 50-mers and 31-mers diversity were computed as

detailed above.

Analysis of the results

The profile and binning reports are processed with OPAL 0.2.8[12] and AMBER 0.7.0[13] against the

ground truth to obtain a wide range of metrics. Binning reports are processed to obtain a file for each

taxonomic rank (genus/species), moving reads up from lowest level. The profiles of the candidate

methods and the ground truth are filtered to discard low coverage taxa at different thresholds (below

values corresponding to 1/10/100/1000 reads) and all metrics are computed for all values. When a

container is not able to provide a profile as output, the LEMMI platform generates one using the

proportion of reported reads. Taxa detection metrics are based on OPAL and thus on the profile

output. Methods reporting a profile with 0.0 for low abundance taxa despite being present in their

binning files will shift the balance from recall to precision. The low abundance score takes into

account both the profile and binning output and is a custom metric calculated separately to evaluate

the ability of the method to correctly identify organisms represented with very low read coverage, but

penalizing methods likely to recover them by recurrent report of the same taxids owed to very poor

precision. To achieve this, as precision of low abundance organisms cannot be defined for a single

dataset (false positives always have a true abundance of zero and cannot be categorized as low

abundance), the metric is computed by pairing two datasets to judge if a prediction can be trusted.

The datasets (D1 and D2) include sets of taxa T1 and T2 that contain a subset of low abundance taxa

(T1_low ≠ T2_low, < 100 reads coverage,). Each taxon belonging to T1_low identified in D1 increases

the low abundance score given to the method for D1 (recall) only when it is not identified in D2 if

absent from T2. Otherwise, a correct prediction of the taxon in D1 is canceled and does not improve

the score (acting as proxy for low abundance precision). This is illustrated with Supplementary Figure

10. The score (0.0 - 1.0) is processed from both sides (D1, D2), to obtain an independent score for

each of the paired dataset. This metric is only defined for the pair of LEMMI_LOWDIV and the pair of

LEMMI_MEDDIV datasets (low abundance species: n=10, n=8, n=98, n=138 for

LEMMI_LOWDIV_001, LEMMI_LOWDIV_002, LEMMI_MEDDIV_001, LEMMI_MEDDIV_002

respectively). The runtime corresponds to the time in minutes during which the container is loaded.

The memory is the peak value of total_rss memory reported when the container is loaded to complete

one task. Methods unable to deliver part of the expected outputs are assigned 0.0 for the

corresponding metrics (e.g. methods unable to provide a read binning report).

Ranking score

All metrics that are not already values between 0.0 and 1.0, with 1.0 being the best score, are

transformed. The L1 distance is divided by its maximum value of 2.0 and subtracted from 1.0, the

weighted UniFrac score is divided by its maximum value of 16.0 and subtracted from 1.0. The

unweighted UniFrac score is divided by an arbitrary value of 25,000 and subtracted from 1.0. The

memory and runtime are divided by 2x the maximum value (as defined by the LEMMI user through

the interface) and subtracted from 1.0, to obtain a range between 0.5 and 1.0. This approach allows

the user to segregate methods that remain below the limit from those that exceed it and get the value

0.0. Any transformed metric below 0.0 or above 1.0 is set to be 0 and 1 respectively. Each value is

calculated for genus and species at 1, 10, and 100 reads low coverage filtering level and used or

ignored according to the choice of the LEMMI user regarding these parameters. The final score

displayed in the ranking is the harmonic mean of all metrics, taken into account 0, 1, or 3 times

depending on the weight assigned to the metric by the LEMMI user.

Data availability

356   All containers representing evaluated methods are available on https://lemmi.ezlab.org. The LEMMI

357   demo dataset is available in the Zenodo repository with the identifier.

358   https://zenodo.org/record/2651062.

Acknowledgement

360   We would like to thank all members of the Zdobnov group for discussions and feedback. This work

361   was supported by the Swiss National Science Foundation funding 31003A_166483 and

362   310030_189062 to E.Z.

Author contributions

MS and EZ conceived the study. MS coded the platform. MS and MM conducted the analyses. MS and MM wrote the documentation. MS, MM and EZ wrote the manuscript.

Competing interests

The authors declare no competing interests.

Reference

1. Kim, D., Song, L., Breitwieser, F. P. & Salzberg, S. L. Centrifuge: rapid and sensitive classification of metagenomic sequences. *Genome Res.* **26**, 1721–1729 (2016).

2. Truong, D. T. *et al.* MetaPhlAn2 for enhanced metagenomic taxonomic profiling. *Nat. Methods* **12**, 902–903 (2015).

3. Jacobs, J. Microbe Land. (2018). https://microbe.land/2018/12/13/97-metagenomics-classifiers/

4. Norel, R., Rice, J. J. & Stolovitzky, G. The self-assessment trap: can we all be better than average? *Mol. Syst. Biol.* **7**, 537 (2011).

5. McIntyre, A. B. R. *et al.* Comprehensive benchmarking and ensemble approaches for metagenomic classifiers. *Genome Biol.* **18**, 182 (2017).

6. Ye, S. H., Siddle, K. J., Park, D. J. & Sabeti, P. C. Benchmarking Metagenomics Tools for Taxonomic Classification. *Cell* **178**, 779–794 (2019).

7. Lindgreen, S., Adair, K. L. & Gardner, P. P. An evaluation of the accuracy and speed of metagenome analysis tools. *Sci. Rep.* **6**, (2016).

8. Gardner, P. P. *et al.* Identifying accurate metagenome and amplicon software via a meta-analysis of sequence to taxonomy benchmarking studies. *PeerJ* **7**, e6160 (2019).

9. Peabody, M. A., Van Rossum, T., Lo, R. & Brinkman, F. S. L. Evaluation of shotgun metagenomics sequence classification methods using in silico and in vitro simulated communities. *BMC Bioinformatics* **16**, (2015).

10. Sczyrba, A. *et al.* Critical Assessment of Metagenome Interpretation—a benchmark of

metagenomics software. *Nat. Methods* **14**, 1063–1071 (2017).

11. Bremges, A. & McHardy, A. C. Critical Assessment of Metagenome Interpretation Enters the

Second Round. *mSystems* **3**, (2018).

12. Meyer, F. *et al.* Assessing taxonomic metagenome profilers with OPAL. *Genome Biol.* **20**, (2019).

13. Meyer, F. *et al.* AMBER: Assessment of Metagenome BinnERs. *GigaScience* **7**, (2018).

14. Belmann, P. *et al.* Bioboxes: standardised containers for interchangeable bioinformatics software.

GigaScience **4**, (2015).

15. Capella-Gutierrez, S. *et al. Lessons Learned: Recommendations for Establishing Critical Periodic*

Scientific Benchmarking. (Bioinformatics, 2017). doi:10.1101/181677

16. Mangul, S. *et al.* Systematic benchmarking of omics computational tools. *Nat. Commun.* **10**, 1393

(2019).

17. Maier-Hein, L. *et al.* Why rankings of biomedical image analysis competitions should be

interpreted with care. *Nat. Commun.* **9**, (2018).

18. Mangul, S., Martin, L. S., Eskin, E. & Blekhman, R. Improving the usability and archival stability of

bioinformatics software. *Genome Biol.* **20**, (2019).

19. da Veiga Leprevost, F. *et al.* BioContainers: an open-source and community-driven framework for

software standardization. *Bioinformatics* **33**, 2580–2582 (2017).

20. Wood, D. E. & Salzberg, S. L. Kraken: ultrafast metagenomic sequence classification using exact

alignments. *Genome Biol.* **15**, R46 (2014).

21. Wood, D. E., Lu, J. & Langmead, B. *Improved metagenomic analysis with Kraken 2.*

(Bioinformatics, 2019). doi:10.1101/762302

22. Lu, J., Breitwieser, F. P., Thielen, P. & Salzberg, S. L. Bracken: estimating species abundance in

metagenomics data. *PeerJ Comput. Sci.* **3**, e104 (2017).

23. Truong, D. T. *et al.* MetaPhlAn2 for enhanced metagenomic taxonomic profiling. *Nat. Methods*

12, 902–903 (2015).

24. O'Leary, N. A. *et al.* Reference sequence (RefSeq) database at NCBI: current status, taxonomic

expansion, and functional annotation. *Nucleic Acids Res.* **44**, D733–D745 (2016).

25. Nasko, D. J., Koren, S., Phillippy, A. M. & Treangen, T. J. RefSeq database growth influences the

accuracy of k-mer-based lowest common ancestor species identification. *Genome Biol.* **19**,

(2018).

26. Peabody, M. A., Van Rossum, T., Lo, R. & Brinkman, F. S. L. Evaluation of shotgun

metagenomics sequence classification methods using in silico and in vitro simulated

communities. *BMC Bioinformatics* **16**, (2015).

27. Bokulich, N. A. *et al.* mockrobiota: a Public Resource for Microbiome Bioinformatics

Benchmarking. *mSystems* **1**, (2016).

28. Menzel, P., Ng, K. L. & Krogh, A. Fast and sensitive taxonomic classification for metagenomics

with Kaiju. *Nat. Commun.* **7**, (2016).

29. Piro, V. C., Dadi, T. H., Seiler, E., Reinert, K. & Renard, B. Y. ganon: continuously up-to-date with

database growth for precise short read classification in metagenomics. *bioRxiv* 406017 (2018).

doi:10.1101/406017

30. Müller, A., Hundt, C., Hildebrandt, A., Hankeln, T. & Schmidt, B. MetaCache: context-aware

classification of metagenomic reads using minhashing. *Bioinformatics* **33**, 3740–3748 (2017).

31. Marcelino, V. R. *et al. CCMetagen: comprehensive and accurate identification of eukaryotes and*

prokaryotes in metagenomic data. bioRxiv 641332 (2019). doi:10.1101/641332

32. Federhen, S. The NCBI Taxonomy database. *Nucleic Acids Res.* **40**, D136–D143 (2012).

33. Parks, D. H. *et al. Selection of representative genomes for 24,706 bacterial and archaeal species*

clusters provide a complete genome-based taxonomy. (Microbiology, 2019). doi:10.1101/771964

34. Parks, D. H. *et al.* A standardized bacterial taxonomy based on genome phylogeny substantially

revises the tree of life. *Nat. Biotechnol.* (2018). doi:10.1038/nbt.4229

35. Paez-Espino, D. *et al.* IMG/VR v.2.0: an integrated data management and analysis system for

cultivated and environmental viral genomes. *Nucleic Acids Res.* **47**, D678–D686 (2019).

36. McKinney, W. Data Structures for Statistical Computing in Python. 6 (2010).

37. Oliphant, T. E. *Guide to NumPy*. (2015).

38. Koster, J. & Rahmann, S. Snakemake--a scalable bioinformatics workflow engine. *Bioinformatics*

28, 2520–2522 (2012).

39. Hunter, J. D. Matplotlib: A 2D Graphics Environment. *Comput. Sci. Eng.* **9**, 90–95 (2007).

40. Belmann, P. *et al.* Bioboxes: standardised containers for interchangeable bioinformatics software.

GigaScience **4**, (2015).

41. Huerta-Cepas, J., Serra, F. & Bork, P. ETE 3: Reconstruction, Analysis, and Visualization of

Phylogenomic Data. *Mol. Biol. Evol.* **33**, 1635–1638 (2016).

42. Johnson, S., Trost, B., Long, J. R., Pittet, V. & Kusalik, A. A better sequence-read simulator

program for metagenomics. *BMC Bioinformatics* **15**, S14 (2014).

43. Keegan, K. P. *et al.* A Platform-Independent Method for Detecting Errors in Metagenomic

Sequencing Data: DRISEE. *PLoS Comput. Biol.* **8**, e1002541 (2012).

44. Marçais, G. & Kingsford, C. A fast, lock-free approach for efficient parallel counting of

occurrences of k-mers. *Bioinformatics* **27**, 764–770 (2011).

45. Kozich, J. J., Westcott, S. L., Baxter, N. T., Highlander, S. K. & Schloss, P. D. Development of a

Dual-Index Sequencing Strategy and Curation Pipeline for Analyzing Amplicon Sequence Data

on the MiSeq Illumina Sequencing Platform. *Appl. Environ. Microbiol.* **79**, 5112–5120 (2013).

Figures

Fig. 1 | Connecting users and developers through benchmarking. The LEMMI platform facilitates

the access to up-to-date implementations of methods for taxonomic binning and profiling. LEMMI

creates a link between developers and users as it provides independent and unbiased benchmarks

that are valuable to both. Developers need comparative evaluations to keep improving the

methodology and to get their work published in peer-reviewed journals. Method users need a

resource that keeps track of new developments and provides a flexible assessment of their

performances to match their experimental goals, resources, and expectations. The containerized

approach of LEMMI guarantees the transfer of a stable and usable implementation of each method

from the developer to the final user, as they appear in the evaluation.

Fig. 2 | LEMMI web interface. (i) The LEMMI users obtain a list of entries suited to their needs through the dynamic ranking interface that allows them to select and weight the criteria that are important. The ranking visible here shows the performances when identifying species while ignoring taxa under 100 reads, balancing precision and recall. The score assigned to each entry visible in LEMMI rankings averages selected metrics over all tested datasets. (ii) A unique "fingerprint" allows custom rankings to be shared and restored at any time on the LEMMI platform through the address bar. (iii) The benchmark category can be selected in the dashboard. (iv) Prediction accuracy metrics can be chosen along with their importance (Weight for "Important" is 3, "Somewhat" is 1, and "Not at all" is 0). This will cause the list to be updated with the corresponding scores. (v) Several presets corresponding to common expectations are available. (vi) Computational resources and the time required to complete the analysis can be included as an additional factor to rank the methods.

Fig. 3 | "Details by datasets" interface. Plots for up to 17 metrics are available for each dataset and

the LEMMI user can toggle each line representing a method associated with a reference and specific

parameters individually (*). Plots can be zoomed in to disentangle overlapping points and permit

focused interpretations (**). The pages exist for all taxonomic ranks investigated, i.e. genus and

species in the release beta01. The illustration shows in the upper panel (a) the precision-recall curve

in species identification of a mix of methods using references freely provided or built using the current

maximal capacity of LEMMI of 245GB, and (b) the corresponding area under the precision-recall

curve. The lower panels show results when assessing methods using an identical built reference, with

panel (c) illustrating how LEMMI assesses the precision improvement by filtering low abundance taxa,

and (d) reporting the peak of memory necessary to construct the reference.