Identifying complex motifs in massive omics data with a variable-convolutional layer in deep neural network

Jing-Yi Li[1,#], Shen Jin[2,#], Xin-Ming Tu[1], Yang Ding[1,3,*], and Ge Gao[1,*]

[1] Biomedical Pioneering Innovation Center (BIOPIC) & Beijing Advanced Innovation Center for Genomics (ICG), Center for Bioinformatics (CBI), and State Key Laboratory of Protein and Plant Gene Research at School of Life Sciences, Peking University, Beijing, 100871, China, [2] Computational Biology Department, Carnegie Mellon University, Pittsburgh, Pennsylvania, 15213,[3] Current address: Beijing Institute of Radiation Medicine, Beijing, 100850, China

[#] These authors contributed equally to this work.

[*] To whom correspondence should be addressed. Email: gaog@mail.cbi.pku.edu.cn, and mail could also be sent to dingy@mail.cbi.pku.edu.cn

Biographical Note:

Ge Gao is a Principal Investigator at the Biomedical Pioneering Innovation Center (BIOPIC) & Beijing Advanced Innovation Center for Genomics (ICG), Peking University. His research group focuses on developing novel computational tools for deciphering the function and evolution of gene regulation circuits.

Yang Ding is a PostDoc Research Fellow at Beijing Institute of Radiation Medicine. He is interested in high-throughput computing-based data mining and methodology development in genomics and bioinformatics.

Jing-Yi Li is a Ph.D. candidate at Peking University. He is interested in developing deep learning methods for omics data.

Xin-Ming Tu is an undergraduate student at Peking university. He is interested in using machine learning to understand genomics.

Shen Jin is a PhD candidate student at Technische Universität München. He is interested in using computational methods to understand host-microbe interactions.

ABSTRACT

Motif identification is among the most common and essential computational tasks for

bioinformatics and genomics. Here we proposed a novel convolutional layer for deep neural

network, named Variable Convolutional (vConv) layer, for effective motif identification in high-

throughput omics data by learning kernel length from data adaptively. Empirical evaluations on

DNA-protein binding and DNase footprinting cases well demonstrated that vConv-based

networks have superior performance to their convolutional counterparts regardless of model

complexity. Meanwhile, vConv could be readily integrated into multi-layer neural networks as

an "in-place replacement" of canonical convolutional layer. All source codes are freely available

on GitHub for academic usage.

INTRODUCTION

Recurring sequence motifs [1, 2] have been well demonstrated to exert or regulate important biological functions, such as protein binding [3], transcription initiation [4], alternative splicing [5], subcellular localization [6], translation control [7], and microRNA targeting [8]. Effectively and efficiently identifying these motifs in massive omics data is a critical step for follow-up investigations.

Various computational tools have been developed to identify sequence motifs via word-based and profile-based models [9-14]. Word-based tools start with a fixed-length and conservative segment and then perform a global scanning; such tools include DREME [15], Fmotif [16], RSAT peak-motifs [17], SIOMICS [18, 19], and Discover [20]. While these tools can theoretically obtain the globally optimal solution, they suffer from high computational complexity when applied to data with complex motifs or large-scale datasets [10]. Profile-based tools attempt to find representative motifs by heuristically fine-tuning a series of possible motifs, either generated from a subset of input data or randomly chosen [21-25], leading to a faster (but probably sub-optimal) motif calling [12].

Several convolutional neural network (CNN)-based tools have been proposed recently as a more scalable approach for identifying motifs. Alipanahi et al. developed DeepBind to identify protein binding motifs from large-scale ChIP-Seq datasets [26] by treating each convolutional kernel as an individual motif scanner and discriminating motif-containing sequences from others based on the output of all kernels. Along with this line, several convolution-based networks have been proposed to effectively handle large amount of data in various settings [27-34]. Meanwhile, however, the inherent fixed-kernel design of canonical convolutional networks could hinder effective identification [35-37] of *bona fide* sequence patterns, which are usually of various lengths and unknown *a priori* and often function combinatorially [38, 39]. One possible workaround is to build these representations in a hierarchical manner [28, 32], yet the deeper structure itself would demand additional time/space cost for network training and hyper-parameter search (also see Supplementary Notes 1).

Here, we proposed a novel convolutional layer for deep neural network called Variable Convolutional neural layer (vConv), which learns the kernel length directly from the data. Evaluations based on both simulations and real-world datasets showed that vConv-based networks outperformed canonical convolution-based networks, making it an ideal option for the *ab initio* discovery of motifs from high-throughput datasets. Further inspection also suggested the vConv layer being robust for various hyper-parameter setups. All source codes are publicly available on GitHub (https://github.com/gao-lab/vConv).

MATERIAL AND METHODS

Design and implementation of vConv

Without loss of generality, we focus on nucleotide sequences where each nucleotide can take

only one of four alphabets (A, C, G, and T (for DNA) or U (for RNA)). vConv (Fig. 1) is designed

to be a convolutional layer equipped with a trainable "mask" to adaptively tune the effective

length of the kernel during training.

In brief, vConv uses the trainable left and right boundary values ($w_m^{z,0}$ and $w_m^{z,1}$, respectively) to

generate two sigmoid functions ($S(x) = \frac{1}{1+e^{-x}}$) of opposite orientations (Fig. 1A-B), overlays

them to define the final mask (Fig. 1C and Equation 5), uses this mask to mask a raw kernel

(Fig. 1D), and finally uses the masked kernel to convolve sequences (Fig. 1E).

$$f^*\left(\left(w_m^{z,0}, w_m^{z,1}\right)\right)[i,j] := \frac{1}{1+e^{-\left((i-1)-w_m^{z,0}\right)}} + \frac{1}{1+e^{-\left(w_m^{z,1}-(i-1)\right)}} - 1 \quad (5)$$

In practice, for a kernel with length L, the mask is generated as follows:

(1) We first generate an $L \times 4$ matrix M where $M[i,j] = i - 1$ (the grey numbered matrix in

Fig. 1A-B);

(2) We generate the first sigmoid ($\frac{1}{1+e^{-\left((i-1)-w_m^{z,0}\right)}}$ in Equation (5)) by subtracting $w_m^{z,0}$ from M

followed by a sigmoid transformation, thus pushing all those $M[i,j]$ ($i \ll w_m^{z,0}$) towards 0

and all those $M[i,j]$ ($i \gg w_m^{z,0}$) towards 1 (white and black cells in Fig. 1A, respectively);

(3) Similarly, we generate the second sigmoid ($\frac{1}{1+e^{-\left(w_m^{z,1}-(i-1)\right)}}$ in Equation (5)) by adding $w_m^{z,0}$

to $-1 \times M$ followed by a sigmoid transformation, thus pushing all those $M[i,j]$ ($i \ll w_m^{z,1}$)

towards 1 and all those $M[i,j]$ ($i \gg w_m^{z,1}$) towards 0 (black and white cells in Fig. 1B,

respectively);

(4) Finally, we sum up the two sigmoid functions and shift all elements by -1 to restrict them

within [0, 1] (Fig. 1C) to get the final mask.

One can multiply this mask and the original kernel by the Hadamard product ∘ (i.e., $f^*(w_m^z)$ ∘

w^z) to effectively mask the raw kernel with the corresponding close-to-0 elements and obtain

the masked kernel (Fig. 1D). This masked kernel can then be used as an ordinary kernel in a

canonical convolutional layer (Fig. 1E). During training, the masking is essentially an operator

with trainable weights ($w_m^{z,0}$ and $w_m^{z,1}$) and will be automatically trained together with other

weights.

As Equation 5 implies, all i's falling outside the boundaries (i.e., $i < w_m^{z,0}$ or $i > w_m^{z,1}$) have their

(masking) elements $f^*\left(\left(w_m^{z,0}, w_m^{z,1}\right)\right)[i,j]$ close to zero, and all i's within the boundaries have

their elements close to 1; those i's around the boundaries have their elements around 0.5, thus

'soft'-masking boundary kernel elements.

To make $w_m^{z,0}$ and $w_m^{z,1}$ converge faster during training, we combine the binary cross-entropy

(BCE) loss with a sum of masked Shannon losses (MSLs) from each kernel mask.

Mathematically, we have the following total loss L:

$\quad L = \text{BCE} + \lambda \cdot \sum_z MSL(w^z, w_m^z)$

$\quad = \sum_{c=1}^{N} \left(y_c \log \hat{y}_c + (1 - y_c) \log \left(1 - \hat{y}_c \right) \right) + \lambda \cdot \sum (f^*(w_m^z) \cdot H(P_z) - threshold)$ (6)

where $H(P_z) := \sum_{i=1}^{L_k} (-\sum_{j=1}^{4} ((P_z)[i,j]) log_2((P_z)[i,j]))$ is the sum of the Shannon entropy across

all nucleotide positions of P_z, the position weight matrix (PWM) learned by the z-th kernel. For

preciseness, we set $P_z = P(w^z, b = 2)$, where $(P_z)[i,j] = \frac{(w^z)[i,j]}{\sum_{i'=1}^{4}(w^z)[i',j]}$ following the exact

kernel-to-PWM transformation specified by Ding et al. [40]. One can then immediately deduce

the formula for updating the left boundary $w_m^{z,0}[t-1]$ at time step t via gradient descent with

learning rate r (r>0):

$$w_m^{z,0}[t] = w_m^{z,0}[t-1] - r \cdot \frac{\partial L(D)}{\partial w_m^{z,0}[t-1]}$$

$$= w_m^{z,0}[t-1] - r \cdot \frac{\partial BCE}{\partial w_m^{z,0}[t-1]} - r \cdot \frac{\partial MSL(w^z, w_m^z[t-1])}{\partial w_m^{z,0}[t-1]}$$

$$= w_m^{z,0}[t-1] - r \cdot \frac{\partial BCE}{\partial w_m^{z,0}[t-1]} + r \sum_{i=0}^{L_k-1} \frac{e^{-((i-1)-w_m^{z,0}[t-1])}}{(1 + e^{-((i-1)-w_m^{z,0}[t-1])})^2} 2(H(P(w^z, 2))_i$$

$$- threshold)$$

Similarly, for updating the right boundary $w_m^{z,1}[t-1]$, we have:

$$w_m^{z,1}[t] = w_m^{z,1}[t-1] - r \cdot \frac{\partial L(D)}{\partial w_m^{z,1}[t-1]}$$

$$= w_m^{z,1}[t-1] - r \cdot \frac{\partial BCE}{\partial w_m^{z,1}[t-1]} - r \sum_{i=0}^{L_k-1} \frac{e^{-(w_m^{z,1}[t-1]-(i-1))}}{(1 + e^{-(w_m^{z,1}[t-1]-(i-1))})^2} 2(H(P(w^z, 2))_i$$

$$- threshold)$$

The Shannon entropies of all kernel positions far from the mask boundaries ($w_m^{z,0}, w_m^{z,1}$)

contribute little to the final derivatives. Therefore, if most boundary-flanking kernel positions

have a low Shannon entropy (i.e., a high information content; defined by $H(P(w^z, 2))_i -$

$threshold < 0$), then the masked Shannon loss (MSL) will help push the boundaries outwards

(i.e., $\frac{\partial MSL(w^z, w_m^z[t-1])}{\partial w_m^{z,0}[t-1]} < 0$ and $\frac{\partial SL(w^z, w_m^z[t-1])}{\partial w_m^{z,1}[t-1]} > 0$) during gradient descent, just as if the current

mask is too narrow to span all informative positions. Likewise, if most boundary-flanking kernel

positions have a high Shannon entropy (i.e. a low information content; defined by

$H(P(w^z, 2))_i - threshold > 0$), then the MSL will help push the boundaries inwards (i.e.,

$\frac{\partial MSL(w^Z, w_m^Z[t-1])}{\partial w_m^{Z,0}[t-1]} > 0$ and $\frac{\partial SL(w^Z, w_m^Z[t-1])}{\partial w_m^{Z,1}[t-1]} < 0$), just as if the current mask is too broad to exclude

some positions with low information content.

To speed up computation in practice, we approximate the sum by ignoring most small, outside-

mask kernel positions and retaining only those terms with $i \in \left[\lfloor w_m^{Z,0} \rfloor - 2, \lceil w_m^{Z,0} \rceil + 2\right]$ or $\left[\lfloor w_m^{Z,1} \rfloor - \right.$

$\left. 2, \lceil w_m^{Z,1} \rceil + 2\right]$.

Finally, when introducing a vConv layer into a model, values of $(w_m^{Z,0}[t=0], w_m^{Z,1}[t=0])$, λ,

and $threshold$ in MSL are of user's choice. In all subsequent benchmarking on vConv-based

networks, unless otherwise specified, we set for each vConv layer the $(w_m^{Z,0}[t=0], w_m^{Z,1}[t=$

$0])$ as $(\frac{1-l}{2}, \frac{1+l}{2})$ for an unmasked kernel length of l, the λ as 0.0025, and the $threshold$ in MSL

as $-\frac{7}{10}\log_2\frac{7}{10} + \sum_{i=1}^{c-1} -\frac{3}{10*(c-1)}\log_2\frac{3}{10*(c-1)}$ for a kernel with c channels. This value of

$threshold$ is the Shannon entropy for the (discrete) distribution whose highest probability is

0.7, and all others c-1's are equally divided. When processing the nucleic acid sequence, there

are totally c=4 different probability values, so the probability of the remaining 3 items equally

divided is (1-0.7)/3; on the other hand, in Basenji-based Basset networks, the c for deeper

convolutional layers is not necessarily 4.

Fig. 1. The design of vConv. To build up the mask matrix, vConv generates two sigmoid

functions of opposite orientations (A and B), followed by overlaying them (C). Then vConv

"masks" this mask matrix onto the kernel using the Hadamard product (D), and treats the

masked kernel as an ordinary kernel to convolve the input sequence (E).

Benchmark vConv-based networks on simulated sequence classification

We simulated for each motif case 6,000 sequences (with 3,000 positive and 3,000 negative) of

length 1,000, picked 600 as the test dataset randomly, and split the rest into 4,860 training and

540 validation sequences by setting "validation_split=0.1" in model.fit of Keras Model API

(version 2.2.4) [41]; in this way, for each motif case, the same collection of training, validation,

and test datasets was used for all hyper-parameter settings tested (see below). The ratio of

counts of positive to negative sequences in the test dataset was within [0.8, 1.2] for all 7 motif

cases. All sequences were generated independently from each other. Each negative sequence

is a random sequence whose bases were independently sampled from the categorical

distribution P(A)=P(C)=P(G)=P(T)=0.25. For each positive sequence, we first constructed a

random sequence as described above, then overwrote/replaced a random-choice fragment

with a sequence fragment generated from one of the motifs associated with the case in question

("signal fragment", see Table 1 for more details). For the cases of 2, 4, 6 and 8 motifs, new

motifs were introduced incrementally (i.e., all motifs in "2 motifs" were also included in "4 motifs",

all motifs in "4 motifs" were also included in "6 motifs", and all motifs in "6 motifs" were also

included in "8 motifs").

In each iteration of benchmarking a certain case, we (1) picked a hyper-parameter setting from

Table 2; (2) used the training and validation datasets to train first a vConv-based network (see

Supplementary Fig. 1 for its structure) with this hyper-parameter setting and then a canonical

convolution-based network with a model structure identical to that of the vConv-based network,

except that the vConv layer was replaced with a canonical convolutional layer with the same

kernel number and (unmasked) kernel length; and (3) obtained the AUROC values of these two

networks on the test dataset. Iterating over all possible hyper-parameter settings yielded a

series of AUROC values for both the vConv-based network and the convolution-based network

for the case at hand.

Dataset	Motif composition
2 motifs	MA0234.1 (length=6), MA0963.1 (length=8)
4 motifs	MA0234.1 (length=6), MA0963.1 (length=8), MA0626.1 (length=10), MA0667.1 (length=10)
6 motifs	MA0234.1 (length=6), MA0963.1 (length=8), MA0626.1 (length=10), MA0667.1 (length=10), MA1146.1 (length=15), MA1147.1 (length=15)
8 motifs	MA0234.1 (length=6), MA0963.1 (length=8), MA0626.1 (length=10), MA0667.1 (length=10), MA1146.1 (length=15), MA1147.1 (length=15), MA0009.2 (length=16), MA0470.1 (length=11)
TwoDiffMotif1	MA0138.2 (length=21), MA0157.2 (length=8)
TwoDiffMotif2	MA1046.1 (length=9), MA1148.1 (length=18)
TwoDiffMotif3	MA0326.1 (length=8), MA0556.1 (length=15)

198 **Table 1.** Motifs used to generate each dataset. All motifs were derived from JASPAR [42].

Hyper-parameter	Value range space
Kernel number	{64, 96, 128}
Kernel length	{6, 8, 10, 12, 14, 16, 18, 20}
Random Seeds	16 different seeds
Momentum in AdaDelta optimizer	{0.9, 0.99, 0.999}
Delta in AdaDelta optimizer	{1e-4, 1e-6, 1e-8}

Table 2. Hyper-parameter space for the comparison between vConv-based networks and convolution-based networks on simulation datasets.

We used AdaDelta [43] with learning rate 1 as the optimizer. All parameters except for vConv-exclusive ones were initialized by the Glorot uniform initializer [44]; vConv-exclusive parameters were initialized as specified in the subsection "Design and implementation of vConv". Both convolution-based and vConv-based networks were trained with early stopping on validation loss with patience set to 50. All vConv-based networks with n kernels except for vConv-based Basset networks were first trained without updating $\{w_m^z \mid \forall z \in \{1, \ldots, n\}\}$ for 10 epochs and then trained with updating $\{w_m^z \mid \forall z \in \{1, \ldots, n\}\}$; for vConv-based Basset networks, we updated $\{w_m^z \mid \forall z \in \{1, \ldots, n\}\}$ since the first epoch.

Benchmark vConv-based networks on real-world sequence classification

To further demonstrate the performance of vConv-based networks in the real world, we examined whether replacing convolutional layers with vConv helps to improve the performance for motif identification in real-world ChIP-Seq data, against three published convolution-based networks: DeepBind [26], Zeng et al.'s convolution-based networks [45], and Basset [46].

For the first comparison, we downloaded DeepBind's original training (with positively sequences only) and test datasets from https://github.com/jisraeli/DeepBind/tree/master/data/encode, and generated negative training dataset by shuffling positive sequences with matching dinucleotide composition as specified by DeepBind [26]. We then trained vConv-based networks (see below for the model structure and training details) and compared their AUROC on test datasets with those of three sets of DeepBind performances from Supplementary Table 5 of DeepBind's original paper [26]: (1) the DeepBind* networks, which were trained by using all the training dataset; (2) the DeepBind networks, whose positive training sequences consist of those from the top 500 odd-numbered peaks only; and (3) the DeepBindbest networks, the one of DeepBind and DeepBind* with larger AUROC for each test dataset. During comparison, we found that there are two datasets with different AUROC values yet sharing the same model name in their original dataset (REST_HepG2_NRSF_HudsonAlpha and REST_SK-N-SH_NRSF_HudsonAlpha), which makes us unable to determine their true AUROC values, so we excluded them from the comparison.

For the second comparison between vConv-based networks and Zeng et al.'s [45] convolution-

based networks, we downloaded 690 ENCODE ChIP-Seq-based training and test datasets

representing the DNA binding profile of various transcription factors and other DNA-binding

proteins from http://cnn.csail.mit.edu/motif_discovery/. We then trained vConv-based networks

(see below for the model structure and training details) and compared its AUROC value on test

datasets with the AUROC values of Zeng et al.'s networks from

http://cnn.csail.mit.edu/motif_discovery_pred/.

The first two comparisons used the same model structure (Supplementary Fig. 1) and hyper-

parameter space (Supplementary Table 1). For direct comparison between vConv-based

networks and convolution-based networks for DeepBind and Zeng et al.'s cases [45], the

vConv-based network was implemented by replacing the convolutional layer of each network

considered for comparison with a vConv layer (with exactly the same hyper-parameters for the

number of kernels and the initial (unmasked) kernel length). The hyper-parameter space is

listed in the Supplementary Table 1. The remaining details of parameter initialization followed

those of the corresponding convolution-based networks [26, 45], and all these networks used

the training strategy described in the simulation case.

Finally, for the third comparison with the Basset network [46], we used the Basenji

reimplementation of Basset [28]

(https://github.com/calico/basenji/tree/master/manuscripts/basset) made and recommended

by the original author of Basset (Kelley D., personal communications); this reimplementation is

a deep CNN with nine convolutional layers (see Supplementary Fig. 2 for the full details). We

(1) generated the datasets by running "make_data.sh" under "manuscripts/basset/" (of this

repository), (2) re-trained the original Basset networks (which makes prediction for 164 cell

types by a single model) by running "python basenji_train.py -k -o train_basset

params_basset.json data_basset" under "manuscripts/basset/" (of this repository) to obtain

their AUROC values, (3) replaced either the first ('Single vConv-based'; left figure in

Supplementary Fig. 3) or all nine ('Completed vConv-based'; right figure in Supplementary Fig.

3) convolutional layers in the Basset network with vConv layer(s), re-initialized all weights, and

retrained it to obtain the AUROC value of the vConv-based Basset network, and finally (4)

compared the AUROC values between the two types of networks. The details of parameter

initialization (except for the vConv-exclusive parameters) and stochastic gradient descent-

based optimization (with learning rate 0.005) were exactly the same between the vConv-based

and the original Basset networks (Supplementary Fig. 2 and 3).

Benchmark vConv-based networks on real-world motif discovery

Finally, we compared vConv-based networks with the canonical methods on the motif discovery

problem. We followed the protocol proposed by Zhang et al. (Zhang, et al., 2015) to assess the

accuracy of the extracted representative motifs based on the ENCODE CTCF ChIP-Seq

datasets [47]. In brief, for each motif discovery tool and each ChIP-Seq dataset, we located the

motif-containing sequence fragments for candidate motifs discovered by this tool, checked

whether they overlapped with the ChIP-Seq peaks with CisFinder (retrieved from

https://lgsun.grc.nia.nih.gov/CisFinder/download.html at Feb 22, 2020), and reported the

largest per-motif ratio of overlapping fragments to all fragments across all candidate motifs as

the final accuracy of this tool on this dataset (see Supplementary Fig. 4 for more details). For

the sake of demonstrating the advantage of vConv-based networks, here the model structure

of the vConv-based network was chosen to be the one used in simulation (Supplementary Fig.

1).

RESULTS

vConv-based networks identify motifs more effectively than convolution-based
networks

We first present direct comparisons between vConv-based and convolution-based networks

based on multiple simulated datasets (see the Methods for more details). vConv-based

networks performed statistically significantly better across most hyperparameter settings of all

seven cases (Fig. 2; with all Wilcoxon rank sum test's p-values < 1e-18 for the null hypothesis

that the AUROC of the vConv-based network is equal to or smaller than that of the convolution-

based network). This improvement became larger when more motifs are introduced (2 motifs

to 8 motifs in Supplementary Fig. 5) and with increased heterogeneity of the motif length (2

motifs v.s. TwoDiffMotif1/2/3 in Supplementary Fig. 5). In addition, vConv-based networks

showed a smaller mean standard error of the AUROC than convolution-based networks across

different hyper-parameter settings (Levene's test, p-value < 0.001 for all datasets; see

Supplementary Table 2), suggesting that vConv-based networks also have a better robustness

to hyper-parameters than convolution-based networks.

Fig. 2. Pairwise comparison of AUROC between vConv-based and convolution-based networks with exactly the same hyper-parameter. As expected, vConv-based networks performed better than convolution-based networks in most cases. The percentage in the title on the figure indicates the percentage of those cases where the vConv-based network was better than the convolution-based network.

We further visualized the first layer of trained vConv-based and convolution-based networks on the most complex dataset (8 motifs), and found that vConv-based networks accurately recovered the underlying real motif from sequences and converge to the real length well (Supplementary Fig. 6). Of note, we found that the vConv-based networks successfully learned a motif (MA0234.1) which was missed by canonical convolution-based networks (Supplementary Fig. 6, second row).

These findings further compelled us to suspect that vConv-based networks will perform better than convolution-based networks on real-world cases possibly with combinatorial regulation.

To test this hypothesis, we examined whether replacing convolutional layer(s) with vConv would
improve performance of the following convolution-based networks: (1) DeepBind [26], a series
of DNA-protein-binding classifiers trained for each of 504 ENCODE ChIP-Seq datasets; (2)
Zeng et al.'s convolution-based networks [45], a series of structurally optimized variants of
DeepBind models for each of 690 ChIP-Seq datasets; and (3) Basset [46], a complex DNase
footprint predictor with nine convolutional layers (see Methods for more details). As expected,
vConv-based networks showed a statistically significantly improved performance compared to
their convolution-based network counterparts for all these three cases (Fig. 3 and
Supplementary Fig. 7), with a few exceptions some of which can be attributed to small sample
size of the input dataset (Supplementary Fig. 8A-B) and disappeared upon additional grid-
search on kernel length (Supplementary Fig. 8C). Of note, stacking vConv layers for a complex
convolution-based network like Basset can statistically significantly improve the performance
with respect to both the original Basset network and the single vConv-based network (Fig. 3C),
well demonstrating its combined power with the popular hierarchical representation learning
strategy in CNN application.

335
Fig. 3. vConv-based networks outperformed convolution-based networks on real-world cases.
(A), comparison of AUROC between vConv-based networks and DeepBindbest networks for
DeepBind (see also Supplementary Fig. 7 for comparison with other DeepBind networks). (B),
comparison of AUROC between vConv-based networks and networks from Zeng et al. . (C),
comparison of AUROC between vConv-based networks with 'Completed vConv-based', the
vConv-based network with all convolutional layers of Basset network replaced by vConv (right

figure in Supplementary Fig. 3; see Methods for more details) and networks from Basset. All p-

values shown are from Wilcoxon rank sum test, single-tailed, with the null hypothesis that the

AUROC of the vConv-based network is equal to or smaller than that of the convolution-based

network. See Methods for more details of each specific network.

vConv-based networks discover motifs from real-world sequences more accurately and

faster than canonical tools

We further evaluated vConv-based networks' performance for *ab initio* motif discovery. In brief,

for a particular trained vConv-based network, we first selected kernels with corresponding

dense layer weights higher than a predetermined baseline (defined as mean (all dense layer

weights) - standard deviation (all dense layer weights)) and then extracted and aligned these

kernels' corresponding segments to compute the representative PWM (Fig. 4A). We then

compared the accuracy of recovering ChIP-Seq peaks by the vConv-based motif discovery and

other motif discovery tools across all these ChIP-Seq datasets [47] (see the Methods for details).

Out of all 100 CTCF datasets, the vConv-based network outperformed DREME [15] on 95

datasets, CisFinder [23] on 91 datasets and MEME-ChIP [25] on 87 datasets with respect to

AUROC (Fig. 4B; see also Supplementary Fig. 9 for other metrics). In addition, the vConv-

based network ran much faster than DREME and MEME-ChIP on large datasets (more than

17 million base pairs finished in less than 30 minutes compared to hours by DREME and

MEME-ChIP's; see Fig. 4C).

Fig. 4. vConv-based networks discover motifs more accurately and faster. (A) shows the process of calling a representative motif from a trained vConv-based network. (B) shows the difference in accuracy, defined as the accuracy of vConv-based motif discovery minus the accuracy of the motif discovery algorithm shown on the x-axis on the same dataset. MEME [24] failed to complete the discovery within a reasonable time (~50% datasets remained unfinished even after running for 1.5 weeks with 2,000 cores, amounting to 504,000 CPU hours) for these datasets, and its results were thus not listed here. See also Supplementary Fig. 9 for other metrics. (C) shows the time cost of each motif discovery algorithm as a function of millions of base pairs in the dataset tested.

DISCUSSION

Inspired by the theoretical model (Supplementary Notes 1) for analyzing the influence of the kernel size in the convolutional layer, we designed and implemented a novel convolutional layer, vConv, which adaptively tunes the kernel lengths at run time. Evaluations based on both simulations and real-world datasets showed that such design enables vConv-based networks

to outperform canonical convolution-based network (see Fig. 3 and 4, as well as Supplementary
Fig. 5-8 for more details), especially on datasets containing multiple combinatorially regulatory
cis-elements of various lengths [38, 48]. Meanwhile, vConv could be readily integrated into
multi-layer neural networks, as an "in-place replacement" of canonical convolutional layer with
potential applications in more scenarios such as *cis*-regulatory motif prediction [49], predicting
non-coding functions *de novo* [50], predicting the transcription factors binding intensities [51],
and quantitative detection of histone modifications [52]. To facilitate its application in various
fields, we have implemented vConv as a new type of convolutional layer in Keras
(https://github.com/gao-lab/vConv).

In theory, a regular fixed-length convolution kernel with size larger than that of the *bona fide*
motif, may be able to converge to a solution where the kernel captures the motif faithfully with
zero padding everywhere else, just as what the vConv kernel does. Nevertheless, preliminary
empirical evaluations suggest that such "perfect" solution could be very rare in reality with a
general training strategy: none of the convolution-based network kernels similar to the ground
truth motifs in the 8 motifs case (as determined by Tomtom; see Supplementary Fig. 6) contains
more than 1 position whose sum of absolute elements are one order of magnitude more closer
to 0 than other positions.

vConv is scalable considering the fact that its current design only adds a $O(ncl)$ per n-kernel-
convolutional layer (with kernel length l and number of channels c) replaced to the overall time
complexity compared with that of the canonical fixed-kernel convolutional layer, and that
preliminary empirical evaluations suggest no evidence of convergence slowdown (as
benchmarked in Supplementary Fig. 10 for the simulation case). While we notice that the
current variable-length kernel strategy implemented by vConv could, in theory, be approximated
by combing multiple fixed-length-kernel networks, we'd argue that such approximation would
lead to serious inflation for the number of trainable parameters, and higher time cost for training
and optimization. For example, to approximate a simple network with one vConv layer of n
unmasked kernels with average length l (which needs $n*(4*l+2)+n = n*(4*l+3)$ parameters), the
ensemble of m convolution-based networks would take $m*(n*(4*l)+n) = m*(n*(4*l+1))$
parameters, far larger than $n*(4*l+3)$ when m is of tens or hundreds - a popular choice in
ensemble learning.

vConv-based networks show robustness with various hyper-parameters and initialization
setups (Supplementary Table 2). We believe that the major vConv-exclusive components,
Shannon loss (MSL) and boundary parameters, contribute to the increased robustness.
Intuitively, such components could regularize the parameters to learn, making the overall
objective function simpler (i.e., having fewer suboptima) and thus more robust. Consistently,
we found out that the vConv-based network -- when equipped with MSL -- had a smaller
variance of AUROC that is statistically significantly different from that of the vConv-based

network without MSL in 3 out of all 7 simulation cases (Levene's test, p<0.001; Supplementary Table 3), suggesting that MSL does contribute to this increased robustness in certain conditions. Of interest, equipping MSL also improved the AUROC of the vConv-based network (Supplementary Fig. 11).

FURTHER WORK

We note that the current theoretical analysis (see details in Supplementary Notes 1) reported above relies on prior knowledge of the real motif $\mathcal{M}$, which may not be feasible to obtain for real-world datasets. A possible workaround is to estimate the empirical null distribution of P_{real} over a set of randomly initialized PWMs and kernels and then derive the expectation of P_{real} over the given dataset. Such theoretical distribution, once established, could serve as a general background distribution for further development of motif scanners.

Moreover, although current motifs in convolution-based networks are automatically represented by PWMs, this might be an oversimplified representation of the genuine motifs, which may allow insertions and deletions within motifs (e.g., the HMM motifs from Pfam [53] and Rfam [54]). While recurrent neural networks have been expected to be able to learn such motifs [55-58], the interpretation of such models is still challenging. A promising alternative would be to use the CNN framework to learn complex motifs directly, as demonstrated by a recently developed CNN model HOCNNLB [59] which can learn first-order Markov models by re-encoding input sequences. Combining the variable-length nature of vConv and such complex-motif-capturing models might be much more useful for mining biological motifs.

DATA AVAILABILITY

A Keras-based implementation is released at GitHub (https://github.com/gao-lab/vConv) for academic usage, with all scripts/data for reproducing results available at https://github.com/gao-lab/vConv-Figures_and_Tables.

ACKNOWLEDGEMENT

The authors would like to thank Drs. Cheng Li, Letian Tao, Minghua Deng, Zemin Zhang, Jian Lu and Liping Wei at Peking University for their helpful comments and suggestions during the study. The analysis was supported by the High-performance Computing Platform of Peking University, and we thank Dr. Chun Fan and Yin-Ping Ma for their assistance during the analysis.

KEY POINTS

- We proposed a novel convolutional layer, vConv, which learns kernel structure from data adaptively.
- vConv could be readily integrated into multi-layer neural networks, as an "in-place

replacement" of canonical convolutional layer.

●   vConv's high robustness and low time footprint further enable its usage for real-world

massive omics data.

FUNDING

This work was supported by funds from the National Key Research and Development Program

[grant number 2016YFC0901603]; the China 863 Program [grant number 2015AA020108]; the

State Key Laboratory of Protein and Plant Gene Research; the Beijing Advanced Innovation

Center for Genomics (ICG) at Peking University; and in part by the National Program for the

Support of Top-notch Young Professionals [to G.G.].

Conflict of interest statement. None declared.

REFERENCES

1.   Achar A, Sætrom P. RNA motif discovery: a computational overview, Biology
direct 2015;10:61.
2.   Kulakovskiy IV, Makeev VJ. DNA sequence motif: a jack of all trades for ChIP-
Seq data. Advances in protein chemistry and structural biology. Elsevier, 2013, 135-
171.
3.   Stormo GD. DNA motif databases and their uses, Current protocols in
bioinformatics 2015;51:2.15. 11-12.15. 16.
4.   Kadonaga JT. Perspectives on the RNA polymerase II core promoter, Wiley
Interdisciplinary Reviews: Developmental Biology 2012;1:40-51.
5.   Blencowe BJ. Exonic splicing enhancers: mechanism of action, diversity and role
in human genetic diseases, Trends in biochemical sciences 2000;25:106-110.
6.   Zhang B, Gunawardane L, Niazi F et al. A novel RNA motif mediates the strict
nuclear localization of a long noncoding RNA, Molecular and cellular biology
2014;34:2318-2329.
7.   Zucchelli S, Cotella D, Takahashi H et al. SINEUPs: A new class of natural and
synthetic antisense long non-coding RNAs that activate translation, RNA biology
2015;12:771-779.
8.   Thomson DW, Dinger ME. Endogenous microRNA sponges: evidence and
controversy, Nature Reviews Genetics 2016;17:272.
9.   Liu B, Yang J, Li Y et al. An algorithmic perspective of de novo cis-regulatory
motif finding based on ChIP-seq data, Brief Bioinform 2018;19:1069-1081.
10. Das MK, Dai H-K. A survey of DNA motif finding algorithms. In: BMC
bioinformatics. 2007, p. S21. Springer.
11. Tran NT, Huang CH. A survey of motif finding Web tools for detecting binding site
motifs in ChIP-Seq data, Biol Direct 2014;9:4.
12. Lihu A, Holban S. A review of ensemble methods for de novo motif discovery in
ChIP-Seq data, Brief Bioinform 2015;16:964-973.
13. Zambelli F, Pesole G, Pavesi G. Motif discovery and transcription factor binding
sites before and after the next-generation sequencing era, Briefings in bioinformatics

2013;14:225-237.

14. Caldonazzo Garbelini JM, Kashiwabara AY, Sanches DS. Sequence motif finder using memetic algorithm, BMC bioinformatics 2018;19:4.

15. Bailey TL. DREME: motif discovery in transcription factor ChIP-seq data, Bioinformatics 2011;27:1653-1659.

16. Jia C, Carson MB, Wang Y et al. A new exhaustive method and strategy for finding motifs in ChIP-enriched regions, PLoS one 2014;9:e86044.

17. Thomas-Chollier M, Herrmann C, Defrance M et al. RSAT peak-motifs: motif analysis in full-size ChIP-seq datasets, Nucleic Acids Res 2012;40:e31.

18. Ding J, Hu H, Li X. SIOMICS: a novel approach for systematic identification of motifs in ChIP-seq data, Nucleic Acids Res 2014;42:e35.

19. Ding J, Dhillon V, Li X et al. Systematic discovery of cofactor motifs from ChIP-seq data by SIOMICS, Methods 2015;79-80:47-51.

20. Maaskola J, Rajewsky N. Binding site discovery from nucleic acid sequences by discriminative learning of hidden Markov models, Nucleic Acids Res 2014;42:12995-13011.

21. Kulakovskiy IV, Boeva VA, Favorov AV et al. Deep and wide digging for binding motifs in ChIP-Seq data, Bioinformatics 2010;26:2622-2623.

22. Ikebata H, Yoshida R. Repulsive parallel MCMC algorithm for discovering diverse motifs from large sequence sets, Bioinformatics 2015;31:1561-1568.

23. Sharov AA, Ko MS. Exhaustive search for over-represented DNA sequence motifs with CisFinder, DNA Res 2009;16:261-273.

24. Bailey TL, Williams N, Misleh C et al. MEME: discovering and analyzing DNA and protein sequence motifs, Nucleic Acids Res 2006;34:W369-373.

25. Machanick P, Bailey TL. MEME-ChIP: motif analysis of large DNA datasets, Bioinformatics 2011;27:1696-1697.

26. Alipanahi B, Delong A, Weirauch MT et al. Predicting the sequence specificities of DNA-and RNA-binding proteins by deep learning, Nature biotechnology 2015;33:831.

27. Angermueller C, Lee HJ, Reik W et al. DeepCpG: accurate prediction of single-cell DNA methylation states using deep learning, Genome biology 2017;18:67.

28. Kelley DR, Reshef YA, Bileschi M et al. Sequential regulatory activity prediction across chromosomes with convolutional neural networks, Genome research 2018;28:739-750.

29. Wang M, Tai C, E W et al. DeFine: deep convolutional neural networks accurately quantify intensities of transcription factor-DNA binding and facilitate evaluation of functional non-coding variants, Nucleic acids research 2018;46:e69-e69.

30. Zhang J, Peng W, Wang L. LeNup: learning nucleosome positioning from DNA sequences with improved convolutional neural networks, Bioinformatics 2018;34:1705-1712.

31. Zhou J, Theesfeld CL, Yao K et al. Deep learning sequence-based ab initio prediction of variant effects on expression and disease risk, Nature genetics 2018;50:1171.

32. Koo PK, Eddy SR. Representation learning of genomic sequence motifs with convolutional neural networks, PLoS computational biology 2019;15:e1007560.

33. Lan G, Zhou J, Xu R et al. Cross-Cell-Type Prediction of TF-Binding Site by Integrating Convolutional Neural Network and Adversarial Network, Int J Mol Sci 2019;20.

34. Zhang Q, Shen Z, Huang DS. Modeling in-vivo protein-DNA binding by combining multiple-instance learning with a hybrid deep neural network, Sci Rep

2019;9:8484.

35. Yin W, Schütze H. Multichannel variable-size convolution for sentence classification, arXiv preprint arXiv:1603.04513 2016.

36. Zhang Q, Zhu L, Huang D-S. High-order convolutional neural network architecture for predicting DNA-protein binding sites, IEEE/ACM transactions on computational biology and bioinformatics 2018;16:1184-1192.

37. Han S, Meng Z, Li Z et al. Optimizing filter size in convolutional neural networks for facial action unit recognition. In: Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition. 2018, p. 5070-5078.

38. Reiter F, Wienerroither S, Stark A. Combinatorial function of transcription factors and cofactors, Curr Opin Genet Dev 2017;43:73-81.

39. Lambert SA, Jolma A, Campitelli LF et al. The Human Transcription Factors, Cell 2018;175:598-599.

40. Ding Y, Li J-Y, Wang M et al. An exact transformation of convolutional kernels enables accurate identification of sequence motifs, bioRxiv 2018:163220.

41. Chollet F, others. Keras 2015.

42. Khan A, Fornes O, Stigliani A et al. JASPAR 2018: update of the open-access database of transcription factor binding profiles and its web framework, Nucleic acids research 2017;46:D260-D266.

43. Zeiler MD. Adadelta: an adaptive learning rate method, arXiv preprint arXiv:1212.5701 2012.

44. Glorot X, Bengio Y. Understanding the difficulty of training deep feedforward neural networks. In: Yee Whye T., Mike T. eds). Proceedings of the Thirteenth International Conference on Artificial Intelligence and Statistics. Proceedings of Machine Learning Research: PMLR, 2010, 249--256.

45. Zeng H, Edwards MD, Liu G et al. Convolutional neural network architectures for predicting DNA–protein binding, Bioinformatics 2016;32:i121-i127.

46. Kelley DR, Snoek J, Rinn JL. Basset: learning the regulatory code of the accessible genome with deep convolutional neural networks, Genome research 2016;26:990-999.

47. ENCODE Project Consortium. An integrated encyclopedia of DNA elements in the human genome, nature 2012;489:57.

48. Nair S, Kim DS, Perricone J et al. Integrating regulatory DNA sequence and gene expression to predict genome-wide chromatin accessibility across cellular contexts, Bioinformatics 2019;35:i108-i116.

49. Yang J, Ma A, Hoppe AD et al. Prediction of regulatory motifs from human Chip-sequencing data using a deep learning framework, Nucleic Acids Res 2019;47:7809-7824.

50. Quang D, Xie X. DanQ: a hybrid convolutional and recurrent deep neural network for quantifying the function of DNA sequences, Nucleic Acids Res 2016;44:e107.

51. Wang M, Tai C, E W et al. DeFine: deep convolutional neural networks accurately quantify intensities of transcription factor-DNA binding and facilitate evaluation of functional non-coding variants, Nucleic Acids Res 2018;46:e69.

52. Yin Q, Wu M, Liu Q et al. DeepHistone: a deep learning approach to predicting histone modifications, BMC genomics 2019;20:193.

53. El-Gebali S, Mistry J, Bateman A et al. The Pfam protein families database in 2019, Nucleic Acids Res 2019;47:D427-D432.

54. Kalvari I, Argasinska J, Quinones-Olvera N et al. Rfam 13.0: shifting to a genome-centric resource for non-coding RNA families, Nucleic Acids Res 2018;46:D335-D342.

55. Min S, Park S, Kim S et al. Pre-Training of Deep Bidirectional Protein Sequence Representations with Structural Information, arXiv preprint arXiv:1912.05625 2019.

56. Vazhayil A, KP S. DeepProteomics: Protein family classification using Shallow
and Deep Networks, arXiv preprint arXiv:1809.04461 2018.
57. Liu X. Deep recurrent neural network for protein function prediction from
sequence, arXiv preprint arXiv:1701.08318 2017.
58. Liza FF, Grzes M. Relating RNN layers with the spectral WFA ranks in sequence
modelling, Association for Computational Linguistics 2019:24-33.
59. Zhang Q, Zhu L, Huang DS. High-Order Convolutional Neural Network
Architecture for Predicting DNA-Protein Binding Sites, IEEE/ACM Trans Comput
Biol Bioinform 2019;16:1184-1192.
617