Phenotypic, functional and taxonomic features predict host–pathogen interactions

Wang Liu-Wei, Şenay Kafkas, Robert Hoehndorf[*]

Computer, Electrical and Mathematical Sciences and Engineering Division, Computational Bioscience Research Center, King Abdullah University of Science and Technology, Thuwal 23955, Saudi Arabia

* robert.hoehndorf@kaust.edu.sa

Abstract

Identification of host-pathogen interactions (HPIs) can reveal mechanistic insights of infectious diseases for potential treatments and drug discoveries. Current computational methods for the prediction of HPIs often rely on our knowledge on the sequences and functions of pathogen proteins, which is limited for many species, especially for species of emerging pathogens. Matching the phenotypes elicited by pathogens with phenotypes associated with host proteins might improve the prediction of HPIs. We developed an ontology-based method that prioritizes potential interaction protein partners for pathogens using machine learning models. Our method exploits the underlying disease mechanisms by associating phenotypic and functional features of pathogens and human proteins, corroborated by multiple ontologies as background knowledge. Additionally, by embedding the phenotypic information of the pathogens within a formally represented taxonomy, we demonstrate that our model can also accurately predict interaction partners for pathogens without known phenotypes, using a combination of their taxonomic relationships with other pathogens and information from ontologies as background knowledge. Our results show that the integration of phenotypic, functional and taxonomic knowledge not only improves the prediction of HPIs, but also enables us to investigate novel pathogens in emerging infectious diseases.

Author summary

Infectious diseases are caused by various types of pathogens, such as bacteria and viruses, and lead to millions of deaths each year, especially in low-income countries. Researchers have been attempting to predict and study possible host-pathogen interactions on a molecular level. Understanding these interactions can shed light on how pathogens invade cells or disrupt the immune system. We propose a novel method to predict such interactions by associating phenotypes (e.g., the signs and symptoms of patients) associated with pathogens and phenotypes associated with human proteins. We are able to accurately predict and prioritize possible protein partners for dozens of pathogens. We further extended the prediction model by relating pathogens without phenotypes with those with phenotypes through their taxonomic relationships. We found that the addition of taxonomic knowledge greatly increased the number of pathogens that we can study, without diminishing the accuracy of the model. To the best of our knowledge, we are the first to predict host-pathogen interactions based on phenotypes and taxonomy. Our work has important implications for new pathogens and emerging infectious diseases that are not yet well-studied.

Introduction

Infectious diseases from bacteria, viruses and fungi are one of the major causes of deaths around the globe, especially in low-income regions [1]. Pathogens disrupt host cell functions [2] and target immune pathways [3] through complex interactions among proteins [4], RNA [5] and DNA [6]. The study of host-pathogen interactions (HPI) can provide insights into molecular mechanisms underlying infectious diseases and enable the development of novel therapeutic discoveries. For example, a previous study of many HPIs showed that pathogens typically interact with the protein hubs (those with many interaction partners) and bottlenecks (those of central location to important pathways) in human protein-protein interaction (PPI) networks [4]. However, due to high costs and time constraints, experimentally validated pairs of interacting host-pathogen proteins are limited in number. Moreover, there exists a time delay for a validated HPI to be included in a database of HPIs, often requiring text-mining efforts [7]. Therefore, the computational prediction of HPIs is useful in suggesting candidate interaction partners out of all the human proteins.

Existing HPI prediction methods typically utilizes features of interacting protein pairs, such as PPI network topology, structural and sequential homology, or functional profiling such as Gene Ontology similarity and KEGG pathway analysis [8]. While such protein-specific features exist for some extensively studied pathogens, such as *Mycobacterium tuberculosis* [9], human immunodeficiency virus [10], *Salmonella* and *Yersinia* [11], for most of the other pathogens, especially the newly emerging ones, these features are scarce (or non-existent) and expensive to obtain. As new virus species are discovered each year with potentially many more to come [12], a method is needed to aggregate our existing phenotypic, functional and taxonomic knowledge about HPIs and predict for pathogens that are less well studied or novel.

The phenotypes elicited by pathogens, i.e., the signs and symptoms observed in a patient, may provide information about molecular mechanisms [13]. The information that phenotypes provide about molecular mechanisms is commonly exploited in computational studies of Mendelian disease mechanisms [14, 15], for example to suggest candidate genes [16, 17] or diagnose patients [18], but can also be used to identify drug targets [19] or gene functions [20]. To the best of our knowledge, phenotypes and phenotype similarity have not yet been used to suggest host-pathogen interactions.

We use the hypothesis that phenotypes elicited by an infection with a pathogen are – among others – the result of molecular interactions, and that knowledge of the phenotypes in the host can be used to suggest the protein perturbations through which these phenotypes arise. While a large number of phenotypes resulting from infections are a consequence of immune system processes that are shared across a wide range of different types of pathogens, certain hallmark phenotypes – such as decreased CD4 count in infections with human immunodeficiency virus or microcephaly resulting from Zika virus infections – can be used to suggest candidate host proteins through which these phenotypes are elicited. Phenotypes shared across many pathogens could also contribute to the prediction of interacting host proteins as well as the absence of certain phenotypes.

We developed a method to predict candidate interacting proteins for pathogens by integrating phenotypic, functional and taxonomic information about pathogens and human proteins. We systematically compare phenotypes arising from infection with a pathogen to phenotypes associated with human genes; we further relate phenotypes to protein functions and compare pathogen-associated phenotypes with human protein functions. Relying on recent progress in deep learning with structured and semantic data [21], we construct a model that combines this information as well as structured information about taxonomic relations between pathogens to predict host-pathogen interactions. We demonstrate that our model can not only accurately predict the

interacting protein partners for pathogens with phenotypic information, but also their   53
relatives without phenotypes by aggregating knowledge through the taxonomy.   54

Results   55

Feature generation and representation learning for human   56
proteins and pathogens   57

The first step in our method is the generation of features that represent a pathogen or a   58
human protein. We represent human proteins through their associated phenotypes, the   59
phenotypes associated with their mouse ortholog, and their functions. We obtained   60
loss-of-function phenotypes of mouse genes from the Mouse Genome Informatics (MGI)   61
database [22] and phenotype annotations of human genes from Human Phenotype   62
Ontology (HPO) database [23]. We obtained protein function annotations from the   63
Gene Ontology (GO) database [24, 25]. For pathogens, we use the phenotype   64
annotations from the PathoPhenoDB [26], a database of pathogen-phenotype   65
associations, and taxonomic information from the NCBI Taxonomy [27].   66
    We represent the phenotypes and functions through ontologies. To associate human   67
and mouse phenotypes, we use the cross-species phenotype ontology   68
PhenomeNET [16, 28], which combined the Human Phenotype Ontology (HP) [23] and   69
the Mammalian Phenotype Ontology (MP) [29]. To incorporate knowledge of protein   70
functions, we use the Gene Ontology [24, 25]. For the taxonomic relations between   71
pathogens, we used the NCBI Taxonomy database [27]. These ontologies contain   72
formalized biological background knowledge [30]. Using the information in ontologies as   73
background knowledge during feature generation has the potential to significantly   74
improve the performance of these features in machine learning and predictive   75
analyses [21].   76
    We use the OPA2Vec [21] method to generate features from annotations of pathogen   77
taxa and human proteins while using the ontologies that are used to express them as   78
background knowledge. To determine the effect of different annotations and ontologies   79
on the performance of our models, we generated feature vectors of human proteins from   80
human phenotype annotations, the phenotypes of their mouse orthologs, and functional   81
annotations individually with their respective ontologies, as well as their union and   82
intersection by combining the annotations and merging the ontologies.   83

Phenotypic and functional prediction of interaction partners   84

We obtained high-confidence interaction pairs of pathogens and human proteins from   85
the Host-Pathogen Interaction Database (HPIDB) [31]. We then trained an artificial   86
neural network model (ANN) to predict host-pathogen interactions using the feature   87
vectors of pathogens and human proteins as input. We performed leave-one-taxon-out   88
cross-validation (LOOCV), in which we leave out one pathogen taxon in our positive set   89
for validation, and use all the other pathogens and their interactions as training data.   90
We evaluated our model by ranking the true positive protein partners of the validation   91
taxon (see Methods). We perform the training and evaluation separately based on   92
taxonomic groups, i.e., viruses and bacteria. Table 1 provides an overview over the   93
underlying data used for these predictions, and Figure 1 shows the prediction results.   94
    For viruses, the model using features that combine phenotypic and functional   95
information has the best performance in prioritizing true protein partners. This model   96
is able to prioritize 50% of the true positives within the first 10% of all proteins. For   97
bacteria, the model that uses only functions of human proteins performs better than all   98

Table 1. Datasets used for phenotypic and functional predictions. The features are human phenotypes (HP), mouse phenotypes (MP), gene ontology terms (GO), their union and their intersection. The coverage shows the total number of proteins annotated with the respective features. The number of unique interacting pairs, pathogen taxa and human proteins are listed for both viruses and bacteria.

Features	Coverage	Viruses			Bacteria		
		Interactions	Taxa	Proteins	Interactions	Taxa	Proteins
HP	3740	101	24	78	18	9	18
MP	9153	214	29	174	47	15	46
GO	18084	291	30	247	57	16	56
HP∪MP∪GO	18349	291	30	247	57	16	56
HP∩MP∩GO	2955	92	23	69	18	9	18

(a) Viruses **(b)** Bacteria

Fig 1. The TPR curves by normalized rank of proteins with different phenotypic and functional features The solid curves represent the different features used to generate the feature vectors of human proteins. The dashed line represents a random classifier.

other features. The TPR curve is less smooth compared to the viruses due to the limited number of exact matches of bacterial taxa between HPIDB and PathoPhenoDB.

Taxonomic prediction of interaction partners

The phenotypic and functional prediction of HPIs has several drawbacks: firstly, there are many pathogen taxa in HPIDB that cannot be matched with those in PathoPhenoDB at the exact taxon level; secondly, there is considerably less training data for bacteria compared to viruses, leading to the non-smoothness of the TPR curve. To address the taxonomic inconsistencies between HPIDB and PathoPhenoDB, we generated feature vectors for all the pathogens that can be represented as a class in NCBI Taxonomy by merging the NCBI Taxonomy Ontology and the PhenomeNet Ontology during the generation of features. Our aim is not only to increase the taxonomic coverage but also to encode phenotypic and taxonomic information for pathogens and their relatives by exploiting the underlying ontological structures. Table 2 shows that almost all of the pathogens we consider have some relatives within the same family that have some phenotypic annotations in PathoPhenoDB, and over two

thirds within the same species (i.e., species, subspecies, or strain). ₁₁₄

Table 2. Coverage of phenotypic features through taxonomy The percentages stand for the proportion of pathogens that have relatives within the same family, genus or species with phenotypic annotations.

Features	Viruses			Bacteria		
	Family	Genus	Species	Family	Genus	Species
HP	100%	90%	77%	97%	97%	79%
MP	100%	90%	76%	98%	98%	83%
GO & HP∪MP∪GO	100%	89%	75%	98%	98%	83%
HP∩MP∩GO	100%	90%	75%	97%	97%	79%

We retrained the models with the extended set of pathogens and evaluated their ₁₁₅ performance using LOOCV. Table 3 shows that there is more than 50% increase in the ₁₁₆ number of interactions and pathogen taxa after the inclusion of taxonomic features. ₁₁₇ Figure 2 shows the model performance after retraining with the extended set of ₁₁₈ pathogens. For both viruses and bacteria, the prediction model shows an increase in ₁₁₉ AUC for every feature of human proteins. Again, the features representing functions of ₁₂₀ gene products perform better than the phenotype features individually. However, ₁₂₁ collectively the features that combine phenotypic and functional information perform ₁₂₂ best and prioritize around 70% of the true positive protein partners within the first 10% ₁₂₃ of all proteins. ₁₂₄

Table 3. Datasets used for taxonomic predictions The numbers in brackets indicate the increase in data after adding taxonomic features.

Features	Coverage	Viruses			Bacteria		
		Interactions	Taxa	Proteins	Interactions	Taxa	Proteins
HP	3740	363 (+262)	98 (+74)	211 (+133)	47 (+29)	29 (+20)	34 (+16)
MP	9153	829 (+615)	144 (+115)	510 (+336)	98 (+51)	40 (+25)	80 (+34)
GO	18084	1125 (+834)	155 (+125)	746 (+499)	121 (+64)	42 (+26)	100 (+44)
HP∪MP∪GO	18349	1126 (+835)	155 (+125)	747 (+500)	121 (+64)	42 (+26)	100 (+44)
HP∩MP∩GO	2955	331 (+239)	96 (+73)	184 (+115)	47 (+29)	29 (+20)	34 (+16)

Discussion ₁₂₅

We developed an ontology-based method for predicting HPIs using the phenotypic, ₁₂₆ functional and taxonomic features of pathogens and human proteins. Unlike previous ₁₂₇ methods that target protein-protein interactions and utilize features from protein ₁₂₈ structures and sequences [8], we focused on predicting pathogen-protein interactions and ₁₂₉ use features that are relatively easy and fast to obtain from patients' symptoms and ₁₃₀ taxonomic identification of pathogens. ₁₃₁

Phenotype-based approaches have been successful in predicting disease-gene ₁₃₂ associations for Mendelian diseases [16], but have not yet been used for prediction of ₁₃₃ host-pathogen interactions for infectious diseases. Our results demonstrate that the ₁₃₄ phenotypes associated with human proteins and protein functions (i.e., GO classes), can ₁₃₅ generate accurate predictions. While GO classes have been shown to perform well in ₁₃₆ HPI predictions previously [32, 33], they still rely on sequence homology of pathogen ₁₃₇ proteins. We only target interactions between pathogen taxa and host proteins instead ₁₃₈ of direct protein-protein interactions, and therefore avoid the common bottleneck of ₁₃₉ identifying the functions of pathogen proteins. Instead, we introduce a novel and – in ₁₄₀ the context of infectious diseases – rarely explored type of feature, the phenotypes ₁₄₁

(a) Viruses   **(b)** Bacteria

Fig 2. The TPR curves by normalized rank of proteins after adding taxonomic features

elicited by pathogens in their hosts, as a "proxy" for the molecular mechanisms that result in the phenotypes.

The focus of our method on utilizing features generated based on endo-phenotypes observed in humans and mice [34] has the crucial advantage that we can identify host-pathogen interactions that may contribute to particular signs and symptoms. For example, our model predicts an interaction between Zika virus (`NCBITaxon:64320`) and DDX3X (`UniProt:O00571`). Infections with Zika virus have the potential to result in abnormal embryogenesis and, specifically, microcephaly [35]. Phenotypes associated with DDX3X in the mouse ortholog include abnormal embryogenesis, microcephaly, and abnormal neural tube closure [36]. DDX3X mutations in humans have been found to result in intellectual disability, specifically in females and affecting individuals in dose-dependent manner [37]. While DDX3X has previously been linked to the infectivity of Zika virus [38], our model further suggests a role of DDX3X in the development of the embryogenesis phenotypes resulting from Zika virus infections.

The lack of phenotypic annotations is often a challenge for such phenotype-based predictions, which is also the case for many pathogens in our study. We demonstrated that by integrating a formalized taxonomy in our feature generation, not only did we greatly increase the number of taxa but also improved the prediction performance. This suggests that our model was able to learn high level representations of the phenotypes caused by pathogens across their taxonomic hierarchy. This is the first attempt, to our knowledge, for a taxonomy ontology to be used in a machine learning method to transfer and distribute information across different taxonomic levels. This method can be potentially extended to many applications where data are only present for some levels of taxonomy, such as the modeling of some other ecological systems where many species interact.

Materials and methods

Data sources

We downloaded interactions between hosts and pathogens from the Host Pathogen Interaction Database (HPIDB) [31] on July 16, 2018. The dataset contains 27,533

distinct interaction pairs of human proteins to pathogen species with the IntAct and ₁₇₁
Virhostnet MI scores provided. We further filtered the interactions by the MI scores ₁₇₂
with a threshold of 0.5, reducing the number of interaction pairs to 1,682. We obtained ₁₇₃
phenotypes associated with pathogens from the PathoPhenoDB [26], a database of ₁₇₄
manually curated and text-mined associations of pathogens, diseases and phenotypes. ₁₇₅
We downloaded the version 1 of the PathoPhenoDB database ₁₇₆
(`http://patho.phenomebrowser.net/`) on Oct 11, 2018. Similarly to the ₁₇₇
implementation at the PathoPhenoDB web interface, species level taxa are also ₁₇₈
annotated with the phenotypes of all their subclasses in the taxonomy of pathogens. ₁₇₉

We downloaded phenotypes of human genes on August 26, 2018 from the Human ₁₈₀
Phenotype Ontology (HPO) database. The dataset contains 3,777 human genes and ₁₈₁
131,045 associations between human genes and HPO classes. We downloaded ₁₈₂
phenotypes associated with mouse genes from the Mouse Genome Informatics (MGI) ₁₈₃
database [22] on September 17, 2018, using the `MGI_GenePheno.rpt` file with 12,182 ₁₈₄
mouse genes and 165,892 associations of mouse genes and Mammalian Phenotype ₁₈₅
ontology (MP) classes. We then associated MP classes with human genes by mapping ₁₈₆
mouse genes to human genes based on the orthologies provided in ₁₈₇
`HMD_HumanPhenotype.rpt` downloaded from MGI on July 16, 2018. We mapped all the ₁₈₈
genes to Uniprot proteins using the Uniprot Retrieve/ID mapping tool ₁₈₉
(`https://www.uniprot.org/uploadlists/`), and used only reviewed Swissprot ₁₉₀
mappings. We downloaded Gene Ontology (GO) annotations of human proteins from ₁₉₁
the Gene Ontology website [24, 25] on September 27, 2018. To identify broad taxonomic ₁₉₂
groups, i.e., bacteria and viruses, we used the NCBI Taxonomy Categories file ₁₉₃
(`ftp://ftp.ncbi.nih.gov/pub/taxonomy`) downloaded on September 3, 2018. ₁₉₄

To obtain formal representations of phenotypes and GO classes, we downloaded the ₁₉₅
cross-species PhenomeNET Ontology [16, 28] from the AberOWL ontology ₁₉₆
repository [39] on September 13, 2018, and we downloaded the Gene Ontology [24, 25] ₁₉₇
from the Gene Ontology website on September 27, 2018. For taxonomy features, we ₁₉₈
downloaded the NCBI Taxonomy in OWL format from the OBO Foundry website ₁₉₉
(`http://www.obofoundry.org/ontology/ncbitaxon.html`) on October 8th, 2018. ₂₀₀

Generation of feature embeddings ₂₀₁

For feature generation, we used OPA2Vec [21], a tool that generates feature vectors ₂₀₂
from entities and their annotation from ontologies. OPA2vec first generates a corpus ₂₀₃
consisting of relevant annotations of pathogens and proteins (i.e., HP, MP, GO, and ₂₀₄
NCBI Taxonomy classes), the complete set of class axioms and the metadata of the ₂₀₅
ontologies. For OPA2Vec parameters, we used the default skipgram model with a ₂₀₆
window size of 5 and a minimum count parameter of 2. We tested different embedding ₂₀₇
sizes (i.e., 50, 100, 150, 200 and 300) and fixed the embedding size to 300 throughout ₂₀₈
our experiments in this paper. ₂₀₉

Supervised prediction models ₂₁₀

We train an ANN as a binary classifier that predicts a confidence score of an interaction ₂₁₁
between a host protein and a pathogen taxon, and we use leave-one-taxon-out ₂₁₂
cross-validation to report performance results. During each taxon-fold, we use the ₂₁₃
trained ANN to predict possible interacting proteins for the validation taxon. We ₂₁₄
evaluate the prediction results by ranking the confidence scores of its true protein ₂₁₅
partners among those of all the proteins. By aggregating the ranks of these true positive ₂₁₆
at each taxon fold, we plotted a true positive rate (TPR) curve by the normalized ranks ₂₁₇
of proteins and calculated an Area Under Curve (AUC) metric by trapezoidal rule for ₂₁₈
integration. ₂₁₉

We obtained positives by extracting interaction pairs of human proteins and ²²⁰
pathogen taxa from HPIDB. To generate the negatives, we first generated all possible ²²¹
combinations between all the proteins with a feature vector and pathogens that are in ²²²
the positives, and then randomly sampled within the ones that did not occur in the ²²³
positives. We treat all "unknown" interactions as negatives. ²²⁴

The AUC metric shows our model's ability to prioritize the true protein partners ²²⁵
under the assumption that a perfectly random model will have an AUC of 0.5. Due to ²²⁶
the large number of negatives in relation to the positives, normalized ranks approximate ²²⁷
the true negative rate (TNR) and the AUC measure approximates the area under the ²²⁸
receiver operating characteristic (ROC) curve [40]. ²²⁹

We searched for an optimal set of hyperparameters using the Hyperas library ²³⁰
(`https://github.com/maxpumperla/hyperas`) based on the TPE algorithm [41] for ²³¹
one of our models (i.e., the model using only the HP features). A complete list of ²³²
hyperparameter search space is provided in Supplementary Table S1. After searching, ²³³
we fixed our parameters to the following throughout all the experiments: one hidden ²³⁴
layer of 256 units with Rectified Linear Unit (ReLU) [42] as activation function; one ²³⁵
batch normalization layer; one dropout layer with a dropout rate of 0.52; one output ²³⁶
layer with a sigmoid activation function; an the Adam optimizer with cross entropy as ²³⁷
loss function. ²³⁸

References

1. World Health Organization. The top 10 causes of death;. Available at `www.who.int/news-room/fact-sheets/detail/the-top-10-causes-of-death` [Accessed 15 November 2018].

2. Finlay BB, Cossart P. Exploitation of Mammalian Host Cell Functions by Bacterial Pathogens. Science. 1997;276(5313):718–725. doi:10.1126/science.276.5313.718.

3. Dyer MD, Neff C, Dufford M, Rivera CG, Shattuck D, Bassaganya-Riera J, et al. The Human-Bacterial Pathogen Protein Interaction Networks of Bacillus anthracis, Francisella tularensis, and Yersinia pestis. PLOS ONE. 2010;5(8):1–12. doi:10.1371/journal.pone.0012089.

4. Dyer MD, Murali TM, Sobral BW. The Landscape of Human Proteins Interacting with Viruses and Other Pathogens. PLOS Pathogens. 2008;4(2):1–14. doi:10.1371/journal.ppat.0040032.

5. Fajardo T Jr, Sung PY, Roy P. Disruption of Specific RNA-RNA Interactions in a Double-Stranded RNA Virus Inhibits Genome Packaging and Virus Infectivity. PLOS Pathogens. 2015;11(12):1–22. doi:10.1371/journal.ppat.1005321.

6. Weitzman MD, Carson CT, Schwartz RA, Lilley CE. Interactions of viruses with the cellular DNA repair machinery. DNA Repair. 2004;3(8):1165 – 1173. doi:https://doi.org/10.1016/j.dnarep.2004.03.018.

7. Thieu T, Joshi S, Warren S, Korkin D. Literature mining of host–pathogen interactions: comparing feature-based supervised learning and language-based approaches. Bioinformatics. 2012;28(6):867–875. doi:10.1093/bioinformatics/bts042.

8. Nourani E, Khunjush F, Durmuş S. Computational approaches for prediction of pathogen-host protein-protein interactions. Frontiers in Microbiology. 2015;6:94. doi:10.3389/fmicb.2015.00094.

9. Huo T, Liu W, Guo Y, Yang C, Lin J, Rao Z. Prediction of host - pathogen protein interactions between Mycobacterium tuberculosis and Homo sapiens using sequence motifs. BMC Bioinformatics. 2015;16(1):100. doi:10.1186/s12859-015-0535-y.

10. Mukhopadhyay A, Ray S, Maulik U. Incorporating the type and direction information in predicting novel regulatory interactions between HIV-1 and human proteins using a biclustering approach. BMC Bioinformatics. 2014;15(1):26. doi:10.1186/1471-2105-15-26.

11. Kshirsagar M, Carbonell J, Klein-Seetharaman J. Techniques to cope with missing data in host–pathogen protein interaction prediction. Bioinformatics. 2012;28(18):i466–i472. doi:10.1093/bioinformatics/bts375.

12. Woolhouse M, Scott F, Hudson Z, Howey R, Chase-Topping M. Human viruses: discovery and emergence. Philosophical Transactions of the Royal Society B: Biological Sciences. 2012;367(1604):2864.

13. Gkoutos GV, Schofield PN, Hoehndorf R. The anatomy of phenotype ontologies: principles, properties and applications. Briefings in Bioinformatics. 2018;19(5):1008–1021. doi:https://doi.org/10.1093/bib/bbx035.

14. Oellrich A, Collier N, Groza T, Rebholz-Schuhmann D, Shah N, Bodenreider O, et al. The digital revolution in phenotyping. Briefings in Bioinformatics. 2016;17(5):819–830. doi:10.1093/bib/bbv083.

15. Schofield PN, Hoehndorf R, Gkoutos GV. Mouse genetic and phenotypic resources for human genetics. Human Mutation. 2012;.

16. Hoehndorf R, Schofield PN, Gkoutos GV. PhenomeNET: a whole-phenome approach to disease gene discovery. Nucleic acids research. 2011;39(18):e119–e119.

17. Meehan TF, Conte N, West DB, Jacobsen JO, Mason J, Warren J, et al. Disease model discovery from 3,328 gene knockouts by The International Mouse Phenotyping Consortium. Nature genetics. 2017;49(8):1231–1238.

18. Köhler S, Schulz MH, Krawitz P, Bauer S, Dölken S, Ott CE, et al. Clinical Diagnostics in Human Genetics with Semantic Similarity Searches in Ontologies. The American Journal of Human Genetics. 2009;85(4):457 – 464. doi:https://doi.org/10.1016/j.ajhg.2009.09.003.

19. Hoehndorf R, Hiebert T, Hardy NW, Schofield PN, Gkoutos GV, Dumontier M. Mouse model phenotypes provide information about human drug targets. Bioinformatics. 2013;.

20. Hoehndorf R, Hardy NW, Osumi-Sutherland D, Tweedie S, Schofield PN, Gkoutos GV. Systematic Analysis of Experimental Phenotype Data Reveals Gene Functions. PLoS ONE. 2013;8(4):e60847. doi:10.1371/journal.pone.0060847.

21. Smaili FZ, Gao X, Hoehndorf R. OPA2Vec: combining formal and informal content of biomedical ontologies to improve similarity-based prediction. Bioinformatics. 2018; p. bty933. doi:10.1093/bioinformatics/bty933.

22. Smith CL, Blake JA, Kadin JA, Richardson JE, Bult CJ, the Mouse Genome Database Group. Mouse Genome Database (MGD)-2018: knowledgebase for the laboratory mouse. Nucleic Acids Research. 2018;46(D1):D836–D842. doi:10.1093/nar/gkx1006.

23. Köhler S, Carmody L, Vasilevsky N, Jacobsen JOB, Danis D, Gourdine JP, et al. Expansion of the Human Phenotype Ontology (HPO) knowledge base and resources. Nucleic Acids Research. 2018; p. gky1105. doi:10.1093/nar/gky1105.

24. Ashburner M, Ball CA, Blake JA, Botstein D, Butler H, Cherry JM, et al. Gene Ontology: tool for the unification of biology. Nature genetics. 2000;25(1):25.

25. The Gene Ontology Consortium. Expansion of the Gene Ontology knowledgebase and resources. Nucleic Acids Research. 2017;45(D1):D331–D338. doi:10.1093/nar/gkw1108.

26. Kafkas S, Abdelhakim M, Hashish Y, Kulmanov M, Abdellatif M, Schofield PN, et al. PathoPhenoDB: linking human pathogens to their disease phenotypes in support of infectious disease research. bioRxiv. 2018;doi:10.1101/489971.

27. Sayers EW, Barrett T, Benson DA, Bryant SH, Canese K, Chetvernin V, et al. Database resources of the National Center for Biotechnology Information. Nucleic Acids Research. 2009;37(suppl_1):D5–D15. doi:10.1093/nar/gkn741.

28. Rodríguez-García MÁ, Gkoutos GV, Schofield PN, Hoehndorf R. Integrating phenotype ontologies with PhenomeNET. Journal of biomedical semantics. 2017;8(1):58.

29. Smith CL, Carroll, Eppig JT. The Mammalian Phenotype Ontology as a tool for annotating, analyzing and comparing phenotypic information. Genome Biology. 2004;6(1):R7.

30. Hoehndorf R, Schofield PN, Gkoutos GV. The role of ontologies in biological and biomedical research: a functional perspective. Briefings in Bioinformatics. 2015;.

31. Ammari MG, Gresham CR, McCarthy FM, Nanduri B. HPIDB 2.0: a curated database for host–pathogen interactions. Database. 2016;2016:baw103. doi:10.1093/database/baw103.

32. Mei S. Probability Weighted Ensemble Transfer Learning for Predicting Interactions between HIV-1 and Human Proteins. PLOS ONE. 2013;8(11):1–14. doi:10.1371/journal.pone.0079606.

33. Mei S, Zhu H. Computational reconstruction of proteome-wide protein interaction networks between HTLV retroviruses and Homo sapiens. BMC Bioinformatics. 2014;15(1):245. doi:10.1186/1471-2105-15-245.

34. Schofield PN, Hoehndorf R, Smith CL, Eppig JT, Gkoutos GV. 25 - The Informatics of Developmental Phenotypes. In: Morriss-Kay RBBRD, editor. Kaufman's Atlas of Mouse Development Supplement. Boston: Academic Press; 2016. p. 307 – 318. Available from: http://www.sciencedirect.com/science/article/pii/B9780128000434000257.

35. Wang A, Thurmond S, Islas L, Hui K, Hai R. Zika virus genome biology and molecular pathogenesis. Emerging Microbes & Infections. 2017;6(3):e13.

36. Chen CY, Chan CH, Chen CM, Tsai YS, Tsai TY, Wu Lee YH, et al. Targeted inactivation of murine Ddx3x: essential roles of Ddx3x in placentation and embryogenesis. Human Molecular Genetics. 2016;25(14):2905–2922. doi:10.1093/hmg/ddw143.

37. Blok LS, Madsen E, Juusola J, Gilissen C, Baralle D, Reijnders MRF, et al. Mutations in DDX3X Are a Common Cause of Unexplained Intellectual Disability with Gender-Specific Effects on Wnt Signaling. The American Journal of Human Genetics. 2015;97(2):343 – 352. doi:https://doi.org/10.1016/j.ajhg.2015.07.004.

38. Doňate-Macián P, Jungfleisch J, Pérez-Vilaró G, Rubio-Moscardo F, Perálvarez-Marín A, Díez J, et al. The TRPV4 channel links calcium influx to DDX3X activity and viral infectivity. Nature Communications. 2018;9:2307.

39. Hoehndorf R, Slater L, Schofield PN, Gkoutos GV. Aber-OWL: a framework for ontology-based data access in biology. BMC bioinformatics. 2015;16(1):26.

40. Fawcett T. An introduction to ROC analysis. Pattern Recogn Lett. 2006;27(8):861 – 874. doi:DOI: 10.1016/j.patrec.2005.10.010.

41. Bergstra JS, Bardenet R, Bengio Y, Kégl B. Algorithms for hyper-parameter optimization. In: Advances in neural information processing systems; 2011. p. 2546–2554.

42. Nair V, Hinton GE. Rectified linear units improve restricted boltzmann machines. In: Proceedings of the 27th international conference on machine learning (ICML-10); 2010. p. 807–814.