Skeletal descriptions of shape provide unique and privileged perceptual information for object recognition

Vladislav Ayzenberg
Stella F. Lourenco
Department of Psychology, Emory University

Correspondence:
Vladislav Ayzenberg (vayzenb@emory.edu)
Stella F. Lourenco (stella.lourenco@emory.edu)
Department of Psychology, Emory University
36 Eagle Row
Atlanta, GA 30322

Abstract

With seemingly little effort, humans can both identify an object across large changes in orientation and extend category membership to novel exemplars. Although researchers argue that object shape is crucial in these cases, it remains unknown how shape is represented for object recognition. Here we tested whether the human visual system incorporates a three-dimensional skeletal descriptor of shape to determine an object's identity. Skeletal models not only provide a compact description of an object's global shape structure, but also provide a quantitative metric by which to compare the visual similarity between shapes. Our results showed that a model of skeletal similarity explained the greatest amount of variance in participants' object dissimilarity judgments when compared with other computational models of visual similarity (Experiment 1). Moreover, parametric changes to an object's skeleton led to proportional changes in perceived similarity, even when controlling for another model of structure (Experiment 2). Importantly, participants preferentially categorized objects by their skeletons across changes to local shape contours and non-accidental properties (Experiment 3). Our findings highlight the importance of skeletal structure in vision, not only as a shape descriptor, but also as a diagnostic cue of object identity.

Introduction

The same object produces vastly different shapes on the retina across changes in orientation, and objects of the same category have vastly different shape contours across exemplars. Yet, with very little experience, humans (adults: Biederman & Bar, 1999; infants: Mash, Arterberry, & Bornstein, 2007) and nonhuman animals (monkeys: Logothetis, Pauls, Bülthoff, & Poggio, 1994; chicks: Wood, 2013; rats: Zoccolan, Oertelt, DiCarlo, & Cox, 2009) recognize objects rapidly and with ease across such variations. Research in the vision sciences suggests that shape is crucial for object recognition (Biederman & Ju, 1988; Elder, 2018; Marr & Nishihara, 1978). Humans readily use shape to recognize objects in the absence of other visual information (e.g., texture and shading; Biederman & Ju, 1988; Wagemans et al., 2008), and both adults and children preferentially categorize novel objects by their shape across conflicting color and texture cues (Elder & Velisavljević, 2009; Landau, Smith, & Jones, 1988). Moreover, human representations of shape are robust to changes in view (Biederman, 1987; Biederman & Bar, 1999), contour perturbation (Kanizsa, 1976; Spröte, Schmidt, & Fleming, 2016), and deformations from bending or stretching (e.g., hand poses; Barenholtz & Tarr, 2008; Leyton, 1989; Spröte & Fleming, 2016), suggesting a reliance on global shape properties over local contour information (Baker & Kellman, 2018; Sanocki, 1993). However, few studies have offered a formalized account of how humans represent and compare global shape properties to recognize objects (for review, see Elder, 2018). In the current study, we tested whether humans incorporate a computational model of global shape structure based on the medial axis, or 'shape skeleton', to determine an object's identity.

Shape skeletons are a class of geometric models, based on the medial axis of the shape. These models describe shape via the set of symmetry axes that lie equidistant between two or more points along the boundary (Blum, 1967, 1973). More specifically, skeletons describe an object's shape structure by specifying the spatial configuration of contours and component parts. Modern skeletal algorithms (i.e., pruned medial axis models; Shaked & Bruckstein, 1998; Wieser, Seidl, & Zeppelzauer, 2017) are particularly good descriptors of an object's global shape because their structure remains relatively stable across contour variations typical of natural contexts (e.g., perturbations, bending; Feldman & Singh, 2006; Liu & Geiger, 1999; Trinh & Kimia, 2011). Importantly, research in computer vision has formalized many methods by which to compare skeletons (e.g., distance metrics; Sebastian, Klein, & Kimia, 2004), thereby providing a quantitative metric by which to compare shapes. These methods have been used successfully to identify objects across viewpoints and exemplars (for review, see Kimia, 2003), with classification accuracy matching human performance for superordinate object categories (i.e., animals and plants; Wilder, Feldman, & Singh, 2011).

Accumulating evidence suggests that the skeletal structure of objects is extracted by the primate visual system during shape perception. In particular, behavioral studies have shown that human participants extract the skeletons of different 2D shapes (Firestone & Scholl, 2014; Harrison & Feldman, 2009; Kovács, Fehér, & Julesz, 1998; Kovacs & Julesz, 1994; Psotka, 1978) and those skeletal structures remain relatively stable across border disruptions resulting from perturbations or illusory contours (Ayzenberg, Yousif, & Lourenco, 2016). Increasingly, studies have shown that skeletal structures may be represented in three dimensions (3D) within an object-centered reference frame. Indeed, humans are better at discriminating 3D objects by skeletal differences than by differences in component parts (e.g., part orientation; Lowet, Firestone, & Scholl, 2018). Moreover, studies using neural recording (i.e., fMRI and electrophysiology) with humans and

monkeys have found sensitivity to 3D object skeletons in high-level visual cortical areas (e.g., IT), including those known to support object recognition (Hung, Carlson, & Connor, 2012; Lescroart & Biederman, 2013). Skeletal sensitivity in these regions was decoded across changes in orientation and variations in local shape properties, suggesting a 3D object-centered representation that is robust to changes in viewpoint and component parts.

Despite the success of skeletal descriptions in computer vision systems (e.g., Trinh & Kimia, 2011) and their biological plausibility in the primate visual system (e.g., Hung et al., 2012), shape skeletons are rarely incorporated into models of object recognition. Instead, modern computational approaches to object recognition emphasize image statistics (Oliva & Torralba, 2006) or hierarchical feature extraction operations such as those implemented by convolutional neural networks (CNNs; Krizhevsky, Sutskever, & Hinton, 2012; Serre, Wolf, Bileschi, Riesenhuber, & Poggio, 2007). Yet, without explicitly invoking any skeletal description, these models match human performance on object recognition tasks (Krizhevsky et al., 2012), and they are predictive of both human behavioral and neural responses (Jozwik, Kriegeskorte, Storrs, & Mur, 2017; Schrimpf et al., 2018; Yamins et al., 2014). Even models that do emphasize global shape properties do so by describing the local properties of components parts (e.g., geons) and the coarse, categorically defined, spatial relations (Biederman, 1987; Hummel, 2001), not a skeletal structure (but, see Lescroart & Biederman, 2013). Given that these other models successfully approximate human object recognition, one might ask whether skeletal descriptions of shape are necessary for human object recognition at all. Thus, in the current study, we tested the degree to which skeletal descriptions of shape make unique, and possibly privileged, contributions to human object recognition in comparison to several other models of shape and object perception.

If the shape's skeletal structure provides unique contributions to object recognition, then humans will perceive objects with similar skeletons as more similar to one another, even when controlling for other models. Moreover, if skeletal structures are a privileged source of information for object recognition, then humans will favor the shape skeleton over both non-shape based models of visual similarity, as well as other descriptors of shape. To this end, we assessed whether participants' perceptual judgments of object similarity scaled with the skeletal similarity between novel 3D objects (Experiment 1), including objects whose coarse spatial relations could not be used for judging similarity (Experiment 2). We also tested how participants classified objects when the shape's skeletal structure was placed in conflict with the object's surface form, a manipulation that altered the shape's contours and non-accidental properties (NAPs) without changing its skeleton (Experiment 3). In all cases, we examined the unique contributions of skeletal structures in object recognition by contrasting the shape skeleton with models of vision that do not explicitly incorporate a skeletal structure, but are nevertheless predictive of human object recognition. These models included those that describe visual similarity by their image statistics, namely, the Gabor-Jet model (Margalit, Biederman, Herald, Yue, & von der Malsburg, 2016) and GIST model (Oliva & Torralba, 2001), as well as biologically plausible neural networks models, namely, the HMAX model (Serre, Wolf, et al., 2007) and AlexNet, a CNN pre-trained to identify objects (Krizhevsky et al., 2012). To anticipate our findings, a model of skeletal similarity was predictive of participants' perceptual similarity and classification judgments even when accounting for these other models, suggesting that skeletal descriptions of shape play a crucial role in human object recognition, independent of other models of shape and object perception.

Experiment 1 – Is perceived object similarity predicted by a model of skeletal similarity?

Here we tested one of the predictions outlined above: namely, as object skeletons becomes more similar, participants should judge the objects as being more alike. To test for a relation between human perceptual judgments and the shape skeleton, we generated a novel set of 3D objects that varied in their skeletal structures. Crucially, we compared the predictive power of skeletal descriptions to other models of visual similarity and tested the degree to which a model of skeletal similarity explained unique variance in human perceptual judgments.

Stimuli and experimental design. A total of 150 3D objects consisting of 30 skeletons were generated (see Figure 1). All objects were comprised of three segments and were normalized for overall size (see Methods). Each object was rendered with five surface forms, serving to change the visible shape of the object on the retina without altering the underlying skeleton (see Figure 3A and Methods). Skeletal similarity between every object was calculated in 3D, object-centered, space as the mean Euclidean distance between each point on one skeleton and the closest point on the second skeleton following maximal alignment (see Figure 2A and Methods). We chose to test a 3D skeletal description because of behavioral (Erdogan & Jacobs, 2017) and neural (Yamane, Carlson, Bowman, Wang, & Connor, 2008) evidence for 3D object-centered representations in the visual system, which include a sensitivity to 3D skeletal structures (Hung et al., 2012; Lowet et al., 2018).

Figure 1. Stimuli used in Experiment 1. Objects were procedurally generated to have different skeletal structures. Each object was also rendered with five surface forms. All objects in this figure are displayed in one surface form (see Figure 3A for other surface forms and Methods for stimulus details). Subsets of these stimuli were used in Experiments 2 and 3 (see Methods).

Participants (*n* = 42) were administered a discrimination task in which they were shown images of two objects presented simultaneously in one of three depth orientations (-30°, 0°, +30°), with either the same or different skeletons. Participants were instructed to decide whether the two images showed the same or different object (independent of orientation). Participants were given unlimited time to respond but the instructions emphasized speed and accuracy.

Results and discussion. Skeletal similarity was a significant predictor of participants' judgments, *r* = 0.30, *p* < 0.001 (significance determined via permutation test; see Figure 2B). That is, as the similarity between skeletal structures increased, participants were more likely to judge the objects as the same. However, one might ask whether another model of vision, which does not incorporate skeletal information, could account for this effect, especially given that objects with similar skeletons might also have similar image-level properties. To address this possibility, we compared participants' judgments to Gabor-Jet, GIST, HMAX, and CNN models (see Figure 2A). When compared independently, these models were all predictive of participants' judgments (*rs* = 0.25 – 0.32), with no significant differences between models (see Figure 2B). Nevertheless, it is unclear whether these models are accounting for the same variance in participants' perceptual judgments or whether a model of skeletal similarity explains unique variance. To answer this question, we used variance partitioning analyses (Bonner & Epstein, 2018; Lescroart, Stansbury, & Gallant, 2015) to examine the amount of variance unique to each model (see Figure 2C), as well as shared between models (see Supplemental Table 1). Our model of skeletal similarity independently explained the greatest amount of variance in participants' responses (33.13%; see Figure 2C and Supplemental Table 1). A 4-predictor model consisting of the Gabor-jet, GIST, HMAX, and AlexNet-fc6 predicted the next greatest amount of variance (15.49%; see Supplemental Table 1). Taken together, these analyses suggest that, although all of the tested models of visual similarity were predictive of participants' perceptual judgments, a model of skeletal similarity explained these judgments over and above other models. These results suggest that skeletal structures may provide unique and privileged information regarding an object's identity.

Figure 2. Results from Experiment 1. (A) Dissimilarity matrices computed from human discrimination judgments, as well as from models of skeletal and visual similarity. (B) Bar plot displaying the correlations (Pearson) between each model and human perceptual similarity judgments. Models did not significantly differ in the degree to which they predicted human judgments. (C) Bar plot displaying the percentage of unique variance explained by each model. A model of skeletal similarity explained the most variance in human judgments when compared to any single model or combination of models (see Supplemental Table 1 for the coefficients and percentage explained by all model combinations). Error bars are bootstrapped standard error.

Experiment 2 – Can perceived similarity be explained by another model of structure?

The results of Experiment 1 suggest that humans incorporate skeletal representations when making object similarity judgments. However, an alternative possibility is that participants' sensitivity reflected a different model of structure, namely one based on the coarse spatial relations between object parts (Biederman & Gerhardstein, 1993; Hummel, 2000; Hummel & Stankiewicz, 1996). A model based on coarse spatial relations suggests that the structure of an object is represented by the approximate arrangement of component parts (e.g., two components below a third; see Figure 3A). In contrast to skeletal descriptions of shape, which describe quantitative relations between component parts, a coarse spatial-relations model would predict that only qualitative changes to the overall spatial arrangement of the parts (e.g., moving a component from the bottom to the side) should influence object recognition. Yet objects with similar spatial relations also have more similar skeletal structures. Thus, the relation between skeletal similarity and human perceptual judgments in Experiment 1 could have reflected the co-variation between the shape skeleton and an object's coarse spatial relations.

Here we tested whether participants' judgments of perceptual similarity were influenced by an object's skeletal structure even when coarse spatial relations were held constant, and thus unable to be used as a similarity cue. If perception of object shape is based on a skeletal structure, then a proportional change to the shape skeleton would elicit a proportional decrease in recognition, even when the coarse spatial relations are unchanged. Thus, as two skeletons become more dissimilar, participants should judge the objects as more different from one another.

Stimuli and experimental design. To test whether proportional changes to the shape skeleton led to proportional deficits in recognition, despite constant coarse spatial relations, we adapted three objects from Experiment 1 to have six increments of skeletal dissimilarity (0%, 10%, 20%, 30%, 40%, 50% difference; see Methods for additional details). Changes to the skeleton were implemented by moving one component along the length of another component in 10% increments (see Figure 3A). This manipulation caused systematic changes to the shape skeleton without changing the coarse spatial relations between the object's component parts.

Participants (n = 42) completed a discrimination task in which they were shown two simultaneously presented objects and were instructed to judge whether the objects were the same or different in their coarse spatial relations. Crucially, participants were instructed to ignore any changes to the precise positions of the object parts (i.e., exact skeleton) so as to make their decision on the basis of "overall shape." Participants were given a training phase to ensure they understood that these instructions referred to objects with the same coarse spatial relations (e.g., in Figure 3A each column consists of objects with the same "overall shape" but different skeletons). Objects were presented from three orientations that maximized the visibility of the object's structure (30°, 60°, and 90°). Participants were given unlimited time to respond but were encouraged to respond quickly and accurately.

Results and discussion. Participants performed significantly above chance (0.50) at every level of skeletal change, $ts(34) > 2.32$, $ps < 0.026$, $ds > 0.39$, demonstrating that they followed the task instructions to identify objects by their coarse spatial relations. Crucially, however, participants' performance in discriminating between objects with the same coarse spatial relations was less accurate as a function of skeletal change, $F(1, 34) = 51.77$, $p < 0.001$, $\eta_p^2 = 0.60$ (Figure 3B), suggesting that when participants make perceptual similarity judgments, they incorporate fine-grained structural information, as suggested by a skeletal model. Nevertheless, as in the previous experiment, a change to the object's shape skeleton also induced changes along other visual dimensions (e.g., image-statistics). Thus, we tested whether participants' performance was better described by other models of vision. To this end, we used a random-effects regression analysis, with the skeletal similarity model and other models (i.e., Gabor-Jet, GIST, HMAX, and CNN) as predictors (subject and object as the random effects; see Methods for additional details). Analyses revealed that the model of skeletal similarity remained a significant predictor of human performance even when controlling for the other models, $\chi^2(1) = 22.30$, $p < 0.001$, and that it explained the greatest amount of variance in participants' responses, $\beta = -1.24$. The only other model to explain unique variance was GIST, $\chi^2(1) = 19.55$, $p < 0.001$, $\beta = 0.63$, suggesting a role for image-statistics in this process (see Supplemental Table 2 for the results of the other models). Taken together, these findings suggest that participants' judgments of perceived object similarity reflect the metric positions of object parts, consistent with an object representation based on skeletal structure, not the course spatial relations. Combined with Experiment 1, these results provide further support for the unique and privileged role of skeletal descriptions of shape in object recognition.

Figure 3. Example stimuli and results from Experiment 2. (A) On the 'same' test trials (objects within a column), participants were presented with a reference object (0%) and an object with the same coarse spatial relations. Crucially, objects with the same spatial relations varied in skeletal similarity by increments of 0%, 10%, 20%, 30%, 40%, or 50% (each row within a column). On the 'different' test trials (objects within a row), participants were presented with objects that had different coarse spatial relations. (B) Participants' recognition accuracy (proportion correct) for objects with the same coarse spatial relations decreased as a function of skeletal change, suggesting that humans represent object structure by their skeletons. The dotted line represents chance performance and the error bars are standard error of the mean.

Experiment 3 – Are skeletal structures a privileged source of information for object recognition?

A model of skeletal similarity was most predictive of human perception in Experiments 1 and 2, when compared to other, non-shape-based, models of visual similarity (i.e., Gabor-Jet, GIST, HMAX, and a CNN), as well as another descriptor of structure (i.e., coarse spatial relations). Together, these results suggest that shape information, particularly skeletal descriptors of shape, plays an important role in object recognition. However, there exist alternative descriptors of shape, which emphasize local contour information (Elder, 1999; Op de Beeck, Torfs, & Wagemans, 2008) or the non-accidental properties (NAPs) of component parts (Biederman, 1987), not skeletal structures. Thus, it remains unknown whether, for object recognition, skeletal structures offer a more informative descriptor of shape than local contour information and component parts.

To test this hypothesis, the skeleton of an object was pitted against its surface form in a match-to-sample task. Surface forms were designed to alter the object's contours without changing the object's underlying skeleton (Hung et al., 2012). As described in more detail below, surface form similarity was perceptually matched to skeletal similarity and surface forms were well characterized by other models of vision. Moreover, surface forms were created such that they differed in NAPs in order to compare the skeletal descriptions against a model of shape based on component parts (Amir, Biederman, & Hayworth, 2012; Biederman, 1987). NAPs, such as the

degree to which a component tapers or bulges outward, are thought to play an essential role in models of shape perception because they serve as unique identifiers of component parts, allowing objects to be identified from a variety of viewpoints (Biederman, 1987, 2000). Thus, by pitting an object's skeleton against its surface form, we can better understand the degree to which different descriptors of shape are used for object recognition.

Surface form properties. To quantify the degree of visual similarity between surface forms, participants (n = 41) conducted a surface form discrimination task (see Methods). In this task, participants judged whether two objects were the same or different in surface form (same skeletons). Surface form discrimination accuracy was compared to skeletal discrimination accuracy from Experiment 1 for the four skeletons used here (see Methods). This analysis revealed that surface form discrimination accuracy (M = 0.87, SD = 0.19) did not differ from skeleton discrimination accuracy (M = 0.86, SD = 0.20), $t(77)$ = 0.76, p = 0.94. Follow up analyses revealed that participants' surface form discrimination performance was well described by Gabor-jet, GIST, HMAX, and CNN models, rs = 0.63-0.77, with the CNN explaining unique variance when all three models were entered into a random-effects regression, $\chi^2(1)$ = 12.71, p < 0.001.

To test whether surface forms were comprised of unique NAPs, a separate group of participants (n = 41) were taught to identify different NAPs and they then rated the degree to which each surface form exhibited a particular NAP (e.g., "To what extent do parts of this object exhibit taper?") on a 7-point Likert scale (1 "not at all"; 7 "a lot"; see Methods for details). A k-means cluster analysis (Hartigan & Wong, 1979) revealed that participants' ratings were best described by four clusters, and a permutation test, in which cluster labels were shuffled 10,000 times, revealed that cluster labels were predictive of each surface form significantly better than chance (ps < 0.002). That the surface forms were better described by four, rather than five (one for each surface form), clusters is consistent with two of the surface forms having the same NAPs, but differing in metric properties such as circumference (see Figure 4A; Amir et al., 2012; Vogels, Biederman, Bar, & Lorincz, 2001).

Match-to-sample task: design. Having confirmed that the surface forms were perceptually matched to skeletal differences, and that they were comprised of unique NAPs, we were in a position to test whether skeletal descriptions of shape were a privileged source of information for object recognition relative to other descriptors of shape. In a match-to-sample task, a separate group of participants (n = 39) were presented with a sample object and two choice objects (i.e., target and distractor; see Figure 4B). They were instructed to judge which of the two choice objects was most likely to be from the same category as the sample object. The target object matched the sample object in either its skeleton or surface form. The distractor object differed from the sample object by its skeleton, surface form, or both. These trials ensured that participants were able to match objects by either their skeleton or surface form when either property was presented in isolation. Other trials presented a conflict between the object's skeleton and surface form such that one of the choice objects matched the sample's skeleton, but not surface form, and the other object matched the object's surface form, but not skeleton (see Figure 4B). The conflict trials tested whether the skeletal descriptors served as a preferred cue for object recognition. The objects were presented as still images in one of three depth orientations (30°, 60°, 90°). Participants were instructed to ignore the orientations of the objects and, on each trial, to choose which of the two choice objects was from the same category as the sample object.

Match-to-sample task: results and discussion. Participants successfully categorized objects by either their skeletons, $t(38)$ = 27.01, p < 0.001, d = 4.32, 95% CI [3.35, 5.41], or surface forms, $ts(38)$

= 15.51, $p < 0.001$, $d = 2.48$, 95% CI [1.87, 3.16], when each cue was presented in isolation, as indicated by their above chance performance in these conditions (see Figure 4C). Crucially, however, on the conflict trials, participants categorized objects by their skeletons, not surface forms, $t(38) = 6.63$, $p < 0.001$, $d = 1.06$, 95% CI [0.66, 1.45] (see Figure 4C, D). Indeed, participants preferentially categorized objects by their skeletons when pitted against all ($Ms > 0.61$, $ts[38] > 2.52$, $ps < .016$, $ds > 0.40$) but one ($M = 0.58$, $p = .059$, $d = 0.31$) surface form. Thus, although surface forms were perceptually matched to the objects' skeletons and were comprised of unique NAPs, participants relied more heavily on the shape skeleton when classifying objects, suggesting that skeletal structure may be a privileged source of shape information for object recognition.

Figure 4. Stimuli and results from the match-to-sample task of Experiment 3. (A) Five surface forms (illustrated here for objects with the same skeleton) were generated so as to vary in contour shape and in NAPs without disrupting the object's skeleton. A cluster analysis revealed that the first and second surface form (from left to right) were comprised of the same NAPs. (B) A conflict trial from the match-to-sample task. The two choice objects (below) matched the sample object (above) by either the shape skeleton (left) or surface form (right). (C) Participants' performance on trials in which only a skeleton or surface form match was possible, as well as the conflict trials. Although participants successfully matched objects by their skeletal structure or surface forms when each cue was presented in isolation, they were more likely to match objects by their skeleton, as opposed to their surface forms, when these cues conflicted with one another. (D) Histogram of participants' responses on the conflict trials. A value greater than zero indicates greater weighting of skeletal information. The majority of participants matched objects by their skeleton, demonstrating a consistent pattern of responses across participants.

General Discussion

The ability to determine the similarity between shapes is crucial for object recognition. Shape skeletons may be particularly useful in this context because they provide a compact descriptor of shape, as well as a formalized method for computing shape similarity. Nevertheless, few models of biological object recognition include skeletal descriptions in their implementation. Here we tested whether skeletal structures provide an important source of information for object recognition when compared with other models of vision. Our results showed that a model of skeletal similarity was most predictive of human object judgments when contrasted with models based on image-statistics or neural networks, as well another model of structure based on coarse spatial relations. Moreover, we found that skeletal structures were a privileged source of information when compared to other properties thought to be important for shape perception, such as object contours and component parts. Thus, our results suggest that not only does the visual system show sensitivity to the skeletal structure of objects (Hung et al., 2012; Kovács et al., 1998; Lowet et al., 2018), but also that perception and comparison of object skeletons may be crucial for successful object recognition.

The strength of skeletal models is that they provide a compact description of an object's global shape structure, as well as a metric by which to determine shape similarity. Indeed, shape skeletons may offer a concrete formalization for the oft poorly defined concept of global shape. Skeletal descriptions exhibit many properties ascribed to global shape percepts such as relative invariance to local contour variations (Ayzenberg et al., 2016; Shaked & Bruckstein, 1998). Moreover, there exist many methods by which to compare skeletal structures, such as by their hierarchical organization (e.g., Shokoufandeh, Macrini, Dickinson, Siddiqi, & Zucker, 2005) or using distance metrics (as used here; Sebastian et al., 2004), thereby allowing for a quantitative description of shape similarity. Such a description may be particularly important when recognizing objects across previously unseen views or categorizing novel object exemplars.

In the current study, we chose to test whether humans represent a 3D skeletal structure rather than a 2D skeleton that is arguably more easy to compute from an image (Trinh & Kimia, 2011). Our decision was motivated by behavioral (Lowet et al., 2018) and neuroimaging work (Hung et al., 2012; Lescroart & Biederman, 2013) suggesting sensitivity to 3D skeletons in the primate visual system, as well as accumulating evidence that object perception (at least for novel objects) is best described by a 3D object-centered shape representation (Erdogan & Jacobs, 2017; Yamane et al., 2008). However, it remains unknown how a 3D skeletal structure arises from 2D images on the retina. One possibility is that skeletal computations in the visual system invoke generative shape processes (Elder, Oleskiw, Yakubovich, & Peyré, 2013; Trinh & Kimia, 2007). These processes may be able to recover an object's 3D skeletal structure from retinal images by incorporating a small number of image-computable 2D skeletons (e.g., one from each eye; Qiu, Hatori, & Sakai, 2015). Alternatively, it is possible that an object's 3D structure may be recovered from a single image by first creating a representation based off of depth properties and surface orientation, a so-called 2.5D sketch (Marr & Nishihara, 1978). Indeed, recent neural network models have been able to successfully reconstruct an object's 3D shape from single images by incorporating 2.5D sketches (Wu et al., 2017), offering a possible mechanism for 3D skeleton generation. Consistent with these possibilities, our results showed that object judgments were well described by a 3D skeletal structure even though participants were only ever shown object images from a limited number of

viewpoints. Nevertheless, more research is needed to understand how 3D skeletal representations arise from 2D images on the retina.

Although our findings suggest that skeletal descriptors play an important role in object recognition, we would not argue that skeletal descriptions alone are sufficient. Humans do not perceive the visual environment simply as a collection of skeletons, but rather, as complete objects where local contours, textures, and colors are integrated with a shape structure. Indeed, our results showed that other models of vision were also predictive of participants' object judgments to varying degrees in every experiment. That other models were also predictive may be unsurprising, given that both shape- and non-shape-related properties are known to play important roles in object recognition. For instance, local contour information may be particularly useful for making subordinate-level category distinctions where the skeletons of objects are roughly the same (e.g., different dog breeds; Davitt, Cristino, Wong, & Leek, 2014; Hummel & Stankiewicz, 1996). Similarly, texture statistics and feature descriptions have been shown to be important indicators of both basic- (Elder & Velisavljević, 2009; Ullman, Assif, Fetaya, & Harari, 2016) and superordinate-level (Long, Störmer, & Alvarez, 2017; Long, Yu, & Konkle, 2018) object distinctions. And, although it is currently unclear whether feed-forward neural network models (such as the one tested here) incorporate global shape information (Baker, Lu, Erlikhman, & Kellman, 2018; Geirhos et al., 2018), more biologically plausible models with recurrent architectures may begin to approximate human shape perception (Tang et al., 2018). Nevertheless, our work highlights the importance of formalized models of shape for object recognition, particularly the unique, and possibly privileged, role that skeletal structures may play.

<div align="center">

Methods

</div>

Participants. 205 participants were tested in the current study (M_{age} = 19.75 years; *range* = 18.03 – 23.48 years). Of these participants, 16 were excluded for exhibiting chance, or below chance, performance (3 from Experiment 1; 7 from Experiment 2; 3 from the surface form discrimination task of Experiment 3). Because accuracy could not be evaluated in the NAP rating task of Experiment 3, we ensured that participants exhibited reliable performance; 6 participants were excluded from this experiment for failing to meet this criterion (αs < 0.7).

Apparatus. All tasks were presented on a desktop computer with a 19-inch screen (1280 × 1024 px) and controlled using custom software written in Visual Basic (Microsoft). Participants sat at a distance of ~60 cm from the computer screen.

Experiment 1

Stimulus generation. Objects were procedurally generated using the Python API for Blender (Blender Foundation). Each skeleton was comprised of three segments created from Bezier curves of a random size and curvature scaled between .05 and .25 virtual Blender units (vu). The first axis segment was oriented forward towards the 'camera'. The second and third segments were oriented perpendicular to the first segment and attached to the first segment or second segment at a random point along their length. Surface forms were created by applying a circular bevel to the object's skeleton along with one of five taper properties that determined the shape of the surface form. Finally, the overall size of the object was normalized to .25 vu.

Skeletal similarity model. The coordinates of the skeleton for each object were extracted by sampling 999 points along the length of each axis segment (2997 points in total). Skeletal points

were normalized by the length of each segment by subsampling points along the skeletal structure until these points were evenly spaced across the skeleton by 0.0005 vu (for ease of analysis, coordinates were rescaled by a factor of 1000). Skeletal similarity was calculated as the mean Euclidean distance between each point on one skeleton structure with the closest point on the second skeleton structure following maximal alignment. Maximal alignment was achieved by overlaying each structure by its center of mass and then iteratively rotating each object in the picture plane orientation by 15° until the smallest distance between structures was found.

Gabor-jet model. The Gabor-jet model is a low-level model of image similarity inspired by the response profile of complex cells in early visual cortex (Margalit et al., 2016). It has been shown to scale with human psychophysical dissimilarity judgments of faces and simple objects (Yue, Biederman, Mangini, von der Malsburg, & Amir, 2012). To simulate the response profile of complex cell responses, the model overlays a 12 × 12 grid of Gabor filters (5 scales × 8 orientations) along the image. The image is convolved with each filter, and the magnitude and phase of the filtered image is stored as a feature vector. Dissimilarity between each image is computed as the mean Euclidean distance between feature vectors of each image. A single dissimilarity value was computed for each object by taking the mean Gabor activation distance for an object pair across the three orientations (30 objects × 3 orientations).

GIST. The GIST model is considered a mid-level model of image similarity that describes the content of an image through global image features (Oliva & Torralba, 2001). It has been shown to accurately describe the content of natural images, particularly as they relate to scene perception (Oliva & Torralba, 2006). The model overlays a grid of Gabor filters (4 scales × 8 orientations) on the image and then convolves the image with the filters, creating a feature activation map. This feature map is divided into 16 regions (based on the 4 × 4 grid) and then mean activation within each region is computed and stored as a GIST feature vector. GIST dissimilarity between each image is computed as the mean Euclidean distance between feature vectors of each image. A single dissimilarity value was computed for each object by taking the mean Euclidean distance for an object pair across the three orientations (30 objects × 3 orientations).

HMAX. The HMAX (hierarchical MAX) model is a biologically inspired hierarchical neural network model that describes an image by max-pooling over a series of simple (S1, S2) and complex (C1, C2) units (Serre, Oliva, & Poggio, 2007; Serre, Wolf, et al., 2007). It has been shown to match human performance on simple category judgment tasks (e.g., animals and non-animals) and exhibits some invariance to changes in position and scale. In the current study, we used the feature patches provided with the HMAX model. In the first layer (S1), each image is convolved with Gabor filters (8 scales × 4 orientations), the output of which is fed into a second layer (C1) that determines the local maximum over all positions and scales. The outputs of these layers are fed through a second set of simple and complex units (S2, C2). Dissimilarity was computed by extracting the C2 activations for each image and correlating (Pearson) it with the activations for every other image. A single dissimilarity value was computed for each object by taking the mean correlation for an object pair across the three orientations (30 objects × 3 orientations).

CNN. As a model of high-level vision, we used AlexNet, an eight layer deep CNN pre-trained to classify objects from the ImageNet database (Krizhevsky et al., 2012; Russakovsky et al., 2015). We adopted AlexNet rather than other CNNs in our analyses because its architecture is relatively simple by comparison and because it can identify objects with high accuracy (Krizhevsky et al., 2012). Importantly, AlexNet has been shown to be predictive of human object similarity judgments

(Jozwik et al., 2017). CNN similarity for each object was calculated by extracting the unit activations of each convolutional, and fully connected, layer for each object image, and then computing the mean Euclidean distance between activations for each image with every other image. A single difference value was computed for each object pair by taking the mean CNN difference for an object pair across the three orientations (30 objects × 3 orientations). Dissimilarity values were calculated for every layer and correlated to participants' behavioral judgments. Participants' similarity judgments in Experiment 1 were most strongly correlated with fully-connected layer 6 (fc6) of AlexNet, $r = 0.34$ (see Figure 2B). Because fc6 was most predictive in this experiment, we tested only fc6 in subsequent experiments.

Discrimination task. On each trial, participants were shown images of two objects (side-by-side) presented simultaneously in one of three depth orientations (-30°, 0°, +30°). Objects were matched for surface form and either had the same or different skeleton. Participants were instructed to decide whether the two images showed the same or different object (independent of orientation). Each object was paired with every other object (including itself) during the experimental session. Participants were administered a total of 885 trials (435 different and 450 same trials). Each trial began with a fixation cross (500 ms), followed by a pair of objects, which remained onscreen until a response was made, followed by an inter-trial interval (500 ms). Each object was approximately 6° × 6° in size and subtended 9° from the center of the screen.

Experiment 2

Stimulus generation and model analyses. A k-means cluster analysis was conducted on participants' discrimination data from Experiment 1. This analysis revealed that objects were well described by four clusters. Based on these clusters, three perceptually matched objects were chosen whose skeletons could be altered without changing the coarse spatial relations. Six versions of each object (0%, 10%, 20%, 30%, 40%, and 50% skeleton difference) were generated by moving one segment along the length of the central segment in 10% increments (relative to the length of the central component). Objects were rendered with only the thinnest surface form to prevent component parts from overlapping. Images of each object (18 total) were generated in three orientations (30°, 60°, 90°) intended to maximize the view of each object. Each object was analyzed and compared with every other object using the same models and procedure described in Experiment 1.

Discrimination task. On each trial, participants were shown images of two objects (side-by-side) presented simultaneously in one of the three depth orientations (30°, 60°, 90°). Each object was rendered with the same surface form (see Figure 3A) and either had the same or different coarse spatial relations. On each 'same' trial, participants were presented with both a reference object (0% skeletal difference) and another object that had the same coarse spatial relations but different skeleton in one of the increments described previously (see also Figure 3A). Participants were instructed to decide whether the two images showed an object with the same or different "overall shape" (independent of orientation). Participants were given instructions and 8 training trials (with feedback) using a separate set of objects to ensure that they understood that "overall shape" referred to objects with the same coarse spatial relations. In the same trials, each skeletal difference was presented an equal number of times. Participants were administered at total of 648 trials (324 same trials and 324 different trials). Each trial began with a fixation cross (500 ms), followed by a pair of objects, which remained onscreen until a response was made, followed by an inter-trial

interval (500 ms). Each object was approximately 6° × 6° in size and subtended 9° from the center of the screen.

Experiment 3

Stimulus generation and model analyses. Four perceptually matched objects were chosen from the object clusters identified in Experiment 2. Images of each object (4 objects × 5 surface forms) were generated in three orientations (30°, 60°, 90°) intended to maximize the view of each object.

Surface form discrimination task. On each trial, participants were shown images of two objects (side-by-side) in one of the three depth orientations (30°, 60°, 90°). Objects had the same shape skeleton and either the same or different surface forms. Participants were instructed to decide whether the two images showed the same or different object (independent of orientation). Each surface form was paired with every other surface form an equal number of times for a total of 600 trials.

NAP task. To test whether surface forms were comprised of unique component parts, participants rated each surface form on the degree to which it exhibited a specific NAP. During a training phase, participants were taught a subset of NAPs (drawn from Amir et al., 2012) and then shown a subset of objects that they were asked to rate on the degree to which they exhibited the specific NAP. The four NAPs were: (1) *taper,* defined as the degree to which the thickness of an object was reduced towards the end (taper in the current study corresponds to 'expansion of cross-section' in Amir et al., 2012); (2) *positive curvature*, defined as the degree to which an object part curved outwards; (3) *negative curvature,* defined as the degree to which an object part curved inwards; and (4) *convergence to vertex,* defined as the degree to which an object part ended in a point. We excluded the curved versus straight axis property of Amir et al. (2012) because it was confounded with the object's skeleton. We also excluded the change in cross-section property (e.g., circular vs. rectangular shape) because all of the surface forms had a circular cross-section. Participants were tested on their understanding of the four NAPs with a task in which they were presented with pairs of single-part objects (simultaneously on screen) where one exhibited an NAP and the other did not. Participants were instructed to select the object that exhibited more/less of a particular NAP (e.g., "Which object exhibits more positive curvature?"; feedback was provided). During the rating phase, participants were shown each test stimulus with each surface form (4 objects × 5 surface forms) and asked to rate the degree to which each surface form exhibited a particular NAP (e.g., "To what extent do parts of this object exhibit taper?") on a 7-point Likert scale (1 = "not at all"; 7 = "a lot").

Match-to-sample task. On each trial, participants were shown one object (sample) placed centrally near the top of the screen above two objects near the bottom of the screen (target and distractor). Participants were instructed to choose which of the two bottom objects was most likely to be in the same category as the sample. Participants were presented with three possible trial types: skeleton and surface form trials, in which one object matched the sample in either the skeleton or surface form, respectively (the other object matched on neither); and conflict trials in which one object matched in skeleton, but not surface form, and the other object matched in surface form, but not skeleton. Participants were administered a total of 480 trials (160 of each trial type). Each trial began with a fixation cross (500 ms), followed by the two objects, which remained onscreen until a response was made, followed by an inter-trial interval (500 ms). Each stimulus was approximately 6° × 6° in size and subtended 9° from the center of the screen.

Supplemental Table 1. Coefficients and percentages of the unique and shared variance explained for each model and model combinations used in Experiment 1.

Model	Coefficient	Percent
SKEL	0.066	33.305
GBJ	0.017	8.669
GIST	0.006	2.949
HMAX	0.007	3.678
fc6	0.005	2.508
SKEL + GBJ	-0.006	-3.218
SKEL + GIST	-0.002	-1.209
GBJ + GIST	-0.005	-2.569
SKEL + HMAX	-0.002	-0.859
GBJ + HMAX	0.003	1.730
GIST + HMAX	0.000	0.187
SKEL + fc6	0.010	5.046
GBJ + fc6	0.012	6.116
GIST + fc6	-0.001	-0.525
HMAX + fc6	0.004	2.235
SKEL + GBJ + GIST	0.002	1.125
SKEL + GBJ + HMAX	-0.001	-0.477
SKEL + GIST + HMAX	0.000	-0.047
GBJ + GIST + HMAX	0.000	0.162
SKEL + GBJ + fc6	0.003	1.502
SKEL + GIST + fc6	0.000	-0.237
GBJ + GIST + fc6	0.019	9.302
SKEL + HMAX + fc6	0.002	1.187
GBJ + HMAX + fc6	0.010	5.109
GIST + HMAX + fc6	0.000	-0.196
SKEL + GBJ + GIST + HMAX	0.000	-0.032
SKEL + GBJ + GIST + fc6	0.010	5.027
SKEL + GBJ + HMAX + fc6	0.000	0.186
SKEL + GIST + HMAX + fc6	0.000	0.045
GBJ + GIST + HMAX + fc6	0.031	15.493
SKEL + GBJ + GIST + HMAX + fc6	0.008	3.809

Supplemental Table 2. Random-effects regression results for each model used in Experiment 2. The unstandardized coefficients and *t*-values are drawn from a full regression model that includes each of the visual models as predictors. The χ^2 and *p*-values are calculated by iteratively testing the full regression model against ones without the predictor of interest.

Model	Unstandardized Coefficients		Standardized Coefficients			
	B	Std. Error	β	*t*	χ^2	*p*
(Intercept)	0.90	0.04		22.51		
Skeleton	-0.02	0.00	-1.24	-4.80	22.30	< 0.001
Gabor-Jet	0.00	0.00	0.32	1.44	1.81	0.18
GIST	0.58	0.13	0.63	4.46	19.55	< 0.001
HMAX	0.00	0.00	-0.07	-0.50	0.19	0.66
AlexNet-fc6	0.00	0.00	0.06	0.21	0.05	0.83

<div style="text-align:center">References</div>

Amir, O., Biederman, I., & Hayworth, K. J. (2012). Sensitivity to nonaccidental properties across various shape dimensions. *Vision Research, 62*, 35-43. doi:https://doi.org/10.1016/j.visres.2012.03.020

Ayzenberg, V., Yousif, S., & Lourenco, S. (2016). The medial axis as a robust model of object representation. *Journal of Vision, 16*(12), 169-169.

Baker, N., & Kellman, P. J. (2018). Abstract shape representation in human visual perception. *Journal of Experimental Psychology: General, 147*(9), 1295-1308. doi:10.1037/xge0000409

Baker, N., Lu, H., Erlikhman, G., & Kellman, P. J. (2018). Deep convolutional networks do not classify based on global object shape. *PLOS Computational Biology, 14*(12), e1006613. doi:10.1371/journal.pcbi.1006613

Barenholtz, E., & Tarr, M. J. (2008). Visual judgment of similarity across shape transformations: Evidence for a compositional model of articulated objects. *Acta Psychologica, 128*(2), 331-338. doi:https://doi.org/10.1016/j.actpsy.2008.03.007

Biederman, I. (1987). Recognition-by-components: a theory of human image understanding. *Psychological Review, 94*(2), 115-147.

Biederman, I. (2000). Recognizing depth-rotated objects: A review of recent research and theory. *Spatial vision, 13*(2), 241-253.

Biederman, I., & Bar, M. (1999). One-shot viewpoint invariance in matching novel objects. *Vision Research, 39*(17), 2885-2899.

Biederman, I., & Gerhardstein, P. C. (1993). Recognizing depth-rotated objects: evidence and conditions for three-dimensional viewpoint invariance. *Journal of Experimental Psychology: Human Perception and Performance, 19*(6), 1162-1182.

Biederman, I., & Ju, G. (1988). Surface versus edge-based determinants of visual recognition. *Cognitive Psychology, 20*(1), 38-64. doi:https://doi.org/10.1016/0010-0285(88)90024-2

Blum, H. (1967). A transformation for extracting descriptors of shape. In W. Wathen-Dunn (Ed.), *Models for the Perception of Speech and Visual Form* (pp. 362-380). Cambridge, MA: MIT Press.

Blum, H. (1973). Biological shape and visual science (Part I). *Journal of Theoretical Biology, 38*(2), 205-287.

Bonner, M. F., & Epstein, R. A. (2018). Computational mechanisms underlying cortical responses to the affordance properties of visual scenes. *PLOS Computational Biology, 14*(4), e1006111. doi:10.1371/journal.pcbi.1006111

Davitt, L. I., Cristino, F., Wong, A. C. N., & Leek, E. C. (2014). Shape information mediating basic- and subordinate-level object recognition revealed by analyses of eye movements. *Journal of Experimental Psychology: Human Perception and Performance, 40*(2), 451-456. doi:10.1037/a0034983

Elder, J. H. (1999). Are Edges Incomplete? *International Journal of Computer Vision, 34*(2), 97-122. doi:10.1023/a:1008183703117

Elder, J. H. (2018). Shape from Contour: Computation and Representation. *Annual Review of Vision Science, 4*(1), 423-450. doi:10.1146/annurev-vision-091517-034110

Elder, J. H., Oleskiw, T. D., Yakubovich, A., & Peyré, G. (2013). On growth and formlets: Sparse multi-scale coding of planar shape. *Image and Vision Computing, 31*(1), 1-13. doi:https://doi.org/10.1016/j.imavis.2012.11.002

Elder, J. H., & Velisavljević, L. (2009). Cue dynamics underlying rapid detection of animals in natural scenes. *Journal of Vision, 9*(7), 1-20. doi:10.1167/9.7.7

Erdogan, G., & Jacobs, R. A. (2017). Visual shape perception as Bayesian inference of 3D object-centered shape representations. *Psychological Review, 124*(6), 740-761.

Feldman, J., & Singh, M. (2006). Bayesian estimation of the shape skeleton. *Proceedings of the National Academy of Sciences, 103*(47), 18014-18019.

Firestone, C., & Scholl, B. J. (2014). "Please tap the shape, anywhere you like" shape skeletons in human vision revealed by an exceedingly simple measure. *Psychological Science, 25*(2), 377-386.

Geirhos, R., Rubisch, P., Michaelis, C., Bethge, M., Wichmann, F. A., & Brendel, W. (2018). ImageNet-trained CNNs are biased towards texture; increasing shape bias improves accuracy and robustness. *arXiv preprint arXiv:1811.12231*.

Harrison, S. J., & Feldman, J. (2009). The influence of shape and skeletal axis structure on texture perception. *Journal of Vision, 9*(6), 1-21. doi:10.1167/9.6.13

Hartigan, J. A., & Wong, M. A. (1979). Algorithm AS 136: A K-Means Clustering Algorithm. *Journal of the Royal Statistical Society. Series C (Applied Statistics), 28*(1), 100-108. doi:10.2307/2346830

Hummel, J. E. (2000). Where view-based theories break down: The role of structure in shape perception and object recognition. In E. Dietrich & A. Markman (Eds.), *Cognitive dynamics: Conceptual change in humans and machines* (pp. 157-185). Hillsdale, NJ: Erlbaum.

Hummel, J. E. (2001). Complementary solutions to the binding problem in vision: Implications for shape perception and object recognition. *Visual Cognition, 8*(3-5), 489-517.

Hummel, J. E., & Stankiewicz, B. J. (1996). Categorical relations in shape perception. *Spatial vision, 10*(3), 201-236.

Hung, C.-C., Carlson, E. T., & Connor, C. E. (2012). Medial axis shape coding in macaque inferotemporal cortex. *Neuron, 74*(6), 1099-1113.

Jozwik, K. M., Kriegeskorte, N., Storrs, K. R., & Mur, M. (2017). Deep convolutional neural networks outperform feature-based but not categorical models in explaining object similarity judgments. *Frontiers in Psychology, 8*(1726), 1-18. doi:10.3389/fpsyg.2017.01726

Kanizsa, G. (1976). Subjective contours. *Scientific American, 234*(4), 48-52.

Kimia, B. B. (2003). On the role of medial geometry in human vision. *Journal of Physiology-Paris, 97*(2), 155-190.

Kovács, I., Fehér, Á., & Julesz, B. (1998). Medial-point description of shape: A representation for action coding and its psychophysical correlates. *Vision Research, 38*(15), 2323-2333.

Kovacs, I., & Julesz, B. (1994). Perceptual sensitivity maps within globally defined visual shapes. *Nature, 370*(6491), 644-646.

Krizhevsky, A., Sutskever, I., & Hinton, G. E. (2012). *Imagenet classification with deep convolutional neural networks.* Paper presented at the Advances in Neural Information Processing Systems.

Landau, B., Smith, L. B., & Jones, S. S. (1988). The importance of shape in early lexical learning. *Cognitive Development, 3*(3), 299-321.

Lescroart, M. D., & Biederman, I. (2013). Cortical representation of medial axis structure. *Cerebral Cortex, 23*(3), 629-637.

Lescroart, M. D., Stansbury, D. E., & Gallant, J. L. (2015). Fourier power, subjective distance, and object categories all provide plausible models of BOLD responses in scene-selective visual areas. *Frontiers in Computational Neuroscience, 9*(135), 1-20. doi:10.3389/fncom.2015.00135

Leyton, M. (1989). Inferring Causal History froms Shape. *Cognitive Science, 13*(3), 357-387. doi:doi:10.1207/s15516709cog1303_2

Liu, T.-L., & Geiger, D. (1999). *Approximate tree matching and shape similarity.* Paper presented at the the Proceedings of the Seventh IEEE International Conference on Computer Vision.

Logothetis, N. K., Pauls, J., Bülthoff, H. H., & Poggio, T. (1994). View-dependent object recognition by monkeys. *Current Biology, 4*(5), 401-414.

Long, B., Störmer, V. S., & Alvarez, G. A. (2017). Mid-level perceptual features contain early cues to animacy. *Journal of Vision, 17*(6), 1-20. doi:10.1167/17.6.20

Long, B., Yu, C.-P., & Konkle, T. (2018). Mid-level visual features underlie the high-level categorical organization of the ventral stream. *Proceedings of the National Academy of Sciences, 115*(38), E9015-E9024. doi:10.1073/pnas.1719616115

Lowet, A. S., Firestone, C., & Scholl, B. J. (2018). Seeing structure: Shape skeletons modulate perceived similarity. *Attention, Perception, & Psychophysics, 80*(5), 1278-1289. doi:10.3758/s13414-017-1457-8

Margalit, E., Biederman, I., Herald, S. B., Yue, X., & von der Malsburg, C. (2016). An applet for the Gabor similarity scaling of the differences between complex stimuli. *Attention, Perception, & Psychophysics, 78*(8), 2298-2306. doi:10.3758/s13414-016-1191-7

Marr, D., & Nishihara, H. K. (1978). Representation and recognition of the spatial organization of three-dimensional shapes. *Proceedings of the Royal Society of London B: Biological Sciences, 200*(1140), 269-294.

Mash, C., Arterberry, M. E., & Bornstein, M. H. (2007). Mechanisms of visual object tecognition in infancy: Five-month-olds generalize beyond the interpolation of familiar views. *Infancy, 12*(1), 31-43. doi:doi:10.1111/j.1532-7078.2007.tb00232.x

Oliva, A., & Torralba, A. (2001). Modeling the Shape of the Scene: A Holistic Representation of the Spatial Envelope. *International Journal of Computer Vision, 42*(3), 145-175. doi:10.1023/A:1011139631724

Oliva, A., & Torralba, A. (2006). Building the gist of a scene: The role of global image features in recognition. *Progress in brain research, 155*, 23-36.

Op de Beeck, H. P., Torfs, K., & Wagemans, J. (2008). Perceived Shape Similarity among Unfamiliar Objects and the Organization of the Human Object Vision Pathway. *The Journal of Neuroscience, 28*(40), 10111-10123. doi:10.1523/jneurosci.2511-08.2008

Psotka, J. (1978). Perceptual processes that may create stick figures and balance. *Journal of Experimental Psychology: Human Perception and Performance, 4*(1), 101-111.

Qiu, W., Hatori, Y., & Sakai, K. (2015). Neural construction of 3D medial axis from the binocular fusion of 2D MAs. *Neurocomputing, 149, Part B*, 546-558. doi:http://dx.doi.org/10.1016/j.neucom.2014.08.019

Russakovsky, O., Deng, J., Su, H., Krause, J., Satheesh, S., Ma, S., . . . Bernstein, M. (2015). Imagenet large scale visual recognition challenge. *International Journal of Computer Vision, 115*(3), 211-252.

Sanocki, T. (1993). Time course of object identification: Evidence for a global-to-local contingency. *Journal of Experimental Psychology: Human Perception and Performance, 19*(4), 878-898. doi:10.1037/0096-1523.19.4.878

Schrimpf, M., Kubilius, J., Hong, H., Majaj, N. J., Rajalingham, R., Issa, E. B., . . . DiCarlo, J. J. (2018). Brain-Score: Which Artificial Neural Network for Object Recognition is most Brain-Like? *bioRxiv*. doi:10.1101/407007

Sebastian, T. B., Klein, P. N., & Kimia, B. B. (2004). Recognition of shapes by editing their shock graphs. *IEEE Transactions on pattern Analysis and Machine Intelligence, 26*(5), 550-571.

Serre, T., Oliva, A., & Poggio, T. (2007). A feedforward architecture accounts for rapid categorization. *Proceedings of the National Academy of Sciences, 104*(15), 6424-6429. doi:10.1073/pnas.0700622104

Serre, T., Wolf, L., Bileschi, S., Riesenhuber, M., & Poggio, T. (2007). Robust object recognition with cortex-like mechanisms. *IEEE Transactions on Pattern Analysis & Machine Intelligence*(3), 411-426.

Shaked, D., & Bruckstein, A. M. (1998). Pruning medial axes. *Computer Vision and Image Understanding, 69*(2), 156-169. doi:http://dx.doi.org/10.1006/cviu.1997.0598

Shokoufandeh, A., Macrini, D., Dickinson, S., Siddiqi, K., & Zucker, S. W. (2005). Indexing hierarchical structures using graph spectra. *IEEE Transactions on pattern Analysis and Machine Intelligence, 27*(7), 1125-1140. doi:10.1109/TPAMI.2005.142

Spröte, P., & Fleming, R. W. (2016). Bent out of shape: The visual inference of non-rigid shape transformations applied to objects. *Vision Research, 126*, 330-346. doi:https://doi.org/10.1016/j.visres.2015.08.009

Spröte, P., Schmidt, F., & Fleming, R. W. (2016). Visual perception of shape altered by inferred causal history. *Scientific reports, 6*, 1-11. doi:http://dx.doi.org/10.1038/srep36245

Tang, H., Schrimpf, M., Lotter, W., Moerman, C., Paredes, A., Ortega Caro, J., . . . Kreiman, G. (2018). Recurrent computations for visual pattern completion. *Proceedings of the National Academy of Sciences, 115*(35), 8835-8840. doi:10.1073/pnas.1719397115

Trinh, N. H., & Kimia, B. B. (2007, 14-21 Oct. 2007). *A Symmetry-Based Generative Model for Shape.* Paper presented at the 2007 IEEE 11th International Conference on Computer Vision.

Trinh, N. H., & Kimia, B. B. (2011). Skeleton search: Category-specific object recognition and segmentation using a skeletal shape model. *International Journal of Computer Vision, 94*(2), 215-240.

Ullman, S., Assif, L., Fetaya, E., & Harari, D. (2016). Atoms of recognition in human and computer vision. *Proceedings of the National Academy of Sciences, 113*(10), 2744-2749.

Vogels, R., Biederman, I., Bar, M., & Lorincz, A. (2001). Inferior temporal neurons show greater sensitivity to nonaccidental than to metric shape differences. *Journal of Cognitive Neuroscience, 13*(4), 444-453.

Wagemans, J., De Winter, J., de Beeck, H. O., Ploeger, A., Beckers, T., & Vanroose, P. (2008). Identification of everyday objects on the basis of silhouette and outline versions. *Perception, 37*(2), 207-244.

Wieser, E., Seidl, M., & Zeppelzauer, M. (2017). A study on skeletonization of complex petroglyph shapes. *Multimedia Tools and Applications, 76*(6), 8285-8303. doi:10.1007/s11042-016-3395-1

Wilder, J., Feldman, J., & Singh, M. (2011). Superordinate shape classification using natural shape statistics. *Cognition, 119*(3), 325-340. doi:https://doi.org/10.1016/j.cognition.2011.01.009

Wood, J. N. (2013). Newborn chickens generate invariant object representations at the onset of visual object experience. *Proceedings of the National Academy of Sciences, 110*(34), 14000-14005.

Wu, J., Wang, Y., Xue, T., Sun, X., Freeman, B., & Tenenbaum, J. (2017). *Marrnet: 3d shape reconstruction via 2.5 d sketches.* Paper presented at the Advances in Neural Information Processing Systems.

Yamane, Y., Carlson, E. T., Bowman, K. C., Wang, Z., & Connor, C. E. (2008). A neural code for three-dimensional object shape in macaque inferotemporal cortex. *Nature Neuroscience, 11*, 1352-1360. doi:http://dx.doi.org/10.1038/nn.2202

Yamins, D. L., Hong, H., Cadieu, C. F., Solomon, E. A., Seibert, D., & DiCarlo, J. J. (2014). Performance-optimized hierarchical models predict neural responses in higher visual cortex. *Proceedings of the National Academy of Sciences, 111*(23), 8619-8624.

Yue, X., Biederman, I., Mangini, M. C., von der Malsburg, C., & Amir, O. (2012). Predicting the psychophysical similarity of faces and non-face complex shapes by image-based measures. *Vision Research, 55*, 41-46.

Zoccolan, D., Oertelt, N., DiCarlo, J. J., & Cox, D. D. (2009). A rodent model for the study of invariant visual object recognition. *Proceedings of the National Academy of Sciences, 106*(21), 8748-8753.