Attention Promotes the Neural Encoding of Prediction Errors

Cooper A. Smout*[1,2], Matthew F. Tang[1,2], Marta I. Garrido[1,2,3,4], and

Jason B. Mattingley[1,3,5,6]

[1]Queensland Brain Institute, University of Queensland, Brisbane, Australia

[2]Australian Research Council Centre of Excellence for Integrative Brain Function, Australia

[3]School of Mathematics and Physics, University of Queensland, Brisbane, Australia

[4]Centre for Advanced Imaging, University of Queensland, Brisbane, Australia

[5]School of Psychology, University of Queensland, Brisbane, Australia

[6]Canadian Institute for Advanced Research (CIFAR)

* cooper.smout@gmail.com

This research was supported by the Australian Research Council (ARC) Centre of Excellence for Integrative Brain Function (ARC Centre Grant CE140100007). J.B.M was supported by an ARC Australian Laureate Fellowship (FL110100103). M.I.G. was supported by a University of Queensland Fellowship (2016000071). The authors declare no competing financial interests.

Abstract

The human brain is thought to optimise the encoding of incoming sensory information through two principal mechanisms: *prediction* uses stored information to guide the interpretation of forthcoming sensory events, and *attention* prioritizes these events according to their behavioural relevance. Despite the ubiquitous contributions of attention and prediction to various aspects of perception and cognition, it remains unknown how they interact to modulate information processing in the brain. A recent extension of predictive coding theory suggests that attention optimises the expected precision of predictions by modulating the synaptic gain of prediction error units. Since prediction errors code for the *difference* between predictions and sensory signals, this model would suggest that attention increases the selectivity for *mismatch information* in the neural response to a surprising stimulus. Alternative predictive coding models proposes that attention increases the activity of prediction (or 'representation') neurons, and would therefore suggest that attention and prediction synergistically modulate selectivity for *feature information* in the brain. Here we applied multivariate forward encoding techniques to neural activity recorded via electroencephalography (EEG) as human observers performed a simple visual task, to test for the effect of attention on both mismatch and feature information in the neural response to surprising stimuli. Participants attended or ignored a periodic stream of gratings, the orientations of which could be either predictable, surprising, or unpredictable. We found that surprising stimuli evoked neural responses that were encoded according to the difference between predicted and observed stimulus features, and that attention facilitated the encoding of this type of information in the brain. These findings advance our understanding of how attention and prediction modulate information processing in the brain, and support the theory that attention optimises precision expectations during hierarchical inference by increasing the gain of prediction errors.

Introduction

Perception is believed to arise from a process of active inference [1], during which the brain

retrieves information from past experiences to build predictive models of likely future

occurrences and compares these predictions with incoming sensory evidence [2,3]. In support

of the idea that prediction increases the efficiency of neural encoding, previous studies have

demonstrated that predicted visual events typically evoke smaller neural responses than

surprising events (e.g. evoked activity measured in terms of changes in electrical potential or

blood oxygen level dependent (BOLD) response; for a review, see [4]). Interestingly, recent

studies have shown that selective attention can increase [5] or reverse [6] the suppressive effect

of prediction on neural activity, suggesting that attention and prediction facilitate perception

[7] via synergistic modulation of bottom-up sensory signals [8–11]. It remains unclear,

however, what *type of information* is modulated in the interaction between attention and

prediction. This question is important because different predictive coding models make distinct

predictions about how information is transmitted through the cortical hierarchy [3,8,12,13].

Here, we used multivariate forward encoding analyses to assess selectivity for two distinct

types of information in the neural response to surprising stimuli – *feature* and *mismatch*

information - and to test the effect of attention on these two informational codes.

A prominent version of predictive coding theory claims that top-down prediction signals

'cancel out' bottom-up sensory signals that match the predicted content, leaving only the

remaining prediction error to propagate forward and update a model of the sensory

environment [2,8,9]. Since error propagation is thought to be associated with superficial

pyramidal cells [9], and these cells are thought to be primarily responsible for generating EEG

signals [14,15], this theory predicts that surprising events will increase the selectivity of EEG

responses to the *difference* between predicted and observed stimulus features, i.e. mismatch

information. Furthermore, a recent extension of this theory suggests that selective attention

optimises the expected precision of predictions by modulating the synaptic gain (post-synaptic

responsiveness) of prediction error units [8] – that is, neurons coding for behaviourally relevant

prediction errors should be more responsive than those coding for irrelevant prediction errors.

On this account, attention should further increase selectivity for mismatch information in the

neural response to surprising stimuli relative to unsurprising stimuli. Here we call this account

the *mismatch information model*.

Alternative predictive coding models [12,13,16] propose that predictions – as opposed to

prediction errors – are propagated forward through the visual hierarchy, and it is these

prediction signals that are modulated by attention. For example, the model proposed by

Spratling [12] simulates the common physiological finding that attention to a stimulus

enhances the firing rate of neurons tuned to specific stimulus features (e.g., orientation or

colour for visual neurons), and has been shown to be mathematically equivalent to the biased

competition model of attention [17–20]. In line with these alternative models, we investigated

a second hypothesis – here termed the *feature information model* – which proposes that the

interaction between attention and prediction at the level of neural responses is driven by

changes in feature-specific information in the brain.

Here we tested whether the *feature information model* or the *mismatch information model*

provides a better account of the neural coding of surprising stimuli in the human brain, and

examined the influence of selective attention on each of these two neural codes. Participants

attended to, or ignored, periodic streams of visual gratings, the orientations of which were

either predictable, surprising, or unpredictable. We applied forward encoding models to whole-

brain neural activity measured using EEG to quantify the neural selectivity for information

related to the grating orientation and the mismatch between the predicted and observed grating

orientations. We show that surprising stimuli evoke neural responses that contain information

related to the difference between predicted and observed stimulus features, consistent with the *mismatch information model*. Crucially, we also find that attention increases the selectivity for mismatch information in the neural response to surprising stimuli, supporting the hypothesis that attention increases the gain of prediction errors [8].

Results

We recorded brain activity using EEG as human observers (N = 24) undertook a rare-target detection task (see *Methods*; *Fig 1*). Participants fixated centrally and were presented with a periodic stream of gratings (100 ms duration, 500 ms ISI, 415 gratings per block) in one of two conditions (randomised across blocks). In *roving standard* blocks [21] (see *Fig 1A*), grating orientation was repeated between 4 and 11 times (*standards*) before changing to a new orientation (*deviants*, pseudo-randomly selected from one of nine orientations, spanning 0 - 160° in 20° steps). Grating orientation was thus 'predictable' for standards and 'surprising' for deviants. In *equiprobable blocks* [22] (see *Fig 1B*), gratings changed orientation on every presentation and thus could not be predicted ('unpredictable' *controls*). Attention was manipulated by having participants either monitor the grating stimuli for rare targets with a different spatial frequency ('grating task', *attended*), or ignore the gratings and instead monitor for rare fixation-dot targets with decreased contrast ('dot task', gratings *ignored*).

Fig 1. Example stimuli in each of the two block types used in the study. (A) Roving oddball sequence. In this sequence, the orientation of gratings was repeated over short sequences of stimuli (*standards*), before changing to a different orientation (*deviant*). During the grating or dot task, participants responded to rare gratings with high spatial frequency (*grating target*) or to rare decreases in fixation-dot contrast (*dot target*), respectively. (B) Equiprobable sequence. In this sequence, the orientation of control gratings changed with each successive presentation.

Participants completed the grating task and dot task in separate sessions, approximately one week apart (session order counterbalanced). At the beginning of each session, participants completed three practice blocks of the specified task, during which target salience levels were titrated to approximate a target detection rate of 75% (see *Methods*). Participants were then fitted with a 64-electrode EEG cap before completing 21 test blocks. One participant detected fewer than 50% of targets in both tasks and was therefore excluded from all further analyses. The remaining participants detected an equivalent percentage of targets in the grating task (75.64 ± 1.76%, mean ± SEM) and dot task (72.73 ± 2.54%; $t(22) = 1.57$, $p = 0.13$, $BF_{10} = 0.12$), and also produced similar numbers of false alarms in each (20.43 ± 3.79 and 22.57 ± 5.47, respectively; $t(22) = -0.41$, $p = .684$, $BF_{10} = 0.18$), suggesting that difficulty was well matched between attention conditions.

EEG data were pre-processed offline using EEGlab [23] and epoched according to the onset of each grating (see *Methods* for details). Statistical analyses were conducted using cluster-based permutation tests in Fieldtrip [24]. *S1 Fig* shows the main effects and interactions for the factors of attention and prediction on event related potentials (ERPs). Briefly, ERPs were modulated by both attention (86 - 434 ms, cluster-corrected $p < .001$; *S1A and S1C Figs*) and prediction (39 - 550 ms, cluster-corrected $p < .001$, *S1A Fig*). Follow-up analyses of the simple effects of prediction revealed that deviants elicited larger responses than both standards (39 - 550 ms, cluster-corrected $p < .001$; *S1A and S1D Figs*) and controls (324 - 550 ms, cluster-corrected $p = .002$; *S1A and S1E Figs*). The difference between deviants and controls emerged later and was smaller than the difference between deviants and standards, consistent with the notion that the former comparison reflects the pure effects of prediction ("genuine" mismatch response (MMR), [22]), whereas the latter comparison confounds the effects of prediction with those of adaptation to the standard ('classic' MMR, see [4] for a review).

We also observed an interaction between attention and prediction (180 - 484 ms, cluster-corrected $p < .001$; *S1A Fig*). Follow-up analyses revealed that attention increased both the classic MMR (176 - 469 ms, cluster-corrected $p < .001$; *S1F and S1G Figs*) and the genuine MMR (176 - 550 ms, cluster-corrected $p < .001$; *S1H and S1I Figs*). In the attended condition, both the classic and the genuine MMRs emerged approximately 200 ms after stimulus onset over posterior-lateral (PO7, PO8) electrodes (*S1B Fig*, solid green and yellow lines, respectively). Whereas the onset of the genuine MMR is consistent with previous literature [22], the classic MMR we report here emerged slightly later than what has typically been reported previously (~150 ms; for a review see [4]). We note, however, that at least one previous study reported a visual MMR beginning as late as 250 ms [25], highlighting the variable nature of this component.

In the ignored condition, we observed classic and genuine MMRs (*S1B Fig,* dotted green and

yellow lines, respectively) with positive polarities over posterior (PO7, PO8) and frontal (Fz)

electrodes, respectively. In contrast, previous studies have typically (but not always; see [5])

reported mismatch *negativities*, even in the absence of attention [4]. A number of differences

between previous studies and our own could explain this discrepancy (e.g. stimuli,

interstimulus interval, presentation duration, task etc). In particular, we used large sinusoidal

gratings (11º of visual angle) to optimise orientation decoding, in contrast to previous studies

that presented much smaller oriented bars (~3-4º of visual angle, e.g. [22,26]). Thus, the stimuli

in the current study likely activated a larger area of visual cortex than those used in previous

studies, which produced a different dipole (or combination of multiple dipoles) and associated

projection to scalp electrodes (due to the complex folding structure of the cortex, [4]) than has

previously been observed. Indeed, close inspection of the ERPs seems to indicate the presence

of a single dipole projecting to frontal and posterior electrodes (note the highly similar pattern

of activity between electrodes Fz and Pz, but with opposite sign, *S1A Fig*), which has not

typically been observed in previous studies (e.g., note the relatively uniform responses across

the scalp in [22,27,28]).

Orientation information is enhanced with attention but not surprise

The *feature information model* predicts that the orientation-selective neural response to

surprising stimuli (deviants) will be different to that of control stimuli. To investigate this

hypothesis, we used a forward encoding model to estimate orientation selectivity from neural

activity measured with EEG (see *Methods* for details). Briefly, we used multivariate regression

to transform activity in electrode space into an orientation-selective 'feature space' [29–32],

comprised of nine hypothetical 'orientation channels' matching those presented in the

experiment (0 - 160º, in 20º steps). For each orientation channel, we modelled the expected

activation across trials by convolving the presented orientation with a canonical orientation-

selective tuning function. We then regressed this pattern of expected activity against the EEG

data, separately for each time point (-100 - 550 ms after stimulus onset), to produce a weight

matrix that converted multivariate activity in electrode space into activity in the specified

orientation channel. The spatial weights for each orientation channel were then inverted to

reconstruct the forward model and applied to an independent set of test trials (using a cross-

validation procedure) to estimate activity across all orientation channels. As shown in *Fig 2A*,

using the forward encoding approach we reconstructed distinct response profiles for each of

the nine grating orientations presented to participants. Orientation channels were then realigned

for each trial such that the presented orientation channel was centred on 0º, and activation

patterns were averaged across trials in each condition. The forward encoding model revealed

an orientation-tuned response throughout the epoch (*Fig 2B and 2C*). This response emerged

soon after stimulus onset, peaked at ~130 ms, and declined gradually until the end of the epoch.

Fig 2. Stimulus-evoked orientation channel response profiles. **(A)** Reconstructed orientation channels, corresponding to each of the nine grating orientations presented to participants (0 - 160°, in 20° steps). Coloured dots indicate the modelled orientation channel activity across trials in which the labelled orientation was presented. Curved lines show functions fitted to the grand average data for illustrative purposes. Note that each coloured line is approximately centred on the presented orientation. **(B)** Time-resolved orientation response profile, centred on the presented orientation in each trial and averaged across participants and conditions. Orientation response profiles emerged shortly after stimulus onset and lasted until the end of the epoch. **(C)** Orientation response profiles, averaged across all participants and conditions in each of three successive 100 ms time windows. Dots show activation in each of the nine modelled orientation channels (mean-centred). Curved lines show functions fitted to the grand average data for illustrative purposes. Orientation information (response profile amplitude) was strongest from 100 – 200 ms and decreased throughout the epoch. Data are available at https://doi.org/10.17605/osf.io/a3pfq. a.u. = arbitrary units.

To quantify the effects of attention and prediction on orientation response profiles, we fitted the condition-averaged orientation channel responses with an exponentiated cosine function [33,34] using least squares regression:

$$y(x) = Ae^{\kappa\,(cos\,2(x - \mu)\text{-}1)} + B$$

where y is the predicted orientation channel activity in response to a grating with orientation x;

A is the peak response amplitude, κ is the concentration (i.e. inverse dispersion; a larger value

corresponds to a "tighter" function), μ is the centre of the function, and B is the baseline offset

(see *Methods*).

Attention increased the amplitude of orientation response profiles (219 - 550 ms, cluster-

corrected $p < .001$; *Fig 3A and 3B*) but did not modulate the tuning concentration (all clusters

$p > .104$). There was a significant main effect of prediction on the amplitude of orientation

response profiles late in the epoch ($324 - 550$ ms, cluster-corrected $p < .001$; *S2C and S2D*

Figs), as well as a non-significant but trending cluster early in the epoch (94 - 145 ms, cluster-

corrected $p = .154$; *S2C Fig*, cluster not shown). Follow-up analyses revealed that orientation

response profiles evoked by standards (0.11 ± 0.01 a.u.) were smaller than those of both

deviants (0.25 ± 0.03 a.u.; $t(22) = -4.32$, $p < 0.001$, $BF_{10} = 1469.10$) and controls (0.22 ± 0.03

a.u.; $t(22) = -3.79$, $p < 0.001$, $BF_{10} = 156.16$; *S2C and S2D Figs*). Crucially, the amplitudes of

orientation response profiles evoked by deviants and controls were equivalent ($t(22) = 0.78$, p

$= 0.443$, $BF_{10} = 0.19$; *Fig 3A, S2C and S2D Figs*). Finally, there was no effect of prediction on

the concentration of orientation response profiles (all clusters $p > .403$), and no interaction

between attention and prediction on either the amplitude (cluster-corrected $p = .093$, *S2E and*

S2F Figs) or concentration (no clusters found) of orientation response profiles.

Fig 3. Effects of attention and prediction error on orientation and mismatch response profiles. **(A-C)** Orientation response profiles. (**A**) Orientation selectivity (response profile amplitude) for each condition over time. Shading indicates the SEM. Thin black lines indicate differences between deviants and controls, separately for attended and ignored stimuli. The dark grey bar along the x-axis indicates the main effect of attention (cluster-corrected). (**B**) Orientation response profiles, averaged across the significant effect of attention shown in **A** (219 - 550 ms). Dots show activation in each of the nine modelled mismatch channels. Curved lines show functions fitted to channel responses (fitted to grand average data for illustrative purposes). (**C**) Univariate sensitivity for stimulus orientation across all conditions (see *Methods*). Topography shows the permutation-corrected z-scores, averaged across the significant effect of attention shown in **A** (219 - 550 ms). Posterior electrodes were the most sensitive to orientation information. **(D-F)** Mismatch response profiles (observed minus predicted orientation). (**D**) Mismatch selectivity (response profile amplitude) for each condition over time. The grey, solid black, and dotted black bars along the x-axis indicate the main effect of attention, main effect of prediction, and the interaction, respectively (cluster-corrected). Attention enhanced the mismatch response profile in response to deviants but not controls. (**E**) Mismatch response profiles, collapsed across the significant interaction shown in **D** (332 – 480 ms). (**F**) Univariate sensitivity for mismatch response profiles evoked by attended deviants (see *Methods*), averaged across 332 – 480 ms. Posterior electrodes were the most sensitive to mismatch information. Note that **C** and **F** use different scales. Data are available at https://doi.org/10.17605/osf.io/a3pfq. a.u. = arbitrary units.

To determine the scalp topography that was most informative for orientation encoding, we calculated univariate sensitivity separately for each electrode across all trials, and averaged across time points in the significant main effect of attention (see *Methods*). As revealed in *Fig 3C*, posterior electrodes were the most sensitive to orientation information, as would be expected for a source in visual cortex.

Attention facilitates the neural encoding of mismatch information

The *mismatch information model* proposes that prediction errors are represented in populations of neurons tuned to the *difference* between predicted and observed stimulus features.

According to this model, therefore, surprising stimuli (deviants) should produce a more

mismatch-selective neural response than control stimuli. Furthermore, if attention enhances the

gain of prediction errors [8], we should expect an interaction between attention and prediction,

such that attention enhances the amplitude of mismatch response profiles evoked by deviants

more than that of controls, because deviants should evoke a larger prediction error [2]. To

investigate these hypotheses, we trained a separate forward encoding model, as described

above, on the angular difference between gratings (deviants or controls) and the preceding

stimuli. That is, deviants were coded according to the difference between the deviant

orientation and the preceding standard orientation, and controls were coded according to the

difference between successive control orientations. For example, if a horizontally oriented

deviant (0°) was preceded by a standard that was oriented at 40° (clockwise of horizontal), it

would be coded as a mismatch of -40° (0 - 40°).

As shown in *Fig 3D and 3E*, we were able to reconstruct mismatch response profiles for

attended deviants. By contrast, mismatch response profiles were clearly weaker in response to

controls and ignored deviants. There was a significant main effect of attention on the amplitude

of mismatch response profiles (attended > ignored, 188 – 550 ms, cluster-corrected p = .002;

Fig 3D, grey bar along x-axis). There was also a significant main effect of prediction (deviant

> control, 113 – 550 ms, cluster-corrected p < .001; *Fig 3D*, solid black bar along x-axis),

suggesting that prediction error is encoded according to the mismatch between predicted and

observed features. Crucially, attention and prediction interacted to influence the amplitude of

mismatch response profiles (332 – 480 ms, cluster-corrected p = .031; *Fig 3D*, dotted black bar

along x-axis). As can be seen in *Fig 3D and 3E*, attention enhanced the amplitude of deviant

mismatch response profiles but had little effect on those evoked by controls, supporting the

hypothesis that attention boosts prediction errors [8].

The concentration of mismatch response profiles was not modulated by attention (all clusters

$p > .888$) or the interaction between attention and prediction (all clusters $p > .615$), although

we did find a significant main effect of prediction on the concentration of mismatch response

profile fits (controls > deviants, 344 - 422 ms, cluster-corrected $p < .001$). Since controls

seemed to produce negligible mismatch response profiles during this time period (yellow lines,

Fig 3D), however, we followed up this result by averaging mismatch response amplitudes

across the significant timepoints and comparing these values to zero with a *t*-test and Bayes

Factor analysis (uniform prior, lower bound: 0, upper bound = 0.3). We found that control

mismatch response profile amplitudes (.005 ± .023 a.u.) were equivalent to zero ($t(22) = 0.19$,

$p = .848$, $BF_{10} = 0.11$), suggesting that the observed effect on concentration was more likely

an artefact of the fitting procedure than a true effect of prediction on mismatch response

profiles.

We calculated the sensitivity of each electrode to mismatch information in trials that contained

attended deviants, and collapsed across the significant interaction between 332 and 480 ms. As

revealed in *Fig 3F*, posterior electrodes were again the most informative, but the topography

of mismatch sensitivity was weaker and more sparsely distributed than that of orientation

decoding (*Fig 3C*).

Mismatch information increases with the strength of predictions

Next, we investigated whether the number of preceding standards was related to the amplitude

of prediction error response profiles. Repeated presentations of the standard are thought to

increase the strength of the memory trace, resulting in larger prediction errors to a subsequent

surprising stimulus [35]. Mismatch response profiles evoked by attended deviants were

grouped according to the number of preceding standards (4-7 repetitions vs 8-11 repetitions)

and fitted with exponentiated cosine functions (see *Methods*). As can be seen in *Fig 4A and*

4B, increasing the number of standard repetitions also increased the amplitude of mismatch

response profiles (387 - 520 ms, cluster-corrected *p* = .050). This finding is consistent with the

notion that successive standards allow a more precise prediction to be generated, which results

in enhanced prediction errors when violated. Finally, there was no effect of the number of

standard repetitions on the concentration of mismatch response profiles (cluster-corrected *p* =

.314).

Fig 4. Mismatch response profiles (putative prediction error) evoked by attended deviants. (**A**) Effect
of standard repetition on mismatch selectivity (response profile amplitude). Mismatch response
profiles evoked by attended deviants were larger following long standard sequences (8 - 11
repetitions) than short standard sequences (4 - 7 repetitions). The black bar along the x-axis denotes
significant differences (cluster-corrected). (**B**) Mismatch response profiles, collapsed across
significant time points in **A** (387 - 520 ms). Dots show activation in each of the nine modelled
mismatch channels. Curved lines show functions fitted to channel responses (fitted to grand average
data for illustrative purposes). (**C**) Effect of deviation angle on mismatch selectivity. Mismatch
response profile amplitude increased with the magnitude of deviation (±80° > ±20°). (**D**) Mismatch
response profiles for each deviation angle, collapsed across the earlier cluster shown in **C** (215 - 410
ms). Curved lines show functions fitted with a variable centre (fitted to grand average data for
illustrative purposes). Data are available at https://doi.org/10.17605/osf.io/a3pfq. a.u. = arbitrary units.

Mismatch information increases with the magnitude of violation

We also tested whether larger deviations from the prediction increased selectivity for mismatch

information. Mismatch response profiles of attended deviants were grouped according to the

angular difference between the deviant and preceding standard (i.e., the original mismatch

values entered into the encoding model) and fitted with exponentiated cosine functions

(variable centre, see *Methods*). There was a significant main effect of deviation magnitude on

mismatch response profile amplitude (215 - 410 ms, cluster-corrected *p* = .004). As shown in

Fig 4C, the amplitude of mismatch response profiles increased with the absolute deviation

angle (±80° > ±60° > ±40° > ±20°), supporting the notion that larger angular deviations (from

the predicted orientation) produce more prediction error. A second cluster emerged later in the

epoch (465 - 550 ms, cluster-corrected *p* = .031), which followed a similar pattern but with the

amplitude of the ±40° and ±60° responses reversed. Intriguingly, individual mismatch response

profiles were typically centred on the orthogonal deviation angle (90°, *Fig 4D*). This pattern of

results differs from the individual orientation response profiles (*Fig 2A*), which were

(approximately) centred on the presented orientation.

Attention produces temporally stable mismatch response profiles

In a final step, we investigated whether the spatial maps that produce mismatch response

profiles are stable or evolve dynamically over time. We used the same forward encoding

analysis as above, with the exception that the trained weights at each time point were tested on

all time points in the epoch [30,36] (see *Methods*). This produced a *train time* x *test time*

generalisation matrix of mismatch channel responses, to which we fitted exponentiated cosine

functions. *Fig 5* shows the mismatch selectivity (response profile amplitude) for attended and

ignored deviants, generalised across time. As revealed in *Fig 5A*, the mismatch response profile

evoked by attended deviants generalised across the latter part of the epoch (black outline

surrounding large red patch in upper right quadrant between ~200 - 550 ms, cluster-corrected

p = .010), indicating that the spatial map associated with mismatch information was relatively

consistent throughout this period. Note also that this pattern of generalisation was asymmetrical

(triangular-shaped, rather than square-shaped). Specifically, the spatial map trained at ~450 ms

generalised to the (test) time point at ~250 ms, but training at ~250 ms did not generalise to

testing at ~450 ms. Since asymmetrical generalisation can indicate differences in signal-to-

noise ratios between time points [36], this finding suggests that the strength of prediction error

signals may have increased toward the end of the epoch. It is also worth noting that the apparent

generalisation of spatial maps trained at stimulus onset ($t_{train} = 0$) to later times in the epoch

(~200 – 550 ms, red patch along the x-axis) was not significantly different from zero (no

clusters found in this region) and produced high residuals in the function fits (see *S3 Fig*),

suggesting that this pattern represents noise. Finally, the mismatch response profile evoked by

ignored stimuli (*Fig 5B*) did not generalise across time points (all clusters $p > .935$) and was

significantly smaller than that of attended stimuli (significant difference denoted by the opaque

patch in *Fig 5C*; $p = .026$).

Fig 5. Generalised mismatch response profiles in response to (**A**) attended deviants and (**B**) ignored
deviants. The dashed diagonal line indicates on-axis encoding (equivalent to the time-series plot in
Fig 4A). The black outline shows mismatch response profiles significantly larger than zero (cluster-
corrected). (**C**) Difference map (attended minus ignored), thresholded to show the significant effect of
attention on mismatch response profiles (cluster-corrected). Data are available at
https://doi.org/10.17605/osf.io/a3pfq. a.u. = arbitrary units.

Discussion

Here we set out to determine what type of information is modulated in the interaction between

attention and prediction [8]. To achieve this, we used forward encoding models of EEG data

to quantify the selectivity for orientation and mismatch information in the neural responses to

surprising and unpredictable stimuli in the well-established roving oddball paradigm [21,37].

Relative to unpredictable stimuli (controls), we found that EEG responses to surprising stimuli

(deviants) were equally selective for orientation information, but more selective for

information related to the *difference* between predicted and observed stimulus features. These

results are consistent with the *mismatch information model*, and support the idea that top-down

prediction signals 'cancel out' matching bottom-up sensory signals and leave only the

remaining prediction error to propagate forward [2,3,8,9]. Crucially, we also found that

attention increased the selectivity for mismatch information in neural responses to surprising

but not control stimuli. This finding demonstrates that attention boosts mismatch information

evoked by surprising stimuli (putative prediction errors), and is consistent with a recent version

of predictive coding theory that proposes attention optimises the expected precision of

predictions by increasing the gain of prediction errors [8].

We found no difference between orientation response profiles evoked by surprising and

unpredictable stimuli (a prediction of the *feature information model*), suggesting that the

increase in EEG activity that is typically observed with surprise is not coded according to

stimulus features. This finding contradicts predictive coding models in which predictions (or

'representations') of stimulus features are passed up the visual hierarchy [12,16,17]. Because

feedforward connections largely originate primarily from superficial pyramidal cells and it is

this activity that is measured with EEG [9,14,15], these models would predict that surprise

changes the feature-selectivity of EEG responses: a finding we do not observe here. This

finding might also seem to contradict a recent study that demonstrated greater selectivity for

orientation information in early visual cortex BOLD activity following presentation of a

predicted grating, relative to a surprising grating [38]. Since BOLD activity indirectly measures

the activity patterns of heterogenous populations of neurons, however, this change in feature-

selectivity could have reflected a change in either of the two neuronal populations proposed to

underlie predictive coding - *predictions* or *prediction errors*. The latter interpretation is

inconsistent with the results of the present study, which suggests that prediction errors are

encoded according to the mismatch between predicted and observed stimulus features, and not

the features themselves. The former interpretation (i.e. that predictions are coded according to

the stimulus features) fits well with a recent study that showed prediction induces feature-

specific templates immediately prior to stimulus onset [31]. Thus, a parsimonious account of

the literature to date suggests that *predictions* and *prediction errors* are represented in the brain

via distinct neural codes: whereas predictions are represented according to stimulus features,

prediction errors are represented according to the *mismatch* between predicted and observed

stimulus features.

In a recent study by our group [39], we observed a decrease in orientation selectivity in the

neural response to predicted stimuli, relative to surprising stimuli, shortly after stimulus onset

(79 – 185 ms). Here we observed a similar (but non-significant) trend in the same direction

(standards < deviants) at approximately the same time (94 - 145 ms, *S2C Fig*, cluster not

shown). Close inspection of the present results, however, suggests that some orientation

information evoked by the previous standard was still present in the brain at the onset of the

subsequent standard (indicated by the above-zero amplitude of the orientation response to

standards at stimulus onset, t = 0 ms, *S2C Fig*), which may have obscured detection of the early

effect reported in Tang et al. [39]. Interestingly, the present results revealed a late effect of

prediction (standards < deviants, 324 -550 ms, *S2C and S2D Figs*) that was not observed in our

previous work [39]. Since a critical difference between the two studies was the number of times

identical stimuli could be presented consecutively (no more than twice in the previous study),

we speculate that the late effect observed here might reflect the minimal amount of model-

updating required after the presentation of a precisely predicted stimulus.

We also found that attention increased the amplitude of orientation response profiles (*Fig 3A*

and 3B), consistent with previous studies that applied forward encoding models to human fMRI

[34,40] and time-frequency-resolved EEG data [29]. The present study replicates and extends

these studies with the application of forward encoding models to time-resolved EEG recordings

(resulting in <30 ms temporal resolution after smoothing), demonstrating that attention

increases feature selectivity in the human brain from approximately 200 ms after stimulus

onset.

Crucially, we also tested the interactive effects of attention and prediction on information

processing in the brain. There was a large and significant effect of attention on mismatch

response profiles in response to surprising but not unpredictable stimuli (beginning around 150

ms after stimulus onset and reaching significance from ~350 ms). This finding demonstrates

that attention boosts prediction errors evoked by surprising stimuli, and is consistent with a

recent iteration of predictive coding theory according to which attention optimises the expected

precision of prediction errors [8]. Previous studies have found evidence for an interaction

between attention and prediction in both the auditory [5] and visual [6,41] modalities.

Importantly, these studies used *activation-based* analyses to compare differences between

predicted and unpredicted stimuli at the level of overall neural activity, but did not investigate

what *type of information* is modulated in the interaction between attention and prediction. In

contrast, the present study used *information-based* analyses [42] to identify specific patterns of

neural activity that are associated with orientation-mismatch information in the brain, and

showed that selectivity for this type of information (but not feature information) is increased

with attention. Thus, the present study provides clear support for the hypothesis that attention

boosts the gain of prediction errors [8]. It will be important for future research to investigate

whether the interactive effects of attention and prediction on mismatch information is

contingent on the type of attention (e.g., feature-based versus spatial attention) or prediction

(e.g., rule-based versus multimodal cue-stimulus predictions; [31,43]).

Interestingly, we found that the magnitude of mismatch response profiles correlated with the

number of preceding standards (*Fig 4A and 4B*). Previous work in the auditory domain

demonstrated that successive repetitions of the standard evoke progressively increased

responses to a subsequent attended deviant [35]. Here we find a corollary for this effect in the

visual domain and demonstrate that the neural activity modulated by the number of preceding

standards is likely encoded as mismatch information. This finding is also consistent with the

notion that repeating the standard allows a more precise prediction to be generated, which

results in a larger prediction error to a subsequent surprising stimulus [44].

We also found that mismatch response profiles increased with the magnitude of the mismatch

between predicted and observed stimulus features (*Fig 4C*). Previous work in the auditory

domain has demonstrated a correlation between deviation magnitude and the amplitude of the

neural response to deviants (i.e. the mismatch negativity) [45]. Here we demonstrate a

relationship between deviation magnitude and selectivity for mismatch information (as

opposed to activation levels) in the visual domain, suggesting that the magnitude of mismatch

information might be used by the brain to guide updating of the predictive model. Since the

present study investigated mismatch signals with respect to a continuous and circular feature

dimension (i.e. orientation), it will be important for future research to extend the current line

of research to non-circular (e.g. luminance, auditory frequency) and categorical (e.g. facial

emotions) feature dimensions.

Somewhat surprisingly, there was a lateral shift in the response profile of individual mismatch

channels toward the orthogonal (90°) channel (*Fig 4D*). The extent of this effect depended on

the deviation magnitude, with large deviations (±40-80°) being predominantly stacked over the

90° channel and smaller deviations (±20°) being more closely aligned with their veridical

mismatch angle (*Fig 4D*). We speculate that this might indicate a qualitative difference in the

way that small and large prediction errors were treated by the brain in the present study. Small

deviations may have resulted in updating and retention of the current model (via a near-

veridical mismatch signal), whereas large deviations may have resulted in the wholesale

rejection of the current model (via a generic mismatch signal) in favour of an alternative model

that represents the deviant stimulus. In the latter case, the magnitude of the (orthogonal)

mismatch channel response might represent an efficient code that the brain utilises to select

from a number of likely alternative models.

Intriguingly, a number of recent studies failed to find an interaction between the effects of

attention and prediction on stimulus information in the brain [31,38,46]. If predictions are

encoded according to stimulus features, as we argue above, these null findings contradict the

theory that attention boosts predictions [47]. In contrast, we show that *prediction errors*,

represented according to the *mismatch* between predicted and observed stimulus features, are

enhanced with attention. Although the present study cannot speak to the activity of single

neurons, we note that the emerging picture is consistent with the notion that predictions and

prediction errors are represented in distinct populations of neurons [2] that encode two distinct

types of information and are differentially influenced by attention. Under this framework,

feature information encoded by prediction units would be immune to attention, whereas

mismatch information encoded by *prediction error* units would be enhanced by attention.

Future research could test these hypotheses at the single-cell level, for example by using single-

unit electrode recordings or 2-photon calcium imaging to assess whether different neurons

within a given cortical area satisfy these constraints.

Methods

Ethics Statement

The study was approved by The University of Queensland Human Research Ethics Committee (approval number: 2015001576) and was conducted in accordance with the Declaration of Helsinki. Participants provided informed written consent prior to commencement of the study.

Participants

Twenty-four healthy participants (11 female, 13 male, mean = 23.25 years, SD = 9.01 years, range: 18 to 64 years) with normal or corrected-to-normal vision were recruited via an online research participation scheme at The University of Queensland.

Stimuli

Stimuli were presented on a 61 cm LED monitor (Asus, VG248QE) with a 1920 x 1080 pixel resolution and refresh rate of 120 Hz, using the PsychToolbox presentation software [48] for Matlab (v.15b) running under Windows 7 with a NVidia Quadro K4000 graphics card. Participants were seated in a comfortable armchair in an electrically shielded laboratory, with the head supported by a chin rest at a viewing distance of 57 cm.

During each block, 415 gratings with Gaussian edges (outer diameter: 11º, inner mask diameter: 0.83º, spatial frequency: 2.73 c/º, 100% contrast) were presented centrally for 100 ms with a 500 ms ISI. Grating orientations were evenly spaced between 0º (horizontal) and 160º (in 20º steps). Eighteen (18) gratings in each block (2 per orientation) were presented with a higher spatial frequency (range: 2.73 - 4.55 c/º, as per staircase procedure, below), with a gap of at least 1.5 s between any two such gratings. We used a modified de Bruijn sequence to balance the order of grating orientations across conditions, sessions, and participants. Specifically, we generated two 9-character (orientation) sequences without successive

repetitions (e.g. ABCA, not ABCC) - one with a 3-character sub-sequence (504 characters

long) and another with a 2-character sub-sequence (72 characters long) - and appended two

copies of the former sequence to three copies of the latter sequence (1224 characters in total).

This master sequence was used to allocate the order of both deviants and controls in each

session (using different, random start-points), and ensured that each orientation was preceded

by equal numbers of all other orientations (up to 2+ preceding stimuli) so that decoding of any

specific orientation could not be biased by the orientation of preceding stimuli.

In roving oddball sequences, the number of Gabor repetitions (i.e., standards) was balanced

across orientations within each session, such that each orientation repeated between 4 and 11

times according to the following distribution: (31, 31, 31, 23, 5, 5, 5, 5), respectively. During

each block, the fixation dot (diameter: 0.3º, 100% contrast) decreased in contrast 18 times

(contrast range: 53-98% as per staircase procedure, below) for 0.5 s (0.25 s linear ramp on and

off). Contrast decrement onsets were randomised separately for each block, with a gap of at

least 1.5 s between any two decrement onsets.

Procedure

Participants attended two testing sessions of 60 minutes duration, approximately one week

apart, and completed one of two tasks in each session (*Fig 1*, session order counterbalanced

across participants). For the grating task, participants were informed that approximately 1/20

of the gratings would be a target grating with a higher spatial frequency than non-targets, and

were asked to press a mouse button as quickly as possible when they detected a target grating;

all other gratings were to be ignored. For the dot task, participants were informed that the

fixation dot would occasionally decrease in contrast, and were asked to press a mouse button

as quickly as possible when they detected such a change. Participants initially completed three

practice blocks (3.5 min per block) with auditory feedback (high or low tones) indicating

missed targets and the accuracy of their responses. During practice blocks in the first testing

session, target salience (spatial frequency or dot contrast change, depending on the task) was

adjusted dynamically using a Quest staircase procedure [49] to approximate 75% target

detection. During practice blocks in the second testing session, target salience was adjusted to

approximate the same level of target detection observed in the first testing session. Participants

were requested to minimise their number of false alarms. After the practice blocks, participants

were fitted with an EEG cap (see *EEG Data Acquisition*) before completing a total of 21 test

blocks (3 equiprobable, 18 roving standard, block order randomised) without auditory

feedback. After each block participants were shown the percentage of targets correctly

detected, the speed of these responses, and how many non-targets were responded to (false

alarms).

Behavioural Data Analysis

Participant responses were scored as hits if they occurred within one second of the onset of a

target grating in the grating task, or within one second of the peak contrast decrement in the

dot task. Target detection was then expressed as a percentage of the total number of targets

presented in each testing session. One participant detected less than 50% of targets in both

sessions and was removed from further analysis. Target detections and false alarms across the

two sessions were compared with paired-samples *t*-tests and Bayes Factors. Bayes factors

allow for quantification of evidence in favour of either the null or alternative hypothesis, with

$B_{01} > 3$ indicating substantial support for the alternative hypothesis and $B_{01} < 0.33$ indicating

substantial support for the null hypothesis [50]. Bayes factors were computed using the Dienes

[50,51] calculator in Matlab, with uniform priors for target detection (lower bound: -25%,

upper bound: 25%) and false alarms (lower bound: -50, upper bound: 50).

EEG Data Acquisition

Participants were fitted with a 64 Ag-AgCl electrode EEG system (BioSemi Active Two: Amsterdam, Netherlands). Continuous data were recorded using BioSemi ActiView software (http://www.biosemi.com), and were digitized at a sample rate of 1024 Hz with 24-bit A/D conversion and a .01 – 208 Hz amplifier band pass. All scalp electrode offsets were adjusted to below 20μV prior to beginning the recording. Pairs of flat Ag-AgCl electro-oculographic electrodes were placed on the outside of both eyes, and above and below the left eye, to record horizontal and vertical eye movements, respectively.

EEG Data Preprocessing

EEG recordings were processed offline using the EEGlab toolbox in Matlab [23]. Data were resampled to 256 Hz and high-pass filtered with a passband edge at 0.5 Hz (1691-point Hamming window, cut-off frequency: 0.25 Hz, -6 db). Raw data were inspected for the presence of faulty scalp electrodes (2 electrodes, across 2 sessions), which were interpolated using the average of the neighbouring activations (neighbours defined according to the EEGlab Biosemi 64 template). Data were re-referenced to the average of all scalp electrodes, and line noise at 50 and 100 Hz was removed using the Cleanline plugin for EEGlab (https://www.nitrc.org/projects/cleanline). Continuous data were visually inspected and periods of noise (e.g., muscle activity) were removed (1.4% of data removed in this way, across sessions).

For artefact identification, the cleaned data were segmented into 500 ms epochs surrounding grating onsets (100 ms pre- and 400 ms post-stimulus). Improbable epochs were removed using a probability test (6SD for individual electrode channels, 2SD for all electrode channels, 6.5% of trials across sessions), and the remaining data were subjected to independent components analyses (ICA) with a reduced rank in cases of a missing EOG electrode (2 sessions) or an

interpolated scalp electrode (2 sessions). Components representing blinks, saccades, and

muscle artefacts were identified using the SASICA plugin for EEGlab [52].

For further analysis, the cleaned data (i.e., prior to the ICA analysis) were segmented into 800

ms epochs surrounding grating onsets (150 ms pre- and 650 ms post-stimulus). Independent

component weights from the artefact identification process were applied to this new data set,

and previously identified artefactual components were removed. Baseline activity in the 100

ms prior to each stimulus was removed from each epoch. Grating epochs were then separated

into their respective attention and prediction conditions. Epochs in the grating task were

labelled as 'Attended' and epochs in the dot task were labelled as 'Ignored'. Epochs in the

roving oddball sequence were labelled as 'Deviants' when they contained the first stimulus in

a repeated train of gratings, and 'Standards' when they contained a grating that had been

repeated between five and seven times. Epochs in the equiprobable sequence were labelled as

'Controls'.

Event-Related Potential Analyses

Trials in each attention and prediction condition were averaged within participants to produce

event-related potentials (ERPs) for each individual. The effect of attention was assessed using

a two-tailed cluster-based permutation test across participant ERPs (Monte-Carlo distribution

with 5000 permutations, $p_{cluster}$<0.05; sample statistic: dependent samples t-statistic,

aggregated using the maximum sum of significant adjacent samples, p_{sample}<.05). Because there

were three, rather than two, levels of prediction, we tested the effect of prediction with a cluster-

based permutation test that used f-statistics at the sample level and a one-sided distribution to

account for the positive range of f-statistics (Monte-Carlo distribution with 5000 permutations,

$p_{cluster}$<0.05; sample statistic: dependent samples f-statistic, aggregated using the maximum

sum of significant adjacent samples, p_{sample}<.05). Simple contrasts between prediction

conditions (deviants vs standards, and deviants vs controls) were tested using two-tailed

cluster-based permutation tests (with the same settings as used to investigate attention). The

interaction between attention and prediction was assessed by subtracting the ignored ERP from

the attended ERP within each prediction condition and subjecting the resulting difference

waves to a one-tailed cluster-based permutation test across participant ERPs (Monte-Carlo

distribution with 5000 permutations, $p_{cluster}<0.05$; sample statistic: dependent samples f-

statistic, aggregated using the maximum sum of significant adjacent samples, $p_{sample}<.05$). The

interaction effect was followed-up by comparing difference waves (attended - ignored)

between deviants and standards, and between deviants and controls (two-tailed cluster-based

permutation tests, same settings as above).

Forward Encoding Models

To investigate the informational content of orientation signals, we used a forward encoding

model [29,53] designed to control for noise covariance in highly correlated data [31,54;

https://github.com/Pim-Mostert/decoding-toolbox], such as EEG. We modelled an idealised

basis set of the nine orientations of interest (0-160° in 20° steps) with nine half-wave rectified

cosine functions raised to the 8^{th} power, such that the response profile associated with any

particular orientation in the 180° space could be equally expressed as a weighted sum of the

nine modelled orientation channels [29]. We created a matrix of nine regressors that

represented the grating orientation presented on each trial in the training set (1 = the presented

orientation, 0 = otherwise) and convolved this regressor matrix with the basis set to produce a

design matrix, C (9 orientation channels x n trials). The EEG data could thus be described by

the linear model:

$$B = WC + N,$$

where $\boldsymbol{B}$ represents the data (64 electrodes x n trials), $\boldsymbol{W}$ represents a spatial weight matrix that

converts activity in channel space to activity in electrode space (64 electrodes x 9 orientation

channels) and $\boldsymbol{N}$ represents the residuals (i.e., noise).

To train and test the forward encoding model, we used a three-fold cross-validation procedure

that was iterated 100 times to increase reliability of the results. Within each cross-validation

iteration, the experimental blocks were folded into thirds: one third of trials served as the test

set and the remaining two-thirds served as the training set, and folds were looped through until

each fold had served as a test set. Across successive iterations of the cross-validation procedure,

the number of trials in each condition was balanced within folds by random selection (on the

first iteration) or by selecting the trials that had been utilised the least across previous folds

(subsequent iterations).

Prior to estimating the forward encoding model, each electrode in the training data was de-

meaned across trials, and each time point was averaged across a 27.3 ms window centred on

the time point of interest (corresponding to an *a priori* window of 30 ms, rounded down to an

odd number of samples to prevent asymmetric centring). Separately for each time point and

orientation channel of interest, i, we solved the linear equation using least square regression:

$$\mathbf{w}_i = \mathbf{B}_{train}\, \mathbf{c}_{train,i}^{\mathrm{T}}\, (\mathbf{c}_{train,i}\, \mathbf{c}_{train,i}^{\mathrm{T}})^{-1},$$

646
647   where $\mathbf{w}_i$ represents the spatial weights for channel i, $\mathbf{B}_{train}$ represents the training data (64

648   electrodes x n_{train} trials), and $\mathbf{c}_{train,i}$ represents the hypothetical response of channel i across the

649   training trials (1 x n_{train} trials). Following Mostert et al. [54], we then derived the optimal spatial

650   filter $\mathbf{v}_i$ to recover the activity of the ith orientation channel:

$$\mathbf{v}_i = \frac{\tilde{\Sigma}_i^{-1}\, \mathbf{w}_i}{\mathbf{w}_i^{\mathrm{T}}\, \tilde{\Sigma}_i^{-1}\, \mathbf{w}_i},$$

652   where Σ_i is the regularized covariance matrix for channel i, estimated as follows:

653
$$\widetilde{\Sigma}_i = \frac{1}{n_{train} - 1} \, \varepsilon_i \, \varepsilon_i^{\mathrm{T}}$$

654
$$\varepsilon_i = \mathbf{B}_{train} - \mathbf{w}_i \mathbf{c}_{train,i},$$

655   where n_{train} is the number of training trials. The covariance matrix $\widetilde{\Sigma}_i$ was regularized by using

656   the analytically determined shrinkage parameter [31]. Combining the spatial filters across each

657   of the nine orientation channels produced a channel filter matrix $\mathbf{V}$ (64 electrodes x 9 channels).

658
$$\mathbf{C}_{test} = \mathbf{V}^{\mathrm{T}} \, \mathbf{B}_{test} \,,$$

where $\mathbf{B}_{test}$ represents the test data at the time point of interest (64 electrodes x n_{test} trials),

averaged over a 27.3 ms window (as per the training data). Finally, the orientation channel

responses for each trial were circularly shifted to centre the presented orientation on $0°$, and the

zero-centred responses were averaged across trials within each condition to produce the

condition-average orientation channel response (*Fig 3B*).

To assess information related to the mismatch between predicted and observed stimulus

features (*Fig 3D and 3E*), we computed a second forward encoding model as above, with the

exception that now the regression matrix represented the difference between the current grating

orientation (deviant or control) and the previous grating orientation (standard or control,

respectively). That is, a grating at $60°$ orientation that followed a grating at $20°$ orientation

would be coded as $40°$ (current minus previous orientation).

To assess the dynamic nature of mismatch response profiles (*Fig 5*), we trained the weight

matrix, W, at a single time point in the training set, B_1 (using a 30 ms sliding window), and

then applied the weights to *every third* time point in the test set, B_2 (using a 30 ms sliding

window). This process was repeated for every third time point in the training set, resulting in a

3-dimensional matrix that contained the population response profile at each cross-generalised

time point (9 orientations x 66 training time points x 66 testing time points).

Quantifying Channel Responses

Previous studies have utilised a number of different methods to quantify the selectivity of

neural response profiles [30,31]. Since we were interested in characterising the properties of

neural response profiles, we opted to fit an exponentiated cosine function to the modelled data

[33,34] using least square regression:

681
$$y(x) = Ae^{\kappa(\cos 2(x-\mu).1)} + B$$

where *y* is the predicted orientation channel activity in response to a grating with orientation *x;*

A is the peak response amplitude*, κ* is the concentration parameter, *μ* is the centre of the

distribution, and *B* is the baseline offset. Fitting was performed using the non-linear least square

method in MATLAB (trust region reflective algorithm). The free parameters *A*, *κ*, and *B* were

constrained to the ranges (-0.5, 2), (1.5, 200), and (-1.0, 0.5), respectively, and initiated with

the values 0.5, 2, and 0, respectively. The free parameter *μ* was constrained to be zero when

quantifying mean-centred orientation or mismatch response profiles (which should be centred

on zero, *Figs 3, 4A and 4B*). When quantifying individual (uncentred) mismatch channel

response profiles (*Fig 4C and 4D*), the free parameter *μ* was allowed to vary between -90° and

90°. To reduce the likelihood of spurious (inverted) fits, the parameter search was initiated with

a *μ* value centred on the channel with the largest response.

The main effects of attention and prediction on orientation or mismatch response profiles were

assessed with cluster-based permutation tests across participant parameters (amplitude,

concentration). The interaction effects (between attention and prediction) on orientation and

mismatch response profiles were assessed by first subtracting the ignored response from the

attended response, and then subjecting the resulting difference maps to cluster-based

permutation tests. In cases where two levels were compared (i.e. the main effect of attention

on orientation response profiles, and all effects on mismatch response profiles), we used two-

tailed cluster-based permutation tests across participant parameters (Monte-Carlo distribution

with 5000 permutations, $p_{cluster}<0.05$; sample statistic: dependent samples t-statistic,

aggregated using the maximum sum of significant adjacent samples, $p_{sample}<.05$). In cases

where three levels were compared (i.e. the main effect of prediction and the interaction effect

on orientation response profiles), we used one-tailed cluster-based permutation tests across

participant parameters (Monte-Carlo distribution with 5000 permutations, $p_{cluster}<0.05$; sample

statistic: dependent samples f-statistic, aggregated using the maximum sum of significant

adjacent samples, $p_{sample}<.05$), and followed up any significant effects by collapsing across

significant timepoints and comparing individual conditions with paired-samples t-tests and

Bayes Factors (uniform prior, lower bound: -0.3 a.u., upper bound: 0.3 a.u.).

Univariate Electrode Sensitivity

To determine which electrodes were most informative for the forward encoding analyses, we

tested the sensitivity of each electrode to both orientation and mismatch information (*Fig 3C*

and 3F). The baseline-corrected signal at each electrode and time point in the epoch was

regressed against a design matrix that consisted of the sine and cosine of the variable of interest

(orientation or mismatch), and a constant regressor [30]. We calculated sensitivity, *S*, using the

square of the sine (β_{SIN}) and cosine (β_{COS}) regression coefficients:

717
$$S = \sqrt{(\beta_{SIN}^2 + \beta_{COS}^2)}.$$

S was normalised against a null distribution of the values expected by chance. The null

distribution was computed by shuffling the design matrix and repeating the analysis 1000

times. The observed (unpermuted) sensitivity index was ranked within the null distribution (to

produce a p-value) and z-normalised using the inverse of the cumulative Gaussian distribution

($\mu = 0$, $\sigma = 1$). The topographies shown in *Fig 3C and 3F* reflect the group averaged z-scores,

averaged across each time period of interest.

References

1. Helmholtz H v. Handbuch der Physiologishen Optik. Leipzig: Leopold Voss; 1867.

2. Friston KJ. A theory of cortical responses. Philos Trans R Soc B Biol Sci.
2005;360(1456):815–36.

3. Rao RPN, Ballard DH. Predictive coding in the visual cortex: a functional
interpretation of some extra-classical receptive-field effects. Nat Neurosci.
1999;2(1):79–87. DOI: 10.1038/4580

4. Stefanics G, Kremlácek J, Czigler I. Visual mismatch negativity: a predictive coding
view. Front Hum Neurosci. 2014;8(September):1–19. DOI:
10.3389/fnhum.2014.00666

5. Auksztulewicz R, Friston K. Attentional Enhancement of Auditory Mismatch
Responses: a DCM/MEG Study. Cereb Cortex. 2015;1–11. DOI:
10.1093/cercor/bhu323

6. Kok P, Rahnev D, Jehee JFM, Lau HC, De Lange FP. Attention reverses the effect of
prediction in silencing sensory signals. Cereb Cortex. 2012;22(9):2197–206. DOI:
10.1093/cercor/bhr310

7. Bar M. Visual objects in context. Nat Rev Neurosci. 2004;5(8):617–29. DOI:
10.1038/nrn1476

8. Feldman H, Friston KJ. Attention, uncertainty, and free-energy. Front Hum Neurosci.
2010;4(December):215. DOI: 10.3389/fnhum.2010.00215

9. Friston KJ. The free-energy principle: a rough guide to the brain? Trends Cogn Sci.
2009;13(7):293–301. DOI: 10.1016/j.tics.2009.04.005

10. Schröger E, Marzecová A, SanMiguel I. Attention and prediction in human audition: a
lesson from cognitive psychophysiology. Eur J Neurosci. 2015;41(5):641–64. DOI:
10.1111/ejn.12816

11. Summerfield C, de Lange FP. Expectation in perceptual decision making: neural and
computational mechanisms. Nat Rev Neurosci. 2014;(October). DOI: 10.1038/nrn3838

12. Spratling MW. Predictive coding as a model of biased competition in visual attention.
Vision Res. 2008;48(12):1391–408. DOI: 10.1016/j.visres.2008.03.009

13. Spratling MW. A review of predictive coding algorithms. Brain Cogn. 2017;112:92–7.
DOI: 10.1016/j.bandc.2015.11.003

14. Buzsáki G, Anastassiou CA, Koch C. The origin of extracellular fields and currents —
EEG, ECoG, LFP and spikes. Nat Rev Neurosci. 2012;13(6):407–20. DOI:
10.1038/nrn3241

15. Cohen MX. Where does EEG come from and what does it mean? Trends Neurosci.
2017;40(4):208–18. DOI: 10.1016/j.tins.2017.02.004

16. Lee TS, Mumford D. Hierarchical Bayesian inference in the visual cortex. J Opt Soc
Am A Opt Image Sci Vis. 2003;20(7):1434–48. DOI: 10.1364/JOSAA.20.001434

17. Spratling MW. Reconciling predictive coding and biased competition models of
cortical function. 2008;2(October):1–8. DOI: 10.3389/neuro.10.004.2008

18. Desimone R, Duncan J. Neural mechanisms of selective visual attention. Annu Rev
Neurosci. 1995;18(1):193–222. DOI: 10.1146/annurev.ne.18.030195.001205

19. Mitchell JF, Sundberg KA, Reynolds JH. Spatial Attention Decorrelates Intrinsic
Activity Fluctuations in Macaque Area V4. Neuron. 2009;63(6):879–88. DOI:
10.1016/j.neuron.2009.09.013

20. Reynolds JH, Chelazzi L, Desimone R. Competitive mechanisms subserve attention in
macaque areas V2 and V4. J Neurosci. 1999;19(5):1736–53. DOI:
10.1523/JNEUROSCI.19-05-01736.1999

21. Garrido MI, Friston KJ, Kiebel SJ, Stephan KE, Baldeweg T, Kilner JM. The
functional anatomy of the MMN: A DCM study of the roving paradigm. Neuroimage.
2008;42:936–44. DOI: 10.1016/j.neuroimage.2008.05.018

22. Kimura M, Katayama J, Ohira H, Schröger E. Visual mismatch negativity: New
evidence from the equiprobable paradigm. Psychophysiology. 2009;46:402–9. DOI:
10.1111/j.1469-8986.2008.00767.x

23. Delorme A, Makeig S. EEGLAB: an open source toolbox for analysis of single-trial
EEG dynamics including independent component anlaysis. J Neurosci Methods.
2004;134:9–21.

24. Oostenveld R, Fries P, Maris E, Schoffelen JM. FieldTrip: Open source software for
advanced analysis of MEG, EEG, and invasive electrophysiological data. Comput
Intell Neurosci. 2011;2011:1–9. DOI: 10.1155/2011/156869

25. Tales A, Newton P, Troscianko T, Butler S. Mismatch negativity in the visual
modality. Neuroreport. 1999;10(16):3363–7. DOI: 10.1097/00001756-199911080-
00020

26. Astikainen P, Lillstrang E, Ruusuvirta T. Visual mismatch negativity for changes in
orientation - a sensory memory-dependent response. Eur J Neurosci. 2008;28:2319–
24. DOI: 10.1111/j.1460-9568.2008.06510.x

27. Kimura M, Takeda Y. Automatic prediction regarding the next state of a visual object:
Electrophysiological indicators of prediction match and mismatch. Brain Res.
2015;1626:31–44. DOI: 10.1016/j.brainres.2015.01.013

28. Kimura M, Takeda Y. Task difficulty affects the predictive process indexed by visual
mismatch negativity. Front Hum Neurosci. 2013;7(June):1–13. DOI:
10.3389/fnhum.2013.00267

29. Garcia JO, Srinivasan R, Serences JT. Near-real-time feature-selective modulations in
human cortex. Curr Biol. 2013;23(6):515–22. DOI: 10.1016/j.cub.2013.02.013

30. Myers NE, Rohenkohl G, Wyart V, Woolrich MW, Nobre AC, Stokes MG. Testing
sensory evidence against mnemonic templates. Elife. 2015;4(December):1–25. DOI:
10.7554/eLife.09000

31. Kok P, Mostert P, de Lange FP. Prior expectations induce prestimulus sensory
templates. Proc Natl Acad Sci. 2017;1–6. DOI: 10.1073/pnas.1705652114

32. Brouwer GJ, Heeger DJ. Cross-orientation suppression in human visual cortex. J
Neurophysiol. 2011;106:2108–19. DOI: 10.1152/jn.00540.2011.

33. Patterson CA, Wissig SC, Kohn A. Distinct effects of brief and prolonged adaptation
on orientation tuning in primary visual cortex. J Neurosci. 2013;33(2):532–43. DOI:
10.1523/JNEUROSCI.3345-12.2013

34. Ester EF, Sutterer DW, Serences JT, Awh E. Feature-selective attentional modulations
in human frontoparietal cortex. J Neurosci. 2016;36(31):8188–99. DOI:
10.1523/JNEUROSCI.3935-15.2016

35. Haenschel C, Vernon DJ, Dwivedi P, Gruzelier JH, Baldeweg T. Event-related brain
potential correlates of human auditory sensory memory-trace formation.
2005;25(45):10494–501. DOI: 10.1523/JNEUROSCI.1227-05.2005

36. King JR, Dehaene S. Characterizing the dynamics of mental representations: The
temporal generalization method. Trends Cogn Sci. 2014;18(4):203–10. DOI:
10.1016/j.tics.2014.01.002

37. Cowan N, Winkler I, Teder W, Näätänen R. Memory prerequisites of mismatch
negativity in the auditory event-related potential (ERP). J Exp Psychol Learn Mem
Cogn. 1993;19(4):909–21. DOI: 10.1037/0278-7393.19.4.909

38. Kok P, Jehee JFM, de Lange FP. Less is more: Expectation sharpens representations in
the primary visual cortex. Neuron. 2012;75:265–70. DOI:
10.1016/j.neuron.2012.04.034

39. Tang MF, Smout CA, Arabzadeh E, Mattingley JB. Prediction error and repetition
suppression have distinct effects on neural Rrpresentations of visual information. Elife.
2018;7:1–21. DOI: 10.7554/eLife.33123

40. Sprague TC, Serences JT. Attention modulates spatial priority maps in the human
occipital, parietal and frontal cortices. Nat Publ Gr. 2013;16(12):1879–87. DOI:
10.1038/nn.3574

41. Marzecová A, Widmann A, SanMiguel I, Kotz SA, Schröger E. Interrelation of
attention and prediction in visual processing: Effects of task-relevance and stimulus
probability. Biol Psychol. 2017;125:76–90. DOI: 10.1016/j.biopsycho.2017.02.009

42. Kriegeskorte N, Bandettini P. Analyzing for information, not activation, to exploit
high-resolution fMRI. Neuroimage. 2007;38(4):649–62. DOI:
10.1016/j.neuroimage.2007.02.022

43. Hsu Y, Hämäläinen JA, Waszak F. Both attention and prediction are necessary for
adaptive neuronal tuning in sensory processing. Front Hum Neurosci.
2014;8(March):152. DOI: 10.3389/fnhum.2014.00152

44. Lieder F, Stephan KE, Daunizeau J, Garrido MI, Friston KJ. A neurocomputational
model of the mismatch negativity. PLoS Comput Biol. 2013;9(11). DOI:
10.1371/journal.pcbi.1003288

45. Tiitinen H, May P, Reinikainen K, Näätänen R. Attentive novelty detection in humans
is governed by pre-attentive sensory memory. Nature. 1994;372(6501):90–2. DOI:

10.1038/372090a0

46.   Wyart V, Nobre AC, Summerfield C. Dissociable prior influences of signal probability
and relevance on visual contrast sensitivity. Proc Natl Acad Sci. 2012;109(9):3593–8.
DOI: 10.1073/pnas.1120118109

47.   Rao RPN. Bayesian inference and attentional modulation in the visual cortex.
Neuroreport. 2005;16(16):1843–8. DOI: 10.1097/01.wnr.0000183900.92901.fc

48.   Kleiner, M., Brainard, D., Pelli, D., Ingling, A., Murray, R., & Broussard C. What's
new in Psychtoolbox-3. Perception. 2007;36(14):1.

49.   Watson AB, Pelli DG. Quest: A Bayesian adaptive psychometric method. Percept
Psychophys. 1983;33(2):113–20. DOI: 10.3758/BF03202828

50.   Dienes Z. Using Bayes to get the most out of non-significant results. Front Psychol.
2014 Jul 29;5(July):1–17. DOI: 10.3389/fpsyg.2014.00781

51.   Dienes Z. Understanding psychology as a science: An introduction to scientific and
statistical inference. Palgrave Macmillan. 2008. DOI: 10.1021/jp2005088

52.   Chaumon M, Bishop DVM, Busch NA. A practical guide to the selection of
independent components of the electroencephalogram for artifact correction. J
Neurosci Methods. 2015;250:47–63. DOI: 10.1016/j.jneumeth.2015.02.025

53.   Brouwer GJ, Heeger DJ. Decoding and reconstructing color from responses in human
visual cortex. J Neurosci. 2009;29(44):13992–4003. DOI: 10.1523/JNEUROSCI.3577-
09.2009

54.   Mostert P, Kok P, Lange FP De. Dissociating sensory from decision processes in
human perceptual decision making. Sci Rep. 2015;5:1–13. DOI: 10.1038/srep18253

S1 Fig. Event-related potentials (ERPs) and mismatch responses (MMRs). **(A)** ERPs at selected electrodes, shown separately for each condition. Bars underneath each plot indicate time points at which there was a significant main effect of attention (solid grey bar), significant main effect of prediction (solid black bar), or a significant interaction between attention and prediction (dotted black bar) at the plotted electrode. **(B)** Classic MMR (deviants - standards) and genuine MMR (deviants – controls) at selected electrodes, plotted separately for each level of attention. Green and yellow lines denote the classic MMR and genuine MMR, respectively; solid and dashed lines denote attended and ignored stimuli, respectively. Bars underneath each plot indicate timepoints at which there was a significant MMR in the corresponding condition, at the plotted electrode. Attended deviants were significantly different from attended standards (39 – 504 ms, cluster-corrected $p <$ .001) and attended controls (172 – 550 ms, cluster-corrected $p <$ .001). Ignored deviants were significantly different from ignored standards (47 – 438 ms, cluster-corrected $p <$ .001) and ignored controls (285 – 461 ms, cluster-corrected $p =$ .001) **(C-I)** Topographies of effects collapsed across time points between 200 and 300 ms. Asterisks and dots denote electrodes with larger, or smaller responses, respectively, in at least 25% of the displayed time points. **(C)** Main effect of attention (attended – ignored). **(D)** Classic MMR (deviants – standards). **(E)** Genuine MMR (deviants - controls). **(F)** Classic MMR during the grating task (attended deviants – attended standards). **(G)** Classic MMR during the dot task (ignored deviants – ignored standards). **(H)** Genuine MMR during the grating task (attended deviants – attended controls). **(G)** Genuine MMR during the dot task (ignored deviants – ignored standards).

S2 Fig. Independent main effects of attention and prediction on orientation response profiles, showing standards, deviants, and controls. **(A)** Main effect of attention on orientation response profiles. The amplitude of attended gratings was larger than that of ignored gratings (219 - 550 ms, cluster-corrected p = .001). Shading denotes standard error of the mean. The black bar along the x-axis denotes significant time points. **(B)** Orientation response profiles, collapsed across significant time points in **A**. Dots show activation in each of the nine modelled orientation channels. Curved lines show the functions used to quantify the amplitude and concentration of orientation-tuned responses (fitted to grand average data for illustrative purposes). **(C)** Main effect of prediction on orientation response profiles (black bar along the x-axis denotes significant time points, 324 – 550 ms, cluster-corrected p < .001). The amplitude of standards was reduced relative to both deviants and controls. **(D)** Orientation response profiles, collapsed across significant time points in **C**. **(E)** Interaction between attention and prediction on orientation response profile amplitude. Time-courses show the effect of attention (attended – ignored) on each stimulus type. **(F)** Orientation response profiles, collapsed across time points in the non-significant but trending cluster in **E** (414 - 481 ms, not displayed, cluster-corrected p = .093).

903 **S3 Fig.** Residual sum of squares (RSS) for exponentiated cosine functions fitted to generalised
904 mismatch response profiles (*Fig 5*). Note the high RSS values along the x-axis beginning at 200 ms,
905 indicating that the apparent generalisation of spatial maps trained at stimulus onset to later times in
906 the epoch (*Fig 5*, red patch along the x-axis) was likely due to noise.