Attention Promotes the Neural Encoding of Prediction Errors

Cooper A. Smout*[1,3], Matthew F. Tang[1,3], Marta I. Garrido[1,2,3,4], and

Jason B. Mattingley[1,3,5]

[1]Queensland Brain Institute, University of Queensland, Brisbane, Australia

[2]School of Mathematics and Physics, University of Queensland, Brisbane, Australia

[3]Australian Research Council Centre of Excellence for Integrative Brain Function, Australia

[4]Centre for Advanced Imaging, University of Queensland, Brisbane, Australia

[5]School of Psychology, University of Queensland, Brisbane, Australia

* Corresponding author:

QBI Building 79
University of Queensland
St Lucia QLD 4072
email: cooper.smout@gmail.com

This research was supported by the Australian Research Council (ARC) Centre of Excellence for Integrative Brain Function (ARC Centre Grant CE140100007). J.B.M was supported by an ARC Australian Laureate Fellowship (FL110100103). M.I.G. was supported by a University of Queensland Fellowship (2016000071). The authors declare no competing financial interests.

Abstract

The human brain is thought to optimise the encoding of incoming sensory information through two principal mechanisms: *prediction* uses stored information to guide the interpretation of forthcoming sensory events, and *attention* prioritizes these events according to their behavioural relevance. Despite the ubiquitous contributions of attention and prediction to various aspects of perception and cognition, it remains unknown how they interact to modulate information processing in the brain. A recent extension of predictive coding theory suggests that attention optimises the expected precision of predictions by modulating the synaptic gain of prediction error units. Since prediction errors code for the *difference* between predictions and sensory signals, this model would suggest that attention increases the selectivity for *mismatch information* in the neural response to a surprising stimulus. Alternative predictive coding models proposes that attention increases the activity of prediction (or 'representation') neurons, and would therefore suggest that attention and prediction synergistically modulate selectivity for *feature information* in the brain. Here we applied multivariate forward encoding techniques to neural activity recorded via electroencephalography (EEG) as human observers performed a simple visual task, to test for the effect of attention on both mismatch and feature information in the neural response to surprising stimuli. Participants attended or ignored a periodic stream of gratings, the orientations of which could be either predictable, surprising, or unpredictable. We found that surprising stimuli evoked neural responses that were encoded according to the difference between predicted and observed stimulus features, and that attention facilitated the encoding of this type of information in the brain. These findings advance our understanding of how attention and prediction modulate information processing in the brain, and support the theory that attention optimises precision expectations during hierarchical inference by increasing the gain of prediction errors.

Introduction

Perception is believed to arise from a process of active inference [1], during which the brain retrieves information from past experiences to build predictive models of likely future occurrences and compares these predictions with incoming sensory evidence [2,3]. In support of the idea that prediction increases the efficiency of neural encoding, previous studies have demonstrated that predicted visual events typically evoke smaller neural responses than surprising events (e.g. evoked activity measured in terms of changes in electrical potential or blood oxygen level dependent (BOLD) response; for a review, see [4]). Interestingly, recent studies have shown that selective attention can increase [5] or reverse [6] the suppressive effect of prediction on neural activity, suggesting that attention and prediction facilitate perception [7] via synergistic modulation of bottom-up sensory signals [8–11]. It remains unclear, however, what *type of information* is modulated in the interaction between attention and prediction. This question is important because different predictive coding models make distinct predictions about how information is transmitted through the cortical hierarchy [3,8,12,13]. Here, we used multivariate forward encoding analyses to assess selectivity for two distinct types of information in the neural response to surprising stimuli – *feature* and *mismatch information* - and to test the effect of attention on these two informational codes.

A prominent version of predictive coding theory claims that top-down prediction signals 'cancel out' bottom-up sensory signals that match the predicted content, leaving only the remaining prediction error to propagate forward and update a model of the sensory environment [2,8,9]. Since error propagation is thought to be associated with superficial pyramidal cells [9], and these cells are thought to be primarily responsible for generating EEG signals [14,15], this theory predicts that surprising events will increase the selectivity of EEG responses to the *difference* between predicted and observed stimulus features, i.e. mismatch information. Furthermore, a recent extension of this theory suggests that selective

attention optimises the expected precision of predictions by modulating the synaptic gain

(post-synaptic responsiveness) of prediction error units [8] – that is, neurons coding for

behaviourally relevant prediction errors should be more responsive than those coding for

irrelevant prediction errors. On this account, attention should further increase selectivity for

mismatch information in the neural response to surprising stimuli relative to unsurprising

stimuli. Here we call this account the *mismatch information model*.

Alternative predictive coding models [12,13,16] propose that predictions – as opposed to

prediction errors – are propagated forward through the visual hierarchy, and it is these

prediction signals that are modulated by attention. For example, the model proposed by

Spratling [12] simulates the common physiological finding that attention to a stimulus

enhances the firing rate of neurons tuned to specific stimulus features (e.g., orientation or

colour for visual neurons), and has been shown to be mathematically equivalent to the biased

competition model of attention [17–20]. In line with these alternative models, we investigated

a second hypothesis – here termed the *feature information model* – which proposes that the

interaction between attention and prediction at the level of neural responses is driven by

changes in feature-specific information in the brain.

Here we tested whether the *feature information model* or the *mismatch information model*

provides a better account of the neural coding of surprising stimuli in the human brain, and

examined the influence of selective attention on each of these two neural codes. Participants

attended to, or ignored, periodic streams of visual gratings, the orientations of which were

either predictable, surprising, or unpredictable. We applied forward encoding models to

whole-brain neural activity measured using EEG to quantify the neural selectivity for

information related to the grating orientation and the mismatch between the predicted and

observed grating orientations. We show that surprising stimuli evoke neural responses that

contain information related to the difference between predicted and observed stimulus

features, consistent with the *mismatch information model*. Crucially, we also find that

attention increases the selectivity for mismatch information in the neural response to

surprising stimuli, supporting the hypothesis that attention increases the gain of prediction

errors [8].

Results

We recorded brain activity using EEG as human observers (N = 24) undertook a rare-target

detection task (see Methods; *Fig 1*). Participants fixated centrally and were presented with a

periodic stream of gratings (100 ms duration, 500 ms ISI, 415 gratings per block) in one of

two conditions (randomised across blocks). In *roving standard* blocks [10] (see *Fig 1A*),

grating orientation was repeated between 4 and 11 times (*standards*) before changing to a

new orientation (*deviants*, pseudo-randomly selected from one of nine orientations, spanning

0 - 160º in 20º steps). Grating orientation was thus 'predictable' for standards and

'surprising' for deviants. In *equiprobable* blocks [11] (see *Fig 1B*), gratings changed

orientation on every presentation and thus could not be predicted ('unpredictable' *controls*).

Attention was manipulated by having participants either monitor the grating stimuli for rare

targets with a different spatial frequency ('grating task', *attended*), or ignore the gratings and

instead monitor for rare fixation-dot targets with decreased contrast ('dot task', gratings

ignored).

Fig 1. Example stimuli in each of the two block types used in the study. (**A**) Roving oddball
sequence. In this sequence, the orientation of gratings was repeated over short sequences of stimuli
(*standards*), before changing to a different orientation (*deviant*). During the grating or dot task,
participants responded to rare gratings with high spatial frequency (*grating target*) or to rare
decreases in fixation-dot contrast (*dot target*), respectively. (**B**) Equiprobable sequence. In this
sequence, the orientation of control gratings changed with each successive presentation.

Participants completed the grating task and dot task in separate sessions, approximately one

week apart (session order counterbalanced). At the beginning of each session, participants

completed three practice blocks of the specified task, during which target salience levels were

titrated to approximate a target detection rate of 75% (see *Methods*). Participants were then

fitted with a 64-electrode EEG cap before completing 21 test blocks. One participant detected

fewer than 50% of targets in both tasks and was therefore excluded from further

analyses. The remaining participants detected an equivalent percentage of targets in the

grating task (75.64 ± 1.76%, mean ± SEM) and dot task (72.73 ± 2.54%, paired t-test $p =$

0.13), and also produced similar numbers of false alarms in each (20.43 ± 3.79 and 22.57 ±

5.47, respectively, paired t-test $p = .684$). Bayes statistics supported the null hypotheses that

target detection (uniform prior, lower bound = 0, upper bound = 0.5, B = 0.09) and false

alarm rates (uniform prior, lower bound = 0, upper bound = 100, B = 0.14) were equivalent

across the two tasks, suggesting that difficulty was well matched between attention

conditions.

EEG data were pre-processed offline using EEGlab and epoched according to the onset of

each grating (Delorme and Makeig, 2004; see *Methods* for details). Statistical analyses were

conducted using cluster-based permutation tests in Fieldtrip [24]. *Fig S1* shows the main

effects and interactions for the factors of attention and prediction on event related potentials

(ERPs). Briefly, ERPs were modulated by both attention (86 - 434 ms, cluster-corrected p <

.001; *Fig S1A,C*) and prediction (39 - 550 ms, cluster-corrected p < .001, *Fig S1A*). Follow-

up analyses of the simple effects of prediction revealed that deviants elicited larger responses

than both standards (39 - 550 ms, cluster-corrected p < .001; *Fig S1A,D*) and controls (324 -

550 ms, cluster-corrected p = .002; *Fig S1A,E*). The difference between deviants and controls

emerged later and was smaller than the difference between deviants and standards, consistent

with the notion that the former comparison reflects the pure effects of prediction ("genuine"

mismatch response (MMR), [22]), whereas the latter comparison confounds the effects of

prediction with those of adaptation to the standard ('classic' MMR, see [4] for a review).

We also observed an interaction between attention and prediction (180 - 484 ms, cluster-

corrected p < .001; *Fig S1A*). Follow-up analyses revealed that attention increased both the

classic MMR (176 - 469 ms, cluster-corrected p < .001; *Fig S1F-G*) and the genuine MMR

(176 - 550 ms, cluster-corrected p < .001; *Fig S1H-I*). In the attended condition, both the

classic and the genuine MMRs emerged approximately 200 ms after stimulus onset over

posterior-lateral (PO7, PO8) electrodes (*Fig S1B*, solid green and yellow lines, respectively).

Whereas the onset of the genuine MMR is consistent with previous literature [22], the classic

MMR we report here emerged slightly later than what has typically been reported previously

(~150 ms; for a review see [4]). We note, however, that at least one previous study reported a

visual MMR beginning as late as 250 ms [25], highlighting the variable nature of visual

MMRs.

In the ignored condition, we observed classic and genuine MMRs (*Fig S1B,* dotted green and

yellow lines, respectively) with positive polarities over posterior (PO7, PO8) and frontal (Fz)

electrodes, respectively. This is in contrast to previous studies, which typically (but not

always, see [5]) report relatively large mismatch *negativities*, even in the absence of attention

[4]. This divergence might be due to physical differences between the stimuli used here

(gratings, 11º of visual angle) and those in previous studies (single oriented bars, typically 3-

4º of visual angle, e.g. [22,26]), which would likely affect both the polarity and amplitude of

mismatch responses [4].

Orientation information is enhanced with attention but not surprise

The *feature information model* predicts that surprising stimuli (deviants) should produce a

more orientation-selective neural response than control stimuli. To investigate this

hypothesis, we used a forward encoding model to estimate orientation selectivity from neural

activity measured with EEG (see *Methods* for details).

Briefly, we used multivariate regression to transform activity in electrode space into an

orientation-selective 'feature space' [27–30], comprised of nine hypothetical 'orientation

channels' matching those presented in the experiment (0 - 160º, in 20º steps). For each

orientation channel, we modelled the expected activation across trials by convolving the

presented orientation with a canonical orientation-selective tuning function. We then

regressed this pattern of expected activity against the EEG data, separately for each time

point (-100 - 550 ms after stimulus onset), to produce a weight matrix that converted

multivariate activity in electrode space into activity in the specified orientation channel. The

spatial weights for each orientation channel were then inverted to reconstruct the forward

model and applied to an independent set of test trials (using a cross-validation procedure) to

estimate activity across all orientation channels. As shown in *Fig 2A*, using the forward

encoding approach we reconstructed distinct response profiles for each of the nine grating

orientations presented to participants. Orientation channels were then realigned for each trial

such that the presented orientation channel was centred on $0º$, and activation patterns were

averaged across trials in each condition. The forward encoding model revealed an

orientation-tuned response throughout the epoch (*Fig 2B-C*). This response emerged soon

after stimulus onset, peaked at ~130 ms, and declined gradually until the end of the epoch.

Fig 2. Stimulus-evoked orientation channel response profiles. **(A)** Reconstructed orientation channels, corresponding to each of the nine grating orientations presented to participants (0 - 160°, in 20° steps). Coloured dots indicate the modelled orientation channel activity across trials in which the labelled orientation was presented. Curved lines show functions fitted to the grand average data for illustrative purposes. Note that each coloured line is approximately centred on the presented orientation. **(B)** Time-resolved orientation response profile, centred on the presented orientation in each trial and averaged across participants and conditions. Orientation response profiles emerged shortly after stimulus onset and lasted until the end of the epoch. **(C)** Orientation response profiles, averaged across all participants and conditions in each of three successive 100 ms time windows. Dots show activation in each of the nine modelled orientation channels (mean-centred). Curved lines show functions fitted to the grand average data for illustrative purposes. Orientation information (response profile amplitude) was strongest from 100 – 200 ms and decreased throughout the epoch. a.u. = arbitrary units.

To quantify the effects of attention and prediction on orientation response profiles, we fitted

the condition-averaged orientation channel responses with an exponentiated cosine function

[31,32] using least squares regression:

$$y(x) = Ae^{\kappa\,(\cos\,2(x\,-\,\mu)\text{-}1)} + B$$

where y is the predicted orientation channel activity in response to a grating with orientation

x; A is the peak response amplitude, κ is the concentration (i.e. inverse dispersion; a larger

value corresponds to a "tighter" function), μ is the centre of the function, and B is the

baseline offset (see *Methods*). Consistent with previous literature [27], attention increased the

amplitude of orientation response profiles (219 - 550 ms, cluster-corrected $p < .001$; *Fig*

3A,B) but did not modulate the tuning concentration (all clusters $p > .104$). There was a main

effect of prediction on the amplitude of orientation response profiles (324 – 550 ms, cluster-

corrected $p < .001$, *Fig S2C,D*). Follow-up analyses revealed that orientation response

profiles evoked by standards (0.11 ± 0.01) were smaller than those of both deviants (0.25 ±

0.03, paired t-test $p < 0.001$) and controls (0.22 ± 0.03, paired t-test $p < 0.001$; *Fig S2C,D*).

Since standards were preceded by identical stimuli, this effect may reflect stimulus-specific

adaptation rather than a 'genuine' effect of prediction [22]. Crucially, the amplitudes of

orientation response profiles evoked by deviants and controls were not significantly different

(paired t-test $p = 0.443$; *Fig 3A,B*) and Bayes statistics supported the null hypothesis that

deviant orientation response amplitudes were equal to those of controls (uniform prior, lower

bound = -0.3, upper bound = 0.3, $B = 0.19$). Finally, there was no effect of prediction on the

concentration of orientation response profiles (all clusters $p > .403$), and no interaction

between attention and prediction on either the amplitude (cluster-corrected $p = .093$, *Fig*

S2E,F) or concentration (no clusters found) of orientation response profiles.

To determine the scalp topography that was most informative for orientation encoding, we

calculated univariate sensitivity separately for each electrode across all trials, and averaged

across time points in the significant main effect of attention (see *Methods*). As revealed in

Fig 3C, posterior electrodes were the most sensitive to orientation information, as would be

expected for a source in visual cortex.

Fig 3. Effects of attention and prediction error on orientation and mismatch response profiles. **(A-C)**
Orientation response profiles. (**A**) Orientation selectivity (response profile amplitude) for each
condition over time. Shading indicates the SEM. Thin black lines indicate differences between
deviants and controls, separately for attended and ignored stimuli. The dark grey bar along the x-axis
indicates the main effect of attention (cluster-corrected). (**B**) Orientation response profiles, averaged
across the significant effect of attention shown in **A** (219 - 550 ms). Dots show activation in each of
the nine modelled mismatch channels. Curved lines show functions fitted to channel responses (fitted
to grand average data for illustrative purposes). (**C**) Univariate sensitivity for stimulus orientation
across all conditions (see *Methods*). Topography shows the permutation-corrected z-scores,
averaged across the significant effect of attention shown in **A** (219 - 550 ms). Posterior electrodes
were the most sensitive to orientation information. **(D-F)** Mismatch response profiles (observed minus
predicted orientation). (**D**) Mismatch selectivity (response profile amplitude) for each condition over
time. The grey, solid black, and dotted black bars along the x-axis indicate the main effect of attention,
main effect of prediction, and the interaction, respectively (cluster-corrected). Attention enhanced the
mismatch response profile in response to deviants but not controls. (**E**) Mismatch response profiles,
collapsed across the significant interaction shown in **D** (332 – 480 ms). (**F**) Univariate sensitivity for
mismatch response profiles evoked by attended deviants (see *Methods*), averaged across 332 – 480
ms. Posterior electrodes were the most sensitive to mismatch information. Note that **C** and **F** use
different scales. a.u. = arbitrary units.

Attention facilitates the neural encoding of mismatch information

The *mismatch information model* proposes that prediction errors are represented in

populations of neurons tuned to the *difference* between predicted and observed stimulus

features. According to this model, therefore, surprising stimuli (deviants) should produce a

more mismatch-selective neural response than control stimuli. Furthermore, if attention

enhances the gain of prediction errors [8], we should expect an interaction between attention

and prediction, such that attention enhances the amplitude of mismatch response profiles

evoked by deviants more than that of controls, because deviants should evoke a larger

prediction error [2].

To investigate these hypotheses, we trained a separate forward encoding model, as described

above, on the angular difference between gratings (deviants or controls) and the preceding

stimuli. That is, deviants were coded according to the difference between the deviant

orientation and the preceding standard orientation, and controls were coded according to the

difference between successive control orientations. For example, if a horizontally oriented

deviant (0°) was preceded by a standard that was oriented at 40° (clockwise of horizontal), it

would be coded as a mismatch of -40° (0 - 40°).

As shown in *Fig 3D-E*, we were able to reconstruct mismatch response profiles for attended

deviants. By contrast, mismatch response profiles were clearly weaker in response to controls

and ignored deviants. There was a significant main effect of attention on the amplitude of

mismatch response profiles (attended > ignored, 188 – 550 ms, cluster-corrected p = .002;

Fig 3D, grey bar along x-axis). There was also a significant main effect of prediction (deviant

> control, 113 – 550 ms, cluster-corrected p < .001; *Fig 3D*, solid black bar along x-axis),

suggesting that prediction error is encoded according to the mismatch between predicted and

observed features. Crucially, attention and prediction interacted to influence the amplitude of

mismatch response profiles (332 – 480 ms, cluster-corrected p = .031; *Fig 3D*, dotted black

bar along x-axis). As can be seen in *Fig 3D-E*, attention enhanced the amplitude of deviant

mismatch response profiles but had little effect on those evoked by controls, supporting the

hypothesis that attention boosts prediction errors [8].

The concentration of mismatch response profiles was not modulated by attention (all clusters

$p > .888$) or the interaction between attention and prediction (all clusters $p > .615$), but we did

find a significant main effect of prediction on the concentration of mismatch response profile

fits (controls > deviants, 344 - 422 ms, cluster-corrected $p < .001$). Since controls seemed to

produce negligible mismatch response profiles during this time period (yellow lines, *Fig 3D*),

however, we followed up this result and found that control mismatch response profile

amplitudes (.005 ± .023 a.u.) were not significantly different from zero (paired *t*-test $p =$

0.848). Furthermore, Bayesian statistics supported the null hypothesis that controls did not

evoke mismatch response profiles during this time (uniform prior, lower bound = 0, upper

bound = 0.3, $B = 0.11$), suggesting that the observed effect on concentration was more likely

an artefact of the fitting procedure than a true effect of prediction on mismatch response

profiles.

We calculated the sensitivity of each electrode to mismatch information in trials that

contained attended deviants, and collapsed across the significant interaction between 332 and

480 ms. As revealed in *Fig 3F*, posterior electrodes were again the most informative, but the

topography of mismatch sensitivity was weaker and more sparsely distributed than that of

orientation decoding (*Fig 3C*).

Mismatch information increases with the strength of predictions

Next, we investigated whether the number of preceding standards was related to the

amplitude of prediction error response profiles. Repeated presentations of the standard are

thought to increase the strength of the memory trace, resulting in larger prediction errors to a

subsequent surprising stimulus [33]. Mismatch response profiles evoked by attended deviants

were grouped according to the number of preceding standards (4-7 repetitions vs 8-11

repetitions) and fitted with exponentiated cosine functions (see *Methods*). As can be seen in

Fig 4A-B, increasing the number of standard repetitions also increased the amplitude of

mismatch response profiles (387 - 520 ms, cluster-corrected $p = .050$). This finding is

consistent with the notion that successive standards allow a more precise prediction to be

generated, which results in enhanced prediction errors when violated. Finally, there was no

effect of the number of standard repetitions on the concentration of mismatch response

profiles (cluster-corrected $p = .314$).

Fig 4. Mismatch response profiles (putative prediction error) evoked by attended deviants. (**A**) Effect of standard repetition on mismatch selectivity (response profile amplitude). Mismatch response profiles evoked by attended deviants were larger following long standard sequences (8 - 11 repetitions) than short standard sequences (4 - 7 repetitions). The black bar along the x-axis denotes significant differences (cluster-corrected). (**B**) Mismatch response profiles, collapsed across significant time points in **A** (387 - 520 ms). Dots show activation in each of the nine modelled mismatch channels. Curved lines show functions fitted to channel responses (fitted to grand average data for illustrative purposes). (**C**) Effect of deviation angle on mismatch selectivity. Mismatch response profile amplitude increased with the magnitude of deviation (±80° > ±20°). (**D**) Mismatch response profiles for each deviation angle, collapsed across the earlier cluster shown in **C** (215 - 410 ms). Curved lines show functions fitted with a variable centre (fitted to grand average data for illustrative purposes). a.u. = arbitrary units.

Mismatch information increases with the magnitude of violation

We also tested whether larger deviations from the prediction increased selectivity for mismatch information. Mismatch response profiles of attended deviants were grouped according to the angular difference between the deviant and preceding standard (i.e., the original mismatch values entered into the encoding model) and fitted with exponentiated cosine functions (variable centre, see *Methods*). There was a significant main effect of deviation magnitude on mismatch response profile amplitude (215 - 410 ms, cluster-corrected $p = .004$). As shown in *Fig 4C*, the amplitude of mismatch response profiles increased with the absolute deviation angle (±80° > ±60° > ±40° > ±20°), supporting the notion that larger

angular deviations (from the predicted orientation) produce more prediction error. A second

cluster emerged later in the epoch (465 - 550 ms, cluster-corrected $p = .031$), which followed

a similar pattern but with the amplitude of the ±40° and ±60° responses reversed.

Intriguingly, individual mismatch response profiles were typically centred on the orthogonal

deviation angle (90°, *Fig 4D*). This pattern of results differs from the individual orientation

response profiles (*Fig 3A*), which were (approximately) centred on the presented orientation.

Attention produces temporally stable mismatch response profiles

In a final step, we investigated whether the spatial maps that produce mismatch response

profiles are stable or evolve dynamically over time. We used the same forward encoding

analysis as above, with the exception that the trained weights at each time point were tested

on *all* time points in the epoch [28,34] (see *Methods*). This produced a *train time* x *test time*

generalisation matrix of mismatch channel responses, to which we fitted exponentiated

cosine functions. *Fig 5* shows the mismatch selectivity (response profile amplitude) for

attended and ignored deviants, generalised across time. As revealed in *Fig 5A*, the mismatch

response profile evoked by attended deviants generalised across the latter part of the epoch

(black outline surrounding large red patch in upper right quadrant between ~200 - 550 ms,

cluster-corrected $p = .011$), indicating that the spatial map associated with mismatch

information was relatively consistent throughout this period. Note also that this pattern of

generalisation was asymmetrical (triangular-shaped, rather than square-shaped). Specifically,

the spatial map trained at ~450 ms generalised to the (test) time point at ~250 ms, but training

at ~250 ms did not generalise to testing at ~450 ms. Since asymmetrical generalisation can

indicate differences in signal-to-noise ratios between time points [34], this finding suggests

that the strength of prediction error signals may have increased toward the end of the epoch.

It is also worth noting that the apparent generalisation of spatial maps trained at stimulus

onset ($t_{train} = 0$) to later times in the epoch (~200 – 550 ms, red patch along the x-axis) was

not significantly different from zero (no clusters found in this region) and produced high

residuals in the function fits (see *Fig S3*), suggesting that this pattern represents noise.

Finally, the mismatch response profile evoked by ignored stimuli (*Fig 5B*) did not generalise

across time points (all clusters $p > .355$) and was significantly smaller than that of attended

stimuli (significant difference denoted by the opaque patch in *Fig 5C*; $p = .018$).

Fig 5. Generalised mismatch response profiles in response to (**A**) attended deviants and (**B**) ignored
deviants. The dashed diagonal line indicates on-axis encoding (equivalent to the time-series plot in
Fig 4A). The black outline shows mismatch response profiles significantly larger than zero (cluster-
corrected). (**C**) Difference map (attended minus ignored), thresholded to show the significant effect of
attention on mismatch response profiles (cluster-corrected). a.u. = arbitrary units.

367   **Discussion**

Here we set out to determine what type of information is modulated in the interaction

between attention and prediction [8]. To achieve this, we used forward encoding models of

EEG data to quantify the selectivity for orientation and mismatch information in the neural

responses to surprising and unpredictable stimuli in the well-established roving oddball

paradigm [21,35]. Relative to unpredictable stimuli (controls), we found that EEG responses

to surprising stimuli (deviants) were equally selective for orientation information, but more

selective for information related to the *difference* between predicted and observed stimulus

features. These results are consistent with the *mismatch information model*, and support the

idea that top-down prediction signals 'cancel out' matching bottom-up sensory signals and

leave only the remaining prediction error to propagate forward [2,3,8,9]. Crucially, we also

found that attention increased the selectivity for mismatch information in neural responses to

surprising but not control stimuli. This finding demonstrates that attention boosts mismatch

information evoked by surprising stimuli (putative prediction errors), and is consistent with a

recent version of predictive coding theory that proposes attention optimises the expected

precision of predictions by increasing the gain of prediction errors [8].

We found no difference between orientation response profiles evoked by surprising and

unpredictable stimuli (a prediction of the *feature information model*), suggesting that the

changes in EEG that are typically seen with prediction are not coded according to stimulus

features. This finding contradicts predictive coding models in which predictions (or

'representations') of stimulus features are passed up the visual hierarchy [12,16,17]. Because

feedforward connections originate primarily from superficial pyramidal cells and it is this

activity that is measured with EEG [9,14,15], these models would predict that surprise

changes the feature-selectivity of EEG responses: a finding we do not observe here. This

finding might also seem to contradict a recent study that demonstrated greater selectivity for

orientation information in early visual cortex BOLD activity following presentation of a

predicted grating, relative to a surprising grating [36]. Since BOLD activity indirectly

measures the activity patterns of heterogenous populations of neurons, however, this change

in feature-selectivity could have reflected a change in either of the two neuronal populations

proposed to underlie predictive coding - *predictions* or *prediction errors*. The latter

interpretation is inconsistent with the results of the present study, which suggests that

prediction errors are encoded according to the mismatch between predicted and observed

stimulus features, and not the features themselves. The former interpretation (i.e. that

predictions are coded according to the stimulus features) fits well with a recent study that

showed prediction induces feature-specific templates immediately prior to stimulus onset

[29]. Thus, a parsimonious account of the literature to date suggests that *predictions* and

prediction errors are represented in the brain via distinct neural codes: whereas predictions

are represented according to stimulus features, prediction errors are represented according to

the *mismatch* between predicted and observed stimulus features.

Crucially, we also tested the interactive effects of attention and prediction on information

processing in the brain. There was a large and significant effect of attention on mismatch

response profiles in response to surprising but not unpredictable stimuli (beginning around

150 ms after stimulus onset and reaching significance from ~350 ms). This finding

demonstrates that attention boosts prediction errors evoked by surprising stimuli, and is

consistent with a recent iteration of predictive coding theory according to which attention

optimises the expected precision of prediction errors [8]. Previous studies have found

evidence for an interaction between attention and prediction in both the auditory [5] and

visual [6,37] modalities. Importantly, these studies used *activation-based* analyses to

compare differences between predicted and unpredicted stimuli at the level of overall neural

activity, but did not investigate what *type of information* is modulated in the interaction

between attention and prediction. In contrast, the present study used *information-based*

analyses [38] to identify specific patterns of neural activity that are associated with

orientation-mismatch information in the brain, and showed that selectivity for this type of

information (but not feature information) is increased with attention. Thus, the present study

provides clear support for the hypothesis that attention boosts the gain of prediction errors

[8]. It will be important for future research to investigate whether the interactive effects of

attention and prediction on mismatch information is contingent on the type of attention (e.g.,

feature-based versus spatial attention) or prediction (e.g., rule-based versus multimodal cue-

stimulus predictions; [29,39]).

Interestingly, we found that the magnitude of mismatch response profiles correlated with the

number of preceding standards (*Fig 4A-B*). Previous work in the auditory domain

demonstrated that successive repetitions of the standard evoke progressively increased

responses to a subsequent attended deviant [33]. Here we find a corollary for this effect in the

visual domain and demonstrate that the neural activity modulated by the number of preceding

standards is likely encoded as mismatch information. This finding is also consistent with the

notion that repeating the standard allows a more precise prediction to be generated, which

results in a larger prediction error to a subsequent surprising stimulus [40]. Crucially, we also

found that mismatch response profiles increase with the magnitude of the mismatch between

predicted and observed stimulus features (*Fig 4E*). Previous work in the auditory domain has

demonstrated a correlation between deviation magnitude and the amplitude of the neural

response to deviants (i.e. the mismatch negativity) [41]. Here we demonstrate a relationship

between deviation magnitude and selectivity for mismatch information (as opposed to

activation levels) in the visual domain, suggesting that the magnitude of mismatch

information might be used by the brain to guide updating of the predictive model.

Somewhat surprisingly, there was a lateral shift in the response profile of individual

mismatch channels, such that mismatch response profiles ($\pm$40-80°) were approximately

centred on the 90° (orthogonal) channel (*Fig 4D*). We speculate that this finding may indicate

the brain uses an efficient neural code to encode prediction errors. Given that there are an

infinite number of possible predictions and observations, it would be inefficient for the brain

to represent all possible prediction errors discretely. A more efficient code might rely upon a

reduced set of mismatch channels (e.g., one mismatch channel per feature of interest), with

the magnitude of these mismatch channels indicating the degree of model update required.

Intriguingly, a number of recent studies failed to find an interaction between the effects of

attention and prediction on stimulus information in the brain [29,36,42]. If predictions are

encoded according to stimulus features, as we argue above, these null findings contradict the

theory that attention boosts predictions [43]. In contrast, we show that *prediction errors*,

represented according to the *mismatch* between predicted and observed stimulus features, are

enhanced with attention. Although the present study cannot speak to the activity of single

neurons, we note that the emerging picture is consistent with the notion that predictions and

prediction errors are represented in distinct populations of neurons [2] that encode two

distinct types of information and are differentially influenced by attention. Under this

framework, feature information encoded by prediction units would be immune to attention,

whereas mismatch information encoded by *prediction error* units would be enhanced by

attention. Future research could test these hypotheses at the single-cell level, for example by

using single-unit electrode recordings or 2-photon calcium imaging to assess whether

different neurons within a given cortical area satisfy these contraints.

463   **Methods**

Participants

Twenty-four healthy participants (11 female, 13 male, mean = 23.25 years, SD = 9.01 years)

with normal or corrected-to-normal vision were recruited via an online research participation

scheme at The University of Queensland, and provided written consent prior to

commencement of the study. The study was approved by The University of Queensland

Human Research Ethics Committee and was in accordance with the Declaration of Helsinki.

Stimuli

Stimuli were presented on a 61 cm LED monitor (Asus, VG248QE) with a 1920 x 1080 pixel

resolution and refresh rate of 120 Hz, using the PsychToolbox presentation software [44] for

Matlab (v.15b) running under Windows 7 with a NVidia Quadro K4000 graphics card.

Participants were seated in a comfortable armchair in an electrically shielded laboratory, with

the head supported by a chin rest at a viewing distance of 57 cm.

During each block, 415 gratings with Gaussian edges (outer diameter: 11º, inner mask

diameter: 0.83º, spatial frequency: 2.73 c/º, 100% contrast) were presented centrally for 100

ms with a 500 ms ISI. Grating orientations were evenly spaced between 0º (horizontal) and

160º (in 20º steps). Eighteen (18) gratings in each block (2 per orientation) were presented

with a higher spatial frequency (range: 2.73 - 4.55 c/º, as per staircase procedure, below),

with a gap of at least 1.5 s between any two such gratings. We used a modified de Bruijn

sequence to balance the order of grating orientations across conditions, sessions, and

participants. Specifically, we generated two 9-character (orientation) sequences without

successive repetitions (i.e. ABCA, not ABCC) - one with a 3-character sub-sequence (504

characters long) and another with a 2-character sub-sequence (72 characters long) - and

appended two copies of the former sequence to three copies of the latter sequence (1224

characters in total). This master sequence was used to allocate the order of both deviants and

controls in each session (using different, random start-points), and ensured that each

orientation was preceded by equal numbers of all other orientations (up to 2+ preceding

stimuli) so that decoding of any specific orientation could not be biased by the orientation of

preceding stimuli.

In roving oddball sequences, the number of Gabor repetitions (i.e., standards) was balanced

across orientations within each session, such that each orientation repeated between 4 and 11

times according to the following distribution: (31, 31, 31, 23, 5, 5, 5, 5), respectively. During

each block, the fixation dot (diameter: 0.3º, 100% contrast) decreased in contrast 18 times

(contrast range: 53-98% as per staircase procedure, below) for 0.5 s (0.25 s linear ramp on

and off). Contrast decrement onsets were randomised separately for each block, with a gap of

at least 1.5 s between any two decrement onsets.

Procedure

Participants attended two testing sessions of 60 minutes duration, approximately one week

apart, and completed one of two tasks in each session (*Fig 1*, session order counterbalanced

across participants). For the grating task, participants were informed that approximately 1/20

of the gratings would be a target grating with a higher spatial frequency than non-targets, and

were asked to press a mouse button as quickly as possible when they detected a target

grating; all other gratings were to be ignored. For the dot task, participants were informed

that the fixation dot would occasionally decrease in contrast, and were asked to press a mouse

button as quickly as possible when they detected such a change. Participants initially

completed three practice blocks (3.5 min per block) with auditory feedback (high or low

tones) indicating missed targets and the accuracy of their responses. During the practice

blocks, target salience (spatial frequency or dot contrast change, depending on the task) was

adjusted dynamically using a Quest staircase procedure [45] to approximate 75% target

detection. Participants were requested to minimise their number of false alarms. After the

practice blocks, participants were fitted with an EEG cap (see *EEG Data Acquisition*) before

completing a total of 21 test blocks (3 equiprobable, 18 roving standard, block order

randomised) without auditory feedback. After each block participants were shown the

percentage of targets correctly detected, the speed of these responses, and how many non-

targets were responded to (false alarms).

Behavioural Data Analysis

Participant responses were scored as hits if they occurred within one second of the onset of a

target grating in the grating task, or within one second of the peak contrast decrement in the

dot task. Target detection was then expressed as a percentage of the total number of targets

presented in each testing session. One participant detected less than 50% of targets in both

sessions and was removed from further analysis. Target detections and false alarms across the

two sessions were compared with paired-samples t-tests.

EEG Data Acquisition

Participants were fitted with a 64 Ag-AgCl electrode EEG system (BioSemi Active Two:

Amsterdam, Netherlands). Continuous data were recorded using BioSemi ActiView software

(http://www.biosemi.com), and were digitized at a sample rate of 1024 Hz with 24-bit A/D

conversion and a .01 – 208 Hz amplifier band pass. All scalp electrode offsets were adjusted

to below 20µV prior to beginning the recording. Pairs of flat Ag-AgCl electro-oculographic

electrodes were placed on the outside of both eyes, and above and below the left eye, to

record horizontal and vertical eye movements, respectively.

EEG Data Preprocessing

EEG recordings were processed offline using the EEGlab toolbox in Matlab [23]. Data were

resampled to 256 Hz and high-pass filtered with a passband edge at 0.5 Hz (1691-point

Hamming window, cut-off frequency: 0.25 Hz, -6 db). Raw data were inspected for the

presence of faulty scalp electrodes (2 electrodes, across 2 sessions), which were interpolated

using the average of the neighbouring activations (neighbours defined according to the

EEGlab Biosemi 64 template). Data were re-referenced to the average of all scalp electrodes,

and line noise at 50 and 100 Hz was removed using the Cleanline plugin for EEGlab

(https://www.nitrc.org/projects/cleanline). Continuous data were visually inspected and

periods of noise (e.g., muscle activity) were removed (1.4% of data removed in this way,

across sessions).

544 For artefact identification, the cleaned data were segmented into 500 ms epochs surrounding

545 grating onsets (100 ms pre- and 400 ms post-stimulus). Improbable epochs were removed

546 using a probability test (6SD for individual electrode channels, 2SD for all electrode

547 channels, 6.5% of trials across sessions), and the remaining data were subjected to

548 independent components analyses (ICA) with a reduced rank in cases of a missing EOG

549 electrode (2 sessions) or an interpolated scalp electrode (2 sessions). Components

550 representing blinks, saccades, and muscle artefacts were identified using the SASICA plugin

551 for EEGlab [46].

552 For further analysis, the cleaned data (i.e., prior to the ICA analysis) were segmented into 800

553 ms epochs surrounding grating onsets (150 ms pre- and 650 ms post-stimulus). Independent

554 component weights from the artefact identification process were applied to this new data set,

555 and previously identified artefactual components were removed. Baseline activity in the 100

556 ms prior to each stimulus was removed from each epoch, and improbable epochs were

557 removed using a probability test (6SD for individual electrode channels, 2SD for all electrode

558 channels, 7.1% of trials across sessions).

559 Grating epochs were then separated into their respective attention and prediction conditions.

560 Epochs in the grating task were labelled as 'Attended' and epochs in the dot task were

561 labelled as 'Ignored'. Epochs in the roving oddball sequence were labelled as 'Deviants'

562 when they contained the first stimulus in a repeated train of gratings, and 'Standards' when

563 they contained a grating that had been repeated between five and seven times. Epochs in the

564 equiprobable sequence were labeled as 'Controls'.

 Event-Related Potential Analyses

Trials in each attention and prediction condition were averaged within participants to produce

event-related potentials (ERPs) for each individual. The effect of attention was assessed using

a two-tailed cluster-based permutation test across participant ERPs (Monte-Carlo distribution

with 5000 permutations, $p_{cluster}<0.05$; sample statistic: dependent samples t-statistic,

aggregated using the maximum sum of significant adjacent samples, $p_{sample}<.05$). Because

there were three, rather than two, levels of prediction, we tested the effect of prediction with a

cluster-based permutation test that used f-statistics at the sample level and a one-sided

distribution to account for the positive range of f-statistics (Monte-Carlo distribution with

5000 permutations, $p_{cluster}<0.05$; sample statistic: dependent samples f-statistic, aggregated

using the maximum sum of significant adjacent samples, $p_{sample}<.05$). Simple contrasts

between prediction conditions (deviants vs standards, and deviants vs controls) were tested

using two-tailed cluster-based permutation tests (with the same settings as used to investigate

attention). The interaction between attention and prediction was assessed by subtracting the

ignored ERP from the attended ERP within each prediction condition and subjecting the

resulting difference waves to a one-tailed cluster-based permutation test across participant

ERPs (Monte-Carlo distribution with 5000 permutations, $p_{cluster}<0.05$; sample statistic:

dependent samples f-statistic, aggregated using the maximum sum of significant adjacent

samples, $p_{sample}<.05$). The interaction effect was followed-up by comparing difference waves

(attended - ignored) between deviants and standards, and between deviants and controls (two-

tailed cluster-based permutation tests, same settings as above).

Forward Encoding Models

To investigate the informational content of orientation signals, we used a forward encoding

model [27,47] designed to control for noise covariance in highly correlated data [29,48;

https://github.com/Pim-Mostert/decoding-toolbox], such as EEG. We modelled an idealised

basis set of the nine orientations of interest (0-160° in 20° steps) with nine half-wave rectified

cosine functions raised to the 8^{th} power, such that the response profile associated with any

particular orientation in the 180° space could be equally expressed as a weighted sum of the

nine modelled orientation channels [27]. We created a matrix of nine regressors that

represented the grating orientation presented on each trial in the training set (1 = the

presented orientation, 0 = otherwise) and convolved this regressor matrix with the basis set to

produce a design matrix, C (9 orientation channels x n trials). The EEG data could thus be

described by the linear model:

598
$$B = WC + N,$$

where B represents the data (64 electrodes x n trials), W represents a spatial weight matrix

that converts activity in channel space to activity in electrode space (64 electrodes x 9

orientation channels) and N represents the residuals (i.e., noise).

To train and test the forward encoding model, we used a three-fold cross-validation

procedure that was iterated 100 times to increase reliability of the results. Within each cross-

validation iteration, the experimental blocks were folded into thirds: one third of trials served

as the test set and the remaining two-thirds served as the training set, and folds were looped

through until each fold had served as a test set. Across successive iterations of the cross-

validation procedure, the number of trials in each condition was balanced within folds by

random selection (on the first iteration) or by selecting the trials that had been utilised the

least across previous folds (subsequent iterations).

Prior to estimating the forward encoding model, each electrode in the training data was de-

meaned across trials, and each time point was averaged across a 27.3 ms window centred on

the time point of interest (corresponding to an *a priori* window of 30 ms, rounded down to an

odd number of samples to prevent asymmetric centring). Separately for each time point and

orientation channel of interest, i, we solved the linear equation using least square regression:

$$\mathbf{w}_i = \mathbf{B}_{train}\, \mathbf{c}_{train,i}{}^{\mathrm{T}} \,(\mathbf{c}_{train,i}\, \mathbf{c}_{train,i}{}^{\mathrm{T}})^{-1},$$

616
where $\mathbf{w}_i$ represents the spatial weights for channel i, $\mathbf{B}_{train}$ represents the training data (64

electrodes x n_{train} trials), and $\mathbf{c}_{train,i}$ represents the hypothetical response of channel i across

the training trials (1 x n_{train} trials). Following Mostert et al. [48], we then derived the optimal

spatial filter $\mathbf{v}_i$ to recover the activity of the ith orientation channel:

$$\mathbf{v}_i = \frac{\widetilde{\Sigma}_i^{-1}\, \mathbf{w}_i}{\mathbf{w}_i^{\mathrm{T}}\, \widetilde{\Sigma}_i^{-1}\, \mathbf{w}_i},$$

where Σ_i is the regularized covariance matrix for channel i, estimated as follows:

$$\widetilde{\Sigma}_i = \frac{1}{n_{train} - 1}\, \varepsilon_i\, \varepsilon_i^{\mathrm{T}}$$

$$\varepsilon_i = \mathbf{B}_{train} - \mathbf{w}_i \mathbf{c}_{train,i},$$

where n_{train} is the number of training trials. The covariance matrix $\widetilde{\Sigma}_i$ was regularized by

using the analytically determined shrinkage parameter [29]. Combining the spatial filters

across each of the nine orientation channels produced a channel filter matrix $\mathbf{V}$ (64 electrodes

x 9 channels).

$$\mathbf{C}_{test} = \mathbf{V}^{\mathrm{T}}\, \mathbf{B}_{test},$$

where $\mathbf{B}_{test}$ represents the test data at the time point of interest (64 electrodes x n_{test} trials),

averaged over a 27.3 ms window (as per the training data). Finally, the orientation channel

responses for each trial were circularly shifted to centre the presented orientation on 0°, and

the zero-centred responses were averaged across trials within each condition to produce the

condition-average orientation channel response (*Fig 3B*).

To assess information related to the mismatch between predicted and observed stimulus

features (*Fig 3D-E*), we computed a second forward encoding model as above, with the

exception that now the regression matrix represented the difference between the current

grating orientation (deviant or control) and the previous grating orientation (standard or

control, respectively). That is, a grating at 60° orientation that followed a grating at 20°

orientation would be coded as 40° (current minus previous orientation).

To assess the dynamic nature of mismatch response profiles (*Fig 5*), we trained the weight

matrix, *W*, at a single time point in the training set, B_1 (using a 30 ms sliding window), and

then applied the weights to *every third* time point in the test set, B_2 (using a 30 ms sliding

window). This process was repeated for every third time point in the training set, resulting in

a 3-dimensional matrix that contained the population response profile at each cross-

generalised time point (9 orientations x 66 training time points x 66 testing time points).

Quantifying Channel Responses

Previous studies have utilised a number of different methods to quantify the selectivity of

neural response profiles [28,29]. Since we were interested in characterising the properties of

neural response profiles, we opted to fit an exponentiated cosine function to the modelled

data [31,32] using least square regression:

$$y(x) = Ae^{\kappa (\cos 2(x - \mu) . 1)} + B$$

where y is the predicted orientation channel activity in response to a grating with orientation

x; A is the peak response amplitude, κ is the concentration parameter, μ is the centre of the

distribution, and B is the baseline offset. Fitting was performed using the non-linear least

square method in MATLAB (trust region reflective algorithm). The free parameters A, κ, and

B were constrained to the ranges (-0.5, 2), (1.5, 200), and (-1.0, 0.5), respectively, and

initiated with the values 0.5, 2, and 0, respectively. The free parameter μ was constrained to

be zero when quantifying mean-centred orientation or mismatch response profiles (which

should be centred on zero, *Fig 3, 4A-B*). When quantifying individual (uncentred) mismatch

channel response profiles (*Fig 4C-D*), the free parameter μ was allowed to vary between -90°

and 90°. To reduce the likelihood of spurious (inverted) fits, the parameter search was

initiated with a μ value centred on the channel with the largest response. The effects of

attention and prediction on orientation or mismatch response profiles were assessed with two-

tailed cluster-based permutation tests across participant parameters (Monte-Carlo distribution

with 5000 permutations, $p_{cluster} < 0.05$; sample statistic: dependent samples t-statistic,

aggregated using the maximum sum of significant adjacent samples, $p_{sample} < .05$).

Univariate Electrode Sensitivity

To determine which electrodes were most informative for the forward encoding analyses, we

tested the sensitivity of each electrode to both orientation and mismatch information (*Fig

3C,F*). The baseline-corrected signal at each electrode and time point in the epoch was

regressed against a design matrix that consisted of the sine and cosine of the variable of

interest (orientation or mismatch), and a constant regressor [28]. We calculated sensitivity, S,

using the square of the sine (β_{SIN}) and cosine (β_{COS}) regression coefficients:

$$S = \sqrt{(\beta_{SIN}^2 + \beta_{COS}^2)}.$$

S was normalised against a null distribution of the values expected by chance. The null

distribution was computed by shuffling the design matrix and repeating the analysis 1000

times. The observed (unpermuted) sensitivity index was ranked within the null distribution

(to produce a p-value) and z-normalised using the inverse of the cumulative Gaussian

distribution ($\mu = 0$, $\sigma = 1$). The topographies shown in *Fig 3C,F* reflect the group averaged z-

scores, averaged across each time period of interest.

Online Data and Code

All data and scripts used in this study have been made available online via the Open Science

Framework (https://www.doi.org/10.17605/OSF.IO/A3PFQ).

685   **References**

1.   Helmholtz H v. Handbuch der Physiologishen Optik. Leipzig: Leopold Voss; 1867.

2.   Friston KJ. A theory of cortical responses. Philos Trans R Soc B Biol Sci.
2005;360(1456):815–36.

3.   Rao RPN, Ballard DH. Predictive coding in the visual cortex: a functional
interpretation of some extra-classical receptive-field effects. Nat Neurosci.
1999;2(1):79–87.

4.   Stefanics G, Kremlácek J, Czigler I. Visual mismatch negativity: a predictive coding
view. Front Hum Neurosci. 2014;8(September):1–19.

5.   Auksztulewicz R, Friston K. Attentional Enhancement of Auditory Mismatch
Responses: a DCM/MEG Study. Cereb Cortex. 2015;1–11.

6.   Kok P, Rahnev D, Jehee JFM, Lau HC, De Lange FP. Attention reverses the effect of
prediction in silencing sensory signals. Cereb Cortex. 2012;22(9):2197–206.

7.   Bar M. Visual objects in context. Nat Rev Neurosci. 2004;5(8):617–29.

8.   Feldman H, Friston KJ. Attention, uncertainty, and free-energy. Front Hum Neurosci.
2010;4(December):215.

9.   Friston KJ. The free-energy principle: a rough guide to the brain? Trends Cogn Sci.
2009;13(7):293–301.

10.   Schröger E, Marzecová A, SanMiguel I. Attention and prediction in human audition: a
lesson from cognitive psychophysiology. Eur J Neurosci. 2015;41(5):641–64.

11.   Summerfield C, de Lange FP. Expectation in perceptual decision making: neural and
computational mechanisms. Nat Rev Neurosci. 2014;(October).

12.   Spratling MW. Predictive coding as a model of biased competition in visual attention.
Vision Res. 2008;48(12):1391–408.

13.   Spratling MW. A review of predictive coding algorithms. Brain Cogn. 2017;112:92–7.

14.   Buzsáki G, Anastassiou C a., Koch C. The origin of extracellular fields and currents —
711   EEG, ECoG, LFP and spikes. Nat Rev Neurosci. 2012;13(6):407–20.

712   15.   Cohen MX. Where Does EEG Come From and What Does It Mean? Trends Neurosci.
713   2017;40(4):208–18.

714   16.   Lee TS, Mumford D. Hierarchical Bayesian inference in the visual cortex. J Opt Soc
715   Am A Opt Image Sci Vis. 2003;20(7):1434–48.

716   17.   Spratling MW. Reconciling predictive coding and biased competition models of
717   cortical function. 2008;2(October):1–8.

718   18.   Desimone R, Duncan J. Neural mechanisms of selective visual attention. Annu Rev
719   Neurosci. 1995;18(1):193–222.

720   19.   Mitchell JF, Sundberg K a., Reynolds JH. Spatial Attention Decorrelates Intrinsic
721   Activity Fluctuations in Macaque Area V4. Neuron. 2009;63(6):879–88.

722   20.   Reynolds JH, Chelazzi L, Desimone R. Competitive mechanisms subserve attention in
723   macaque areas V2 and V4. J Neurosci. 1999;19(5):1736–53.

724   21.   Garrido MI, Friston KJ, Kiebel SJ, Stephan KE, Baldeweg T, Kilner JM. The
725   functional anatomy of the MMN: A DCM study of the roving paradigm. Neuroimage.
726   2008;42(2):936–44.

727   22.   Kimura M, Katayama J, Ohira H, Schröger E. Visual mismatch negativity: New
728   evidence from the equiprobable paradigm. Psychophysiology. 2009;46:402–9.

729   23.   Delorme A, Makeig S. EEGLAB: an open sorce toolbox for analysis of single-trial
730   EEG dynamics including independent component anlaysis. J Neurosci Methods.
731   2004;134:9–21.

732   24.   Oostenveld R, Fries P, Maris E, Schoffelen JM. FieldTrip: Open source software for
733   advanced analysis of MEG, EEG, and invasive electrophysiological data. Comput
734   Intell Neurosci. 2011;2011:1–9.

735   25.   Tales A, Newton P, Troscianko T, Butler S. Mismatch negativity in the visual
736   modality. Neuroreport. 1999;10(16):3363–7.

737   26.   Astikainen P, Lillstrang E, Ruusuvirta T. Visual mismatch negativity for changes in
738   orientation--a sensory memory-dependent response. Eur J Neurosci.
739   2008;28(11):2319–24.

740   27.   Garcia JO, Srinivasan R, Serences JT. Near-Real-Time Feature-Selective Modulations
741   in Human Cortex. Curr Biol. 2013;23(6):515–22.

742   28.   Myers NE, Rohenkohl G, Wyart V, Woolrich MW, Nobre AC, Stokes MG. Testing
743   sensory evidence against mnemonic templates. Elife. 2015;4(DECEMBER2015):1–25.

744   29.   Kok P, Mostert P, de Lange FP. Prior expectations induce prestimulus sensory
745   templates. Proc Natl Acad Sci. 2017;201705652.

746   30.   Brouwer GJG, Heeger DJD. Cross-orientation suppression in human visual cortex. J
747   Neurophysiol. 2011;106(5):2108–19.

748   31.   Patterson CA, Wissig SC, Kohn A. Distinct Effects of Brief and Prolonged Adaptation
749   on Orientation Tuning in Primary Visual Cortex. J Neurosci. 2013;33(2):532–43.

750   32.   Ester EF, Sutterer DW, Serences JT, Awh E. Feature-Selective Attentional
751   Modulations in Human Frontoparietal Cortex. J Neurosci. 2016;36(31):8188–99.

752   33.   Haenschel C, Vernon DJ, Dwivedi P, Gruzelier JH, Baldeweg T. Event-Related Brain

753		Potential Correlates of Human Auditory Sensory Memory-Trace Formation.
754		2005;25(45):10494–501.
755	34.	King JR, Dehaene S. Characterizing the dynamics of mental representations: The
756		temporal generalization method. Trends Cogn Sci. 2014;18(4):203–10.
757	35.	Cowan N, Winkler I, Teder W, Näätänen R. Memory prerequisites of mismatch
758		negativity in the auditory event-related potential (ERP). J Exp Psychol Learn Mem
759		Cogn. 1993;19(4):909–21.
760	36.	Kok P, Jehee JFM, de Lange FP. Less Is More: Expectation Sharpens Representations
761		in the Primary Visual Cortex. Neuron. 2012;75(2):265–70.
762	37.	Marzecová A, Widmann A, SanMiguel I, Kotz SA, Schröger E. Interrelation of
763		attention and prediction in visual processing: Effects of task-relevance and stimulus
764		probability. Biol Psychol. 2017;125:76–90.
765	38.	Kriegeskorte N, Bandettini P. Analyzing for information, not activation, to exploit
766		high-resolution fMRI. Neuroimage. 2007;38(4):649–62.
767	39.	Hsu Y, Hämäläinen JA, Waszak F. Both attention and prediction are necessary for
768		adaptive neuronal tuning in sensory processing. Front Hum Neurosci.
769		2014;8(March):152.
770	40.	Lieder F, Stephan KE, Daunizeau J, Garrido MI, Friston KJ. A Neurocomputational
771		Model of the Mismatch Negativity. PLoS Comput Biol. 2013;9(11).
772	41.	Tiitinen H, May P, Reinikainen K, Näätänen R. Attentive novelty detection in humans
773		is governed by pre-attentive sensory memory. Nature. 1994;372(6501):90–2.
774	42.	Wyart V, Nobre AC, Summerfield C. Dissociable prior influences of signal probability
775		and relevance on visual contrast sensitivity. Proc Natl Acad Sci. 2012;109(9):3593–8.
776	43.	Rao RPN. Bayesian inference and attentional modulation in the visual cortex.
777		Neuroreport. 2005;16(16):1843–8.
778	44.	Kleiner, M., Brainard, D., Pelli, D., Ingling, A., Murray, R., & Broussard C. What's
779		new in Psychtoolbox-3. Perception. Perception. 2007;36(14):1.
780	45.	Watson AB, Pelli DG. Quest: A Bayesian adaptive psychometric method. Percept
781		Psychophys. 1983;33(2):113–20.
782	46.	Chaumon M, Bishop DVM, Busch NA. A practical guide to the selection of
783		independent components of the electroencephalogram for artifact correction. J
784		Neurosci Methods. 2015;250:47–63.
785	47.	Brouwer GJ, Heeger DJ. Decoding and Reconstructing Color from Responses in
786		Human Visual Cortex. J Neurosci. 2009;29(44):13992–4003.
787	48.	Mostert P, Kok P, Lange FP De. Dissociating sensory from decision processes in
788		human perceptual decision making. Sci Rep. 2015;(December):1–13.
789		

Supplementary Figures

Fig S1. Event-related potentials (ERPs) and mismatch responses (MMRs). **(A)** ERPs at selected
electrodes, shown separately for each condition. Bars underneath each plot indicate time points at
which there was a significant main effect of attention (solid grey bar), significant main effect of
prediction (solid black bar), or a significant interaction between attention and prediction (dotted black
bar) at the plotted electrode. **(B)** Classic MMR (deviants - standards) and genuine MMR (deviants –
controls) at selected electrodes, plotted separately for each level of attention. Green and yellow lines
denote the classic MMR and genuine MMR, respectively; solid and dashed lines denote attended and
ignored stimuli, respectively. Bars underneath each plot indicate timepoints at which there was a
significant MMR in the corresponding condition, at the plotted electrode. Attended deviants were
significantly different from attended standards (39 – 504 ms, cluster-corrected p < .001) and attended
controls (172 – 550 ms, cluster-corrected p < .001). Ignored deviants were significantly different from
ignored standards (47 – 438 ms, cluster-corrected p < .001) and ignored controls (285 – 461 ms,
cluster-corrected p = .001) **(C-I)** Topographies of effects collapsed across time points between 200
and 300 ms. Asterisks and dots denote electrodes with larger, or smaller responses, respectively, in
at least 25% of the displayed time points. **(C)** Main effect of attention (attended – ignored). **(D)** Classic
MMR (deviants – standards). **(E)** Genuine MMR (deviants - controls). **(F)** Classic MMR during the
grating task (attended deviants – attended standards). **(G)** Classic MMR during the dot task (ignored
deviants – ignored standards). **(H)** Genuine MMR during the grating task (attended deviants –
attended controls). **(G)** Genuine MMR during the dot task (ignored deviants – ignored standards).

Fig S2. Independent main effects of attention and prediction on orientation response profiles, showing
standards, deviants, and controls. **(A)** Main effect of attention on orientation response profiles. The
amplitude of attended gratings was larger than that of ignored gratings (219 - 550 ms, cluster-
corrected *p* = .001). Shading denotes standard error of the mean. The black bar along the x-axis
denotes significant time points. **(B)** Orientation response profiles, collapsed across significant time
points in **A**. Dots show activation in each of the nine modelled orientation channels. Curved lines
show the functions used to quantify the amplitude and concentration of orientation-tuned responses
(fitted to grand average data for illustrative purposes). **(C)** Main effect of prediction on orientation
response profiles (black bar along the x-axis denotes significant time points, 324 – 550 ms, cluster-
corrected *p* < .001). The amplitude of standards was reduced relative to both deviants and controls.
(D) Orientation response profiles, collapsed across significant time points in **C**. **(E)** Interaction
between attention and prediction on orientation response profile amplitude. Time-courses show the
effect of attention (attended – ignored) on each stimulus type. **(F)** Orientation response profiles,
collapsed across time points in the non-significant but trending cluster in **E** (414 - 481 ms, not
displayed, cluster-corrected *p* = .093).

Fig S3. Residual sum of squares (RSS) for exponentiated cosine functions fitted to generalised
mismatch response profiles (*Fig 5*). Note the high RSS values along the x-axis beginning at 200 ms,
indicating that the apparent generalisation of spatial maps trained at stimulus onset to later times in
the epoch (*Fig 5*, red patch along the x-axis) was likely due to noise.