Modular structure of human olfactory receptor codes reflects the bases of odor perception

Ji Hyun Bak[1]**, Seogjoo J. Jang**[2,3]**, and Changbong Hyeon**[1,*]

[1]Korea Institute for Advanced Study, Seoul 02455, Korea; [2]Department of Chemistry and Biochemistry, Queens College, City University of New York, New York 11367, USA; [3]PhD programs in Chemistry and Physics, and Initiative for Theoretical Sciences, Graduate Center, City University of New York, New York 10016, USA; [*]Correspondence: hyeoncb@kias.re.kr

The circuits of olfactory signaling are reminiscent of complex computational devices. The olfactory receptor code, which represents the responses of receptors elicited by olfactory stimuli, is effectively an input code for the neural computation of odor sensing. Here, analyzing a recent dataset of the odorant-dependent responses of human olfactory receptors (ORs), we show that the space of human olfactory receptor codes is partitioned into a modular structure where groups of receptors are "labeled" for key olfactory features. Our analysis reveals a low-dimensional structure in the space of human odor perception, with the receptor groups as the bases to represent major features in the perceptual odor space. These findings provide a novel evidence that some fundamental olfactory features are already hard-coded at the level of ORs, separately from the higher-level neural circuits.

INTRODUCTION

Olfaction is a sensory process that captures environmental signals by detecting molecular stimuli through a repertoire of olfactory receptors (ORs). Although the full processing of olfactory information is realized in the complicated neural circuits [1], the first step of olfactory sensing involves a selective binding of odorants to the cognate ORs, which is biochemical in nature [2]. The binding elicits an array of downstream responses in the corresponding olfactory receptor neurons (ORNs) [3]. The response pattern encoded into ORs or ORNs, termed the olfactory *receptor code* [4], provides the first neural representation of an odor and is essential in the early stage of olfactory sensing.

Lying at a crucial juncture in the flow of olfactory information, the receptor code bridges between the molecular and neural spaces. An olfactory stimulus in the *molecular space*, representing the physiochemical properties of the odorants, is translated into the *receptor code space* to form an "input code". The information is then processed through the higher-order *neural spaces*, and eventually evokes the sense of smell that constitutes the *perceptual odor space* (see Fig. 1). Recent insights into the processing of olfactory

information were gained mostly based on the olfactory sensing of non-human species [5–7] or through theoretical studies [8, 9]. A separate branch of research attempts to relate the molecular space directly with the perceptual odor space [10, 11]. However, the goal of understanding the principles of olfactory computation in humans faces a fundamental difficulty due to our limited access to the neural circuitry in the human brain.

Here, we show that a critical progress can still be made by a systematic analysis of the receptor code space. Whereas the OR repertoire is known to encode the input signal from odorants like a piano keyboard that combinatorially produces a variety of musical chords [4], it may be further "formatted" to facilitate the processing of relevant information, perhaps by appropriately reflecting the structure of the perceptual odor space. Specifically, we analyze a set of receptor codes for different odorants, extracted from the biochemical measurement of downstream responses of the human ORs [12–14]. Because the receptor code is implemented by the many-to-many pairwise interaction between odorants and ORs [4, 15], we treat the interaction of each odorant-receptor pair as either "on" (responding) or "off" (not responding), and analyze the binary pattern of pairwise interaction, considering it a zeroth-order representation of the receptor code. Our analysis of overlap between distinct receptor codes (receptor code redundancy) reveals the intrinsic structure of the human receptor code space, which is also correlated with the set of coarse-grained features in the perceptual odor space. This suggests that the processing of olfactory information is already at work in the receptor space.

RESULTS

We present a quantitative analysis of the pattern of odorant-receptor interactions, employing a dataset that reports the responses of 303 receptors against 89 odorants [14]. The state of all $N = 303$ receptors can be represented in terms of an N-dimensional binary vector $\mathbf{y}$, where $y_i = 1$ if the i-th receptor is "on", and $y_i = 0$ if it is "off". For a given odor $\mathbf{x}$, the corresponding *receptor code* $\mathbf{y}$ represents

Figure 1: **Schematic of olfactory information flow.** The *molecular space*, representing physiochemical features of odorant molecules, is first recognized by OR repertoire and encoded into the *receptor code space*. The information stored in the receptor codes is modified while it goes through the higher-level *neural spaces* and finally projected on the *perceptual odor space*, and sensed as a smell.

the odor $\mathbf{x}$ in the N-dimensional binary receptor code space.

We collected all 535 pairwise interactions reported in the dataset, including 60 de-activations [16], and visualized the receptor codes in the form of an interaction network (Fig. 2a). In this interaction network, each node is either an odorant or a receptor, and each edge connects an interacting odorant-receptor pair. For a more detailed version of the interaction network with varying parameters, see Fig. S1.

Interaction network reveals odorant hubs with non-redundant receptor codes

In the odorant-OR interaction network (Fig. 2a), the number of edges attached to an odorant node indicates the number of receptors that recognize this odorant. We call this number the *degree* of the odorant node, and denote it by k_λ, where λ is the index for the odorant (also see Methods).

We observe two properties from the statistics of odorant degrees. First, the receptor-space representation of single odorants is sparse: On average, an odorant is recognized by only 6 ($\langle k \rangle \simeq 6$) out of $N = 303$ receptors, which amounts to 2% of the receptor space. The sparsity observed in the network is consistent with previous reports from the ORN responses [17, 18]. Second, the degrees of the odorants in the dataset are non-uniformly distributed with a heavy tail, which can be approximately fitted to $P(k) \sim k^{-\alpha}$ with $\alpha \approx 0.9$ (Fig. 2b). Such distribution allows us to identify a small number of high-degree odorant "hubs". The six highest-degree hub odorants are labeled in Fig. 2a. It is worth noting that the receptor codes for the hub odorants are highly non-redundant with one another (Fig. 2c); among the six highest-degree odorants, 10 out of all 15 pairs have completely disjoint sets of receptor codes. In particular, despite significant similarity in chemical structures, there is no co-activated OR between eugenol and eugenol acetate, which differ in a single functional group (hydroxy group versus acetate in the

aromatic ring). The overlap of receptor codes among the hub odorants is significantly smaller than what is expected from a random mixture of odorants whose receptor codes cover the same number of receptors ($p < 0.02$; also see Methods and Fig. S3).

We introduce an idea of *receptor code redundancy*, a quantitative measure of (dis-)similarity between the olfactory responses of two distinct odorants. If two odors have exactly the same receptor codes, they are perceived as the same olfactory signal. We hypothesize that two odors are poorly distinguishable when their receptor codes have a higher redundancy. For example, consider a discriminatory task where the goal is to detect a target odorant in the presence of a constant background odor [19, 20]. When there was no background odor, the signal would elicit responses in $|\mathbf{y}_{\text{targ}}|$ receptors, where $\mathbf{y}_{\text{targ}}$ is the receptor code for the target odorant. But when some receptors also respond to the background, $\mathbf{y}_{\text{bg}}$, the states of the overlapping receptors would not change upon the addition of the target odorant; the receptor code overlap $|\mathbf{y}_{\text{targ}} \cap \mathbf{y}_{\text{bg}}|$ reduces the effective size of the response (also see Fig. 2d-e). Therefore we define the receptor code redundancy in terms of the fraction $\chi = |\mathbf{y}_{\text{targ}} \cap \mathbf{y}_{\text{bg}}| / |\mathbf{y}_{\text{targ}}|$. If this fraction is small, as in Fig. 2d, the target odorant is deemed unambiguously detected even in the presence of the background odorant.

Taken together, the single-odorant representation in the receptor space is sparse and non-uniform, giving rise to high-degree "hub" odorants. The receptor code is almost non-redundant among these hub odorants, whereas the odorants that have a greater receptor code redundancy with a hub odorant are grouped around it. As presented below, analysis of the receptor code redundancy enables us to decipher the structure of the receptor code space more quantitatively.

Figure 2: **Odorant-receptor interaction network and receptor codes.** **(a)** The odorant-receptor interaction network that visualizes all the interactions between 89 odorants (blue squares) and 303 receptors (orange circles) from the dataset [14]. An edge is drawn when odorant and receptor is interacting. Node size reflects the degree; six highest-degree odorants are marked. Also see Fig. S1 for an extended display with all odorant labels, and with edge attributes for pairwise interaction properties. **(b)** The histogram of odorant degrees. The degree distribution is fitted to $P(k) \sim k^{-\alpha}$ with $\alpha = 0.9$ ($R^2 = 0.74$ from a linear regression of $\log P(k)$ vs. $\log k$), and has an average value $\langle k \rangle \simeq 6$ (also see Fig. S2). **(c)** The overlaps between the receptors codes for the six hub odorants identified in **a** (also see Fig. S3). **(d-e)** Illustration of the idea of receptor code redundancy. The first two columns show two equivalent representations of the receptor code space, as an interaction network and as a set of binary vectors. We consider the receptor code redundancy of a target odorant (blue) with respect to a background odorant (gray). In the third column, the receptor code redundancy is illustrated with Venn diagrams of interacting receptors. The redundancy of adding the target odorant in the presence of the background odorant is represented by the relative size of overlap (striped area) with respect to the total size of target signal (blue-shaded area). Although the number of overlapping receptors is the same in both cases, the normalized redundancy is smaller in **d** (two out of five) than in **e** (two out of three). In the last column, the interaction network is projected to a co-activation graph of receptors.

Figure 3: **Schematics for the partitioning of receptor code. (a)** Given an interaction network with particular statistics of the hub odorants, **(b)** the modular structure is revealed more clearly in the co-activation pattern of receptors. **(c)** We characterize the local structure from the receptor groups around the odorant hubs, and **(d)** merge the local groups to obtain the best partitioning of the receptor code. Also see Fig. S4 for a more detailed illustration.

The receptor code space is naturally partitioned to show a modular structure

The grouped structure is better manifested when the interaction network is projected to the space of receptors. Here we consider the *co-activation graph* of receptors, which inherits all receptor nodes in the original interaction network; two receptor nodes are connected by an edge if they share a common odorant in the original network (Fig. 2d-e, last column). Of particular interest in the co-activation graph are the "receptor *cliques*", or the groups of receptors that are co-activated by the same odorants. Because each pair of receptors interacting with a shared odorant λ is connected in the co-activation graph of receptors, the set of all receptors that interact with a given odorant always form a clique. Given the particular structure of the interaction network, with hub odorants with largely non-redundant receptor codes (Fig. 3a), the co-activation graph of receptors is bound to have large and mostly non-overlapping cliques that are associated to the hub odorants (Fig. 3b). We use the receptor cliques to *partition* the receptor space into non-overlapping groups, such that each receptor group is associated to a shared odorant; when a receptor is a part of more than one receptor clique, it is assigned to the larger clique (Fig. 3c).

The receptor groups can be used to group odorants based on their receptor codes. The idea is to construct odorant groups such that an odorant λ belongs to an odorant group Λ if its receptor code redundancy with respect to the group Λ, $\chi_{\lambda|\Lambda} = |\mathbf{y}_\lambda \cap \mathbf{y}_\Lambda| / |\mathbf{y}_\lambda|$, is large (see Methods). First, we used the receptor groups to determine the reference receptor codes for odorant groups ($\mathbf{y}_\Lambda$'s). Specifically, for each receptor group Λ (note that the group index is shared between the receptors and the odorants), we make a binary vector $\mathbf{y}_\Lambda$ such that $[\mathbf{y}_\Lambda]_i = 1$ if and only if receptor i belongs to the group Λ. Then we assigned each odorant to the group Λ where the receptor code redundancy $\chi_{\lambda|\Lambda}$ is maximized. This results in a simultaneous partitioning of odorants and receptors (Fig. 3d, local groups).

The local groups emerge naturally from the particular statistics of the receptor codes with hub odorants, and capture the local co-activation pattern; receptors are grouped together if they are co-activated by the same odorant. If we were to characterize the overall structure of the receptor code space in terms of the groups, however, the pairs that are *not* grouped together also carry important information. In our case, a grouping is "good" if receptors in the same group respond to the same sets of odorants, *and* receptors in different groups to different odorants. Now we step further to obtain an optimal grouping of the receptor code space based on the co-activation patterns: we carry out a *secondary* grouping of the receptors by merging the *primary* groups obtained above by identifying receptor cliques. We merge a pair of primary groups when their overlap in the co-activation matrix is larger than a threshold (see Methods for details), where the threshold for merging is determined to maximize the goodness of grouping (Fig. S5). Because we partition the odorants and the receptors simultaneously, a merging of receptor groups automatically leads to a merging of the corresponding odorant groups (Fig. 3d).

Application of the grouping procedure to the human olfactory receptor codes results in the sorted interaction matrix in Fig. 4, where each row represents the receptor code for a given odorant. The rows and columns of the interaction matrix are sorted according to the orders in the respective odorant/receptor groups (Fig. 4a-b). The interaction matrix has a roughly block-diagonal form (Fig. 4c), with much less significant contributions from the off-diagonal elements. Notice that we have already arranged the interaction network layout to represent a grouped structure, which is visualized more clearly in Fig. 5, where colored territories (Groups 1–6) represent the best partitioning of the receptor code space. The feasibility of grouping reflects a special structure of the receptor code; such clear grouping is not obtained from a random network with the same degree statistics. Specifically, we randomize the interaction matrix while preserving (i) the number of interactions, (ii) the number of interactions for each odorant (degree) and (iii) the primary grouping structure. In all three cases, it was highly unlikely to find a grouping as good as or better than what we observed from the human receptor code data ($p \leq 0.002$; see Methods and Fig. S6).

Figure 4: **Simultaneous partitioning of odorant and receptors, based on the co-activation pattern and the receptor code redundancy.** The primary and secondary groups are shown for **(a)** the odorants and **(b)** the receptors, where the indices are simultaneously sorted by the group rank. Also see Fig. S5 and Fig. S6 for validations. **(c)** The rows and columns of interaction matrix is consequently sorted by the odorant and receptor indices. Each row represents the receptor code for the corresponding odorant. The six largest secondary groups are colored across all panels. Diagonal-block shades in the interaction matrix are added for better visualization of the simultaneous partitioning of odorants and receptors. In **(a)**, odorants with odor qualities consistent with the characteristic olfactory feature of the corresponding secondary group (plant-like for Group 1; animal-like for Groups 2 and 6; culinary for Groups 3, 4 and 5) are marked with asterisks. Also see Table S1.

Group 1
Group 4
Group 5
Group 3
Group 6
Group 2

Figure 5: **Territories in the odorant-receptor network.** The six largest global groups, ranked by the number of receptors in the group, are shown in distinct colors. The sub-structures (local groups), if any, are also shown in lighter shades.

Odorants in the same group tend to carry similar olfactory features

Our analysis so far only concerned the receptor codes for the test odorants; we did not use any other information about the odorants. On the other hand, because the dataset was constructed to include those odorants that were considered in previous psychology studies [13, 14], each test odorant has a known perceptual quality; i.e., how it smells to human.

It turns out that the two hub odorants in the largest receptor-code-based group (Group 1) represent the two sub-classes of plant-related odors: the characteristic "green" odor of fresh-cut grass (cis-3-hexen-1-ol) and the characteristic "floral" odor that is encountered in many natural essential oils (geranyl acetate). Moreover, there are many other odorants in Group 1 that belong to similar perceptual categories, namely green (phenyl acetaldehyde, sandalwood, terpineol); floral (linalool, lilial, lyral, anisaldehyde); and minty (methyl salicylate, spearmint, and the carvones). In Group 2, all three hub odorants are related to the body odor. Androstenone and androstadienone (the "human pheromone") are contained in sweat or saliva; butyric acid with its characteristic sweaty smell is naturally formed in the human body by fermentation, and is

also found in milk and butter. Among the smaller-degree odorants, heptanoic acid carries a rancid sweaty odor, and 2-methyl-1-propanethiol is associated with meaty or beer-like flavors. In Groups 3, 4 and 5, we find the ingredients of culinary spices. The two hub odorants in Groups 3 and 4 are the major constituents of clove oil (eugenol and eugenol acetate); the two hub odorants in Group 5 are common food-flavoring agents (ethyl vanillin and cinnamon). Group 3 includes more spice- or food-related odorants: nutmeg and banana have their well-known flavors, guaiacol is known to give the characteristic flavor to whiskey and roasted coffee, and 2-heptanone is related to the typical smell of gorgonzola cheese.

These observations lead to a hypothesis that, whereas our analysis is based only on the receptor codes and their redundancy, it results in a grouping of perceptually similar odorants together. In order to make the idea more quantitative, we labeled each odorant with a coarse-grained *olfactory feature* out of five categories (plant-like, animal-like, culinary, citrus, and others). More specifically, we first labeled the odorants using the eight perceptual odor categories identified from a previous work [21] (the primary odor category), then merged some of the categories that show similar co-occurrence patterns as described below (the secondary odor category); also see Fig. S7c and Table S1. Note that throughout this paper, we will use the term "olfactory features" specifically to refer to the perceptual odor qualities that are labeled by a discrete set of categories. Details of the labeling procedures are described in Methods. As a result, each odorant is assigned two independently determined labels: one for the receptor-code group (the "group") and another for the perceptual odor category (the olfactory "feature"). Similarly as with the receptor-code groups, in this analysis we will consider the secondary odor categories which provide a more parsimonious representation of the perceptual odor space.

We sampled the joint distribution of receptor-code groups and olfactory features in the 89 test odorants, where each odorant is weighted by its degree so that its impact on the receptor space is taken into account (see Methods). We can say that an olfactory feature is *enriched* in a given group if the pair of two labels is observed more frequently in the joint distribution than expected from the marginal distributions of the individual labels. In particular, we quantified their joint enrichment in terms of the weighted log likelihood ratio (Fig. 6a), which sum up to give the mutual information between the two labels (see Methods). We find strong enrichments of plant-like odor in Group 1, animal-like odor in Groups 2 and 6, and culinary (food-related) odor in Groups 3, 4 and 5, supporting the hypothesis stated above. We also find that citrus is enriched in the union of all smaller groups, with the size-ranked group indices 7 and above. We performed the G-test and the chi-squared test to evaluate the statistical significance of the claim, and obtained $p < 0.001$ from both methods ($G = 57.5$ and $\chi^2 = 62.2$ for 24 de-

Figure 6: **Link to the perceptual odor categories. (a)** The joint enrichment between the receptor-code groups and the perceptual odor labels, measured in terms of the weighted log likelihood ratios. Also see Fig. S7. **(b)** The average number of major groups, out of six, that are covered by a random mixture of odorants as the number of odorants is varied (purple). The group coverage was closer to 6 than to 5 at $m \gtrsim 33$. Result is based on 500 independent sampling for each m, and the standard errors are smaller than the line width. If we instead consider up to five groups, the cutoff is $m \gtrsim 25$ (gray).

grees of freedom; see Methods for details).

Groups in the odor space explain the "olfactory white"

Lastly, we show that our results can be connected to the reported phenomenon of "olfactory white" [22], in which human subjects cannot distinguish odor mixtures if more than 30–40 odorants are randomly mixed while spanning the odor space. However, the idea of "spanning the odor space" remains at the level of a qualitative analogy to lower-dimensional sensory modalities such as color vision or tonal audition. In this study, we showed that the olfactory space can be understood in terms of a small number of (six) groups, both at the level of receptor codes and of perceptual features. Now we explore the idea of olfactory white more quantitatively, by asking when the odor space, partitioned in terms of the six major groups identified from the receptor codes, is fully covered by a mixture of odorants.

We sample a random set of m odorants from our test dataset, and count the number of major groups (out of six) with at least one odorant in the sampled set. Repeating the sampling while varying the mixture size m, we examine the average number of groups covered by the mixture (Fig. 6b). It turns out that a random sampling of $m \sim 33$ odorants is just enough to sample each of the 6 major groups at least once, in the sense that the average group coverage is > 5.5. On the other hand, the average receptor coverage (the number of receptors that recognize at least one odorant in the mixture) by a mixture of $m \sim 34$ random odorants is equivalent to the cov-

erage by the 6 hub odorants (Fig. S3b). Therefore, we can say that a random mixture of 30–40 odorants is equivalent to a complete spanning of the odor space (up to the six major groups), in terms of the group coverage (number of bases spanned) as well as in terms of the receptor coverage. Our characterization of the human olfactory space, in terms of the receptor-code groups, offers a quantitative account for the number of random odorants needed to construct perceptually convergent odor mixtures ("olfactory whites").

DISCUSSION

We discovered a natural partitioning of the receptor code, by identifying groups of olfactory receptors (ORs) with correlated response patterns. The same procedure also identifies groups of odorants with similar receptor codes. Whereas the grouping was performed without any external label other than the receptor codes, we find that odorants in the same group tend to carry similar olfactory features, which indicates the existence of "labeled groups" in the receptor code space. Below we will elaborate this idea and discuss its implications from a broader perspective of human odor perception.

Receptor groups as the bases of perceptual odor space

The presence of perceptually labeled receptor groups implies a low-dimensional nature of olfactory processing. Because the odor space is represented by the response pattern of $N \approx 400$ functional ORs, there are in principle 2^{400} possible OR states, even in the binary regime. But when a group of receptors respond in a correlated way, not all 2^{400} states are equally likely. Therefore, a significant amount of dimensionality reduction is made in the receptor code space. This aligns with the previous ideas involving the effective sparsity of odor space that, despite the apparent high-dimensionality implicated by physiochemical properties of odorants, olfaction is working in a much lower dimension in effect [23–25]; or that the odor space is intrinsically clustered rather than uniform [21, 22].

The effective sparsity of the receptor code space, which may once again propagate to the perceptual odor space, has an analogy to vision. When one says that the natural visual scene is sparse [26], it means that the scene consists of a small number of features, such as lines or edges [27]. Here we take a viewpoint that the coarse-grained *olfactory features* (labeled by a small number of odor categories) are the "lines and edges" of the perceptual odor space, and that receptor groups represent the receptive fields for these features, with correlated response patterns. Whereas feature-extracting coding was thought to be the realm of higher-level neurons [28, 29], here we found a concrete evidence that it already starts at the level of receptors. It remains an open question to study how the encoded information is further organized through the downstream interaction between the OR neurons [30, 31].

Hard-coded labels in the receptor space

Our findings of labeled groups support the idea that primary features of olfactory perception may already be "hard-coded" in the receptor code space [32, 33], enabling innate as well as learned behavioral responses. Indeed, if there exist some basic olfactory features relevant to the core functions of the organism, there is a clear advantage in keeping hard-coded labels for such features: fewer layers would enable a faster information processing [34] that does not require higher-level neural computations. It is also likely that such important features are the most strongly conserved over the course of evolution of the olfactory genome [35]. In fact, most examples of labeled-line receptors in other organisms are coarse-grained discriminators for certain groups of odorants [36, 37], or simply for good versus bad [33, 38], which is arguably the most important axis of odor perception for humans as well [24, 39, 40]. This extends the idea of *labeled lines*, in the sense that a group of receptors maintains a set of dedicated channels for a distinct perceptual feature.

However, we also note that the labeled-lines picture is not a perfect explanation of the data. The grouping of receptor codes is itself noisy (there are false positives and false negatives in the co-activation matrix of receptors), and the perceptual labeling of groups is noisy as well (e.g., there are odorants that belong to Group 2 yet carry plant-like odors). This implies that the receptor code also has signatures of *combinatorial coding*, a flexible point of view that assumes that the collective activities of receptors (rather than the activation of any specific receptor) encodes the odor information. For example, odorants that belong to the same receptor-code groups may carry different perceptual meanings (e.g., whereas all receptors that respond to the odorant 1-octanethiol also respond to cinnamaldehyde, 1-octanethiol smells like sulfur while cinnamaldehyde carries a pleasant, cinnamon-like scent). Our results therefore represent a hybrid between the two coding strategies. This adds to the growing evidence that olfactory coding in most organisms, including humans, are clearly more complicated than the dichotomy between labeled lines and combinatorial coding [41–43], although there are some cases in which one strategy seems to dominate [4, 38].

More on the importance of hub odorants

At the core of our analysis are the hub odorants that elicit responses in the large population of receptors. The hub odorants create an important structure in the receptor space. According to our statistical analysis, the receptor codes for the largest hubs are almost non-redundant, and they "span" the receptor code space. If we take seriously the proposal that structures in the receptor code space represent the features in the perceptual odor space, we may further hypothesize that the hub odorants correspond to the important stimuli in the natural olfactory environment.

On the other hand, the six hub odorants in the dataset are described as the "typical" or "characteristic" odor of certain category, which are also commonly encountered in a human's life. For example, cis-3-hexen-1-ol is recognized as the characteristic grassy smell; geranyl acetate is found in many natural essential oils and carries a floral aroma; butyl acetate and androstenone are found in the human and animal body; eugenol (clove), cinnamon, and ethyl vanillin (vanilla) each represents a characteristic and widely used ingredient for food flavoring.

Taking the observations together, we hypothesize that the receptor code is designed to assign a larger number of receptors to a more *salient* stimulus, whose presence is more strongly correlated with a particular olfactory feature. The existence of salient odorants in the natural odor space is in fact plausible from the biological viewpoint. For example, because the types of odorants produced by the flower is an outcome of evolutionary selection, most flowers have a few common odorants, with their physiochemical properties attracting the pollinating insects [44]. When more salient stimulus is encoded by the response of more ORs, it has the advantage that important olfactory signals (carried by the salient odorants) are detected reliably: i.e., responses are not lost under perturbations in the receptor space, such as the functional loss of certain ORs due to genetic mutation [45, 46]. If the hypothesis was correct, one would be able to predict the saliency of odorants in the natural odor space based on the number of receptors that respond. This opens up a series of problems related to the natural odor statistics. In particular, an interesting problem would be to explore whether the statistical salience has any relationship with the statistics of co-occurrence between odors [47].

Limitations and open problems

Here we briefly discuss the limitations of our current approach, and the related problems for future research.

First of all, our analysis considers a binary approximation of the receptor code space, marking an odorant-receptor pair as "interacting" if there is a response at all. The ultimate understanding of the receptor codes should also incorporate the higher-order effects, such as the dependence on odor concentration [17, 48]; the effect of inverse agonists [49]; or the interaction between different odorants [50]. Only then will it be possible to fully address how the information in the receptor code is collectively processed, by the inter-glomerular interactions [30, 31]; with the temporal effects [51] involving sniffs [52]; or under different abundances of the receptors [53]. As for the concentration dependence, we show that the current framework can be extended by constructing a family of binary interaction networks at varying odor concentrations (Fig. S2). The effect of odorant concentration on receptor code is in principle straightforward to analyze under our odorant-receptor

based framework even for a mixture of odorants at heterogeneous concentrations; however, meaningful investigation of such effect on human olfactory sensing would require a more systematic normalization with respect to the human detection thresholds that are different for the individual odorants [40, 54]. Our work lays down a general framework on which more specific questions like this can be addressed.

Second, in light of the three levels of olfactory processing that we laid out at the beginning (Fig. 1), it is natural to expect that the receptor code space also reflects the chemical properties of the odorants that comprise the molecular space. Although we did not extend our analysis to the molecular space in this work, previous works suggest a correlation between the molecular similarity between pairs of odorants and the similarity of their olfactory responses at the level of OR neurons [12, 17, 48, 55]. Now that we have a low-dimensional characterization of the receptor code space in terms of the groups, an interesting problem would be to investigate the correlation between the receptor-code groups and the chemical properties of the odorants.

Third, whereas our analysis achieved an unprecedented link between the receptor code space and the perceptual odor space, further progress can be made a better characterization of the perceptual space. In particular, we relied on a specific mapping of the test descriptors to the set of reference words that describe the eight perceptual odor categories [21]. This process can be replaced by a more systematic quantification of similarity between the descriptor words, which would require the understanding of the underlying semantic space for olfactory descriptors.

Concluding remarks

A set of concrete messages can be drawn from our study: (i) The existence of odorant groups, or the correlated patterns between the receptor codes, greatly reduces the dimensionality of the receptor code space and allows us to identify coarse-grained olfactory features in the perceptual odor space. (ii) The odorant and receptor groups revealed from our study clarify the balance between the labeled lines and combinatorial coding strategies. The labeled receptor groups on top of non-uniformly distributed receptor codes imply a hybrid strategy, which can be used to leverage both the fidelity of the labeled-line design and discriminative capacity of the combinatorial coding. (iii) Each large group of odorants is described by the coarse-grained olfactory feature (e.g. plant-related, animal-related odor).

In summary, by analyzing the dataset of OR responses, we identified a modular structure inherent in the receptor code space of human olfaction. Insights from these findings could be extended to the broader study of human odor perception and help understand exceptionally diverse data on olfaction in a more systematic manner.

METHODS

Modeling

Network representation of the receptor code space. We analyze the dose-response curves of 535 interacting odorant-receptor pairs, involving 89 odorants and 303 olfactory receptors (ORs), from the dataset of [14]. The interacting odorant-OR pairs were screened from a library of 511 human OR genes [13, 14]; the final number of 303 ORs include only those that respond to at least one odorant in the dataset. The panel of odorants was selected to span the 20-dimensional physiochemical space that explains the variance in mammalian OR responses [12]. The receptors in the dataset, which cover a near-full ($\sim 3/4$) space of known human ORs, can be viewed as the receptor-space representation of the odorant. On the other hand, the set of cognate odorants found for each receptor, which is only a small sampling of the olfactory environment (humans can detect at least $\gtrsim 10^4$ odorants), is not guaranteed to be complete. We note that the dataset also includes several natural odors that are not monomolecular odorants (for example "banana"), which do not exactly fit in our formulation of pairwise odorant-OR interactions. Nevertheless, these are only a minor fraction of the dataset, and we included all reported odors in our analysis.

A graph can be formally written as $G = (V, E)$, where V is the set of all nodes ("vertices") in the graph, and E is the set of all edges. In the binary regime, each edge in E is an unordered pair of nodes in V; this gives a binary graph, which can also be represented in terms of an *adjacency matrix* A, whose (i, j)-th element A_{ij} represents whether there is an edge between the two nodes i and j in the graph. Specifically, the odorant-receptor network is a *bipartite graph*, where each node belongs to either of two node types (either odorants or receptors) and every edge connects one odorant node to one receptor node. If V_O and V_R are the sets of all odorants nodes and the set of all receptors nodes, respectively, each edge in E connects exactly one node in V_O and the other node in V_R. This bipartite structure is cast into the $M \times N$ sub-matrix of the full adjacency matrix, $A_{\lambda i}$, where $N = |V_R|$ is the number of receptor nodes in the network, and $M = |V_O|$ the number of odorant nodes. Each element of the matrix is defined as $A_{\lambda i} = 1$ if and only if there is an edge between odorant λ and receptor i. We call $A_{\lambda i}$ the *interaction matrix*.

Binary vector representation of a receptor code. The receptor code space representation of an odorant, written in a binary vector $\mathbf{y}$, is equivalent to the corresponding row of the interaction matrix. That is, $[\mathbf{y}_\lambda]_i = A_{\lambda i}$, where $[\mathbf{y}]_i$ is the i-th element of vector $\mathbf{y}$.

The union of two binary vectors is defined element-wise as $[\mathbf{y}_1 \cup \mathbf{y}_2]_i = [\mathbf{y}_1]_i \vee [\mathbf{y}_2]_i$, where $\vee$ is the logical "or" operation between two binary variables. Similarly, the intersection is defined as $[\mathbf{y}_1 \cap \mathbf{y}_2]_i = [\mathbf{y}_1]_i \wedge [\mathbf{y}_2]_i$, where $\wedge$ is the logical "and" operation. We also define the difference of two binary vectors as $[\mathbf{y}_1 \setminus \mathbf{y}_2]_i =$

$[\mathbf{y}_1]_i \wedge \neg [\mathbf{y}_2]_i$, where $\neg$ is the logical "not" operation. For the union and the intersection, the definitions easily extend to more than two binary vectors.

Degree of an odorant. The *degree* of a node is the number of edges attached to it, or (when there is no loop) the number of other nodes that are connected to it. It is useful to define the *size* of a binary vector as the number of its non-zero elements: $|\mathbf{y}| = \sum_{i=1}^{N} [\mathbf{y}]_i$.

The degree of an odorant node is the number of receptor nodes connected to it:

$$k_\lambda = \sum_{i \in V_R} A_{\lambda i} = |\mathbf{y}_\lambda|, \quad \lambda \in V_O. \tag{1}$$

In the current study, we primarily consider the odorant degree, or how broadly (or narrowly) an odorant is "targeting" the receptors. This breadth of interaction for the odorant is well-defined, because there is a finite number of olfactory receptors. The dataset in [14] covers a majority of the known (functional) human olfactory receptor repertoire: 303 out of ~ 400 ORs. Our approach has advantage over other studies that considered whether a given receptor is "narrowly tuned" or "broadly tuned" across different odors, which is hard to quantify without a good metric of the odor space.

The degree distribution of odorants, $P_O(k)$, is measured by counting the number of odorants at each degree k. $P_O(k)$ appears approximately straight in the log-log scale, and is fitted to the curve, $P(k) \sim k^{-\alpha}$. However, the fit does not necessarily indicate an underlying distribution that is power-law in a strict sense; we are simply using the power-law dependence to describe the heavy-tailed shape of the degree distribution.

Co-activation graph. The *co-activation graph* is a projection of the original bipartite graph to one of the two node types. For example, the co-activation graph of receptors, $G_R = (V_R, E_{R;O})$, inherits all receptor nodes V_R from the original bipartite graph. Two receptor nodes in the co-activation graph G_R are connected by an edge if there is a common odorant node in the original graph G that is connected simultaneously to both receptors (see Fig. S4a,f). To define the edges, $E_{R;O}$, it is sufficient to define the corresponding adjacency matrix A_R, where $(A_R)_{ij} = 1$ indicates an edge between two receptors i, j in the co-activation graph. We call A_R the *co-activation matrix* of receptors. Each element of the co-activation matrix is given as $(A_R)_{ij} = \bigvee_{\lambda \in V_O} (A_{\lambda i} \wedge A_{\lambda j})$, which indicates whether there is at least one odorant λ for which $A_{\lambda i}$ and $A_{\lambda j}$ are both 1, where $A_{\lambda i}$ is the interaction matrix for the original bipartite graph.

Receptor code redundancy

We define the receptor code redundancy as $\chi = (n_{\text{full}} - n_{\text{eff}})/n_{\text{full}}$, where n_{full} is the full impact of a signal in the absence of redundancy, and n_{eff} is the net effect of the signal under redundancy.

Receptor code redundancy of a target with respect to the background. For a discrimination task of a target odorant λ in the presence of a background odorant μ, the effect of redundancy reduces the net effect of adding λ from $n_{\text{full}} = |\mathbf{y}_\lambda|$ to $n_{\text{eff}} = |\mathbf{y}_\lambda \setminus \mathbf{y}_\mu|$. In this case, the receptor code redundancy is $\chi_{\lambda|\mu} = (|\mathbf{y}_\lambda| - |\mathbf{y}_\lambda \setminus \mathbf{y}_\mu|)/|\mathbf{y}_\lambda| = |\mathbf{y}_\lambda \cap \mathbf{y}_\mu| / |\mathbf{y}_\lambda|$.

Receptor coverage by a mixture of odorants. We can also consider an odor signal that consists of a mixture of odorants. We define its *receptor coverage* as the number of receptors that respond to at least one odorant in the mixture, $n_{\text{union}} = |\mathbf{y}_1 \cup \cdots \cup \mathbf{y}_m|$. We can also count the sum of individual odorant degrees, $n_{\text{sum}} = |\mathbf{y}_1| + \cdots + |\mathbf{y}_m|$. Note that the net receptor coverage n_{union} corresponds to n_{eff}, and the sum of individual coverages n_{sum} to n_{full}, in the above construction (also see Fig. S3a).

Receptor code redundancy in a mixture of odorants. The two numbers, n_{union} and n_{sum}, are different when there are overlaps between the receptor codes for the odorants in the mixture. Therefore, we characterize the net amount of receptor code overlap as $n_{\text{sum}} - n_{\text{union}}$, and define the receptor code redundancy in a mixture as $\chi_{\text{mix}} = (n_{\text{sum}} - n_{\text{union}})/n_{\text{sum}}$.

Odorant mixture test. We selected mixtures of m odorants from the interaction network, either randomly (random mixture), or selecting the highest-degree odorants first (mixture of hubs). For each mixture, we counted the receptor coverage n_{union} and the sum of individual coverages n_{sum}. For the random mixtures, we drew 500 independent samplings at each m; because we tried 90 different values of $0 \leq m \leq 89$, we have 45,000 random mixture samples.

The receptor coverage by the six hub odorants is $n_{\text{union}} = 155$, about half of the receptor space (Fig. S3b). However, its receptor code redundancy is only $\chi_{\text{mix}} = 0.08$. This is much smaller than what is expected from a random-odorant mixture at the same receptor coverage ($\chi_{\text{mix}} \approx 0.23$ using the average counts); none of 105 random mixtures at the fixed receptor coverage $n_{\text{union}} = 155$ had a smaller redundancy ($p < 0.01$). Considering all mixtures with $n_{\text{union}} \leq 155$, we got $p < 0.02$ (317 out of 17340). If we consider all random mixtures and count the samples that are below the red curve in Fig. S3c, we get $p = 0.05$ (2420 out of 45,000), where we note that most of the extreme samples come from the top end of the curves, where the newly added odorants are no longer "hubs". Besides, the average redundancy curves show that the level of redundancy with the six hubs ($\chi_{\text{mix}} \approx 0.1$) is reached already at a receptor coverage of $n_{\text{union}} \approx 70$ in an average random mixture, which corresponds to $m \approx 13$ odorants (Fig. S3c).

We also note that the redundancy curve for the mixture of hubs (Fig. S3c, red) deviates most greatly from the "chance curve" obtained from the random mixtures (gray) when the six hub odorants were selected. This adds support to our focus on the six hub odorants.

Grouping in the receptor code space

We will provide details of the grouping process in three steps: node ranking, primary grouping and secondary grouping. To start, we rank the odorants and receptors in the dataset.

Ranking odorants and receptors by the degrees. Odorants are ranked by their degree of interaction, k (Eq. 1). When there are multiple odorants with the same degree, they are ranked according to the order they are indexed in the original dataset [14]. We call this ordering h_0, such that each odorant λ (where λ may be an arbitrary index) is assigned a unique rank $h_0(\lambda) \in \{1, \cdots, M\}$.

Receptors are ranked by their degree in the co-activation graph. The degree in the co-activation graph represents the number of other receptors that share at least one odorant partner with the given receptor. When there are multiple receptors with the same degree of co-activation, they are ranked according to the order they are indexed in the original dataset [14]. Similarly as for the odorants, we call this ordering g_0, such that each receptor i is assigned a unique rank $g_0(i) \in \{1, \cdots, N\}$.

Primary grouping. We first partition the receptor space into a set of non-overlapping groups, and subsequently use these to classify the odorants based on the receptor code overlap.

In the primary receptor grouping (g_1), receptors are grouped such that each receptor "signs up" to the largest receptor clique it belongs to. Specifically, we assign to each receptor the rank h_0 of the highest-degree odorant it interacts with; in case of ties, we choose odorants of higher ranks (smaller h_0). We re-rank the receptor group index while preserving the order of the associated rank h_0, by assigning the primary group index $I = 1$ to the largest receptor group, and the index $I = 2$ to the next largest group, and so on ($I = 1, 2, \cdots I_{\max}$). This results in a grouping $g_1 : i \mapsto I$ that maps each receptor i to a group index $g_1(i) = I$.

In the primary odorant grouping (h_1), each odorant is assigned to the above-determined receptor group (g_1) to which its receptor code overlaps the most. The primary odorant grouping $h_1 : \lambda \mapsto I$ (or $h_1(\lambda) = I$) is defined by choosing the receptor group of index I, with which the odorant's receptor code ($\mathbf{y}_\lambda$) displays the maximum overlap, namely $I = \mathrm{argmax}_J \chi_{\lambda|J}$. Here, the receptor code overlap of an odorant λ to a receptor group index I is quantified as $\chi_{\lambda|I} = |\mathbf{y}_\lambda \cap \mathbf{y}_I| / |\mathbf{y}_\lambda|$, where the binary vector $\mathbf{y}_I$ represents the receptor code for the group I by having each element $(\mathbf{y}_I)_i = 1$ if $g_1(i) = I$, and $(\mathbf{y}_I)_i = 0$ otherwise. Note that the resulting odorant group indices span through $I = 1, 2, \cdots, I_{\max}$, shared with the receptor group indices.

Secondary grouping. We merge the primary groups based on the amount of co-activation in the receptor code space.

In the secondary receptor grouping (g_2), pairs of primary receptor groups are merged if there is a strong co-activation. For two primary receptor groups I, J, we calculate the amount of co-activation between the two groups, simply in terms of the density of off-diagonal-block contribution in the co-activation matrix A_R:

$$v_{IJ} = \frac{\sum_{i \in I} \sum_{j \in J} (A_R)_{ij}}{\sum_{i \in I} \sum_{j \in J} 1} = \frac{1}{|I| \cdot |J|} \sum_{i \in I, j \in J, i < j} (A_R)_{ij}, \quad (2)$$

where $i \in I$ is a shorthand to indicate that the sum runs over all receptors i such that $g_1(i) = I$. We merge each pair of primary groups I and J whenever their co-activation is stronger than a threshold, i.e., if $v_{IJ} \geq \bar{v}$. Here we used an optimal threshold value of $\bar{v} = 0.15$, where the grouping was most informative (Fig. S5; also see Statistical validation). Note that this is a greedy and transitive grouping. For example, if there are three primary groups I_1, I_2, I_3 such that $v_{I_1 I_2}, v_{I_2 I_3} > \bar{v}$ but $v_{I_3 I_1} < \bar{v}$, then all three are merged together in the secondary grouping; the two groups I_1, I_2 are first combined, then I_3 is also pulled into the group that I_2 belongs to. After performing all pairwise merges, we once again re-rank the resulting group indices while preserving the order. This defines a grouping $G_{12} : I \mapsto I'$ that maps each primary group I to a (re-numbered) secondary group I'. Each receptor i is then assigned a secondary group index $g_2(i) = G_{12}(g_1(i))$.

In the secondary odorant grouping (h_2), pairs of primary odorant groups are merged if there is a strong co-activation. Because the primary grouping was a simultaneous partitioning of odorants and receptors, the above merging operation of receptor groups from $g_1(i)$ to $g_2(i)$ automatically propagates to the odorant groups. Specifically, each odorant λ is assigned a secondary group index $h_2(\lambda) = G_{12}(h_1(\lambda))$.

Labeling with the perceptual odor categories

Descriptor space. The perceptual odor quality of each odorant is characterized by a list of odor descriptors (Table S2). We collected the odor descriptors for the 89 test odorants in the dataset [14], from multiple sources including public databases, academic works and industrial reports (see Table S5 for data sources). In particular, we obtained a majority of odor descriptors from the Good Scents Company Information System [56], using custom scripts for web-scraping.

Let W be the set of all descriptors that appear at least once in our collection. We have $N_W = |W| = 194$ unique descriptor words for the $M = 89$ test odorants in the dataset [14]. We can think of an $M \times N_W$ binary matrix, $\{\tilde{A}_{\lambda w}\}$, such that $\tilde{A}_{\lambda w} = 1$ if odorant λ is described by the word w, and 0 otherwise.

Perceptual odor categories. We adopt the 8 odor categories identified in a previous work [21]. Each category $s \in \{1, 2, \cdots, 8\}$ is defined by a list of reference descriptors, $\bar{W}_s$, provided in Figure 7 in the original paper (also shown in Table S3). For convenience, we also nickname each category with a single representative descriptor: (1) citrus, (2) chemical, (3) minty, (4) floral, (5) fruity, (6)

green, (7) spicy, and (8) animal. The representative nickname for each category was chosen according to our own semantic senses; its only role is to provide an intuitive name by which we can easily refer to the category, and it does not play any further role in the analysis.

Labeling odor descriptors. We first label each descriptor $w \in W$ with a unique perceptual category $s \in \{1, 2, \cdots, 8, 9\}$, where the additional 9th category stands for "unsorted". This defines a map $\tilde{g} : w \mapsto s$. Here we only consider a deterministic categorization of descriptors, such that $p(s|w) \propto \delta_{s,\tilde{g}(w)}$. The mapping is straightforward when the descriptor is directly contained in the reference vocabulary; because $\bar{W}_s$'s are non-overlapping by construction, we can find a unique category s for the descriptor in this case. However, some descriptors do not exactly match with any of the reference words, in which case the mapping requires a sense of similarity between the words in the underlying semantic space.

Here we attempt to make a projection of each descriptor onto the space of reference words. Specifically, for each test descriptor w, we choose a proxy $w' \in \cup_{s'} \bar{W}_{s'}$ from the reference vocabulary that can approximate the descriptor w, and identify the category s for which $w' \in \bar{W}_s$. The extra category "unsorted" is assigned to abstract or ambiguous descriptors [57]. Null descriptors like "odorless" or "weak" are also labeled as unsorted. The proxies were determined manually by the authors using the human sense of the semantic space, and the entire mapping is made available as a supplementary table (Table S4) so that the reader can reproduce and/or judge the procedure.

Labeling odorants. Next, we label each odorant λ with a perceptual category s. To summarize how each odorant is associated with a set of descriptors, we write a conditional probability

$$p(w|\lambda) = \frac{\tilde{A}_{\lambda w}}{\tilde{k}_\lambda}, \qquad \tilde{k}_\lambda = \sum_{w \in W} \tilde{A}_{\lambda w}. \tag{3}$$

This allows us to write $p(s|\lambda) = \sum_{w \in W} p(s'|w) p(w|\lambda)$. For simplicity, we consider a deterministic map that involves a "vote" by all descriptors of each odorant:

$$p(s|\lambda) = \delta_{s,\tilde{h}(\lambda)}, \quad \tilde{h}(\lambda) = \operatorname*{argmax}_{s'} \sum_{w \in W} p(s'|w) p(w|\lambda). \tag{4}$$

In case of ties, we put more weight to the descriptor that was marked as the representative "odor type" in the GoodScents database [56]. Now we have a map $\tilde{h} : \lambda \mapsto s$ that assigns a perceptual odor category s to each odorant λ.

Joint distribution of receptor-code groups and perceptual odor categories. Treating the receptor-code group index s_R and the perceptual odor category index s_W as random variables, we can for-

mally write down their joint probability distribution as:

$$p(s_R, s_W) = \sum_{\lambda=1}^{M} p(s_R|\lambda) p(s_W|\lambda) p_O(j). \tag{5}$$

This is to say that the two group/category indices are *sampled* by the test odorants, where the two grouping maps $p(s_R|\lambda)$ and $p(s_W|\lambda)$ are conditionally independent for a given odorant λ.

Because we already defined the two deterministic maps, we can write down the two conditional distributions as $p(s_R|\lambda) = \delta_{s_R,h(\lambda)}$ and $p(s_W|\lambda) = \delta_{s_W,\tilde{h}(\lambda)}$. The third term, $p_O(\lambda)$, represents the weight to each odorant. If we were to count all odorants equally, we would have used a uniform $p_O(\lambda) = 1/M$. However, we would like a sampling that is aware of the odorant's "weight' in the receptor space, such that an odorant that affects more receptors (a higher-degree odorant) counts more. To this end, we write

$$p_O(\lambda) = \sum_{i=1}^{N} p(\lambda|i) p_R(i) \propto k_\lambda, \tag{6}$$

where $k_\lambda = \sum_{i=1}^{N} A_{\lambda i}$ is the degree of the odorant λ in the interaction network. Note that this approach assumes a uniform $p_R(i) \propto 1$ for the receptors, rather than the odorants. In this case, $p_O(\lambda)$ can be interpreted as the probability that a randomly chosen receptor recognizes the odorant λ. Summarizing, the joint distribution is sampled as

$$p(s_R, s_W) = \frac{\sum_{\lambda=1}^{M} \delta_{s_R,h(\lambda)} \delta_{s_W,\tilde{h}(\lambda)} k_\lambda}{\sum_{\lambda'=1}^{M} k_{\lambda'}}. \tag{7}$$

We can also consider the two marginal distributions, $p(s_R) = \sum_{s_W} p(s_R, s_W)$ and $p(s_W) = \sum_{s_R} p(s_R, s_W)$, and consequently the two conditional distributions, $p(s_R|s_W) \equiv p(s_R, s_W)/p(s_W)$ and $p(s_W|s_R) \equiv p(s_R, s_W)/p(s_R)$.

Statistical validation

Optimal threshold for secondary receptor grouping. In the secondary receptor grouping, our goal was to obtain the best partitioning of the receptors so that the resulting structure captures the co-activation pattern. Because we start from the primary receptor groups as the "units", and work by merging them based on the overlaps, the grouping depends on the threshold $\bar{\chi}$. In the limit where the threshold is too small, most units are merged together and a giant cluster is formed (Fig. S5a). On the other hand, when the threshold is too large, most units stay un-merged, failing to capture the global structure (Fig. S5c). The optimal threshold is where the grouping is most *informative* (see below), in the sense that more strongly co-activating primary groups are merged together in the same secondary group, and non-co-activating groups stay apart (Fig. S5b).

Here we consider our grouping as a binary classifier, where each receptor pair has one of the two real states (either co-activated by an

odorant or not), and one of the two predicted states (either grouped together or not). We count the number of receptor pairs that belong to each of the four outcomes: co-activated and grouped (true positive; TP), co-activated and ungrouped (false negative; FN), non-co-activated and grouped (false positive; FP), and non-co-activated and ungrouped (true negative; TN). We also define the real positive (RP = TP + FN) and the real negative (RN = TN + FP) in the data, and similarly the predictive positive (PP = TP + FP) and the predicted negative (PN = TN + FN) according to the grouping. There are multiple ways to quantify the informativeness of the classifier, but the basic idea is to understand the tradeoff between the type I (FP) and type II (FN) errors. Here we take two common approaches, considering the sensitivity-specificity and the precision-recall tradeoff respectively. The *sensitivity* is defined as the true positive rate TPR = TP/RP, which is also called the *recall*. The *specificity* is defined as the true negative rate TNR = TP/RN. It is also common to write the specificity in terms of the *fall-out*, or the false positive rate FPR = TP/RN with a simple relationship FPR = $1-$TNR. The *precision* is defined as the positive predicted value PPV = TP/PP. Also see Fig. S5d.

To find the optimal grouping in terms of the sensitivity and the specificity, we minimize the sum of squared error, SSE = $\text{FNR}^2 + \text{FPR}^2 = ((1-\text{sensitivity})^2 + (1-\text{specificity})^2)$. This is also graphically equivalent to finding the point that is closest to the upper left corner of the receiver operating characteristic (ROC) plane, which plots the sensitivity versus the $1-$specificity at varying threshold $\bar{\chi}$ (Fig. S5e-f).

Alternatively, we can use the F_β score, another popular quantity defined as the weighted harmonic average of precision and recall [58]:

$$F_\beta = \frac{(1+\beta^2)}{\frac{1}{\text{precision}} + \beta^2 \frac{1}{\text{recall}}} = \frac{(1+\beta^2)\text{TP}}{(1+\beta^2)\text{TP} + (\text{FP} + \beta^2 \text{FN})}.$$
(8)

A larger β puts more weight to the recall (pays more attention to the false negatives), whereas a smaller β puts more weight to precision (more attention to the false positives). Because the actual dataset is strongly imbalanced such that RN > RP, we choose a value of β that penalizes false negatives more heavily [59]. Specifically, we use $\hat{\beta} = \sqrt{\text{RN}/\text{RP}}$, so that the weighted combination becomes $(\text{FP} + \hat{\beta}^2 \text{FN}) \propto ((1 - \text{TNR}) + (1 - \text{TPR}))$. We can also plot the precision-recall curve as the threshold is varied (Fig. S5h-g). In our case, the two optimization conditions (minimum SSE and maximum F_β) are satisfied at the same threshold $\bar{\chi} = 0.15$, which defines the best secondary receptor grouping (Fig. S5f,h).

Shuffling test for receptor-code groups. To test the statistical significance of the observed receptor groups, we compare the result to three null models constructed by shuffling the odorant-receptor interactions. We consider three null models, with shuffling rules that preserve different marginal statistics.

First, we make a full shuffling of the activation matrix, $A_{\lambda i}$, such that the number of non-zero elements (the number of interactions in the network) is preserved (Fig. S6a). This is also equivalent to fixing the average degree of the odorants.

Second, we construct a more constrained null model where the degree distribution is preserved. Specifically, we shuffle each odorant-row of the activation matrix $A_{\lambda i}$ independently, such that each odorant re-connects to the receptors randomly, while the degree is kept fixed (Fig. S6b).

Third, to test the effect of the secondary grouping separately from the primary grouping, we consider a null model that preserves the primary grouping structure (Fig. S6c). For each odorant λ in a primary group $g = h_1(\lambda)$, We shuffle the the set of receptors that belong to the same primary group, $\{i \in \{1, \cdots, N\} \mid g_1(i) = g\}$, and separately shuffle the rest of receptors that belong to all other primary groups, $\{i \mid g_1(i) \neq g\}$ (also see Fig. S6d). But as a result of this shuffling, the goodness of the original primary grouping becomes exaggerated, because shuffling destroys all residual correlation that was not captured by the primary groups. So we add extra randomness to restore the precision of primary grouping as it appears in the original data. We do this by making an appropriate number of *degree-preserving swaps*, as suggested by [60]. The degree-preserving swaps are made in the following way. We randomly choose 2 columns and 2 rows from the activation matrix, which defines a 2×2 binary sub-matrix. If the sub-matrix is either diagonal or anti-diagonal, we replace the sub-matrix with the other form, and count this as one swap. It is clear that such a swap preserves both the column-sum and the row-sum of the matrix. If the chosen sub-matrix has neither of the two forms, no action is made, and we proceed to sample a new sub-matrix. The two goodness measures are simultaneously restored to the levels that correspond to the original primary grouping, with 40 extra swaps (Fig. S6d).

Under each null model, we draw multiple shuffles to sample the distributions of the test statistics, in this case the two goodness measures SSE and F_β. For each shuffle of the interaction data, we constructed the corresponding receptor co-activation matrix, and applied the grouping algorithm at varying overlap threshold $\bar{\chi}$. We chose the best grouping results as the test statistics for the sample, either at minimum SSE (Fig. S6e-f) or at maximum F_β (Fig. S6g-h). The two measures were optimized separately, and may correspond to different optimal thresholds for the same shuffled sample. This procedure allows us to estimate the (one-tailed) p-value, which indicates the probability to have a grouping result from a shuffled dataset that is as good as or better than what we observe from real data. Because there was only up to 1 out of 500 shuffled samples that clusters better than the original dataset, we can say that $p \leq 0.002$ (Fig. S6i-j).

Joint enrichment between receptor-code groups and perceptual odor categories. To quantify the correlation between the receptor-code groups s_R and the perceptual odor categories s_W, we consider the likelihood ratio $p(s_R, s_W)/p(s_R)\,p(s_W)$. If this ratio is larger than 1 for a given (s_R, s_W) pair, it indicates an over-representation (enrichment) of the pair in the dataset, compared to the expectation from the null hypothesis that the two labels are completely uncorrelated (Fig. S7a). Note that the likelihood ratio can also be interpreted as the enrichment of one label given another, if re-written as $p(s_R|s_W)/p(s_R)$ or $p(s_W|s_R)/p(s_W)$.

The weighted sum of the log likelihood ratios is the mutual information:

$$I(s_R; s_W) = \sum_{s_R, s_W} p(s_R, s_W) \log \frac{p(s_R, s_W)}{p(s_R)p(s_W)}; \qquad (9)$$

it is also equivalent to the Kullback-Leibler (KL) divergence, $D_{KL}[p(s_R, s_W)\|p(s_R)p(s_W)]$. This sum quantifies the amount of information that is lost by incorrectly describing the observed joint distribution $p(s_R, s_W)$ with the null hypothesis $p(s_R)p(s_W)$.

It is also useful to look at each pair's contribution to the mutual information, which has the form of a weighted log likelihood ratio $\rho(s_R, s_W) = p(s_R, s_W) \log[p(s_R, s_W)/p(s_R)p(s_W)]$. For the purpose of understanding which pairs are more significantly enriched, we find it more informative to consider the weighted log likelihood ratio (Fig. S7b) than the log likelihood ratio alone (Fig. S7a). The weighting properly takes into account that the log likelihood adds up with independent observations. We will call $\rho(s_R, s_W)$ the *joint enrichment* between the receptor-code groups s_R and the perceptual odor categories s_W.

Merging the categories for dimensionality reduction. Because the amount of information that can be drawn from data is fixed, it is important that we keep only as many groups/categories as relevant to our conclusion. In the receptor code space, we considered the six largest groups and treated the rest as a single extra group (6 degrees of freedom). In the perceptual odor space, we looked at which of the 8 odor categories have similar enrichment patterns (Fig. S7b), and also used the common-sense semantic knowledge, to merge the plant-like (green, floral, minty, chemical) and the culinary (spicy, fruity) labels together (Fig. S7c). The grouping of "chemical" with the plant-like category is based on the correlations in the enrichment pattern, although we should note that there is only one odorant in our dataset (quinoline) that is labeled as "chemical" according to our procedure. This results in a set of reduced perceptual odor categories with 4 degrees of freedom, labeled as plant-like, animal-like, culinary, citrus and others, which gives a more parsimonious classification of the perceptual odor space while preserving the enrichment pattern. For convenience, we distinguish the two set of labels with the names "Category 1" (the primary categories adopted from [21]) and "Category 2' (the secondary categories after dimensionality reduction). The secondary category for the perceptual quality of an odorant is determined by its primary category (Table S1).

Evaluating the significance of group labeling. We used the G-test to evaluate the statistical significance of our finding that the receptor-code groups can be labeled with perceptual odor categories. The G-test statistic is defined as $G = 2\sum_{s_R, s_W} O_{s_R, s_W} \log(O_{s_R, s_W}/E_{s_R, s_W})$, where O_{s_R, s_W} and E_{s_R, s_W} are the observed and the expected number of odorants with the pair of labels (s_R, s_W). By construction, we have $O_{s_R, s_W} = Mp(s_R, s_W)$ and $E_{s_R, s_W} = Mp(s_R)p(s_W)$, where M is the number of test odorants (observations). This gives $G = 2M \cdot D_{KL}$. We can calculate the p-value for this joint classification, by assuming that G approximately follows the chi-squared distribution with the appropriate degrees of freedom. In this case, the number of degrees of freedom for the chi-squared distribution is d.o.f. $= (|S_R|-1)(|S_W|-1)$, where $|S_R|$ is the number of distinct receptor-code groups, and $|S_W|$ is the number of distinct odor categories. Using the primary odor categories, we get $G = 68.9$, which translates to $p = 0.03$ with 48 degrees of freedom (Fig. S7b). Using the secondary odor categories, we get $G = 57.5$ and $p < 0.001$ with 24 degrees of freedom (Fig. S7d).

To further validate our use of the G-test, we also compared the result with the chi-squared test, for which the test statistics is defined as $\chi^2 = \sum_{s_R, s_W} (O_{s_R, s_W} - E_{s_R, s_W})^2/E_{s_R, s_W}$. (Note that this χ^2 should not be confused with the overlap measure χ or the overlap threshold $\bar{\chi}$ in our analysis of the receptor code space.) We get $\chi^2 = 71.4$ and $p = 0.02$ using the primary odor categories (Fig. S7e), and $\chi^2 = 62.2$ and $p < 10^{-4}$ using the secondary categoreis (Fig. S7f). Both tests give small and consistent p-values, especially with the secondary odor categories with reduced degrees of freedom. This confirms the statistical significance of our findings, in which each major group in the receptor code space is associated with a characteristic label in the perceptual odor space.

Data availability

The list of test odorants are provided in two sets of supplementary tables, with receptor-code groups and perceptual odor categories (Table S1) and with raw odor descriptors (Table S2) respectively. The list of reference words for each perceptual category [21] is provided as Table S3. Our labeling of each perceptual odor descriptor is shown in Table S4. Data sources are listed in Table S5.

Formatted data files to reproduce the network representation of odorant-receptor interaction with full attributes for each node and edge (as .cyjs and .cys files, to open in Cytoscape) are freely available at `https://github.com/jihyunbak/ORnetwork`.

Code availability

The Matlab code for the grouping analysis, along with associated documentation, is available under the MIT license at `https:`

//github.com/jihyunbak/ORnetwork.

ACKNOWLEDGMENTS

We thank the KIAS Center for Advanced Computation for providing computing resources. This study was partly supported by the grants from the National Research Foundation of Korea (NRF-2018R1A2B3001690) (C.H.), and the National Science Foundation (CHE-1362926) (S.J.J).

AUTHOR CONTRIBUTIONS

J.H.B., S.J.J. and C.H. designed the projects. J.H.B. and C.H. performed research and analyzed the data. J.H.B., S.J.J. and C.H. wrote the paper.

COMPETING INTERESTS

The authors declare that they have no competing interests.

SUPPLEMENTARY MATERIALS

Supplementary Materials include seven figures and five tables, with accompanying text. All items are available at the end of this manuscript in the following order.

References

[1] Su, C. Y., Menuz, K., & Carlson, J. R. Olfactory Perception: Receptors, Cells, and Circuits. *Cell* **139**, 45–59 (2009).

[2] Block, E., Jang, S., Matsunami, H., Sekharan, S., Dethier, B., et al. Implausibility of the vibrational theory of olfaction. *Proc. Natl. Acad. Sci. U.S.A.* **112**, E2766–E2774 (2015).

[3] DeMaria, S & Ngai, J. The cell biology of smell. *J. Cell. Biol.* **191**, 443–452 (2010).

[4] Malnic, B., Hirono, J., Sato, T., & Buck, L. B. Combinatorial Receptor Codes for Odors. *Cell* **96**, 713–723 (1999).

[5] Stevens, C. F. What the fly's nose tells the fly's brain. *Proc. Natl. Acad. Sci. U.S.A.* **112**, 9460–9465 (2015).

[6] Dasgupta, S., Stevens, C. F., & Navlakha, S. A neural algorithm for a fundamental computing problem. *Science* **358**, 793–796 (2017).

[7] Roland, B., Deneux, T., Franks, K. M., Bathellier, B., & Fleischmann, A. Odor identity coding by distributed ensembles of neurons in the mouse olfactory cortex. *eLife* **6**, e26337 (2017).

[8] Zhang, Y & Sharpee, T. O. A robust feedforward model of the olfactory system. *PLoS Comp. Biol.* **12**, 1–15 (2016).

[9] Zwicker, D., Murugan, A., & Brenner, M. P. Receptor arrays optimized for natural odor statistics. *Proc. Natl. Acad. Sci. U.S.A.* **113**, 5570–5575 (2016).

[10] Keller, A., Gerkin, R. C., Guan, Y., Dhurandhar, A., Turu, G., et al. Predicting human olfactory perception from chemical features of odor molecules. *Science* **355**, 820–826 (2017).

[11] Poivet, E., Tahirova, N., Peterlin, Z., Xu, L., Zou, D.-J., et al. Functional odor classification through a medicinal chemistry approach. *Science Adv.* **4**, eaao6086 (2018).

[12] Saito, H., Chi, Q., Zhuang, H., Matsunami, H., & Mainland, J. D. Odor Coding by a Mammalian Receptor Repertoire. *Science Signaling* **2**, ra9–ra9 (2009).

[13] Mainland, J. D., Keller, A., Li, Y. R., Zhou, T., Trimmer, C., et al. The missense of smell: functional variability in the human odorant receptor repertoire. *Nat. Neurosci.* **17**, 114–120 (2013).

[14] Mainland, J. D., Li, Y. R., Zhou, T., Liu, W. L. L., & Matsunami, H. Human olfactory receptor responses to odorants. *Scientific Data* **2**, 150002 (2015).

[15] Araneda, R. C., Kini, A. D., & Firestein, S. The molecular receptive range of an odorant receptor. *Nat. Neurosci.* **3**, 1248 (2000).

[16] Bak, J. H., Jang, S. J., & Hyeon, C. Implications for human odor sensing revealed from the statistics of odorant-receptor interactions. *PLoS Comp. Biol.* **14**, 1–16 (2018).

[17] Hallem, E. A & Carlson, J. R. Coding of Odors by a Receptor Repertoire. *Cell* **125**, 143–160 (2006).

[18] Lin, D. Y., Shea, S. D., & Katz, L. C. Representation of natural stimuli in the rodent main olfactory bulb. *Neuron* **50**, 937–949 (2006).

[19] Mathis, A., Rokni, D., Kapoor, V., Bethge, M., & Murthy, V. N. Reading out olfactory receptors: Feedforward circuits detect odors in mixtures without demixing. *Neuron* **91**, 1–19 (2016).

[20] Rokni, D., Hemmelder, V., Kapoor, V., & Murthy, V. N. An olfactory cocktail party: figure-ground segregation of odorants in rodents. *Nat. Neurosci.* **17**, 1225–1232 (2014).

[21] Castro, J. B., Ramanathan, A., & Chennubhotla, C. S. Categorical Dimensions of Human Odor Descriptor Space Revealed by Non-Negative Matrix Factorization. *PLoS ONE* **8** (2013).

[22] Weiss, T., Snitz, K., Yablonka, A., Khan, R. M., Gafsou, D., et al. Perceptual convergence of multi-component mixtures in olfaction implies an olfactory white. *Proc. Natl. Acad. Sci. U.S.A.* **109**, 19959–19964 (2012).

[23] Secundo, L., Snitz, K., & Sobel, N. The perceptual logic of smell. *Curr. Opin. Neurobiol.* **25**, 107–115 (2014).

[24] Koulakov, A. A., Kolterman, B. E., Enikolopov, A. G., & Rinberg, D. In search of the structure of human olfactory space. *Front. Syst. Neurosci.* **5**, 65 (2011).

[25] Wu, A., Pashkovski, S., Datta, S. R., & Pillow, J. W. Learning a latent manifold of odor representations from neural responses in piriform cortex. *Advances in Neural Information Processing Systems 31* pages 5383–5393 (2018).

[26] Field, D. J. What Is the Goal of Sensory Coding? *Neural Computation* **6**,

559–601 (1994).

[27] Olshausen, B. A & Field, D. J. Sparse coding with an overcomplete basis set: A strategy employed by V1? *Vis. Res.* **37**, 3311–3325 (1997).

[28] Jeanne, J. M., Fişek, M., & Wilson, R. I. The Organization of Projections from Olfactory Glomeruli onto Higher-Order Neurons. *Neuron* **98**, 1198–1213.e6 (2018).

[29] Yoshida, I & Mori, K. Odorant Category Profile Selectivity of Olfactory Cortex Neurons. *J. Neurosci.* **27**, 9105–9114 (2007).

[30] Berck, M. E., Khandelwal, A., Claus, L., Hernandez-Nunez, L., Si, G., et al. The wiring diagram of a glomerular olfactory system. *eLife* **5** (2016).

[31] Zwicker, D. Normalized neural representations of complex odors. *PLoS ONE* **11**, 1–16 (2016).

[32] Lapid, H., Shushan, S., Plotkin, A., Voet, H., Roth, Y., et al. Neural activity at the human olfactory epithelium reflects olfactory perception. *Nat. Neurosci.* **14**, 1455 (2011).

[33] Semmelhack, J. L & Wang, J. W. Select Drosophila glomeruli mediate innate olfactory attraction and aversion. *Nature* **459**, 218 (2009).

[34] Boesveldt, S., Frasnelli, J., Gordon, A. R., & Lundström, J. N. The fish is bad: Negative food odors elicit faster and more accurate reactions than other odors. *Biol. Psychol.* **84**, 313–317 (2010).

[35] Hughes, G. M., Teeling, E. C., & Higgins, D. G. Loss of olfactory receptor function in hominin evolution. *PLoS ONE* **9**, 1–6 (2014).

[36] Ai, M., Min, S., Grosjean, Y., Leblanc, C., Bell, R., et al. Acid sensing by the Drosophila olfactory system. *Nature* **468**, 691 (2010).

[37] Kurtovic, A., Widmer, A., & Dickson, B. J. A single class of olfactory neurons mediates behavioural responses to a Drosophila sex pheromone. *Nature* **446**, 542 (2007).

[38] Li, Q & Liberles, S. D. Aversion and Attraction through Olfaction. *Curr. Biol.* **25**, R120–R129 (2015).

[39] Khan, R. M., Luk, C.-H., Flinker, A., Aggarwal, A., Lapid, H., et al. Predicting Odor Pleasantness from Odorant Structure: Pleasantness as a Reflection of the Physical World. *J. Neurosci.* **27**, 10015–10023 (2007).

[40] Keller, A., Zhuang, H., Chi, Q., Vosshall, L. B., Matsunami, H., et al. Genetic variation in a human odorant receptor alters odour perception. *Nature* **449**, 468–72 (2007).

[41] Howard, J. D & Gottfried, J. A. Configural and elemental coding of natural odor mixture components in the human brain. *Neuron* **84**, 857–869 (2014).

[42] Andersson, M. N., Löfstedt, C., & Newcomb, R. D. Insect olfaction and the evolution of receptor tuning. *Front. Ecol. Evol.* **3**, 53 (2015).

[43] Haverkamp, A., Hansson, B. S., & Knaden, M. Combinatorial codes and labeled lines: How insects use olfactory cues to find and judge food, mates, and oviposition sites in complex environments. *Front. Physiol.* **9**, 49 (2018).

[44] Wright, G. A & Thomson, M. G. Odor Perception and the Variability in Natural Odor Scenes. In Romeo, J. T, editor, *Recent Advances in Phytochemistry* volume 39 pages 191–226. Elsevier (2005).

[45] Fleischmann, A., Shykind, B. M., Sosulski, D. L., Franks, K. M., Glinka, M. E., et al. Mice with a "Monoclonal Nose": Perturbations in an Olfactory Map Impair Odor Discrimination. *Neuron* **60**, 1068–1081 (2008).

[46] Keller, A & Vosshall, L. B. Influence of odorant receptor repertoire on odor perception in humans and fruit flies. *Proc. Natl. Acad. Sci. U.S.A.* **104**, 5614–9 (2007).

[47] Zhou, Y., Smith, B. H., & Sharpee, T. O. Hyperbolic geometry of the olfactory space. *Sci. Adv.* **4** (2018).

[48] Si, G., Kanwal, J. K., Hu, Y., Tabone, C. J., Baron, J., et al. Structured Odorant Response Patterns across a Complete Olfactory Receptor Neuron Population.

Neuron **101**, 1–13 (2019).

[49] Reddy, G., Zak, J. D., Vergassola, M., & Murthy, V. N. Antagonism in olfactory receptor neurons and its implications for the perception of odor mixtures. *eLife* **7**, e34958 (2018).

[50] Singh, V., Murphy, N. R., Balasubramanian, V., & Mainland, J. D. Competitive binding predicts nonlinear responses of olfactory receptors to complex mixtures. *Proc. Natl. Acad. Sci. U.S.A.* **116**, 9598–9603 (2019).

[51] Su, C.-Y., Martelli, C., Emonet, T., & Carlson, J. R. Temporal coding of odor mixtures in an olfactory receptor neuron. *Proc. Natl. Acad. Sci. U.S.A.* **108**, 5075–5080 (2011).

[52] Shusterman, R., Smear, M. C., Koulakov, A. A., & Rinberg, D. Precise olfactory responses tile the sniff cycle. *Nat. Neurosci* **14**, 1039–1044 (2011).

[53] Tesileanu, T., Cocco, S., Monasson, R., & Balasubramanian, V. Adaptation of olfactory receptor abundances for efficient coding. *eLife* **8**, 1–39 (2019).

[54] Doty, R. L., McKeown, D. A., Lee, W. W., & Shaman, P. A Study of the Test-retest Reliability of Ten Olfactory Tests. *Chemical Senses* **20**, 645–656 (1995).

[55] Haddad, R., Khan, R., Takahashi, Y. K., Mori, K., Harel, D., et al. A metric for odorant comparison. *Nature Methods* **5**, 425–9 (2008).

[56] Luebke, W. *The Good Scents Company Information System*. Online Access: http://www.thegoodscentscompany.com (2019).

[57] Zarzo, M & Stanton, D. T. Identification of latent variables in a semantic odor profile database using principal component analysis. *Chemical Senses* **31**, 713–724 (2006).

[58] Powers, D. M. W. Evaluation: from precision, recall and F-measure to ROC, informedness, markedness and correlation. *J. Machine Learning Technol.* **2**, 37–63 (2011).

[59] Saito, T & Rehmsmeier, M. The precision-recall plot is more informative than the ROC plot when evaluating binary classifiers on imbalanced datasets. *PLoS ONE* **10**, 1–21 (2015).

[60] Verhelst, N. D. An Efficient MCMC Algorithm to Sample Binary Matrices with Fixed Marginals. *Psychometrika* **73**, 705–728 (2008).

[61] Jang, S & Hyeon, C. Kinetic Model for the Activation of Mammalian Olfactory Receptor. *J. Phys. Chem. B* **121**, 1304–1311 (2017).

[62] Shannon, P., Markiel, A., Ozier, O., Baliga, N. S., Wang, J. T., et al. Cytoscape: A software environment for integrated models of biomolecular interaction networks. *Genome Research* **13**, 2498–2504 (2003).

[63] Koulakov, A., Gelperin, A., & Rinberg, D. Olfactory Coding With All-or-Nothing Glomeruli. *J. Neurophysiol.* **98**, 3134–3142 (2007).

[64] Zeng, X.-N., Leyden, J. J., Lawley, H. J., Sawano, K., Nohara, I., et al. Analysis of characteristic odors from human male axillae. *J. Chem. Ecol.* **17**, 1469–1492 (1991).

[65] Jacob, T. J., Wang, L., Jaffer, S., & McPhee, S. Changes in the odor quality of androstadienone during exposure-induced sensitization. *Chem. Senses* **31**, 3–8 (2006).

SUPPLEMENTARY TEXT

Interaction network with full edge attributes

We start from previous characterization of the pairwise interactions in the dataset, based on a minimal kinetic model [61]. For each interacting pair of an odorant and a receptor, the dose-response curve $r(c|\theta)$, or the activity of the receptor in response to an odorant concentration c, is characterized with four parameters $\theta = \{B, E, K_{1/2}, H\}$ as $r(c|\theta) = B + (E - B) \cdot c^H/(c^H + K_{1/2}^H)$. Here B is the basal activity of the receptor; E is the efficacy, or the maximum response from the interaction; $K_{1/2}$ is the EC_{50}, the effective concentration of the odorant required to elicit half-maximum response; and H is the Hill coefficient. The net amplitude (or the strength) of the response is measured by the difference $A \equiv E - B$. The interaction is either activating ($E > B$), or de-activating ($E < B$). In the previous study [16], we determined the four parameters $\{B, E, K_{1/2}, H\}$ for each of the 535 interacting odorant-receptor pairs from the dataset of [14]. The interaction parameters are displayed as the edge attributes in Fig. S1. A network file with full information on all nodes and edges, ready to import in an interactive platform (Cytoscape [62]), is also available online (https://github.com/jihyunbak/ORnetwork).

Interaction network at fixed odorant concentrations

Here we show how the analysis used in our work can be extended beyond the binary regime by taking into account the effect of odorant concentration.

We construct a binary interaction network at a fixed odorant concentration, c, assumed to be uniform for all odorants considered. In this case, an edge between each odorant-receptor pair indicates that the receptor is *activated* when the odorant is present at this concentration c; this selects all activations (positive responses) with $c > K_{1/2}$, and excludes the de-activations (negative responses). This binarization scheme is consistent with the prediction that the olfactory response is effectively binary at the level of receptor neurons [16]; it is also related to the ON/OFF model considered in [63]. Varying the odorant concentration c uniformly for all odorants, we obtain a family of binary (unweighted and undirected) interaction networks (see Fig. S2a). As expected, the average degree of an odorant decreases as c decreases (Fig. S2b). Specifically, the average degree is $\langle k \rangle \simeq 6$ at high odorant concentration ($c \gg K_{1/2}^* \sim 100~\mu M$ [16]), but is reduced to $\langle k \rangle \simeq 3.6$ at $c \approx K_{1/2}^*$. The degree distributions still look qualitatively similar (consistent with the form $P(k) \sim k^{-\alpha}$), while the decay becomes steeper at lower concentrations (Fig. S2c). We also show three snapshots of the interaction network at $c = 0.1M$, $c = 100\mu M$ and $c = 1\mu M$ respectively (Fig. S2d-f).

Figure S1: **Interaction network with full edge attributes.** The edge color indicates the signs of interactions, with gray for activations and magenta for de-activations. The edge line style indicates the range of the characteristic concentration $K_{1/2}$: we used solid lines ($\log_{10} K_{1/2} \leq -5$), dashed lines ($-5 < \log_{10} K_{1/2} \leq -2$), and dotted lines ($\log_{10} K_{1/2} > -2$), as also shown in the legends in Fig. S1. We note that the distribution of $K_{1/2}$ has a peak around the average value $K_{1/2}^* \approx \langle K_{1/2} \rangle \sim 100 \,\mu\text{M}$ [16]. The edge thickness indicates the net amplitude of the response, A, such that a thicker line represents an interaction that elicits a larger response. We also varied the edge transparency to indicate the goodness of fit for the determination of the four parameters, such that a more opaque (less transparent) edge means a higher correlation coefficient, or a better fit. See the accompanying supplementary text for more details. A network file with full information on all nodes and edges, prepared for easy interactive access, is also available online.

Figure S2: **Interaction network at fixed odorant concentrations. a.** Construction of the binary interaction network at fixed odorant concentration, c, assumed uniform for all odorants. **b.** The average degree of odorants at varying c. Average was taken either over all the odorants in the network (solid line) or over the odorants connected to at least one receptor at the respective concentration level (dotted line). **c.** Degree distributions obtained by counting activations at three fixed odorant concentrations (c =0.1 M, 100 μM, 1 μM), each showing a heavy tail but a different rate of decay. **d-f:** Binary interaction networks at the three fixed odorant concentrations. For easy comparison, node sizes are inherited from the original network; i.e., they reflect the number of all interactions, including the ones that are suppressed at the respective concentrations.

Figure S3: **Odorant mixture test.** **a.** Illustrations of the net receptor coverage n_{union} (gray area, which also equivalent to unstriped blue area), and the sum of individual receptor coverages n_{sum} (total blue area), in a mixture of odorants. The receptor code redundancy in a mixture, χ_{mix}, is defined by the fraction of the overlap (striped area) with respect to **b.** We plot the receptor coverage by a mixture of odorants, n_{union}, at varying number of odorants in the mixture, m. A mixture contains either the m highest-degree odorant in the test dataset (red) or a random selection of m odorants from the test dataset (gray); we take 500 independent samples of random mixtures. With the six highest-degree odorants, the receptor coverage is $n_{\mathrm{union}} = 155$, which is comparable to a random mixture with $m \approx 34$ odorants on average. The dashed lines show n_{sum} for comparison. **c.** We plot the redundancy in a mixture, χ_{mix}, versus the receptor coverage for the corresponding mixture, n_{union}. Again, a mixture is selected either from the highest-degree odorants (red) or randomly (gray). The gray line indicates the redundancy calculated from the average counts $\langle n_{\mathrm{union}} \rangle$ and $\langle n_{\mathrm{sum}} \rangle$ over all 500 random mixtures at each m. Gray dots show the results from all 45,000 random mixtures (500 repetitions at each m, and 90 different values of m).

Figure S4: **The grouping procedure. a-e.** Illustration using an example interaction network. **a.** The co-activation graph is a one-mode projection from the bipartite interaction network. Co-activation graph of either node type can be considered, but disjoint hubs (high-degree nodes) in one node type give rise to isolated cliques in the co-activation graph on the other node type. In this example case, almost disjoint odorant hubs (blue squares) are reflected in the almost isolated cliques in the co-activation graph of receptors (orange circles). **b.** Odorants are grouped consequently. **c.** A co-activation matrix, where each row or column is a receptor; receptor cliques appear as square blocks. Receptors are sorted such that cliques are ordered by the size; this is called the primary grouping. **d.** Odorants are again grouped consequently. **e.** Receptors are grouped once again by the redundancy, and re-sorted according to this secondary grouping. See text for details. **f-h.** Analysis on the odorant-receptor interaction dataset [14], binarized by counting all interactions. **f.** The co-activation graph from the real dataset. **g.** Sorted co-activation matrix for the 303 receptors. Diagonal blocks indicate the primary grouping of receptors. each around a shared hub odorant. **h.** Secondary grouping of receptors, based on the receptor code redundancy between the odorant hubs. We colored the 6 largest groups, which already span more than 250 receptors cumulatively. The hub odorants for several large primary groups are labeled.

Figure S5: **Finding the optimal threshold $\bar{\chi}$ for the secondary grouping of receptors. a-c.** Secondary grouping results at different thresholds, $\bar{\chi} = 0.05$, $\bar{\chi} = 0.15$ and $\bar{\chi} = 0.25$ respectively. Each panel shows the co-activation matrix of receptors, sorted and colored by the corresponding secondary groups. **d.** The 2×2 contingency table for the binary classifier, and the different definitions of success rates considered in this analysis. **e.** The ROC curve of grouping at varying threshold $\bar{\chi}$. The two diagonals, the line of no discrimination which corresponds to random guesses (positive diagonal) and the line of balance points where sensitivity equals specificity (negative diagonal), are shown in dashed lines. Gray contours indicate the lines of constant error (sum of squared error; SSE). **f.** SSE at varying threshold $\bar{\chi}$. **g.** The precision-recall curve at varying threshold $\bar{\chi}$. Gray contours indicate the lines of constant F_β score, evaluated at $\beta = 3.37$ that represents the balance of positives and negatives in data. **h.** F_β at varying threshold $\bar{\chi}$.

Figure S6: **Shuffling test for receptor code grouping. (a-c)** Examples of null models, obtained by **a.** full shuffling, **b.** degree-preserving shuffling, and **c.** primary group (g_1)-preserving shuffling and extra swaps. Upper panels show the shuffled interaction matrices. Lower panels show the receptor co-activation matrices, sorted and colored by the best grouping, in the sense of prediction error minimization (red circles in **e**). **(d)** Schematic illustrations of the three shuffling rules. See Methods for more details. The goodness of the original primary grouping is restored at 40 extra swaps, for both goodness measures we considered in this analysis (SSE and F_β, also see the next panels). Plots show the averages over 30 repetitions of shuffle-and-swaps, with standard error bars. **(e-f)** Sensitivity-specificity analysis. **e.** The ROC curves for the real data and the three null models, with the lines of constant sum-of-squared error (SSE) shown in gray. **f.** SSE at varying threshold $\bar{\chi}$. **(g-h)** Precision-recall analysis. **g.** The precision-recall curves, with the constant-F_β lines (evaluated at $\beta = 3.37$) in gray. **h.** The F_β score at varying threshold $\bar{\chi}$. For each null model, the solid line is evaluated with its own value of β, whereas the dotted line is evaluated at the $\beta = 3.37$ determined for the original dataset. **(i-j)** Evaluation of statistical significance by sampling the distributions of the two test statistics, **i.** SSE and **j.** F_β score, under the null models. We sampled 500 independent shuffles under each null model.

Figure S7: **Joint statistics between the receptor-code groups, s_R, and the perceptual odor categories, s_W. a.** The log likelihood ratios between the full joint distribution (observed) and the uncorrelated null model (expected). **b.** The weighted log likelihood ratios, that sum up to give the Kullback-Leibler divergence D_{KL} (in this case also equal to the mutual information between s_R and s_W). The corresponding summary statistics are $D_{KL} = 0.385$ and $G = 68.9$, which gives $p = 0.027$ with 48 degrees of freedom. **c.** Dimensionality reduction of the perceptual odor categories by merging. **d.** The weighted log-likelihood ratios using the reduced odor categories. The summary statistics are $D_{KL} = 0.323$ and $G = 57.5$, which gives $p = 1.4 \times 10^{-4}$ at 24 degrees of freedom. **e-f.** The local chi-squared values. **e.** Using all eight perceptual odor categories, we get $\chi^2 = 71.4$ and $p = 0.016$ (48 degrees of freedom). **f.** Using the reduced categories, we get $\chi^2 = 62.2$ and $p = 3.0 \times 10^{-5}$ (24 degrees of freedom).

Idx	Odorant	Degree	Group1	Group2	Category1	Category2
1	cis-3-hexen-1-ol	36	1	1	green	plant-like
2	phenyl acetaldehyde	10	1	1	green	plant-like
3	n-amyl acetate	8	1	1	fruity	culinary
4	nootkatone	7	1	1	citrus	citrus
5	2-ethylfenchol	4	1	1	green	plant-like
6	3-methyl-2-hexenoic acid	3	1	1	animal	animal-like
7	methyl salicylate	2	1	1	minty	plant-like
8	octyl aldehyde	1	1	1	citrus	citrus
9	pyrazine	1	1	1	spicy	culinary
10	geranyl acetate	27	3	1	floral	plant-like
11	sandalwood	5	3	1	green	plant-like
12	lilial	5	3	1	floral	plant-like
13	Cyclohexanone	1	3	1	minty	plant-like
14	cinnamaldehyde	20	7	1	spicy	culinary
15	coumarin	11	7	1	spicy	culinary
16	spearmint	9	7	1	minty	plant-like
17	quinoline	7	7	1	chemical	plant-like
18	1-octanethiol	6	7	1	animal	animal-like
19	coffee difuran	5	7	1	spicy	culinary
20	thioglycolic acid	3	7	1	animal	animal-like
21	dicyclohexyl disulfide	1	7	1	animal	animal-like
22	eugenol methyl ether	15	10	1	spicy	culinary
23	terpineol	1	10	1	green	plant-like
24	linalool	11	12	1	floral	plant-like
25	(-)-carvone	6	21	1	minty	plant-like
26	(+)-carvone	5	21	1	minty	plant-like
27	r-carvone	1	21	1	minty	plant-like
28	lyral	5	23	1	floral	plant-like
29	anisaldehyde	1	25	1	floral	plant-like
30	methyl octanoate	1	32	1	green	plant-like
31	butyric acid	23	5	2	animal	animal-like
32	acetophenone	2	5	2	floral	plant-like
33	butyl acetate	2	5	2	fruity	culinary
34	androstenone	24	6	2	animal	animal-like
35	anise	6	6	2	minty	plant-like
36	3-phenyl propyl propionate	4	6	2	floral	plant-like
37	1-butanol	1	6	2	animal	animal-like
38	jasmine	11	13	2	floral	plant-like
39	androstadienone	14	14	2	animal	animal-like
40	heptanoic acid	1	14	2	animal	animal-like
41	p-cymene	1	14	2	green	plant-like
42	5,5-Dimethyl-1,3-cyclohexanedione	1	14	2	unsorted	other
43	2-methyl-1-propanethiol	1	14	2	animal	animal-like
44	caramel furanone	1	14	2	spicy	culinary
45	amyl butyrate	1	14	2	fruity	culinary

Table S1: **List of odorants with receptor-code group and perceptual odor category labels.** (Continued to the next page)

Idx	Odorant	Degree	Group1	Group2	Category1	Category2
46	isoeugenol	13	15	2	spicy	culinary
47	ambrette	8	16	2	green	plant-like
48	(+)-dihydrocarvone	3	30	2	minty	plant-like
49	eugenol	36	2	3	spicy	culinary
50	TMT	5	2	3	animal	animal-like
51	2-methoxy-4-methylphenol	4	2	3	spicy	culinary
52	butyl anthranilate	4	2	3	fruity	culinary
53	r-limonene	3	2	3	citrus	citrus
54	2-heptanone	2	2	3	green	plant-like
55	(+)-menthol	2	2	3	minty	plant-like
56	nutmeg	2	2	3	spicy	culinary
57	banana	1	2	3	fruity	culinary
58	guaiacol	1	2	3	spicy	culinary
59	eugenol acetate	23	4	4	spicy	culinary
60	caproic acid	2	4	4	animal	animal-like
61	pentadecalactone	1	4	4	spicy	culinary
62	ethyl vanillin	19	8	5	spicy	culinary
63	helional	4	8	5	floral	plant-like
64	dihydrojasmone	1	8	5	green	plant-like
65	hexyl octanoate	1	8	5	fruity	culinary
66	cinnamon	14	11	5	spicy	culinary
67	benzene	1	11	5	floral	plant-like
68	nonanedioic acid	1	11	5	spicy	culinary
69	pyridine	1	11	5	animal	animal-like
70	isovaleric acid	11	9	6	animal	animal-like
71	propionic acid	1	9	6	animal	animal-like
72	beta-ionone	1	9	6	fruity	culinary
73	decyl aldehyde	5	17	7	citrus	citrus
74	undecanal	1	17	7	floral	plant-like
75	geraniol	9	18	8	floral	plant-like
76	ethylene brassylate	8	19	9	floral	plant-like
77	vanillin	8	20	10	spicy	culinary
78	(-)-menthol	5	22	11	minty	plant-like
79	allyl phenylacetate	4	24	12	spicy	culinary
80	nonyl aldehyde	3	29	13	citrus	citrus
81	2-decenal	4	27	14	floral	plant-like
82	diacetyl	4	28	15	spicy	culinary
83	1-formylpiperidine	1	28	15	unsorted	other
84	isobutyric acid	2	31	16	animal	animal-like
85	galaxolide	1	33	17	floral	plant-like
86	(-)-citronellal	1	43	22	citrus	citrus
87	1-octanol	1	44	23	floral	plant-like
88	nonanal	1	45	24	citrus	citrus
89	r-limonene	1	46	25	citrus	citrus

Table S1: **List of odorants with receptor-code group and perceptual odor category labels.** The 89 odorants are listed according to the groups identified in our work. The order of odorants is the same as in the row order in Fig. 4 in the main text. The columns "Group1" and "Group2" show the primary odorant group rank and the secondary odorant group rank, respectively, ranked by the size of the corresponding receptor groups. The columns "Category1" shows the perceptual odor category as adopted from [21]. "Category2" shows the reduced odor label, obtained by merging Category1.

Idx	Odorant	Descriptors
1	cis-3-hexen-1-ol	**green** grassy foliage oily herbal vegetable melon-rind fresh pungent
2	phenyl acetaldehyde	**green** rose floral honey sweet cocoa chocolate earthy hyacinth fermented clover powdery
3	n-amyl acetate	**fruity** pear ethereal banana apple
4	nootkatone	**citrus** orange grapefruit peely grapefruit-peel sweet gardenia woody
5	2-ethylfenchol	**earthy** camphoreous patchouli musty humus rooty
6	3-methyl-2-hexenoic acid	sweaty
7	methyl salicylate	**minty** camphoreous phenolic sweet aromatic root-beer wintergreen
8	octyl aldehyde	**aldehydic** orange fatty peely citrus green orange-peel waxy
9	pyrazine	**nutty** barley-roasted-barley hazelnut corn roasted sweet hazelnut-roasted-hazelnut pungent
10	geranyl acetate	**floral** herbal rose cooling green waxy lavender
11	sandalwood	**woody** herbal terpenic sweet balsamic spicy cashew sandalwood
12	lilial	**floral** cumin green muguet watery powdery
13	Cyclohexanone	**minty** acetone
14	cinnamaldehyde	**spicy** cinnamon sweet candy warm
15	coumarin	**tonka** hay-new-mown-hay sweet hay coumarinic
16	spearmint	**minty** spearmint
17	quinoline	**medicinal** tobacco rubbery earthy musty leathery
18	1-octanethiol	**sulfurous**
19	coffee difuran	**coffee** sulfurous chicken roasted meaty meaty-roasted-meaty coffee-roasted-coffee potato onion cabbage
20	thioglycolic acid	unpleasant pungent rotten
21	dicyclohexyl disulfide	**alliaceous** eggy clam nut-skin coffee seafood onion
22	eugenol methyl ether	**spicy** phenolic cinnamon vegetable peppery sweet musty warm clove carnation waxy fresh
23	terpineol	**terpenic** lilac cooling lime floral citrus pine lemon woody resinous
24	linalool	**floral** orange rose terpenic citrus sweet green bois-de-rose waxy woody blueberry
25	(-)-carvone	**minty** spearmint herbal sweet
26	(+)-carvone	**minty** caraway spicy bready
27	r-carvone	**minty** spearmint herbal sweet
28	lyral	**floral** rhubarb muguet woody cyclamen
29	anisaldehyde	**anisic** hawthorn coumarinic floral creamy sweet woody powdery balsamic spicy mimosa vanilla anise
30	methyl octanoate	**waxy** orange aldehydic herbal vegetable green sweet
31	butyric acid	unpleasant rancid penetrating obnoxious
32	acetophenone	**floral** marzipan hawthorn coumarinic chemical nutty sweet heliotrope acacia vanilla cherry mimosa pungent almond
33	butyl acetate	**ethereal** sharp solvent banana fruity
34	androstenone	**sweaty** urinous woody floral
35	anise	**anise** phenolic licorice herbal sweet resinous
36	3-phenyl propyl propionate	**floral** hyacinth balsamic fruity mimosa
37	1-butanol	**fermented** oily whiskey fusel sweet balsamic
38	jasmine	**floral** jasmin phenolic jammy spicy fruity
39	androstadienone	sweaty
40	heptanoic acid	**cheesy** sour sweaty waxy fermented pineapple fruity rancid
41	p-cymene	**terpenic** cumin cilantro chemical citrus lemon origanum woody fresh spicy
42	5,5-Dimethyl-1,3-cyclohexanedione	odorless weak
43	2-methyl-1-propanethiol	**sulfurous** mustard vegetable cooked
44	caramel furanone	**caramellic** maple sugar-burnt-sugar cotton-candy sweet coffee sugar-brown-sugar
45	amyl butyrate	**fruity** banana sweet tropical pineapple cherry

Table S2: **List of odorants with perceptual odor descriptors.** (Continued to the next page)

Idx	Odorant	Descriptors
46	isoeugenol	**spicy** floral sweet clove carnation woody
47	ambrette	**amber** musk weedy fruit-dried-fruit woody powdery fresh
48	(+)-dihydrocarvone	**minty** mentholic herbal
49	eugenol	**spicy** phenolic bacon cinnamon allspice sweet clove woody ham savory
50	TMT	fox-odor
51	2-methoxy-4-methylphenol	**spicy** phenolic sweet smoky candy clove medicinal leathery vanilla
52	butyl anthranilate	**fruity** plum floral sweet berry petitgrain winey powdery grape
53	r-limonene	**citrus** orange peely sweet fresh
54	2-heptanone	**cheesy** herbal banana creamy sweet green ketonic coconut woody spicy fruity
55	(+)-menthol	**mentholic** cooling minty
56	nutmeg	**spicy** balsamic warm nutmeg
57	banana	**fruity** banana creamy tropical
58	guaiacol	**phenolic** meaty smoky woody medicinal spicy savory vanilla
59	eugenol acetate	**spicy** floral sweet clove carnation woody fresh malty
60	caproic acid	**fatty** sour sweaty cheesy
61	pentadecalactone	**musk** licorice tobacco animal heliotrope powdery natural fruity brown coumarinic
62	ethyl vanillin	**vanilla** caramellic creamy sweet root-beer
63	helional	**floral** green ozone hay watery cyclamen fresh
64	dihydrojasmone	**floral** fresh-outdoors jasmin herbal myrrh sweet woody powdery spicy fruity
65	hexyl octanoate	**green** berry apple waxy estery fruity
66	cinnamon	**spicy** honey sweet aromatic warm woody cinnamyl resinous fruity
67	benzene	**aromatic** sweet gasoline-like
68	nonanedioic acid	fatty
69	pyridine	**fishy** sour ammoniacal
70	isovaleric acid	**cheesy** sour fatty ripe sweaty acidic tropical dairy fruity pungent
71	propionic acid	**acidic** cheesy dairy vinegar pungent
72	beta-ionone	**floral** beeswax sweet berry green woody tropical fruity
73	decyl aldehyde	**aldehydic** orange floral citrus sweet orange-peel waxy citrus-rind
74	undecanal	**aldehydic** orange cilantro fatty soapy watermelon floral citrus green waxy cloth-laundered-cloth pineapple
75	geraniol	**floral** citronella rose citrus sweet waxy fruity
76	ethylene brassylate	**musk** floral ambrette sweet woody powdery spicy vanilla
77	vanillin	**vanilla** phenolic creamy sweet chocolate
78	(-)-menthol	**mentholic** minty cooling peppermint
79	allyl phenylacetate	**honey** fruity rummy
80	nonyl aldehyde	**aldehydic** fatty peely rose orris citrus green orange-peel waxy cucumber fresh lemon-peel
81	2-decenal	**fatty** orange aldehydic rose floral green
82	diacetyl	**buttery** caramellic creamy sweet pungent
83	1-formylpiperidine	odorless
84	isobutyric acid	**acidic** sour cheesy buttery dairy rancid
85	galaxolide	**musk** floral sweet
86	(-)-citronellal	**citrus** herbal clean
87	1-octanol	**waxy** orange aldehydic fatty rose floral citrus green sweet mushroom coconut
88	nonanal	**aldehydic** fatty peely rose orris citrus green orange-peel waxy cucumber fresh lemon-peel
89	r-limonene	**citrus** orange peely sweet fresh

Table S2: **List of odorants with perceptual odor descriptors.** For each odorant, all descriptors were obtained from a single source. If they were obtained from the Good Scents Company Information System [56], and if an odor type was specified, the odor type descriptor is boldfaced in the list. Descriptor sources are separately provided in Table S5.

Category	Nickname	Reference
1	citrus	fruity/citrus, lemon, grapefruit, orange
2	chemical	nail polish remover, mothballs, alcoholic, etherish, anaesthetic, cleaning fluid, gasoline, solvent, turpentine (pine oil), leather, tar, creosote, disinfectant, carbolic, medicinal, chemical, ammonia, new rubber, kerosene, paint, varnish, metallic
3	minty	tea leaves, caraway, minty, peppermint, camphor, eucaliptus, anise (licorise), cheesy, cool, cooling
4	floral	floral, rose, violets, lavender, cologne, musk, perfumery, fragrant, aromatic, soapy, incense, light
5	fruity	fruity/other than citrus, pineapple, grape juice, strawberry, pear, cantaloupe, honeydew melon, peach (fruit), banana, cherry (berry), sweet, raisins
6	green	laurel leaves, black pepper, green pepper, dill, oak wood, cognac, woody, resinous, cedarwood, geranium leaves, celery, fresh green vegetables, crushed weeds, crushed grass, herbal, green, cut grass, raw cucumber, cardboard, rope, wet paper, musty, earthy, moldy, raw potato, mushroom, beany, bark, birth bark, cork, dry, powdery, chalky
7	spicy	honey, almond, nutty (walnut etc), spicy, clove, cinnamon, chocolate, vanilla, maple syrup, caramel, malty, molasses, coconut, hay, bakery (fresh bread), peanut butter, burnt, smoky, fresh tobacco smoke, coffee, stale tobacco smoke, burnt paper, burnt milk, burnt candle, oily, fatty, buttery, fresh butter, popcorn, fried chicken, warm
8	animal	apple (fruit), seasoning (for meat), grainy (as grain), yeasty, sour milk, fermented (rotten), fruit, beery, wet wool, wet dog, dirty linen, stale, mouse, eggy (fresh eggs), burnt rubber, bitter, sharp, pungent, acid, sour, vinegar, sauerkraut, urine, cat urine, fishy, kippery (smoked fish), seminal, sperm, sooty, meaty (cooked, good), soupy, cooked vegetables, rancid, sweaty, household gas, sulfidic, garlic, onion, blood, raw meat, animal, sewer, putrid, foul, decayed, fecal (like manure), cadaverous (dead animal), sickening, heavy

Table S3: **Reference descriptors for the perceptual odor categories.** Category numbers and the list of reference words are copied directly from Figure 7 in [21]. We name each category for convenience (column Nickname).

Descriptor	Proxy	Cat.	Descriptor	Proxy	Cat.	Descriptor	Proxy	Cat.
acacia	floral	4	estery	fruity	5	orange	orange	1
acetone	chemical	2	ethereal	fruity	5	orange-peel	orange	1
acidic	acid	8	fatty	fatty	7	origanum	spicy	7
aldehydic	soapy	4	fermented	fermented	8	orris	fragrant	4
alliaceous	onion	8	fishy	fishy	8	ozone	chemical	2
allspice	spicy	7	floral	floral	4	patchouli	minty	3
almond	nutty	7	foliage	green	6	pear	pear	5
amber	resin	6	fox-odor	animal	8	peely	citrus	1
ambrette	musk	4	fresh	unsorted	9	penetrating	sharp	8
ammoniacal	urine	8	fresh-outdoors	green	6	peppermint	minty	3
animal	animal	8	fruit-dried-fruit	raisins	5	peppery	pepper	6
anise	anise	3	fruity	fruity	5	petitgrain	citrus	1
anisic	anise	3	fusel	fermented	8	phenolic	tar	2
apple	apple	8	gardenia	floral	4	pine	green	6
aromatic	aromatic	4	gasoline-like	gasoline	2	pineapple	fruity	5
bacon	meaty	8	grape	fruity	5	plum	fruity	5
balsamic	aromatic	4	grapefruit	citrus	1	potato	potato	6
banana	banana	4	grapefruit-peel	citrus	1	powdery	powdery	6
barley-roasted-barley	burnt	7	grassy	cut-grass	6	pungent	pungent	8
beeswax	soapy	4	green	green	6	rancid	rancid	8
berry	berry	5	ham	meaty	8	resinous	resinous	6
blueberry	berry	5	hawthorn	floral	4	rhubarb	green	6
bois-de-rose	rose	4	hay	hay	7	ripe	fruity	5
bready	bakery	7	hay-new-mown-hay	hay	7	roasted	burnt	7
brown	burnt	7	hazelnut	nutty	7	root-beer	bark	6
buttery	butery	7	hazelnut-roasted-hazelnut	nutty	7	rooty	musty	6
cabbage	vegetable	6	heliotrope	floral	4	rose	rose	4
camphoreous	camphor	3	herbal	herbal	6	rotten	rotten	8
candy	honey	7	honey	honey	7	rubbery	new-rubber	2
caramellic	caramel	7	humus	earthy	6	rummy	molasses	7
caraway	caraway	3	hyacinth	floral	4	sandalwood	woody	6
carnation	clove	7	jammy	molasses	7	savory	cooked	8
cashew	nutty	7	jasmin	floral	4	seafood	fishy	8
cheesy	cheesy	3	ketonic	chemical	2	sharp	sharp	8
chemical	chemical	2	lavender	lavender	4	smoky	smoky	7
cherry	berry	5	leathery	leather	2	soapy	soapy	4
chicken	fried-chicken	7	lemon	lemon	1	solvent	chemical	2
chocolate	chocolate	7	lemon-peel	lemon	1	sour	sour	8
cilantro	herbal	6	licorice	anise	3	spearmint	minty	3
cinnamon	cinnamon	7	lilac	floral	4	spicy	spicy	7
cinnamyl	cinnamon	7	lime	citrus	1	sugar-brown-sugar	molasses	7
citronella	citrus	1	malty	malty	7	sugar-burnt-sugar	molasses	7
citrus	citrus	1	maple	maple-syrup	7	sulfurous	sulfidic	8
citrus-rind	citrus	1	marzipan	honey	7	sweaty	sweaty	8
clam	fishy	8	meaty	meaty	8	sweet	sweet	5
clean	light	4	meaty-roasted-meaty	meaty	8	terpenic	resinous	6
cloth-laundered-cloth	soapy	4	medicinal	medicinal	2	tobacco	tobacco	7
clove	clove	7	melon-rind	melon	5	tonka	vanilla	7
clover	green	6	mentholic	minty	3	tropical	fruity	5
cocoa	chocolate	7	mimosa	fragrant	4	unpleasant	foul	8
coconut	coconut	7	minty	minty	3	urinous	urine	8
coffee	coffee	7	muguet	floral	4	vanilla	vanilla	7
coffee-roasted-coffee	coffee	7	mushroom	mushroom	6	vegetable	vegetable	6
cooked	cooked	8	musk	musk	4	vinegar	vinegar	8
cooling	cool	3	mustard	spicy	7	warm	warm	7
corn	popcorn	7	musty	musty	6	watermelon	fruity	5
cotton-candy	honey	7	myrrh	resin	6	watery	light	4
coumarinic	spicy	7	natural	unsorted	9	waxy	unsorted	9
creamy	burnt-milk	7	nut-skin	nutty	7	weak	unsorted	9
cucumber	cucumber	6	nutmeg	spicy	7	weedy	grass	6
cumin	spicy	7	nutty	nutty	7	whiskey	malty	7
cyclamen	floral	4	obnoxious	foul	8	winey	grape	5
dairy	buttery	7	odorless	unsorted	9	wintergreen	green	6
earthy	earthy	6	oily	oily	7	woody	woody	6
eggy	eggy	8	onion	onion	8			

Table S4: **Labeling odor descriptors.** For each of the 184 test descriptors, we chose a best approximation (proxy) from the list of reference words for the perceptual odor categories (Table S3). The category label is determined by the proxy.

RESOURCE	SOURCE	IDENTIFIER
Deposited data		
Pairwise odorant-receptor interaction	[14]	Data Record 3 (dose-response)
Information of olfactory receptors	[14]	Data Record 4 (receptors)
Information of odorants	[14]	Data Record 5 (odorants)
		*Corrected name of odorant #1391 from "amyl laurate" to "nootkatone" (CAS 4674-50-4)
Pairwise interaction properties	[16]	S1 Table
Modular layout of interaction network	This paper	https://github.com/jihyunbak/ORnetwork
Perceptual odor categories	[21]	Figure 7
Odor descriptors		
3-methy-2-hexenoic acid	[64]	N/A
thioglycolic acid	NIOSH Pocket Guide to Chemical Hazards	https://www.cdc.gov/niosh/npg/npgd0610.html
benzene	NIOSH Emergency Response Safety and Health Database	https://www.cdc.gov/niosh/ershdb/emergencyresponsecard_29750032.html
butyric acid	NIH PubChem	CID 264, https://pubchem.ncbi.nlm.nih.gov/compound/Butyric-acid
androstenone	[40]	N/A
androstadienone	[65]	N/A
5,5-Dimethyl-1,3-cyclohexanedione	Fisher Scientific	SDS: 5,5-Dimethyl-1,3-cyclohexanedione
	EMD Millipore Corporation	MSDS: Dimedone GR for analysis (reagent for aldehydes)
nonanedioic acid	Columbus Chemical Industries	SDS: Azaleic Acid
1-formylpiperidine	EMD Millipore Corporation	MSDS: N-Formylpiperidine for synthesis
All other odorants in dataset	GoodScents [56]	http://www.thegoodscentscompany.com

Table S5: **List of data sources.** SDS: Safety Data Sheet; MSDS: Material Safety Data Sheet.