MOU-EC: model-based whole-brain effective connectivity to extract biomarkers for brain dynamics from fMRI data and study distributed cognition

Gilson M, Zamora-López G, Pallarés V, Adhikari MH, Senden M,
Tauste Campo A, Mantini D, Corbetta M, Deco G, Insabato A

January 27, 2019

Abstract

Neuroimaging techniques are increasingly used to study brain cognition in humans. Beyond their individual activation, the functional associations between brain areas have become a standard proxy to describe how information is distributed across the brain network. Among the many analysis tools available, dynamic models of brain activity have been developed to overcome the limitations of original connectivity measures such as functional connectivity. In particular, much effort has been devoted to the assessment of directional interactions between brain areas from their observed activity. This paper summarizes our recent approach to analyze fMRI data based on our whole-brain effective connectivity referred to as MOU-EC, while discussing the pros and cons of its underlying assumptions with respect to other established approaches. Once tuned, the model provides a connectivity measure that reflects the dynamical state of BOLD activity obtained using fMRI, which can be used to explore the brain cognition. We focus on two important applications. First, as a connectivity measure, MOU-EC can be used to extract biomarkers for task-specific brain coordination, understood as the patterns of areas exchanging information. The multivariate nature of connectivity measures raises several challenges for whole-brain analysis, for which machine-learning tools presents some advantages over statistical testing. Second, we show how to interpret changes in MOU-EC connections in a collective and model-based manner, bridging with network analysis. To illustrate our framework, we use a dataset where subjects were recorded in two conditions, watching a movie and a black screen (referred to as rest). Our framework provides a comprehensive set of tools that open exciting perspectives for the study of distributed cognition, as well as neuropathologies.

1 Connectivity measures for neuroimaging data

The study of brain cognition has flourished in the recent decades due to the abundance of neuroimaging data that give access to neural activity in human subjects. Among non-invasive techniques, functional magnetic resonance imaging (fMRI) has become a tool of choice to investigate how the brain activity is shaped when performing tasks [100, 89, 68, 29]. The blood-oxygen-level dependent (BOLD) signals recorded in fMRI measure the energy consumption of brain cells, reflecting modulations in neural activity [8, 44, 9, 97]. Since early fMRI analyses, a main focus has been on identifying with high spatial precision regions of interest (ROIs) in the brain that significantly activate or deactivate for specific tasks [30, 88, 138]. Because the measure of BOLD activity during task requires the quantification of a baseline, the brain activity for idle subjects became an object

of study and developed as a proper line of research [15, 122]. This revealed stereotypical patterns of correlated activity between brain regions, leading to the definition of the functional connectivity or FC [20, 59]. Together with studies of the anatomical connectivity using structural MRI [125, 73], fMRI studies progressively shifted from focusing on specific ROIs to whole-brain analyses [36]. For example, high-order cognition involves changes in BOLD activity that are distributed across the whole brain [111, 27], which cannot be restrained to a small set of preselected ROIs. The typical description of the whole-brain activity in these methods is a ROI-ROI matrix, which we refer to as connectivity measure.

Recently, fMRI studies for both rest and tasks have also evolved to incorporate the temporal structure of BOLD signals in their analysis [75, 82, 28, 99, 64, 68, 23, 137], in addition to the spatial structure. Models have also been developed to formalize the link between the observed BOLD and the neuronal activity [56, 89, 38, 94, 64, 52, 137]. This has led to many definitions for connectivity measures and variations thereof. In this introductory section we present fundamental concepts about connectivity measures that set our model-based approach in context (see also the glossary for definitions).

1.1 Model-based versus model-free approaches

A recurrent discussion opposes model-free and model-based approaches in neuroscience, which also applies for connectivity measures. For instance, FC calculated using Pearson correlation between time series (blue matrix in Fig. 1A) can be directly calculated from data —see Eq. (2) in Annex D— and may thus seen as model-free. However, the interpretation of the FC values for the pairs of ROIs in the matrix is based on the theory of graphical models, which assumes Gaussian distributions for the data. The Pearson correlation is an observable of the generated activity. The underlying connectivity in the graphical model corresponds to the partial correlations (PC) represented by the green matrix in Fig. 1A. The PC symmetric matrix describes the undirected linear interactions between Gaussian variables that result in the observed correlations. Our viewpoint is thus that connectivity measures are always related to a model, so it is thus crucial to bear in mind their assumptions when interpreting their values.

In the literature of whole-brain modeling, three families of connectivity measures have emerged:

- Structural connectivity (SC): It measures the density or probability of anatomical pathways that connect two ROIs, mostly via the white matter [116]. This led to the definition of the human connectome at the whole-brain level [125, 73].

- Functional connectivity (FC): Pairwise interactions defined by correlation or synchrony measures for the observed activity of ROIs [20, 59]. Apart from the Pearson correlation of the BOLD signals [15, 122], other common FC measures include mutual information [78] and synchrony of instantaneous phases [22, 23]. Conceptually, it corresponds an observable measure that can be applied to the data and the model activity.

- Effective connectivity (EC): Measure of the directional interactions in a dynamic model, interpreted as neuronal coupling. The original concept comes from electrophysiology [3]. It has been brought to neuroimaging in the 2000s when building models of the BOLD response and further developed in the context of the dynamic causal model (DCM) [56, 54, 130]. Note that it is also still used close to its original formulation when measuring stimulation-driven responses in neuroimaging [87].

To go beyond statistical relationships, the combination of several types of data requires a model, as with the SC and FC in Fig. 1A (bottom left box). Following, the choice of the model ingredients, especially their dynamics, has important implications that we detail now.

Figure 1: **Connectivity measures. A:** Schematic diagram of 6 brain regions of interest (ROIs), whose fMRI activity is captured by several types of connectivity measures. Here the activity is generated using a directed matrix. The corresponding structural connectivity (SC, black matrix) indicates the topology of anatomical connections between the 6 ROIs, which can be estimated using structural MRI. Functional connectivity (FC, blue matrix), often calculated using the Pearson correlation of the BOLD signals. Partial correlation (PC, green matrix) corresponds to the "projection" of the data on a graphical model. The multivariate autoregressive (MAR, orange matrix) assumes linear dynamics while taking the temporal structure of the data into account. Effective connectivity (EC, red matrix), which is the focus of the present review, depends on the choice for dynamic model, as well as input properties. **B:** Autocorrelograms of the data (in gray, left plot) for 6 ROIs and two network models (middle and right plots). The graphical model related to the FC and PC (in green) has a flat autocorrelogram away from the central peak. In contrast, the profile of the MAR process (in orange) has a decaying exponential profile.

Glossary:

- Generative model: Model of (dynamic) equations that generates a signal to be fit to empirical data. This definition is different from the definition in statistics where a generative model describes the joint probability distribution of observed and predicted variables (here the network activity), as opposed to a discriminative model that describes the conditional probability of the predicted variables with respect to the observed variables.

- Observable: Measure of model activity or applied to empirical data.

- Graphical model: Generative model of Gaussian variables with linear interactions. Its output variables have a flat autocovariance (apart from zero time lag) and is used to model noisy data without temporal structure.

- Multivariate Ornstein-Uhlenbeck (MOU) process: Dynamic generative model in continuous time with linear interactions. Its output variables have both spatial and temporal correlations.

- Multivariate autoregressive (MAR) process: Dynamic generative model in discrete time with linear interactions. It is the equivalent of the MOU process in discrete time.

- Lyapunov optimization or natural gradient descent: Tuning procedure for the EC weights in the MOU network that fits the model FC covariance matrices to their empirical counterparts.

- Classification pipeline: Succession of machine-learning algorithms that aims to learn the mapping from input vectors to output labels (or categories). Here we use neuroimaging connectivity measures to predict cognitive conditions (like the task performed by a subject).

- Multinomial logistic regression (MLR): Linear classifier that can be efficiently trained using a gradient descent.

- k-nearest neighbour (kNN): Classifier that uses k known specimens per category to predict the category of new samples based on a similarity measure.

- Biomarker: Subset of observed features (here EC/FC links) that enable a robust classification.

- Communicability: Measure of pairwise interactions between nodes (ROIs) in a network that takes indirect paths into account. In the present study, it corresponds to interactions over time for the MOU model.

- Flow: Extension of communicability that incorporates the effect of input properties in the MOU model.

1.2 Choice of model and interpretability

In our framework we borrow the EC terminology that can be understood in a broad sense as the underlying connectivity in a generative model, here for BOLD activity. For the graphical model related to Pearson correlation taken as FC, the equivalent of EC is the partial correlation (PC, green matrix in Fig. 1A). As illustrated by the flat green autocorrelogram for non-zero time lags in Fig. 1B, the generated signals by the graphical model are independently and identically distributed (i.i.d.) variables and do not have temporal correlations. In contrast, the multivariate autoregressive process (MAR, in orange in Fig. 1A-B) can have directed connectivity (asymmetric matrix) and produces in temporally correlated signals. When these models are fitted to data, they do not capture the same part of the data structure (here spatial versus spatio-temporal). Conversely, the choice for a connectivity measure as an 'observable' on the BOLD activity to fit a model should be made adequately, knowing the mapping between the parameters (e.g. connectivity) and the signals generated by the model. When the MAR model is considered, the estimation results in directed connectivity that depends on the spatio-temporal correlation structure of the observed activity (or spatio-temporal FC). The graphical model is fitted to the spatial FC does not "naturally" give directed connectivity, although techniques based on optimization with regularization have been developed for that purpose [115].

EC usually describes causal and directional interactions that interplay with other dynamic parameters in the model to determine the global network pattern of activity. When optimizing a model to reproduce BOLD signals, the parameter can be seen as representations or "projections" of the BOLD signals, in a top-down or data-driven approach [130]. Importantly, the estimated EC depends on the choice for the model dynamics. For example, the DCM was developed to formalize the link between neural and BOLD activities [56, 126, 54]. The DCM-EC is the neuronal connectivity in a network of ROIs and determine their activities, from which the BOLD signals are generated.

We keep in mind that all interpretations of fMRI signals sit on the hypothesis that correlated BOLD activity between brain areas reflects the activity of their neuronal populations [67, 33, 91, 76], which in turn mediates the transmission of neuronal information [53]. However, many metabolic mechanisms like breathing (which are usually ignored in whole-brain models) alter the BOLD signals [106] and the adequate procedure to minimize the corruption of data and obtain a satisfactory signal-to-noise ratio is still under debate [105].

A distinct line of research [22, 38, 114, 108] has focuses on the development of whole-brain models in a more bottom-up fashion (model-driven), combining various datasets and biologically-inspired mechanisms, such as oscillators to produce rhythms observed in the brain. Such approaches allow for the study of the influence of specific parameters (as ingredients in the model) in collectively shaping the global network activity. Compared to connectivity estimation, a major distinction of many of those models is that SC is taken as the intracortical connectivity to focus on the influence of the local dynamics in shaping network activity patterns; see [94] for a review.

1.3 Consistency of pipeline from preprocessed data to modeling and analysis

The incentive for novelty has fostered the development of many methods in computational neuroscience. This makes results difficult to compare, especially for resting-state fMRI studies when no ground truth is available. Another caveat concerns network analysis when it is applied on connectivity estimates from time-varying signals (e.g. BOLD) with metrics (e.g. to detect communities) that do not genuinely relate to the physical values of the data. Our practical answer to this point is thus to develop for the same dynamic model a set of analysis tools, covering parameter inference [64] to machine learning and network analysis. Although the mathematical tractability of the model limits the richness of its dynamic repertoire compared to more elaborate bottom-up models [38, 114],

it provides an intuitive understanding for the roles of parameters as well as analytical derivations for the parameter estimation or model interpretation. We believe that such an effort for formalization and consistency is beneficial to the field, both for didactic purpose and designing tailored methodology for complex models.

The paper follows the pipeline displayed in Fig. 2A. The second section presents the dynamic model and our recent optimization procedure [64, 61] to estimate MOU-EC for whole-brain fMRI data (Fig. 2B). It also discusses technical aspects in relation with other models used with neuroimaging data. The third section shows how connectivity measures can be used to predict cognitive states (Fig. 2C) and uncover their underlying structure. Importantly, the use of datasets with multiple tasks allows for an in-depth benchmarking of the connectivity measures. It also highlights some advantages of machine learning over statistical testing in making use of the multivariate nature of connectivity measures, transposing and abstracting concepts presented in a recent study for subject identification [102]. The fourth section bridges with network analysis [63, 62], interpreting changes in MOU-EC connections in a collective and model-based manner. In particular, it adapts community detection to our model (Fig. 2D).

2   Capturing the whole-brain BOLD dynamics with MOU-EC

Using a generative model to reproduce the BOLD statistics, the optimized MOU-EC can be seen as an estimate that extracts spatio-temporal information about the BOLD *dynamics*. In fact, the main innovation of the modeling is the optimization procedure in Fig. 2B [64]. This section reviews important points about the underlying multivariate Ornstein-Uhlenbeck (MOU) dynamic model and its tuning. Further mathematical details can be found in Annex (see Fig. S1). Our approach aims to combine several key aspects:

- **Whole-brain** connectivity estimates are necessary to properly take into account the experimentally observed distributed information across distant regions [36, 27], without a-priori selection of ROIs.

- From the overall **spatio-temporal structure** of BOLD signals, the dynamic model only reproduces their covariances (without and with time lag, see Fig. 2B). This concerns the same fast timescale as recent studies [98, 99], which also demonstrated the influence of behavioral states such as sleep versus wake. The choice of BOLD covariances as observables —to be reproduced by the model— is supported by previous results that showed that most of the information was in the second-order statistics of BOLD signals [78].

- **Causality** is inherent to the concept of EC [56, 54, 130] that are represented by the directed connections in the dynamic model (red arrows in Fig. 2B). From the estimated EC that best reproduces the data, we interpret strong MOU-EC weights as causal relationships and can examine their asymmetry to evaluate for a pair of ROIs which one drives the other. The optimization can deal with common inputs for ROIs, to explain the observed correlated activity by an interplay between the directed connectivity and correlated inputs [61].

- The MOU-EC **topology** is the inter-regional infrastructure, namely which connections exist and which do not in the brain network. When SC is available, its binarization (black matrix in Fig. 1A) can be used to constrain the MOU-EC topology in order to reduce the number of parameters to estimate. This enforces the model to "explain" changes in the FC by existing connections only, in contrast to PC and MAR (Fig. 1A). It is thus important to remember that MOU-EC estimates are not related to SC values.

Figure 2: **EC-based analysis of empirical BOLD signals. A:** Pipeline for brain coordination analysis using MOU-EC. For each fMRI session, the model is optimized by tuning its parameters, especially its connectivity, to reproduce the statistics of the BOLD signals (depicted in the right side of the brain). A schematic parcellation is represented on the left hemisphere of brain. The estimated MOU-EC can then be used to predict cognitive states using classification algorithms. On the other hand, MOU-EC can be analyzed as a graph (or network) to uncover collective properties. A contribution of our approach is to link the network-oriented analysis with machine-learning techniques. **B:** From the BOLD signals, two FC matrices are calculated, FC0 without time lag in blue and FC1 with a time lag of 1 TR in green. The model parameters (EC and Σ) are optimized to reproduce these empirical FC matrices taken as 'observables'. Classification focuses on the model connectivity (MOU-EC), but the influence of Σ will be incorporated in the network analysis. See Fig. S1 for further details. **C:** Schematic representation of the FC and MOU-EC matrices (1 sample per session) in their own spaces for two cognitive states (R for rest and M for movie). For each connectivity measure, the prediction of R versus M is robust when the sample distributions represented by the dashed circles do not overlap. **D:** The left diagram represents community detection in a structural undirected network. The right diagram represents the MOU-EC networks, from which we want to define dynamical communities.

- The optimization procedure tunes all MOU-EC weights while taking into account network effects. For each fMRI session, we obtain a **multivariate** estimate of more than 1000 parameters that represent the dynamical "state" of the brain activity. This contrasts with previous models that used the symmetric SC as connectivity matrix in dynamic models and focused on choosing or tuning the nodal dynamics with a few parameters only [38, 94, 114].

- A constraint of the model up to now is the assumption of stationarity for the BOLD signals over each fMRI session, which limits our approach to ongoing non-switching tasks.

2.1 Multivariate Ornstein-Uhlenbeck dynamics as generative model for BOLD signals

Formally, our model-based analysis is based on the multivariate Ornstein-Uhlenbeck (MOU) process that is described by Eq. 3 in Annex C. It corresponds to a network with linear feedback that is the equivalent in continuous time of the discrete-time multivariate autoregressive (MAR) process. These dynamic systems with linear feedback have been widely used in neuroscience to model the propagation of fluctuating activity, mixing "noise" and structure, for example in modeling single neuronal dynamics [21], relating the connectivity and activity in a network [58] and defining neural complexity [129, 6]. It also corresponds to the linearization of nonlinear population models like Wilson-Cowan neurons [139].

The choice for the MOU dynamics is motivated by the balance between simplicity, which ensures tractable analytical calculation, and richness of the generated activity when modulating the parameters (especially the MOU-EC weights). Thus, it is well adapted to whole-brain data with parcellation involving many ROIs (≥ 100). In addition, the MOU dynamics implies exponential decaying autocovariances in the model, which have similar profiles to the empirical data (see the left plot in Fig. 1B corresponding to straight lines in log-plot in Fig. S1).

Intuitively, it can be understood as a network when fluctuating activity (akin to noise) is generated at each ROI and propagates via the recurrent EC. In other words, MOU-EC (red matrix in the bottom box) acts as a transition matrix and quantifies the propagation of fluctuating BOLD activity across ROIs. The MOU-EC matrix is usually sparse when its topology is constrained by SC (black matrix) to match anatomical white-matter connections between ROIs. The fluctuating activity for all ROIs is described by their (co)variance matrix Σ, which is diagonal in the present case (see the purple vector of variances). In a previous study, cross-correlations for Σ also involve common inputs to homotopic sensory ROIs [61].

2.2 Parameter estimation capturing network effects in BOLD propagation

To capture the BOLD dynamics (i.e. propagation of fluctuating activity), we use the two BOLD covariance matrices FC0 and FC1 in Fig. 2B, without and with time lag, respectively. This also ensures a one-to-one mapping between an FC configuration (a pair FC0 and FC1) and a MOU-EC configuration. This choice is in line with previous adjustments of DCM to model the resting-state that relied on the cross-spectrum, namely the Fourier transform of covariances with all possible time lags [54]. It is richer than fitting only an FC matrix without time lag [38, 94] and complies with a recent study of the task-dependent modification of the BOLD temporal structure at short time scales [99].

The MOU-EC estimate is obtained for the minimum model error in reproducing the empirical FC0 and FC1 for each session (see the fit plot between the boxes in Fig. S1). The optimization is akin to a 'natural' gradient descent [4] in that it takes into account the nonlinearity of the mapping from MOU-EC to the observables FC0 and FC1. This arises because of the network feedback (even

though linear) and may result in strong correlations (in FC) for disconnected ROIs (EC=0) provided strong indirect pathways connect them (via other ROIs). Annex D provides the mathematical details of the optimization, which applies the gradient descent to both MOU-EC and Σ [61], extending the initial formulation with a heuristic optimization for Σ [64].

For illustration purpose, this paper uses a whole-brain parcellation consisting with 66 ROIs. The SC density is 28%, giving 1180 MOU-EC weights to estimate (see Annex A). Each fMRI session has 300 time points separated by TR $= 2$ seconds, so the number of data points is $66 \times 300 \simeq 2.10^4$, about 16 times larger than the number of model parameters. EC should be like a summary of the BOLD signals: informative (not too short), but extracting and compressing relevant information (not too long). Our method was also successfully applied to the AAL parcellation with 116 ROIs and sessions of 5 minutes [102]. Typically, the MOU-EC estimation for a session and about 100 ROIs takes less than a minute of computation time on a desktop computer. For more refined parcellation or shorter sessions, the FC matrices may become quasi singular and the model estimates are expected to be noisier. The reduction of the number of parameters to estimate by using SC is crucial to work at the level of individual fMRI session and avoid overfitting. Here, overfitting would correspond to the situation where many distinct MOU-EC configurations in the model giving very similar FC (observables), giving a larger overlap for MOU-EC than in Fig. 2C and the same small overlap for FC. The comparison between FC and MOU-EC as multivariate representation of cognitive states will be the subject of the next section. An important conceptual difference between MOU-EC and SC is that MOU-EC accounts for the dynamical properties of the brain activity, which are modulated when engaging a task. In other words, MOU-EC is hypothesized to account for the concentration of receptors or neurotransmitters, local excitability, etc., not only the density of the synaptic fibers.

2.3 Comparison with other approaches to extract information from BOLD signals

Other approaches have been proposed to characterize activity "states" based on the temporal structure of BOLD signals. For example, the 'dynamic FC' relies on sliding windows of several tens of TRs [82, 103, 107, 68], thereby focusing on changes in correlation patterns over minutes. Shorter timescales have been explored using instantaneous phases obtained using the Hilbert transform on the BOLD signals [23] or hidden Markov models (HMMs) [137, 16]. In contrast, the MOU-EC describes the average "transition matrix" over a session while assuming stationarity of the signal propagation and the corresponding statistics (time-lagged covariances with a lag of 1 TR). Moreover, it does not involve a dynamic modulation of EC interactions as used in the DCM [54, 89, 103].

A key innovation to tackle whole-brain fMRI data is the optimization constrained by SC that determines the network topology. This means the model has to explain the spatio-temporal FC structure using the existing connections only. The "prior" information related to SC avoids the preselection of ROIs and can be seen as an alternative to model comparison in choosing the best topology using structural equations [93, 83], Granger causality analysis [66] and early versions of the DCM [56, 130] —note that a recent DCM study incorporates SC for the network topology [123]. Likewise, the MOU-EC density usually depends on the threshold applied to SC and the best choice can be decided using model comparison, although the formulation may not be as natural as in the Bayesian framework.

Several key properties were discussed a few years ago about the defining concepts of EC and DCM as compared to Granger causality analysis [130]. Beyond technical details, three main points are that DCM-EC corresponds to the connectivity weights in a dynamic model, that the model incorporates the hemodynamic response function (HRF) and that the estimation captures the BOLD dynamics, including the subsampling related to the low time resolution of BOLD signals. The EC terminology

was borrowed from the DCM literature [54] because of the model-based aspect. The MOU-EC estimation was developed to solve the trade-off between robust estimation and application to large brain network (70+ ROIs) by using linear dynamics [64]. Since then, the DCM has been applied to whole-brain fMRI data [110, 52].

The FC0 and FC1 matrices taken as observables (Fig. 2B) embody the spatio-temporal BOLD structure in the range of high frequencies. The recent extension of the DCM to analyze resting-state fMRI data reproduces the BOLD statistics via the cross-spectrum [57, 110, 52], which is in line with our approach. Recall that this contrasts with earlier versions of the DCM that reproduced the BOLD time series themselves for stimulation protocols [56, 89]. Because it works in continuous time, the MOU model deals with the BOLD subsampling [64], unlike estimation methods relying on the discrete-time multivariate autoregressive process that may be sensitive to the subsampling of the BOLD signals [120]. Moreover, the observed lags between ROIs in FC —similar to cross-correlograms [98, 99]— are explained by the combination between the estimated inputs Σ and MOU-EC [60].

The time constant τ_x in the MOU model is identical for all ROIs in Eq. (3) in Annex C, which corresponds to an abstraction of the HRF waveform response that was reported with a decay of 5 to 10 seconds [34]. An important difference of our model compared with the underlying dynamic model behind DCM [56, 130], as well as other bio-inspired network models [38], is the absence of an explicit HRF to link the neural activity to the measured BOLD signals [17, 55, 126]. Note that applications of the DCM to resting-state data involve a linearization of the HRF [110, 52]. Thereofore, a foreseen extension of our approach is that of a state-space model with the MOU process generating the neuronal activity which is convolved with a linear HRF filtering. The challenge is to keep the gradient-descent optimization tractable, as was previously done with Granger causality analysis [7, 48].

3 Machine learning for extracting multivariate biomarker specific to cognitive states

Beyond their goodness of fit and how many "realistic" biological mechanism they might incorporate, models can be used to extract information from data in a top-down approach. Once tuned, the model parameters can indeed be used to discriminate cognitive conditions, as a representation of the observed data (BOLD signals here). If this conceptually differs from finding the generative model of activity with the best fit, it is nonetheless expected that a model with poor fit hardly extracts relevant information. Many recent studies have used various connectivity measures to predict tasks performed by the subjects [69], pathological conditions [86, 109] and subject identity [96, 50, 24]. Machine learning is the standard for identifying biomarkers of neuropathologies [133] and is also widely used in voxel-based analysis for cognitive tasks [100, 138]. However, it is less frequently applied for cognition studies using connectivity measures [132]. For a given connectivity measure, a biomarker is a subset of links (i.e. matrix elements) that enables the most robust possible identification of a category of fMRI sessions. In practice, changes in BOLD activity across cognitive conditions are mixed with individual traits and session-to-session variability. Disentangling these contributions is the key to obtain efficient biomarkers [102].

The present section addresses the following questions:

- How to cope with the multivariate nature of connectivity measures (e.g. > 1000 MOU-EC links)? We illustrate some advantages of machine learning compared to statistical testing, about multiple comparisons and beyond.

- What does classification tell about the underlying model? Linear and nonlinear classifiers apply different metrics on the estimated parameters, revealing the distribution of task-specific changes.

- In a complex environment (e.g. many tasks), can we uncover a hierarchy in cognitive states (subgroups of tasks)?

Adopting the language from machine learning, 'samples' refer to fMRI sessions and the links of the connectivity measures are 'features' whose values are used to discriminate 'labels', which are the types of fMRI sessions here. To illustrate our framework, we use data that were previously analyzed [78, 90, 61], whose details are summarized in Annex A. Subjects in the scanner were recorded fixating a point in a black screen (two rest sessions R1 and R2) or a movie. The entire movie session was divided in three sessions (M1, M2 and M3), each corresponding to a different part of the movie. The vectorized MOU-EC estimates are displayed for all subjects and sessions in Fig. 3A. The question is then whether connectivity measures can capture information to identify the movie sessions individually. For example, the MOU-EC links indicated by the gray arrow exhibit strong changes between rest and movie (with small and large values, respectively).

3.1 Variability of connectivity measures with respect to cognitive labels

Before classification, the data structure can be explored to evaluate the similarity or distance across conditions between the connectivity measures, as representations of the BOLD signals. For this type of (passive) task, BOLD synchronization patterns during movie viewing between brain areas (e.g. visual and auditory) as reflected by inter-subject correlations [74] is expected to be also captured by the connectivity measures [61]. The gray arrow in Fig. 3A indicates some MOU-EC links with strong changes between rest and movie.

A usual technique for multivariate data is dimensionality reduction, for example using principal component analysis (PCA) [69] and independent component analysis [25]. Here we compare two linear transformations, the unsupervised PCA in Fig. 3B with the supervised linear discriminant analysis (LDA) in Fig. 3C. The principal component is the direction in the high-dimension space with largest variability across the samples and successive components are ranked in decreasing order for their corresponding variability. It is called unsupervised because it does not use the task labels to compute the components, as can be seen for FC where the first component is not related to the task labels. In comparison, the components for LDA are ranked according to their variability *with respect to task labels*. This can be seen for FC where the first component for PCA does not reflect the separation between movie and rest (the second component does).

The separation of the tasks viewed using the connectivity measures can be evaluated using silhouette coefficients that measure the clustering quality [112], ranging from 1 for separated dot clouds to -1 for overlapping dot clouds. Applied to the LDA coordinates in Fig. 3D), we see a slow increase in silhouette coefficient when incorporating more components to separate the 4 clouds. This reflects the difficulty of the 4-task discrimination, compared to that for the 2 tasks where a single component is sufficient. The viewpoint here is that of clustering, assuming that the reduced space allows for isolating the clouds to characterize the cognitive states [69]

3.2 Cross-validation for assessing the generalization capability of connectivity-based classification

Although machine-learning techniques are now increasingly used to analyze neuroimaging data, the generalization capabilities are not always properly verified [133]. For example, clustering algorithms

Figure 3: **Dimensionality reduction of the connectivity measures. A:** Connectivity estimates (here vectorized EC) for 5 sessions, 2 for rest and 3 for movie, for each of the 22 subject. The 3 movie sessions each correspond to a distinct part (10 minutes) of a movie watched and listened by the subjects. The gray arrow indicates connections (or links) that strongly differ between rest and movie. **B:** Principal component analysis (PCA) applied to the vectorized EC, FC and PC (one for each of the 110 sessions) where the same colors as in panel A correspond to the 4 tasks. For PCA the task labels are not used in the dimensionality reduction (unsupervised algorithm). **C:** Similar plot to panel B with linear discriminant analysis (LDA) for which the labels are used (supervised learning) to separate the 4 tasks for the 110 sessions. **D:** The silhouette coefficient measures the quality of the clustering for the dot clouds when varying the number of LD components (see x-axis). The solid curves correspond to the 4 tasks and the dotted curves to rest versus movie (dark gray versus colors in panel C).

Figure 4: **Train-test classification for task or subject identification. A:** The train-test procedure consists in splitting the sessions in a train set and a test set. The train set is used to optimize the classifier (here find the best boundaries between labels, see dashed green lines), whose accuracy is then measured on the test set. **B:** Accuracy for the classification of session to discriminate movie versus rest (2 labels) for the MLR, 1NN and LDA classifiers, as indicated by the colors. The connectivity measure are indicated on the x-axis: the masked FC is the subset of FC features corresponding to the SC mask used for the MOU-EC model; 'heur' corresponds to the symmetric connectivity matrix obtained using the heuristic optimization in Annex D.2. The classifiers are trained with 80% of the subjects and tested on the remaining subjects, over 40 repetitions. The dashed line indicates the chance level, which corresponds to predicting always movie (3 sessions out of 5). The MLR gives perfect classification for all connectivity measures except for MAR. **C:** Same as panel B for the classification of session to identify the 4 tasks (3 movie sessions and rest). The chance level corresponds to predicting always rest (2 sessions out of 5). **D:** The confusion matrix indicates the errors of the MLR classifier trained with 5 labels (2 labels for rest here), as indicated by the dark green off-diagonal pixels. As expected from panel B, rest and movie are well separated. The movie sessions (M1 to M3) are distinguishable to some extent, but not the rest sessions (R1 and R2). **E-F:** Same as panels C-D for the identification of the 22 subjects. The confusion matrix is rescaled to show the distribution of errors. **G:** Model error for the MOU-EC and heuristic optimizations in the two conditions.

applied on reduced-dimension components (see Fig. 3B-C) give a measure for the separation of the tasks viewed using the connectivity measures (Fig. 3D). The issue is that all sessions are used in the dimensionality reduction there. To evaluate the robustness of a classifier, a cross-validation procedure with train and test sets as described in Fig. 4A is the standard procedure for voxel-wise studies for activation maps [100, 138] and for clinical applications [109, 79]. Note that one may have to include preprocessing steps in the cross-validation scheme to properly evaluate the generalization capability of the classification, for example with functional parcellations derived from the data that should be calculated on the train set only [19]. For LDA in Fig. 3C, this corresponds to setting a linear boundary using the dimensionality reduction on the train set and evaluating the performance on the test set. Here we use cross-validation across subjects, taking 80% of subjects for training and the rest for testing the classifier. This ratio of 80%-20% is often used to evaluate the generalization capability with respect to unseen data (e.g. a new subject in the future). It corresponds to the trade-off between sufficiently many training samples to extract a signature that generalizes over subjects and sufficiently many samples to stabilize the classification accuracy over repetitions.

We consider task discrimination in two flavors: movie versus rest (2 tasks) in Fig. 4B and the movie sessions individually plus rest (4 tasks) in Fig. 4C. For each case, the performance should be considered relatively to perfect accuracy and chance level (dashed line). As expected from Fig. 3, the 4-task discrimination is more difficult that the 2-task one. The relative performance decreases by about a half of perfect accuracy for the 4 tasks compared to the 2 tasks. There are three interesting points coming from the comparison of the performances between the connectivity measures.

First, the MLR and LDA perform much better than the 1NN for the 4-task discrimination, both with MOU-EC and FC; this does not change when using kNN instead of 1NN. This agrees with previous results on subject identification [102] that are transposed to the present dataset in Fig. 4E. For task identification, the Pearson-correlation similarity for FC or MOU-EC does not seem the best choice, especially when the environment is complex. A technical point here is that LDA takes a long time to be trained for a large number of features or for many labels (subjects in Fig. 4E). Over all these results, the MLR seems the best practical choice for a classifier.

Second, and more importantly, the masked FC performs worse than FC for the 4 tasks in Fig. 4C, demonstrating that the SC mask (with 25% density here) cannot be directly used to preselect the most informative FC links that contribute to the good performance. In contrast, MOU-EC has the same number of features as the masked FC and performs as well as FC (up to a few %), even though the silhouette coefficients in Fig. 3D were clearly lower for MOU-EC than FC. Moreover, the MAR connectivity estimate, which extracts temporal information from BOLD signals as MOU-EC does, gives very poor accuracy, even for the 2-task classification. Partial correlations are somewhat in between. For subject identification, MOU-EC performs better than FC in Fig. 4E, in line with previous results [102]. Taken together, these results show that the dynamic model used for MOU-EC estimation is well suited to extract relevant information from the BOLD signals. In a way, MOU-EC can be seen as a more compressed version of the BOLD information than FC (i.e. with fewer parameters) without loss of information.

Last, we consider the symmetric connectivity obtained by the heuristic optimization in Annex D.2 that tunes the MOU model to reproduce the zero-lag covariance FC. In Fig. 4G, the goodness of fit is better for the heuristic method (smaller model error). Moreover, it leads to perfect accuracy for the "simple" classification rest versus movie (Fig. 4B). However, the accuracy decreases by at least 10% compared to MOU-EC for the 4-task and subject classifications (Fig. 4C-E). This shows that the choice for the observable and the connectivity estimation method is crucial to efficiently extract information from the BOLD signals.

3.3 Capturing the hierarchy of cognitive states

The high dimensionality of connectivity measures allows for representing complex environments, such as the 4 tasks considered here. Beyond their ability to classify, the important question is whether MOU-EC or FC can capture the structure of the task categories —rest on one hand and the group of three movie sessions on the other. A similar goal was sought using clustering on FC to identify subtypes of depression [42], although concerns have been raised about the reproducibility of the results [41]. Clustering corresponds to unsupervised learning (without cognitive labels) and seeks a structure in the data for a given metric as with the first two components of PCA in Fig. 3B.

Instead, we rely on supervised learning and propose labels as an informed guess to a classifier, then assess whether they are meaningful using cross-validation. Beyond the performances of the 2-task and 4-task classifications in Fig. 4B-C, each classifier thus defines is a similarity metric for the connectivity measures. This is reflected in the confusion matrices in Fig. 4D, where the classification errors (dark off-diagonal green pixels) indicate which cognitive states are difficult to separate. By the naked eye, the structure of the left confusion matrix for the MLR determines a hierarchy that corresponds to the desired one, similar to the clustering in Fig. 3B and C. When asked to discriminate between the two rest sessions, the classifier gives a negative answer. The three movie sessions are identifiable even though the MLR classifier makes errors between them. In contrast, the right confusion matrix for the 1NN does not provide useful information. Similar matrices without a clear hierarchy are obtained for FC (not shown). This suggests that the Pearson correlation used as a similarity measure in the 1NN is not well suited to describe the cognitive states with sufficient flexibility. In other words, it is less the global EC/FC profile than specific links that significantly vary across tasks and should be the basis for building the task hierarchy. We do not enter into further details here, leaving the comparison between unsupervised and supervised learning in estimating label hierarchies in more depth for future work. As a last comparison, the confusion matrix for subjects in Fig. 4F shows that subjects are well discriminated and no particular structure in the errors is observed, indicating an absence of grouping subjects.

3.4 Biomarker formed of informative MOU-EC links: machine learning versus statistical testing

A biomarker can be extracted for the 2-task and 4-task classifications in Fig. 4B-C by identifying the links that contribute to the correct classification. To do so, we employ recursive feature elimination (RFE) that efficiently works with the MLR classifier [71]. It provides a ranking of the features in order of importance and we select the first ones that give maximal performance. A previous study compared the subnetworks of informative links for subjects and tasks to see whether the two classifications were biased one by the other [102]. Here we make another comparison with the two support networks in Fig. 5E, movie versus rest (10 black and 5 gray links) and for the 4 tasks (10 black and 18 red links). The 10 common links are also a hallmark of the hierarchy mentioned in the previous section, as the more 4-task biomarker extends the 2-task biomarker. Furthermore, the two RFE rankings are strongly aligned (Spearman correlation $\ll 10^{-10}$).

Now we discuss the pros and cons of machine learning compared to statistical testing in finding correlates (i.e. link changes) of cognitive tasks. Formally, these two methods correspond to distinct questions that relate to opposite mappings from measured variables to conditions: changes in the variables across conditions for statistical testing and the prediction of conditions based on the variables for machine learning. However, they can be used to address the same practical question, especially when interpreting data in two conditions (as here with rest versus movie). In neuroimaging data a crucial point relates to the high dimensionality of connectivity measures, which leads to repeated hypothesis testing —are MOU-EC values different across two conditions?— over the 1180

A Support network of informative links

gray: 2 tasks only (rest versus movie)
black: 2 tasks and 4 tasks
red: 4 tasks only

B Classification ranking versus
statistical significance

Figure 5: **Biomarker for tasks and subjects. A:** Support network of the 25 most informative MOU-EC links for the task identification, obtained using recursive feature elimination (RFE). Black links are common to the easier discrimination between rest and movie, whereas red links are specific to the 4 tasks. The ROI colors indicate anatomical grouping: yellow = occipital, green = parietal, cyan = temporal, gray = central, orange = frontal and purple = cingulate. **B:** Correspondence between p-values for Mann-Whitney tests and RFE rankings for the 1180 MOU-EC links. For the 2 tasks, we show two significance thresholds for multiple comparisons: the Benjamini-Hochberg correction (dashed line) and Bonferroni correction equal to $-\log_{10}(0.05/1180)$ (dashed-dotted line). For the 4 tasks, the maximum of the p-values for the 6 pairwise comparisons is plotted, with the same Bonferroni threshold.

connections. This calls for correction for multiple comparisons, which is problematic as the number of connections scales with the square of the number of ROIs in general. We illustrate this point by calculating the p-values for the non-parametric Mann-Whitney test between rest and movie MOU-EC weights for each connection (left plot in Fig. 5F). To identify links that strongly differ across conditions, we use the significance threshold with Bonferroni correction (dashed-dotted line), here $-\log_{10}(0.05/1180)$ for 1180 MOU-EC links, or better with Benjamini-Hochberg correction [10] (dashed line). The same can be done for the 4 tasks (right plot), which involves 6 pairwise tests between the 4 cognitive states. For each connection we retain the smallest p-value among the 6 (as it is informative for at least a pairwise discrimination). For the Bonferroni correction, this gives 47 connections passing the significance threshold for the 4-task, to be compared with 75 for 2 tasks. Using Benjamini-Hochberg correction, we find for the two classifications 346 and 412 links, respectively. This does not satisfactorily reflect the increase of complexity of the cognitive labels —more labels require more connections in the biomarker— while the support network obtained using RFE in Fig. 5E provides a satisfactory description. More importantly, the comparison of the mapping between p-values and the RFE ranking in Fig. 5F also illustrates that efficient classification may rely on link with poor p-values, and that this phenomenon may be stronger when the number of categories increases (like labels here). This conclusion also holds when using the parametric Welch t-test instead of the non-parametric Mann-Whitney test. Beyond the details of the present example, machine learning seems better suited than statistical testing to deal with connectivity measures in a context of multiple labels.

Another conceptual difference between the two approaches is the Gaussian assumption for the parameter distribution. For example, DCM relies in many cases on a single generative model with a distribution for each parameters —typically determined by a mean and a variance for each connection weights— and selects the model that provides the best evidence for all observed FC matrices. Instead, we estimate a single MOU-EC matrix per session, which builds a distribution of point samples for each connection. It remains to explore the implications of the difference in the natures of the estimate distributions and the detection of significant changes in MOU-EC —using the Bayesian machinery for DCM and standard machine learning in our case.

4   Network-oriented analysis for interpreting collective MOU-EC changes across conditions

So far, we have shown how the changes in estimated MOU-EC across conditions can be identified using machine learning. Now, we turn to the collective analysis of MOU-EC as a network. Tools from graph theory have been extensively applied to explore the brain network and understand how cognitive functions were distributed over subnetworks of ROIs. The study of both FC or SC has revealed a hierarchical organization of modular networks that are interconnected by hubs [77, 131, 142], which can be modulated depending on the subject's condition [95, 12, 118]. A particular focus has been on the relationship between the SC and FC [124, 14], in particular using dynamic models at the mesoscopic or macroscopic level [80, 58, 36, 103, 94, 18, 117, 52].

A limitation in many SC and FC studies comes from the direct application of graph measures defined for binary data. In such cases the SC or FC is often binarized after choosing an arbitrary threshold, discarding the information conveyed by the graded values. For SC, a threshold on the fiber density gives the skeleton of strong connections. However, the use of a threshold seems more arbitrary for FC, especially as the brain globally exhibits strong correlations. Another aspect is often overlooked: brain connectivity measures such as FC are inferred from signals that have a temporal structure. This means that network analysis should take time into account. A possibility

is to analyze the evolution of snapshot networks over time using dynamic FC based on sliding windows [85, 127, 5] or a model activity [37]. A last point is that graph measures are often applied to the observed BOLD activity [49, 35, 51] or its counterpart in models [39]. It can therefore be argued that such "integration" measures somehow rely on the observed phenomena (in empirical or model activity) rather than their causes. Rather, models enable the application of graph measures to the underlying connectivity that generates the dynamics, as was discussed in a previous study [110].

Here we rely on our adaptation of graph-like measures for the network dynamics themselves [63, 62], whose main details are presented in the following text; see also Annex E for mathematical details. This section illustrates the following aspects of network-oriented analysis for MOU-EC:

- How to interpret collective changes in MOU-EC in their contribution to shape the network dynamics? We introduce the notion of 'integration time' that discriminates early and late interactions between ROIs in response to a (local) perturbation in the network via MOU-EC.

- Are network measures relevant for discriminating across conditions? Beyond the single-link analysis in Fig. 4, which scale is adequate, like ROIs or groups of ROIs?

- How to detect functional communities from MOU-EC estimates? How strongly is the community structure affected depending on the task performed by subjects?

4.1 Flow as graph-like measure for ROI-ROI interactions across 'integration time'

Figure 6: **Network-oriented analysis of MOU-EC using flow. A:** Conceptual illustration of communicability and flow. The propagation of activity builds up develops over the 'integration time', yielding interactions between ROIs that are not directly connected by MOU-EC. **B:** Two matrices representing the communicability interactions for all 66 ROIs for a single subject at 2 integration times. Initially similar to MOU-EC values, communicability becomes homogeneous. **C:** Example subset of anatomical ROI groups: occipital (OCC), temporal (TMP), parietal (PAR) and frontal (FRNT). **D:** Change in input and output flow as a function of integration time, which sum all incoming and outgoing flow interactions for each ROI, respectively. The ROIs are ordered by anatomical areas and grouped in pairs of left- and right-hemisphere ROIs. **E:** Comparison between the flow between the rest (in black) and movie (in brown) conditions. The curves are averages over subjects and corresponding sessions with error bars indicating the standard error of the mean. Each row corresponds to the flow between ROI groups in panel B; see Eq. (15) for the total flow corresponding to the first row. The upper light-brown (dark-brown) bar indicates the period where the movie flow is significantly larger than the rest flow with p-value < 0.05 (0.01). **F:** Classification based on flow to discriminate rest versus movie (top plot) and the 4 tasks (bottom plot). The features correspond to the flow or MOU-EC for the same ROI groups as in panel C, with directionality indicated along the x-axis. We compare the multivariate flow (orange violin plots) using the relevant matrix elements as a vector of features, their sum (blue violin plots, corresponding to panel D) and the corresponding MOU-EC weights (green violin plots). The dashed black lines indicate chance level.

Our definition of *flow* takes advantage of the information provided by the dynamic model, here applied to the MOU process [63]. As illustrated in Fig. 6A, MOU-EC quantifies the instantaneous causal interactions between pairs of ROIs and the Σ matrix measures the spontaneous or input activity level that each ROI receives (here represented only for ROI i). Built on those estimates, the flow measures the influence of a perturbation at a source ROI i onto a target ROI k after a

A Flow

EC_{kj} $F_{ki}(t)$

EC_{ji}

Σ_{ii}

integration time

B early interactions → late interactions

target ROI

source ROI   source ROI

C FRNT TMP PAR OCC EC Σ

D ROI-based flow measure

input flow   output flow

Difference movie minus rest

integration time (TR)

E Flow decomposition

full

OCC+TMP → PAR

PAR → OCC+TMP

PAR → FRNT

FRNT → PAR

OCC+TMP → FRNT

FRNT → OCC+TMP

total flow

integration time (TR)

F Flow-based classification

multivariate flow   EC

PAR ROI

OCC+TMP ROI   OCC+TMP ROI

summed flow (univariate)

2-task accuracy

full   OCC+TMP↔PAR   PAR↔FRNT   OCC+TMP↔FRNT

given delay, which we call 'integration time'. Importantly, the flow takes into account the network effect (or network response), meaning the contribution of indirect paths in the network (from ROI i to ROI k via ROI j in the figure). See Annex E for the mathematical formulation based on the network impulse response (or Green function), which is analytically tractable for the MOU process. The flow thus aims to capture the dynamic response of the brain to local spontaneous activity (or external inputs) as it propagates from region to region in the network. A special case of flow —termed *dynamic communicability*— that only depends on the MOU-EC (and not Σ) can also be defined assuming that all ROIs have independent spontaneous activity with the same intensity; it corresponds to a diagonal and homogeneous matrix Σ. Like the flow, dynamic communicability describes directional interactions, which differs from the symmetric interactions obtained from the direct application of graph theory to FC or SC [62]. It is worth stressing that the flow and dynamic communicability are graph-like measures that genuinely capture the properties of weighted networks, similar to the previously-proposed graph communicability [47, 46]. In the following we focus on the flow to interpret the BOLD dynamics.

4.2 Integration in the brain network

Following experiments on the propagation of stimulus information from sensory areas to "high-level" brain areas in relation with being conscious of the stimuli [40, 26], the concept of integration was defined in models by quantifying the influence between regions while being in a broader network. Considering again the fMRI dataset in Annex A, we evaluate the flow for the two conditions, movie and rest. Our previous analysis of the same dataset showed that the modulations of MOU-EC between rest and movie implemented a selection of pathways in the cortex [61]. In addition, sensory inputs were reflected by changes in Σ in the model. Here we examine the flow at various scales to test how it captures differences in the BOLD propagation within the brain network. Note that the 'effective drive' defined in our previous study [61] corresponds to the flow at early integration time. The flow changes in Fig. 6D indicate differentiated effects among the ROIs, with increased/decreased listening for input flow and broadcasting for output flow. A previous analysis based on MOU-EC [119] examined the task-dependent changes for the rich club of ROIs that have dense anatomical connectivity and are involved in the default-mode network, namely the precuneus (PCUN), superior parietal cortex (SP) and superior frontal cortex (SF). In line with those previous results, we find an increase of output flow to the rest of the brain (even though small for PCUN). Here among the ROIs with strong increases in output flow, we find the post-cingulate gyrus (PC) in addition to SP, which agrees with previous results about the default-mode network [135, 136].

It is sometimes interesting to evaluate changes for specific brain subsystems, which in our case concerns occipital and temporal ROIs that are related to vision and audition. As an example, we step aside from the whole-brain approach and consider the ROI groups in Fig. 6C, where "sensory inputs" are expected to be reflected as increased Σ in OCC and TMP. Fig. 6E displays the summed flow between the ROI groups in Fig. 6C, comparing the two conditions: black for rest and brown for movie. The total flow over all ROIs shows a weakly, but significant, increase for movie, as indicated by the light brown squares in Fig. 6E. From the significance viewpoint, the preferred pathway in terms of estimated summed flow follows a staged hierarchy from sensory (occipital and temporal) to the parietal ROIs and then to frontal ROIs, see thick arrows in Fig. 6B. In this case the parietal ROIs thus play the role of integration and relay.

The machine-learning equivalent of the statistical testing for the summed flow between subnetworks in Fig. 6C corresponds to the blue violin plots in Fig. 6F. Here a good accuracy means that the pathway is strongly modulated between rest and movie, but the blue violin plots are close to chance level, indicating a weak generalization across subjects. A different question is to which extent the

detailed pattern of flow vary between movie and rest, which is referred to as the multivariate flow (in orange). The striking difference between univariate and multivariate flows indicates that the selection of pathways is diverse for ROI groups. Moreover, the discrepancies with changes in MOU-EC for the same matrix elements (green) shows the importance of network effects, for instance from parietal to frontal ROIs. It is also worth noting the directionality in the changes, for example strong changes from parietal to frontal ROIs, but not the converse. These results speak to a global balance of overall flow in the cortex, with detailed reorganization of cortical pathways [61]. Together with the distributed signature found in Fig. 5F, they also highlight the need for a whole-brain approach to understand the cortical reconfiguration [13], contrasting with previous studies relying on hypothesis testing for a-priori selected ROIs [66, 32, 28, 45].

4.3 Detection of functional communities determined by flow

In parallel to integration, the concept of complexity has been often used to differentiate brain states [129, 128, 6, 141]. Intuitively, complexity measures quantify the diversity of organizational motifs in a network, in the range of interest between the trivial extremes of full disconnectivity and full connectivity. A proxy for complexity is the detection of ROI communities because modular networks are a stereotypical model for complex networks, as was observed with SC [142]. Here we use the flow as a basis for the functional ROI communities in a data-driven manner, which contrasts with the anatomical grouping in Fig. 6C. Such methods developed initially for graphs with a metric called modularity based on weights [101]. Here we consider communities determined by the flow, namely ROIs with strong exchange of activity in the estimated dynamics [63].

Fig. 7A displays the evolution of communities over integration time for rest and movie. Strong coparticipation values indicate the robustness of the community structure across subjects. It shows a merging of almost all ROIs that eventually exchange flow in an even manner. This agrees with our previous results for resting state only and a different parcellation [62]. This speaks to a transition from segregated processing (within each diagonal block of left matrices) to a global integration. The number of communities can be taken as another proxy for the complexity in the brain network and our approach provides a dynamical perspective about it. The community merging goes hand in hand with the homogenization of the flow matrix in Fig. 7B, as quantified by the diversity of the matrix elements in the flow matrix that decreases and eventually stabilizes [63]. In our data the diversity is slightly higher for movie compared to rest.

Going a step further, we can examine the difference between the community structures of the two conditions, see the last row of Fig. 7A. This shows that the changes in flow for specific pairs of ROIs between rest and movie (Fig. 6F) have an important collective impact. The strongest differences appear when the network effects are very strong at $t = 4$ TRs. This is confirmed by Fig. 7C, where the flow is most different between rest and movie at the same integration time (see arrow). These results bridge between the local and global scales, as they describe the organization of groups of ROIs determined by MOU-EC properties.

5 Conclusions

This paper combines important aspects of our MOU-EC framework into a general and flexible formalism to study cognition using fMRI/BOLD data. Our model-based approach allows for the analysis of whole-brain dynamics at various scales, from individual connections to ROI-centric and global measures. We stress that it is consistent from estimation to interpretation, focusing on the dynamical aspect of the network model. By fitting the dynamic model to the spatio-temporal covariance structure of the BOLD signals, our approach aims to capture the BOLD dynamics averaged

Figure 7: **Community detection. A:** Communities correspond to ROIs that bidirectionally exchange strong flow. Darker orange pixels indicate stable communities across the subjects for the each condition. The top row corresponds to rest and the middle row to movie for three integration times. The bottom row displays the significant increases (in red) and decreases (blue) of the community coparticipation values for movie with respect to rest. Here statistical testing is performed by computing surrogate communities by mixing the condition and retaining values outside the 90% central values. The ROI ordering corresponds to the early community structure for rest. **B:** Flow diversity for rest (black curve) and movie (in brown) measuring the heterogeneity within each flow matrix when integration time increases; see Eq. (16). It is a proxy for the "complexity" of interactions between ROIs; for details see [63, 62]. **C:** 4-task classification based on flow (same as full flow in Fig. 6E) as a function of integration time and comparison with EC-based classification. The maximum at $t = 4$ TRs is indicated by the arrow.

over each fMRI session. The estimated MOU-EC can be seen as a "projection" of the BOLD signals on anatomically-constrained connectivity, thereby characterizing the dynamical state of the brain. In contrast, analyses based on the static FC can be considered as a "projection" of BOLD signals on a graphical model, and thus does not take the temporal dimension into account (i.e. BOLD values are i.i.d. variables). Dynamic FC methods have been developed to incorporate time in the analysis [103, 107, 68, 23], but they do not genuinely capture the propagating nature of BOLD signals. Dynamic causal models have just been adapted to deal with whole-brain fMRI data [110, 104, 52] and it will be interesting to compare the estimated connectivities.

The MOU process provides a useful balance between the richness of the generated BOLD dynamics, the robustness of the model optimization and intuition for interpretability. Behind the model details, this work has illustrated important concepts related to the use of whole-brain dynamic models for quantifying "states" related to cognition (or neuropathologies) and for interpreting BOLD signals in a collective manner.

5.1 Biomarkers for cognition and neuropathologies

The robust estimation of the (multivariate) parameters allows for a powerful representation of cognitive states by the MOU-EC estimates (Fig. 4), as well as the extraction of task-specific biomarkers (Fig. 5). An important point considering connectivity measures is that machine learning solves the problem of multiple comparisons: instead of determining p-values and then a threshold for connections with significant changes, we can characterize which MOU-EC links —as features— contribute to the correct classification. It has been recently advocated that machine learning can be used to avoid "excessive reductionism", namely linking brain activity in localized regions to narrow experimental protocols in a way that cannot generalize to more complex protocols [132]. Although the focus has been on machine-learning techniques, we remind that hypothesis testing of significant changes for preselected ROIs or links can be performed in our framework (see Fig. 6D-E with the flow). In that case, whole-brain changes can also provide a baseline reference for the considered links or ROIs. Beyond the fact that though the question

On the technical side, it remains to be explored which parcellation gives the best biomarkers, as evaluated using the classification performance [31, 43, 65]. The trade-off to solve is between the richness of the connectivity measure (more links can reproduce richer environments) and their robustness (more parameters may result in noisier estimation). The alignment of distinct datasets with various MRI protocols also remains a difficult question for practical application to large datasets [134].

In parallel to the study of cognition, the presented framework can be applied to neuropathologies with the aim to inform clinical diagnosis [92]. The rationale is that BOLD activity specifically reflects neuropathologies, even in the resting state [70, 79]. If SC is increasingly used for strokes or Alzheimer disease that strongly impact the brain anatomy, fMRI may provide additional information [121, 72]. Other diseases like depression [42] or some motor disorders [113] may be better investigated using functional imaging. Importantly, many neural diseases are likely to affect multiple brain regions and thus require adequate tools to capture their distributed nature. Another direction where machine learning is a key tool is the development of personalized medicine, adapting the models to individual patients beyond group analyses [140].

5.2 Network-oriented analysis of dynamics

The network analysis for our dynamic model relies on the flow, a graph-like connectivity measure that describes the integration of propagating activity in the network (Figs. 6 and 7). In particular, small changes in EC that are not individually significant can collectively induce large changes in the flow, especially when feedback loops are involved. In this sense, the flow quantitatively captures the

Figure 8: Schematic representation of the extraction of biomarkers for three tasks compared to rest. Connection-wise biomarkers corresponds to changes in EC while the bottom row refers to biomarkers for changes in flow in the dynamic network. Tasks A and B correspond to two modulations of the connectivity, which lead to similar changes in the flow of the dynamic system (stronger for B). For task C, extra inputs are received by two nodes, which increase the flow towards the corresponding two target nodes.

interplay between parameters, so the resulting communication cannot always be simply understood at the level of single estimated parameters. As an example, many small changes in EC (below significance level) may collectively result in a strong dynamical effect, as seen for task A in Fig. 8. Strong coordinated changes in EC result in large changes in the dynamics (task B). Moreover, changes in input properties may only be captured by the dynamics, in particular when the connectivity does not change (task C). Building biomarkers that capture network effects is important to make use of the multivariate nature of the fMRI data. This is important when interpreting data in terms of concepts such as integration, segregation and complexity [128, 40, 39, 141].

5.3   Limitations and future work

Recall also that any interpretation of BOLD in term of brain communication relies on the assumption that changes in neuronal activity are reliably reflected in the BOLD signals, which is under debate [67, 91, 76]. In practice, the preprocessing of fMRI signals must strive to increase the signal-to-noise ratio [106, 105].

Recall also that causal interactions between brain regions come from the directed connectivity in the model, whose "best"' parametrization is estimated from the data. Without a proper experimental interaction with the brain activity, the notion of causality is subject to the initial model assumption [84, 81]. This remark also applies to other methods for directed connectivity, such as Granger causality and DCM [130]. The quantitative comparison between MOU-EC and such other methods to extract biomarkers or interpret fMRI data will be the subject for future studies. A particular point concerns the observed heterogeneity of HRF across different brain regions and how it affects the estimated connectivity and its directionality.

The basic tools for the presented analyses are available in the open-source language Python with

example data on `github.com/MatthieuGilson/WBLEC_toolbox`. The classification uses the library scikit-learn [2].

Annex:

The following sections summarize details about the data and mathematical framework used in this paper. For machine learning, the readers are referred to the online documentation `http://scikit-learn.org/` of the scikit-learn library [2].

A Movie dataset

The experimental procedure was approved by the Ethics Committee of the Chieti University and the participants signed a written informed consent. We use the data from 22 right-handed young and healthy volunteers (15 females, 20-31 years old) that had recordings for both a resting state with eyes opened and a natural viewing condition (30 minutes of the movie 'The Good, the Bad and the Ugly').

The fMRI time resolution (TR) is 2 seconds and each session of 10 minutes corresponds to 300 frames (or volumes). The preprocessing performed using SPM8 involves the coregistration of structural and functional MRI, spatial normalization in the MNI coordinates and motion correction. The data are parcellated in $N = 66$ ROIs [73]. The generic structural matrix is obtained from averaging individual matrices obtained using the diffusion spectrum imaging. A threshold was then applied to retain the 27% largest connections. Inter-hemispheric connections between homotopic ROIs were added, increasing the density to 28%. The same generic SC matrix is used to determine the MOU-EC topology for all subjects.

We refer the readers to previous publications [78, 90, 61] for further details.

B Functional connectivity measures

For each session of $T = 300$ time points (2 for rest and 3 for movie), we denote the BOLD time series by s_i^t for each region $1 \leq i \leq N$ with time indexed by $1 \leq t \leq T$. The mean signal is $\bar{s}_i = \frac{1}{T} \sum_t s_i^t$ for all i. Following [64], the empirical FC consists of two BOLD covariance matrices (see the blue and green matrices in the top box of Fig. S1), without and with time lag:

$$\widehat{Q}_{ij}^0 = \frac{1}{T-2} \sum_{1 \leq t \leq T-1} (s_i^t - \bar{s}_i)(s_j^t - \bar{s}_j) \; , \tag{1}$$

$$\widehat{Q}_{ij}^1 = \frac{1}{T-2} \sum_{1 \leq t \leq T-1} (s_i^t - \bar{s}_i)(s_j^{t+1} - \bar{s}_j) \; .$$

Pearson correlation can be calculated from the covariances in Eq. (1):

$$K_{ij} = \frac{\widehat{Q}_{ij}^0}{\sqrt{\widehat{Q}_{ii}^0 \widehat{Q}_{jj}^0}} \; . \tag{2}$$

C Multivariate Ornstein-Uhlenbeck (MOU) process to model whole-brain dynamics

The network dynamics are determined by two sets of parameters:

- the time constant τ_x is an abstraction of the

Figure S1: **Dynamic model and optimization procedure to capture BOLD dynamics.**
From the BOLD signals of the parcellation (top left in top box), two empirical FC matrices (blue
and green matrices) are calculated, both without and with time lag as depicted by the blue and green
curve. The dynamic network model describes the activity of the ROIs (only two are represented
by the grey circles) and comprises a parameter for the spontaneous activity of each ROI (Σ in
the bottom box) and for each directed connection between ROIs (effective connectivity, MOU-EC).
The topology of existing connections is determined by the structural connectivity (black matrix
in top box). The optimization of the model is similar to a gradient descent during which the
model FC matrices are evaluated at each step and compared to their empirical counterparts. From
the differences between the corresponding matrices an update of the MOU-EC and Σ parameters
is calculated and the procedure is repeated until reaching a minimum for the model error (light
gray-blue curves in the left central panel between the boxes), which corresponds to a high value
for the Pearson correlation between the matrix elements of the model and empirical FCs (black
curve). Before the optimization, the time constant τ_x of the BOLD autocovariances (see log-plot)
is evaluated to calibrate the nodal dynamics in the model. Details can be found in [64, 61].

- the network effective connectivity (MOU-EC) between these ROIs embodied by the matrix C, whose topological skeleton is determined by structural data;

- the local variability embodied in the matrix Σ inputed individually to each of the $N = 66$ ROIs.

The activity variables obey are described by a multivariate Ornstein-Uhlenbeck process. Each activity variable x_i of node i decays exponentially according to the time constant τ_x and evolves depending on the activity of other populations:

$$\mathrm{d}x_i = \big(\frac{-x_i}{\tau_x} + \sum_{j \neq i} C_{ij} x_j\big)\mathrm{d}t + \mathrm{d}B_i \ . \tag{3}$$

Here the fluctuating inputs $\mathrm{d}B_i$ are independent and correspond to a diagonal covariance matrix Σ, as represented in purple by the vector of variances Σ_{ii} in the bottom box of Fig. S1. In the model, all variables x_i have zero mean. Their spatiotemporal covariances are denoted by Q_{ij}^1, where $\tau \in \{0, 1\}$ is the time lag, and correspond to the the blue and green matrices in the bottom box of Fig. S1. They can be calculated by solving the consistency equations:

$$JQ^0 + Q^0 J^\dagger \ = \ -\Sigma \ , \tag{4}$$
$$Q^1 \ = \ Q^0 e^{J^\dagger} \ . \tag{5}$$

The first equation is the continuous Lyapunov equation, which can be solved using the Bartels-Stewart algorithm in scipy [1]. Here J is the Jacobian of the dynamical system and depends on the time constant τ_x and the network MOU-EC: $J_{ij} = \frac{-\delta_{ij}}{\tau_x} + C_{ij}$, where δ_{ij} is the Kronecker delta and the superscript $\dagger$ denotes the matrix transpose. In the second equation e denotes the matrix exponential.

Ideally, the model should be extended to incorporate subcortical areas and the relevance of input cross-correlations inputs should be evaluated for all ROI pairs [102].

D Parameter estimation procedures

D.1 Lyapunov optimization or natural gradient descent

We tune the model such that its covariance matrices Q^0 and Q^1 reproduce the empirical FC0 and FC1 matrices in Fig. 2B, denoted here by $\widehat{Q}^0$ and $\widehat{Q}^1$, respectively. The uniqueness of this maximum-likelihood estimation follows from the bijective mapping from the model parameters τ_x, C and Σ to the FC pair (Q^0, Q^1). The iterative optimization procedure for C is similar to the original version [64], which can be related to the concept of "natural" gradient descent [4] that takes the non-linearity of the mapping between J and the matrix pair Q^0 and Q^1 in the second line of Eq. (4). Note that the parameters τ_x and Σ also follow a gradient descent now.

For each session (subject and condition), we calculate the time constant τ_{ac} associated with the exponential decay of the autocovariance averaged over all ROIs using time lags from 0 to 2 TRs:

$$\tau_{\mathrm{ac}} = -\frac{N}{\sum_{1 \leq i \leq N} a(v_i|u)} \ , \tag{6}$$

where $a(v_i|u)$ is the slope of the linear regression of $v_i = [\log(\widehat{Q}_{ii}^0), \log(\widehat{Q}_{ii}^1), \log(\widehat{Q}_{ii}^2)]$ by $u = [0, 1, 2]$. The model is initialized with $\tau_x = \tau_{\mathrm{ac}}$ and no connectivity $C = 0$, as well as unit variances without covariances ($\Sigma_{ij} = \delta_{ij}$). At each step, the Jacobian J is straightforwardly calculated from the current

values of τ_x and C. Using the current Σ, the model FC matrices Q^0 and Q^1 are then computed from the consistency equations, using the Bartels-Stewart algorithm to solve the Lyapunov equation. The difference matrices $\Delta Q^0 = \widehat{Q}^0 - Q^0$ and $\Delta Q^1 = \widehat{Q}^1 - Q^1$ determine the model error

$$E = \frac{1}{2}\frac{\sum_{i,j}(\Delta Q^0_{ij})^2}{\sum_{i,j}(\widehat{Q}^0_{ij})^2} + \frac{1}{2}\frac{\sum_{i,j}(\Delta Q^1_{ij})^2}{\sum_{i,j}(\widehat{Q}^1_{ij})^2} \ , \tag{7}$$

where each term - for FC0 and FC1 - is the matrix distance between the model and the data observables, normalized by the latter. The desired Jacobian update is the matrix

$$\Delta J^\dagger = (Q^0)^{-1}[\Delta Q^0 + \Delta Q^1 e^{J^\dagger}] \ , \tag{8}$$

which decreases the model error E at each optimization step, similar to a gradient descent. The best fit corresponds to the minimum of E. Finally, the connectivity update is

$$\Delta C_{ij} = \eta_C \Delta J_{ij} \tag{9}$$

for existing connections only; other weights are forced at 0. We also impose non-negativity for the MOU-EC values during the optimization. To take properly the effect of cross-correlated inputs into account, we adjust the Σ update from the heuristic update in [64]:

$$\Delta \Sigma = -\eta_\Sigma (J\Delta Q^0 + \Delta Q^0 J^\dagger) \ . \tag{10}$$

As with weights for non-existing connections, only diagonal elements of Σ —and possible cross-correlated inputs [61]— are tuned; others are kept equal to 0 at all times. Last, to compensate for the increase of recurrent feedback due to the updated C, we also tune the model time constant τ_x as

$$\Delta \tau_x = \eta_\tau \left(\tau_{\mathrm{ac}} + \frac{1}{\lambda_{\max}}\right) \ , \tag{11}$$

where $\lambda_{\max}$ is the maximum negative real part of the eigenvalues of the Jacobian J. The rationale is to avoid an explosion of the network dynamics (when $\lambda_{\max} \to 0$) while letting the model connectivity C develop a non-trivial structure to reproduce FC.

D.2   Heuristic optimization

Instead of the derivation of the Jacobian in Eq. (8) that takes into account the nonlinearity of the mappings in Eq. (4), one can use a greedy algorithm to optimize the weights to fit the covariance matrix Q^0 to the data

$$\Delta C_{ij} = \Delta Q^0_{ij} \ . \tag{12}$$

E   Communicability and flow for network analysis

Following our previous paper [63], we firstly define "dynamic" *communicability* to characterize the network interactions due to the MOU-EC connectivity C, ignoring the input properties Σ. Our definition is adapted to study complex networks associated with realistic (stable) dynamics where time has a natural and concrete meaning. In comparison, a previous version of communicability for graphs [47] relied on abstract dynamics. The basis of our framework is the network response over time, or Green function, which is the basis of the concept of dynamic communicability, which focuses on the temporal evolution of such interactions. Although we constrain the present study to the MOU process, our framework can be easily adapted to distinct local dynamics for which the Green function is known. In addition to the MOU-EC matrix C, the MOU dynamics is determined by the input properties, so we use the flow in the present study (Figs. 6 and 7).

E.1 Communicability and flow

Formally, communicability is the "deformation" of the Green function e^{Jt} of the MOU process due to the presence of the (weighted and directed) matrix C, as compared to the Green function $e^{J^0 t}$ corresponding to the Jacobian with leakage only and no connectivity, $J^0_{ij} = -\delta_{ij}/\tau$. It is defined as the family of time-dependent matrices depicted in Fig. 6A:

$$\mathcal{C}(t) = ||J^0||\left(e^{Jt} - e^{J^0 t}\right) . \tag{13}$$

The scaling factor $||J^0||^{-1} = ||\int_{t \geq 0} e^{J^0 t} \mathrm{d}t||$ where $|| \cdot ||$ is the L1-norm for matrices (i.e., sum of elements in absolute value) is used for normalization purpose [63]. Recall that $t \geq 0$ here is the time for the propagation of activity in the network, referred to as 'impulse-response time' in the figures. To incorporate the effect of local spontaneous activity or excitability (inputs in the model), we define the flow that fully characterizes the complex network dynamics [63]. The input statistics of interest for a stable MOU process correspond to the input (co)variance matrix Σ, which are independent parameters from the MOU-EC matrix C. This is represented by the purple arrows in the left diagram of Fig. 6A, indicating that the fluctuation amplitude is individual for each ROI. The Σ matrix may be non-diagonal when ROIs experience cross-correlated noise [61], as represented by the purple dashed arrows. The flow describes the propagation of local fluctuating activity over time via the recurrent connectivity and is defined by the

$$\mathcal{F}(t) = \mathcal{C}(t)\sqrt{\Sigma}, \tag{14}$$

where $\sqrt{\Sigma}$ is the real symmetric "square-root" matrix of the input covariance matrix, satisfying $\Sigma = \sqrt{\Sigma}\sqrt{\Sigma}^\dagger$. Communicability is thus a particular case of the flow for homogeneous input statistics. From the time-dependent matrices $\mathcal{F}(t)$, we define the total flow that sums all interactions

$$\mathcal{S}^{\mathcal{F}}(t) = \sum_{\{i,j\}} \mathcal{F}_{ij}(t) . \tag{15}$$

Total communicability for graphs has been used to define a version of centrality [11]. Here the proximity between ROIs correspond to how much flow they exchange. We also define the diversity (or heterogeneity) among the ROI interactions in the time-dependent matrices $\mathcal{F}(t)$, which can be seen as a proxy for their homogenization over time:

$$\mathcal{D}^{\mathcal{F}}(t) = \frac{\sigma_{\{i,j\}}[\mathcal{F}_{ij}(t)]}{\mu_{\{i,j\}}[\mathcal{F}_{ij}(t)]} , \tag{16}$$

defined as a coefficient of variation where $\mu_{\{i,j\}}$ and $\sigma_{\{i,j\}}$ are the mean and standard deviation over the matrix elements indexed by (i,j).

E.2 Community detection

To detect communities from $\mathcal{F}(t)$ in Fig. 7D, we rely on Newman's greedy algorithm for modularity [101] that was originally designed for weight-based communities in a graph. Adapting it here to the flow matrix $\mathcal{F}(t)$ at a given time t, we seek for communities where ROIs have strong bidirectional flow interactions. In the same manner as with weighted modularity, we calculate a null model for MOU-EC:

$$C^{\mathrm{null}} = \frac{\mathbf{c}^{\mathrm{in}}\mathbf{c}^{\mathrm{out}\dagger}}{\mathcal{S}^C} . \tag{17}$$

Note that we preserve the empty diagonal. The resulting matrix contains from the expected weight for each connection, given the observed input strengths $\mathbf{c}^{\text{in}}$ and output strengths $\mathbf{c}^{\text{out}}$; $\mathcal{S}^C$ is the total sum of the weights in C. Then we caclulate $\mathcal{F}^{\text{null}}(t)$ using Eq. (14) with C^{null} instead of C. Starting from a partition where each ROI is a singleton community, the algorithm iteratively aggregates ROIs to form a partition of K communities denoted by S_k that maximizes the following quality function:

$$\Phi = \sum_{1 \leq k \leq K} \sum_{i,j \in S_k} \left(\mathcal{F}(t) - \mathcal{F}^{\text{null}}(t)\right)_{ij} + \left(\mathcal{F}(t) - \mathcal{F}^{\text{null}}(t)\right)_{ji}. \tag{18}$$

At each step of the greedy algorithm, the merging of two of the current communities that maximizes the increase of Φ is performed. Note that communicability-based communities can be defined similarly using $\mathcal{C}(t)$ and the corresponding null model $\mathcal{C}^{\text{null}}(t)$.

References

[1] http://scipy.org/, numpy-scipy python library.

[2] A. Abraham, F. Pedregosa, M. Eickenberg, P. Gervais, A. Mueller, J. Kossaifi, A. Gramfort, B. Thirion, and G. Varoquaux. Machine learning for neuroimaging with scikit-learn. *Front Neuroinform*, 8:14, 2014.

[3] A. M. Aertsen, G. L. Gerstein, M. K. Habib, and G. Palm. Dynamics of neuronal firing correlation: modulation of "effective connectivity". *J Neurophysiol*, 61:900–917, 1989.

[4] S.-i. Amari. Natural gradient works efficiently in learning. *Neural Computation*, 10:251–276, 1998.

[5] A. Avena-Koenigsberger, B. Misic, and O. Sporns. Communication dynamics in complex brain networks. *Nat Rev Neurosci*, 19:17–33, 2017.

[6] L. Barnett, C. L. Buckley, and S. Bullock. Neural complexity and structural connectivity. *Phys Rev E Stat Nonlin Soft Matter Phys*, 79:051914, 2009.

[7] L. Barnett and A. K. Seth. Granger causality for state-space models. *Phys Rev E Stat Nonlin Soft Matter Phys*, 91:040101, 2015.

[8] A. Bartels, N. K. Logothetis, and K. Moutoussis. fmri and its interpretations: an illustration on directional selectivity in area v5/mt. *Trends Neurosci*, 31:444–453, 2008.

[9] R. Becker, M. Reinacher, F. Freyer, A. Villringer, and P. Ritter. How ongoing neuronal oscillations account for evoked fmri variability. *J Neurosci*, 31:11016–11027, 2011.

[10] Y. Benjamini, Yoav; Hochberg. Controlling the false discovery rate: a practical and powerful approach to multiple testing. *Journal of the Royal Statistical Society, Series B*, 57:289–300, 1995.

[11] M. Benzi and C. Klymko. Total communicability as a centrality measure. *Journal of Complex Networks*, 1:124–149, 2013.

[12] M. A. Bertolero, B. T. T. Yeo, and M. D'Esposito. The modular and integrative functional architecture of the human brain. *Proc Natl Acad Sci U S A*, 112:6798–6807, 2015.

[13] V. Betti, S. Della Penna, F. de Pasquale, D. Mantini, L. Marzetti, G. L. Romani, and M. Corbetta. Natural scenes viewing alters the dynamics of functional connectivity in the human brain. *Neuron*, 79:782–797, 2013.

[14] R. G. Bettinardi, G. Deco, V. M. Karlaftis, T. J. Van Hartevelt, H. M. Fernandes, Z. Kourtzi, M. L. Kringelbach, and G. Zamora-López. How structure sculpts function: Unveiling the contribution of anatomical connectivity to the brain's spontaneous correlation structure. *Chaos*, 27:047409, 2017.

[15] B. B. Biswal. Resting state fmri: a personal history. *Neuroimage*, 62:938–944, 2012.

[16] T. A. W. Bolton, A. Tarun, V. Sterpenich, S. Schwartz, and D. Van De Ville. Interactions between large-scale functional brain networks are captured by sparse coupled hmms. *IEEE Trans Med Imaging*, 37:230–240, 2018.

[17] G. M. Boynton, S. A. Engel, G. H. Glover, and D. J. Heeger. Linear systems analysis of functional magnetic resonance imaging in human V1. *J Neurosci*, 16:4207–4221, 1996.

[18] M. Breakspear. Dynamic models of large-scale brain activity. *Nat Neurosci*, 20:340–352, 2017.

[19] K. H. Brodersen, T. M. Schofield, A. P. Leff, C. S. Ong, E. I. Lomakina, J. M. Buhmann, and K. E. Stephan. Generative embedding for model-based classification of fmri data. *PLoS Comput Biol*, 7:e1002079, 2011.

[20] R. L. Buckner. Human functional connectivity: new tools, unresolved questions. *Proc Natl Acad Sci U S A*, 107:10769–10770, 2010.

[21] A. N. Burkitt. A review of the integrate-and-fire neuron model: I. homogeneous synaptic input. *Biol Cybern*, 95:1–19, 2006.

[22] J. Cabral, E. Hugues, O. Sporns, and G. Deco. Role of local network oscillations in resting-state functional connectivity. *Neuroimage*, 57:130–139, 2011.

[23] J. Cabral, D. Vidaurre, P. Marques, R. Magalhães, P. Silva Moreira, J. Miguel Soares, G. Deco, N. Sousa, and M. L. Kringelbach. Cognitive performance in healthy older adults relates to spontaneous switching between states of functional connectivity during rest. *Sci Rep*, 7:5135, 2017.

[24] V. D. Calhoun, S. M. Lawrie, J. Mourao-Miranda, and K. E. Stephan. Prediction of individual differences from neuroimaging data. *Neuroimage*, 145:135–136, 2017.

[25] V. D. Calhoun, J. Liu, and T. Adali. A review of group ica for fmri data and ica for joint inference of imaging, genetic, and erp data. *Neuroimage*, 45:S163–172, 2009.

[26] R. L. Carhart-Harris, S. Muthukumaraswamy, L. Roseman, M. Kaelen, W. Droog, K. Murphy, E. Tagliazucchi, E. E. Schenberg, T. Nest, C. Orban, R. Leech, L. T. Williams, T. M. Williams, M. Bolstridge, B. Sessa, J. McGonigle, M. I. Sereno, D. Nichols, P. J. Hellyer, P. Hobden, J. Evans, K. D. Singh, R. G. Wise, H. V. Curran, A. Feilding, and D. J. Nutt. Neural correlates of the lsd experience revealed by multimodal neuroimaging. *Proc Natl Acad Sci U S A*, 113:4853–4858, 2016.

[27] L. Chang, P. Gianaros, S. Manuck, A. Krishnan, and T. Wager. A sensitive and specific neural signature for picture-induced negative affect. *PLoS Biol*, 13:e1002180, 2015.

[28] P. Ciuciu, P. Abry, and B. J. He. Interplay between functional connectivity and scale-free dynamics in intrinsic fMRI networks. *Neuroimage*, 95:248–263, 2014.

[29] J. R. Cohen. The behavioral and cognitive relevance of time-varying, dynamic changes in functional connectivity. *Neuroimage*, 180:515–525, 2018.

[30] D. Cordes, V. M. Haughton, K. Arfanakis, G. J. Wendt, P. A. Turski, C. H. Moritz, M. A. Quigley, and M. E. Meyerand. Mapping functionally related regions of brain with functional connectivity MR imaging. *Am J Neuroradiol*, 21:1636–1644, 2000.

[31] R. C. Craddock, G. A. James, P. E. Holtzheimer, 3rd, X. P. Hu, and H. S. Mayberg. A whole brain fMRI atlas generated via spatially constrained spectral clustering. *Hum Brain Mapp*, 33:1914–1928, 2012.

[32] J. Daunizeau, K. Stephan, and K. Friston. Stochastic dynamic causal modelling of fMRI data: should we care about neural noise? *Neuroimage*, 62:464–481, 2012.

[33] O. David, I. Guillemain, S. Saillet, S. Reyt, C. Deransart, C. Segebarth, and A. Depaulis. Identifying neural drivers with functional mri: an electrophysiological validation. *PLoS Biol*, 6:2683–2697, 2008.

[34] G. d'Avossa, G. L. Shulman, and M. Corbetta. Identification of cerebral networks by classification of the shape of bold responses. *J Neurophysiol*, 90:360–371, 2003.

[35] F. de Pasquale, S. Della Penna, A. Z. Snyder, L. Marzetti, V. Pizzella, G. L. Romani, and M. Corbetta. A cortical core for dynamic integration of functional networks in the resting human brain. *Neuron*, 74:753–764, 2012.

[36] G. Deco, V. Jirsa, and A. McIntosh. Emerging concepts for the dynamical organization of resting-state activity in the brain. *Nat Rev Neurosci*, 12:43–56, 2011.

[37] G. Deco and M. L. Kringelbach. Hierarchy of information processing in the brain: A novel 'intrinsic ignition' framework. *Neuron*, 94:961–968, 2017.

[38] G. Deco, A. Ponce-Alvarez, D. Mantini, G. Romani, P. Hagmann, and M. Corbetta. Resting-state functional connectivity emerges from structurally and dynamically shaped slow linear fluctuations. *J Neurosci*, 33:11239–11252, 2013.

[39] G. Deco, G. Tononi, M. Boly, and M. L. Kringelbach. Rethinking segregation and integration: contributions of whole-brain modelling. *Nat Rev Neurosci*, 16:430–439, 2015.

[40] S. Dehaene and L. Naccache. Towards a cognitive neuroscience of consciousness: basic evidence and a workspace framework. *Cognition*, 79:1–37, 2001.

[41] R. Dinga, L. Schmaal, B. Penninx, M. J. van Tol, D. Veltman, L. van Velzen, N. van der Wee, and A. Marquand. Evaluating the evidence for biotypes of depression: attempted replication of drysdale et.al. 2017. *bioRxiv*, 2018.

[42] A. T. Drysdale, L. Grosenick, J. Downar, K. Dunlop, F. Mansouri, Y. Meng, R. N. Fetcho, B. Zebley, D. J. Oathes, A. Etkin, A. F. Schatzberg, K. Sudheimer, J. Keller, H. S. Mayberg, F. M. Gunning, G. S. Alexopoulos, M. D. Fox, A. Pascual-Leone, H. U. Voss, B. J. Casey, M. J. Dubin, and C. Liston. Resting-state connectivity biomarkers define neurophysiological subtypes of depression. *Nat Med*, 23:28–38, 2017.

[43] S. B. Eickhoff, B. Thirion, G. Varoquaux, and D. Bzdok. Connectivity-based parcellation: Critique and implications. *Hum Brain Mapp*, 36:4771–4792, 2015.

[44] A. Ekstrom. How and when the fMRI BOLD signal relates to underlying neural activity: the danger in dissociation. *Brain Res Rev*, 62:233–244, 2010.

[45] R. W. Emerson, S. J. Short, W. Lin, J. H. Gilmore, and W. Gao. Network-level connectivity dynamics of movie watching in 6-year-old children. *Front Hum Neurosci*, 9:631, 2015.

[46] E. Estrada. Communicability in temporal networks. *Phys Rev E Stat Nonlin Soft Matter Phys*, 88:042811, 2013.

[47] E. Estrada and N. Hatano. Communicability in complex networks. *Phys Rev E Stat Nonlin Soft Matter Phys*, 77:036111, 2008.

[48] L. Faes, S. Stramaglia, and D. Marinazzo. On the interpretability and computational reliability of frequency-domain granger causality. *F1000Res*, 6:1710, 2017.

[49] D. A. Fair, N. U. F. Dosenbach, J. A. Church, A. L. Cohen, S. Brahmbhatt, F. M. Miezin, D. M. Barch, M. E. Raichle, S. E. Petersen, and B. L. Schlaggar. Development of distinct control networks through segregation and integration. *Proc Natl Acad Sci U S A*, 104:13507–13512, 2007.

[50] E. S. Finn, X. Shen, D. Scheinost, M. D. Rosenberg, J. Huang, M. M. Chun, X. Papademetris, and R. T. Constable. Functional connectome fingerprinting: identifying individuals using patterns of brain connectivity. *Nat Neurosci*, 18:1664–1671, 2015.

[51] P. Fransson, B. C. Schiffler, and W. H. Thompson. Brain network segregation and integration during an epoch-related working memory fmri experiment. *Neuroimage*, 178:147–161, 2018.

[52] S. Frässle, E. I. Lomakina, L. Kasper, Z. M. Manjaly, A. Leff, K. P. Pruessmann, J. M. Buhmann, and K. E. Stephan. A generative model of whole-brain effective connectivity. *Neuroimage*, May 2018.

[53] P. Fries. A mechanism for cognitive dynamics: neuronal communication through neuronal coherence. *Trends Cogn Sci*, 9:474–480, 2005.

[54] K. Friston. Functional and effective connectivity: A review. *Brain Connect*, 1:8, 2011.

[55] K. Friston, A. Mechelli, R. Turner, and C. Price. Nonlinear responses in fMRI: the balloon model, volterra kernels, and other hemodynamics. *Neuroimage*, 12:466–477, 2000.

[56] K. J. Friston, L. Harrison, and W. Penny. Dynamic causal modelling. *Neuroimage*, 19:1273–1302, 2003.

[57] K. J. Friston, J. Kahan, B. Biswal, and A. Razi. A DCM for resting state fMRI. *Neuroimage*, 94:396–407, 2014.

[58] R. F. Galán. On how network architecture determines the dominant patterns of spontaneous neural activity. *PLoS One*, 3:e2148, 2008.

[59] C. R. Gillebert and D. Mantini. Functional connectivity in the normal and injured brain. *Neuroscientist*, 19:509–522, 2013.

[60] M. Gilson. Analysis of fmri data using noise-diffusion network models: a new covariance-coding perspective. *Biological Cybernetics*, Dec 2018.

[61] M. Gilson, G. Deco, K. Friston, P. Hagmann, D. Mantini, V. Betti, G. L. Romani, and M. Corbetta. Effective connectivity inferred from fmri transition dynamics during movie viewing points to a balanced reconfiguration of cortical interactions. *Neuroimage*, 180:534–546, 2018.

[62] M. Gilson, N. E. Kouvaris, G. Deco, J.-F. Mangin, C. Poupon, S. Lefranc, D. Riviere, and G. Zamora-Lopez. Analysis of brain network dynamics estimated from fmri data: A new framework based on communicability and flow. *bioRxiv*, 2018.

[63] M. Gilson, N. E. Kouvaris, G. Deco, and G. Zamora-López. Framework based on communicability and flow to analyze complex network dynamics. *Phys Rev E*, 97:052301, 2018.

[64] M. Gilson, R. Moreno-Bote, A. Ponce-Alvarez, P. Ritter, and G. Deco. Estimation of directed effective connectivity from fMRI functional connectivity hints at asymmetries of cortical connectome. *PLoS Comput Biol*, 12:e1004762, 2016.

[65] M. F. Glasser, T. S. Coalson, E. C. Robinson, C. D. Hacker, J. Harwell, E. Yacoub, K. Ugurbil, J. Andersson, C. F. Beckmann, M. Jenkinson, S. M. Smith, and D. C. Van Essen. A multimodal parcellation of human cerebral cortex. *Nature*, 536:171–178, 2016.

[66] R. Goebel, A. Roebroeck, D. Kim, and E. Formisano. Investigating directed cortical interactions in time-resolved fMRI data using vector autoregressive modeling and Granger causality mapping. *Magn Reson Imaging*, 21:1251–1261, 2003.

[67] J. B. M. Goense and N. K. Logothetis. Neurophysiology of the bold fmri signal in awake monkeys. *Curr Biol*, 18(9):631–40, May 2008.

[68] J. Gonzalez-Castillo and P. A. Bandettini. Task-based dynamic functional connectivity: Recent findings and open questions. *Neuroimage*, 2017.

[69] J. Gonzalez-Castillo, C. W. Hoy, D. A. Handwerker, M. E. Robinson, L. C. Buchanan, Z. S. Saad, and P. A. Bandettini. Tracking ongoing cognition in individuals using brief, whole-brain functional connectivity patterns. *Proc Natl Acad Sci U S A*, 112:8762–8767, 2015.

[70] M. Greicius. Resting-state functional connectivity in neuropsychiatric disorders. *Curr Opin Neurol*, 21:424–430, 2008.

[71] I. Guyon, J. Weston, S. Barnhill, and V. Vapnik. Gene selection for cancer classification using support vector machines. *Machine Learning*, 46(1):389–422, 2002.

[72] M. Habib, E. Mak, S. Gabel, L. Su, G. Williams, A. Waldman, K. Wells, K. Ritchie, C. Ritchie, and J. T. O'Brien. Functional neuroimaging findings in healthy middle-aged adults at risk of alzheimer's disease. *Ageing Research Reviews*, 36:88–104, 2017.

[73] P. Hagmann, L. Cammoun, X. Gigandet, R. Meuli, C. J. Honey, V. J. Wedeen, and O. Sporns. Mapping the structural core of human cerebral cortex. *PLoS Biol*, 6:e159, 2008.

[74] U. Hasson, Y. Nir, I. Levy, G. Fuhrmann, and R. Malach. Intersubject synchronization of cortical activity during natural vision. *Science*, 303:1634–1640, 2004.

[75] B. J. He. Scale-free properties of the functional magnetic resonance imaging signal during rest and task. *J Neurosci*, 31:13786–13795, 2011.

[76] Y. He, M. Wang, X. Chen, R. Pohmann, J. R. Polimeni, K. Scheffler, B. R. Rosen, D. Kleinfeld, and X. Yu. Ultra-slow single-vessel bold and cbv-based fmri spatiotemporal dynamics and their correlation with neuronal intracellular calcium signals. *Neuron*, 97:925–939, 2018.

[77] C. C. Hilgetag and S. Grant. Cytoarchitectural differences are a key determinant of laminar projection origins in the visual cortex. *Neuroimage*, 51:1006–1017, 2010.

[78] J. Hlinka, M. Palus, M. Vejmelka, D. Mantini, and M. Corbetta. Functional connectivity in resting-state fMRI: is linear correlation sufficient? *Neuroimage*, 54:2218–2225, 2011.

[79] C. Hohenfeld, C. J. Werner, and K. Reetz. Resting-state connectivity in neurodegenerative disorders: Is there potential for an imaging biomarker? *Neuroimage Clin*, 18:849–870, 2018.

[80] C. J. Honey, R. Kötter, M. Breakspear, and O. Sporns. Network structure of cerebral cortex shapes functional connectivity on multiple time scales. *Proc Natl Acad Sci U S A*, 104:10240–10245, 2007.

[81] R. I. G. Hughes. Models and representation. *Philosophy of Science*, 64:S325–S336, 1997.

[82] R. M. Hutchison, T. Womelsdorf, E. A. Allen, P. A. Bandettini, V. D. Calhoun, M. Corbetta, S. Della Penna, J. H. Duyn, G. H. Glover, J. Gonzalez-Castillo, D. A. Handwerker, S. Keilholz, V. Kiviniemi, D. A. Leopold, F. de Pasquale, O. Sporns, M. Walter, and C. Chang. Dynamic functional connectivity: promise, issues, and interpretations. *Neuroimage*, 80:360–378, 2013.

[83] G. James, M. Kelley, R. Craddock, P. Holtzheimer, B. Dunlop, C. Nemeroff, H. Mayberg, and X. Hu. Exploratory structural equation modeling of resting-state fMRI: applicability of group models to individual subjects. *Neuroimage*, 45:778–787, 2009.

[84] D. M. Kaplan. Explanation and description in computational neuroscience. *Synthese*, 183:339, 2011.

[85] A. N. Khambhati, A. E. Sizemore, R. F. Betzel, and D. S. Bassett. Modeling and interpreting mesoscale network dynamics. *Neuroimage*, Jun 2017.

[86] S. Kurth, E. Moyse, M. A. Bahri, E. Salmon, and C. Bastin. Recognition of personally familiar faces and functional connectivity in alzheimer's disease. *Cortex*, 67:59–73, 2015.

[87] L.-P. Lafleur, S. Tremblay, K. Whittingstall, and J.-F. Lepage. Assessment of effective connectivity and plasticity with dual-coil transcranial magnetic stimulation. *Brain Stimul*, 9:347–355, 2016.

[88] A. R. Laird, S. B. Eickhoff, C. Rottschy, D. Bzdok, K. L. Ray, and P. T. Fox. Networks of task co-activations. *Neuroimage*, 80:505–514, 2013.

[89] B. Li, X. Wang, S. Yao, D. Hu, and K. Friston. Task-dependent modulation of effective connectivity within the default mode network. *Front Psychol*, 3:206, 2012.

[90] D. Mantini, U. Hasson, V. Betti, M. G. Perrucci, G. L. Romani, M. Corbetta, G. A. Orban, and W. Vanduffel. Interspecies activity correlations reveal functional correspondence between monkey and human brain areas. *Nat Methods*, 9:277–282, 2012.

[91] T. Matsui, T. Murakami, and K. Ohki. Neuronal origin of the temporal dynamics of spontaneous bold activity correlation. *Cereb Cortex*, 2018.

[92] P. M. Matthews and A. Hampshire. Clinical concepts emerging from fmri functional connectomics. *Neuron*, 91:511–528, 2016.

[93] A. McIntosh and F. Gonzalez-Lima. Structural equation modeling and its application to network analysis in functional brain imaging. *Human Brain Mapping*, 2:2–22, 1994.

[94] A. Messé, D. Rudrauf, H. Benali, and G. Marrelec. Relating structure and function in the human brain: relative contributions of anatomy, stationary dynamics, and non-stationarities. *PLoS COmput Biol*, 10:e1003530, 2014.

[95] D. Meunier, K. D. Ersche, K. J. Craig, A. Fornito, E. Merlo-Pich, N. A. Fineberg, S. S. Shabbir, T. W. Robbins, and E. T. Bullmore. Brain functional connectivity in stimulant drug dependence and obsessive-compulsive disorder. *Neuroimage*, 59:1461–1468, 2012.

[96] O. Miranda-Dominguez, B. D. Mills, S. D. Carpenter, K. A. Grant, C. D. Kroenke, J. T. Nigg, and D. A. Fair. Connectotyping: model based fingerprinting of the functional connectome. *PLoS One*, 9:e111048, 2014.

[97] A. Mitra, A. Kraft, P. Wright, B. Acland, A. Z. Snyder, Z. Rosenthal, L. Czerniewski, A. Bauer, L. Snyder, J. Culver, J.-M. Lee, and M. E. Raichle. Spontaneous infra-slow brain activity has unique spatiotemporal dynamics and laminar structure. *Neuron*, 98:297–305, 2018.

[98] A. Mitra, A. Snyder, C. Hacker, and M. Raichle. Lag structure in resting-state fMRI. *J Neurophysiol*, 111:2374–2391, 2014.

[99] A. Mitra, A. Z. Snyder, E. Tagliazucchi, H. Laufs, and M. Raichle. Propagated infra-slow intrinsic brain activity reorganizes across wake and slow wave sleep. *Elife*, 4, 2015.

[100] T. Naselaris, K. N. Kay, S. Nishimoto, and J. L. Gallant. Encoding and decoding in fmri. *Neuroimage*, 56:400–410, 2011.

[101] M. E. J. Newman. Modularity and community structure in networks. *Proc Natl Acad Sci U S A*, 103:8577–8582, 2006.

[102] V. Pallarés, A. Insabato, A. Sanjuán, S. Kühn, D. Mantini, G. Deco, and M. Gilson. Extracting orthogonal subject- and condition-specific signatures from fmri data using whole-brain effective connectivity. *Neuroimage*, 178:238–254, 2018.

[103] H.-J. Park and K. Friston. Structural and functional brain networks: from connections to cognition. *Science*, 342:1238411, 2013.

[104] H.-J. Park, K. J. Friston, C. Pae, B. Park, and A. Razi. Dynamic effective connectivity in resting state fmri. *Neuroimage*, 180:594–608, 2018.

[105] L. Parkes, B. Fulcher, M. Yücel, and A. Fornito. An evaluation of the efficacy, reliability, and sensitivity of motion correction strategies for resting-state functional mri. *NeuroImage*, 171:415 – 436, 2018.

[106] J. D. Power, M. Plitt, S. J. Gotts, P. Kundu, V. Voon, P. A. Bandettini, and A. Martin. Ridding fmri data of motion-related influences: Removal of signals with distinct spatial and physical bases in multiecho data. *Proceedings of the National Academy of Sciences*, 115:E2105–E2114, 2018.

[107] M. G. Preti, T. A. Bolton, and D. Van De Ville. The dynamic functional connectome: State-of-the-art and perspectives. *Neuroimage*, 160:41–54, 2017.

[108] T. Proix, A. Spiegler, M. Schirner, S. Rothmeier, P. Ritter, and V. K. Jirsa. How do parcellation size and short-range connectivity affect dynamics in large-scale brain network models? *Neuroimage*, 142:135–149, 2016.

[109] M. Rahim, B. Thirion, D. Bzdok, I. Buvat, and G. Varoquaux. Joint prediction of multiple scores captures better individual traits from brain images. *Neuroimage*, 158:145–154, 2017.

[110] A. Razi, M. L. Seghier, Y. Zhou, P. McColgan, P. Zeidman, H.-J. Park, O. Sporns, G. Rees, and K. J. Friston. Large-scale dcms for resting-state fmri. *Netw Neurosci*, 1:222–241, 2017.

[111] J. Rissman and A. D. Wagner. Distributed representations in memory: insights from functional brain imaging. *Annu Rev Psychol*, 63:101–128, 2012.

[112] P. Rousseeuw. Silhouettes: A graphical aid to the interpretation and validation of cluster analysis. *Journal of Computational and Applied Mathematics*, 20:53–65, 1987.

[113] J. B. Rowe and H. R. Siebner. The motor system and its disorders. *Neuroimage*, 61(2):464–77, Jun 2012.

[114] P. Sanz-Leon, S. A. Knock, A. Spiegler, and V. K. Jirsa. Mathematical framework for large-scale brain network modeling in the virtual brain. *Neuroimage*, 111:385–430, 2015.

[115] J. Schiefer, A. Niederbühl, V. Pernice, C. Lennartz, J. Hennig, P. LeVan, and S. Rotter. From correlation to causation: Estimating effective connectivity from zero-lag covariances of brain signals. *PLoS Comput Biol*, 14:e1006056, 2018.

[116] J. D. Schmahmann and D. N. Pandya. Cerebral white matter–historical evolution of facts and notions concerning the organization of the fiber pathways of the brain. *J Hist Neurosci*, 16:237–267, 2007.

[117] M. Schmidt, R. Bakker, C. C. Hilgetag, M. Diesmann, and S. J. van Albada. Multi-scale account of the network structure of macaque visual cortex. *Brain Struct Funct*, 223:1409–1435, 2018.

[118] M. Senden, R. Goebel, and G. Deco. Structural connectivity allows for multi-threading during rest: the structure of the cortex leads to efficient alternation between resting state exploratory behavior and default mode processing. *Neuroimage*, 60:2274–2284, 2012.

[119] M. Senden, N. Reuter, M. P. van den Heuvel, R. Goebel, G. Deco, and M. Gilson. Task-related effective connectivity reveals that the cortical rich club gates cortex-wide communication. *Hum Brain Mapp*, 2017.

[120] A. K. Seth, P. Chorley, and L. C. Barnett. Granger causality analysis of fmri bold signals is invariant to hemodynamic convolution but not downsampling. *Neuroimage*, 65:540–555, 2013.

[121] J. S. Siegel, L. E. Ramsey, A. Z. Snyder, N. V. Metcalf, R. V. Chacko, K. Weinberger, A. Baldassarre, C. D. Hacker, G. L. Shulman, and M. Corbetta. Disruptions of network connectivity predict impairment in multiple behavioral domains after stroke. *Proc Natl Acad Sci U S A*, 113:4367–4376, 2016.

[122] A. Z. Snyder and M. E. Raichle. A brief history of the resting state: the washington university perspective. *Neuroimage*, 62:902–910, 2012.

[123] A. A. Sokolov, P. Zeidman, M. Erb, P. Ryvlin, M. A. Pavlova, and K. J. Friston. Linking structural and effective brain connectivity: structurally informed parametric empirical bayes (si-peb). *Brain Struct Funct*, 2018.

[124] O. Sporns, G. Tononi, and G. M. Edelman. Theoretical neuroanatomy: relating anatomical and functional connectivity in graphs and cortical connection matrices. *Cereb Cortex*, 10:127–141, 2000.

[125] O. Sporns, G. Tononi, and R. Kötter. The human connectome: A structural description of the human brain. *PLOS Computational Biology*, 1:0010042, 2005.

[126] K. Stephan, L. Harrison, W. Penny, and K. Friston. Biophysical models of fMRI responses. *Curr Opin Neurol*, 14:629–635, 2004.

[127] W. H. Thompson, P. Brantefors, and P. Fransson. From static to temporal network theory: Applications to functional brain connectivity. *Net Neurosci*, 1(2):69–99, 2017.

[128] G. Tononi, G. M. Edelman, and O. Sporns. Complexity and coherency: integrating information in the brain. *Trends Cogn Sci*, 2:474–484, 1998.

[129] G. Tononi, O. Sporns, and G. M. Edelman. A measure for brain complexity: relating functional segregation and integration in the nervous system. *Proc Natl Acad Sci U S A*, 91:5033–5037, 1994.

[130] P. Valdes-Sosa, A. Roebroeck, J. Daunizeau, and K. Friston. Effective connectivity: Influence, causality and biophysical modeling. *Neuroimage*, 58:339–361, 2011.

[131] M. P. van den Heuvel and H. E. Hulshoff Pol. Exploring the brain network: a review on resting-state fmri functional connectivity. *Eur Neuropsychopharmacol*, 20:519–534, 2010.

[132] G. Varoquaux and R. A. Poldrack. Predictive models avoid excessive reductionism in cognitive neuroimaging. *Curr Opin Neurobiol*, 55:1–6, 2019.

[133] G. Varoquaux, P. R. Raamana, D. A. Engemann, A. Hoyos-Idrobo, Y. Schwartz, and B. Thirion. Assessing and tuning brain decoders: Cross-validation, caveats, and guidelines. *Neuroimage*, 145:166–179, 2017.

[134] G. Varoquaux, Y. Schwartz, R. A. Poldrack, B. Gauthier, D. Bzdok, J.-B. Poline, and B. Thirion. Atlases of cognition with large-scale human brain mapping. *PLoS Comput Biol*, 14:e1006565, 2018.

[135] D. Vatansever, D. K. Menon, A. E. Manktelow, B. J. Sahakian, and E. A. Stamatakis. Default mode dynamics for global functional integration. *J Neurosci*, 35:15254–15262, 2015.

[136] D. Vatansever, D. K. Menon, and E. A. Stamatakis. Default mode contributions to automated information processing. *Proc Natl Acad Sci U S A*, 114:12821–12826, 2017.

[137] D. Vidaurre, R. Abeysuriya, R. Becker, A. J. Quinn, F. Alfaro-Almagro, S. M. Smith, and M. W. Woolrich. Discovering dynamic brain networks from big data in rest and task. *Neuroimage*, 180:646–656, 2018.

[138] A. Walther, H. Nili, N. Ejaz, A. Alink, N. Kriegeskorte, and J. Diedrichsen. Reliability of dissimilarity measures for multi-voxel pattern analysis. *Neuroimage*, 137:188–200, 2016.

[139] H. Wilson and J. Cowan. A mathematical theory of the functional dynamics of nervous tissue. *Kybernetik*, 13:55–80, 1973.

[140] N. Yahata, K. Kasai, and M. Kawato. Computational neuroscience approach to biomarkers and treatments for mental disorders. *Psychiatry Clin Neurosci*, 71:215–237, 2017.

[141] G. Zamora-López, Y. Chen, G. Deco, M. L. Kringelbach, and C. Zhou. Functional complexity emerging from anatomical constraints in the brain: the significance of network modularity and rich-clubs. *Sci Rep*, 6:38424, 12 2016.

[142] G. Zamora-López, C. Zhou, and J. Kurths. Exploring brain function from anatomical connectivity. *Front Neurosci*, 5:83, 2011.