Individual tree-crown detection in RGB imagery using semi-supervised deep learning neural

networks

Ben. G. Weinstein[1], Sergio Marconi[1], Stephanie Bohlman[2], Alina Zare[3], Ethan White[1]

[1] Department of Wildlife Ecology and Conservation, University of Florida, Gainesville, Florida, USA

[2] School of Forest Resources and Conservation, University of Florida, Gainesville, Florida, USA

[3] Department of Electrical and Computer Engineering, University of Florida, Gainesville, Florida, USA

Abstract

Remote sensing can transform the speed, scale, and cost of biodiversity and forestry surveys.

Data acquisition currently outpaces the ability to identify individual organisms in high resolution

imagery. We outline an approach for identifying tree-crowns in RGB imagery using a semi-

supervised deep learning detection network. Individual crown delineation has been a long-

standing challenge in remote sensing and available algorithms produce mixed results. We show

that deep learning models can leverage existing lidar-based unsupervised delineation to

generate trees used for training an initial RGB crown detection model. Despite limitations in the

original unsupervised detection approach, this noisy training data may contain information

from which the neural network can learn initial tree features. We then refine the initial model

using a small number of higher-quality hand-annotated RGB images. We validate our proposed

approach using an open-canopy site in the National Ecological Observation Network. Our

results show that a model using 434,551 self-generated trees with the addition of 2,848 hand-

annotated trees yields accurate predictions in natural landscapes. Using an intersection-over-

union threshold of 0.5, the full model had an average tree crown recall of 0.69, with a precision

of 0.61 for visually-annotated data. The model had an average tree detection rate of 0.82 for

field collected stems. The addition of a small number of hand-annotated trees improved

performance over the initial self-supervised model. This semi-supervised deep learning

approach demonstrates that remote sensing can overcome a lack of labeled training data by

generating noisy data for initial training using unsupervised methods and retraining the

resulting models with high quality labeled data.

Keywords: Deep Learning; Trees; Detection; Remote Sensing; LIDAR; RGB; NEON

1. Introduction

Image-based artificial intelligence can advance our understanding of individual organisms,

species, and ecosystems by greatly increasing the scale and efficiency of data collection [1]. The

growing availability of sub-meter airborne imagery brings opportunities for remote sensing of

biological landscapes that scales from individual organisms to global systems. However, the use

of this imagery remains limited by the laborious, non-reproducible, and costly annotation of

these datasets [2].

Tree detection is a central task in forestry and ecosystem research and both commercial

and scientific applications rely on delineating individual tree crowns from imagery [3,4]. While

there has been considerable research in unsupervised tree detection using airborne LIDAR

(Light Detection and Ranging; a sensor that uses laser pulses to map three dimensional

structure) [3,5,6], less is known about tree detection in RGB (red, green, blue) orthophotos.

Compared to LIDAR, two dimensional RGB orthophotos are less expensive to acquire and easier

to process but lack direct three-dimensional information on crown shape. Effective RGB-based

tree detection would unlock data at much larger scales due to increasing satellite-based RGB

resolution and the growing use of uncrewed aerial vehicles. Initial studies of tree detection in

RGB imagery focused on pixel-based methods and watershed algorithms to find local maxima

among pixels to create potential tree crowns [7]. Combined with hand-crafted rules on tree

geometries, these approaches separately performed tree-detection and crown delineation

[8,9]. The need to hand-craft tree geometry rules makes it a challenge to create a single

approach that encompass a range of tree types [10].

Deep learning is a well-established method for detecting and identifying objects in RGB

images but has only recently been applied to vegetation detection [11,12]. Compared to

previous rule-based approaches, deep learning has three features that make it ideal for tree

detection. First, convolutional neural networks (CNNs) delineate objects of interest directly

from training data rather than using hand-crafted pixel features. This reduces the expertise

required for each use-case and improves transferability among projects [13]. Second, CNNs

learn hierarchical combinations of image features that focus on object-level, rather than pixel-

level, representations of objects. Finally, neural networks are re-trainable to incorporate the

idiosyncrasies of individual datasets. This allows models to be refined with data from new local

areas without discarding information from previous training sets.

The challenge for applying deep learning to natural systems is the need for large training

datasets. A lack of training data is a pervasive problem in remote sensing due to the cost of

data collection and annotation [14]. In addition, the spatial extent of training data often

prohibits field-based verification of annotated objects. For tree detection, the high variation in

tree crown appearance due to taxonomy, health status, and human management increases the

risk of overfitting when using small amounts of training data [11]. One approach to addressing

data limitation in deep learning is "self-supervised learning" (*sensus* [15]), which uses

unsupervised methods to generate training data that is used to train supervised models [16].

This approach has recently been applied to remote sensing for hyperspectral image

classification [10]. Self-supervision, which relies only on unlabeled data, can be combined with

labeled data in a semi-supervised framework (*sensu* [15]), which may improve deep learning on

limited training data by providing neural networks the opportunity to learn generalized features

on a wider array of training examples, followed by retraining on a smaller number of high

quality annotations [17]. Given the imperfect nature of existing unsupervised tree delimitation

approaches, it is unknown whether moderate to low quality annotations can be used to

generate trees for initial model training.

2. Materials and Methods

We propose a semi-supervised pipeline for detecting tree crowns based on RGB data. This

pipeline is outlined in Fig. 1. In the proposed workflow, a LIDAR unsupervised algorithm

generates initial tree predictions. The bounding box for each tree is extracted and the

corresponding RGB crop is used to train an initial deep learning model. Then, using this self-

supervised model as a starting point, we retrain the model using a small number of hand-

annotations to correct errors from the unsupervised detection. The LIDAR data is used only to

initialize the training of the network. It is not used for the final prediction step. The result is a

deep learning neural network that combines unsupervised and supervised approaches to

perform tree delineation in new RGB imagery without the need for co-registered LIDAR data.

This provides the potential for expanding the use of deep learning in remote sensing

applications with limited labeled data by exploring whether generating hundreds of thousands

of noisy labels will yield improved performance even though these labeled data are imperfect

due to the limitations of the generative algorithm [18].

Figure 1. A conceptual figure of the proposed semi-supervised pipeline. A LIDAR-based

unsupervised detection generates initial training data for a self-supervised RGB deep

learning model. The model is then retrained based on a small number of hand-annotated

trees to create the full model.

2.1. Study Site and Field Data

We used data from the National Ecological Observatory Network (NEON) site at the San Joaquin

Experimental Range in California to assess our proposed approach (Figure 2). The site contains

open woodland of live oak (*Quercus agrifolia*), blue oak (*Quercus douglasii*) and foothill pine

(*Pinus sabiniana*) forest. The majority of the site is a single-story canopy with mixed understory

of herbaceous vegetation.

101

Figure 2. Map showing the location of the study site in the western United States.

The aerial remote sensing data products were provided by the NEON Airborne

Observation Platform. We used the NEON 2018 "classified LiDAR point cloud" data product

(NEON ID: DP1.30003.001), and the "orthorectified camera mosaic" (NEON ID: DP1.30010.001).

The LiDAR data consist of 3D spatial point coordinates (4-6 points/m^2) which provides high

resolution information about crown shape and height. The RGB data are a 1km x 1km mosaic of

individual images with a cell size of 0.1 meters. Both data products are georeferenced in the

UTM projection Zone 11. In addition to airborne data, NEON field teams semi-annually catalog

"Woody Plant Vegetation Structure" (NEON ID: DP1.10098.001), which lists the tag and species

identity of trees with diameter at breast height > 10cm in 40m x 40m plots at the site. For each

tagged tree, the trunk location was obtained using the azimuth and distance to the nearest

georeferenced point within the plot. All data are publicly available on the NEON Data Portal

(http://data.neonscience.org/). All code for this project is available on GitHub

(https://github.com/weecology/DeepLidar) and archived on Zenodo [19].

Figure 3. The San Joaquin, CA (SJER) site (C) in National Ecological Observation Network

contains 148 1km^2 tiles (B), each with a spatial resolution of 0.1m. For our analysis, we further

divided each tile in 40x40m windows (A) for individual tree prediction (n=729 per 1km^2 tile).

For hand annotations, we selected two 1km x 1km RGB tiles and used the program

RectLabel (https://rectlabel.com/) to draw bounding boxes around each visible tree. We chose

not to include snags, or low bushes that appeared to be non-woody. In total, we hand-

annotated 2,848 trees for the San Joaquin site. In addition to the two 1km tiles, we hand-

annotated canopy bounding boxes on the cropped RGB images for each NEON field plot (n=34),

which were withheld from training and used as a validation dataset.

2.2. Unsupervised LIDAR Detection

We tested three existing unsupervised algorithms for use in generating trees for the self-

supervised portion of the workflow [20–22]. Existing unsupervised algorithms yield imperfect

crown delineations in part because: 1) the algorithms are not designed to learn the specifics of

different regions and datasets; 2) it is difficult to design hand-crafted features that are flexible

enough to encompass the high variability in tree appearance; 3) distinguishing between trees

and vertical objects such as boulders and artificial structures can be difficult with only three-

dimensional LIDAR data. We evaluated three available unsupervised LIDAR detection algorithms

using the recall and precision statistics for hand-annotated images (see Model evaluation) in

order to choose the best performing algorithm to generate training labels [20–22]. We then

used the best performing method ([22]) to create initial self-supervised tree predictions in the

LIDAR point cloud. This algorithm uses a canopy height model and threshold of tree height to

crown width to cluster the LIDAR cloud into individual trees (Figure 4). We used a canopy height

model of 0.5m resolution to generate local tree tops, and a maximum crown diameter of 60%

of tree height. A bounding box was automatically drawn over the entire set of points assigned

to each tree to create the training data. In total, we generated 434,551 unsupervised tree labels

to use during model training. By pretraining the RGB network on these unsupervised labels, the

model learns a wider variety of tree shapes and appearances than would be possible solely

using hand annotated training data.

Figure 4. Example results from the unsupervised lidar algorithm [22], as implemented in the R

liDR package [23]. Two plots from the San Joaquin NEON site are shown (SJER_009, SJER_010).

2.3. Deep Learning RGB detection

Convolutional neural networks are often used for object detection, due to their ability to

represent semantic information as combinations of image features. Early applications passed a

sliding window over the entire image and treated each window as a separate classification

problem. This was improved by considering potential detection boxes generated by image

segmentation techniques [24] or by combining the bounding box proposal and classification

into a single deep learning framework [25]. We chose the retinanet one-stage detector [26,27],

which allows pixel information to be shared at multiple scales, from individual pixels to groups

of connected objects for learning both bounding boxes and image classes. Retinanet differs

from other object detection frameworks, such as RCNN, by combining object detection and

classification into a single network. This allows for faster training and decreases the sensitivity

to the number of box proposals among images [26]. We used a resnet-50 classification

backbone pretrained on the ImageNet dataset [28]. We experimented with deeper

architectures (resnet-101 and resnet-152) but found no improvement that offset the increased

training time.

Since the entire 1km RGB tile cannot fit into GPU memory, we first cut the tile into

smaller windows for model training. We experimented with a number of different window sizes

and found optimal performance at 400 X 400 pixels due to a balance between memory

constraints and providing the model sufficient spatial context for tree detection. To ensure we

captured all trees that potentially were divided among images during cropping, we allowed

each window to overlap by 5%. This resulted in 729 windows per 1km tile. The order of tiles and

windows were randomized before training to minimize overfitting among epochs. Using the

pool of unsupervised tree predictions, we trained the network with a batch size of 6 on a Tesla

K80 GPU for 8 epochs. For each predicted tree the model returns a bounding box and a

confidence score (0-1). After prediction, we passed each image through a non-max suppression

filter to remove predicted boxes that overlapped by more than 15%, maintaining only the box

with the superior predicted score. Finally, we removed boxes within confidence scores less than

0.2.

2.4. Model Evaluation

We used the NEON woody vegetation data to evaluate tree recall using field-collected points

corresponding to individual tree stems (n=111 trees). A field-collected tree point was

considered correctly predicted if the point fell within a predicted bounding box. This is a more

conservative approach than most other studies, where the field-collected tree point is

considered correctly predicted if an edge of the bounding box falls within a horizontal search

radius (e.g 3m in [29] to 8m in [30]). Due to these variations in accuracy measurement, it is

difficult to establish state-of-art performance, but 70-80% detection rate between predicted

trees and field located trees is typical [5,10]. Given the variation in tree appearance and

segmentation difficulty, there are too few previous attempts at individual tree crown prediction

to provide an expectation for accuracy.

To evaluate the hand-annotated crown areas, we computed recall and precision based

on an intersection-over-union score of greater than 0.5 for each predicted crown. The

intersection-over-union evaluation metric measures the area of overlap divided by the area of

union of the ground truth bounding box and the predicted bounding box. Direct comparisons of

predicted and observed crown overlap are rarely performed due to the difficulty of collecting

data for a sufficient number of validation examples. The most common approach is to compare

the predicted crown area to a matched tree, such as in [31] or use per pixel overlap in visually

annotated data [10,32]. Compared to previous works, our use of a minimum 0.5 intersection-

over-union score is more stringent. We chose this value because it more closely resembles the

required accuracy for forestry and ecological investigations [33]. Finally, to provide a baseline of

comparison, we reran the evaluation data with a model trained solely using the hand-

annotated data. This allows for a direct comparison of the contribution of high-quality

annotations compared to the self-supervised model or the full model combining both self-

supervision and hand-annotation data.

3. Results

Initial exploration of existing lidar-based tree detection tools showed that the best performing

algorithm [22] was able to correctly recall the crown area of 14% of trees at intersection-over-

union score of 0.5 (Table 1). Challenges included over-segmentation of large individual trees,

erroneous predicted tree objects based on imperfections in the ground model, and inclusion of

non-tree vertical objects (Figure 5).

Table 1. Exploratory analysis of lidar-based unsupervised algorithms. Recall and precision

statistics are shown for intersection-over-union with a threshold of 0.5 overlap for the hand

annotated trees on the NEON field plots (n=271 trees).

LIDAR Algorithm	Recall	Precision
Li et. al (2012) [21]	0.107	0.021
Dalponte et al. (2016) [20]	0.138	0.083
Silva et al. (2016) [22]	0.142	0.071

Using the bounding boxes from the Silva et al. (2016) predictions, we extracted RGB crops and

pretrained the RGB neural network. This self-supervised network had a field collected stem

recall of 0.83, and a hand-annotated crown area recall of 0.53 with a precision of 0.32.

Retraining the self-supervised model with hand-annotated trees increased the recall of the

hand annotated tree crowns to 0.69 with a precision of 0.61 (Table 2, Figure 5). The field

collected stem recall did not meaningfully change among models. We anticipate the remaining

stems that were not captured are either not visible in the airborne image or belong to trees

judged to be too small based on the training data.

Figure 5. Predicted individual tree crowns for the unsupervised lidar (A, B), self-supervised RGB

(C, D) and full (semi-supervised) model (E, F) for two NEON tower plots, SJER_015 (A, C, E), and

SJER_053 (B, D, F) at the San Joaquin, CA site. For each tree prediction, the detection

probability is shown in white.

224   Table 2. Evaluation metrics for each of the models. All evaluation was conducted on the 34

225   NEON field plots. Stem recall was calculated using the field-collected tree stem locations (n=111

226   trees). Precision and recall for crown overlap was calculated on hand-annotated bounding

227   boxes around each tree crown (n=271 trees) with a minimum predicted probability threshold of

228   0.5.

Model	Hand-annotated crown overlap (>50%)		Stem Recall
	Recall	Precision	
Silva et al. 2016	0.14	0.07	0.79
Hand-annotation only	0.38	0.60	0.79
Self-supervised RGB	0.53	0.32	0.83
Full Model	0.69	0.61	0.81

By comparing images of the predictions from the unsupervised lidar detection, the self-

supervised RGB deep learning model, and the combined full model, we can learn about the

contributions of each stage of the pipeline. The LIDAR unsupervised detection does a good job

of identifying trees versus background based on height. Most small trees are well segmented,

but there is consistent over-segmentation of the large trees, with multiple crown predictions

abutting together. Visual inspection shows that these predictions represent multiple major

branches of a single large tree, rather than multiple small trees (Figure 5.A). In the self-

supervised RGB model, these large trees are more accurately segmented, but there is a

proliferation of bounding boxes, and overall lower confidence scores for even well-resolved

trees (Figure 5.D). This is shown in the precision-recall curves for the hand-annotated validation

data, which has a higher level of precision for the same level of bounding box recall (Figure 6).

Figure 6. Precision-recall curves for the hand-annotated NEON plots. For each model, we

calculated the proportion of correctly predicted boxes for score thresholds [0,0.1,…,0.7]. An

annotation was considered correctly predicted if the intersection-over-union (IoU) score was

greater than 0.5. The recall and precision scores for the initial lidar-based unsupervised

algorithm is shown in black X.

By combining the self-supervised and the hand annotated datasets, the full model

reduces the extraneous boxes and improves the segmentation of large trees (Figure 7). The full

model has optimal performance in areas of well-spaced large trees (Figure 7.B) but tends to

under-segment small clusters of trees (Figure 7.C).

251

Figure 7. Predictions from the full model on data withheld from model training. Canopy

complexity increases from a) well-defined large trees to B) mixed-species canopies to c) tightly

packed clusters of trees. As canopy complexity increases, the full model tends to under-

segment small tree clusters.

4. Discussion

Using recent developments in deep learning, we built a neural network-based pipeline for

identifying individual trees in RGB imagery. Commercial high resolution RGB data is increasingly

available at near global scales, meaning that accurate RGB based crown delineation methods

could be used to detect overstory trees at unprecedented extents. To address the long-standing

challenge of a lack of labeled training data, we used an unsupervised LIDAR tree detection

algorithm to generate labels for initial training. This self-supervised approach allows the

network to learn the general features of trees even if the LIDAR-based unsupervised detection

is imperfect. The addition of only 2,848 hand-annotated trees generated a final model that

performed well when applied to a large geographic area. This approach opens the door for the

use of deep learning in airborne biodiversity surveys, despite the persistent lack of annotated

data in forestry and ecology datasets.

Many of the false positives in our evaluation dataset were due to disagreements

between the hand annotations, unsupervised LIDAR pretraining and RGB prediction in what

defines a tree. For example, small trees were often considered too low for inclusion in the

LIDAR algorithm (Figure 5.A), whereas they were included in the full model based on the hand-

annotations (Figure 5.B). Similarly, large bushes were sometimes included in hand annotations

due to the difficulty of determining overall woody structure. When deploying these models to

applied problems, it will be important to have strict quantitative guidelines that define tree

definitions. Where LIDAR data is available, draping the 2D boxes over the 3D point cloud to

filter out points based on vertical height should be useful for improving precision. It should be

noted that the quantitative results are likely biased toward the RGB model, since the hand-

annotations were made by looking at the RGB, and not the LIDAR data. However, the good

recall rate for the field-collected stems suggests that hand annotations were useful in capturing

field conditions. An unexpected benefit of the RGB model was the ability to discriminate trees

from other vertical objects, such as houses or poles, despite a lack of distinction in the

unsupervised LIDAR training data (Figure 8). This may be useful in urban tree detection and

other non-forested sites.

Figure 8. Improvement in prediction quality during the training pipeline. A) Bounding boxes

from the lidar-based unsupervised detection erroneously identified artificial structures as trees.

B) Predictions from the self-supervised RGB model showed that the addition of RGB data

diminished the effect of incorrectly labeled training data, with only edges of the artificial

structures maintained as tree predictions. C) In the full semi-supervised model, combining the

self-supervised RGB data with hand-annotations eliminated the influence of the original

misclassification in the training data, while still capturing the majority of trees in the image.

It is likely that accurate tree detection will be region specific, and that the best model will

vary among environments. This will require training a new model for each geographic area

using both RGB and LIDAR training data. The proposed approach could save resources by

allowing a smaller scale LIDAR flight to generate training data, and then cover a much larger

area with less expensive RGB orthophotos. Uncrewed aerial vehicles (UAVs) can be used for

capturing LIDAR at high resolution, but at a limited spatial extent. In combination with our

method, these UAVs may allow cost effective development of custom regional tree detection

models. In addition, the National Ecological Observatory Network, which provided the data for

this analysis, has 45 forested NEON sites selected to cover the major ecoclimatic domains in the

United States. These sites could serve as pools of LIDAR and RGB data at 10,000 ha scales for

regional model training. Combining these two detectors together could produce accurate

individual level tree maps at broad scales, with potential applications to forest inventory,

ecosystem health, post-natural disaster recovery, and carbon dynamics.

While the semi-supervised deep learning method performed well at the open-canopy test

site, geographic areas with complex canopy conditions will be more challenging. As the scale

and tree diversity increase, the model will need additional hand-annotated training data to

capture the variation within the tree class. While there is no hard rule for the minimum hand-

annotations needed, we found that approximately 2000 trees produced reasonable

performance in the oak woodland landscape. Given the complex nature of convolutional neural

networks, it is difficult to diagnose the exact nature of the features used for tree detections.

One potential is that the model detects shadows of vertical objects and uses them to help

locate crown areas. Whether these features generalize to more complex canopy structures and

new ecosystems remains an open question.

The current model only uses LIDAR in the pretraining step. Where available, directly

incorporating a LIDAR canopy height model into the deep learning approach should allow the

model to simultaneously learn the vertical features of individual trees in addition to the two-

dimensional color features in the RGB data. Recent applications of three-dimensional CNNs

[34], as well as point-based semantic segmentation [35], provide new avenues for joint multi-

sensor modeling. These developments will be crucial in segmenting complex canopies that

overlap in the two-dimensional RGB imagery. In addition, recent extensions of region-proposal

networks refine bounding boxes to identify the individual pixels that belong to a class [36]. This

will provide a better estimate of tree crown area, as trees typically have a non-rectangular

shape.

5.   Conclusions

Applying deep learning models to natural landscapes opens new opportunities in ecology,

forestry, and land management. Despite a lack of high-quality training data, deep learning

algorithms can be deployed for tree prediction using unsupervised detection to produce

generated trees for pretraining the neural network. Although the lidar-based algorithm used to

generate the pretraining data achieved less than 20% recall of hand-annotated tree crowns, the

deeply learned RGB features from those data achieved greater than 50% recall. When

combined with a small number of hand-annotated images, recall increased to 69% with 60%

precision. As shown by the comparison with field-collected stems, the majority of the remaining

predictions represent valid trees (>80%), but the overlap with hand-estimated crown area was

less than the desired 50%. Many previous papers have used a lower overlap threshold (e.g.,

20% overlap in [37]), and we expect this value to improve with a combination of better

validation data and more hand-annotated training samples.

In addition to scaling tree detection at much lower costs, there is the potential for this

method to provide additional important information about natural systems. The current model

could be expanded from a single class, "Tree", to one that provides more detailed classifications

based on taxonomy and health status. For example, splitting the "Tree" class into living and

dead trees would provide management insight when surveying for outbreaks of tree pests and

pathogens [38], as well as post-fire timber operations [39]. The growing use of drones in

environmental remote sensing also opens us additional possibilities of combining high density

local information with broad scale information captured from traditional fixed wing and

satellite mounted sensors. Unsupervised tree detection algorithms have been showed to be

more effective at very high point densities (e.g [37]). We anticipate that as the quality of the

unsupervised algorithm data increases, fewer hand annotated samples will be needed to

customize the model to a local geographic area. In addition, the availability of hyperspectral

data could assist in dividing the 'tree' class into multiple species labels. This would yield

additional insights into the economic value, ecological habitat, and carbon storage capacity for

large geographic areas [40]. While further work is needed to understand the best way to

combine data among scales and sensors, we show deep learning-based approaches hold the

potential for large scale actionable information on natural systems to be derived from remote

sensing data.

6. Author Contributions

BGW, EPW, SB and AZ conceived of project design. EW and SM collected the preliminary data.

BGW performed the analysis and wrote the text. All authors contributed to the text.

7. Funding

This research was supported by the Gordon and Betty Moore Foundation's Data-Driven

Discovery Initiative through grant GBMF4563 to E.P. White. The authors declare no conflict of

interest.

8. References

1. Anderson, C.B. Biodiversity monitoring, earth observations and the ecology of scale. *Ecol.*

Lett. **2018**.

2.   Weinstein, B.G. A computer vision for animal ecology. *J. Anim. Ecol.* **2018**, *87*, 533–545.

3.   Wu, B.; Yu, B.; Wu, Q.; Huang, Y.; Chen, Z.; Wu, J. Individual tree crown delineation using

localized contour tree method and airborne LiDAR data in coniferous forests. *Int. J. Appl.*

Earth Obs. Geoinf. **2016**, *52*, 82–94.

4.   Caughlin, T.T.; Graves, S.J.; Asner, G.P.; Van Breugel, M.; Hall, J.S.; Martin, R.E.; Ashton,

M.S.; Bohlman, S.A. A hyperspectral image can predict tropical tree growth rates in

single-species stands. *Ecol. Appl.* **2016**, *26*, 2367–2373.

5.   Ayrey, E.; Fraver, S.; Kershaw, J.A.; Kenefic, L.S.; Hayes, D.; Weiskittel, A.R.; Roth, B.E.

Layer Stacking: A Novel Algorithm for Individual Forest Tree Segmentation from LiDAR

Point Clouds. *Can. J. Remote Sens.* **2017**, *43*, 16–27.

6.   Liu, T.; Im, J.; Quackenbush, L.J. A novel transferable individual tree crown delineation

model based on Fishing Net Dragging and boundary classification. *ISPRS J. Photogramm.*

Remote Sens. **2015**, *110*, 34–47.

7.   Gougeon, F.A.; Leckie, D.G. The Individual Tree Crown Approach Applied to Ikonos

Images of a Coniferous Plantation Area. *Photogramm. Eng. Remote Sens.* 2006, *72*, 1287–

1297.

8.   Liu, T.; Im, J.; Quackenbush, L.J. A novel transferable individual tree crown delineation

model based on Fishing Net Dragging and boundary classification. *ISPRS J. Photogramm.*

Remote Sens. **2015**, *110*, 34–47.

9.   Weinmann, M.; Weinmann, M.; Mallet, C.; Brédif, M. A classification-segmentation

framework for the detection of individual trees in dense MMS point cloud data acquired

in urban areas. *Remote Sens.* **2017**, *9*.

10.   Gomes, M.F.; Maillard, P.; Deng, H. Individual tree crown detection in sub-meter satellite

390   imagery using Marked Point Processes and a geometrical-optical model. *Remote Sens.*

391   *Environ.* **2018**, *211*, 184–195.

392   11.   Li, W.; Fu, H.; Yu, L.; Cracknell, A. Deep Learning Based Oil Palm Tree Detection and

393   Counting for High-Resolution Remote Sensing Images. *Remote Sens.* **2016**, *9*, 22.

394   12.   Guirado, E.; Tabik, S.; Alcaraz-Segura, D.; Cabello, J.; Herrera, F. Deep-learning Versus

395   OBIA for Scattered Shrub Detection with Google Earth Imagery: Ziziphus lotus as Case

396   Study. *Remote Sens.* **2017**, *9*, 1220.

397   13.   Ayrey, E.; Hayes, D. The Use of Three-Dimensional Convolutional Neural Networks to

398   Interpret LiDAR for Forest Inventory. *Remote Sens.* **2018**, *10*, 649.

399   14.   Zhu, X.X.; Tuia, D.; Mou, L.; Xia, G.-S.; Zhang, L.; Xu, F.; Fraundorfer, F. Deep Learning in

400   Remote Sensing: A Comprehensive Review and List of Resources. *IEEE Geosci. Remote*

401   *Sens. Mag.* **2017**, *5*, 8–36.

402   15.   Dahlkamp, H.; Kaehler, A.; Stavens, D.; Thrun, S.; Bradski, G. Self-supervised Monocular

403   Road Detection in Desert Terrain. In Proceedings of the Robotics: Science and Systems II;

404   Robotics: Science and Systems Foundation, 2006.

405   16.   Wu, H.; Prasad, S. Semi-Supervised Deep Learning Using Pseudo Labels for Hyperspectral

406   Image Classification. *IEEE Trans. Image Process.* **2018**, *27*, 1259–1270.

407   17.   Romero, A.; Ballas, N.; Kahou, S.E.; Chassang, A.; Gatta, C.; Bengio, Y. FitNets: Hints for

408   Thin Deep Nets. **2014**, 1–13.

409   18.   Erhan, D.; Manzagol, P.-A.; Bengio, Y.; Bengio, S.; Vincent, P. The Difficulty of Training

410   Deep Architectures and the Effect of Unsupervised Pre-Training. *Twelfth Int. Conf. Artif.*

411   *Intell. Stat. (AISTATS), JMLR Work. Conf. Procedings* **2009**, *5*, 153–160.

412   19.   Weinstein, B.; White, E. weecology/DeepForest: Resubmission II (Version 1.0).

413   20.   Dalponte, M.; Coomes, D.A. Tree-centric mapping of forest carbon density from airborne

414   laser scanning and hyperspectral data. *Methods Ecol. Evol.* **2016**, *7*, 1236–1245.

415   21.   Li, W.; Guo, Q.; Jakubowski, M.K.; Kelly, M. A New Method for Segmenting Individual

416   Trees from the Lidar Point Cloud. *Photogramm. Eng. Remote Sens.* **2012**, *78*, 75–84.

417   22.   Silva, C.A.; Hudak, A.T.; Vierling, L.A.; Loudermilk, E.L.; O'Brien, J.J.; Hiers, J.K.; Jack, S.B.;

418   Gonzalez-Benecke, C.; Lee, H.; Falkowski, M.J.; et al. Imputation of Individual Longleaf

419   Pine (Pinus palustris Mill.) Tree Attributes from Field and LiDAR Data. *Can. J. Remote*

420   *Sens.* **2016**, *42*, 554–573.

421   23.   Roussel, J.-R.; David Auty lidR: Airborne LiDAR Data Manipulation and Visualization for

422   Forestry Applications. **2019**.

423   24.   Uijlings, J.R.R.; Van De Sande, K.E.A.; Gevers, T.; Smeulders, A.W.M. Selective search for

424   object recognition. *Int. J. Comput. Vis.* **2013**, *104*, 154–171.

425   25.   Ren, S.; He, K.; Girshick, R.; Sun, J. Faster r-cnn: Towards real-time object detection with

426   region proposal networks. *Nips* **2015**, 91–99.

427   26.   Lin, T.Y.; Goyal, P.; Girshick, R.; He, K.; Dollar, P. Focal Loss for Dense Object Detection.

428   *Proc. IEEE Int. Conf. Comput. Vis.* **2017**, *2017-Octob*, 2999–3007.

429   27.   Hans Gaiser, Maarten de Vries, Valeriu Lacatusu, Ashley Williamson, Enrico Liscio, D.D.

430   fizy-r/Keras-retinanet 2018.

28.   He, K.; Zhang, X.; Ren, S.; Sun, J. Deep Residual Learning for Image Recognition. *Comput.*

Vis. Pattern Recognit. (CVPR), 2016 **2016**, 770–778.

29.   Vastaranta, M.; Kankare, V.; Holopainen, M.; Yu, X.; Hyyppä, J.; Hyyppä, H. Combination

of individual tree detection and area-based approach in imputation of forest variables

using airborne laser data. *ISPRS J. Photogramm. Remote Sens.* **2012**, *67*, 73–79.

30.   Duncanson, L.I.; Cook, B.D.; Hurtt, G.C.; Dubayah, R.O. An efficient, multi-layered crown

delineation algorithm for mapping individual tree structure across multiple ecosystems.

Remote Sens. Environ. **2014**, *154*, 378–386.

31.   Coomes, D.A.; Dalponte, M.; Jucker, T.; Asner, G.P.; Banin, L.F.; Burslem, D.F.R.P.; Lewis,

S.L.; Nilus, R.; Phillips, O.L.; Phua, M.H.; et al. Area-based vs tree-centric approaches to

mapping forest carbon in Southeast Asian forests from airborne laser scanning data.

Remote Sens. Environ. **2017**, *194*, 77–88.

32.   Yin, D.; Wang, L. Individual mangrove tree measurement using UAV-based LiDAR data:

Possibilities and challenges. *Remote Sens. Environ.* **2019**, *223*, 34–49.

33.   Jeronimo, S.M.A.; Kane, V.R.; Churchill, D.J.; McGaughey, R.J.; Franklin, J.F. Applying

LiDAR Individual Tree Detection to Management of Structurally Diverse Forest

Landscapes. *J. For.* **2018**, *116*, 336–346.

34.   Zhou, Y.; Tuzel, O. VoxelNet: End-to-End Learning for Point Cloud Based 3D Object

Detection. **2017**.

35.   Qi, C.R.; Su, H.; Mo, K.; Guibas, L.J. PointNet: Deep learning on point sets for 3D

classification and segmentation. *Proc. - 30th IEEE Conf. Comput. Vis. Pattern Recognition,*

CVPR 2017 **2017**, *2017-Janua*, 77–85.

36.   He, K.; Gkioxari, G.; Dollar, P.; Girshick, R. Mask R-CNN. *Proc. IEEE Int. Conf. Comput. Vis.*

2017, *2017-Octob*, 2980–2988.

37. Wallace, L.; Lucieer, A.; Watson, C.S. Evaluating tree detection and segmentation

routines on very high resolution UAV LiDAR ata. *IEEE Trans. Geosci. Remote Sens.* **2014**,

52, 7619–7628.

38. Wulder, M.A.; Dymond, C.C.; White, J.C.; Leckie, D.G.; Carroll, A.L. Surveying mountain

pine beetle damage of forests: A review of remote sensing opportunities. *For. Ecol.*

Manage. **2006**, *221*, 27–41.

39. Vogeler, J.C.; Yang, Z.; Cohen, W.B. Mapping post-fire habitat characteristics through the

fusion of remote sensing tools. *Remote Sens. Environ.* **2016**, *173*, 294–303.

40. Deng, S.; Katoh, M.; Yu, X.; Hyyppä, J.; Gao, T. Comparison of tree species classifications

at the individual tree level by combining ALS data and RGB images using different

algorithms. *Remote Sens.* **2016**, *8*.

466