SimRVSequences: an R package to simulate genetic sequence data for pedigrees

Christina Nieuwoudt[1], Angela Brooks-Wilson[2,3], and Jinko Graham[1, *]

[1]Department of Statistics and Actuarial Science, Simon Fraser University, Burnaby

[2]Canada's Michael Smith Genome Sciences Centre, BC Cancer, Vancouver

[3]Department of Biomedical Physiology and Kinesiology, Simon Fraser University, Burnaby

1 Abstract

Summary: Family-based studies have several advantages over case-control studies such as increased power to detect causal rare variants, smaller sample size requirements, and improved detection of sequencing errors. However, collecting suitable families to study and compiling their data is time-consuming and expensive. To aid in evaluation of methodology to identify causal rare vari-

ants in family-based studies, one can use simulated data. For this purpose we present the R package SimRVSequences to simulate genetic sequence data in pedigrees. SimRVSequences allows users to model genetic heterogeneity among families. To simulate sequence data, users supply a sample of pedigrees and single-nucleotide variant data from a sample of unrelated individuals. For ease of use, SimRVSequences offers methods to import and format single-nucleotide variant data and pedigrees from existing software.

Availability and Implementation: SimRVSequences is available as a library for R $\geq$ 3.5.0.

Contact: jgraham@sfu.ca

2 Introduction

Family-based studies are comprised of pedigrees, which may be small or may include many individuals and span several generations. Families may belong to a population cohort, or they may be ascertained on the basis of disease-affected relatives. When the disease of interest is rare, the possibility of observing pedigrees with multiple disease-affected relatives by chance alone is small. However, for diseases with a sporadic component, study samples may include both genetic and sporadic pedigrees, and pedigrees with both genetic and sporadic cases. To evaluate methodology to identify causal rare variants (cRVs) in family-based studies of disease, we have developed the R package SimRVSequences.

Family-based studies can be more attractive than case-control studies because they have more power to detect causal rare variants (Wijsman, 2012). Even so, family-based studies may not identify a strong association between a disease and rare variants within a gene. This may be the result of genetic heterogeneity, which

occurs when different loci predispose to the same disease (Nussbaum et al., 2007). The disease-predisposing variants may be restricted to a single gene or they may be contained in a pathway, or a set of related genes. `SimRVSequences` allows users to model genetic heterogeneity, and has added functionality to simulate genetic heterogeneity in a pathway.

To our knowledge, `SimRVSequences` is the only R package that simulates genetic sequence data conditionally given the cRV status of family members. This feature allows users to specify the genetic landscape of a disease in terms of causal rare variants prior to simulating genetic data in pedigrees.

3 Description

`SimRVSequences` is a publicly-available, platform-independent R package for R $\geq 3.5.0$ (R Core Team, 2013). To simulate sequence data for a family-based study with `SimRVSequences`, users must provide:

- a sample of ascertained pedigrees, and

- single-nucleotide variant (SNV) data from unrelated individuals representing the population of pedigree founders.

We now describe each of the user-supplied items in detail followed by a brief description of the model to simulate genetic data for pedigrees.

3.1 Pedigree Data

`SimRVSequences` can accept pedigree data from any source provided that pedigrees are properly formatted. In particular, users who wish to simulate the segregation of known cRVs must specify the cRV status of each pedigree member. For

ease of use, we note that pedigrees simulated by the R package `SimRVPedigree` are appropriately formatted for `SimRVSequences`. `SimRVPedigree` simulates pedigrees dynamically by way of a competing risk model and makes use of age-specific hazard rates of disease-onset and death provided by the user. At the individual level, disease onset is influenced by the presence (or absence of) a cRV, by way of a proportional hazards model. At the family level, `SimRVPedigree` models complex ascertainment so that simulated pedigrees are representative of sampled pedigrees (Nieuwoudt et al., 2018).

Properly formatted pedigrees are data frames that include the following variables.

1. `FamID`: family identification number

2. `ID`: individual identification number

3. `sex`: sex identification variable: `sex = 0` for males, and `sex = 1` females.

4. `dadID`: identification number of father

5. `momID`: identification number of mother

6. `affected`: disease-affection status: `affected = TRUE` if individual has developed disease, and `FALSE` otherwise.

7. `DA1`: paternally inherited allele at the cRV locus: `DA1 = 1` if the cRV is inherited, and 0 otherwise.

8. `DA2`: maternally inherited allele at the cRV locus: `DA2 = 1` if the cRV is inherited, and 0 otherwise.

Please note, if the variables `DA1` and `DA2` are not provided, the pedigree is assumed to be fully-sporadic, i.e. `DA1 = DA2 = 0` for all members.

3.2 Single-Nucleotide Variant Data

By convention, each individual in a pedigree can be classified as a founder or a non-founder. Founders are individuals whose parents are not included in the pedigree, while non-founders have both a mother and a father represented in the pedigree. Users are required to provide the haplotypes for the founders in the form of SNV data.

SimRVSequences can accept SNV data obtained from various sources (e.g. msprime or 1000 genomes project); however, users must ensure that the SNV data are properly formatted. For ease of use, SimRVSequences includes methods to import and format SNV data simulated by the freely-available software SLiM (Haller and Messer, 2017). We have found SLiM to be the most practical for simulation of genome-wide, exon-only SNV data in a large sample of unrelated individuals.

Users interested in simulating exon-only sequence data with SLiM will enjoy the additional functionality provided by SimRVSequences. With SLiM, users may specify a recombination map to simulate mutations over non-contiguous genomic regions such as the exons (e.g. Harris and Nielsen (2016)). SimRVSequences may be used to create the recombination map to simulate exon-only data in SLiM. To create the recombination map, users provide a map of exons and specify the genome-wide, per-site, per-generation recombination and mutation rates. If desired, a map of exons from the UCSC Genome Browser (Kent et al., 2002) is available for this task. By default, we set the recombination rate to be 1×10^{-8} per-site per-generation (Harris and Nielsen, 2016), and assume that all mutations in exons are neutral and arise at a rate of 1×10^{-8} per-site per-generation (Harris and Nielsen, 2016; 1000 Genomes Project, 2010). Users may alter the default

settings, however, to create a variety of recombination maps for SLiM.

After simulating the SNV data, `SimRVSequences` may be used to import SLiM data into `R`. In addition to importing the SLiM data to `R`, `SimRVSequences` will format the data appropriately, for ease of use. For additional information regarding the required format for SNV data please refer to the supplementary material.

3.3 Pathway Implementation and Selection of Founder Haplotypes

Upon importing and formatting SNV data, the user must specify which mutations will be modelled as *c*RVs. We allow users to model genetic heterogeneity through the specification of a pool of *c*RVs from a pathway. Users may also implement allelic heterogeneity among families by selecting *c*RVs in the same gene. Each pedigree is assumed to segregate at most one *c*RV. Thus, for each pedigree segregating a causal variant, we sample a single *c*RV from the user-specified pool of *c*RVs with replacement. Hence, different families may segregate different *c*RVs.

Upon identifying the familial rare variant, the haplotypes for each pedigree founder are sampled from the user-supplied distribution of haplotypes conditioned on the founder's *c*RV status at the familial disease locus. Thus, we ensure that the *c*RV is introduced by the appropriate founder.

For additional information regarding the specification of *c*RVs please refer to the supplementary material.

3.4 Simulation of Sequence Data for Non-founders

To simulate sequence data for non-founders we perform a conditional gene-drop, which can be described as a two-part process. The first step involves simulating the formation of gametes from parental haplotypes, and the second involves conditional inheritance of a gamete given the offspring's rare variant status at the familial disease locus.

To simulate formation of gametes we use the model proposed by Voorrips and Maliepaard (2012) for recombination with chiasmata interference. Although the proposed model can be applied to tetraploids, in `SimRVSequences` we restrict attention to diploid organisms.

Given a parent-offspring pair, we simulate the formation of four gamete cells from the genetic material of the parent. To determine which gamete is transmitted from parent to offspring, we employ a conditional gene-drop algorithm which depends upon the cRV status of the parent and the offspring. This algorithm is described as follows:

- Case 1: If both the parent and offspring carry the cRV, we sample the offspring's gamete from the parental gametes that carry the cRV with equal probability. For example, in the father to offspring transmission in Figure 1, we choose from the paternal gametes represented by the top two chromatids.

- Case 2: If the parent carries the cRV but the offspring does not, we sample the offspring's gamete from the parental gametes that do not carry the cRV with equal probability. For example, in the father to offspring transmission in Figure 1, we choose from the paternal gametes represented by the bottom two chromatids.

- Case 3: If a parent is not a carrier of the cRV, we sample the offspring's gamete from all possible parental gametes with equal probability. For example, this would be the case in the mother to offspring transmission in Figure 1, since she is not a carrier of the cRV.

Figure 1: A family trio with possible maternal and paternal recombinant chromatids for a diploid organism with a single set of homologous chromosomes. The cRV locus is indicated by a dashed vertical line over the chromatids, and the cRV is indicated by a black vertical bar within the chromatids. The top two chromatids of the father contain the only copies of the cRV.

To simulate genetic data in an entire pedigree, we repeat this process, forwards-in-time, for each parent-offspring pair to ensure the correct genetic variability among relatives.

4 Method Overview

The methods provided by `SimRVSequences` are described as follows.

- Methods to assist with creating the recombination map for SLiM:

- – `combine_exons`: This function will be useful to users who would like to combine overlapping exon observations into a single observation. Upon supplying a data frame which contains overlapping exon segments, this function will return a data frame with combined segments.

- – `create_slimMap`: This function is used both before and after simulating SLiM data. Prior to simulating the SNV data with SLiM, this function can be used to create the recombination map required by SLiM to simulate exon-only SNV data (see section 3.1 of the supplement). Additionally, if this function was used to create the recombination map users may then supply the output of this function to `read_slim` to remap mutations to their correct locations when importing SLiM data to R (see section 3.2 of the supplement).

- Method to assist with importing SLiM data to R.

  - – `read_slim`: This function is used to import to R data stored to a .txt file by SLiM's outputfull() method (see section 3.2 of the supplement).

- Methods to assist with simulation and basic manipulation of SNV data for pedigrees

  - – `sim_RVstudy`: This function is used to simulate the SNV data for a sample of pedigrees (see section 5.1 of the supplement).

  - – `summary.famStudy`: This function is used to obtain a summary of the SNVs shared by the disease-affected relatives in each pedigree (see section 5.3 of the supplement).

5 Example

We demonstrate the procedure to simulate sequence data for a sample of pedigrees given properly formatted inputs. After installing `SimRVSequences` we load the package with the `library` function.

```
library(SimRVSequences)
```

We simulate sequence data using the `sim_RVstudy` function. This function has three required inputs:

- `ped_files` A data frame of pedigree data for all families in the study.

- `haplos` A sparse matrix of haplotypes for a sample of unrelated individuals.

- `SNV_map` A data frame which describes the mutations in `haplos`; that is, each row of `SNV_map` catalogues information about the mutation in the corresponding column of `haplos`.

For additional information regarding the optional inputs for the `sim_RVstudy` function please refer to the supplementary material.

Assume that the pedigree data frame is stored as `study_peds`; the matrix of haplotypes is stored as `hap_mat`; and the mutation data is stored as `mut_dat`. To simulate the sequence data for the pedigrees in `ped_files` we use the `sim_RVstudy` command as follows.

```
study_seq <- sim_RVstudy(ped_files = study_peds,
                         haplos = hap_mat,
                         SNV_map = mut_dat)
```

As displayed in the command above, the output of the sim_RVstudy function has been stored as study_seq. To determine the class of study_seq we use the class function.

```
class(study_seq)
[1] "famStudy" "list"
```

From the output above, we see that sim_RVstudy returns a object of class famStudy that inherits from the list class. Objects of class famStudy are lists that contain the following four items:

- a data frame named ped_files.

- a sparse matrix named ped_haplos,

- a data frame named haplo_map,

- and a data frame named SNV_map.

The item ped_files is a data frame containing the pedigree data for the individuals with simulated sequence data. The sparse matrix ped_haplos contains the simulated haplotypes for each individual in ped_files. The haplo_map data frame is used to map the haplotypes (i.e. rows) in ped_haplos to the individuals in ped_files. Finally, the output SNV_map catalogs the SNVs, i.e. columns, in ped_haplos. For a extensive description of objects of class famStudy please refer to the supplementary material.

6 Discussion

Although gene-dropping can be computationally expensive, SimRVSequences stores and extracts haplotypes efficiently (Cheng et al., 2015; Voorrips and Maliepaard,

2012) for improved performance in `R`. Simulating the transmission of 178,430 rare SNVs across the 22 human autosomes for the disease-affected relatives in one pedigree requires, on average, 0.5 seconds on a Windows OS with an i7-4790 @ 3.60GHz and 12 GB of RAM. Due to data-allocation limitations in `R`, users who wish to simulate more than 250,000 SNVs may need to run chromosome-specific analyses.

We emphasize that while `SimRVSequences` can model genetic heterogeneity among families, we assume that within a family genetic cases are due to a single causal SNV. Hence, `SimRVSequences` is not appropriate for users who wish to simulate the transmission of multiple causal SNVs in the same pedigree. Furthermore, `SimRVSequences` does not allow for simulation of sequence data in sex-chromosomes.

7   Conclusion

Simulated sequence data for family-based studies is essential to evaluate methodology to identify causal rare variants. `SimRVSequences` allows for efficient simulation of SNV data for a sample of pedigrees in `R`. Users may model known genetic heterogeneity and incorporate pedigrees that include individuals with sporadic disease in simulation. With this tool in hand, researchers may evaluate a variety of methods to identify *c*RVs in ascertained pedigrees.

8   Funding

This work was supported in part by the Natural Science and Engineering Research Council of Canada (NSERC), the Canadian Institutes of Health Research; and the

Canadian Statistical Sciences Institute

References

1000 Genomes Project. A map of human genome variation from population-scale sequencing. *Nature*, 467:1061–1073, 2010.

H Cheng, D Garrick, and R Fernando. Xsim: Simulation of descendants from ancestors with sequence data. *G3 (Bethesda)*, 5:1415–1417, 2015.

B C Haller and P W Messer. Slim 2: Flexible, interactive forward genetic simulations. *Mol. Biol. Evol.*, 34:230–240, 2017.

K Harris and R Nielsen. The Genetic Cost of Neanderthal Introgression. *Genetics*, 203:881–891, 2016.

W J Kent, C W Sugnet, T S Furey, K M Roskin, T H Pringle, A M Zahler, and D Haussler. The human genome browser at UCSC. *Genome Res*, 12:996–1006, 2002.

C Nieuwoudt, S J Jones, A Brooks-Wilson, and J Graham. Simulating pedigrees ascertained for multiple disease-affected relatives. *Source Code Biol. Med.*, 13: 2, 2018.

R L Nussbaum, R R McInnes, H F Willard, and A Hamosh. Patterns of single-gene inheritance. In *Thompson & Thompson Genetics in Medicine*, pages 115–149. Saunders/Elsevier, Philadelphia, 7th edition, 2007.

R Core Team. *R: A Language and Environment for Statistical Computing*. R Foundation for Statistical Computing, Vienna, Austria, 2013. URL `http://www.R-project.org/`.

R E Voorrips and C A Maliepaard. The simulation of meiosis in diploid and tetraploid organisms using various genetic models. *BMC Bioinformatics*, 13: 248, 2012.

E M Wijsman. The role of large pedigrees in an era of high-throughput sequencing. *Hum Genet*, 131:1555–1563, 2012.