The development, recognition, and learning mechanisms of animal-like neural network

[1]Feng Qi and [1]Wenchuan Wu

[1]Oxford Centre for Functional MRI of the Brain, Wellcome Centre for Integrative

Neuroimaging, Nuffield Department of Clinical Neurosciences, University of Oxford, UK

How animal neural system addresses the object identity-preserving recognition problem is largely unknown[1]. Artificial neural network such as convolution network[2] (CNN) has reached human level performance in recognition tasks, however, animal neural system does not support such kernel scanning operation across retinal neurons, and thus the neuronal responses do not match that of CNN units. Here, we used an alternative recognition-reconstruction network (RRN) architecture as an analogy to animal-like system, and the resulting neural characteristics agreed fairly well with electrophysiological measurements in monkey studies[3,4]. First, in network development study, the RRN also experienced critical developmental stages characterized by specificities in neuronal types, connectivity strength and firing pattern, from early stage of coarse salience map recognition to mature stage of fine structure recognition. In digit recognition study, we witnessed that the RRN could maintain object invariance representation under various viewing conditions by coordinated adjustment of responses of population neurons. And such concerted population responses contained untangled object identity and properties information that could be accurately extracted via a simple weighted summation decoder. In the learning and forgetting study, novel structure recognition was implemented by adjusting entire synapses in low magnitude while pattern specificities of original synaptic connectivity were preserved, which guaranteed a learning process without disrupting the existing functionalities. This work benefits the understanding of human neural mechanism and the development of humane-like machine intelligence.

30
Fig.1| Development process. **a**, Network parameters evolution over the whole development
process (Extended Data Table 1). The development process contains three stages (the early,
middle and late stage), and 9 critical time points (ctp) according to the key changes in synaptic
weights, neuronal firing patterns, and digit reconstruction performance. **b,** Digit reconstructions
across the development process, where RRN first figured out the digit's salience map with
correct retinal location, size and orientation (early stage), then engraved the basic structure based
on the salience map (middle stage), finally refined the structural details in a longer duration (late
stage). **c,** Evolution of neuronal response maps for 10 different digit instances, ranging from
initial non-specific firing to final object-related firing. Neurons are presented in order, and layers
are indicated by colors. **d,** Evolution of synaptic weights from retina to the first layer (Extended
Data Fig.2 for all neurons). The increase of weight strength of both excitatory (positive) and
inhibitive (negative) synapses facilitated to capture the basic characteristics of digits (ctp0-5),
whereas the subsequent drop of weight strength, while keeping synaptic pattern sharpen, enabled
to recognize structure details (ctp5-8). **e.** Evolution of distribution of excitatory (red) and
inhibitive (blue) synapses (Extended Data Fig.3 for all neurons). At the beginning, it shows
random distributed patterns (ctp0-1), followed by cluster-like patterns (ctp2-4), and finally
stripe-like patterns(ctp5-8). Note, k represents 1,000 steps and m represents 1,000,000 steps.
48
49

Experimental neuroscience[5] discovers that ventral stream in primate brain has been used for core
object recognition with information transmission through a feedforward, reflexive, hierarchical
neural network to rapidly untangle the object identity manifold[6,7]. Inspired from this, we build a
simple recognition and reconstruction network (RRN) (Extended Data Fig.1) to provide an
analogy to animal neural system, and expect similar traits could be derived independently in
response to similar recognition challenges.
56
As primates have distinct development stages (e.g. baby, adolescence and adult etc.)
characterized with significant difference in neural anatomy, physiology and cognition[8], the RRN
also experienced similar development process (i.e. the Early, Middle, and Late stages)
characterized by 9 critical time points (ctp) each with unique firing pattern, synaptic connectivity
pattern, and recognition performance (Fig.1). In the Early stage (ctp0-4), RRN took relatively
few steps, 100k only, to learn to capture the salience map of objects in retina. The RRN started
with random assigned synaptic weights (ctp0) that possessed no power for recognition though
digits were presented in retina. Despite there was only slight synaptic plasticity in initial stage
(ctp1), the RRN started to realize that those digits were likely to appear in the center of retina.
The initial activity changes occurred only in higher layer, indicating the importance of early
development of other cortices (like cortices for audition, proprioception and association etc.) and
their feedback signals in shaping those V1-like synapses[9]. The ctp2 witnessed a sudden drop in
number of excitatory synapses (so was the increase of inhibitive synapses), and ctp2 is also the
starting point of strength growth of both excitatory and inhibitory synapses. These changes
allowed the RRN to identify whether the digits were presented on left or right part of the retina,
which was clearly reflected by the horizontal segmentation of positive and negative synapses
(Fig1.e). Following the same trend of synaptic alterations, the RRN could identify the vertical
position and orientation of objects in ctp3, with specific cluster-like distributions gradually
formed. The units also showed remarkable firing specificity with respect to digit's retinal
position. In ctp4, the RRN could capture the object scale information, and this was also the start
point when RRN came to identify digit's morphology, namely, entering the Middle stage (ctp4-
6). In the Middle stage, the most striking changes occurred in ctp5, where both excitatory and
inhibitory synapses stopped strengthening and began to shrink to enhance the recognition, quite
similar to the prune mechanism in animal brain to improve the neural network efficiency[10]. At
ctp6 the prune effect was quite clearly demonstrated in both activity maps with significantly
sparser firing patterns and synaptic weight maps with fewer but sharper distributions. At the
same time, V1-like units formed specific visual field in retinal region[11]. From ctp6, the RRN
could basically recognize and reconstruct a correct digit, and the further refinement of the
structural details was developed in the Late stage (ctp6-8) on a longer time scale. The excitatory
to inhibitory ratio of synapse number continually declined in a moderate speed till cpt7 where the
network's recognition performance reached a peak level[12,13]. And the subsequent synaptic
plasticity (in ctp8 and further) appeared to stabilize and so were other parameters. The entire
process matches the development[14,15] of animal and human.
90

Fig. 2 | Neuronal responses to digit translation, scaling, and in-plane rotation. **a.** Neuronal
responses to 128 trials of horizontal translation x (top), and significantly correlated x-neurons
(bottom). Note that all layers contained certain x-neurons. **b.** The correlation coefficient (cc)
between neuronal activity and x position for 128 trials (top), where each point represents one
trial, and only 32 neurons in the Encoding layer are presented. The middle and bottom panels
show the averaged cc across 128 trials and 5 significant ($P < 0.01$) x-neurons, respectively. **c.** x
translation, and corresponding responses of x-neurons. Note, activities of neuron 24 (n24, orange
point, the most significantly x-related) were strongly modulated by digits' x positions, identities,
and even morphologies. **d.** Neuronal categorization according to digits' properties. The non-
specific and x, y, s, r specific neurons took proportion of 46.9%, 15.6%, 9.4%, 34.4%, 6.3%
respectively with certain overlaps. **e.** Prediction of position x. The encoding layer contained
untangled x information that were easily extracted by a simple linear decoder implemented by a
downstream layer. Similar studies were performed for vertical translation (y), scaling (s), and
rotation (r) in the Extended Data Fig. 4-7. **f.** Prediction performance (coefficient of determination
R^2 and mean square error) for digit properties. The retinal position (x, y) were predicted with

relatively high accuracy, while scaling and orientation (r, s) were with relatively low accuracy,
primarily due to the innate property variations in the training set. **g.** The influence of n24 on digit
reconstructions regarding to x position. From left column to right, x position increases from -0.2
to +0.2 as illustrated on top row of original digit images. All other rows are images reconstructed
with modified neuronal activities of n24. Red bars highlight the optimal activities derived from
RRN. **h-j** similar plots for y, s, and r. Neurons were selected by lowest p-value during correlation
studies.
115
After 5 million steps training, the RRN was mature in recognition of both digit properties and
structure details. Then, we quantitatively characterized the information represented in the pivot
Encoding layer to investigate how the digit properties were encoded by these 32 neurons. Fig. 2a
shows the correlation analysis between retinal position x and neuronal activity across 128
horizontal translation trials (Method). We witness that all layers contain certain number of x-
related ($P < 0.01$) neurons, which is reasonable and even necessary, because precise digit
reconstruction requires retinal position information being carried throughout the whole network.
Five out of 32 neurons in the Encoding layer are x-neurons in fig. 2b-c, in which activity of
neuron 24 (n24, the most significantly related) demonstrates three characteristics: (1) digit
position modulated activity of n24; (2) the modulation relied on digit identity and morphology;
(3) continuous position alteration resulted in continuous change of neuronal response. The
characteristics of diffeomorphic mapping of RRN can guarantee the tolerance to position
variation. All these are consistent with the characteristics of property preserving representation
of IT neurons[1,16] in monkey studies.
130
Similar correlation studies were performed on properties of y, s and r (Extended Data Fig. 4-7),
and the 32 neurons were functionally categorized into 5 classes (Fig. 2d), which demonstrate the
population coding nature[17] of these neurons. To test whether these population responses
represent the digit properties, a simple linear summation decoder of downstream circuit
(Extended Data Fig. 1) was implemented (method) to predict position x from population
responses of the Encoding neurons. Fig. 2e demonstrates that downstream layer could perceive
the objective (predicted) x value with a simple linear circuit. Fig. 2f shows the predictive
performance in term of R^2 and mean square error (MSE), demonstrating that perceptions of
retinal position x and y were most accurate, while that of digit size was worse, and in-plane
orientation was the worst. Interestingly, although we didn't train the RRN with any digit
properties, it could automatically untangle the manifolds of these properties[6,18].
142
To investigate what individual neuronal response represents, we modulated each neuronal
activity while traced the alteration of image reconstruction. Fig. 2g demonstrates how n24
response influences reconstruction of digit 5 in various x positions, where we have three
observations: (1) for each column, though n24 significantly changed activity, reconstructions of
digit 5 were always placed in correct x positions, which suggests that neighbor neuronal
activities together also contained the position x information, and n24 activity alone could not

move reconstruction position. (2) For each column, different n24 activity did severely change the
reconstructed morphology, however, without communicating with neighbor neurons in the same
layer, n24 could readily obtain accurate activity from feedforward inputs of previous layer,
which suggests the response of n24 (the most significant x-related neuron) was induced by
features in specific retinal regions. (3) across all blocks, there was no sudden change occurring
no matter slight move of digit or change of n24 activity, which suggested the RRN
reconstruction possessed noise tolerance to digit translation and neuronal activity[19]. Quite similar
is the influence of n31 activity on digit's y position, but the reconstruction quality of morphology
was more sensitive to the variation of n31 activity. Fig. 2i-j shows that both digit scaling and
rotating were significantly correlated to n27 activity, which maintained fairly low but extremely
important activity magnitude around 0.1, and disturbing such magnitude would substantially
worsen the reconstruction quality, which suggests both big and small responses are necessary
parts of the population coding[20]. In sum, in the population coding scheme, what exactly a single
neuronal activity represents can hardly be described, because the interpretation may dramatically
alter when neighboring neurons change firing patterns.
164
165
166

168
169

Figure 3: Digit identity recognition. a, Correlation coefficient matrix between neuronal activity
and digit identity, and significantly (P < 0.01) identity related neurons highlighted in white. **b,**
Lesion of n14 (whose activity was highly correlated to occurrence of digit 7) damaged the
reconstruction of various digit 7 in different degree. **c,** Digits judging accuracy without or with
perturbation of x, y, s, r properties. Though training was conducted with no digit labels, a simple
logistic classifier could be used to predict digit identity from population responses of the
Encoding layer. Note, accuracy of natural guess is 10%. **d,** Population similarity matrices[4] for x
translation. The 100 by 100 correlation coefficient matrix was computed between population
responses across 32 Encoding neurons to each of 100 stimuli, which were constituted by ten x-
position blocks, each contained ten digits from 0 to 9 (method). Note that the paradiagonal
stripes indicate property-invariant digit selectivity. **e-f** are similar matrices for properties of y, s,
and r. **h,** Non-overlapping view of digit instances in 2D tSNE space. It clearly demonstrates that
these images were primarily arranged according to retinal positions, while digit identities were
intertwined. **i-j,** Distribution of digit 0 and 1 in 2D tSNE space, respectively. **k-o,** Distribution of
image identities and properties of x, y, s, r in 2D tSNE space. Retinal position x and y clearly
dominated the global distribution of images, while digit identity, scaling and orientation showed
different locally clustering characteristics. **p-r,** The first 3 highest responsive neurons for each
image in 2D tSNE space. n24 and n31 fired strongest for most digit images, which seemed to
encode features in specific retinal regions, while other neurons managed to add or subtract
structural details in these regions. **s,** top5 favorite and average (of top20) images. These neurons
fired in favor of some features in specific regions, not necessarily pointing to specific digit
identity.
192

To tackle whether neuronal activities encode digit identity, correlation coefficients between
neuronal activities and digit identities were computed (fig.3a), where nearly all neurons were
involved in digit identity coding[21,22]. The Extended Data Fig.8 shows that though variations
existed in digit morphologies, these corresponding digit-related neurons had conservative
response pattern regarding to each identity[23,24]. Nevertheless, there was no single identity neuron
found in the Encoding layer. For instance, n14 (the most correlated neuron to digit 7) showed
diverse influence on reconstruction of digit 7 in different conditions (fig.3b). Then, we used a
simple logistic regression layer (Extended Data Fig.1) to assess whether neurons ensemble
contain explicit digit identity information. As compared with the baseline accuracy of 10%, this
simple logistic regression layer could predict digit with accuracy of 60% (fig. 3c), though no
labels were provided during the training process, which indicates that the Encoding neurons are
capable of untangling digit identity which allows downstream layers to easily associate category
or name to such neurons. In addition, we found that if the digits were placed in the retinal center,
certain rotating or scaling would not drastically deteriorate the recognition accuracy, however,
placing digits to peripheral regions especially on top or bottom of retina would significantly
damage the digit recognition[25,26], that's why eye movement is necessary for animal neural
network.
210

211
212
Visual processing needs to handle identity preserving image transformation problem, or to
tolerate property variations during identity recognition. To investigate this, we introduced
similarity matrices[4] between population responses to digits with gradual changing properties
(method). One remarkable feature in Fig. 3d is the presence of paradiagonal stripes, which
indicates same digit with decent horizontal displacement will not severely disturb population
response pattern. The other feature is the high correlation region on top right, which indicates
that digits placed on right part of retina will elicit similar neuronal activities regardless their
identities. Vertical variation of digit position has resembled similarity matrix (fig.2e).
Nevertheless, variation of digit size demonstrates remarkably more and stronger paradiagonal
stripes than others, which suggests that for scaling effect, digits with same morphology were
encoded by similar population response pattern, and only slight modulation on population
activities was needed for recognizing the size alteration[27]. In contrast, relatively large adjustment
of coordinated population response was needed to recognize retinal position changes[28], which is
consistent with Extended Data Fig. 9. So the natural neural mechanism in handling translational
invariance is not based on max pooling[29] but on coordinated adjustment of population responses.
228
t-Distributed Stochastic Neighbor Embedding (tSNE)[30] could provide visible insights into how
these digit instances organized in a 2D state space. Fig. 3h-j illustrate two main findings: (1)
retinal position x and y dominated the global distribution of digit in the tSNE space; (2) digit
identities had a tendency to cluster locally. So alteration of retinal position meant a big move in
tSNE space, which required a large scale adjustment of coordinated responses to achieve it;
while alteration of digit size meant a small nudge (due to unchanged x and y) in the tSNE space,
which required little adjustment in population responses and showed remarkably more and
stronger paradiagonal strips. From fig.3p-r, we witness that activities of n24, n31, n2 and n25
might provide location guidance information for image reconstruction, while other neurons
provided relatively small activity to refine the structure in such regions. However, both big and
small responses were integral parts of population coding. Fig. 3s (Extended Data Fig. 10) shows
that neurons did fire in favor of features[31] in specific retinal region, instead of digit identities.
241
242

243
244

Fig4. Learning and forgetting. **a,** Reconstruction of new structures including solid square, triangle, mirrored digits and double digits. **b,** Synaptic weights distribution and changes after 10,000 steps training of known and novel (symbol x) structures. **c,** Performance evolution during training and forgetting processes. The RRN was trained with novel symbol x for the first 10,000 steps, followed by known digits in the next 10,000 steps. Red represents test performance (or MSE in upside-down y-axis) of novel structure x, while blue represents known digits. Six distinguished ctps (0-5) were observed across the entire process. **d,** enlarged view of the first 500 steps which clearly demonstrates the initial drop and subsequent rise of reconstruction performance. **e-f,** Illustrate the reconstruction of symbol x and digits for 6 ctps, which reflected the performance evolution.

Learning new and forgetting old skills (or knowledge) are basic characteristics of animal brains[32–34]. Here, we will reveal how new recognition skills are added into the working network while previous skills are still preserved without big disruption. It is not surprising, when novel structures are fed into RRN, it treats the input as known digits and reconstructs output accordingly. In fig.4a, the RRN treated the square as compacted digit 8, and double digit as a wide single digit. Fig.4b demonstrates that novel structures (symbol x) induced significantly (2.5

times, P = 2.43e-50) stronger synaptic plasticity than known structures (digits). More
importantly, these changes occurred on all synapses in relatively small magnitude, so that
previous sharp synaptic patterns could be retained[35,36]. This guarantees that those known
structures could still elicit similar neuronal responses, which enable downstream layers to
process data properly and robustly without big modulation. This also guarantees that any novel
structure is learnt and recognized by population coding scheme.
270
The population rewiring process of learning and forgetting involved several key stages (fig. 4c-
f). At ctp-0, the RRN could recognize and reconstruct both novel and known structures with
relatively good quality. Surprisingly, the first 30 steps training of symbol x made sudden drop of
performance for both structures until ctp-1. Novel experience made RRN unstable, but after
transition 0-1 the RRN found a new attractor to settle on in the state space[37], thenceforth a new
round of adjustment started. In transition 1-2, RRN rapidly improved the performance for
symbol x because it was the only input to the network. Unexpectedly, the performance for
known digits also got improved, which might be due to the synaptic adjustment for better reuse
of previous connectivity. After sufficient recovery of RRN capacity, performance for known
structure began to decline again until ctp-3. After that, the RRN began to see only digits again,
the network soon recovered the digit recognition performance to original level, while forgetting
of symbol x took effect rapidly. For transition 4-5 and further, input of digits continued to
enhance the digit recognition while decrease that of symbol x. Note that real neural network is
much larger, the performance alteration (blue curve from ctp-0 to ctp-3) would not change such
dramatically. Here, we want to differentiate between recognition learning and knowledge
learning, where the former (like tasting spicy will gradually lower the perception of spicy taste)
is a long term process requiring plasticity of sensory synapses along processing stream, while the
later (like learning a new foreign word) could be a short process requiring certain new
association connectivity formed between sensory and downstream regions.
290
291   Under the same principle of minimizing free energy of system[30], animal and RRN independently
292   evolved similar neural network, with matched observations in developments, neuronal response,
293   and learning characteristics etc. The work provides insights into studies of both neuroscience and
294   AI.
295
296
297

Reference
1.   Dicarlo, J. J., Zoccolan, D. & Rust, N. C. How Does the Brain Solve Visual Object
Recognition ? *Neuron* **73,** 415–434 (2012).
2.   Lecun, Y., Bengio, Y. & Hinton, G. Deep learning. *Nature* **521,** 436–444 (2015).
3.   Li, N., Cox, D. D., Zoccolan, D. & Dicarlo, J. J. What Response Properties Do Individual
Neurons Need to Underlie Position and Clutter " Invariant " Object Recognition ? *J.*
Neurosci. **102,** 360–376 (2009).
4.   Winrich A. Freiwald, D. Y. T. Functional Compartmentalization and Viewpoint
Generalization Within the Macaque Face-Processing System. *Science (80-.).* **330,** 845–
852 (2010).
5.   Felleman, D. J. & Essen, D. C. Van. Distributed Hierarchical Processing in the Primate
Cerebral Cortex. *Cereb. Cortex* **1,** 1–47 (1991).
6.   Dicarlo, J. J. & Cox, D. D. Untangling invariant object recognition. *Trends Cogn. Sci.* **11,**
333–341 (2007).
7.   Cadieu, C. F. *et al.* Deep Neural Networks Rival the Representation of Primate IT Cortex
for Core Visual Object Recognition. *PLoS Comput. Biol.* **10,** e1003963 (2014).
8.   Ashwell, K. W. S., Waite, P. M. E. & Marotte, L. Ontogeny of the Projection Tracts and
Commissural Fibres in the Forebrain of the Tammar Wallaby (Macropus eugenii):
Timing in Comparison with Other Mam m als. *Brain Behav. Evol.* **64,** 8–22 (1996).
9.   Coogan, T. A. & Essen, D. C. V. A. N. Development of Connections Within and Between
Areas V l and V2 of Macaque Monkeys. *J. Comp. Neurol.* **372,** 327–342 (1996).
10.   Chechik, G. Neuronal Regulation : A Mechanism for Synaptic Pruning During Brain
Maturation. *neural Comput.* **11,** 2061–2080 (1999).
11.   Raichle, M. E. Functional analysis of primary visual cortex (V1) in humans. *Proc. Natl.*
Acad. Sci. USA **95,** 811–817 (1998).
12.   Yamahachi, H., Marik, S. A., Mcmanus, J. N. J., Denk, W. & Gilbert, C. D. Article Rapid
Axonal Sprouting and Pruning Accompany Functional Reorganization in Primary Visual
Cortex. *Neuron* **64,** 719–729 (2009).
13.   Mataga, N., Mizuguchi, Y. & Hensch, T. K. Experience-Dependent Pruning of Dendritic
Spines in Visual Cortex by Tissue Plasminogen Activator. *Neuron* **44,** 1031–1041 (2004).
14.   Paolicelli, R. C. *et al.* Synaptic Pruning by Microglia Is Necessary for Normal Brain
Development. *Science (80-.).* **333,** 1456–1458 (2011).
15.   Magueresse, C. Le & Monyer, H. Review GABAergic Interneurons Shape the Functional
Maturation of the Cortex. *Neuron* **77,** 388–405 (2013).
16.   Dicarlo, J. J. & Maunsell, J. H. R. Anterior Inferotemporal Neurons of Monkeys Engaged
in Object Recognition Can be Highly Sensitive to Object Retinal Position. *J neurophysiol*
89, 3264–3278 (2002).
17.   Meyers, E. M. *et al.* Dynamic Population Coding of Category Information in Inferior
Temporal and Prefrontal Cortex. *J neurophysiol* **100,** 1407–1419 (2019).
18.   Pagan, M., Urban, L. S., Wohl, M. P. & Rust, N. C. Signals in inferotemporal and
perirhinal cortex suggest an untangling of visual target information. *Nat. Neurosci.* **16,**

339    1132–1139 (2013).

340 19. Bienenstock, E. L., Cooper, N. & Munro, W. THEORY FOR THE DEVELOPMENT OF
341    NEURON SELECTIVITY◻: ORIENTATION AND BINOCULAR INTERACTION
342    VISUAL CORTEX1 IN. *J. Neurosci.* **2,** 32–48 (1982).

343 20. Haxby, J. V *et al.* Distributed and Overlapping Representations of Faces and Objects in
344    Ventral Temporal Cortex. *Science (80-.).* **293,** 2425–2431 (2001).

345 21. Averbeck, B. B., Latham, P. E. & Pouget, A. Neural correlations , population coding and
346    computation. *Nat. Rev. Neurosci.* **7,** 358–366 (2006).

347 22. Vinje, W. E. & Gallant, J. L. Sparse Coding and Decorrelation in Primary Visual Cortex
348    During Natural Vision. *Science (80-.).* **287,** 1273–1277 (2000).

349 23. Wallis, G. & Bu, H. H. Effects of temporal association on. *Proc. Natl. Acad. Sci. USA* **98,**
350    4800–4804 (2001).

351 24. Hung, C. P., Kreiman, G., Poggio, T. & Dicarlo, J. J. Fast Readout of Object Identity from
352    Macaque Inferior Temporal Cortex. *Science (80-.).* **2164,** 863–867 (2005).

353 25. Kravitz, D. J., Vinson, L. D. & Baker, C. I. How position dependent is visual object
354    recognition◻? *Trends Cogn. Sci.* **3,** 114–122 (2008).

355 26. Cox, D. D., Meier, P., Oertelt, N. & Dicarlo, J. J. ' Breaking ' position-invariant object
356    recognition. *Nat. Neurosci.* **8,** 1145–1147 (2005).

357 27. Chang, L., Bao, P. & Tsao, D. Y. color patches. *Nat. Commun.* **8,** 2064 (2017).

358 28. Cox, D. D. & Dicarlo, J. J. Does Learned Shape Selectivity in Inferior Temporal Cortex
359    Automatically Generalize Across Retinal Position◻? *J. Neurosci.* **28,** 10045–10055
360    (2008).

361 29. Nagi, J. *et al.* Max-Pooling Convolutional Neural Networks for Vision-based Hand
362    Gesture Recognition. *2011 IEEE Int. Conf. Signal Image Process. Appl.* 342–347 (2011).

363 30. G.E. Hinton, R. R. S. Reducing the Dimensionality of Data with Neural Networks.
364    *Science (80-.).* **313,** 504–508 (2006).

365 31. Treue, S. & Martinez, J. C. T. Feature-based attention influences motion processing gain
366    in macaque visual cortex. *Nautre* **399,** 575–579 (1999).

367 32. Kirkpatrick, J. *et al.* Overcoming catastrophic forgetting in neural networks. *Proc. Natl.*
368    *Acad. Sci. USA* **114,** 3521–3526 (2017).

369 33. Hardt, O., Nader, K. & Nadel, L. Decay happens◻: the role of active forgetting in
370    memory. *Trends Cogn. Sci.* **17,** 109–118 (2013).

371 34. Frankland, P. W., Ko, S. & Josselyn, S. A. Hippocampal neurogenesis and forgetting.
372    *Trends Cogn. Sci.* **9,** 497–503 (2013).

373 35. Martin, S. J., Grimwood, P. D. & Morris, R. G. M. Synaptic plasticity and memory: An
374    evaluation of the hypothesis. *Annu. Rev. Neurosci.* **23,** 649–711 (2000).

375 36. Tigaret, C. M., Olivo, V., Sadowski, J. H. L. P., Ashby, M. C. & Mellor, J. R. Hebbian
376    synaptic plasticity. *Nat. Commun.* **7,** 1–14 (2016).

377 37. Friston, K. The free-energy principle◻: a unified brain theory◻? *Nat. Rev. Neurosci.* **11,**
378    127–138 (2010).

379 38. Rosenblatt, F. & Nonr-, C. THE PERCEPTRON◻: A PROBABILISTIC MODEL FOR

380   INFORMATION STORAGE AND ORGANIZATION. *Psychol. Rev.* **65,** 386–408
381   (1958).
382   39.   Eslami, S. M. A. *et al.* Neural scene representation and rendering. *Science (80-.).* **1210,**
383   1204–1210 (2018).
384   40.   Bello, I., Zoph, B., Vasudevan, V. & Le, Q. V. Neural Optimizer Search with
385   Reinforcement Learning. *Proc. 34th Int. Conf. Mach. Learn.* (2017).
386
387
388

389   Method
390

RRN architecture. The RRN contains ten densely-connected layers[38], that process the data by
means of Outputs = sigmoid (inputs * W +b), where W is synaptic weights matrix, b is bias
vector, and sigmoid is the activation function. The serial processing architecture (Extended Data
Fig. 1) contains two components of Recognition and Reconstruction[39], where the former can
convert 28*28 image into low dimensional features represented by 32 Encoding neuronal
responses, and the later can convert such responses into reconstructed image. After that, the
image reconstruction error is calculated and back propagated, and synaptic weights and biases
are updated by Adam optimizer[40]. For digit identity and properties prediction, we branch the
Encoding layer to a simple logistic and linear layer, respectively. The network was implemented
by Tensorflow r.1.12.0 and sklearn 0.20.2 under python3.6. Note, we don't differentiate between
neuron and unit, between response and activity. Training parameters were selected as, learning
rate = 0.001, Batch size = 128, training steps = 5m, and all other parameters were default values.
403

Image processing. The digit images were from mnist (http://yann.lecun.com/exdb/mnist/),
which had a training set of 60,000 examples and a test set of 10,000 examples. We used imgaug
0.2.7 to further expand the mnist set with variation of translation, scaling and in-plane rotation.
Other object images like square, triangle, mirrored digit, double digits, and symbol x, were
created by custom python codes. All figures were created by matplotlib 3.0.2. Properties were
randomly selected in ranges of retinal position $x \in [-0.2, 0.2]$, position $y \in [-0.2, 0.2]$, scaling s
$\in [0.5, 0.7]$, rotation $r \in [-36°, 36°]$, so as to keep the transformed images in frame.
411

Correlation study of digit properties. Considering retinal position x as an example, we
performed 128 trials of simulation on the mature (5million steps trained) RRN network to
compute the correlation coefficients between neuronal activity and x value for each neuron. Each
trail contained 100 images of same random digit instance but varying position x from -0.2 to
+0.2. So for each trial, with the 1*100 x-vector and 1*100 neuronal activity vector, one pair of cc
and p-value could be obtained for each neuron. And then the averaged cc and p-value could be
computed by averaging across all 128 trials, and the significant x-neurons were selected with
threshold 0.01. The same operations were performed for digit property y, s, and r, whose results
are presented in Extended Data Fig. 4-7. Correlation computation was implemented with
scipy.stats.pearsonr.
422

Digit properties prediction. Considering retinal position x as example, we first took 1024 digits
from mnist test set, and then transformed each digit with random properties while documented
the x value. Next, by feeding digits into the RRN, the activities array of the Encoding neurons
could be obtained. After that, the sklearn.linear_model.LinearRegression was trained with the
documented x values and corresponding activity arrays. In prediction phase, we created another
1024 unseen digits transformed with random properties while position x documented. By feeding
these new digits into RRN, a new set of activity arrays were obtained. Taking these new activity

arrays as input to the sklearn.linear_model.LinearRegression, we obtained the predicted position
x. Finally, r2_score and mean_squared_error functions from sklearn.metrics were used to
compute the prediction performance in term of R square and MSE, respectively. Predictions of
properties y, s and r were processed in similar way.

Correlation study of digit identity. 1024 mnist digits were sequentially processed with random
operation of scaling [0.5,0.7], rotating [-36°, 36°], x translation [-0.2, 0.2], and y translation [-
0.2, 0.2] to produce digit instances with various properties, while identities (mnist labels in one-
hot mode) were documented. By feeding these digit instances into (5million steps trained) RRN
network, population responses were obtained for each instance. Finally, the scipy.stats.pearsonr
was used to compute correlation coefficient and p-value for each pair of digit identity and
neuronal activity (Fig. 3a).

Digit identity prediction under property perturbation. Considering perturbation of x position
as an example, two sets (one for training, one for testing) of 1024 mnist digits were sequentially
processed by shrinking s = 0.6, and then random x ∈ [-0.2, 0.2] to produce digit instances with x
perturbation, while documented digit identities. By feeding the training set of transformed digit
instances into the (5million steps trained) RRN network, population responses were obtained.
Then, we trained the sklearn.linear_model.LogisticRegression model with population responses
(32 neurons in Encoding layer) and corresponding digit labels. For the test set of transformed
digits, RRN output another set of population responses, by feeding which, the trained
LogisticRegression model produced digit labels predictions. By comparing the predicted and
original labels, the statistics under x-perturbation were displayed as boxplot in Fig. 3c. Similar
processes were conducted for other properties.

Similarity matrix. Considering translation x as an example, ten mnist digits (0-9, one for each
identity) were first shrank with s = 0.6, then duplicated 10 times with each copy being
transformed by a x-value from -0.2 to 0.2. Totally 100 images were created and arranged in
order, where 10 blocks represented 10 x values, while each block contained 10 different digit
identities. By feeding these 100 images into the (5million steps trained) RRN network, we
obtained a 100 by 32 response matrix, where each row was a population response vector from 32
neurons with respect to one image. Finally, the correlation coefficient between any two images
were computed by the scipy.stats.pearsonr model. Putting all 100 by 100 correlation coefficients
together, we constructed the similarity matrix of fig. 3d. Similar processes were conducted for
other properties (fig. 3e-g).

tSNE space representation. 1024 mnist digits were transformed with random properties of s, r,
x and y to produce the non-biased dataset. By feeding these digit instances into the (5million
steps trained) RRN network, the population responses were obtained in form of a 1024 by32
matrix (32 neurons in the Encoding layer). sklearn.manifold.TSNE (perplexity = 30,
n_components = 2, init = 'pca', n_iter = 1000) was used to reduce the 32 dimensional

representation into 2D. Taking these two components as x-axis and y-axis, and property as color,
the property distribution in 2D tSNE space was presented (fig. 3k-r).
473
Top-5 and average (top-20) image instances. 1024 mnist digits were transformed with random
properties of s, r, x and y to produce the non-biased dataset. By feeding these digit instances into
the (5million steps trained) RRN network, the population responses were obtained. For each
neuron, rearrange the image instances in a descending order, according to its activity strength.
After that, it output the first five images that elicited the highest neuronal responses (Fig. 3s and
Extended Data Fig. 10). The 'avg' image was averaged across the top-20 images, and the 'sigf'
images contained pixels whose values (over these top-20 images) were significantly (P < 0.01)
different from zero.
482
Learning and forgetting. Based on the (5million steps trained) RRN network, we first trained it
with additional 10,000 steps of novel symbol x images (with above mentioned random affine
transformation to diversify the training set), and then trained it with another 10,000 steps of
known digit images. For symbol x recognition, the former was a learning process, and the latter
was a forgetting process. The reciprocal of mean square error (MSE) between original and
reconstructed images was used as a measure of performance.
489
490
491
492

493
494
495
496
Extended Data Fig. 1 | The RRN architecture. It is a hierarchical modular network containing
recognition and reconstruction components, each comprising several layers of homogeneous
units with layer name and number of units labeled. Images are fed into retina (28*28), followed
by a serial feedforward processing throughout the whole network till layer dd, where
reconstructed image is compared with original image to formed the mean square error (MSE),
then the synaptic weights is updated via error back propagation process. By taking population
responses of the Encoding layer as input, a linear decoder could be used to predict digit
properties such as x, y, r and s, and a logistic regression decoder could be used to predict digit
identity.
506

stage	steps	loss	avg(W)	avg(|W|)	avg(d_W)	#(W+)	avg(W+)	#(W-)	avg(W-)
0	0	0.2234	-1.9E+05	0.0380	0.0000	100427	0.0379	100277	-0.0380
1	10k	0.0195	-5.7E+05	0.0381	4.0E-05	100338	0.0380	100366	-0.0381
2	14k	0.0179	-0.0073	0.0479	-0.0033	93034	0.0437	107670	-0.0514
3	20k	0.0182	-0.0121	0.0792	-0.0012	91865	0.0733	108839	-0.0842
4	100k	0.0154	-0.0371	0.1987	-0.0004	89742	0.1807	110962	-0.2132
5	600k	0.0102	-0.0587	0.3744	-7.7E-05	93293	0.3399	107501	-0.4043
6	1.4m	0.0057	-0.0725	0.2754	3.2E-05	91328	0.2229	109376	-0.3192
7	2.5m	0.0041	-0.0941	0.2695	4.2E-04	88642	0.1984	112062	-0.3256
8	5.0m	0.0027	-0.1118	0.2714	-3.2E-05	87346	0.1834	113358	-0.3393

Extended Data Table 1 | parameters alteration across 9 developmental stages. In each column, the table presents the stage, step, value of loss function, average of connectivity strength, average of absolute connectivity strength, average of connectivity changes, number of positive (excitatory) connectivity, average of positive connectivity strength, number of negative (inhibitive) connectivity, and average of negative connectivity strength. Note, k represents 1,000 and m represents 1,000,000.

514
515
516
517

518
519
Extended Data Fig.2 | synapse weight evolution over 9 critical time points (ctp). Here we
present the synaptic connection pattern from retina to the first layer, because only these synapses
have retinotopic patterns. For each ctp we have 16*16 blocks (each block represents a neuron in
the first layer), and each block contains 28*28 pixel (each pixel represents a neuron in retina).
Each connectivity strength is rendered by pixel color intensity, where red represents excitatory
while blue represents inhibitive.
526
527

528
529
530
531 **Extended Data Fig.3 | evolution of excitatory and inhibitive synapse over 9 ctps.** Similar
532 plots as Extended Data Fig.2. Here, we present a binary connectivity patterns, where we can see
533 it evolved from random distributed pattern, to cluster-like distribution, finally strip-like
534 distribution.
535

536
Extended Data Fig. 4 | study of translation x. a, Correlation studies between neuronal activity and x
value for all neurons (x-axis). (Top panel) correlation coefficients for each trial (y-axis), with cc value
rendered by bwr color map. (Second panel) averaged correlation coefficient for each neuron, with neuron
layers rendered by colors. (Third panel) significant (P < 0.01) correlation for 128 trials highlighted with
white points. (Forth panel) significant neurons across all layers, with y-axis represents p-value in range (0,
0.01). **b,** Correlation studies for 32 neurons in the Encoding layer. (Top panel) correlation coefficient for
128 trials (each point represents cc value of one trial). Note, n8 and n24 had all 128 trial cc values close to
-1. (Second panel) averaged cc value across 128 trials. (Third panel) p-value for 128 trials (each point
represents p-value of one trial). Note, n8 and n24 had all trial p-values close to 0. (Fourth Panel) 5
significant (averaged P < 0.01) x-neurons of n5, n8, n17, n21 and n24. **c,** Neuronal activities vary with
respect to x position of digits. **d,** Comparison between true x position and linearly predicted x position. R
square value is highlighted on top. **e,** Prediction performance (in term of R square values) improved as
more neuronal activity were added into predictor. Note, x-axis presents neurons ordered by its
significance (small p-value on the left). **f,** Similar to **e,** but y-axis presents MSE.

Extended Data Fig. 5 | study of translation y. a, Correlation studies between neuronal activity and y
value for all neurons (x-axis). (Top panel) correlation coefficients for each trial (y-axis), with cc value
rendered by bwr color map. (Second panel) averaged correlation coefficient for each neuron, with neuron
layers rendered by colors. (Third panel) significant (P < 0.01) correlation for 128 trials highlighted with
white points. (Forth panel) significant neurons across all layers, with y-axis represents p-value in range (0,
0.01). **b,** correlation studies for 32 neurons in the Encoding layer. (Top panel) correlation coefficient for
128 trials (each point represents cc value of one trial). Note, n31 had all 128 trial cc values close to -1.
(Second panel) averaged cc value across 128 trials. (Third panel) p-value for 128 trials (each point
represents p-value of one trial). Note, n31 had all trial p-values close to 0. (Fourth Panel) 3 significant
(averaged P < 0.01) y-neurons of n13, n22, and n31. **c,** Neuronal activities vary with respect to y position
of digits. **d,** Comparison between true y position and linearly predicted y position. R square value is
highlighted on top. **e,** Prediction performance (in term of R square values) improved as more neuronal
activity were added into predictor. Note, x-axis presents neurons ordered by its significance (small p-
value on the left). **f,** Similar to **e,** but y-axis presents MSE.

Extended Data Fig. 6 | study of scaling s. a, Correlation studies between neuronal activity and s value for all neurons (x-axis). (Top panel) correlation coefficients for each trial (y-axis), with cc value rendered by bwr color map. (Second panel) averaged correlation coefficient for each neuron, with neuron layers rendered by colors. (Third panel) significant (P < 0.01) correlation for 128 trials highlighted with white points. (Forth panel) significant neurons across all layers, with y-axis represents p-value in range (0, 0.01). **b,** correlation studies for 32 neurons in the Encoding layer. (Top panel) correlation coefficient for 128 trials (each point represents cc value of one trial). Note, n27 had all 128 trial cc values close to +1. (Second panel) averaged cc value across 128 trials. (Third panel) p-value for 128 trials (each point represents p-value of one trial). Note, n27 had all trial p-values close to 0. (Fourth Panel) 11 significant (averaged P < 0.01) s-neurons. **c,** Neuronal activities vary with respect to scaling s of digits. **d,** Comparison between true scaling s and linearly predicted scaling s. R square value is highlighted on top. **e,** Prediction performance (in term of R square values) improved as more neuronal activity were added into predictor. Note, x-axis presents neurons ordered by its significance (small p-value on the left). **f,** Similar to **e,** but y-axis presents MSE.

581
Extended Data Fig. 7 | study of rotation r. a, Correlation studies between neuronal activity and r value
for all neurons (x-axis). (Top panel) correlation coefficients for each trial (y-axis), with cc value rendered
by bwr color map. (Second panel) averaged correlation coefficient for each neuron, with neuron layers
rendered by colors. (Third panel) significant (P < 0.01) correlation for 128 trials highlighted with white
points. (Forth panel) significant neurons across all layers, with y-axis represents p-value in range (0,
0.01). **b,** correlation studies for 32 neurons in the Encoding layer. (Top panel) correlation coefficient for
128 trials (each point represents cc value of one trial). Note, we cannot find neuron with clustered trial cc
values. (Second panel) averaged cc value across 128 trials. (Third panel) p-value for 128 trials (each point
represents p-value of one trial). Note, n24 and n27 had relatively concentrated p-values close to 0 though
several trials exception. (Fourth Panel) 2 significant (averaged P < 0.01) r-neurons of n24 and n27. **c,**
Neuronal activities vary with respect to rotation r of digits. **d,** Comparison between true rotating r values
and linearly predicted r values. R square value is highlighted on top. **e,** Prediction performance (in term of
R square values) improved as more neuronal activity were added into predictor. Note, x-axis presents
neurons ordered by its significance (small p-value on the left). **f,** Similar to **e,** but y-axis presents MSE.

596
597
598 **Extended Data Fig. 8 | Digit instances and the neuronal activities of identity-related**
599 **neurons.** According to fig. 3a, for different digit identities there are different neurons (in the
600 Encoding layer) whose activities were significantly ($P < 0.01$) correlated to the digit identities.
601 We can clearly witness that constant response pattern of these neurons were generally kept for
602 their identities over changes in morphologies or properties.
603
604

605
606
Extended Data Fig. 9 | Changes of neuronal activities according to alteration of properties.
It demonstrates how 32 neurons (in the Encoding layer) adjust their activities in different
viewing conditions of one digit 5 instance (top) and one digit 6 instance (bottom). x-axis
represents the variation of properties of x, y, s and r in 4 columns, y-axis represents the neuronal
activity strength, and color represents different neurons. We witness that population neurons
need a relatively high magnitude of concerted adjustment of ensemble activities to handle
position change, while relatively low adjustment for scaling change. The relationship between
changes of properties and neuronal responses follows diffeomorphic mapping due to the
continuity nature of the RRN network.
616

Extended Data Fig. 10 | Top-20, average and significant images for 6 neurons. For the first 6
strongest firing neurons (fig. 3p-r) including n24, n31, n02, n20, n22 and n23, we display their
top-20 image instances (among 1024 instances) that elicited strongest neuronal activity for each
neuron. The 'avg' image was averaged across the top 20 images, and the 'sigf' image contained
pixels whose values (over these top-20 images) were significantly (P < 0.01) different from zero.
These images show that these neuron fires in favor of specific features in specific retinal regions.
625