Computational analysis of molecular networks using spectral graph theory, complexity measures and information theory

Chien-Hung Huang[1], Jeffrey J. P. Tsai[2], Nilubon Kurubanjerdjit[3]
Ka-Lok Ng[2,4] *

[1]*Department of Computer Science and Information Engineering, National Formosa University, Yun-Lin, Taiwan*

[2]*Department of Bioinformatics and Medical Engineering, Asia University, Taichung, Taiwan*

[3]*SIQ-DIT research group, School of Information Technology, Mae Fah Luang University, Chiang Rai, Thailand*

[4]*Department of Medical Research, China Medical University Hospital, China Medical University, Taichung, Taiwan*

[1]*chhuang@nfu.edu.tw,* [2]*jjptsai@gmail.com,* [3]*sendtoopal@gmail.com*

* *corresponding author*

[2,4]* *ppiddi@gmail.com*

Abstract

Biological processes are based on molecular networks, which exhibit biological functions through interactions among the various genetic elements. This study presents a graph-based method to characterize molecular networks by decomposing them into directed multigraphs: network motifs. Spectral graph theory, reciprocity, and complexity measures were utilized to quantify the network motifs. It was found that graph energy, reciprocity, and cyclomatic complexity can optimally specify network motifs with some degree of degeneracy. A total of 72 molecular networks were analyzed, of three types: cancer networks, signal transduction networks, and cellular processes. It was found that molecular networks are built from a finite number of motif patterns; hence, a graph energy cutoff exists. In addition, it was found that certain motif patterns are absent from the three types of networks; hence, the Shannon entropy of the motif frequency distribution is not maximal. Furthermore, frequently found motifs are irreducible graphs. These are novel findings: they warrant further investigation and may lead to important applications.

The present study provides a systematic approach for dissecting biological networks.

Our discovery supports the view that there are organizational principles underlying

molecular networks.

Keywords: network motifs, cancer networks, signal transduction networks, cellular
processes, graph theory, information theory, graph energy, network complexity,
entropy

Background

Biological networks, network motifs, and graphlets

Molecular networks are the basis of biological processes, in which biological

functions emerge through interactions among the various genetic components. A

network can be modeled by a collection of smaller modules; each module is expected

to perform specific functions, and is separable from the functions of other modules [1-

3]. Such modular networks can be decomposed into smaller units, known as network

motifs. These motifs show interesting dynamical behaviors, in which cooperativity

effects between the motif components play a critical role in human diseases.

We classify network-based analysis into the following major categories: (1) motif

identification and analysis, (2) global architecture study, (3) local topological

properties, and (4) robustness of the network under different types of perturbations.

For the first category, there are a number of publicly available network motif

detection tools namely, MFINDER [4], MAVISTO [5], FANMOD [6], NetMatch [7],

and SNAVI [8].

For the second category, many studies have employed random graph theory to

characterize the global structure of molecular networks: for example, whether a

network is assortative or has the small-world property [9-10]. For instance, it has been

shown that protein-protein interaction networks are scale-free or described by

hierarchical network model [11].

For the third category, topological graph theory has been utilized to characterize

networks by computing topological parameters, such as betweenness centrality,

closeness centrality, clustering coefficients, and eigenvector centrality [12-16].

For the last category, it has been shown that molecular networks are robust under

random perturbation but fragile under attack perturbation [17]. Further work has

demonstrated that molecular networks are also fragile under degree-based,

betweenness-based, and brokering coefficient-based perturbations [18].

Besides network motif description, Przulj [19-20] utilized a graphlet-based approach

to examine the network comparison problem.

. It was demonstrated that directed graphlets are superior for comparing directed

networks [21] and they are effective for studying brain networks [22].

Our study focuses on networks composed of regulatory interactions, such as gene

regulation networks and signal transduction networks but not protein-protein

interaction networks (undirected graphs). We work with network motifs directly;

therefore, our method differs from the graphlet approach.

Although many published works exist on network analysis, many important issues

still remain to be investigated. Most previous studies have utilized graph metrics to

analyze network topology, and so a very relevant question remains unanswered: do

these topological parameters convey enough knowledge about the networks? The

answer seems to be negative. Little is known about the architectures or organizational

principles of molecular networks. For instance, can we have a unique label for

different motifs? Do certain motif patterns occur in a network at a higher frequency?

Seminal works on the use of the concepts of information content, topology, and

entropy in biology were carried out by Dancoff & Quastler [23], Rashvesky [24-25],

and Mowshowitz [26-27]. In particular, Mowshowitz presented an entropy-based

method to measure the complexity of a graph by decomposing it into equivalence

classes.

In this study, it is hypothesized that network motifs are the fundamental building

blocks of a network. In other words, motifs are treated as the core components of a

network. This is similar in spirit to the work of Mowshowitz [27]. Therefore, we

propose that network properties are captured by motifs comprising N nodes, which are

referred to as N-node motifs in the following discussion. To systematically

characterize a large network, one identifies the 3-node motifs, 4-node motifs, up to the

N-node motifs embedded in the network.

For a directed graph, a total of 2, 13, 199, 9364, and 1530843 possible patterns can

be defined for the 2-node, 3-node, 4-node, 5-node, and 6-node motifs, respectively

[28-29]. Since the problem of identifying N-node motifs in a large network is NP-

complete [30], we worked with 3-node motifs and 4-node motifs only. Motifs

composed of five or more nodes are neglected as a first approximation. As we explain

below, this approximation could provide useful insights into dissecting the design

principles underlying molecular networks. Motifs composed of five or more nodes

will be considered in future study.

An earlier work [31] has shown that certain motifs do not appear significantly more

frequently than those appearing in corresponding random graphs; nevertheless, those

motifs still play functional roles. This justifies our approach because the present work

identifies all possible 3-node and 4-node motifs, regardless of their frequency of

occurrence. In other words, we adopt the notion that motifs are the basic building

blocks but do not necessarily occur frequently in a network.

Adami [32] studied undirected colored graphs (in which nodes are labeled with

different colors) and showed that the relative frequency of the colored motifs can be

used to define the information content of the network. In the present work, we

consider motifs that are *directed* graphs and could possibly contain cycles.

Spectral graph theory, reciprocity, complexity measures, and information theory

To characterize network motifs, we utilized the following concepts: spectral graph

theory (SGT), reciprocity, and complexity measures. SGT is a powerful approach that

has been applied in many areas, including computer science and computational

biology [33-34]. The eigenvalues of a matrix defined on a graph play an essential role

in inferring the structural properties of the graph [35]. According to Mowshowitz [36],

the characteristic polynomial of the adjacency matrix of a graph distinguishes

between non-isomorphic graphs. Reciprocity is a parameter that quantifies the degree

of bidirectional connection of a network motif.

Complexity arises from the interactions among the constituent components. Many

complexity measures have been proposed, but there is no standard or formal

definition of complexity metrics that can be applied in all circumstances. Each

complexity measure has strengths and weaknesses [37]. Early work on defining

complexity for directed graphs and infinite graphs can be traced back to Mowshowitz

[38]. The concept of graph complexity indices has been applied to infer the

hierarchical order of chemical structures [39]. Given a network motif pattern, we

make use of two commonly used complexity measures to characterize the motif.

It is possible that some of the network motifs are associated with the same graph

energy (degenerated motifs). Wilson & Zhu [40] have proposed to combine the

spectra of two graph matrices to reduce the cospectrality problem for undirected

graphs and trees. Their results showed that their method can reduce the number of

cospectral pairs of graphs but they are still not completely distinguishable. In addition,

graph descriptors are a useful concept to classify complex networks [41]. In this study,

we used a greedy algorithm to search for an optimal set of parameters that maximize

the removal of degenerate motifs. The parameters we suggested include not only the

motif spectrum but also the graph energy, reciprocity, and complexity measures.

The concept of information entropy has been applied extensively in cancer biology

studies. For instance, it was reported that cancer networks exhibit high information

entropy [42], as well as increased network entropy [43] and signaling entropy [44].

We make use of entropy to measure the frequency distributions of the occurrence of

motifs for the three types of molecular network.

In our previous work [45], we already laid a foundation for the present study. In

another recent work [46], we have extended the previous work [45] by developing a

motif finding algorithm, *PatternFinder,* to identify the 3-node motifs and 4-node

motifs in cancer networks, signal transduction networks, and cellular processes.

152   **Methods**

153   *Workflow of present study*
154   Figure 1 depicts the workflow of the present study.
155
156   KEGG – biological networks
157

Figure 1   The workflow of the present study.

Input data

Network information was obtained from the KEGG database (August 2017) [47].

Four families of networks were employed, including: (i) Environmental Information

Processing, (ii) Cellular Processes, (iii) Organismal Systems, and (iv) Human Cancers.

Not every network recorded by KEGG was imported. After inspection, we

disregarded networks composed of several separate components, such as the "Two-

component system," "MicroRNAs in cancer," "Chemical carcinogenesis," and "Viral

carcinogenesis". In addition, we combined the networks labeled with the name

"signaling pathway," and called them "signal transduction networks (STNs)". We

note that STNs range across different families in the KEGG classification, including

"Signal transduction," "Immune system," and "Endocrine system".

In total, we collected 17 cancer networks, 46 STNs, and 9 cellular processes. We

downloaded KEGG pathway KGML files and made use of the KEGGScape [48] and

KEGGparser [49] packages to visualize and save the node and edge information for

each network.

In Supplementary File 1, Supplementary Table S1 summarizes the nodes, edges,

and motif-associated node information for the 17 cancer networks. The complete list

of node and edge information of the 46 STNs and 9 cellular processes can be found in

Supplementary Table S2 and Supplementary Table S3, respectively, in the same file.

Adjacency matrix

By analyzing the connectivity of each gene, one constructs an adjacency matrix, *A*,

to represent the interaction network. In total, there are 13 3-node motifs and 199 4-

node motifs [3,50].

It is possible that some motifs are subgraphs of other motifs (structural motifs). In a

previous work [51], such subgraphs are called functional motifs. In a brain network, a

structural motif and functional motif represent an anatomical building block and the

elementary processing mode of a network, respectively.

We have developed an algorithm named *PatternFinder* to enumerate all possible

functional motifs embedded in the 3-node motifs and 4-node motifs. Details of

PatternFinder are given in Supplementary File 1 – Supplementary Table S4.

Characterization of network motifs:graph energy, reciprocity and graph

complexity

The energy of a graph is an invariant [52-54], and is equal to the sum of the absolute

values of the eigenvalues of the adjacency matrix A. Originally, the concept of graph

energy introduced by Gutman was applied to study undirected graphs and has been

applied to estimate the π–electron energy of hydrocarbons.

The adjacency matrix A can be expressed in terms of its eigenvectors and

eigenvalues. Since A is a nonsymmetric matrix in general, its eigenvalues may be

complex and all of its eigenvectors are nonorthogonal. Let n, e, and d_i denote the

number of nodes, number of edges, and degree of the ith node of graph G,

respectively; G is called an (n, e)-graph. The energy of a graph G, $E(G)$, is defined by

222
$$E(G) = \sum_{i=1}^{n} |\alpha_i| \qquad\qquad (1)$$

where α_i denotes the ith eigenvalue of A. The sum of all of the eigenvalues is always

equal to zero.

Assume that the graph energy eigenvalues are labeled in descending order: that is,

$\alpha_1 \geq \alpha_2 \geq \ldots \geq \alpha_n$, while the whole spectrum is denoted by $Sp(G) = [\alpha_1, \alpha_2, \ldots \alpha_n]$.

The largest eigenvalue is referred to as the spectral radius of graph G [55].

In spectral graph theory, there are two other matrices—Laplacian [56] and signless

Laplacian [57-58]—that can be defined to characterize graphs. The Laplacian matrix

L and signless Laplacian matrix Q of a graph G are defined as $L = D - A$ and $Q = D +$

A respectively, where *D* is a diagonal matrix in which the diagonal elements are the

node degrees. The Laplacian energy of a graph *G*, *LE(G)*, is defined by

233
$$LE(G) = \sum_{i=1}^{n} |\beta_i| - \frac{2e}{n} \tag{2}$$

234   where $|\beta_i|$ denotes the absolute value of the *i*th eigenvalue of *L*. There is an

235   analogy between the properties of *E(G)* and *LE(G)*, but some significant differences

236   remain between these two quantities [59].

237   The signless Laplacian energy of graph *G*, *QE(G)*, is defined by

238
$$QE(G) = \sum_{i=1}^{n} |\gamma_i| - \frac{2e}{n} \tag{3}$$

where $|\gamma_i|$ denotes the absolute value of the *i*th eigenvalue of *Q*.

A more general definition of graph energy was suggested by Nikiforov [60-61]. Let

M be an $n \times n$ real matrix and the singular values be denoted by s_1, s_2, … s_n. The

singular values of *M* are equal to the positive square roots of the eigenvalues of *MMᵗ*,

where *t* denotes matrix transpose. Let *M* equal *A*, *L*, or *Q* and consider the

eigenvalues of *AAᵗ*, *LLᵗ*, and *QQᵗ*. The total energy, *ME*, obtained from *M*, is defined

by

246
$$ME(G) = \sum_{i=1}^{n} |s_i| \tag{4}$$

ME(G) is called generalized energy. We extend the definition to consider matrix

products of the form MN^t, and therefore define three additional energies: *ALᵗ*, *AQᵗ*,

and *LQ*ᵗ. We call these *asymmetric* generalized energies. The sums of the absolute

values of the eigenvalues of MM^t and M^tM are the same. This also holds for MN^t and

NM^t. Therefore, one needs to compute MM^t and NM^t only. The advantages of using

asymmetric generalized energies will be demonstrated later in this article. To the best

of our knowledge, no (or few) previous studies have made use of *asymmetric*

generalized energies to characterize network motifs. In total, we have devised nine

graph energies to describe the motifs. We also note that Adiga et al. [62] proposed a

parameter named skew energy, obtained from the skew-adjacency matrix, to

characterize directed graphs; however, this parameter does not apply to graphs

consisting of multiple arcs (multigraphs).

Several studies [63-64] have suggested that reciprocal links in directed networks

play an important role in dynamical processes and network growth. The traditional

definition of reciprocity is $R = L^{\leftrightarrow}/L$, where $L^{\leftrightarrow}$ and L denote the number of

"edges pointing in both directions" and the total number of edges respectively. This

definition of reciprocity was modified by Garlaschelli and Loffredo [63], who defined

reciprocity *r* as the correlation coefficient between the entries of the adjacency matrix,

A, given by

266
$$r = \frac{\sum_{i \neq j}(a_{ij} - \overline{a})(a_{ji} - \overline{a})}{\sum_{i \neq j}(a_{ij} - \overline{a})^2} \qquad (5)$$

267   where a_{ij} equals one if there is an edge from node *i* to node *j*; the average, $\overline{a}$, is

268   defined by

269
$$\overline{a} = \frac{\sum_{i \neq j} a_{ij}}{N(N-1)} \qquad (6)$$

A positive value of r indicates that the motif has bidirectional connections, whereas a

negative r implies that the motif has either an in-connection or out-connection.

To further understand the connectivity structure of network motifs, we seek metrics

that can be used to measure graph complexity. In software engineering, the

cyclomatic complexity (CC) is a metric developed by McCabe [65] to measure the

complexity of a program by using its control flow graph. CC is defined by the

expression $CC = e - N + 2P$, where e and N denote the number of edges and number

of nodes of the graph, and P denotes the number of predicate/exit nodes [37,65]. Node

and edge denote a program unit and the execution order of the program. CC depends

only on the global decision structure (the number of edges and nodes) of a program.

In addition to CC, we utilize the algorithmic complexity measure, the Kolmogorov

complexity (KC), to characterize graph complexity. Essentially, the KC of a bit string

is given by the smallest computer program that can generate the string. Given the

adjacency matrix (or the equivalent bit string), we use the block decomposition

method (BDM) [66] to determine the KC for both 3-node [67] and 4-node motifs. A

bit string with a high KC has a higher degree of randomness, contains more

information, and is less compressible. A complete graph has a smaller KC value,

whereas a random graph has higher KC and is less compressible.

Unique identifiers for network motifs

Every 3-node motif and 4-node motif has a different KC value, so the KC can be

used as a unique identifier. However, given the graph energy, asymmetric graph

energies, graph energy spectrum, reciprocity, and *CC*, we seek to determine a minimal

set of parameters that can serve as a label of the network motifs. This set of

parameters describes certain aspects of the motifs differently than the algorithmic

complexity measure. To the best of our knowledge, the concept of using energy,

reciprocity, and *CC* in labeling network motifs is novel. The pseudocode for

determining the minimal set of parameters is based on a greedy strategy and is

described in Supplementary File 1 – Supplementary Table S5.

Frequently found motifs, network entropy, and network similarity

Given a molecular network, *PatternFinder* identifies both the sets of 3-node motifs

and 4-node motifs. Two motifs with the same ID may partially embed the same

genetic element(s); these two motifs are counted twice in our calculations. We expect

that certain motif patterns that occur with higher probabilities are the dominant

underlying network structure. Let $p_3^{(k)}$ denote the frequency (probability) distribution

of a 3-node network motif, where *k* denotes one of the 13 patterns. The Shannon

entropy for 3-node motifs and 4-node motifs, H_3 and H_4, of a molecular network are

computed. The normalized Shannon entropies for the 3-node motifs and 4-node

motifs are given by $H_{3R} = H_3 / \log_2(13)$ and $H_{4R} = H_4 / \log_2(199)$, respectively.

Results

Given the 3-node motifs and 4-node motifs, we used *PatternFinder* to identify their

subgraphs (all possible functional motifs). For the 3-node motifs, it was found that

motif "id_6" (SIM), motif "id_12" (cascade), and motif "id_36" (MIM) are not

composed of any 3-node functional motifs. For the 4-node motifs, there are eight

motifs that are not composed of any 4-node functional motifs: motif "id_14" (SIM),

motif "id_28," motif "id_74," motif "id_76" (MIM), motif "id_280," motif "id_328"

(cascade), motif "id_392," and motif "id_2184". These eight motifs exhibit the

property of *irreducibility*. However, each one of the eight motifs is embedded with

exactly one 3-node functional motif. In other words, given the 4-node motifs, the

irreducible property does not apply if we consider motifs composed of three nodes.

Supplementary File 2 summarizes the functional motifs for 3-node motifs, 4-node

motifs, and 3-node motifs embedded in 4-node motifs, where integers "1" and "0"

denote the presence or absence of a functional motif, respectively.

Spectral graph theory, reciprocity, and complexity measures

Table 1 summarizes the results of the nine graph energies and edge information for

the 3-node motifs. First, since some of the matrices, such as L and Q, are asymmetric,

their eigenvalues are complex in general. In fact, among the 3-node motifs, motif

"id_98" has a pair of complex conjugate eigenvalues, and their associated

eigenvectors are composed of complex components.

Table 1. The results of the nine graph energies and edge information for the 3-node
motifs.

ID	E	LE	QE	AA_i	LL_i	QQ_i	AL_i	AQ_i	LQ_i	e
6	0.00	2.67	2.67	1.41	4.32	4.32	1.41	1.41	3.83	*2*
12	0.00	2.67	2.67	2.00	4.34	4.34	2.00	2.00	3.93	*2*
14	2.00	4.00	4.00	2.41	6.13	6.13	3.00	3.00	5.45	3
36	0.00	2.67	2.67	1.41	4.32	4.32	1.41	1.41	3.83	*2*
38	0.00	4.00	4.00	2.24	6.39	6.34	2.63	2.37	6.01	3
46	2.00	5.33	5.33	2.73	8.24	8.16	2.00	3.86	7.59	*4*
74	2.00	4.00	4.00	2.41	6.13	6.13	3.00	3.00	5.45	3
78	2.83	5.33	5.33	2.83	8.00	8.00	3.86	3.86	7.29	4

98	3.00	4.29	4.46	3.00	6.29	6.46	4.25	4.36	6.01	3
102	3.06	5.33	5.56	3.24	8.17	8.25	4.76	5.02	7.57	4
108	2.00	5.33	5.33	2.73	8.24	8.16	2.00	3.86	7.59	*4*
110	3.24	6.67	6.72	3.49	10.09	10.09	5.38	5.70	9.40	5
238	4.00	8.00	8.00	4.00	12.00	12.00	6.47	6.93	11.21	6

Second, graph energy is correlated with the number of edges of a motif. For

instance, the graph energies of fully connected 3-node motifs and 4-node motifs are

maximal, despite having different energy definitions.

Third, it is quite common for certain motifs to have the same graph energy; that is

energy-degenerated motifs are rather common. Two motifs are said to be

equienergetic if they have the same total energy. For instance, two pairs of motifs

("id_6" and "id_36," and "id_14" and "id_74") are *equienergetic*, regardless of the

graph energy definition. The results of the 4-node motif graph energies and

eigenvectors are given in Supplementary File 3.

Fourth, although the results of the nine graph energies are quite similar, there are

differences among them: for instance, the multiplicity of the energy levels is

somewhat different. For the 3-node motifs, the multiplicities of graph energy E, 0, 2,

and 2.83 are 4, 4, and 1, respectively. For QE, there are three energy values, 2.67,

4.00, and 5.33, that are associated with the multiplicity of 3, 3, and 3, respectively.

Fifth, energy-degenerated motifs may or may not have identical spectra, $Sp(G)$.

This suggests that the use of $Sp(G)$ could allow for further distinction between the

motifs. More details are given below in the "Unique identifiers for network motifs"

section.

In Supplementary File 1, Supplementary Table S6 summarizes the lower (E_{min}) and

upper (E_{max}) graph energy bounds and ratios for the 3-node motifs and 4-node motifs.

For the 3-node motifs, the ratios are bounded between 2 and 4.91. These ratios are

slightly larger for 4-node motifs: they are bounded between 3.00 and 6.88. We found

that most of the molecular biological networks are not composed of motifs with large

graph energies; therefore, the maximum ratio cannot be achieved. Details are reported

below in the "Network motifs absent from the network" section.

Reciprocity of motifs

Table 2 depicts the traditional reciprocity R, reciprocity r, and $\bar{a}$ for the 3-node

motifs. Most of the R values are zero, which indicates that there is no edge pointing in

both directions. Positive and negative values of r denote the presence of cycles. Of the

13 reciprocity values, nine are negative, meaning that the majority of the 3-node

motifs have either in-connections or out-connections only. We note that motifs

containing one or two cycles can still have negative reciprocity values. The complete

sets of R, r, edges and $\bar{a}$ values of the 4-node motifs are given in Supplementary File

4.

Table 2. The results of traditional reciprocity (R), reciprocity (r), edge (e) and average
reciprocity ($\bar{a}$) of the 3-node motifs.

ID	R	r	e	$\bar{a}$
6	0	-0.5	2	1/3
12	0	-0.5	2	1/3
14	0	1/3	3	0.5
36	0	-0.5	2	1/3
38	0	-1	3	0.5
46	0	-0.5	4	2/3
74	0	1/3	3	0.5
78	1	1	4	2/3

98	0	-1	3	0.5
102	0	-0.5	4	2/3
108	0	-0.5	4	2/3
110	0	-0.2	5	5/6
238	1	1	6	1

366 **Graph complexity: cyclomatic complexity and Kolmogorov complexity**

367 For the 3-node motifs, Table 3 summarizes the results of the cyclomatic complexity

368 (*CC*) and Kolmogorov complexity (*KC*), and their rankings. The ranges of these *CC*

369 and *KC* values are 0–3 and 23.34–25.50, respectively. The complete sets of *CC* and

370 *KC* values of the 4-node motifs are given in Supplementary File 5, where the ranges

371 of *CC* and *KC* values are 0–8 and 33.80–43.74, respectively. These findings are

372 compatible with the notion that motifs composed of more nodes have higher

373 complexity.

374 Table 3. The results of the cyclomatic complexity (*CC*) and Kolmogorov complexity
375 (*KC*), and their ranking, for the 3-node motifs.

ID	CC	KC	Rank of CC	Rank of KC
6	3	23.34	11	1
12	1	23.83	3	3
14	2	24.30	8	6
36	1	23.55	3	2
38	2	24.87	8	8
46	3	25.50	11	13
74	0	23.85	1	4
78	1	25.00	3	9
98	0	24.82	1	7
102	1	25.01	3	10
108	1	25.11	3	11
110	2	25.25	8	12
238	3	24.14	11	5

376 A network motif with a large *CC* value suggests a more complex decision structure.

377 From Table 3, it is apparent that *KC* can serve as a parameter for distinguishing motif

378 patterns without any degeneracy. In other words, no two motifs have the same *KC*;

this is also true for the 4-node motifs. Motif "id_238" is a complete graph that is

described by the binary string "011101110," and this string corresponds to lower

algorithmic complexity (5^{th} rank).

Next, we examined the correlations between the two complexity measures. We

ranked *CC* and *KC* in ascending order and computed their Spearman Rank Correlation

Coefficients (*SRCC*). The correlation is not perfect; for example, motif "id_238" is

associated with the largest *CC* value (rank), but this is not the case for *KC* (5^{th} rank).

CC and *KC* show a relatively weak correlation—0.083 and 0.381—at the 3-node and

4-node levels, respectively. This is because *CC* and *KC* have different meanings: *CC*

measures the complexity of a motif's decision structure (the number of independent

gene regulation paths), while *KC* is an algorithmic measure which characterizes the

randomness and compressibility of a bit string.

Lastly, we investigated whether graph energy is proportional to graph complexity.

The results are listed in Supplementary File 1 – Supplementary Table S7. *KC* exhibits

a modest correlation with all the graph energies at the 3-node and 4-node levels. In

contrast, *CC* exhibits relatively weak and modest correlations with graph energy, at

both the 3-node and 4-node motif levels.

Supplementary File 1 – Supplementary Table S8 summarizes the results of strength

of *SRCC* (including minimum, maximum, and ranges) between graph complexity and

graph energy for 3-node and 4-node motifs. Our results suggest that there are

relatively weak (3-node *CC*) and modest correlations (3-node motif *KC* and 4-node

motif *CC and KC*) between graph complexity and graph energy.

Unique identifiers for network motifs

This section reports the results of determining an optimal parameter combination

that maximizes the removal of degenerated motifs. As shown in Table 4, three cases

are considered. "Case a" makes use of graph energy only, "case b" utilizes graph

energy *r* and *CC*, and "case c" employs energy, *r*, *CC*, and the energy spectrum. After

including *r* and *CC*, we can distinguish more motifs. The use of AL^t, *r*, *CC*, and

energy spectrum can fully distinguish the 3-node motifs. For 4-node motifs, the use of

LL^t, QQ^t and LQ^t achieves the best level of distinguishability: 136 out of 199 (68.3%).

Compared with *E, LE*, and *QE*, both *symmetric* and *asymmetric* generalized energies

serve as superior measures for distinguishing different motif patterns.

Table 4. The number of distinguishable motifs using optimal parameter combination
of graph energy, *r, CC*, and energy spectrum. "Case a" uses graph energy only, "case
b" uses graph energy, *r*, and *CC*, and "case c" uses energy, *r*, *CC*, and graph energy
spectrum.

	3-node motifs			4-node motifs		
	case a	case b	case c	case a	case b	case c
E	7	11	11	42	57	60
LE	6	10	11	35	51	96
QE	9	11	11	51	67	72
AA^t	10	12	12	74	86	92
LL^t	10	12	12	94	103	136
QQ^t	10	12	12	88	96	136
AL^t	10	12	13	117	128	130
AQ^t	10	12	12	120	129	131
LQ^t	10	12	12	109	117	136

Frequently found network motifs

Among the 17 cancer networks, 46 STNs, and nine cellular processes, there are 15

(88.2%), 40 (87.0%), and 7 (77.8%) networks, respectively, where more than 70% of

nodes are embedded in both 3-node motifs and 4-node motifs. Therefore, motif-

associated nodes account for a major portion of each network.

To determine frequently occurring motifs, we tabulate the frequency of occurrence

of each motif pattern, normalize the frequency to one, and compute the average

normalized frequency (probability) across the studied networks. Table 5 summarizes

the top seven most frequently found 3-node motifs and 4-node motifs in cancer

networks.

Table 5. The top seven most frequently found 3-node motifs and 4-node motifs in
cancer networks. SIM denotes simple input module, MIM denotes multiple input
module, and FFL denotes feed-forward loop.

	ID	average probability	reciprocity r	Name, embedded motif ID
3-node				
1	6	0.421	-1/2	SIM
2	12	0.414	-1/2	Cascade
3	36	0.152	-1/2	MIM
4	38	0.0091	-1	FFL, 12, 36
5	74	0.0022	1/3	12
6	14	0.0016	1/3	6
7	98	0.00092	-1	3-cycle, 12
4-node				
1	14	0.224	-1/3	SIM
2	328	0.158	-1/3	Cascade
3	28	0.148	-1/3	-
4	74	0.137	-1/3	-
5	76	0.100	-1/3	MIM
6	392	0.099	-1/3	-
7	280	0.0864	-1/3	-

For cancer networks, the three most frequently found 3-node motifs are id_6, id_12

and id_36. By examining the top three motifs, we observe the following common

features: (i) they do not contain any subgraphs (*irreducible*); (ii) they are composed of

a minimal number of edges (*N*-1 edges for a *N*-node motif); (iii) the reciprocity *r*

values are negative (-0.5) and those motifs have *no* cycles; (iv) they account for at

least 8% of the total number of motifs; and (v) they are associated with the lowest or

the second lowest graph energies, regardless of the graph energy definition.

The motifs ranked 4[th] to 7[th] ("id_38," "id_74," "id_14," and "id_98") are composed of

three edges. Motif "id_38" is the so-called feed-forward loop (FFL), which does not

contain cycles, whereas both "id_74" and "id_14" contain cycles. The 7[th]-ranked

motif ("id_98") is the so-called 3-cycle. Motif "id_12" is a subgraph of "id_38,"

"id_74," and "id_98", while "id_36" (MIM) is a subgraph of FFL and SIM is a

subgraph of "id_14". In other words, the frequently found motifs are the simplest

motifs, and are subgraphs of more complex motifs.

For 4-node motifs, the above features (i) to (iv) (but not feature (v)) are also valid for

the top seven most frequently found motifs. It is interesting to note that the

irreducible and negative reciprocity value (that is, -1/3) features hold at the 4-node

level. In addition, feature (v) holds if we consider graph energies *E, LE*, and *QE*, but

not the other six graph energy definitions. Furthermore, the above five features also

hold for STNs and cellular processes (see Supplementary File 1 - Supplementary

Tables S9 and S10).

The ranges of average probability for the top three frequently found 3-node motifs

and the top seven frequently found 4-node motifs are shown in Supplementary File 1 -

Supplementary Tables S11. Other than the 4-node motifs of cellular processes, the

ranges of average probability are quite similar. We note that cellular processes may

differ from the other two families of networks, but it is not clear whether this is

because a relatively small number (nine) of networks is available.

In Table 6, we summarize the top three most frequently found motifs and the top

seven motifs identified among different networks. Cancer networks and STNs exhibit

very similar results, which suggests that the underlying architectures are highly

similar. This indicates that molecular networks are composed of a *finite* number of

motif patterns—around seven patterns—with an upper *graph energy limit*. We

conjecture that other molecular networks, such as cell cycles, may demonstrate

similar properties.

Table 6. Comparison of frequently found motifs identified in cancer networks, STNs,
and cellular processes.

	Cancer networks	STN	Cellular processes
Top three most frequently found motifs			
3-node ID	6, 12, 36	12, 6, 36	12, 36, 6
Rank of *KC*	1, 3, 2	3, 1, 2	3, 2, 1
Top seven most frequently found motifs			
4-node ID	14, 328, 28, 74, 76, 392, 280	14, 28, 74, 328, 280, 76, 392	392, 328, 76, 280, 2184, 74, 28
Rank of *KC*	1, 7, 3, 5, 6, 33, 24	1, 3, 5, 24, 7, 24, 6, 33	33, 7, 6, 24, 7, 16, 5, 3

Next, we examine the association of frequently found motifs and complexity

measures. From Table 6, we observe that frequently found motifs have a lower *KC*

ranking (smaller *KC* value). A smaller *KC* value implies a lower degree of

randomness, less information, and higher compressibility. However, this observation

is not exactly the same at the 4-node level: there are three instances where the rank of

KC is larger. For instance, the rank of *KC* is as high as 16, 24, and 33 for id_2184,

id_280, and id_392, respectively. No obvious association exists between frequently

found motifs and cyclomatic complexity measures.

In summary, according to the above findings, we hypothesize that there are

underlying organizing principles that lead to the emergence of network structures.

Network motifs absent from the network

We enumerated all possible 3-node motifs and 4-node motifs for the 17 cancer

networks, 46 STNs, and nine cellular processes. In Supplementary File 1 -

Supplementary Tables S12 summarizes the number of 3-node motifs and 4-node

motifs with a non-zero frequency of occurrence in cancer networks, STNs, and

cellular processes. It is interesting to see that certain motifs are never present in the

three types of networks, except in two of the cellular processes. The first one is the

"adherens junction" network which consist of a 3-node motif (id_110), composed of

three genes: *CTNNA1*, *ACTB*, and *AFDN*. The second one is the "Signaling pathways

regulating pluripotency of stem cells (hsa04550)" network. We have identified a fully

connected 3-node motif (id_238) with three feedback loops connecting three genes:

Oct4, *Sox2*, and *Nanog*. It is well-known that, with the *LIN28* genes, these four genes

are liable to reprogram human somatic cells into pluripotent stem cells [68].

As long as there are motifs absent in the cancer networks, STNs, and cellular

processes, there is a graph energy cutoff associated with these three families of

networks. Supplementary File 1 - Supplementary Tables S13 depicts the results of the

energy cutoffs, maximum graph energies, and their ratios for the cancer networks.

Among the nine graph energy definitions, the ratios may be as high as 0.750 and

0.667 for 3-node motifs and 4-node motifs, respectively. However, they can be as low

as 0.536 (LQ^t energy) and 0.481 (AQ^t energy) for the 3-node motifs and 4-node motifs,

respectively. The results of the graph energy cutoffs and ratios for the STNs and

cellular processes are given in Supplementary File 1 - Supplementary Tables S14 and

S15. For cellular processes, the cutoff ratio may be as high as 1.00 for the 3-node

motifs, because we have identified a fully connected 3-node motif (id_238). At the 3-

node level, two of the cellular processes exhibit peculiar network structures; this is an

open issue that remains to be investigated.

Nevertheless, our results suggest that there is an existing energy cutoff or ratio that

constrains the presence of certain motifs embedded in a molecular network. In

addition, the data indicate that the cutoff ratio for 3-node motifs is slightly higher than

that for 4-node motifs. Furthermore, the motif probability distribution density and the

graph energy of a motif obeys an inverse relation, that is, the smaller the probability,

the higher the graph energy.

Characterizing the frequency distributions of motifs using entropy

We utilized the entropy-based quantity, normalized Shannon entropy, H_R, to

quantify the frequency distributions of the occurrence of motifs for the cancer

networks. For randomized distribution, H achieves the maximal values, 3.700 ($\log_2$

(13)) and 7.637 ($\log_2$ (199)), for 3-node motifs and 4-node motifs, respectively. Table

7 lists the number of 3-node motifs, N_3; normalized Shannon entropy, H_{3R}, for the 3-

node motifs; number of 4-node motifs, N_4; and normalized Shannon entropy, H_{4R}, for

the 4-node motifs.

Table 7. The results of N_3, N_4, H_{3R} and H_{4R} for cancer networks.

Cancer networks	N_3	H_{3R}	N_4	H_{4R}
Acute_myeloid_leukemia_[hsa05221]	160	0.428	577	0.385
Basal_cell_carcinoma_[hsa05217]	34	*0.323*	51	*0.273*
Breast_cancer_[hsa05224]	145	0.449	445	0.437
Choline_metabolism_in_cancer_[hsa05231]	70	0.465	193	0.406
Chronic_myeloid_leukemia_[hsa05220]	71	0.368	145	0.323
Colorectal_cancer_[hsa05210]	71	0.467	124	0.403
Endometrial_cancer_[hsa05213]	45	0.329	60	0.295
Gastric_cancer_[hsa05226]	87	0.355	153	0.344
Glioma_[hsa05214]	80	0.410	183	0.390
Hepatocellular_carcinoma_[hsa05225]	65	0.355	80	0.350
Melanoma_[hsa05218]	46	0.374	82	0.337
Non-small_cell_lung_cancer_[hsa05223]	103	*0.493*	284	*0.483*
Pancreatic_cancer_[hsa05212]	74	0.422	131	0.371
Pathways_in_cancer_[hsa05200]	640	0.473	2795	0.450
Prostate_cancer_[hsa05215]	102	0.372	357	0.335
Renal_cell_carcinoma_[hsa05211]	58	0.385	114	0.353
Small_cell_lung_cancer_[hsa05222]	61	0.362	96	0.318

For all of the cancer networks we studied, the frequency distributions of the motifs are

not uniformly distributed among the motif patterns; therefore, H_{3R} and H_{4R} are

different from one another. The results of N_3, N_4 H_{3R}, and H_{4R} for STNs and cellular

processes are given in Supplementary File 1 - Supplementary Tables S16 and S17,

respectively.

Supplementary File 1 - Supplementary Table S18 shows the ranges of H_{3R} and H_{4R}

for cancer networks, STNs, and cellular processes. The ranges of H_{3R} and H_{4R} for

cancer networks and cellular processes are quite similar, whereas STNs show larger

ranges: 0.532 and 0.622. We also note that the HIF-1 signaling pathway [hsa04066]

has very small H_{3R} and H_{4R}. This is because the transcription factor, HIF-1β, functions

as a master regulator of many genes; therefore, the SIM motif is the dominant motif at

both 3-node and 4-node levels.

Discussion and conclusions

Network motifs play an important role in biological networks. We made use of a

rigorous   mathematical   and   systematic   approach—spectral   graph   theory—to

characterize 3-node and 4-node network motifs. A total of nine graph energies were

introduced to characterize network motifs. In addition, we characterized their

complexity by using two widely accepted complexity measures, *CC* and *KC*.

The concept of a unique identifier was introduced to label network motifs. This

novel idea combines four parameters—graph energy, reciprocity, *CC*, and eigenvalue

spectrum—to characterize a network motif.

A foreseeable application of this identifier is to examine the transition between

different motifs. It is possible that the regulatory interactions among the genetic

elements may be disrupted or activated because of genetic mutation or epigenetic

modification.

We conjecture that driver mutations are enriched or depleted in certain motif

positions, such as the source node of a motif. A source node is a node that has only

outgoing edges. In other words, a mutation driver gene acts as an upstreaming

regulator. Several studies have reported that certain motif positions, such as the source

nodes and target nodes, are enriched in cancer-associated genes [69-70].

Some of the 3-node motifs and 4-node motifs are interconnected through shared

genetic elements. These types of modules are called coupled motif structures (CMS)

in our previous work [45]. One can merge interconnected motifs to form higher-order

network structures.

We have extended a developed algorithm to identify complete sets of 3-node motifs

and 4-node motifs for 17 cancer networks, 46 STNs, and nine cellular processes.

Except for a few networks, 3-node motifs and 4-node motifs account for more than 70%

of the nodes in the studied networks. Furthermore, this study discovered the following

features:

(i) The relative entropies of the motif distributions are not equal, or close to, one,

indicating that the identified motifs are not distributed uniformly among the 13 and

199 patterns.

(ii) Biological networks are composed of a finite number of motif patterns, this

suggest the presence of graph energy cutoffs.

(iii) Irreducible motif patterns are the most frequently found motifs; for instance, the

cascade pattern is the most frequently found motif, followed by the SIM and MIM

motifs.

(iv) All of the three families of networks exhibit the above features, suggesting that

there is a universal organization principle determining the underlying network

architecture.

In conclusion, this study provides a systematic and rigorous approach to dissecting

the underlying structures of biological molecular networks. SGT serves as a powerful

approach in distinguishing different motif topologies or connectivity patterns, which

inspires our hypothesis that network structures can be understood in terms of the 3-

node and 4-node motifs. The next step is to test our hypothesis by analyzing the 5-

node motifs. We expect that our efforts may help to elucidate the complex nature of

molecular networks.

Supporting information
Supplementary File 1. Input data and Methods
Supplementary Table S1. List of the nodes, edges, and motif-associated nodes
information for the 17 cancer networks.
Supplementary Table S2. List of the nodes, edges, and motif-associated nodes
information for the 46 STNs.
Supplementary Table S3. List of the nodes, edges, and motif-associated nodes
information for the nine cellular processes.
Supplementary Table S4. Motif identification tool - *PatternFinder* algorithm.
Supplementary Table S5. Algorithm for finding a unique identifier for the 3-node
motifs.
Supplementary Table S6. The results of the lower (E_{min}) and upper (E_{max}) bounds of
the nine graph energies and ratios for the 3-node motifs and 4-node motifs.
Supplementary Table S7. The results of the correlation strength (*SRCC*) between
graph complexity and graph energy for the 3-node motifs and 4-node motifs.

Supplementary Table S8. The results of the correlation strength (including minimum,
maximum, and ranges) between graph complexity and graph energy for the 3-node
motifs and 4-node motifs.
Supplementary Table S9. The top seven most frequently found 3-node motifs and
4-node motifs for STNs.
Supplementary Table S10. The top seven most frequently found 3-node motifs and 4-
node motifs for cellular processes.
Supplementary Table S11. The ranges of average probability for the top three
frequently found 3-node motifs and the top seven frequently found 4-node motifs.
Supplementary Table S12. The results of the number of possible 3-node motif
patterns and 4-node motif patterns present in the 17 cancer networks, 46 STNs, and
nine cellular processes.
Supplementary Table S13. The results of the cutoff and maximum graph energies of
the smallest non-zero average probability for the 3-node motifs and 4-node motifs
present in cancer networks.
Supplementary Table S14. The results of the cutoff and maximum graph energies of
the smallest non-zero average probability for the 3-node motifs and 4-node motifs
present in STNs.
Supplementary Table S15. The results of the cutoff and maximum graph energies of
the smallest non-zero average probability for the 3-node motifs and 4-node motifs
present in cellular processes.
Supplementary Table S16. The results of N_3, N_4, H_{3R}, and H_{4R} for STNs.
Supplementary Table S17. The results of N_3, N_4, H_{3R}, and H_{4R} for cellular processes.
Supplementary Tables S18. The ranges of H_{3R} and H_{4R} for cancer networks, STNs,
and cellular processes.
Supplementary File 2. The results of both 3-node and 4-node motif subgraphs.
Supplementary File 3. The results of the 4-node motif graph energies and
eigenvectors.
Supplementary File 4. The complete sets of reciprocity values of the 4-node motifs.
Supplementary File 5. The complete sets of cyclomatic complexity and Kolmogorov
complexity values of the 4-node motifs.
620

Acknowledgments

Dr. Chien-Hung Huang and Mr. Alice, Hsieh work are supported by the Ministry of

Science and Technology (MOST, https://www.most.gov.tw/?l=en) under the grants of

MOST 107-2221-E-150-038. Dr. Ka-Lok Ng work is supported by the grants of

MOST 106-2221-E-468-017, MOST 107-2632-E-468-002, and also supported under

the grants from Asia University, 106-asia-06, 107-asia-02 and 107-asia-09. Dr. Jeffrey

J. P. Tsai work is supported by the grant of MOST 107-2632-E-468-002. We would

like to thank He-Xing Li, Ci-Jun Peng and I-Lun Hsieh, who spent efforts on

developing the codes. The funders, MOST and Asia University, had no role in study

design, data collection and analysis, decision to publish, or preparation of the

manuscript. We also thank the 'Editage Professional English Editing Service, Cactus

Communications', for editing the English.

Conflict of interest

635 None. The authors have declared that no competing interests exist.

Authors' Contributions

Chien-Hung Huang conducted the algorithm development, review and edited the manuscript. Jeffrey J. P. Tsai provided interpretation of the results and review the manuscript. Nilubon Kurubanjerdjit conducted the complexity measure analysis, literature search and participated in discussion. Ka-Lok Ng is the corresponding author, who designed the study, review and drafted the manuscript.

References

1. Hartwell LH, Hopfield JJ, Leibler S, Murray AW. From molecular to modular cell biology. Nature. 1999;402(6761 Suppl):C47-52.
2. Lauffenburger DA. Cell signaling pathways as control modules: complexity for simplicity? Proc Natl Acad Sci USA. 2000;97:5031-5033.
3. Shen-Orr SS, Milo R, Mangan S, Alon U. Network motifs in the transcriptional regulation network of *Escherichia coli*. Nature Genetics.2002; 31:64.
4. Milo R, Shen-Orr S, Itzkovitz S, Kashtan N, Chklovskii D, Alon U. Network motifs: simple building blocks of complex networks. Science. 2002;298:824-827.
5. Schreiber F, Schwobbermeyer H. MAVISTO: a tool for the exploration of network motifs. Bioinformatics. 2005;21:3572-3574.
6. Wernicke S, Rasche F. FANMOD: a tool for fast network motif detection. Bioinformatics. 2006;22:1152-1153.
7. Ferro A, Giugno R, Pigola G, Pulvirenti A, Skripin D, Bader GD, et al. NetMatch: a Cytoscape plugin for searching biological networks. Bioinformatics. 2007;23: 910-912.
8. Ma'ayan A. Insights into the organization of biochemical regulatory networks using graph theory analyses. The Journal of biological chemistry. 2009;284:5451-5455.
9. Jeong H, Tombor B, Albert R, Oltvai ZN, Barabási AL. The large-scale organization of metabolic networks. Nature. 2000;407(6804):651-654.
10. Lee SH, Kim PJ, Jeong H. Global organization of protein complexome in the yeast Saccharomyces cerevisiae. BMC Syst Biol. 2011;5:126.
11. Lee PH, Huang CH, Fang JF, Liu HC, Ng KL. Hierarchical and topological study of the protein-protein interaction networks. Advances in Complex Systems. 2005;8(4):383-397.
12. Bonacich P, Lloyd P. Eigenvector-like measures of centrality for asymmetric relations. Social Networks. 2001;23:191-201.
13. Newman MEJ. The Mathematics of networks, The New Palgrave Encyclopedia of Economics, 2nd edition, L. E. Blume and S. N. Durlauf (eds.), Palgrave Macmillan, Basingstoke (2008).

14. Pavlopoulos GA, Secrier M, Moschopoulos CN, Soldatos TG, Kossida S, Aerts J, et al. Using graph theory to analyze biological networks. BioData Min. 2010;4:10.

15. Konganti, K, Wang G, Yang E, Cai JJ. SBEToolbox: a MATLAB toolbox for biological network analysis. Evol Bioinform Online. 2013;9:355-362.

16. Bloch F, Jackson MO, Tebaldi P. Centrality Measures in Networks. arXiv:1608.05845v3 [physics.soc-ph] (2016).

17. Albert R, Jeong H, Barabasi AL. Error and attack tolerance of complex networks. Nature. 2000;406 (6794):378–382.

18. Huang CH, Chen TH, Ng KL. Graph theory and stability analysis of protein complex interaction networks. IET Systems Biology. 2016;10(2):64-75.

19. Przulj N. Biological network comparison using graphlet degree distribution. Bioinformatics. 2007;23:177-183.

20. Yaveroğlu ÖN, Malod-Dognin N, Davis D, Levnajic Z, Janjic V, Karapandza R, et al. Revealing the hidden language of complex networks. Sci Rep. 2014;4:4547.

21. Trpevski I, Dimitrova T, Boshkovski T, Stikov N, Kocarev L. Graphlet characteristics in directed networks. Sci Rep. 2016;6:37057.

22. Sarajlić A, Malod-Dognin N, Yaveroğlu ÖN, Pržulj N. Graphlet-based Characterization of Directed Networks. Sci Rep. 2016;6:35098.

23. Dancoff SM, Quastler H. Information content and error rate of living things. In: Essays on the Use of Information Theory in Biology, eds. H. Quastler, 263–274. Urbana: University of Illinois Press (1953).

24. Rashevsky N. Topology and life: in search of general mathematical principles in biology and sociology. Bull Math Biophys. 1954;16(4):317-348.

25. Rashevsky N. Life, information theory, and topology. Bull Math Biophys. 1955;17: 229.

26. Mowshowitz A. Entropy and the complexity of the graphs I: An index of the relative complexity of a graph. Bull Math Biophys. 1968;30:175-204.

27. Mowshowitz A. Entropy and the complexity of graphs. II. The information content of digraphs and infinite graphs. Bull Math Biophys. 1968;30(2):225-240.

28. Harary F, Palmer EM. Graphical Enumeration. Academic Press, NY (1973).

29. Sloane, NJA, Plouffe S. The Encyclopedia of Integer Sequences. Academic Press, San Diego (1995).

30. Kim W, Diko M, Rawson K. Network motif detection: algorithms, parallel and cloud computing, and related tools. Tsinghua science and technology. 2013;18(5): 469-489.

31. Konagurthu AS, Lesk AM. On the origin of distribution patterns of motifs in biological networks. BMC System Biology. 2008:2(73):1-8.

32. Adami C, Qian J, Rupp M, Hintze A. Information content of colored motifs in complex networks. Artificial Life. 2011;17(4):375-390.

33. Cvetkovic D, Simic S. Graph spectra in computer science. Linear Algebra and its Applications. 2011:434(6):1545-1562.

34. Banerjee A, Jost J. Graph spectra as a systematic tool in computational biology. Discrete Applied Mathematics. 2009;157(10):2425-2431.

35. Brualdi RA. Spectra of digraphs. Linear Algebra and its Applications. 2010;432(9): 2181-2213.

36. Mowshowitz A. The characteristic polynomial of a graph. Journal of Combinatorial Theory, Series B. 1972;12(2):177-193.

37. Weyuker EJ. Evaluating software complexity measures. IEEE transactions on Software Engineering. 1988;14(9):1357-1365.

38. Mowshowitz A. Entropy and the complexity of the graphs II. The information
content of digraphs and infinite graphs. Bull Math Biophys. 1968;30:225-240.
39. Minoli D. Combinatorial graph complexity. Atti. Accad. Naz. Lincei, VIII. Ser,
Rend, Cl. Sci Fis Mat Nat. 1975;59:651-661.
40. Wilson RC, Zhu, P. A study of graph spectra for comparing graphs and trees.
Pattern Recognition. 2008;41:2833-2841.
41. Mueller LA, Kugler KG, Dander A, Graber A, Dehmer M. QuACN: an R package
for analyzing complex biological networks quantitatively. Bioinformatics.
2011;27(1):140-141.
42. Schramm G, Kannabiran N, König R. Regulation patterns in signaling networks of
cancer. BMC Systems Biology. 2010;4:162.
43. West J, Bianconi G, Severini S, Teschendorff AE. Differential network entropy
reveals cancer system hallmarks. Scientific Report. 2012;2:802.
44. Teschendorff AE, Banerji CR, Severini S, Kuehn R, Sollich P. Increased signaling
entropy in cancer requires the scale-free property of protein interaction networks.
Scientific Report. 2015;5:9646.
45. Hsieh WT, Tzeng KR, Ciou JS, Tsai JJ, Kurubanjerdjit N, Huang CH, et al.
Transcription factor and microRNA-regulated network motifs for cancer and
signal transduction networks. BMC Systems Biology. 2015;9(1):S5.
46. Li HX. In silico study of significant network motifs in the cancer networks.
Master Thesis, National Formosa University, Taiwan (2016). Advisor: Huang, C.
H., co-advisor: Ng, K. L.
47. Nakaya A, Katayama T, Itoh M, Hiranuka K, Kawashima S, Moriya Y, et al.
KEGG OC: a large-scale automatic construction of taxonomy-based ortholog
clusters. Nucleic Acids Res. 2013;41:D353-357.
48. Nishida K, Ono K, Kanaya S, Takahashi K. KEGGscape: a Cytoscape app for
pathway data integration. F1000Research. 2014;3:144.
49. Arakelyan A, Nersisyan L. KEGGParser: parsing and editing KEGG pathway
maps in Matlab. Bioinformatics.2013;29(4):518-519.
50. Alon U. An introduction to systems biology: design principles of biological
circuits. Boca Raton, FL: Chapman & Hall/CRC (2007).
51. Sporns O, Kotter R. Motifs in brain networks. PLoS Biol. 2004;2(11):e369.
52. Gutman I. The Energy of a Graph. Ber. Math-Statist. Sekt. Forschungsz. Graz,
1978;103:1-22.
53. Gutman I. Total π – electron energy of benzenoid hydrocarbons. Topics Curr
Chem. 1992;162:29-63.
54. Li XL, Shi YT, Gutman I. Graph Energy. New York: Springer Verlag (2012).
55. Cvetkovic D, Doob M, Sachs H. Spectra of Graphs: Theory and Applications. 3rd
edition, Huthig Pub Ltd (1997).
56. Chung FRK. Spectral Graph Theory. American Mathematical Soc., USA (1997).
57. Cvetkovic D, Simic SK. Towards a spectral theory of graphs based on signless
Laplacian I. PUBLICATIONS DE L'INSTITUT MATHÉMATIQUE, Nouvelle
série, tome. 2009;85(99):19-33.
58. Cvetkovic D, Simic S. Towards a spectral theory of graphs based on signless
Laplacian II. Linear Algebra and its Applications. 2010;432:2257-2272.
59. Gutman I, Zhou B. Laplacian energy of a graph. Linear Algebra and its
Applications. 2006;414:29-37.
60. Nikiforov V. The energy of graphs and matrices. J Math Anal Appl. 2007;326:
1472-1475.

61. Nikiforov V. Beyond graph energy: Norms of graphs and matrices. Linear
Algebra and its Applications. 2016;506:82-138.
62. Adiga C, Balakrishnan R, So W. The skew energy of a digraph. Linear Algebra
Appl. 2010;432:1825-1835.
63. Garlaschelli D, Loffredo MI. Patterns of Link Reciprocity in Directed Networks.
Phys Rev Lett. 2004;93:268701.
64. Squartini T, Picciolo F, Ruzzenenti F, Garlaschelli D. Reciprocity of weighted
networks. Scientific Reports. 2013;3:2729.
65. McCabe TJ. A complexity measure. IEEE Transactions on Software Engineering.
1976;4:308-320.
66. Soler-Toscano F, Zenil H, Delahaye JP, Gauvrit N. Calculating kolmogorov
complexity from the output frequency distributions of small turing machines.
PLoS ONE. 2014;9(5):e96223.
67. Zenil H, Kiani NA, Tegnér J. Methods of information theory and algorithmic
complexity for network biology. Seminars in Cell and Developmental Biology.
2016;51: 32-43. [an earlier version appeared in arXiv:1401.3604 [q-bio.MN, 15
Oct 2014].
68. Yu J, Vodyanik MA, Smuga-Otto K, Antosiewicz-Bourget J, Frane JL, Tian S, et
al. Induced pluripotent stem cell lines derived from human somatic cells. Science.
2007;318(5858):1917-1920.
69. Awan A, Bari H, Yan F, Moksong S, Yang S, Chowdhury S, et al. Regulatory
network motifs and hotspots of cancer genes in a mammalian cellular signalling
network. IET Syst Biol. 2007;1(5):292-297.
70. Carson MB, Gu J, Yu G, Lu H. Identification of cancer-related genes and motifs
in the human gene regulatory network. IET Syst Biol. 2015;9(4):128-134.
798