MoMI-G: Modular Multi-scale Integrated Genome Graph Browser

Toshiyuki T. Yokoyama, Yoshitaka Sakamoto, Masahide Seki, Yutaka Suzuki, Masahiro Kasahara[*]

Affiliations

Department of Computational Biology and Medical Sciences, Graduate School of Frontier Sciences,

The University of Tokyo, Chiba, Japan

[*]Correspondence should be addressed to

Masahiro Kasahara

E-mail: mkasa@k.u-tokyo.ac.jp

Tel/Fax: +81 4 7136 4110

Keywords

Structural Variant; Genome Browser; Visualization; Variation Graphs; Long-read Sequencing;

Genome Graphs

ABSTRACT

Long-read sequencing allows more sensitive and accurate discovery of structural variants (SVs). While more and more SVs are being identified, a number of them are difficult to visualize using existing SV visualization tools. Therefore, methods to visualize SVs such as nested or large SVs of over a megabase pair need to be developed. To this end, we developed MOdular Multi-scale Integrated Genome graph browser, MoMI-G, a web-based genome browser to visualize SVs, genes, repeats, and other annotations as a variation graph with paths. This browser allows more intuitive recognition of large, nested, and potentially more complex SVs. MoMI-G has view modules for different scales, which allow users to view the whole genome down to nucleotide-level alignments of long reads. Alignments spanning reference alleles and those spanning alternative alleles are shown in the same view. Users can customize the view, if they are not satisfied with the preset views. In addition, MoMI-G has Interval Card Deck, a feature for rapid manual inspection of hundreds of SVs. Herein, we describe the utility of MoMI-G by using representative examples of large and nested SVs found in two cell lines, LC-2/ad and CHM1. MoMI-G is freely available at https://github.com/MoMI-G/MoMI-G under the MIT license.

INTRODUCTION

Structural Variants (SVs), which are often characterized as 50 bp or larger genomic rearrangements of chromosomal segments, are associated with various human diseases (Stankiewicz and Lupski 2010; Weischenfeldt et al. 2013; Sedlazeck et al. 2018a). For example, some fusion genes caused by SVs are known as oncogenes (Mertens et al. 2015). Identifying SVs and interpreting their potential impacts are a critical step toward cataloguing the variations in the human genome and mechanistic understanding of genetic diseases and cancers.

SV visualization is a very important step in an SV calling process because it enables the manual inspection of SVs for achieving two goals. The first is to better understand the relationships between SVs and other genomic features. The second is to ensure a smaller number of false positives. Previously, most structural genomic rearrangements were categorized into insertion, deletion, inversion, duplication, and translocation, which were referred to by some researchers as canonical SVs (Quinlan and Hall 2012; Collins et al. 2017). SV visualization tools focused on visualizing canonical SVs, because they accounted for a significant portion of the identified SVs at that time.

However, as long-read sequencing technologies revealed an increasing number of SVs, SV visualization with the existing tools became more challenging. For example, a large inversion is often identified as two separate translocations at the two breakpoints of the inversion; one might not be able to immediately recognize that the two translocation events are explained by a single large inversion. Another example is a nested SV. When there is a large inversion that contains several smaller SVs such as insertion of transposons or deletions, the nested SVs often obscure the relationship between genomic regions that are distant in the reference genome, but are actually close in the target genome. Thus, SV visualization tools should be able to simultaneously display multiple intervals along with their relationships, even when the breakpoints are distant or when SVs are nested.

For the second goal, manual inspection of SVs identified using SV calling tools is important

because these tools are not yet accurate enough; therefore, human experts are required to accurately

and reliably distinguish true positive SVs from false positive ones. False positives often increase under

the following conditions: (1) when the sequencing coverage is low, (2) when the sequencing error rate

of reads used for SV calling is high, (3) when the target genome has segmental duplications or

abundant repetitive sequences, or (4) when many SVs are heterozygous. Therefore, SV candidates

need to be manually inspected using read alignments and genomic annotations (Guan and Sung 2016)

and tens of thousands of them need to be filtered. However, manual filtering by using existing SV

visualization tools occasionally becomes very difficult for certain cases. For example, for nested SVs

and long reads spanning over multiple breakpoints, existing tools cannot show the read alignments in

multiple intervals at a glance, making it unrealistic to manually judge the authenticity of candidate

SVs.

To achieve these two goals, we developed MoMI-G (pronounced as mo-me-gee), a genome

graph browser that visualizes SVs using variation graphs (Fig. 1, Supplemental Fig. 1). Herein, we

describe the use cases and features of MoMI-G using the LC-2/ad human lung adenocarcinoma cell

line that carries a CCDC6-RET fusion gene (Matsubara et al. 2012; Suzuki et al. 2014, 2015, 2017),

and CHM1, a human hydatidiform mole cell line that originates from a single haploid (Chaisson et al.

2015). MoMI-G helps in understanding the entire picture of SVs, even those that are nested or large,

regardless of their size. MoMI-G allows researchers to obtain novel biological knowledge by

comparing a reference genome with an individual genome by using a variation graph.

The reason for dubbing MoMI-G as a "genome graph" browser is that we employed genome

graphs as a theoretical backbone for providing more systematic way of presenting SVs with varying

complexities, including nested and large SVs. A genome graph is a new technique to represent multiple

genome sequences as a graph (Paten et al. 2017). For example, a cancer genome can be represented as

a graph with SVs embedded as alternative edges (Nattestad et al. 2016a). Several variants in the

definitions of a sequence graph are available (Paten et al. 2018; Garrison et al. 2018). The definition

of a variation graph used herein is almost the same as the one used in SequenceTubeMap

(https://github.com/vgteam/sequenceTubeMap). A variation graph is a bi-directed graph composed of

nodes and paths. A node represents a part of a DNA sequence. A path represents a contiguous sequence,

which can be obtained by concatenating nodes in a way specified by the path (i.e., a list of <node ID,

order, orientation>). SequenceTubeMap is a JavaScript library used in MoMI-G for visualizing a

variation (sub)graph in a web browser (i.e., client side). In the server side, vg is used for retrieving a

subgraph of variation graphs (Garrison et al. 2018). Genome graphs can represent SVs more naturally

than those that represent SVs as differences from a reference genome (e.g., VCF).

To our knowledge, MoMI-G is the only SV visualization tool that satisfies the following

conditions: (1) allows visualization of (possibly distant) multiple intervals; (2) displays SVs that span

multiple intervals; (3) displays SVs at varying scales, i.e., chromosome, gene, and nucleotide scales;

(4a) the chromosome scale view can show the distribution of SVs on one or more chromosomes; (4b)

the gene scale view can show annotations such as exon/intron structures and repeats; (4c) the

nucleotide scale view can show nucleotide-level alignments, in particular, read alignments that

correspond to both alleles of heterozygous SVs are shown simultaneously; and (5) allows users to

manually inspect hundreds of SVs. Most genome browsers such as UCSC (Kent et al. 2002), JBrowse

(Buels et al. 2016), and IGV (Thorvaldsdóttir et al. 2013) are designed for inspecting single-nucleotide

variants or short insertions and deletions by showing annotations and read alignments on a reference

genome, but none of them meet conditions (2), (3), (4a), and (5). Tools for visualizing SVs in a human

genome, such as 10X Loupe (http://loupe.10xgenomics.com/loupe/), iFUSE (Hiltemann et al. 2013),

targetSeqView (Halper-Stromberg et al. 2014), AGFusion (Murphy and Elemento 2016), SVPV

(Munro et al. 2017), BreakPoint Surveyor (Wyczalkowski et al. 2017), NGB (Ahdesmäki et al. 2017),

VIPER (Wöste and Dugas 2018), SV-plaudit (Belyeu et al. 2018), and MAVIS (Reisle et al. 2018), are

suitable for inspecting an SV between two intervals, but they do not visualize an SV spanning over

multiple intervals. Circos (Krzywinski et al. 2009) and Circos-based visualizations such as

GenomeRing (Herbig et al. 2012) and CIRCUS (Naquin et al. 2014) are widely used for visualizing

the distribution of SVs by using the circular layout at the chromosome scale, but they fail in meeting

conditions (3), (4b), and (4c). Svviz (Spies et al. 2015) and BasePlayer (Katainen et al. 2018) can be

used to visualize an SV between multiple intervals of a reference genome, although they cannot be

used to visualize nested SVs. Fastbreak (Bressler et al. 2012) integrates views at different scales by

using a graph representation; however, it has no view for nucleotide-scale information such as read

alignment. Gremlin (O'Brien et al. 2010) and ViVar (Sante et al. 2014) allow visualization of inter-

chromosomal relationships of SVs, but they cannot visualize read alignments. Ribbon and

SplitThreader (Nattestad et al. 2016a, 2016b) are a pair of tools for visualizing SVs with different

views such as Circos, SVs between two chromosomes, read alignments, and genomic annotations, but

they lack tight integration, and hence an ID to specify the coordinate interval needs to be manually

transferred, which could lead to non-negligible time loss when hundreds of SVs need to be inspected.

Moreover, they cannot visualize read alignments for heterozygous SVs. Assembly graph visualization

tools such as ConPath, ABySS Explorer, TGNet, ContigScape, Contiguity, Bandage, and BARLEX

(Kim et al. 2008; Nielsen et al. 2009; Riba-grognuz et al. 2011; Tang et al. 2013; Revanna et al. 2012;

Wick et al. 2015; Colmsee et al. 2015) are also useful for visualizing contigs and their connections.

However, they are designed for small genomes. When these tools are used to visualize a graph for

larger genomes, an uninterpretable large dense hairball is usually obtained. Displaying only a part of

the graph is critical for avoiding the hairball problem. For the same reason, graphviz (Gansner and

North 1999) is unsuitable for a larger genome graph. No tools described above (other than MoMI-G)

meet all conditions (1) to (5).

A.

B.

C.

Figure 1. Overview of MoMI-G. A user typically selects one of the preset combinations of view

modules. The user can customize the window by adding or removing view modules, if necessary.

Three examples showing views of different scales are shown. Comprehensive descriptions for all

modules are shown in Supplemental Fig. 1.

(A) Chromosome-scale view: Circos Plot (left) shows the distribution of SVs over all chromosomes.

Arcs are chromosomes. Curves represent SVs. Feature Table (right) shows a filtered/sorted list of

the SVs in an input VCF file.

(B) Gene-scale view: SequenceTubeMap (top) shows the graphical view of the genomic region

selected in Circos Plot, Feature Table, or Interval Card Deck. A rounded rectangle is a node that

represents a piece of a genomic sequence. The thick lines spanning over nodes are paths; the

horizontal thick black line with light/dark shades is a chromosome of the reference genome, and

the blue line indicates one end of an inversion. The color of lines indicating SVs is assigned

arbitrarily. Read alignments are shown as gray thin lines, suggesting that the inversion here is

likely heterozygous. Interval Card Deck (bottom) queues a list of genomic intervals for candidate

SVs selected by using Circos Plot or Feature Table for rapidly screening hundreds of candidate

intervals.

(C) Nucleotide-scale view: SequenceTubeMap can show nucleotides.

RESULTS

MoMI-G is a web-based genome browser developed as a single-page application implemented in

TypeScript and with React. Because users need different types of views even for the same data, MoMI-

G provides three groups of view modules for the analysis of SVs at different scales, namely,

chromosome-scale, gene-scale, and nucleotide-scale view groups (Supplemental Table 1). Users can

use one or more view modules in a single window.

The input of MoMI-G is a variation graph, read alignment (optional), and annotations

(optional). MoMI-G accepts a succinct representation of a vg variation graph, an XG file, as a variation

graph. A script that converts a FASTA file of a reference genome and a common variant format (VCF)

file into an XG file is included in the MoMI-G package, although the VCF format cannot represent

some types of SVs that the XG format can represent, such as nested insertions. Read alignment data

on the graph need to be a graph alignment map (GAM) file; alternatively, users can convert a binary

alignment map (BAM) file into a GAM file, although this is not recommended due to some limitations.

We show three examples from two samples for demonstrating the utility of MoMI-G. One

of the examples is a large inversion, and the other is nested SVs that are difficult to visualize using

existing tools. We also show nested SVs from the CHM1 dataset (Chaisson et al. 2015). For all the

examples, we used Amazon EC2 instance type t2.large with 8 GB of memory and 2.4 GHz Intel Xeon

processor as a MoMI-G server; the server requirement is minimal. MoMI-G supports common

browsers, including Chrome, Safari, and Firefox.

Data model used in MoMI-G and MoMI-G tools

To our knowledge, no publicly available SV visualization tools are available for large and nested SVs

with alignments of long reads. Thus, we aimed at developing a graph genome browser at the earliest

so that users can obtain new biological knowledge from real data. We used an existing library,

SequenceTubeMap for visualizing a variation subgraph, rather than developing our own library from

scratch.

SequenceTubeMap is a JavaScript library that visualizes multiple related sequences such as

haplotypes. A variation graph used in SequenceTubeMap is a set of nodes and paths, where a node

represents a part of a DNA sequence, and a path represents (a part of) a haplotype. Edges are implicitly

represented by adjacent nodes in paths.

MoMI-G accepts variation graphs in which SVs are represented by paths so that

SequenceTubeMap can visualize them. A deletion is represented by a path that skips over a sequence

that other paths pass through. Similarly, an insertion is represented by a path that passes through an

extra sequence that other paths do not visit; an inversion is represented by a path where a part of the

sequence in other paths is reversed; and a duplication is represented by a path that passes through the

same sequence twice or more.

The MoMI-G package includes a set of scripts (MoMI-G tools) that converts a VCF file into

the variation graph format. We used MoMI-G tools for generating the input variation graphs;

alternatively, users can generate variation graphs on their own. See the method section and

Supplemental Figure 2 for the details of MoMI-G tools. Briefly, MoMI-G tools convert a VCF record

into a path in the output variation graph. A deletion is converted into a path that starts at the most 1

Mbp before one breakend of the deletion, traverses to the breakend, jumps to the other breakend, and

proceeds for a certain length (<1 Mbp). Note that the sequences flanking the deletion are added to

indicate the edge representing the deletion because edges are implicitly represented in

SequenceTubeMap. Insertions, inversions, and duplications are similarly represented by paths with

flanking sequences.

Visualization Examples

Revealing a large SV: A large inversion and a subsequent short deletion

We show an example of revealing a complex SV, where a large inversion and two flanking deletions to the reference genome are identified as two SVs, each of which connects two different points on a chromosome (i.e., INV or BND record in VCF). Previous studies involving the use of whole genome sequencing or RNA-seq by using Illumina HiSeq or Nanopore MinION, identified the CCDC6-RET fusion gene in LC-2/ad (Suzuki et al. 2014, 2015, 2017; Sereewattanawoot et al. 2018). However, those studies focused only on the region around the CCDC6-RET fusion point, and the entire picture, including the other end of the inversion, was unclear. To address this issue, we explored the wider region around CCDC6-RET by using MoMI-G.

First, we sequenced the genome of LC-2/ad by using Oxford Nanopore MinION R9.5 pore chemistry and merged reads with those from a previous study (accession No. DRX143541-DRX143544) (Sereewattanawoot et al. 2018). We generated 3.5 M reads to 12.8× coverage in total, and then aligned them with GRCh38. The average length of the aligned reads was 16 kb (Supplemental Table 2). We detected 11,316 SVs in the VCF format, including the previously known CCDC6-RET fusion gene, on the nuclear DNA of LC-2/ad cell line (Supplemental Table 3). See the method section for details.

The distance between RET (chr10: 43,075,069–43,132,349) and CCDC6 (chr10: 59,786,748–59,908,656) is about 17 Mbp in GRCh38. We confirmed that a CCDC6-RET fusion gene exists in LC-2/ad (Fig. 2A). This fusion gene is presumably caused by an inversion, although only one end of the inversion was found. We found an unknown novel adjacency that well explains the other end of the inversion (Fig. 2B, Supplemental Table 4). MoMI-G was able to display the relationships between the two breakends of the inversion, enabling users to understand large SVs. We explored the read alignments around the fusion and found that the fusion was heterozygous (Fig. 2C). MoMI-G is

the first stand-alone graph genome browser that can display long-read alignments over branching

sequences that represent a heterozygous SV.

Further, we found that the large inversion was flanked by two small deletions. These

deletions are explained by a single deletion event following the large inversion event (Fig. 2D). The

loss of the RET-CCDC6 fusion gene corresponds to the two small deletions on GRCh38. A simple

explanation is that a deletion occurred after the inversion event, but not vice versa, in favor of the

smaller number of mutation events.

Next, we attempted to estimate the breakpoints of the large inversion before the deletion

occurred. There were two possible scenarios for the positions of the two breakends of the large

inversion. The first is that RET-CCDC6 and CCDC6-RET were generated by a large inversion, and

then RET-CCDC6 was lost. The second is that CCDC6 was first broken by a large inversion, and a

subsequent small deletion led to CCDC6-RET. Previous studies support the former scenario. First, the

RET gene often tends to be disrupted in thyroid cancer by paracentric inversion of the long arm of

chromosome 10, or by chromosomal fusion (Santoro and Carlomagno 2013). Second, in a previous

study, two clinical samples had both RET-CCDC6 and CCDC6-RET in the genome (Mizukami et al.

2014). Both studies suggested that an inversion disrupted both CCDC6 and RET, and then a small

deletion disrupted RET-CCDC6. We could never recognize these two deletions flanking the large

inversion without simultaneously observing both the inversion records in VCF.

Nested SVs with alignment coverage

Visualizing nested SVs is necessary for evaluating the output of SV callers. However, most existing

genome browsers cannot visualize nested SVs as well as the relationships between them. Genome

browsers, including IGV, collapse SVs into intervals between breakpoints, and thus the topological

relationships between nested SVs are not shown. MoMI-G can visualize nested SVs as a variation

graph (Fig. 3).

Visualizing nested SVs in a pseudodiploid genome

We show an example of nested SVs in a pseudodiploid genome visualized using MoMI-G. We

downloaded a CHM1 genome with an SV list previously generated in a whole-genome resequencing

study by using PacBio sequencers from human hydatidiform (Chaisson et al. 2015). The SV list

includes insertions, deletions, and inversions for GRCh37/hg19. We converted the BED file of the

SV list of CHM1 to a VCF file, and then filtered out deletions of less than 1,000 bp for focusing on

medium to large SVs. We found nested SVs for which existing genome browsers do not intuitively

show the relationships between them (Fig. 4). This example indicates that four insertions and

deletions occur in the large inversion.

A.

B.

C.

D.

Figure 2. Example of CCDC6-RET

(A) CCDC6-RET shown in MoMI-G (compressed view). The thickest black line is chromosome 10 (reference genome). Note that the two distinct intervals of chromosome 10 are shown, which correspond to RET (left interval) and CCDC6 (right interval) genes,. The blue line represents an inversion identified by Sniffles, showing the CCDC6-RET fusion event. The other lines are gene annotations in hg38; the orange, red, purple lines indicate two isoforms of RET, and the brown line is CCDC6. (B) CCDC6-RET with read alignments shown as grey lines. Further, some alignments do not support the inversion, suggesting that CCDC6-RET is heterozygous. (C) The entire picture of the inversion that caused CCDC6-RET. This inversion is too large to span by a single read; thus, it was identified as two independent fusion events at both the ends of the inversion, which would be difficult to understand if the two fusion events are visualized separately. The red line is a translocation that was not analyzed in this study. (D) Putative evolution process of LC-2/ad at the CCDC6-RET site. First, a long inversion generated two fusion genes, CCDC6-RET and RET-CCDC6. Second, a large deletion caused the loss of RET-CCDC6.

Figure 3. Nested SVs called by Sniffles in LC-2/ad

The thin black lines are repeat annotations. The brown and purple lines are gene annotations. The red

and orange lines are an end of an inversion called by Sniffles. There are two possibilities for the

genome structure: one is that MUC3A and its flanking region are a duplication, and the internal region

of MUC12 is an inverted duplication. The other is that MUC3A and its flanking region are an inverted

duplication, and the internal region of MUC12 is a duplication. Several read alignments support the

former interpretation. Although SVs called from the Illumina reads did not include any of the SVs

shown here, the alignment coverage by the Illumina reads is consistent with both duplications. Note

that the y-axis of the blue thin line on the chromosome showing the alignment coverage is logarithmic.

Figure 4. Nested SVs in CHM1

The black line represents a part of chromosome 5, where a large inversion is shown as the brown line.

The other lines are smaller SVs included in the large inversion. Because CHM1 is a pseudodiploid

genome, all the SVs shown in this figure must be on the same haplotype, although MoMI-G tools

assume diploid (polyploid) genomes and show the inner SVs as heterozygous SVs.

User-interface Design

The optimal way of visualizing SVs might vary. To rapidly explore the distribution of SVs in a genome,

users might wish to use Circos-like plots. Other users might intend to focus on local graph structures

of SVs that might contain a few genes. In another scenario, a user might want to explore individual

nucleotides. To address this issue, MoMI-G provides a customizable view in which users can place

any combination of view modules. Further, preset view layouts are available for users' convenience.

Enabling easy manual inspection of detected SVs

Manual inspection, which includes determining if an SV is heterozygous or homozygous, confirming what part of a gene is affected by that SV, and determining the reason why an SV is called based on read alignments, is an important part for validating called SVs. As variants called by SV callers increase, the burden of manual inspection also increases, underscoring the importance of visualization both to inspect individual SV calls for filtering out false positives and to ensure that a filtered set of SVs is of high confidence (Munro et al. 2017; Wöste and Dugas 2018). MoMI-G help with the efficient inspection of SVs by using (1) Feature Table, which is an SV list; (2) Interval Card Deck, which is genomic coordinate stacks; and (3) shortcut keys. The usage is as follows: (1) one can filter SVs using Feature Table, after which SVs are selected, and then (2) the listed variants are stacked on Interval Card Deck at the bottom of the window. In Interval Card Deck, intervals are displayed as cards, and the interval of the top (leftmost) card of the deck is shown on SequenceTubeMap. Each card can be dragged, and the order of cards can be changed. If one double-clicks on a card, the card moves to the top of the deck. A tag can be added for a card for later reference. Further, a card can be locked to avoid unintended modification or disposal, and the gene name can be input with autocompletion for specifying the interval of a card.

When the interval to view is changed, only a part of the view that needs an update is re-rendered, whereas most genome browsers working on web interface require rendering the entire view. Interval Card Deck enables the rapid assessment of hundreds of intervals. Moreover, deciding whether an SV should be discarded or held becomes easier with shortcut keys. After all SVs are inspected, a set of SVs held on the Interval Card Deck is obtained, which might be a set of interesting SVs or a set of manually validated SVs. MoMI-G enables the rapid inspection of hundreds of SVs, providing a tool for validating hundreds of SVs or for selecting interesting SVs.

Input requirements

MoMI-G inputs an XG format as a variation graph. Users can specify a GAM file with an index that

contains read alignment. They can convert a BAM file into GAM by using MoMI-G tools, or can

generate the GAM file on their own. When a BED file of genes is provided, users can specify a

genomic interval by gene name. A configuration file is written in YAML. MoMI-G also accepts bigBed

and bigWig formats (Kent et al. 2010) for visualizing annotations (e.g., repeats, genes, alignment depth,

and GC content) on the reference genome. The bigBed and bigwig need to be extended for graph

genomes in the future. The list of formats that are accepted by MoMI-G is shown in Table 1.

Table 1. MoMI-G data files

File type	Extension	Description
A succinct index of variation graphs	.xg	Variation graphs displayed in MoMI-G.
Graphical alignment/map	.gam	Read alignment. (optional)
Comma-separated values	.csv	SV list for chromosome-scale view (optional)
Browser extensible data	.bed	Used for converting gene names to genomic intervals. Also used for autocompletion of gene names. (optional)
Compressed binary indexed BED	.bb	Annotations. (optional)
Compressed binary indexed wiggle	.bw	Annotations. (optional)

DISCUSSION

We developed a genome graph browser, MoMI-G, that visualizes SVs on a variation graph. Existing

visualization tools for SVs show either one SV at a time, or all SVs together; the former does not allow

the understanding of the relationships between SVs, whereas the latter is useless when the target

genome is very large and the whole variation graphs are too complicated to view in a single screen

(i.e., the hairball problem). MoMI-G allows viewing only a part of the genome, which resolves the

hairball problem, while providing an intuitive view for multiple SVs, including large and nested SVs.

Further, MoMI-G enables the manual inspection of complex SVs by providing integrated multiple

view modules; users can filter SVs, validate them by using read alignments, and interpret them by

using genomic annotations.

We used vg as a server-side library and SequenceTubeMap as a client-side library for

subgraph retrieving and visualization for genome graphs because, to our knowledge, these are the only

combinations that are publicly available. We found that significant amount of engineering efforts are

required for an even better user experience. For example, vg is a standalone command line application;

therefore, it does not allow to store succinct index on memory; every time only a part of the genome

is retrieved, the entire index of several gigabytes is loaded, which is unnecessary overhead.

SequenceTubeMap displays inversions and duplications as loops; however, we found that new users

occasionally find it difficult to recognize the connections between nodes. Visualizing SVs is still an

open problem.

The currently available tools and formats for SV analysis have many problems. First,

different SV callers output different VCF records even for the same SV. For example, depending on

SV callers, an inversion with both boundaries identified at a base pair level is represented by one of

the following: (1) a single inversion record, (2) two inversion records at both ends, (3) two breakend

records at both ends, or (4) four breakend records at both ends (a variant of (3), but the records are

duplicated for both the strands). Thus, developing a universal tool for variant graph construction is

difficult. Second, certain types of nested SVs such as an insertion within an insertion are impossible

to represent in a VCF file without tricks, although variant graphs can easily handle these SVs.

Therefore, generating a variation graph from a VCF file including SVs is not ideal. We need an SV

caller that directly outputs variation graphs.

Fostering the ecosystem around variation graphs is important for delivering their benefits to

end users, as noted in the ecosystem around the SAM/BAM formats that spurred development of

production-ready tools for end users. MoMI-G is the first step toward such a goal because the

availability of tools ranging from upstream analysis such as read alignment to visualization is critical

for the entire ecosystem.

This is the one million genome era that requires rapid and memory-sufficient data structure

to allow alignments and store haplotype information. Because most parts of the genome are shared

between individuals, we need to focus on differences for reducing computation time and resources.

Therefore, genome graph is considered promising, especially for human variation analysis. Moreover,

new visualization methods as well as genome analysis methods are required. Genome graph browsers

should be able to handle even thousands of genomes in the near future. MoMI-G is a step forward for

visualizing genome graphs and could allow the development of new algorithms on genome graphs.

MATERIAL and METHODS

Datasets

High-molecular-weight (HMW) gDNA was extracted from lung cancer cell line, LC-2/ad by using

Smart DNA prep(a) kit (Analykjena). WGS data were produced from MinION 1D sequencing (SQK-

LSK108), MinION $1D^2$ sequencing (SQK-LSK308), and MinION Rapid sequencing (SQK-

RAD003). For MinION 1D sequencing, 4 µg HMW gDNA was quantified using Tape Station. DNA

repair was performed using NEBNext FFPE DNA Repair Mix (M6630, NEB). End-prep was

performed using NEBNext Ultra II End Repair/dA-Tailing Module (E7546L, NEB). Adapter ligation

was performed using NEBNext Blunt/TA Ligase Master Mix (M0367L, NEB) and Ligation

Sequencing Kit 1D (SQK-LSK108, Oxford Nanopore Technologies). Libraries were sequenced for 48

h by using MinION (R9.5 chemistry, Oxford Nanopore Technologies). For MinION 1D^2 sequencing,

the protocol was the same as that for 1D excluding adapter ligation by using Ligation Sequencing Kit

1D^2 (SQK-LSK308, Oxford Nanopore Technologies). The library for MinION Rapid sequencing

was prepared according to Sequencing Kit Rapid (SQK-RAD003, Oxford Nanopore Technologies).

Nanopore data alignment

Nanopore WGS data were aligned against the GRCh38 human reference genome by using NGM-LR

with "-x ont" option (version 0.2.6) for calling SVs by using Sniffles version 1.0.7 (Sedlazeck et al.

2018b). MinION 1D^2 sequencing can produce a 1D^2 read, which integrates the information of a

read and its complementary read into one read. MinION 1D^2 sequencing produces two types of fastq

files, 1D and 1D^2; there was some redundancy between 1D and 1D^2 reads. Therefore, redundant

1D reads were removed, and only 1D^2 reads were used. Moreover, some redundant 1D^2 reads were

found. These reads were removed from 1D^2 files and used as 1D reads. The percentage of the primary

aligned reads was 54.7% (Supplemental Table 2). This is because we did not filter out reads excluding

1D-fail reads of Rapid sequencing for alignment.

SV calling

Sniffles (version 1.0.7) with a parameter "-s 5" was used to call SVs. The minimum number of

supporting reads was determined such that we could detect the known large deletion of CDKN2A

(Suzuki et al. 2014), but alignment bias for a reference genome reduces the call rate of insertions

compared to that of deletions (Nattestad et al. 2018; Chaisson et al. 2015). We detected 11,316 records

as a VCF file of SVs, including CCDC6-RET, on the nuclear DNA of LC-2/ad cell line (Supplemental

Table 3). Illumina HiSeq 2000 Paired-end WGS data (DDBJ accession number, DRX015205) aligned

against GRCh38 by using bwa (version 7.15) (Li and Durbin 2009) were used for calling SVs by using

Lumpy (version 0.2.13) (Layer et al. 2014), delly (version 0.7.7) (Rausch et al. 2012), and manta

(version 1.0.3) (Chen et al. 2016). The results of these SV callers are listed in Supplemental Table 5.

The four lists of SV candidates detected using Sniffles, Lumpy, delly, and manta were merged using

SURVIVOR (version 1.0.0) (Jeffares et al. 2017) with "5 sv_lists 1000 1 1 0 0" option for clustering

SV candidates (Supplemental Fig. 3). Further, we filtered the merged candidates based on the

following three criteria: (1) Remove SVs of 0 bp to 1 kbp in length to focus on large SVs, (2) Remove

all insertions and non-canonical SV types: INVDUP, DEL/INV, and DUP/INS (technically

unnecessary, but we aimed at cross-validating SV candidates from Illumina reads with which

insertions and non-canonical SV types are hard to call), and (3) Remove SVs overlapping with the

intervals   of   the   10X   default   blacklist

(https://github.com/10XGenomics/supernova/blob/master/tenkit/lib/python/tenkit/sv_data/10X_GRC

h38_no_alt_decoy/default_sv_blacklist.bed) for reducing false positives. After filtering, we obtained

1,790 SV records.

Constructing a variation graph

We constructed a variation graph, including a reference genome (GRCh38) and an individual genome

(either LC-2/ad or CHM1). We developed scripts that we call MoMI-G tools. MoMI-G tools follow

the procedure in SplitThreader Graph (Nattestad et al. 2016a).

1.   Extract a breakpoint list from a VCF file generated by Sniffles.

2. Construct an initial variation graph with each chromosome of the GRCh38 primary assembly as

a single node.

3. Split nodes every 1 Mbp due to the limitation in the implementation of vg used during the

development of MoMI-G; otherwise, vg aborted with an error. The latest version of vg does not

have this limitation.

4. For each breakpoint in the breakpoint list, split the node of the graph that contains the breakpoint

into two nodes at the breakpoint.

5. Create paths that represent the chromosomes in the reference genome.

6. Create paths that represent SVs, each of which corresponds to one record in the input VCF file.

Further, add a node to the graph when the type of an SV is an insertion.

The representation of SVs varies between SV callers: the same SV can be described in different ways

in the current VCF format. Although vg has a "construct" subcommand that constructs a variation

graph from a pair of a reference genome and a VCF file, "vg construct" is incompatible with the output

of SV callers we know of for the following reason. For example, an INV record in VCF means either

a single inversion (both ends included) or only one end of the inversion, depending on the

implementation of SV callers. We wrote custom scripts, MoMI-G tools, for Sniffles.

In general, to display read alignments, we recommend aligning against a variation graph by

directly using "vg map" instead of converting read alignments against the linear reference genomes

into the GAM format. Nevertheless, we intended to inspect the results of Sniffles; therefore, we wrote

a custom script to convert alignments against the linear reference (BAM file) into a GAM file by using

"vg annotate," during which CIGAR is lost; "vg annotate" was originally designed for placing

annotations in BED/GFF files on paths on variation graphs, and not for alignments. One possible

solution to this issue is making SV callers graph-aware.

Inspection of SV candidates

We modified and integrated SequenceTubeMap into MoMI-G so that it can visualize a variation graph

converted from SVs for showing the difference between a reference genome and an individual genome.

The modifications made to SequenceTubeMap are shown in Supplemental Table 6. One can click on

the download button for downloading an SVG image generated by SequenceTubeMap so that a vector

image can be used for publishing.

Visualizing annotations

Ideally, MoMI-G provides annotations on variation graphs. However, annotations available in public

databases are for the linear reference genome. MoMI-G can display annotations in bigWig/bigBed

formats. In particular, for human reference genomes, GRCh19/hg37 and GRCh38/hg38, MoMI-G

provides an interface for retrieving Ensembl gene annotations from the Ensembl SPARQL endpoint

(Jupp et al. 2014) via SPARQList REST API (https://github.com/dbcls/sparqlist). The orientation of

genes is shown in the legend of SequenceTubeMap. Further, if one clicks on a gene name, the website

of the gene information in TogoGenome (Katayama et al. 2019) opens.

Miscellaneous modules

Threshold Filter: Threshold Filter has two use cases. First, one can toggle checkboxes to select whether

to show inter-chromosomal SVs and/or intra-chromosomal SVs. Second, one can filter SVs by using

a slider based on the custom priority (possibly given by SV callers) of each SV.

Annotation Table: Annotation table shows all annotations that are displayed on the SequenceTubeMap.

Moreover, annotations can be downloaded as a BED file.

Linear Genome Browser: To provide a compatible view of a selected genomic region, we integrated

Pileup.js (Vanderkam et al. 2016) into MoMI-G.

Backend server

The MoMI-G backend server caches subgraphs once a client requests a genomic interval on a path. It

then retrieves annotations from bigWig and bigBed with a range query and provides JSON API with

which the client can make queries.

DATA ACCESS

Newly obtained long-read sequencing data of LC-2/ad were deposited in the DDBJ with accession

numbers DRA007941 (DRX156303-DRX156310). Datasets included in this article are also provided

in the database, DBTSS/DBKERO (Suzuki et al. 2018). The source code of MoMI-G is available at

https://github.com/MoMI-G/MoMI-G/ under the MIT license. Further, we have included an example

dataset and annotations as a Docker image.

ACKNOWLEDGMENTS

We thank all testers who provided testing and feedbacks for MoMI-G. We also thank Kazuyuki Shudo

at the Tokyo Institute of Technology and Toshiaki Katayama at the Database Center for Life Science

(DBCLS) of Research Organization of Information and Systems (ROIS), Japan, for their useful and

insightful discussions, Sarun Sereewattanawoot at the University of Tokyo for initial contributions to

Illumina read alignment. This work was supported in part by Information-technology Promotion

Agency, Japan (IPA) and Exploratory IT Human Resources Project (The MITOU Program) in the

fiscal year 2017 and in part by JSPS KAKENHI (Grant Number, 16H06279).

AUTHOR CONTRIBUTIONS

All authors were involved in study design; TY wrote all codes of MoMI-G; Y. Sakamoto preformed MinION sequencing and SV analysis on LC-2/ad; TY, Y. Sakamoto, and MK drafted the manuscript; MS and Y. Suzuki supervised the sequencing analysis; and MK supervised the study. All authors read and approved the final manuscript.

DISCLOSURE DECLARATION

The authors declare that there is no competing financial interest.

REFERENCES

Ahdesmäki MJ, Chapman BA, Cingolani P, Hofmann O, Sidoruk A, Lai Z, Zakharov G, Rodichenko M, Alperovich M, Jenkins D, et al. 2017. Prioritisation of structural variant calls in cancer genomes. *PeerJ* **5**: e3166.

Belyeu JR, Nicholas TJ, Pedersen BS, Sasani TA, Havrilla JM, Kravitz SN, Conway ME, Lohman BK, Quinlan AR, Layer RM. 2018. SV-plaudit: A cloud-based framework for manually curating thousands of structural variants. *Gigascience* **7**: 265058.

Bressler R, Lin J, Eakin A, Robinson T, Kreisberg R, Rovira H, Knijnenburg T, Boyle J, Shmulevich I. 2012. Fastbreak: A tool for analysis and visualization of structural variations in genomic data. *EURASIP J Bioinform Syst Biol* **2012**: 15.

Buels R, Yao E, Diesh CM, Hayes RD, Munoz-Torres M, Helt G, Goodstein DM, Elsik CG, Lewis SE, Stein L, et al. 2016. JBrowse: A dynamic web platform for genome visualization and analysis. *Genome Biol* **17**: 1–12.

Chaisson MJP, Huddleston J, Dennis MY, Sudmant PH, Malig M, Hormozdiari F,

Antonacci F, Surti U, Sandstrom R, Boitano M, et al. 2015. Resolving the complexity

of the human genome using single-molecule sequencing. *Nature* **517**: 608–611.

Chen X, Schulz-Trieglaff O, Shaw R, Barnes B, Schlesinger F, Källberg M, Cox AJ,

Kruglyak S, Saunders CT. 2016. Manta: Rapid detection of structural variants and

indels for germline and cancer sequencing applications. *Bioinformatics* **32**: 1220–1222.

Collins RL, Brand H, Redin CE, Hanscom C, Antolik C, Stone MR, Glessner JT, Mason T,

Pregno G, Dorrani N, et al. 2017. Defining the diverse spectrum of inversions, complex

structural variation, and chromothripsis in the morbid human genome. *Genome Biol*

18: 36.

Colmsee C, Beier S, Himmelbach A, Schmutzer T, Stein N, Scholz U, Mascher M. 2015.

BARLEX—the Barley Draft Genome Explorer. *Mol Plant* **8**: 964–966.

Gansner ER, North SC. 1999. An open graph visualization system and its applications.

Softw—Pract Exp **30**: 1203–1233.

Garrison E, Sirén J, Novak AM, Hickey G, Eizenga JM, Dawson ET, Jones W, Garg S,

Markello C, Lin MF, et al. 2018. Variation graph toolkit improves read mapping by

representing genetic variation in the reference. *Nat Biotechnol* **36**: 875–879.

Guan P, Sung W-K. 2016. Structural variation detection using next-generation sequencing

data. *Methods* **102**: 36–49.

Halper-Stromberg E, Steranka J, Burns KH, Sabunciyan S, Irizarry RA. 2014.

Visualization and probability-based scoring of structural variants within repetitive

sequences. *Bioinformatics* **30**: 1514–1521.

Herbig A, Jäger G, Battke F, Nieselt K. 2012. GenomeRing: Alignment visualization based

on SuperGenome coordinates. *Bioinformatics* **28**: 7–15.

Hiltemann S, McClellan EA, Van Nijnatten J, Horsman S, Palli I, Alves IT, Hartjes T,

Trapman J, Van Der Spek P, Jenster G, et al. 2013. iFUSE: Integrated fusion gene

explorer. *Bioinformatics* **29**: 1700–1701.

Jeffares DC, Jolly C, Hoti M, Speed D, Shaw L, Rallis C, Balloux F, Dessimoz C, Bähler J,

Sedlazeck FJ. 2017. Transient structural variations have strong effects on

quantitative traits and reproductive isolation in fission yeast. *Nat Commun* **8**: 1–11.

Jupp S, Malone J, Bolleman J, Brandizi M, Davies M, Garcia L, Gaulton A, Gehant S,

Laibe C, Redaschi N, et al. 2014. The EBI RDF platform: Linked open data for the life

sciences. *Bioinformatics* **30**: 1338–1339.

Katainen R, Donner I, Cajuso T, Kaasinen E, Palin K, Mäkinen V, Aaltonen LA, Pitkänen

E. 2018. Discovery of potential causative mutations in human coding and noncoding

genome with the interactive software BasePlayer. *Nat Protoc* **13**: 2580–2600.

Katayama T, Kawashima S, Okamoto S, Moriya Y, Chiba H, Naito Y, Fujisawa T, Mori H,

Takagi T. 2019. TogoGenome/TogoStanza: modularized Semantic Web genome

database. *Database* **2019**: 1–11.

Kent WJ, Sugnet CW, Furey TS, Roskin KM, Pringle TH, Zahler AM, Haussler D. 2002.

The Human Genome Browser at UCSC. *Genome Res* **12**: 996–1006.

Kent WJ, Zweig AS, Barber G, Hinrichs AS, Karolchik D. 2010. BigWig and BigBed:

Enabling browsing of large distributed datasets. *Bioinformatics* **26**: 2204–2207.

Kim P-G, Cho H-G, Park K. 2008. A scaffold analysis tool using mate-pair information in

genome sequencing. *J Biomed Biotechnol* **2008**: 1–7.

Krzywinski M, Schein J, Birol I, Connors J, Gascoyne R, Horsman D, Jones SJ, Marra MA.

2009. Circos: An information aesthetic for comparative genomics. *Genome Res* **19**:

1639–1645.

Layer RM, Chiang C, Quinlan AR, Hall IM. 2014. LUMPY: a probabilistic framework for

structural variant discovery. *Genome Biol* **15**: R84.

Li H, Durbin R. 2009. Fast and accurate short read alignment with Burrows-Wheeler

transform. *Bioinformatics* **25**: 1754–1760.

Matsubara D, Kanai Y, Ishikawa S, Ohara S, Yoshimoto T, Sakatani T, Oguni S, Tamura

T, Kataoka H, Endo S, et al. 2012. Identification of CCDC6-RET fusion in the human

lung adenocarcinoma cell line, LC-2/ad. *J Thorac Oncol* **7**: 1872–1876.

Mertens F, Johansson B, Fioretos T, Mitelman F. 2015. The emerging complexity of gene

fusions in cancer. *Nat Rev Cancer* **15**: 371–381.

Mizukami T, Shiraishi K, Shimada Y, Ogiwara H, Tsuta K, Ichikawa H, Sakamoto H, Kato

M, Shibata T, Nakano T, et al. 2014. Molecular mechanisms underlying oncogenic

RET fusion in lung adenocarcinoma. *J Thorac Oncol* **9**: 622–630.

Munro JE, Dunwoodie SL, Giannoulatou E. 2017. SVPV: A structural variant prediction

viewer for paired-end sequencing datasets. *Bioinformatics* **33**: 2032–2033.

Murphy C, Elemento O. 2016. AGFusion: Annotate and visualize gene fusions. *bioRxiv* 1–4.

Naquin D, D'Aubenton-Carafa Y, Thermes C, Silvain M. 2014. CIRCUS: A package for

Circos display of structural genome variations from paired-end and mate-pair

sequencing data. *BMC Bioinformatics* **15**: 198.

Nattestad M, Alford MC, Sedlazeck FJ, Schatz MC. 2016a. SplitThreader：Exploration and

analysis of rearrangements in cancer genomes. *bioRxiv* 1–8.

Nattestad M, Chin C-S, Schatz MC. 2016b. Ribbon: Visualizing complex genome alignments

and structural variation. *bioRxiv* **0344**: 82123.

Nattestad M, Goodwin S, Ng K, Baslan T, Sedlazeck FJ, Rescheneder P, Garvin T, Fang H,

Gurtowski J, Hutton E, et al. 2018. Complex rearrangements and oncogene

amplifications revealed by long-read DNA and RNA sequencing of a breast cancer cell

line. *Genome Res* **28**: 1126–1135.

Nielsen CB, Jackman SD, Birol I, Jones SJM. 2009. ABySS-explorer: Visualizing genome

sequence assemblies. *IEEE Trans Vis Comput Graph* **15**: 881–888.

O'Brien T, Ritz A, Raphael B, Laidlaw D. 2010. Gremlin: An interactive visualization model

for analyzing genomic rearrangements. *IEEE Trans Vis Comput Graph* **16**: 918–926.

Paten B, Eizenga JM, Rosen YM, Novak AM, Garrison E, Hickey G. 2018. Superbubbles,

Ultrabubbles, and Cacti. *J Comput Biol* **25**: 649–663.

Paten B, Novak AM, Eizenga JM, Garrison E. 2017. Genome graphs and the evolution of

genome inference. *Genome Res* **27**: 665–676.

Quinlan AR, Hall IM. 2012. Characterizing complex structural variation in germline and

somatic genomes. *Trends Genet* **28**: 43–53.

Rausch T, Zichner T, Schlattl A, Stütz AM, Benes V, Korbel JO. 2012. DELLY: Structural

variant discovery by integrated paired-end and split-read analysis. *Bioinformatics* **28**:

333–339.

Reisle C, Mungall KL, Choo C, Paulino D, Bleile DW, Muhammadzadeh A, Mungall AJ,

Moore RA, Shlafman I, Coope R, et al. 2018. MAVIS: Merging, Annotation, Validation,

and Illustration of Structural variants. *Bioinformatics* 1–3.

Revanna K V, Munro D, Gao A, Chiu C-C, Pathak A, Dong Q, Frazer K, Elnitski L, Church

D, Dubchak I, et al. 2012. A web-based multi-genome synteny viewer for customized

data. *BMC Bioinformatics* **13**: 190.

Riba-grognuz O, Keller L, Falquet L, Xenarios I, Wurm Y. 2011. Visualization and quality

assessment of de novo genome assemblies. *Bioinformatics* **27**: 3425–3426.

Sante T, Vergult S, Volders PJ, Kloosterman WP, Trooskens G, De Preter K, Dheedene A,

Speleman F, De Meyer T, Menten B. 2014. ViVar: A comprehensive platform for the

analysis and visualization of structural genomic variation. *PLoS One* **9**: 1–12.

Santoro M, Carlomagno F. 2013. Central role of RET in thyroid cancer. *Cold Spring Harb*

Perspect Biol **5**: 1–17.

Sedlazeck FJ, Lee H, Darby CA, Schatz MC. 2018a. Piercing the dark matter:

Bioinformatics of long-range sequencing and mapping. *Nat Rev Genet* **19**: 329–346.

Sedlazeck FJ, Rescheneder P, Smolka M, Fang H, Nattestad M, von Haeseler A, Schatz

MC. 2018b. Accurate detection of complex structural variations using single-molecule

sequencing. *Nat Methods* **15**: 461–468.

Sereewattanawoot S, Suzuki A, Seki M, Sakamoto Y, Kohno T, Sugano S, Tsuchihara K,

Suzuki Y. 2018. Identification of potential regulatory mutations using multi-omics

analysis and haplotyping of lung adenocarcinoma cell lines. *Sci Rep* **8**: 4926.

Spies N, Zook JM, Salit M, Sidow A. 2015. Svviz: A read viewer for validating structural

variants. *Bioinformatics* **31**: 3994–3996.

Stankiewicz P, Lupski JR. 2010. Structural variation in the human genome and its role in

disease. *Annu Rev Med* **61**: 437–455.

Suzuki A, Kawano S, Mitsuyama T, Suyama M, Kanai Y, Shirahige K, Sasaki H, Tokunaga

K, Tsuchihara K, Sugano S, et al. 2018. DBTSS/DBKERO for integrated analysis of

transcriptional regulation. *Nucleic Acids Res* **46**: D229–D238.

Suzuki A, Makinoshima H, Wakaguri H, Esumi H, Sugano S, Kohno T, Tsuchihara K,

Suzuki Y. 2014. Aberrant transcriptional regulations in cancers: Genome,

transcriptome and epigenome analysis of lung adenocarcinoma cell lines. *Nucleic*

Acids Res **42**: 13557–13572.

Suzuki A, Matsushima K, Makinoshima H, Sugano S, Kohno T, Tsuchihara K, Suzuki Y.

2015. Single-cell analysis of lung adenocarcinoma cell lines reveals diverse expression

patterns of individual cells invoked by a molecular target drug treatment. *Genome*

Biol **16**: 66.

Suzuki A, Suzuki M, Mizushima-Sugano J, Frith MC, Makałowski W, Kohno T, Sugano S,

Tsuchihara K, Suzuki Y. 2017. Sequencing and phasing cancer mutations in lung

cancers using a long-read portable sequencer. *DNA Res* **24**: 585–596.

Tang B, Wang Q, Yang M, Xie F, Zhu Y, Zhuo Y, Wang S, Gao H, Ding X, Zhang L, et al.

2013. ContigScape: A Cytoscape plugin facilitating microbial genome gap closing.

BMC Genomics **14**: 1–12.

Thorvaldsdóttir H, Robinson JT, Mesirov JP. 2013. Integrative Genomics Viewer (IGV):

High-performance genomics data visualization and exploration. *Brief Bioinform* **14**:

178–192.

Vanderkam D, Aksoy BA, Hodes I, Perrone J, Hammerbacher J. 2016. Pileup.js: A

JavaScript library for interactive and in-browser visualization of genomic data.

Bioinformatics **32**: 2378–2379.

Weischenfeldt J, Symmons O, Spitz F, Korbel JO. 2013. Phenotypic impact of genomic

structural variation: Insights from and for human disease. *Nat Rev Genet* **14**: 125–

138.

Wick RR, Schultz MB, Zobel J, Holt KE. 2015. Bandage: Interactive visualization of de novo

genome assemblies. *Bioinformatics* **31**: 3350–3352.

Wöste M, Dugas M. 2018. VIPER: A web application for rapid expert review of variant calls.

Bioinformatics **34**: 1928–1929.

Wyczalkowski MA, Wylie KM, Cao S, Mclellan MD, Flynn J, Huang M, Ye K, Fan X, Chen

K, Wendl MC, et al. 2017. BreakPoint Surveyor: A pipeline for structural variant

visualization. *Bioinformatics* **33**: 3121–3122.

SUPPLEMENTAL FIGURES

Supplemental Figure 1. A representative screenshot of MoMI-G with all view modules.

A

B

C

Supplemental Figure 2. Examples of a deletion, balanced inversion, and duplication

(A) Deletion: The orange line indicating a deletion starts before one breakend of the deletion,

passes through the middle node that indicates the deleted sequence, and then proceeds for the

sequence flanking the deletion.

(B) Balanced Inversion: The purple line indicating a balanced inversion includes flanking

sequences on both breakpoints of the inversion.

(C) Duplication: The blue line indicating a duplication passes through the node twice, suggesting

that the sequence of the node is duplicated. The line in the node might terminate if the node is

interrupted by other SVs.

Supplemental Figure 3. Merged SVs from four SV callers by using SURVIVOR

The green circle describes the count of SVs called by Illumina, whereas the red circle presents the

count called by MinION.

SUPPLEMENTAL TABLES

Supplemental Table 1. List of MoMI-G features

Module group	View module	Description
Chromosome-scale View	Circos Plot	Observe the distribution of SVs
	Feature Table	Select and filter SVs
	Threshold Filter	Filter SVs
	Interval Card Deck	Accumulate genomic intervals for inspection
Gene-scale View	SequenceTubeMap	Visualize a subgraph of a variation graph
	Interval Card Deck	Switch between the intervals
Nucleotide-scale View	Linear Browser	Visualize a linear genome with annotations
	Annotation Table	Show annotations
	SequenceTubeMap	Visualize nucleotides of a variation graph
	Interval Card Deck	Switch between the intervals

721 **Supplemental Table 2. Summary of the Oxford Nanopore sequencing data of LC-2/ad**

Number of reads	3,310,982
Coverage	12.8×
Percentage of aligned reads	57.9%
Average length of aligned reads	16,032.2 bp
Average identity of aligned reads	83.0%

723 **Supplemental Table 3. Called SVs in LC-2/ad nuclear DNA from Nanopore reads**

SV Types	Called SVs
DEL	6,366
DUP	323
INS	4,449
INV	99
INVDUP	1
TRA	79
DEL/INV	12
DUP/INS	3

725 **Supplemental Table 4. Breakends in the opposite end of the CCDC6-RET inversion**

Sequencer, aligner, and SV caller	Start	Stop
ONT MinION, NGM-LR + Sniffles	chr10: 42,849,939	chr10: 59,825,707
Illumina HiSeq 2000, BWA + manta	chr10: 42,849,938	chr10: 59,825,707
Illumina HiSeq 2000, BWA + delly	chr10:42,849,938	chr10:59,825,707
Illumina HiSeq 2000, BWA + lumpy	Not called	Not called

731 **Supplemental Table 5. Called SVs in LC-2/ad nuclear DNA from Illumina reads**

SV types	manta	delly	lumpy
BND	3,926	9,787	4,214
DEL	43,886	33,429	2,051
DUP	768	3,213	1,197
INS	29,216	2,212	-
INV	576	2,055	62

733 **Supplemental Table 6. The modifications made to the original SequenceTubeMap**

Original implementation	Modified implementation
Paths are displayed in the same order as they appear in the input.	A selected chromosome path is by default drawn as a straight horizontal line regardless of the path order in the input.
It was impossible to display genes and paths in different colors.	Genes, annotations, chromosomes, and variants can have different colors for easily distinguishing them.
The constant for the linear node width mode was too large for visualizing large SVs.	We implemented another mode suitable for visualizing large SVs.
No bigWig/bigBed support.	We added bigWig/bigBed support.
Non-consecutive genomic intervals are difficult to recognize.	We inserted a shaded gap between distant genomic intervals.