A Recurrent Neural Network Model for Flexible and Adaptive Decision Making based on Sequence Learning

Zhewei Zhang[1,2], Huzi Cheng[1], and Tianming Yang[1*]

[1] Institute of Neuroscience, Key Laboratory of Primate Neurobiology, CAS Center for Excellence in Brain Science and Intelligence Technology, Shanghai Institutes for Biological Sciences, Chinese Academy of Sciences

[2] University of Chinese Academy of Sciences, Beijing 100049, China

*Address correspondence to:

Tianming Yang (tyang@ion.ac.cn)

Institute of Neuroscience

320 Yue Yang Rd.

System Neuroscience Building, Room 302

Shanghai, China 200031

Phone: +86-21-54921737, Fax: +86-21-54921735

Abstract

The brain makes flexible and adaptive responses in the complicated and ever-changing environment for the organism's survival. To achieve this, the brain needs to choose appropriate actions flexibly in response to sensory inputs. Moreover, the brain also has to understand how its actions affect future sensory inputs and what reward outcomes should be expected, and adapts its behavior based on the actual outcomes. A modeling approach that takes into account of the combined contingencies between sensory inputs, actions, and reward outcomes may be the key to understanding the underlying neural computation. Here, we train a recurrent neural network model based on sequence learning to predict future events based on the past event sequences that combine sensory, action, and reward events. We use four exemplary tasks that have been used in previous animal and human experiments to study different aspects of decision making and learning. We first show that the model reproduces the animals' choice and reaction time pattern in a probabilistic reasoning task, and its units' activities mimics the classical findings of the ramping pattern of the parietal neurons that reflects the evidence accumulation process during decision making. We further demonstrate that the model carries out Bayesian inference and may support meta-cognition such as confidence with additional tasks. Finally, we show how the network model achieves adaptive behavior with an approach distinct from reinforcement learning. Our work pieces together many experimental findings in decision making and reinforcement learning and provides a unified framework for the flexible and adaptive behavior of the brain.

Introduction

Consider a scenario in which a cheetah sneaks up on a deer until it starts the final dash to catch it. Every move has to be calculated carefully based on the sensory inputs, for example, the distance to the deer and the surrounding environment, and the past experience, for example, the deer's speed. Furthermore, the cheetah should be able to predict how the deer would respond to its move to allow more timely adjustment of its actions. This is an example of a central function of the brain: to generate responses to maximize the gain based on a continuous stream of sensory inputs and movements that reflect a complicated and volatile world. The contingencies that the brains need to learn should take into account the sensory inputs, the organism's own actions, and the resulting reward outcomes, all strung together into a sequence.

A variety of theoretic models have been used to investigate certain components of this general contingency problem. For example, in the perceptual decision-making and sensory-motor transformation field, the research question often centers around how sensory information as evidence is integrated and leads to specific actions. Theoretical models such as the drift-diffusion model (Ratcliff, 1978; Stone, 1960) and attractor neural network models (X.-J. Wang, 2001; Wong & Wang, 2006) have gained a lot of success in both modeling the behavior and explaining the neuronal response patterns in the brain. Yet these studies often do not take into account the volatile nature of the environment. In contrast, the conditioning and learning field focus on the learning of the associations between reward or punishment outcomes and other events in a volatile environment. The reinforcement learning (RL) framework has become a standard approach to understand the behavior and the brain circuitry in this field (Dayan & Niv,

2008; Schultz, Dayan, & Montague, 1997; Sutton & Barto, 2012). In RL, state and action

values are updated when reward feedbacks differ from expectations. The framework

provides an explanation on how animals gradually learn the values associated with

stimuli and actions and select actions accordingly. Yet, RL does not usually deal with the

problem of inferring states based on noisy sensory inputs. It is inefficient for learning

complicated decision-making tasks, especially those with a large state space. More

problematic is that in most studies RL assumes that states are observable and task

structures are known, which is not true in the real world. Biologically realistic neural

network models of RL that acquires task structures through learning have been

proposed but they are limited to rather simple structures (J. X. Wang et al., 2018; Zhang,

Cheng, Lin, Nie, & Yang, 2018).

So far, there is a lack of a model general or flexible enough to cover different aspects of

decision making and learning. A more general framework is necessary for furthering

our understanding of the brain. Here, we propose a neural network model based on

sequence learning to model the flexible and adaptive behavior and to understand the

underlying neural mechanisms. The network takes inputs in the form of event

sequences and is trained to make predictions of future events with supervised learning.

Importantly, the input event sequences include not only the sensory events, but also the

action events and the reward outcome events, which allow the network to establish the

contingencies between all three types of events. The outputs of the network serve as a

prediction of future events and the network is trained to minimize the difference

between the predictions and the future input sequences. The predictions of action

events are used to generate the model's actual responses, which are assessed for the

network's behavior performance. The predictions of sensory and reward events are not

directly exhibited in behavior, but they are part of the learning and have important

implications in modeling the brain.

To demonstrate how the network model works, we choose four exemplary behavior

tasks that have been previously used in animal and human studies, each covering a

different aspect of decision making and learning. The network is not constructed for any

particular task. Instead, it learns the task structure and task logic through training. The

first task, a reaction time version of probabilistic reasoning task, is one of the most

complicated tasks in the literature that provide us both behavior and single unit

recording data to evaluate the model (Kira, Yang, & Shadlen, 2015; Yang & Shadlen,

2007). We use it to demonstrate the capability of the network to learn complex

contingencies between events in long sequences and the similarity of the units in the

network to the previous neurophysiological findings. We further use a multi-sensory

integration task to show how the network generalizes Bayesian inference across

different sensory modalities (Gu, Angelaki, & DeAngelis, 2008). The third task, a post-

decision wagering task, is chosen to show that the model can support meta-cognition

such as confidence (Kiani & Shadlen, 2009). Last but not least, the final task is adapted

from the two-step task, first described to illustrate model-based RL (Daw, Gershman,

Seymour, Dayan, & Dolan, 2011). The task requires the learning to be extended across

trials, which allows us to demonstrate how the network accounts for adaptive behavior

with a distinct approach from RL.

Together, our results show that a network model that is simply trained to make

predictions based on event sequences may account for a large body of experimental

findings from both the decision making and the reinforcement learning field. Not only

does the model reproduce the animals' and humans' behavior in previous studies, the

units in the network also show response patterns resembling those of the neurons in

the brain. The model makes testable hypotheses on the neuronal response patterns and

circuit structures in the brain and suggests novel interpretations for some of the

previous experimental work. These results suggest the potential of our model to be a

unified framework for decision making and learning that may reveal the computational

principle in the brain.

Results

Network

Our network model contains three layers: the input layer, the hidden layer based on

gated recurrent units (GRU), and the output layer (Fig 1a). The input layer contains

units that carry the information about the sensory, motor, and reward events on a

timeline. Each unit's activity can be a binary variable, representing the presence or the

absence of the corresponding event, or a continuous variable representing stimulus

strength. The input units are fully connected with the next layer. We use vector x_t of

length N_{IL} to describe the activities of the input layer units.

The hidden layer is the core of our model. It is adapted from the GRU network, which

has been shown to be suitable for learning sequences (Cho et al., 2014; Chung, Gulcehre,

Cho, & Bengio, 2014). There are N_h=128 units in the hidden layer. Each gated recurrent

unit's activity is a nonlinear combination of both the inputs and its activity at the

previous time step, which are regulated by an update gate and a reset gate. The

nonlinear reset gate has been shown to be critical for the network to learn long

contingencies across long temporal sequences (Greff, Srivastava, & Koutník, 2016). The

state vector h_t of length N_h describes the responses of these units at time t, which is

updated with the information from the input layer as follows:

$$z_t = \text{Sigmoid}(W_z x_t + U_z h_{t-1} + b_z), \tag{1}$$

$$r_t = \text{Sigmoid}(W_r x_t + U_r h_{t-1} + b_r), \tag{2}$$

$$s_t = (1 - z_t) \bullet h_{t-1} + z_t \bullet \tanh(W_h x_t + U_h (r_t \bullet h_{t-1}) + b_h), \tag{3}$$

$h_t = [s_t]_+,$ (4)

where z_t and r_t represent the update gate vector and the reset gate vector, respectively;

W_z, W_r and W_h are the input connection weight matrices for the update gates, the reset

gates, and the gated units; U_z, U_r and U_h are the recurrent connection weight matrices

for the update gates, the reset gates, and the gated units; b_z, b_r and b_h are the bias

vectors for the update gates, the reset gates, and the gated units; and $\bullet$ indicates the

element-wise multiplication. The rectified-linear function $[\bullet]_+$ keeps the responses h_t

non-negative. The initial value of the state vector h_t at the beginning of each trial is

reset to zero.

The hidden layer units project to the output layer with full connections. The output

layer is composed of an array of units that mirror the input layer units, representing the

network's predictions of the corresponding sensory events, action events and reward

events for the next time step. The activity of the output layer units o_t (a vector of length

N_{OL}) is:

$o_t = \text{Sigmoid}(W_o h_t),$ (5)

where W_o is the output connection weight matrix. The prediction y is a function of

response o_t:

$y_t = \begin{cases} 1 & o_t > 0.5 \\ 0 & o_t < 0.5 \end{cases}$ (6)

The network predicts the corresponding event would happen in the next time step

when y_t^i is 1. If y_t^i corresponds to an action, the probability of the action being carried

out at the next time step is a softmax function of o_t:

$$P\left(a_t = a_i \mid o_t^i\right) = exp\left(\beta * o_t^i\right)/\sum_{j=1} exp\left(\beta * o_t^j\right), \tag{7}$$

where β is the temperature. The chosen action is evaluated for the network's task

performance for testing purposes.

Fig 1a illustrates the network structure with the inputs and outputs corresponding to

the Task 1 that we discuss below. For the other tasks, it is only necessary to change

the input and output units to reflect the relevant events.

The goal of the training is for the network to learn to predict events and generate

sequences that lead to a reward. The loss function L is defined as the sum of mean

squared error between elements in the output o_t and actual event sequence e_{t+1} for all

time points t.

$$L = \left.\sum_{t=1}^{T-1} (o_t - e_{t+1})^2\right/ N_{OL} \tag{8}$$

where T is the length of each trial. The parameter vector θ (including W_*, U_* and b_*) of

the network is updated with the Adam (Kingma & Ba, 2014) and the gradient clipping is

applied to avoid exploding gradients as follows:

$$g_t = \frac{\partial L}{\partial \theta}\big|_{\theta = \theta_{t-1}} * min\left(1, \frac{0.25}{\left|\frac{\partial L}{\partial \theta}\big|_{\theta = \theta_{t-1}}\right|}\right) \tag{9}$$

Figure 1. **a**. The model diagram. The network has three layers: the input layer, the
gated recurrent unit layer, and the output layer. The input layer receives the input
sequences of sensory events, action events, and reward events. The GRU layer has
128 gated recurrent units. The output layer units mirror the input layer units and
represent the prediction of the future events. The diagram illustrates the particular
input and output units for the Task 1. **b**. Task 1: the reaction-time version of
probabilistic reasoning task. The subject fixates at a central point and views a
sequence of shapes to make a decision by moving the eyes toward one of the two
choice targets in the peripheral. Each shape confers information regarding to which
target will be rewarded. An optimal strategy is to integrate the information and
make a choice when the integrated information hits a bound. **c**. The sampling
distributions. Shapes are sampled from the sampling distribution associated with
the correct target in each trial.

Task 1: Probabilistic reasoning task

We train our model with a reaction-time version of the probabilistic reasoning task that

was used to study the neural mechanism of sequential decision making (Kira et al.,

2015). The task is illustrated in Fig 1b. In this task, a subject has to make decisions

between a pair of eye movement targets. Initially, the subject needs to fixate on a

central point on a computer screen. Then a stream of shapes appears sequentially near

the fixation point. There are totally 10 possible shapes. Each shape conveys information

on the correct answer. The subject needs to integrate information of the shapes to form

a decision and move the eyes to look at the choice target whenever ready.

The contingency between the shapes and the targets is described by two distributions.

Each target is associated with a distribution of the appearance probability of the shapes

in the sequence (Fig 1c). In each trial, the computer randomly picks the correct target.

Each shape in the sequence is independently sampled from the distribution associated

with the correct target. Because the likelihoods of observing a particular shape under

the two distributions are different, each shape provides information on which target is

correct. It has been shown that the sequential probability ratio test (SPRT) is an optimal

strategy to solve the task in the sense that it requires the least number of observations

to achieve a desired performance (Wald & Wolfowitz, 1948). In the SPRT, one needs to

accumulate the log likelihood ratio (logLR) associated with each piece of evidence,

which is the log ratio between the conditional probabilities of observing the evidence

given the two testing hypotheses. In our task, the logLRs associated with each shape

range from -0.9 to 0.9 (base 10). We define positive and negative logLRs as evidence

supporting the left and the right target, respectively.

The task has several attractive features for our modeling purposes. First of all, the task

features a sophisticate statistical structure containing the shapes, the choice, and the

reward. As the shapes appear one by one, an ideal observer not only gains information

on what would be the appropriate choice, but also can deduce how likely a particular

shape will appear next and how likely a reward can be expected. Second, this is a

reaction time task in which choices have to be made at appropriate time to achieve a

certain tradeoff between speed and accuracy. This allows us to demonstrate the

flexibility of our model for learning sequences of variable length. Last but not least, the

task is one of the most complicated tasks that have been used in animal studies with

both behavior and neural data available. We not only can compare the behavior

between the model and the animals, but also can look into the network and study the

network units' activities and compare them against the experimental findings.

The training dataset

We train the network with task event sequences created with simulated trials in which

choices are generated with a drift-diffusion model with collapsing bounds. In each trial,

a correct target is randomly determined, and the shapes are generated with its

associated distribution (Fig 1c). A choice is triggered when the accumulated logLR

reaches to either of the two opposite collapsing bounds. The bounds start at ±1.5 and

linearly collapse toward 0 at the rate of 0.1 per shape epoch. The left target is chosen if

the positive bound is reached, and the right target chosen if the negative bound is

reached. If the choice matches the pre-determined correct target, a reward is given, and

the corresponding sequence is included in the training dataset.

The results presented below are based on 20 simulation runs using a training set

generated with 7.5×10^5 simulated trial sequences.

<u>Behavior Performance</u>

After training, the network performs the task well. When the total logLR associated with

the shape sequence is positive, the network tends to choose the left target, and when

the total logLR is negative, it tends to choose the right target (Fig 2a). A logistic

regression reveals that the logLR assigned to each shape correlates well with its

leverage on the choice (Fig 2b). The mean reaction time, quantified as the number of

shapes that the model uses for decision, is 6.36±0.04 (mean±s.e.m.). Both the

distribution of the reaction time and the total logLR at the time of choice suggest that

the model behavior is consistent with the DDM with collapsing bounds (Fig 2c). We use

another logistic regression to examine the effects of shape order on the choice. The first

shapes in the sequence exert similar leverages on the choice to the rest of the shapes,

except for the last shape, suggesting all shapes except the last are used equally in

decision making (Fig 2d). The last shape's sign is almost always consistent with the

choice (> 99% of all trials). This is also consistent with the DDM, in which the last shape

brings the total logLR over the bound. Overall, the network performance resembles,

although understandably better than, the behavior of the macaque monkeys trained

with a very similar task (Kira et al., 2015).

Figure 2. **a**. The psychometric curve. The model more often chooses the target
supported by the accumulated evidence. The black curve is the fitting curve from the
logistic regression. **b.** The leverage of each shape on choice revealed by the logistic
regression is consistent with its assigned logLR. **c.** Reaction time**.** The bars show the
distribution of reaction time, quantified by the number of observed shapes (right y-
axis). Green and red indicate the left and right choices, respectively. The lines
indicate the mean total logLR (left y-axis) at the time of decision, grouped by
reaction time. Trials with only 1 shape or more than 16 shapes comprise less than
0.1% of the total trials and are excluded from the plot. **d**. The leverage of the first 3,
the second and third from the last, and the middle shapes on the choice. Only trials
with more than 6 shapes are included in the analysis. No significant differences are
found between any pair of the coefficients of shape regressors (two-tailed t test with
Bonferroni correction). The error bars in all panels indicate S.E. across runs. Some
error bars are smaller than the data points and not visible.

The good performance of the network is not because the trials sequences in the testing
dataset overlap with those in the training dataset significantly, which is not true
because the possible number of trial sequences in this task is astronomical and each
shape sequence in the training and testing dataset is randomly generated. The network

is able to generalize beyond the training dataset. With a training dataset that contains

only 1000 unique trial sequences, the network can still achieve a good performance

(Supplementary Figure 1). Therefore, the learning of the statistical structure of the task

is likely the reason for the model's performance.

Network analyses – Evidence and Choice encoding

Next, we examine how the evidence and the choice are encoded in the network. The

example unit in Fig 3a shows a classical ramping-up activity pattern that has been

reported in neurons from the prefrontal cortex (Kim & Shadlen, 1999), the parietal

cortex (Kira et al., 2015; Roitman & Shadlen, 2002; Yang & Shadlen, 2007), and the

striatum (Ding & Gold, 2010). Its activity increases when the total logLR grows to

support its preferred choice and decreases when the total logLR is against its preferred

choice. The responses converge around the time when its preferred choice is chosen.

The population analysis using all the units that are selective to the total logLR finds the

same pattern (Fig 3b).

In addition to the units that accumulate evidence and reflect the decision making

process, we also find units that show a ramping-up or ramping-down activity pattern

independent of the choice (Fig 3c). Their activities indicate the passage of time and may

be interpreted as an urgency signal. Neurons with a similar activity pattern have been

reported in the global pallidus (Thura & Cisek, 2017).

Figure 3. **a**. An example unit that prefers the left target. Its activity increases when the evidence supporting the left target grows and decreases when it drops. The unit's responses converge when the network chooses its preferred target. The trials are grouped into quartiles by the accumulated evidence in each epoch, which are indicated with color. The error bars indicate the S.E. across trials. **b**. Population responses of the units that are selective to the total logLR. The trials are grouped based on the accumulated evidence supporting each unit's preferred target in each epoch. The error bars in panels **b**, **c** and **d** indicate the S.E. across units. **c**. Urgency units. Their activities ramp up (upper panel) or down (lower panel) regardless of the choice. **d.** Network unit response variability. The neurons' response variability increases initially (blue curve) but decreases before the choice, more so when the preferred target is chosen (black) than when the non-preferred target is chosen (grey). Only the trials with more than five shapes are included in panel **a**, **b** and **d**.

We use a linear regression to quantify the selectivity of each units (see Methods) to three important parameters for this task: the accumulated evidence, quantified with the total logLR, the choice outcome, and the urgency. During the shape presentation period,

a large portion of units is found to encode the accumulated evidence (N = 63.00 ± 2.49),

the choice outcome (N = 50.60 ± 2.03) and the urgency (N= 86.50 ± 1.10).

Finally, we calculate the response variability of the units in the hidden layer to study the

dynamics of the population responses of the network (Fig 3d). This is analogous to the

variance CE that Churchland and colleagues studied previously in the LIP neurons

(Churchland et al., 2011). Our analyses are more straightforward as the units in our

model do not have intrinsic Poisson noise. The response variability here is simply

calculated as the standard deviation of the units' responses across trials. We find that

the response variability increases initially (linear regression, $k = 0.0088$, $p < 0.001$) as

more shapes are presented and the evidence is accumulated. However, when we align

the trials to the choice, a different pattern emerges. In the trials in which the preferred

target is chosen, the response variability decreases before the choice (linear regression,

$k = -0.0038$, $p < 0.001$; Spearman's rank correlation, $r = -0.045$, $p < 0.01$) and reaches

the minimum around the time of choice. In contrast, in the trials in which the non-

preferred target is chosen, the response variability is significantly higher and its

decrease is not significant until the last shape (linear regression, $k = -0.0017$, $p = 0.07$;

Spearman's rank correlation, $r = -0.017$, $p = 0.28$). The overall pattern is very similar to

that of the LIP neurons reported previously (Churchland et al., 2011).

<u>Network analyses – When and Which</u>

The balance between the speed and accuracy is an important aspect of decision making.

The control of the speed and accuracy balance has been suggested to be exerted

through the same neurons that accumulate evidence (Ding & Gold, 2012; Hanks, Kiani, &

Shadlen, 2014; Heitz & Schall, 2012) or a distinct populations of neurons that reflect

only the speed but not the choice (Thura & Cisek, 2017). We analyze the units' activities

and connectivities in the model to find out which is the case here in our model.

The network has three output units related to the choice. They include a unit for the

fixation (FP) and two units for the saccades toward the left (LT) and the right (RT)

target, respectively. We examine the connection weights between the hidden layer unit

and the output units to understand how hidden layer units drive the choices. For each

hidden layer unit, we estimate how it contributes to the outputs by defining two indices,

I_{when} and I_{which}:

380           $I_{when} = (w_{ho-LT}^{i} + w_{ho-RT}^{i})/2 - w_{ho-FP}^{i}$ (10)

381           $I_{which} = w_{ho-LT}^{i} - w_{ho-RT}^{i}$,   (11)

383   where w_{ho-LT}^{i}, w_{ho-RT}^{i} and w_{ho-FP}^{i} are the connection weights between the hidden layer

384   unit i and the output layer units LT, RT and FP, respectively. Units with large positive

385   I_{when} promote the saccades over fixation, regardless of the direction, thus affect the

386   reaction time. In contrast, units with large I_{which} bias the saccade direction toward their

387   preferred direction.

Figure 4. **a**. The connection weights between the eye movement output units and the *when* units (upper panel) and the *which* units (lower panel). **b**. The effect of lesions to the *when* and *which* units on the reaction time. **c.** The effect of lesions to the *when* and *which* units on the choice. The blue bars indicate the proportion of correct trials. The orange bars indicate the proportion of trials in which the choice is consistent with the sign of the accumulated evidence at the time of choice. The green bars indicate the percentage of trials in which the model chooses the left target. **d**. Speed-accuracy tradeoff. We suppress the output of a different portion of +*when*/-*when* units (see Methods). As more +*when* units' outcome is suppressed, the model's reaction time (black curve, right y-axis) increases along with the accuracy (blue curve, left y-axis). However, the proportion of trials in which the choices are consistent with the evidence (orange curve, left y-axis) stays the same except for the extreme cases. **e**. The maximum flow (upper panel) and the inverse of the geodesic distance (lower panel) between different unit groups. The smaller maximum flow and the larger geodesic distance between *when/which* units and other units suggest the relatively tight connections between the *when* and *which* units. ✳ indicates significant difference ($p < 0.05$, Two tailed t-test with Bonferroni correction). The error bars in all panels indicate the S.E. across runs.

With these indices defined, we select two groups of hidden layer units: the *when* units

and the *which* units. Within each group, we further divide them into a positive subgroup

and a negative subgroup, depending on their signs of I_{when} or I_{which}. The +*when* units are

selected with the following procedure. First, we sort all units with positive I_{when} values

by their I_{when} values in the descending order. Then, we calculate the accumulative I_{when}

along this axis and select the top units that together contribute more than 50% of the

sum of the positive I_{when}. These units are defined as the +*when* units (10.70 ± 0.26 out of

50.60 ± 0.89 units with positive I_{when}). They have larger connection weights to the two

saccade output units than to the fixation output unit (Fig 4a). We use similar procedures

to select the -*when*, the +*which*, and the -*which* units (n=13.80 ± 0.27 out of 77.40 ± 0.89

units with negative I_{when}, 9.80 ± 0.30 out of 64.00 ± 1.25 units with positive I_{which}, and

9.50 ± 0.28 out of 64.00 ± 1.25 units with negative I_{which}, respectively). The -*when* units

have smaller connection weights to the saccade units than to the fixation unit, the

+*which* units have larger connection weights to the left saccade than to the right saccade

output unit, and the -*which* units have smaller connection weights to the left saccade

than to the right saccade output unit (Fig 4a). With these selection criteria, the *when*

units are supposed to contribute more to the decision of when a response should be

made, while the *which* units contribute more to the decision of which target should be

chosen. Together, they constitute 34.22 ± 0.52% of all the units in the hidden layer.

Next, we examine how the ±*when* and ±*which* units affect the network's behavior. The

causality link can be demonstrated by simulated lesions that selectively inactivate the

connections of each group of units to the output layer. With only the outputs

inactivated, the hidden layer itself is not disturbed. When we inactivate the +*when* units,

the RTs become longer while the accuracy remains intact (Fig 4bc). In contrast, when

we inactivate the output of the -*when* units, the network's RTs become smaller (Fig 4b).

Although the network performance has an apparent drop, the network's choice still

accurately reflects the accumulated logLR, suggesting the performance drop is largely

due to the fact that the network has to work with a smaller total logLR due to the

shorter RT (Fig 4c). In comparison, when *which* units are manipulated, only the choice

accuracy is affected but the RT remains the same (Fig 4bc). More specifically,

inactivating +*which* units leads to a bias toward the right target, while inactivating -

which units leads to a bias toward the left target (Fig 4c). These results suggest there are

two distinct populations of hidden layer units contributing to the choice and the

reaction time.

The way how *when* units affect the accuracy and reaction time suggests a possible

mechanism to modulate the speed-accuracy tradeoff. We demonstrate this by

suppressing different amount of *when* units' outputs (see Methods for details). As more

+*when* units' output is suppressed, the reaction time becomes larger (Spearman's rank

correlation, $p<0.001$) and the accuracy becomes higher (Spearman's rank correlation,

$p<0.001$) (Fig 4d). Importantly, the choices are still consistent with the accumulated

evidence except for the most extreme cases.

The distinct functional roles of the *when* and *which* units may suggest they have

different connection patterns. We use the connection matrix of the hidden layer units to

construct a weighted directed graph and calculate the geodesic distance and the

maximum flow between the hidden layer units (see Methods). To account for the units

that are not connected to each other, we use the average maximum flows and inverse of

geodesic distance in the analysis, which is 0 for the unit pairs that are not connected.

Interestingly, we find the inverses of the geodesic distance between the *when* units and

the *which* units are significantly larger than that between the *when*/*which* units and

others. The maximum flows between the *when* units and the *which* units are also

significantly higher than the network average (Fig 4e). These results suggest that the

when and the *which* units belong to a tightly connected sub-network within the hidden

layer and are not topologically separated.

<u>Network analyses – Predictive Coding</u>

So far, we have shown that our network is able to generate appropriate choices based

on shape sequences. However, the network is constructed and trained in the way that

the sensory events are treated exactly the same as the action events. Therefore, the

activities of the output units that correspond to the sensory events should provide

predictions on the sensory events. In other words, our network may also serve as a

generative model for the predictive coding framework.

In the probabilistic reasoning task, each choice is associated with its respective shape

distribution. Therefore, as one accumulates information regarding to the choice, the

probability distribution of the upcoming shapes can also be inferred. We plot the mean

subthreshold activity, o_t, of the ten shape output units in Figure 5a at the time point

right before the onset of each shape. When the current evidence is in favor of the left

target, the activities of the output layer shape units resemble the probabilities from

which the shapes are drawn when the left target is the correct target. When the

evidence is in favor of the right target, the activity pattern of the output layer shape

units shifts and becomes more similar to the sampling distribution associated with the

right target (Fig 5a).

Figure 5. **a**. The normalized subthreshold activities of 10 shape output units. We
calculate the 10 shape units' activities at the time step immediately before each
shape onset for all epochs in all trials in the test dataset (96555 trials and 583445
epochs from 20 runs), normalized by dividing each unit's activity by the sum of
activities of all 10 shape output units. Data are divided into 10 group by the total
logLR before the shape onset, which is indicated by the color. **b**. The Kullback-
Leibler (KL) divergence between the normalized subthreshold activities (as shown
in the Fig. 5a) and the sampling distributions (shown in the Fig.1c). Data are
grouped by the total logLR. The error bars indicate the S.E. across runs.

We quantify the similarity between the activity patterns of the output layer shape units

and the sampling distributions by calculating the Kullback-Leibler (KL) divergence (Fig

5b). The KL divergence between the output layer unit activities and the sampling

distribution associated with the left target decreases as the total logLR supporting the

left target gets larger and grows when the total logLR is smaller. The opposite trend is

observed on the KL divergence between the output layer unit activities and the

sampling distribution associated with the right target. These results suggest the

activities of the output layer shape units encode the probability distribution of the next

shape based on the current accumulated evidence.

Task 2: Multi-sensory integration task

So far, we have shown that the network is able to perform the probabilistic reasoning

task. The decision making process in the task may also be interpreted as Bayesian

inference in which each shape updates the prior information. To more directly illustrate

whether the network performs Bayesian inference, we test the model with a multi-

sensory integration task adapted from Gu et al., 2008 (Gu et al., 2008) and compare it

with the animals' behavior. In this task, the subject has to discriminate whether the

heading direction is toward the left or the right basing on either the visual input, the

vestibular input, or both. Gu and colleagues showed that the animals were able to use

information combined from different modalities optimally and reached a threshold that

matched predictions based on Bayesian inference.

Figure 6. **a**. The psychometric curve. The model is first trained with the single modal
conditions and then tested with both the single modal (green: visual, orange:
vestibular) and the bi-modal (black) conditions. Each data point represents the
proportion of the left choice at a given motion direction condition. The model shows
a steeper psychometric curve for the bi-modal condition, indicating a better
performance. **b**. The performance thresholds. The blue bars are the model's
thresholds under the single modal and the bi-modal conditions, compared against
the thresholds calculated with the optimal Bayesian inference (orange). The
threshold under the bi-modal condition is significantly smaller than the thresholds
under either single modal condition. The differences between the thresholds of the
network and the thresholds calculated with Bayesian inference are not significant.
(two-tailed t-test with Bonferroni correction, p value threshold = 0.05)

To model this task, we assume that the input layer units have Gaussian heading-
direction tuning curves with Poisson noise. They are divided into two groups of 8 units,
corresponding to the visual and vestibular inputs, respectively. Critically, the network is
trained with trials in which inputs are from only one single sensory modality and tested

with trials in which inputs are still limited to single modalities and trials in which inputs

from both modalities are available. We find that the network can generalize the training

to bi-modal inputs. It combines the information from visual and vestibular inputs and

achieves a higher accuracy without further training (Fig 6a). We fit the network model's

choices in both the uni-modal and bi-modal conditions with cumulative Gaussian

functions and define network's performance thresholds as the standard deviation of the

best-fitting function. The threshold under the combined condition is significantly

smaller than the thresholds under either single modality conditions (Fig 6b).

Importantly, it matches the predictions of Bayesian inference. These results suggest

that the network model is able to perform Bayesian inference without being explicitly

trained to do so.

Task 3: Confidence / Post-decision wagering task

It has been argued that the same neurons that represent the decision variable during

decision making may also support meta-cognition such as confidence. We test how our

model performs a post-decision wagering task (Kiani & Shadlen, 2009). In this task, the

model needs to make decisions about the movement direction of a random dot motion

stimulus. The task difficulty is controlled by the proportion of dots moving coherently

and the duration of the random dot stimulus. A reward is delivered if the decision

matches the direction of the coherently moving dots. In half of the trials, a third target

(sure target) appears after the motion viewing period. Choosing the sure target leads to

a smaller but certain reward.

We set up the appropriate inputs and output units for our network model to learn the

task. There are 10 input units for the motion stimulus, among which 5 prefer the

leftward and the other 5 prefer the rightward motion. Their activities represent the

motion strength of the random dots. Independent noises are added to the activities.

Two additional input units indicate the left and the right choice target. Finally, there is

an input unit that indicates the presence of the sure target. Again, the output units are a

mirror copy of the input units, and the activities of the output units corresponding to

the fixations on the choice targets and the sure target are used for generating the

decisions.

The network exhibits a similar choice pattern to the monkeys' behavior (Kiani &

Shadlen, 2009). When the motion strength is weaker and the stimulus duration is

shorter, the task difficulty is higher and the network chooses the sure target more

frequently (Fig 7a). In addition, because the model may opt out for the sure target when

its confidence about the motion direction is low, the overall accuracy becomes higher in

trials in which the sure target is available but the model chooses to indicate the motion

direction than in trials without the sure target (Fig 7b). The model's behavior is

consistent with the monkeys' strategy.

We further look at the response patterns of the units in the hidden layer. In particular,

we want to study the units that show choice selectivity during the delay period before

the choice. This selection criterium is similar to what was employed in the experimental

study (Kiani and Shadlen, 2009, see Methods). The responses of these units are

modulated during the motion viewing period (Fig 7c). More importantly, in the trials

when the network chooses the sure target, their responses reach an intermediate level

between the activity levels in trials when the targets of the preferred and non-preferred

directions are chosen. These units behave like the neurons recorded from the LIP area

and may provide a basis for the post-decision wagering (Kiani & Shadlen, 2009).

Figure 7. **a**. The proportion of trials in which the model chooses the sure target. The
color indicates the motion strength. The frequency of the sure target choices
decreases with the motion strength and the duration of motion viewing. **b**. The
accuracy. Solid lines are the trials with the sure target and dashed lines are the trials
without the sure target. The correct rate is higher when the sure target is provided.
The error bars in panels **a** and **b** are S.E. across runs. **c**. Activities of choice-selective
units. The responses are aligned to the movie onset (left) and the choice (right). The
color of each line denotes the choice and motion direction. The dashed lines are
trials in which the model chooses the sure targets. The units have intermediate
activity level in trials that the sure target is chosen. The error bars are S.E. across
units.

Task 4: Two step task

In the last experiment, we extend our model to a learning task. Learning requires the

model to incorporate trial history information for future decisions. By piecing events

across multiple trials together, our network model should be able to infer contingencies

across trials and achieve adaptive behavior. Notably, because the sensory, motor, and

reward events are all included in our model, it is straightforward to achieve across-trial

learning with our model.

To demonstrate that the network adapts well in changing environment, we use an

adapted version of the origin two-step task (Akam, Costa, & Dayan, 2015; Daw et al.,

2011). In this task, the agent has to choose between two options A1 and A2, each

leading to one of the two intermediate outcomes, B1 and B2, with different but fixed

transition probabilities. In particular, A1 is more likely followed by B1 (common) than

B2 (rare) and A2 is more likely to be followed by B2 (common) than B1 (rare). Finally,

B1 and B2 are each associated with a probabilistic reward (0.8 vs 0.2). The reward

contingencies of B1 and B2 are reversed across blocks. Each block consists of 50 trials.

The task requires the agent to learn that the intermediate states B1 and B2, instead of

the agent's own choice of A1 or A2, are actually the ones that determine the reward.

The training dataset consists of trials with randomly assigned choices. This is to reflect

that the actual learning by human subject starts from rather random choices. During the

training, only the events in the rewarded trials are actually trained. This is because the

goal of the training is to learn the sequences more likely leading to reward. For the

network to learn the event contingencies across trials, the state vector h_t is not re-

initialized at the beginning of each trial and the events in the previous trial are included

in the training procedure. The loss function is calculated based only on the current

rewarded trial, but the errors are back-propagated to the previous trial and the network

connections are updated accordingly. In the testing sessions, the network connections

are not further updated.

After the training, the network learns to make decisions based on the events both in the

current and in the previous trials. Immediately after a block change, the network

performs poorly because of the reversed reward contingency. Its performance then

recovers gradually (Fig 8a). To exclude the possibility that the network simply learns to

reverse its choice every 50 trials, we train the network with 50-trial blocks and test it

with a different block size and observe similar results (Supp fig 2).

To further investigate the network's adaptive behavior, we use a factorial analysis

introduced by Daw and colleagues (Daw et al., 2011) to look at how different factors of

the task affect the choice. We sort the trials based on the intermediate outcomes and the

reward outcomes into four groups: common-rewarded (CR), common-unrewarded

(CU), rare-rewarded (RR) and rare-unrewarded (RU). Then we calculate the probability

of the network repeating the previous choice in the next trial. The probability is higher

after the CR and RU trials than after the CU and RR condition (Fig. 8b). The results

indicate that the task structure information is used for decisions, which was interpreted

as evidence for model-based decision making (Daw et al., 2011). Interestingly, even

though the error signals are only propagated one trial back during the training period,

the history influence on the network's choice extends to many trials back (Fig 8c).

Two more analyses corroborate this conclusion. We first use a logistic regression to

look at how a variety of factors affect network's choices (Fig 8d). The result suggests

that the interaction term between the intermediate outcome and the reward outcome

(*Trans x Out*) is the largest factor affecting the choices. We further fit the network's

behavior with a mixture of the model-free and model-based agent (Akam et al., 2015;

Daw et al., 2011). The higher weight for the model-based strategy (Table 1) indicates

the network's choice behavior is closer to model-based.

w_{model_based}	α_1	λ	α_2	β	p
0.87±0.04	0.75±0.05	0.68±0.05	0.47±0.01	9.49±1.16	0.77±0.08

661
Table 1. Fitted parameters. The S.E. across runs is indicated. The weight for the

model-based algorithm, w_{model_based}, is significantly larger than 0.5 (p<0.001),

indicating a strong contribution of the model-based behavior.

Although the network is not trained explicitly to calculate and compare the value

associated with each state, it is curious whether the network activities encode the Q-

value estimated with RL. Based the RL model fitting above, we estimate the choices' Q-

value in each trial. When we plot the estimated Q-value difference between the two

choices, it shows a clear correlation with the activity difference between the two choice

output units (Figure 8e).

Figure 8. **a**. The two-step task. The thick and thin lines denote the common and rare transitions, respectively. The contingencies indicated by the dashed lines are reversed across blocks. **b.** The switching behavior. Trials are aligned to the block switch (trial 0). The performance first drops to below the chance level but then gradually recovers. **c.** The probability of repeating the previous choice. The stay probabilities of the subsequent trials are higher for the CR and the RU trials than the RR and the CU trials. **d**. Trial history effects. The choice in the current trial is affected by the trial types in the previous trials. Solid dots indicate significant effect (Bonferroni correction, p < 0.05). **e**. Factors affecting the choices. ※ indicates significance (p<0.01). **f**. The response difference between two choice output units is correlated with the difference between the estimated Q-value of the two actions.

Discussion

Here, we present a neural network model for flexible and adaptive decision making. By training essentially the same network model to perform four exemplary tasks, we show that the network model not only can solve complicated decision-making problems, perform Bayesian inference, and support meta-cognition, but also can use past trial history to adapt its choices in a volatile environment. The units in the network exhibit signature behaviors of the decision-related neurons previously described experimentally, encoding the accumulative evidence and urgency signal. We also suggest a possible mechanism of the speed and accuracy trade-off. The network model provides a unified solution to questions that have been investigated previously with different modeling approaches.

Drift-diffusion model and Attractor network models

The probabilistic reasoning task and the post-decision wagering task have been studied with the drift-diffusion model (DDM). In the DDM, the decision-making process is modeled as a diffusion process in which the evidence biases the drift rate. The behavior of the DDM can be accounted for by our model. This is interesting because, unlike the DDM and its variants, our model does not explicitly model the decision as a competition between alternatives in which evidence is accumulated. Yet by training the model to learn the statistical contingencies between events, the model exhibits behavior that fits the DDM well.

Our modeling effort is a distinct approach from the previous work of attractor neural

network models (X.-J. Wang, 2002; Wong & Wang, 2006). Like the DDM, the attractor

network models treat the decision-making process as a competition. The competition in

attractor networks is between two groups of neurons, each receiving sensory inputs

supporting its corresponding option. The sensory inputs drive the network states into

attractor states that represent the final choice. This type of attractor network in its

simplest form is obviously not a general solution for more complex decision-making

tasks, for example, when the decisions require multiple steps as in the two step tasks, or

when the contingency between the sensory inputs and the reward is volatile.

Even if we limit our discussions to the kind of decision making problem that has been

studied with the attractor network model, the current approach provides several new

insights. First, our model describes a potential mechanism for the speed-accuracy

tradeoff in decision making distinct from the attractor models. In our model, there are a

group of units that contribute to reaction time causally. Through the modulation of

these units, one can achieve speed-accuracy tradeoff. In contrast, the speed-accuracy

tradeoff in attractor network models is achieved through the adjustment of the balance

between excitatory and inhibitory connections, which effectively modulate how fast the

network may settle into an attractor state (Lo, Wang, & Wang, 2015). Future

experiments can be designed to distinguish these two scenarios. Second, our model's

decisions do not require the network to converge into attractor states. This allows the

model to perform the post-decision wagering task without additional modules. The

network's state, i.e. the units' activity level, not only reflects the decision outcome, but

also may be used to estimate confidence. It was found to be necessary to introduce an

extra layer to model such a task with a attractor network (Insabato, Pannunzi, Rolls, &

Deco, 2010). Finally, our model does not require its inputs to reflect evidence strength,

which is essential for an attractor network. Therefore, it is able to perform the

probability reasoning task in which the contingencies between the sensory stimuli and

the outcomes are arbitrary. The input flexibility allows our model to be a more general

solution than the attractor network models.

Bayesian Inference

The computation that the network carries out is essentially Bayesian inference. During

decision making, our network provides a representation of the probability distribution

of the sensory events, which are updated over the time as new inputs arrive. Unlike the

probabilistic population coding theory proposed previously (Ma, Beck, Latham, &

Pouget, 2006), our model does not depend on assumptions of the distributions of the

input or the nature of the contingency. The population response of the units in our

model encode the entire distribution. This is a more general solution than the

probabilistic population coding theory. Another recent model also aims to be a general

solution for probabilistic computing (Orhan & Ma, 2017). In comparison, our model

emphasizes the temporal integration of information. The outputs of our model may be

directly mapped to the probability distribution, which may serve as a useful top-down

signal that can be sent back to the sensory cortex.

Reinforcement learning

By learning statistical relationships between sensory, action, and reward events across

trials, our model can exhibit an adaptive behavior, which has been mostly modeled in

the field with the reinforcement learning framework.

An interesting conceptual difference between our model and RL is the role of reward.

The reward plays a central role in RL, in which the learning is aimed at minimizing the

reward prediction error and maximizing the total future reward. The discrepancy

between the actual and the expected rewards is used to update the value of states. In

contrast, our model treats the reward events as part of the event sequences just as the

sensory and action events. The learning in our model is driven by a teaching signal that

includes sensory, action, and reward events. This signal could come from the dopamine

system in the brain. The dopamine neurons have been indicated to signal reward

prediction error and used as evidence for the existence of a reinforcement learning

system in the brain (Schultz et al., 1997). Yet, recent findings have started to reveal a

wider role of dopamine neurons in signaling not just reward prediction error, but also

predictions of sensory stimuli or actions (Engelhard et al., 2018; Jin & Costa, 2010;

Wassum, Ostlund, & Maidment, 2012; Wood, Simon, Koerner, Kass, & Moghaddam,

2017). These findings fit well with the current model in which the prediction errors

need to be calculated for not only the rewards, but also the sensory and action events.

Future experiments may be designed to test whether the dopamine system indeed fit

this role.

Interestingly, our simulation results of the two-step task, along with several previous

modeling studies (J. X. Wang et al., 2018; Zhang et al., 2018), show that online updating

of synaptic weights is not necessary for adaptive behavior. Once the network is trained

and learns the contingency between the events across trials, it can generate adaptive

behavior based on the internal network dynamics, which encodes the past trial

sequences, without further adjusting its internal connection weights. The network may

appear to be learning and its behavior can be well explained by the reinforcement

learning framework, yet no actual learning has to happen at the level of neuronal

connections.

Training

To train the model, it is necessary to feed the model with appropriate sequences of

sensory, action, and reward events. In the real brain, this means there has to be a

separate mechanism to generate appropriate responses at appropriate times and form

these sequences in the first place for the brain to learn. One solution is to start from the

responses based on animals' innate responses or other established stimulus-action

associations relevant to the task. These responses should contain a certain degree of

variations that lead to different responses and reward outcomes (Neuringer, 2002). For

example, when we train monkeys to perform complicated behavior task such as the

probabilistic reasoning task, we start from the most basic delayed saccade task.

Monkeys have an innate tendency of making saccades toward newly appearing visual

stimuli at variable delays. By selectively rewarding saccades with longer delays, we can

train the monkeys to hold the fixation for an extended period before the saccade. More

components of the task can be introduced into the task gradually this way. Similar

strategy can be used to train our model. Starting with simple tasks that the network is

capable of doing, even if only occasionally, we can selectively reinforce the behavior that

leads to reward and use the event sequence leading to the reward for the next stage

training, until we reach to the final version of the task.

Basal Ganglia

It remains an interesting speculation which brain structures may carry out the

computation as our network model does. Areas such as the prefrontal cortex, the

posterior parietal cortex, the cerebellum, the hippocampus, and the basal ganglia

receive a wide range of sensory, motor, and reward inputs and are theoretically

possible to carry out the computations demonstrated here. Indeed, many studies of

these brain structures find neurons that have similar response patterns as the units in

our model.

Among these brain structures, the basal ganglia are particular interesting. It has been

long noticed that the key feature of GRU networks, which is the gating mechanism that

controls the maintenance of old information and the updating with new incoming

information, resembles the anatomical circuitry in the basal ganglia (Frank, Loughry, &

O'Reilly, 2001; O'Reilly & Frank, 2006). The basal ganglia receive broad input from all

over the cortex, including the sensory cortices and motor cortices (Engelhard et al.,

2018), which comprises all the necessary information for learning sequences.

Our model may be applied to the current basal ganglia research in several distinct

directions, which have been largely studied separately.

First of all, our modeling results explain previous studies of the basal ganglia's role in

decision making. For example, Ding and Gold found caudate neurons represented

accumulated information in a random dot motion discrimination task (Ding & Gold,

2010, 2012). Cisek and colleagues observed a group of neurons in the globus pallidus

showed activity patterns similar to the urgency signal (Thura & Cisek, 2017). In rodent

experiments, it has been reported lesions in the striatum led to deficits in evidence

integration and produced a bias in decision making (L. Wang, Rangarajan, Gerfen, &

Krauzlis, 2018; Yartsev, Hanks, Yoon, & Brody, 2018). Our model may account for the

results from these studies.

Second, our model, which is trained to learn sequences, naturally explains the basal

ganglia's role in performing sequential actions and in procedure memory (Geddes, Li, &

Jin, 2018; Jin & Costa, 2010; Wood et al., 2017). It is conceivable that simply setting the

input and output units according to the task requirement, we may train the model to

perform sequential actions.

Third, the basal ganglia have also been indicated to play a central role in habitual and

goal-directed behavior, both are highly relevant to our model (Graybiel, 1995; Graybiel

& Grafton, 2015). On the one hand, by design, our model is capable of generating

habitual behavior after the training. The model simply follows a set sequence of events

and carries out actions, which may be interpreted as habitual responses, even in the

case that the actions have to be determined with the preceding sensory inputs in a

complicated manner. On the other hand, our model may also contribute to goal-directed

behavior. A key component of goal-directed behavior is the ability of assessing which

actions may lead to a desired goal. Such assessment depends on the capability of making

predictions of the actions' consequences, which is exactly what our model can do.

Our model may therefore help us to link the existing studies of basal ganglia from

distinct perspectives to form a coherent computational theory of the basal ganglia's

role. Future work should incorporate more details of the basal ganglia circuitry into the

network structure.

Further investigations

The current results focus on the similarities between the model and the behavior and physiological findings from the previous experiments. It would be interesting to further explore how tweaking components and parameters of the GRU network would affect these results. This knowledge should motivate the experimental investigation of the relevant neural circuitry.

We also have not investigated extensively how the particular loss function we use to train the network in the current study, which treats all events equally and is flat over time, can be improved. One possibility is to normalize the loss function within each domain of sensory, motor, and reward, and use an appropriate weight for each domain to reach a suitable balance. Another possibility is to weigh loss functions differently across the time, so that events remote from the reward in the sequence exerts less influence on learning. Our preliminary explorations in these directions have yielded similar results (not shown), but more detailed investigations may reveal a loss function that may create a network that models the brain better and provides us with further insights.

Our current investigation focuses on the hidden layer, which is where the learning and the decision making occurs. Conceptually, this is similar to the generative model in the predictive coding framework (Friston, 2005; Rao & Ballard, 1999). The output layer in the current study only serves a limited purpose for the verification of the network's performance. One may extend the current work and construct a circuitry in which the

model's outputs are sent to a sensory module and modulate the sensory processing. The

sensory module sends inputs back to the model and forms a loop. This way, we can

create a complete model that may be further used to understand the neural circuitry in

both the sensory and the motor parts of the brain.

Finally, GRU networks have been shown to be able to solve problems at much larger

scales, for example, the natural language processing (Chung et al., 2014). Limited by the

availability of the existing experimental studies, we have only tested the network with

small-scale toy problems. As a result, we use only a small network with 128 units.

Natural language processing demands the learning of complex contingency structures

between elements of language contained in a sequence that can be very long. Although

at a much more complex level, this is essentially the same learning problem as what we

study with our current model. By expanding our network model with more units and

more layers, we should be able to model much more complex behavior. It is an

interesting parallelism between the studies of neural network solutions for natural

language processing, which develops neural networks to solve a complex computational

problem that the human brain does, and the brain modeling studies, which uses

network models to understand the computations in the brain. Our study is a beginning

to bridge the two fields for the benefits of both.

Funding

This work was supported by Shanghai Municipal Science and Technology Major Project (Grant No.2018SHZDZX05) and by Strategic Priority Research Program of Chinese Academy of Science, Grant No. XDB32070100.

Acknowledgements

We thank Zhongqiao Lin, Chechang Nie, Yang Xie, Wenyi Zhang for their help in all phases of the study, and Shan Yu for providing comments and advice. The authors declare no competing financial or nonfinancial interests.

Methods

Network

Our model is a network that contains three layers: an input layer, a hidden layer based on gated recurrent units, and an output layer (Fig 1a). The input layer contains units that carry the information about the sensory, motor, and reward events. (N_{IL}=20).

There is a total of 14 sensory input units. 10 of them represent the 10 shapes in the task. There are 3 additional units indicating the presence of the eye movement targets, including the fixation point, the left target, and the right target. We also include a unit that indicates the absence of any visual stimuli.

There are 4 action input units that represent the efference copies of the motor commands: 1 for fixation on the fixation point, 1 for saccading to and then fixating on the left target, 1 for saccading to and then fixating on the right target, and 1 for saccading to other locations, which is considered as a fixation break and aborts a trial.

Finally, 2 reward input units are included: one for reward and one for the absence of reward.

The output layer includes also 20 units that mirror the inputs.

We set the time step to 100ms in the model training and testing. Our analyses and

conclusions remain valid for smaller time steps.

Behavior Analysis

The parameters of the network are fixed during testing. We generate 5000 random

shape sequences of 25 shapes long as the testing data and feed them into the network

model. A shape sequence is stopped whenever the output units associated with the

saccades are triggered. If the network does not make a response before all 25 shapes

have been presented or makes a response at an inappropriate time, the trial is aborted

(172.50 ± 3.73 or 3.45 ± 0.07 % trials in each run, excluded in further analyses).

Subjective weights (Fig 2b):

We perform a logistic regression to assess how each kind of shape affects the choice.

The probability of choice is a function of the sum of leverages, Q, provided by each kind

of shape:

$$P(choice = left) = \frac{1}{1+10^{-Q}},$$ (12)

$$Q = \beta_0 + \sum_{m=1}^{10} \beta_m N_m ,$$ (13)

where N_m represents the how many times shape m appears in a trial. β_0 is the bias term,

$\beta_{1\sim10}$ are the estimates of how much weight the network model assigns to shapes 1 to

10, and are termed as the subjective weights of evidence (Yang & Shadlen, 2007). Since

the regressors are not independent to each other, here we use the ridge regression to

minimize the variation of the estimation. The hyperparameter controls the trade-off

between the cross-entropy loss and the L2-norm of the coefficients is selected through a

ten-fold cross validation for each fitting.

<u>Shape order (Fig 2d):</u>

To test how the shape order affects the network's choice, we perform a logistic

regression on the trials with more than six epochs:

973
$$Q \;=\; \beta_0 + \sum_{n=1}^{3} \beta_n \mathrm{logLR}_n + \; \beta_4 \sum_{n=3}^{N-3} \mathrm{logLR}_n + \sum_{n=1}^{2} \beta_{n+4} \mathrm{logLR}_{N-n}\,, \quad (14)$$

where logLR_n is the logLR of the shape in epoch n and N is the total number of epochs in

a sequence. β_0 is the bias term, β_1, β_2, β_3 are the fitting coefficients of the shapes in the

first three epochs, β_4 the average effect for the middle epochs, and β_5, β_6 the second

and the third epochs to the last. The regression is done without the final shape (n-th).

This is because the last shape is almost always (>99% of trials) consistent with the

choice. The fitting procedure is similar to what we use above to estimate the subjective

weight of each shape.

<u>Unit Selectivity (Fig 3ab):</u>

We test whether each neuron's activity in the hidden layer is modulated by the total

logLR, absolute value of the total logLR, the urgency, and the choice outcome with a

linear regression. We align the hidden unit state h to the shape onset in each epoch and

use a simple linear regression to characterize the unit's selectivity:

$$h_t = \beta_0 + \beta_1 \sum_{n=1}^{t} \mathrm{logLR}_n + \beta_2 \left|\sum_{n=1}^{t} \mathrm{logLR}_n\right| + \beta_3 u_t + \beta_4 c ,$$

(15)

where h_t is the unit's response at time t aligned to the shape onset, $\sum_{n=1}^{t} \mathrm{logLR}_n$ is the

total logLR of the shapes that have been presented by time t, u_t represents the urgency,

which is quantified as the number of shape epochs, c represents the choice of the

network, which is set to 1 when the left target is chosen, -1 when the right target is

chosen, and 0 if fixation is still maintained by the end of the epoch. The regression is

performed on every time step during the shape representation. We define a unit as

selective to a variable if the variable shows a significant effect on the unit's activity at

every time step in an epoch. The significance is determined by two-tailed t-tests with

Bonferroni correction.

1002

1003   Response Variability (Fig 3d)

1004

1005   We calculate a unit's response variability as the standard deviation of the unit's average

1006   response in each shape epoch across trials. Fig 3d plots the average response variability

1007   for all units that are selective to the total logLR in all 20 simulation runs, using only the

1008   trials with more than 5 shapes.

1009

1010   Speed-accuracy tradeoff (Fig 4d)

1011

To test how *when* units affect the speed-accuracy tradeoff, we suppress the outputs of

the +*when*/-*when* units that are selected with variable criteria. For example, the criteria

of the accumulative I_{when} of the selected +*when* units are set to 10%, 20%, 30%, 40%,

and 50% out of the summed I_{when} of all units with positive I_{when}. At each criterium, the

number of units manipulated is not linearly scaled, but their total contribution to the

behavior, measured by their summed I_{when}, is scaled linearly.

1018

1019 <u>Network analysis (Fig 4cd):</u>

1020

Geodesic distance and max flow are used to quantify how much information may be

transferred between two nodes in a graph. We use weight matrix U_h, which represents

the connection strengths between units in the hidden layer, to construct a weighted

directed graph. Each unit in the hidden layer corresponds to a node in the graph.

Connections with the highest 30% of the absolute value of the connection strength are

turned into the edges in the graph. The results hold if we keep the highest 10% or 50%.

The weight and capacity of each edge are defined as the absolute value of the original

connection strength.

1029

We define the geodesic distance from node A to target B as the minimum summed

inverse of the weights of the edges from node A to B (Newman, 2001). The geodesic

distances between any pairs are calculated with Dijkstra's algorithm (Ahuja, Magnanti,

& Orlin, 1993). The distance between the pairs not connected is defined as infinite. To

account for these pairs, we compare the mean of the inverse of geodesic distance across

all unit pairs in each group.

1036

1037 Task 2: Multi-sensory integration task

1038 <u>Input units:</u>

1039

There are two groups of input units representing the sensory stimuli, corresponding to

the visual and the vestibular inputs. Each group has 8 units with Gaussian tuning curves

with different preferred directions D_{pref} at -90°, -64.3°, -38.6°, -12.9°, 12.9°, 38.6°, 64.3°,

and 90°, respectively. The tuning curve $f(D)$ is described as following:

$$f(D) = N\left(D - D_{pref}, \sigma^2\right), \tag{16}$$

where D is the direction of the motion stimulus in the range between -90° and 90° and

σ=90° is the standard deviation of the Gaussian function. The observed spike count s has

a Poisson distribution:

$$p(s|D) = \frac{e^{-gf(D)}(g \cdot f(D))^s}{s!}, \tag{17}$$

where g=300 is a constant for the gain. Finally, to limit the response of the input units to

be smaller than 1, a sigmoid-like function is used to calculate the response $r(s)$:

$$r(s) = 1/(1 + e^{1-s}). \tag{18}$$

The exact choice of the function is not important. Under the bi-modal condition, the

responses of both the visual and the vestibular input units are calculated with the

heading direction D. Under the uni-modal condition, the responses of the units of the

unavailable modality are set to 0.5 without noise.

1056

1057   <u>Bayesian inference:</u>

1058

We estimate the heading direction by calculating the discretized posterior probability of

the possible motion directions;

$$p(D|s) \propto e^{\sum_i(-g \cdot f_i(D) + s_i \cdot \log(g \cdot f_i(D)))}. \tag{19}$$

The left choice target is chosen if the probability of motion direction towards left, $p(D <$

$0|s)$, is larger than the probability of motion direction towards right, $p(D > 0|s)$.

Otherwise, the right target is chosen.

1065

1066 In the bi-modal condition, we integrate the information from visual and vestibular

1067 system and calculate the posterior probability $p(D|s_{vis}, \ s_{vest})$, which is proportional to

1068 the product of the $p(D|s_{vis})$ and $p(D|s_{vest})$, given the independence between s_{vis} and

1069 s_{vest}.

1070

1071 All analyses are based on 20 simulation runs.

1072

1073 Task 3: Confidence / Post-decision wagering task

1074 Input units:

1075

The network has 22 input units. Ten input units are visual units that respond to motion

stimuli. Five of them prefer the leftward motion and the other five prefer the rightward

motion. Their internal activation, s, is linearly scaled with the coherence, and an

independent Gaussian noise, $N(0, \sigma^2)$, is added to mimic the noise during the sensory

processing, where σ=2.5. A sigmoid function is used as the activation function.

$$s = coh\% \cdot 10 + \ N(0, \sigma^2) \tag{20}$$

$$r = sigmoid(s) \tag{21}$$

where the coherence of the moving dots, coh, is positive when the motion direction

matches unit's prefer direction and negative when not.

1085

The momentary evidence e_t is the response difference between the leftward-preferring

units and the rightward-preferring units. The accumulated evidence E is then the sum

of momentary evidence across time:

$$e_t = \sum_i s_{left}^{t,i} - \sum_i s_{right}^{t,i},\qquad(22)$$

$$E = \sum_{t=1}^{T} e_t,\qquad(23)$$

where $s_{left}^{t,i}$ and $s_{right}^{t,i}$ are the internal activities at time point t of the i-th unit preferring

the leftward and the rightward motion, respectively. T is the duration of the motion

stimulus and is randomly selected from group [1, 2, 3, 4, 6, 8] at equal probabilities. The

final decision is based on the accumulated evidence E. The trial sequences used to train

the model is generated as follows (Kiani & Shadlen, 2009). When the sure target is not

available, the left target is chosen if E is larger than 0 and the right target is chosen if E

is smaller than 0. When the sure target is given, the left and right choice targets are

selected only if $|E|$ is larger than a pre-defined threshold θ. Otherwise, the sure target is

selected. Furthermore, the threshold θ increases linearly over time:

$$\theta = 5 + 2.5t\qquad(24)$$

1101

1102   20 independent runs are simulated for testing the reproducibility.

1103

1104   <u>Unit activity analysis:</u>

1105

1106   The analysis is based on choice selective units. These units are chosen based on their

1107   activities at the time point right before the choice in the trials without the sure target.

1108   The selectivity is determined by the two-tailed t-test with Bonferroni correction. The

1109   choice direction that induces a larger response is defined as a unit's preferred direction

1110   (left: n = 46.75 ± 1.93, right: n = 42.45 ± 1.85).

1111

1112   Two-step Task

1113   Simulation:

1114

1115   We use 20 trained session in our analysis. Each run contains $7.5*10^5$ training trials

1116   (15000 blocks of 50 trials) and 100 testing blocks.

1117

1118   Model fitting:

1119

The analysis was previously described (Akam et al., 2015; Daw et al., 2011; Zhang et al.,

2018). Briefly, the model choice is fitted to a mixed model-free and model-based

algorithm. For the model-free algorithm, the value of the chosen options and observed

intermediate outcomes are updated by a temporal difference algorithm with two free

parameters: the learning rate α_1 and the eligibility λ, representing the proportion of the

reward prediction error that is attributed to the first-stage chosen options A1 and A2. In

the model-based algorithm, the value of the observed intermediate outcome is also

learned with a temporal difference algorithm. The value of each option is the sum of the

products of the transition probabilities and the values of the intermediate outcomes. An

extra parameter, learning rate α_2, is used for the update of the value of the intermediate

outcomes in the model-based algorithm. The overall value of each option is the

weighted average of its value calculated with the model-free and model-based

algorithm ($w_{model-free} + w_{model-based}=1$). Finally, the probability of choosing each option is a

softmax function of the values of the two options:

1134

$$p(action = A_i) = \frac{exp\ (\beta \cdot v(A_i) + p \cdot rep(A_i))}{\sum_{A\prime} exp\ (\beta \cdot v(A\prime) + p \cdot rep(A\prime))} \qquad (25)$$

1135

1136

1137 where inverse temperature parameter, β, controls the randomness of the choice.

1138 $rep(A_i)$ is set to 1 if action A_i is chosen in the previous trial and the parameter p

1139 captures the tendency of repeating the previous trial. $v(A_i)$ is the value of option A_i.

1140 Together, there are six free parameters and a maximum likelihood estimation algorithm

1141 is used for fitting.

1142

1143 Logistic regression:

1144

The analysis was described previously (Akam et al., 2015; Zhang et al., 2018). Briefly,

five potential factors are tested with a logistic regression, which are *Correct*—a

tendency to choose the choice with higher reward probability; *Repeat*—a tendency to

repeat the choice no matter what the reward outcome is; *Outcome*—a tendency to

repeat the rewarded choice in the previous trial; *Transition*—a tendency to repeat the

choice when it leads to common intermediate outcome and switch when rare

intermediate outcome is represented; *Trans x Out*–a tendency to repeat the same choice

when the previous trial is CR or RU, and to switch the choice if the previous trial is CU or

RR.

1154

1155

1156

References

Ahuja, R. K., Magnanti, T. L., & Orlin, J. B. (1993). *Network Flows: Theory, Algorithms, and Applications | Pearson*. Prentice Hall.

Akam, T., Costa, R., & Dayan, P. (2015). Simple Plans or Sophisticated Habits? State, Transition and Learning Interactions in the Two-Step Task. *PLOS Computational Biology*, *11*(12), e1004648-25.

Cho, K., van Merrienboer, B., Gulcehre, C., Bahdanau, D., Bougares, F., Schwenk, H., & Bengio, Y. (2014). Learning Phrase Representations using RNN Encoder-Decoder for Statistical Machine Translation.

Chung, J., Gulcehre, C., Cho, K., & Bengio, Y. (2014). Empirical Evaluation of Gated Recurrent Neural Networks on Sequence Modeling.

Churchland, A. K., Kiani, R., Chaudhuri, R., Wang, X.-J., Pouget, A., & Shadlen, M. N. (2011). Variance as a Signature of Neural Computations during Decision Making. *Neuron*, *69*(4), 818–831.

Daw, N. D., Gershman, S. J., Seymour, B., Dayan, P., & Dolan, R. J. (2011). Model-Based Influences on Humans' Choices and Striatal Prediction Errors. *Neuron*, *69*(6), 1204–1215.

Dayan, P., & Niv, Y. (2008). Reinforcement learning: The Good, The Bad and The Ugly. *Current Opinion in Neurobiology*, *18*(2), 185–196. https://doi.org/10.1016/J.CONB.2008.08.003

Ding, L., & Gold, J. I. (2010). Caudate encodes multiple computations for perceptual decisions. *The Journal of Neuroscience : The Official Journal of the Society for Neuroscience*, *30*(47), 15747–15759.

Ding, L., & Gold, J. I. (2012). Separate, causal roles of the caudate in saccadic choice and execution in a perceptual decision task. *Neuron*, *75*(5), 865–874.

Engelhard, B., Finkelstein, J., Cox, J., Fleming, W., Jang, H. J., Ornelas, S., … Witten, I.

(2018). Specialized and spatially organized coding of sensory, motor, and cognitive

variables in midbrain dopamine neurons. *BioRxiv*, 456194.

https://doi.org/10.1101/456194

Frank, M. J., Loughry, B., & O'Reilly, R. C. (2001). Interactions between frontal cortex and

basal ganglia in working memory: a computational model. *Cognitive, Affective &*

Behavioral Neuroscience, *1*(2), 137–160.

Friston, K. (2005). A theory of cortical responses. *Philosophical Transactions of the Royal*

Society B: Biological Sciences, *360*(1456), 815–836.

https://doi.org/10.1098/rstb.2005.1622

Geddes, C. E., Li, H., & Jin, X. (2018). Optogenetic Editing Reveals the Hierarchical

Organization of Learned Action Sequences. *Cell*, *174*(1), 32-43.e15.

https://doi.org/10.1016/j.cell.2018.06.012

Graybiel, A. M. (1995). Building action repertoires: memory and learning functions of

the basal ganglia. *Current Opinion in Neurobiology*, *5*(6), 733–741.

https://doi.org/10.1016/0959-4388(95)80100-6

Graybiel, A. M., & Grafton, S. T. (2015). The striatum: where skills and habits meet. *Cold*

Spring Harbor Perspectives in Biology, *7*(8), a021691.

https://doi.org/10.1101/cshperspect.a021691

Greff, K., Srivastava, R. K., & Koutník, J. (2016). LSTM: A search space odyssey. *IEEE*

Transactions on …, 1–11.

Gu, Y., Angelaki, D. E., & DeAngelis, G. C. (2008). Neural correlates of multisensory cue

integration in macaque MSTd. *Nature Neuroscience*, *11*(10), 1201–1210.

https://doi.org/10.1038/nn.2191

Hanks, T., Kiani, R., & Shadlen, M. N. (2014). A neural mechanism of speed-accuracy

tradeoff in macaque area LIP. *ELife*, *3*.

Heitz, R. P., & Schall, J. D. (2012). Neural mechanisms of speed-accuracy tradeoff.
Neuron.

Insabato, A., Pannunzi, M., Rolls, E. T., & Deco, G. (2010). Confidence-Related Decision
Making. *Journal of Neurophysiology*, *104*(1), 539–547.
https://doi.org/10.1152/jn.01068.2009

Jin, X., & Costa, R. M. (2010). Start/stop signals emerge in nigrostriatal circuits during
sequence learning. *Nature*, *466*(7305), 457–462.
https://doi.org/10.1038/nature09263

Kiani, R., & Shadlen, M. N. (2009). Representation of Confidence Associated with a
Decision by Neurons in the Parietal Cortex. *Science*, *324*(5928), 759–764.
https://doi.org/10.1126/science.1169405

Kim, J.-N., & Shadlen, M. N. (1999). Neural correlates of a decision in the dorsolateral
prefrontal cortex of the macaque. *Nature Neuroscience*, *2*(2), 176–185.
https://doi.org/10.1038/5739

Kingma, D. P., & Ba, J. (2014). Adam: A Method for Stochastic Optimization.

Kira, S., Yang, T., & Shadlen, M. N. N. (2015). A neural implementation of Wald's
sequential probability ratio test. *Neuron*, *85*(4), 861–873.
https://doi.org/10.1016/j.neuron.2015.01.007

Lo, C.-C., Wang, C.-T., & Wang, X.-J. (2015). Speed-accuracy tradeoff by a control signal
with balanced excitation and inhibition. *Journal of Neurophysiology*, *114*(1), 650–
661. https://doi.org/10.1152/jn.00845.2013

Ma, W. J., Beck, J. M., Latham, P. E., & Pouget, A. (2006). Bayesian inference with
probabilistic population codes. *Nature Neuroscience*, *9*(11), 1432–1438.

Neuringer, A. (2002). Operant variability: Evidence, functions, and theory. *Psychonomic*

Bulletin & Review, *9*(4), 672–705. https://doi.org/10.3758/BF03196324

Newman, M. E. J. (2001). Scientific collaboration networks . II . Shortest paths , weighted networks , and centrality, *64*, 1–7. https://doi.org/10.1103/PhysRevE.64.016132

O'Reilly, R. C., & Frank, M. J. (2006). Making working memory work: A computational model of learning in the prefrontal cortex and basal ganglia. *Neural Computation*, *18*(2), 283–328. https://doi.org/10.1162/089976606775093909

Orhan, A. E., & Ma, W. J. (2017). Efficient probabilistic inference in generic neural networks trained with non-probabilistic feedback. *Nature Communications*, 1–14.

Rao, R. P. N., & Ballard, D. (1999). Predictive coding in the visual cortex: a functional interpretation of some extra-classical receptive-field effects. *Nature Neuroscience*, *2*(1), 79–87. https://doi.org/10.1038/4580

Ratcliff, R. (1978). A theory of memory retrieval. *Psychological Review*, *85*(2), 59–108. https://doi.org/10.1037/0033-295X.85.2.59

Roitman, J. D., & Shadlen, M. N. (2002). Response of Neurons in the Lateral Intraparietal Area during a Combined Visual Discrimination Reaction Time Task. *Journal of Neuroscience*, *22*(21), 9475–9489.

Schultz, W., Dayan, P., & Montague, P. R. (1997). Neural Substrate of Prediction and. *Science*, *275*(5306), 1593–1599.

Stone, M. (1960). Models for choice-reaction time. *Psychometrika*, *25*(3), 251–260. https://doi.org/10.1007/BF02289729

Sutton, R. S., & Barto, A. G. (2012). Reinforcement Learning: An Introduction, 1–334.

Thura, D., & Cisek, P. (2017). The Basal Ganglia Do Not Select Reach Targets but Control the Urgency of Commitment. *Neuron*, *95*(5), 1160-1170.e5. https://doi.org/10.1016/j.neuron.2017.07.039

Wald, A., & Wolfowitz, J. (1948). Optimum Character of the Sequential Probability Ratio

Test. *The Annals of Mathematical Statistics*, *19*(3), 326–339.

https://doi.org/10.1214/aoms/1177730197

Wang, J. X., Kurth-Nelson, Z., Kumaran, D., Tirumala, D., Soyer, H., Leibo, J. Z., …

Botvinick, M. (2018). Prefrontal cortex as a meta-reinforcement learning system.

Nature Neuroscience, *21*(6), 860–868. https://doi.org/10.1038/s41593-018-0147-

Wang, L., Rangarajan, K. V., Gerfen, C. R., & Krauzlis, R. J. (2018). Activation of Striatal

Neurons Causes a Perceptual Decision Bias during Visual Change Detection in Mice.

Neuron, *97*(6), 1369-1381.e5. https://doi.org/10.1016/J.NEURON.2018.01.049

Wang, X.-J. (2001). Synaptic reverberation underlying mnemonic persistent activity.

Trends in Neurosciences, *24*(8), 455–463.

Wang, X.-J. (2002). Probabilistic decision making by slow reverberation in cortical

circuits. *Neuron*, *36*(5), 955–968.

Wassum, K. M., Ostlund, S. B., & Maidment, N. T. (2012). Phasic Mesolimbic Dopamine

Signaling Precedes and Predicts Performance of a Self-Initiated Action Sequence

Task. *Biological Psychiatry*, *71*(10), 846–854.

https://doi.org/10.1016/J.BIOPSYCH.2011.12.019

Wong, K.-F., & Wang, X.-J. (2006). A Recurrent Network Mechanism of Time Integration

in Perceptual Decisions. *Journal of Neuroscience*, *26*(4), 1314–1328.

https://doi.org/10.1523/JNEUROSCI.3733-05.2006

Wood, J., Simon, N. W., Koerner, F. S., Kass, R. E., & Moghaddam, B. (2017). Networks of

VTA Neurons Encode Real-Time Information about Uncertain Numbers of Actions

Executed to Earn a Reward. *Frontiers in Behavioral Neuroscience*, *11*, 140.

https://doi.org/10.3389/fnbeh.2017.00140

Yang, T., & Shadlen, M. N. (2007). Probabilistic reasoning by neurons. *Nature*,

447(7148), 1075–1080. https://doi.org/10.1038/nature05852

Yartsev, M. M., Hanks, T. D., Yoon, A. M., & Brody, C. D. (2018). Causal contribution and

dynamical encoding in the striatum during evidence accumulation. *ELife*, *7*, 1–24.

https://doi.org/10.7554/eLife.34929

Zhang, Z., Cheng, Z., Lin, Z., Nie, C., & Yang, T. (2018). A neural network model for the

orbitofrontal cortex and task space acquisition during reinforcement learning.

PLOS Computational Biology, *14*(1), e1005925.

https://doi.org/10.1371/journal.pcbi.1005925

1290

1291

1292

1293   Supplementary Figure 1. The performance of the network trained with a dataset that

1294   contains only 1000 unique sequences. Same format as in Figure 2.

1295

1296

1297

1298

1299

1300   Supplementary Figure 2. The network's performance when the testing dataset's

1301   block size is set to 70 trials. Same format as in Figure 8.

1302