Disentangling presentation and processing times in the brain

Laurent Caplette[1*], Robin A. A. Ince[2], Karim Jerbi[1] & Frédéric Gosselin[1]

[1]Department of Psychology, Université de Montréal, Montréal, Qc, Canada

[2]Institute of Neuroscience and Psychology, University of Glasgow, Glasgow, United Kingdom

Corresponding author: Laurent Caplette
Email: laurent.caplette@yale.edu
Phone: 1-203-376-0003
Present address: Department of Psychology, Yale University, 2 Hillhouse Avenue, Montréal, New Haven, CT 06520, U.S.A.

Keywords: temporal processing, presentation time, object recognition, face recognition, EEG.

Abstract

Visual object recognition seems to occur almost instantaneously. However, not only does

it require hundreds of milliseconds of processing, but our eyes also typically fixate the

object for hundreds of milliseconds. Consequently, information reaching our eyes at

different moments is processed in the brain together. Moreover, information received at

different moments during fixation is likely to be processed differently, notably because

different features might be selectively attended at different moments. Here, we introduce a

novel reverse correlation paradigm that allows us to uncover with millisecond precision

the processing time course of specific information received on the retina at specific

moments. Using faces as stimuli, we observed that processing at several electrodes and

latencies was different depending on the moment at which information was received. Some

of these variations were caused by a disruption occurring 160-200 ms after the face onset,

suggesting a role of the N170 ERP component in gating information processing; others

hinted at temporal compression and integration mechanisms. Importantly, the observed

differences were not explained by simple adaptation or repetition priming, they were

modulated by the task, and they were correlated with differences in behavior. These results

suggest that top-down routines of information sampling are applied to the continuous visual

input, even within a single eye fixation.

1 Introduction

Visual object recognition is a process that seems to occur almost instantaneously. However, this is just an impression: not only does our brain process the object for hundreds of milliseconds, but we will typically fixate it for hundreds of milliseconds too. Of course, light reflected on the object continually hits our retina throughout this fixation. The light reaching our eyes at each specific moment will then be processed in the brain. Since processing takes some time, light reaching our eyes at different moments during the fixation will typically be processed in the brain at the same moment (but possibly at different processing levels; Figure 1). The brain activity evoked by the perception of an object is a combination of the brain responses to information received on the retina at different moments.

Figure 1. At any given point in time (any horizontal imaginary line in the above graphs), information received at different moments during fixation is simultaneously processed in the brain (possibly at different processing levels). **A)** Processing is identical for information received at different moments. **B)** Processing is different for information received at different moments.

We can expect visual information received at different moments to be processed differently (Figure 1b). This is partly because of the limited processing capacity of higher visual areas[1-2], which prevents too much information from being processed simultaneously. One strategy that can be applied by the visual system to overcome this limitation is to use

visual information received in different time windows to process different features (e.g.,

different regions of space, colors or spatial frequencies). This is often referred to as top-

down attention being guided from one feature to another[3-4], as a visual routine[5], or simply

as a sampling of different features across time.

The use of the information received at specific moments to process specific features

may arise because this is a more efficient strategy for some tasks than using information

received at any moment to process any feature[5]. Moreover, specific strategies may be more

efficient than others. For example, it may be computationally more efficient to process

coarse information before finer noisier features, when recognizing objects or scenes[6-7], and

so, high visual areas might process coarse information received early and fine information

received late but not fine information received early. It follows that relatively stable

strategies may occur in individuals, or even across individuals. Other biases may also result

in stable strategies: for example, a tendency to process the most informative features in the

information received first (which is probably an evolutionarily sensible strategy), or an

attempt to compensate anatomical limitations (e.g., process color from the information

received earlier because color is processed more slowly[8-9]). These strategies are likely to

depend on the expected input and on the task.

How information received at different moments within a fixation is processed for

object recognition is rarely investigated, possibly in part because the distinction between

stimulus presentation time and processing time is not often discussed or appreciated (but

see 10). Still, a few behavioral studies have examined this question, either by randomly

revealing image features across time[9,11-14] or by adding noise that is randomly varying

across time[15-16], and by correlating the samples with the subject's response. These methods

and similar ones (e.g., randomly varying inter-stimulus intervals with high resolution) have

been employed several times in the related literature on attention and detection

mechanisms[17-22]. Using such methods in object recognition paradigms has led to multiple

demonstrations of how observers use the information received at different moments to

categorize an object. Interestingly, these strategies often seem stable across individuals.

For example, as it was hypothesized, correct responses correlate with high spatial

frequency, or fine, information received late, and with low spatial frequency, or coarse,

information received early and late[12-13,23] (see also 24-25). These strategies also seem to be

contingent on the task at hand[26].

While studies have been conducted on the effects of stimulus onset asynchrony[27],

duration[28-29], and ordering[30] on brain activity, the processing by the brain of information

received at specific *moments* during a fixation has, to our knowledge, never been

investigated. This a fundamentally different endeavor: decomposing the processing time

course of an object according to the moment at which information is received should inform

us about the neural mechanisms underlying the differential sampling and integration of

information across time. It should allow us to disentangle the sampling and the processing

of visual information, which are both unraveling through time.

In this study, we aimed to perform such a decomposition. To do so, we randomly

sampled the features of a face across time while subjects were performing a gender or

expression recognition task[9,14] (Figure 2; Movies S1-S4) and while their EEG activity was

recorded. Faces were chosen as stimuli because they are important social stimuli that

human brains are wired by evolutionary pressures to process efficiently; moreover, faces

are particularly well suited to a spatial sampling of information as they all are composed

of the same spatial features with essentially the same spatial configuration. To ensure that

subjects could initiate a potential top-down sampling strategy on time, face stimuli

occurred at predictable moments. We then reverse correlated brain activity at all time points

to information presented in different time windows. We had three main hypotheses: 1) the

processing time course of information received at different moments will be different; 2)

this modulation of processing by the time at which information is received will itself be

modulated by the task; and 3) variations in the processing of information received at

different moments will correlate to variations in the behavioral use of this information for

the task.

Figure 2. Example of a video stimulus used in a random trial. The three face features were smoothly revealed in random frames (1 frame each 8.3 ms) across 200 ms. See movies S1-S4.

2 Materials and Methods

2.1 Participants

Twenty-four neurotypical adults (mean age = 23.0 years; SD = 2.9) were recruited

on the campus of the University of Montreal. Participants did not suffer from any

psychiatric or psychological disorder and had no known history of head concussions. The

experimental protocol was approved by the ethics board of the Faculty of Arts and Sciences

of the University of Montreal and the study was carried in accordance with the approved

guidelines. Written informed consent was obtained from all the participants after the

procedure had been fully explained, and a monetary compensation was provided upon

completion of each experimental session.

2.2 Materials

The experimental program ran on a Ciara Discovery computer with Windows 7 in

the Matlab environment, using custom scripts and functions from the Psychophysics

Toolbox[42-44]. Stimuli were shown on an Asus VG278H monitor, calibrated to allow a linear

manipulation of luminance, with a resolution of 1920×1080 pixels and a 120 Hz refresh

rate. Luminance values ranged from 2.47 cd/m^2 to 269 cd/m^2. A chin rest was used to

maintain a viewing distance of 76 cm. EEG activity was recorded using an ANT Neuro

Waveguard 64-electrode cap with Ag/AgCl electrodes, using a sampling rate of 1024 Hz

and a resolution of 12 bits. Linked mastoids served as initial common reference. Vertical

electro-oculogram (vEOG) was bipolarly registered above and below the dominant eye and

horizontal electro-oculogram (hEOG) at the outer canthi of both eyes. Electrode impedance

was kept below 10 kΩ during recording.

2.3 Stimuli and sampling

Two hundred and sixty-four color images of faces were selected from the image

database *Karolinska Directed Emotional Faces* (KDEF)[45]; only faces facing the camera

were chosen. These were composed of 66 different identities (33 women and 33 men) each

performing a happy and a neutral expression; two different pictures of each facial

expression were used. Faces were aligned on twenty hand-annotated landmarks averaged

to six mean coordinates for left and right eyes, left and right eyebrows, nose and mouth,

using a Procrustes transformation.

We then created an uninformative face background by taking the mean of all

aligned faces and applying a lightly smoothed elliptical mask (horizontal radius = 6 degrees

of visual angle) to conceal the background, hair and shoulders. The areas including and

surrounding the eyes and eyebrows were then covered by two lightly smoothed

approximately circular masks; the area including and surrounding the mouth was covered

by a lightly smoothed elliptical mask. The color of these masks was the mean color of the

unmasked parts of the average face. The three feature masks were of equal area (within a

<1% margin; since feature masks were smoothed, area covered was computed by summing

the mask pixel values).

For use in the sampled-face trials, the mean luminance and the contrast of all

aligned faces (within the feature areas determined by the feature masks previously

discussed) were equalized, separately for each color channel, using the SHINE toolbox[46].

The same procedure was applied but for the whole face (inside the elliptical mask), for use

in the whole-face trials.

On each sampled-face trial, the face features of a randomly selected exemplar face

were gradually revealed at random moments across a total duration of 200 ms; that is,

masked feature areas of the uninformative face background were replaced by the features

of an exemplar face (Figure 2; Movies S1-S4). A duration of 200 ms was chosen so that no

saccade would occur during stimulus presentation on most trials. Specifically, on each trial,

a random 3×72 sparse matrix composed of zeros and a few ones (the probability of each

element being one was constant and was 0.025) was created; each row of 72 elements was

then convolved with a 1-D gaussian kernel, or "bubble"[14,32], with a 1.8 frame (15 ms)

standard deviation. Superfluous padding was removed so that the final smoothed matrix

was 3 × 24 in size and thresholding was applied so that no value exceeded 1. We called

this matrix *sampling matrix* and the value of each element determined the visibility of a

given face feature through the feature background in a given video frame for this trial; more

precisely, $\boldsymbol{p}_{ijk} = \boldsymbol{f}_{ik} \cdot s_{ijk} + b \cdot (1 - s_{ijk})$, where $\boldsymbol{p}_{ijk}$ are the pixel values to be displayed

for face feature *i* on frame *j* in trial *k*, $\boldsymbol{f}_{ik}$ are the original pixel values of face feature *i* of the

exemplar face selected for trial *k*, s_{ijk} is the sampling matrix value for face feature *i* on

frame *j* in trial *k*, and *b* is the feature background color.

2.4 Experimental design

Each participant came to the laboratory twice and filled in a personal information

questionnaire (education, age, sex, hours of sleep, alertness, concussion history, mental

illness history, etc.) on the first session. Participants completed a total of 1000 sampled-

face trials in each session; nine participants also completed in each session 100 additional

whole-face trials in which a non-sampled exemplar face was shown for the same amount

of time. Sampled-face and whole-face trials were randomly intermixed throughout the

experiment. Each experimental session was divided in four equal-size blocks (of 250 or

275 trials) and blocks were interleaved with breaks of approximately 5 minutes. In addition,

after every 5 trials, the screen automatically showed text indicating that the participants

could take a few seconds to blink and rest their eyes before pressing a key to continue the

experiment (participants were instructed not to blink during the trials themselves).

On each trial, a central fixation cross was shown to the participants for 1500 ms,

after which the video stimulus appeared during 200 ms, superposed to the fixation cross,

again followed by the fixation cross until the participant responded (the next trial then

followed after an additional constant 1500 ms); a mid-gray background was always present.

A fixed inter-trial interval was used so that participants could predict the onset of the trials.

Half of the participants had to categorize the sex of the faces while the other half had to

categorize their expression (happy or neutral). Participants had to respond as accurately

and rapidly as possible with two keys on the keyboard (half of the participants had to use

the opposite key combination from the other half, to counterbalance any motor effect).

2.5 Behavioral data analysis

One session from one participant was removed from all analyses because its mean

accuracy was 50%; a session from a different participant was removed because of

prominent EEG artifacts on a large subset of trials. Finally, one 275-trial block from still

another participant was lost due to a technical error.

Accuracies and response times were z-scored within each 250- or 275-trial block.

Trials with a z-scored response time below -3 or above 3, or with an absolute response time

below 100 ms or above 2000 ms, were excluded from further analyses. Sampling matrices

weighted by z-scored accuracies were then averaged together for each session. (Such a

weighted sum is equivalent to a linear regression here since sampling was random.)

Resulting *classification images* were averaged together within each subject and then within

each task. Analyses were repeated with randomly permuted accuracies 10,000 times and a

statistical threshold ($p < .05$, one-tailed, pixel level, corrected for familywise error rate

(FWER)) was determined using the maximum statistic method[47]. Since we were only

interested in which information was used to do the task, we only assessed positive

correlations and performed a one-tailed test.

2.6 EEG data preprocessing

All preprocessing was performed with the help of functions from the Fieldtrip

toolbox[48]. EEG raw data from each session was segmented in trials, filtered between 1 and

30 Hz with two successive 4^{th} order Butterworth IIR filters, baseline corrected using the

average activity between 500 ms and 250 ms before stimulus presentation, and down-

sampled to a 250 Hz sampling rate. Mastoid electrodes were removed due to poor signal-

to-noise ratio on most subjects and data was re-referenced to an average reference.

Anomalous trials, trials in which eye movements were occurring during the stimulus and

anomalous electrodes were identified and removed following careful visual inspection of

the data (mean number of trials = 4.5 (0.5%), SD = 9.22 (0.9%)); bad channels were

interpolated using a spherical spline (mean number of channels = 1.02, SD = 0.81) . An

ICA using Hyvärinen's fixed-point algorithm[49] was then performed to identify blink and

eye movement artifacts. Bad components were identified and removed following careful

visual inspection (mean number of components = 1.38, SD = 0.65). Finally, we computed

single-trial current scalp density (CSD) waveforms using the spherical spline method

(lambda = 1e-5, spline order = 4, degree of Legendre polynomials = 14)[50-51]; all further

analyses were conducted on this CSD data.

2.7 EEG data analysis

2.7.1 Falsely correct trials

In every experiment in which performance is not at ceiling level, part of the trials

initially labeled as correct are correct only by chance: e.g., if 20% of responses are

incorrect, this means that another 20% was in fact correct only by chance (since there is a

50% chance of being correct or incorrect when guessing). Here, we can verify which trials

are comprised in this percentage of "falsely" correct trials by verifying which are the trials

whose sampling matrices correlate the least to the behavioral classification image. Using

this novel analysis method, we kept only true correct trials which were not correct merely

by chance for further analyses.

2.7.2 Regression analyses

Trials with a z-scored response time below -3 or above 3, or with an absolute

response time below 100 ms or above 2000 ms, were excluded from the regression

analyses. For each session, electrode and time point, regularized (ridge) multiple linear

regressions were performed between the standardized feature × presentation time sampling

planes and the standardized EEG amplitudes (Figure S1a). Resulting regression

coefficients were convolved with a Gaussian kernel (standard deviation of 3 time points,

or 12 ms) in the EEG time dimension. Maps of regression coefficients were averaged

within each subject and then across subjects within each task. Analyses were repeated with

randomly permuted trials 1,000 times and statistical thresholds ($p < .05$, two-tailed, FWER-

corrected) at both the pixel and cluster (2D clusters across EEG time and presentation time;

using the summed cluster values; arbitrary primary threshold of $p < .01$, two-tailed,

uncorrected) levels were determined using the maximum statistic method[47]. Analyses were

restricted to time points between 30 ms and 600 ms from face onset. Results are displayed

for representative PO7 (left occipito-temporal; LOT) and PO8 (right occipito-temporal;

ROT) sensors but multiple comparison corrections were applied across all electrodes.

Results were similar for most occipito-temporal sensors; data from all electrodes is

available in an online repository (https://osf.io/3r782/).

2.7.3 Task × stimulus moment ANOVA

To investigate whether processing was significantly modulated by the presentation

moment and the task, a task × presentation moment ANOVA was performed. Maps of

regression coefficients for each subject, face feature and electrode were first linearly

interpolated to a resolution of 0.1 ms, realigned to the feature onset instead of the face onset

(e.g., the EEG activity for the first presentation moment stayed the same, while activity for

the second one was shifted left by 8.3 ms, activity for the third one by 16.7 ms, and so on),

and resampled to the original resolution of 4 ms. Task × presentation moment ANOVAs

were then performed on individual subjects' regression coefficients for each face feature,

electrode, and latency from the feature onset (Figure S1b). Resulting F values were

interpolated in topography space using biharmonic spline interpolation[52]. Analyses were

repeated on the 1,000 null maps obtained by randomly permuting trials and statistical

thresholds ($p < .05$, one-tailed, FWER-corrected) at both the pixel and cluster (3D clusters

across EEG time and topography space; using the summed cluster values; arbitrary primary

threshold of $p < .01$, one-tailed, uncorrected) levels were determined using the maximum

statistic method[47]. A one-tailed test was performed given that F statistics are non-negative.

Analyses were restricted to time points between 50 ms and 400 ms from feature onset.

2. 8 Mutual information between brain and behavior regression coefficients

For each subject, electrode and latency from feature onset, Gaussian copula mutual

information[53-54] was computed between the results of the behavior-stimulus weighted sum

and the absolute values of the results of the EEG-stimulus regression, across stimulus

moments (stimulus presentation time frames). Analyses were repeated with regression

coefficients from the 1,000 null maps obtained by randomly permuting trials and statistical

thresholds ($p < .05$, one-tailed, FWER-corrected) at both the pixel and cluster (3D clusters

across EEG time and topography space; using the summed cluster values; arbitrary primary

threshold of $p < .01$, one-tailed, uncorrected) levels were determined using the maximum

statistic method[47]. A one-tailed test was performed given that mutual information is non-

negative. Analyses were restricted to time points between 50 ms and 400 ms from feature

onset.

3 Results

3.1 Time course of information use

Mean accuracy was 75.8% ($\sigma = 4.2\%$) in the gender task and 82.9% ($\sigma = 6.2\%$) in

the expression task. Mean response time was 711 ms ($\sigma = 87$ ms) in the gender task and

662 ms ($\sigma = 100$ ms) in the expression task.

To identify which face features in which time frames led to accurate responses, we

performed for each session a sum of sampling matrices (indicating the visibility of each

face feature at each time frame in the stimulus on each trial) weighted by accuracies. Mean

results for each task are displayed in Figure 3. As we can see, both eyes were used

at all except the earliest moments, while the mouth was used throughout the presentation

to identify the expression of the face. These results replicate previous studies using a spatial

sampling of the whole face[9,31-33].

Note that these time points refer to the moment of presentation of the feature within

the stimulus, and so, equivalently, to the moment at which information is received on the

retina. To avoid any confusion with processing time (as assessed with EEG), we refer to

this time dimension as stimulus time; to avoid any confusion with stimulus duration, we

will usually refer to stimulus "moments".

Figure 3. Behavioral results indicating, for each task, how each feature presented on each frame correlates with correct responses. Bold segments of line indicate frames that are significant ($p < .05$, one-tailed, FWER-corrected).

3.2 Visual Evoked Potentials

To verify if our sampling method elicited, on average, similar ERPs to whole

unaltered faces, we computed the average of all trials with sampled and whole faces, for

those subjects who performed the task on both kinds of trials. We display the ERPs of

representative left and right occipito-temporal sensors (LOT and ROT), and the overall

topographies (Figure 4). As we can see, ERPs and their associated topographies are very

similar between the conditions. We computed the difference between the ERPs and

assessed its significance using a paired permutation test (500 permutations): there was no

significant difference between the conditions at any time point on either sensor ($p > .05$,

two-tailed, FWER-corrected with the maximum statistic method). This suggests that our

sampling method did not greatly alter the average brain response to faces.

Figure 4. A) Mean ERPs for whole (green) and sampled (blue) faces on LOT and ROT. Shaded areas represent standard errors above and below the mean. **B)** Topographies for whole and sampled faces at selected latencies.

3.3 Uncovering the processing of information received at different moments

For each session, ridge regressions were performed between sampling matrices of

correct trials and EEG amplitude on each time point and electrode (see Methods; Figure

S1a). Although analyses were conducted on all electrodes (and appropriate corrections for

multiple comparisons were applied), we will mostly focus on results from occipito-

temporal sensors (see also Figure S4 for summary scalp maps computed using global

power). Mean maps of regression coefficients are displayed for representative left and right

occipito-temporal sensors (LOT and ROT) on Figures 5 (gender task) and 6 (expression

task). These maps show a complete portrait of what is happening during visual recognition:

how information impinging the retina at different moments throughout fixation is

simultaneously processed through time in the brain.

We can immediately see on most maps (especially the ones for the mouth and the

contralateral eyes) a clear diagonal trend: as it could be expected, information received on

the retina x ms later is on average processed x ms later in the brain. This processing takes

the form, in most cases, of a positive activation followed by a negative one and another

positive one (analogous to the classic P1, N170 and P3 components). However, there also

seem to be important differences in amplitude across stimulus moments. In the next section,

we look at these differences in more details.

3.4 Investigating differences in processing across stimulus moments

To assess whether differences in processing across stimulus moments are

statistically significant, we conducted a task × stimulus moment ANOVA on regression

coefficients for each face feature, electrode and EEG latency, after having realigned each

row of the previous maps so that the zero point on the x axis is the feature onset rather than

the face onset (see Methods; Figure S1b).

Significant modulation of processing by the stimulus moment is visible during

almost all the analyzed time window (~50-360 ms; Figure 7). Differences are strongest on

occipito-temporal sensors, but they are also present on central and frontal sensors,

Figure 5. Mean maps of regression coefficients for each face feature (rows) on LOT and ROT sensors (columns) for the gender task. Within each map, each row refers to the EEG activity (across time) related to the presentation of the face feature on a given frame within the stimulus, i.e. the processing of information received on the retina at a specific moment. Gray outlines indicate significance at the cluster level and black outlines indicate significance at the pixel level ($p < .05$, two-tailed, FWER-corrected). Dashed lines illustrate components with slopes different from one. Arrows point toward some results of interest: (1) an increase in early activity for information received later; (2) late activity is maximal for information received mid-fixation; (3) additional negative peak for information received at the fixation onset; (4) large latency shift for activity related to information received early on ipsilateral electrodes; and (5) increased latency of negative activity for information received at the end of fixation.

especially at higher latencies (e.g., there is a significant effect of stimulus moment peaking

between 300 and 350 ms on frontal Fpz sensor).

On occipito-temporal sensors, variations in the amplitude of the first positive

activation across stimulus moments are leading to significant differences around a latency

of 80-100 ms: specifically, this activation is stronger at late stimulus moments or at all

except intermediate stimulus moments (Arrow 1, Figures 5-6). The last positive activation

peaking at intermediate stimulus moments is also a source of significant variations around

300 ms (Arrow 2, Figures 5-6).

Figure 6. Mean maps of regression coefficients for each face feature (rows) on LOT and ROT sensors (columns) for the expression task. Within each map, each row refers to the EEG activity (across time) related to the presentation of the face feature on a given frame within the stimulus, i.e. the processing of information received on the retina at a specific moment. Gray outlines indicate significance at the cluster level and black outlines indicate significance at the pixel level ($p < .05$, two-tailed, FWER-corrected). Dashed lines illustrate components with slopes different from one. Arrows indicate results of interest : (1) an increase in early activity for information received later; (2) late activity is maximal for information received mid-fixation; (5) increased latency of negative activity for information received at the end of fixation.

3.4.1 An additional negative peak for early stimulus moments

Interestingly, significant differences in amplitude around 150 ms for the

contralateral eyes in the gender task are partly driven by the presence of an apparent

additional peak, for the early stimulus moments (Arrow 3, Figure 5). We verified whether

these two peaks represented two distinct components with different topographies. To do

so, we used the maps of regression coefficients for individual sessions and looked at the

topographies (one value for each electrode) associated with both peaks (at the same

stimulus moment); we analyzed the 12 subjects performing the gender task. We thus had

four topographies per subject and per eye: one for each peak in each session. For each

subject, we computed a cosine similarity metric (1 – the absolute value of the cosine angle)

between the topographies associated to the same peak on different days and averaged them:

this is the within-peak similarity. Next, we computed the same metric for topographies

associated to different peaks on different days and averaged them: this is the between-peaks

similarity. We finally performed t-tests between these similarity metrics: the within-peak

similarities were significantly greater for the right eye ($t(11) = 4.76$, $p_{Bonf} = .002$) but not

for the left eye ($t(11) = 1.38$, $p_{Bonf} > .10$). When using the topographies associated to

different peaks on the *same* day to compute the similarity metric, we still obtained

significantly greater within-peak similarities for the right eye but not for the left eye (left

eye: $t(11) = 0.97$, $p_{Bonf} > .10$; right eye: $t(11) = 3.07$, $p_{Bonf} = .042$). In other words, for the

right eye feature at least, topographies associated with the same peak obtained on different

days are more similar than topographies associated to different peaks, even when these are

obtained on the same day. Consequently, each peak represents a distinct activation with its

own topography and neural generators, with the first one being especially sensitive to the

onset and stopping being receptive after only about 20 ms.

3.4.2 Variations in latencies across stimulus moments

Other variations on occipito-temporal sensors seem to be driven by increases or

decreases in the latency of a component across stimulus moments. To investigate this, we

computed, for each major component, task and feature, the peak latency at each significant

stimulus moment on LOT and ROT (significance at the cluster level; ignoring activations

past 500 ms from the face onset). We then fitted a line across these latencies (see dashed

lines on Figures 5 and 6) and tested (one-sample t-test) whether the slope of the line was

significantly different from 1. Here, a slope of 1 would mean that the feature takes the same

time to be processed at all stimulus moments, whereas a larger slope would mean that the

feature takes increasingly longer to be

processed with increasing stimulus

moment, and a smaller slope that the

feature takes an increasingly shorter

time to be processed with increasing

stimulus moment; a slope of 0 would

mean that features are processed at the

same moment irrespectively of when

they were received on the retina. In

most cases, the latency of the first

positive component from the feature

onset was approximately constant (i.e.

same processing duration for all

stimulus moments; slopes between 0.90

and 1.04, R^2_{adj} > .96, df ≥ 11, t < 2.92,

p_{Bonf} > .10) except in the case of the

right eye on LOT in the gender task,

where it was slightly increasing (slope

= 1.08, R^2_{adj} = .99, $t(22)$ = 3.24, p_{Bonf} =

Figure 7. Effect of stimulus moment on EEG activity, for each face feature. F values are shown for all latencies (from the feature onset) for LOT (blue) and ROT (green) sensors; bold segments indicate time points significant at the pixel level (p < .05, FWER-corrected across sensors and time). These F values indicate how much activity at a given latency is influenced by the exact moment at which information is presented within the stimulus. These time courses are superposed to the mean magnitudes (across stimulus moments) of the regression coefficients (in smaller point and less saturated color). Higher F values do not necessarily coincide with higher average activity. Topographies depict the temporal progression of the effect of presentation moment across the whole scalp: latencies of 100, 150 and 250 ms are shown. Lighter colors indicate higher F values; white curves indicate areas significant at the pixel level and gray curves indicate areas significant at the cluster level (p < .05, one-tailed, FWER-corrected across topography and time).

.049) and in the case of the eyes on ipsilateral electrodes in the gender task where it was

decreasing (slopes < .44, R^2_{adj} > .27, df ≥ 17, t > 8.84, p_{Bonf} < 1.2 × 10⁻⁶). The small slope

for the eyes on ipsilateral electrodes illustrates the striking fact that this component always

occurs about 220 ms after the face onset or later; information received the earliest is thus

processed at about the same time as information received 50-75 ms later (Arrow 4, Figure

5). Regarding the middle negative component, its slope across stimulus moments was not

different from 1 in most cases (slopes between 0.60 and 1.44, R^2_{adj} > .45, df ≥ 16, t < 3.00,

p_{Bonf} > .08) except for the left eye on ROT in the gender task and for the mouth on ROT in

the expression task (slopes > 1.69, R^2_{adj} > .78, $t(22)$ > 3.68, p_{Bonf} < .02). In both these cases,

the slope was significantly larger than 1. This is mostly a consequence of an increase in

latency in the last stimulus moments (Arrow 5, Figures 5 and 6). Finally, in the case of the

last positive component, the slope was significantly smaller than 1 for the eyes on the

contralateral electrodes in the gender task and for the mouth on LOT in the expression task

(slopes between 0.26 and 0.66, R^2_{adj} > .66, df ≥ 13, t > 5.98, p_{Bonf} < 2.0 × 10⁻⁴) and it was

approximately constant for the mouth in the gender task and on ROT in the expression task

(slopes = 0.67 and 0.79, R^2_{adj} > .66, df ≥ 11, t < 3.45, p_{Bonf} > .07).

3.5 Investigating top-down modulations

3.5.1 Effect of the amount of information presented beforehand

The differences in processing across stimulus moments that we uncovered cannot

be caused by differences in *what* has been seen before during a trial since sampling was

random; however, *how much* was seen could have an influence, since the probability of

already having shown information in a trial is greater in the last stimulus frame than in the

first one. Thus, the observed differences could be caused in part by bottom-up effects such

as adaptation or repetition priming. To investigate this possibility, we repeated the previous

regressions only with trials in which just one bubble was revealed: despite a greatly reduced

number of trials, results were remarkably similar (Pearson correlation of .95 between the

maps of regression coefficients; Figures S2 and S3), suggesting that the previously

observed effects are not caused by

differences in the amount of information

presented beforehand.

3.5.2   Interaction   between   stimulus

moment and task

The previous result alone does not

completely exclude the possibility of

bottom-up effects. To investigate whether

differences in activity across stimulus

moments could be explained at least in

part   by   top-down   mechanisms,   we

verified for each face feature, time point

and   location,   whether   there   was   a

significant interaction between stimulus

moment and task, i.e. if the moment at

which information is received modulates

processing differently depending on the

Figure 8. Interaction of stimulus moment and task on EEG activity, for each face feature. F values are shown for all latencies (from the feature onset) for LOT (blue) and ROT (green) sensors; bold segments indicate time points significant at the pixel level ($p < .05$, FWER-corrected across sensors and time). These F values indicate how much the activity variations across stimulus moments are influenced by the task. Topographies depict the temporal progression across the whole scalp: latencies of 100, 150 and 250 ms are shown. Lighter colors indicate higher F values; white curves indicate areas significant at the pixel level and gray curves indicate areas significant at the cluster level ($p < .05$, one-tailed, FWER-corrected across topography and time).

task. There was a significant interaction at several time points and locations, again mostly

on occipito-temporal electrodes but also in more anterior locations. Contrary to what we

observed with the main effect of stimulus moment, there is almost no significant interaction

around 100 ms, but the peak effects are similarly around 150 and 250 ms on right occipito-

temporal sensors (Figure 8). Note that on some more anterior sensors such as CP1,

significant interactions peaked after 300 ms.

3.6 Relating sampling in the brain and in behavior

We evaluated where and when variations in brain activity across stimulus moments

are related to variations in the behavioral use of information. Since differences in brain

activity are likely related to the behavioral use of information in complex nonlinear ways,

the mutual information (MI) metric was used. MI was computed across stimulus moments

between coefficients resulting from the accuracy-weighted sums of sampling matrices

Figure 9. Mutual information (MI) between behavioral and brain coefficients, for selected latencies, for both tasks and all face features. High values indicate that the variations in EEG activity across stimulus moments relate to variations in behavioral accuracy across stimulus moments. Areas significant at the cluster level are outlined by gray lines ($p < .05$, one-tailed, FWER-corrected across topography and time).

(behavioral results) and the magnitudes of brain regression coefficients for each subject,

face feature, latency from feature onset and electrode. Importantly, computing MI

separately for each face feature allowed us to isolate the contribution of *within-feature*

variations across stimulus moments. We observe significant MI mostly on occipito-

temporal sensors at early and late latencies, but also in more anterior locations at later

latencies (Figure 9). Regarding the eyes, significant MI is present early (<130 ms) and late

(>250 ms) in both tasks, but it is present at intermediate latencies (~150-250 ms) only in

the gender task. Interestingly, significant MI for the mouth is visible throughout the time

course, for both tasks. While we did not uncover a significant behavioral use of the mouth

in the gender task in our study, other studies have observed it, sometimes only when

correlating feature visibility with response times instead of accuracy[31-33]. These results

show that the origin of the variations in the use of information across stimulus moments

can be traced back to variations in occipito-temporal activity at early and late latencies, and

to variations in frontal activity at later latencies.

4 Discussion

When we fixate an object, light impinges on our retinas in a continuous fashion, implying

that our brain simultaneously processes information that is received at different moments,

through time and cortical space. This is not typically considered in studies investigating

the processing of visual objects, and so the processing uncovered in those studies

corresponds to a combination of responses to information received at different moments.

In our experiment, we randomly sampled the features of a face across time[14] while brain

activity was being measured to decompose this processing and uncover for the first time

the brain activity related to information received at specific time points during a single eye

fixation.

We first observed that information is processed differently depending on when it is

received on the retina during the fixation. One of the most striking differences is seen in

the ipsilateral representation of the eyes on occipito-temporal sensors in the gender task.

The lateralized anatomy of the visual system tells us that each eye should be processed by

the contralateral hemisphere first[34-35]: the ipsilateral representation is likely to have been

transferred from an early contralateral representation[36]. Here, the contralateral

representation appears to peak at a relatively constant offset of ~175 ms after information

is received on the retina, independently of *when* it is received during the stimulus

presentation (see the diagonal linear trend of the negative activations in Figure 5).

However, the ipsilateral representation appears to be gated: all information received in the

first 50 ms of fixation is represented at the same time, around 220 ms from face onset,

while information received after 50 ms is represented with a fixed offset of ~120 ms,

representation moment increasing linearly with stimulus moment as for the contralateral

representation. Bearing in mind the fact that ipsilateral features must be first processed by

the contralateral hemisphere, this suggests that around 220 ms, broadly consistent with the

tail end of the classical N170 ERP event (see Figure 4), a channel is opened through which

features can be transmitted across hemispheres. The N170 has been demonstrated to reflect

cross-hemispheric transfer of visual features, with the peak ipsilateral representation of the

eyes occurring after the contralateral peak of the N170 event[36]. The linear relationship

between stimulus moment and representation moment after this gating event suggests that

the channel remains open during the remainder of fixation. Despite the same experimental

stimuli, this gating phenomenon is only seen in the gender task, suggesting that it is specific

to lateralized task-relevant features (the eyes being used almost exclusively for the gender

task). In a recent study, the N170 also appeared to filter out task-irrelevant features: while

both task-relevant and task-irrelevant features were processed prior to 170 ms, only task-

relevant features were processed afterwards[37]. Of note, the cause of this gating cannot be

repetition priming because it is also visible in trials where only one feature is revealed once.

Another notable result is the occurrence of two negative peaks instead of one in the

contralateral representation of the eyes in the gender task, with the first one sensitive to

only a narrow time window after the stimulus onset. Interestingly, in the case of the right

eye, these two peaks have significantly distinct topographies, suggesting distinct neural

generators. These generators might resemble the generators of the N170 since the

activations are similarly peaking around 170 ms after the reception of eye information.

Other studies have observed multiple peaks at the expected timing of the N170[40-41]; these

are likely corresponding to activity from different generators. In one study, negative peaks

around 160 ms have been found to originate from the fusiform gyrus while negative peaks

around 180 ms have been localized as originating from the intraparietal sulcus[41].

Interestingly, if we exclude the first peak and only look at the biggest negative cluster, we

notice a pattern that is similar to the positive cluster on the ipsilateral electrodes: all

information received in the first ~50 ms is processed at about the same moment (peak

around 200 ms) while information received afterwards is processed with a relatively

constant (but slightly increasing) offset of 150-170 ms, representation moment increasing

with stimulus moment. It is possible that a gating event occurs here too, preventing

processing by the sources of this component to start before ~200 ms after the face onset.

This gating occurs at about the same latency as the ipsilateral gating, at the expected timing

of the classical N170 ERP component.

Other differences in processing across stimulus moments are also visible. For

example, the negative activation on ROT has an increased latency for late stimulus

moments for some feature/task combinations (that is, this activation peaks after a longer

time interval following the reception of information, if this information is received later).

This may be a consequence of the prioritization of information received earlier. The visual

system is likely to prioritize information received early since it might be unknown for how

long information from that stimulus will reach the retina. Thus, the processing of

information received late is likely to be delayed or processed more slowly. The opposite

phenomenon was visible for the last positive activation in some cases: its latency was

greater at early stimulus moments. In other words, there was "temporal compression":

information received earlier was "maintained" for a longer time and all information was

processed at almost the same moment independently of when it was received on the retina.

It is expected that information received at different moments is processed simultaneously

at some point in the brain if it is to be integrated together by higher level areas. The

temporal compression we observe may be a consequence of this process of accumulation

and integration of information. This is consistent with other studies reporting a component

at similar latencies associated with accumulation of evidence and temporal integration[38-39].

Although adaptation or priming to previously seen features can be ruled out as a

source of these differences because they are also present in trials with only one bubble, a

bottom-up cause still might have been possible. For instance, different parts of the visual

field may always be processed at specific moments during fixation. To investigate whether

there were top-down origins to the effects we observed, we verified whether the task

modulated them. We found significant interactions between information stimulus moment

and task on several sensors at many latencies. In other words, the differences observed in

the processing of information received at different moments were not the same depending

on the task: consequently, these differences are at least partly top-down in origin.

Significant interactions were observed at electrodes and latencies similar to those of the

significant effects of stimulus moment but started slightly later, a result that is expected for

top-down modulations. Moreover, significant interactions were occurring in slightly

different areas. For example, while the processing of the mouth was globally more

modulated by stimulus moment on right occipital electrodes, the interaction with the task

was stronger on central and left occipital electrodes. This suggests that bottom-up

mechanisms and top-down sampling are taking place in different loci.

That the brain processes information differently according to when it was received

during fixation, that this occurs even when only one such information is revealed in the

course of a trial, and that these differences are modulated by the task, all suggest that each

time slot is assigned a different "role" in a top-down fashion. This is compatible with the

idea of ballistic visual routines: different operations may be applied to the visual input in a

sequential fashion, these operations may vary according to the goal of the computation,

and the outcome of the first steps does not change the operations applied thereafter[5,23]. A

non-uniform time course of the behavioral use of information in visual recognition has

been observed in a few studies[11,14,16]; here, we demonstrate it in the brain for the first time

and we show that it is at least partly top-down in origin. Moreover, the variations in

processing across stimulus moments relate to variations in behavior; that is, as it could be

expected, how the brain (particularly occipito-temporal areas) processes information

received at a specific moment relates to how this information will be used to perform the

task.

In summary, we uncovered in this study the neural response to specific information

received at specific moments during fixation and we showed that when light is received on

the retina matters: processing is modulated by the specific moment at which information is

received, even within a single eye fixation. These differences can be quite striking, such as

an additional delay of 100 ms for information received at some moments. Importantly,

these variations remain even when we account for information perceived beforehand, and

they are modulated by the task. Moreover, they correlate to differences in the use of

information for the task. These results suggest that task-dependent visual routines of

information sampling are applied top-down to the continuous visual input.

The novel method introduced in this article also seems a promising avenue to shed

light on the accumulation and integration of information occurring during object

recognition: indeed, it should allow us to visualize the simultaneous processing, at a given

time point and location, of information that was received on the retina at different time

points. Future studies using more spatially resolved brain imaging methods such as MEG

should investigate how information received at different moments is processed,

accumulated, integrated and transferred across brain regions. This method could also be

used with intrinsically dynamic stimuli such as dynamic facial expressions or naturalistic

movies to investigate how an observer integrates evolving information.

598   **References**

1.   Broadbent, D. E. *Perception and communication.* (Pergamon Press, Oxford, 1958).

2.   Desimone, R. & Duncan, J. Neural Mechanisms of Selective Visual Attention. *Ann.*

Rev. Neurosci. **18,** 193–222 (1995).

3.   Carrasco, M. Visual attention: The past 25 years. *Vision Res.* **51,** 1484–1525 (2011).

4.   Baluch, F. & Itti, L. Mechanisms of top-down attention. *Trends Neurosci.* **34,** 210–

224 (2011).

5.   Ullman, S. Visual Routines. *Cognition.* **18,** 97–159 (1984).

6.   Marr, D. *Vision: A computational investigation into the human representation and*

processing of visual information. (MIT Press, Cambridge, 1982).

7.   Watt, R. J. Scanning from coarse to fine spatial scales in the human visual system

after the onset of a stimulus. *J. Opt. Soc. Am. A* **4,** 2006–2021 (1987).

8.   Bartels, A. & Zeki, S. The temporal order of binding visual attributes. *Vision Res.*

46, 2280–2286 (2006).

9.   Dupuis-Roy, N., Faghel-Soubeyrand, S. & Gosselin, F. Time course of the use of

chromatic and achromatic facial information for sex categorization. *Vision Res.* (In

press).

10.   VanRullen, R. Four common conceptual fallacies in mapping the time course of

recognition. *Front. Psychol.* **2,** 365 (2011).

11.   Blais, C., Roy, C., Fiset, D., Arguin, M. & Gosselin, F. The eyes are not the window

to basic emotions. *Neuropsychologia* **50,** 2830–2838 (2012).

12.   Caplette, L., Wicker, B. & Gosselin, F. Atypical Time Course of Object Recognition

in Autism Spectrum Disorder. *Sci Rep* **6,** 35494 (2016).

13.   Caplette, L., Wicker, B., Gosselin, F. & West, G. L. Hand Position Alters Vision by

Modulating the Time Course of Spatial Frequency Use. *J. Exp. Psychol.: Gen.* **7,**

917–923 (2017).

14.   Vinette, C., Gosselin, F. & Schyns, P. Spatio-temporal dynamics of face recognition

in a flash: it's in the eyes. *Cogn. Sci.* **28,** 289–301 (2004).

15.   Nagai, M., Bennett, P. J. & Sekuler, A. B. Spatiotemporal templates for detecting

orientation-defined targets. *J. Vision* **7,** 11 (2007).

16.   Neri, P. & Levi, D. M. Temporal Dynamics of Figure-Ground Segregation in Human

Vision. *J. Neurophysiol.* **97,** 951–957 (2007).

17.   Fiebelkorn, I. C., Saalmann, Y. B. & Kastner, S. Rhythmic Sampling within and

between Objects despite Sustained Attention at a Cued Location. *Curr. Biol.* **23,**

2553–2558 (2013).

18.   Landau, A. N. & Fries, P. Attention Samples Stimuli Rhythmically. *Curr. Biol.* **22,**

1000–1004 (2012).

19.   Neri, P. & Heeger, D. J. Spatiotemporal mechanisms for detecting and identifying

image features in human vision. *Nat. Neurosci.* **5,** 812–816 (2002).

20.   Latour, P. L. Evidence of internal clocks in the human operator. *Acta Psychol.* **27,**

341–348 (1967).

21.   Neri, P. & Levi, D. Temporal dynamics of directional selectivity in human vision.

J. Vision **8,** 22 (2008).

22.   Tse, P. U. Mapping visual attention with change blindness: new directions for a new
643   method. *Cogn. Sci.* **28,** 241–258 (2004).

644   23.   Caplette, L., McCabe, E., Blais, C. & Gosselin, F. The Time Course of Object,
645   Scene, and Face Categorization. *Handbook of Categorization in Cognitive Science*
646   *(2nd Edition).* (Elsevier, Amsterdam, 2017).

647   24.   Parker, D. M., Lishman, J. R. & Hughes, J. Role of coarse and fine spatial
648   information in face and object processing. *J. Exp. Psychol. Hum. Percept. Perform.*
649   **22,** 1448 (1996).

650   25.   Hughes, H. C., Nozawa, G. & Kitterle, F. Global precedence, spatial frequency
651   channels, and the statistics of natural images. *J. Cogn. Neurosci.* **8,** 197–230 (1996).

652   26.   Schyns, P. G. & Oliva, A. Dr. Angry and Mr. Smile: when categorization flexibly
653   modifies the perception of faces in rapid visual presentations. *Cognition* **69,** 243–
654   265 (1999).

655   27.   Bacon-Macé, N., Macé, M. J. M., Fabre-Thorpe, M. & Thorpe, S. J. The time course
656   of visual processing: Backward masking and natural scene categorisation. *Vision*
657   *Res.* **45,** 1459–1469 (2005).

658   28.   Brisson, B. & Jolicoeur, P. The N2pc component and stimulus duration.
659   *NeuroReport.* **18,** 1163–1166 (2007).

660   29.   Tanskanen, T., Näsänen, R., Ojanpää, H. & Hari, R. Face recognition and cortical
661   responses: Effect of stimulus duration. *NeuroImage.* **35,** 1636–1644 (2007).

662   30.   Kauffmann, L., Chauvin, A., Pichat, C. & Peyrin, C. Effective connectivity in the
663   neural network underlying coarse-to-fine categorization of visual scenes. A dynamic
664   causal modeling study. *Brain & Cognition* **99,** 46–56 (2015).

31. Dupuis-Roy, N., Fortin, I., Fiset, D. & Gosselin, F. Uncovering gender
discrimination cues in a realistic setting. *J. Vision* **9,** 10 (2009).

32. Gosselin, F. & Schyns, P. G. Bubbles: a technique to reveal the use of information
in recognition tasks. *Vision Res.* **41,** 2261–2271 (2001).

33. Schyns, P. G., Bonnar, L. & Gosselin, F. Show me the features! Understanding
recognition from the use of visual information. *Psychol. Sci.* **13,** 402–409 (2002).

34. Essen, D. V., Newsome, W. T. & Bixby, J. L. The pattern of interhemispheric
connections and its relationship to extrastriate visual areas in the macaque monkey.
J. Neurosci. **2,** 265–283 (1982).

35. Saenz, M. & Fine, I. Topographic organization of V1 projections through the corpus
callosum in humains. *Neuroimage* **52,** 1224–1229.

36. Ince, R. A. A., Jaworska, K., Gross, J., Panzeri, S., van Rijsbergen, N. J., Rousselet,
G. A. & Schyns, P. G. The deceptively simple N170 reflects network information
processing mechanisms involving visual feature coding and transfer across
hemispheres. *Cereb. Cortex* **26,** 4123–4135 (2016).

37. Zhan, J., Ince, R. A. A., van Rijsbergen, N. J. & Schyns, P. G. Dynamic construction
of reduced representations in the brain for perceptual decision behavior. *Curr. Biol.*
29, 1–8 (2019).

38. Twomey, D. M., Murphy, P. R., Kelly, S. P. & O'Connell, R. G. The classic P300
encodes a build-to-threshold decision variable. *Eur. J. Neurosci.* **42,** 1636–1643
(2015).

39.   O'Connell, R. G., Dockree, P. M. & Kelly, S. P. A supramodal accumulation-to-

bound signal that determines perceptual decisions in humans. *Nat. Neurosci.* **15,**

1729–1735 (2012).

40.   Suzuki, M. & Noguchi, Y. Reversal of the face-inversion effect in N170 under

unconscious visual processing. *Neuropsychol.* **51,** 400–409 (2013).

41.   Di Russo, F., Stella, A., Spitoni, G., Strappini, F., Sdoia, S., Galati, G., Hillyard, S.

A., Spinelli, D. & Pitzalis, S. Spatiotemporal brain mapping of spatial attention

effects on pattern-reversal ERPs. *Hum. Brain Mapp.* **33,** 1334-1351 (2012).

42.   Brainard, D. H. The Psychophysics Toolbox. *Spat. Vis.* **10,** 433–436 (1997).

43.   Pelli, D. G. The VideoToolbox software for visual psychophysics: transforming

numbers into movies. *Spat. Vis.* **10,** 437–442 (1997).

44.   Kleiner, M., Brainard, D. & Pelli, D. What's new in Psychtoolbox-3? *Perception*

36, ECVP Abstract Supplement (2007).

45.   Goeleven, E., De Raedt, R., Leyman, L. & Verschuere, B. The Karolinska Directed

Emotional Faces: A validation study. *Cogn. Emot.* **22,** 1094–1118 (2008).

46.   Willenbockel, V., Sadr, J., Fiset, D., Horne, G. O., Gosselin, F. & Tanaka, J. W.

Controlling low-level image properties: The SHINE toolbox. *Behav. Res. Meth.* **42,**

671–684 (2010).

47.   Holmes, A. P., Blair, R. C., Watson, J. D. G. & Ford, I. Nonparametric Analysis of

Statistic Images from Functional Mapping Experiments. *J. Cereb. Blood Flow*

Metab. **16,** 7–22 (1996).

48. Oostenveld, R., Fries, P., Maris, E. & Schoffelen, J.-M. FieldTrip: Open Source

Software for Advanced Analysis of MEG, EEG, and Invasive Electrophysiological

Data. *Comp. Intell. Neurosci.* **2011,** 156869 (2011).

49. Hyvärinen, A. Fast and Robust Fixed-Point Algorithms for Independent Component

Analysis. *IEEE Trans. Neural Networks* **10,** 626–634.

50. Kayser, J. & Tenke, C. E. Principal components analysis of Laplacian waveforms as

a generic method for identifying ERP generator patterns: I. evaluation with auditory

oddball tasks. *Clin. Neurophysiol.* **117,** 348–368 (2006).

51. Tenke, C. E. & Kayser, J. Generator localization by current source density (CSD):

Implications of volume conduction and field closure at intracranial and scalp

resolutions. *Clin. Neurophysiol.* **123,** 2328–2345 (2012).

52. Sandwell, D. T. Biharmonic spline interpolation of GEOS-3 and SEASAT altimeter

data. *Geophysica Res. Letters* **14,** 139–142 (1987).

53. Ince, R. A. A., van Rijsbergen, N. J., Thut, G., Rousselet, G. A., Gross, J., Panzeri,

S. & Schyns, P. G. Tracing the Flow of Perceptual Features in an Algorithmic Brain

Network. *Sci. Rep.* **5,** 17681 (2015).

54. Ince, R. A. A., Giordano, B. L., Kayser, C., Rousselet, G. A., Gross, J. & Schyns, P.

G. A statistical framework for neuroimaging data analysis based on mutual

information estimated via a gaussian copula. *Hum Brain Mapp* **38,** 1541–1573

(2017).

Acknowledgements

The study was supported by a Discovery Grant (04777-2014) from NSERC to F. G. and

by an Alexander-Graham-Bell Doctoral Scholarship from NSERC to L. C.

Supplementary Figures

 Figure S1

Figure S2

Figure S3

Figure S4

 Supplementary Figure Legends

Figure S1. EEG data analyses. **A)** On each trial, a random sampling matrix determines

how much each face feature is visible on each presentation moment (the *samples*). Only

sampling matrices of truly correct trials (see Methods: EEG Data Analysis) are kept. On

each corresponding trial, EEG activity is also recorded across the scalp for a certain period

of time (examples are shown for one electrode). For each subject, samples (**X**; independent

variable) and EEG activity (**Y**; dependent variable) are combined using a regularized

(ridge) multiple linear regression, which allows us to uncover the EEG activity, across time

and across the scalp (examples are shown for one electrode), related to the presentation of

each specific face feature shown at each stimulus moment. These time courses of regression

coefficients can be arranged in images (maps) for specific face features and electrodes

where amplitude is now represented by color (see panel B or figures 5 and 6 of the

manuscript). **B)** Prior to further analyses, maps of regression coefficients are rearranged so

that the zero point is the onset of the feature instead of the whole face (note the change of

the *x*-axis title). More specifically, EEG activity related to the presentation of a feature 8.3

ms after the face onset is shifted left by 8.3 ms, EEG activity related to the presentation of

a feature 16.7 ms after the face onset is shifted left by 16.7 ms, etc. (see Methods: EEG

Data Analysis). Only the first 400 ms are kept so that there is the same number of time

points associated with each stimulus moment. Each 24-element column of this realigned

image (activity across stimulus moments for each latency from the feature onset) is then

submitted to subsequent analyses (example illustrated for one column). In the task x

presentation moment ANOVA, columns are compared across subjects and the effect of the

task (between-subject factor), the effect of the stimulus moment (within-subject factor),

and the interaction between those factors are computed. Prior to the mutual information

(MI) analysis, coefficients are transformed into their absolute values. For each subject,

mutual information is then computed between the column of values and the vector of 24

values obtained in the behavioral analysis (see Methods: Behavioral data analysis)

associated to the same face feature.

Figure S2. Mean maps of regression coefficients for the gender task, for LOT and ROT

sensors (columns) and for each face feature (rows), when including only trials in which

there was one bubble (one feature revealed once). See Figure 5 in the main manuscript.

Figure S3. Mean maps of regression coefficients for the expression task, for LOT and ROT

sensors (columns) and for each face feature (rows), when including only trials in which

there was one bubble (one feature revealed once). See Figure 6 in the main manuscript.

Figure S4. Global scalp regression coefficients for the gender and expression task

(columns), for each face feature (rows). To compute these maps, we computed the global

field power (standard deviation across sensors) of the regression coefficients for each task

and face feature.

813 **Supplementary Movie Legends**

815 **Movie S1.** Example of a random stimulus.

817 **Movie S2.** Same as Movie S1; slowed down 10 times.

819 **Movie S3.** Another example of a random stimulus.

821 **Movie S4.** Same as Movie S3; slowed down 10 times.