Effect of task and attention on neural tracking of speech

Jonas Vanthornhout, Lien Decruy, Tom Francart

Abstract

EEG-based measures of neural tracking of natural running speech are becoming increasingly popular to investigate neural processing of speech and for applications in domains such as audiology. With a single speaker, it is usually assumed that the listener actively attends to and understands the stimulus. However, as the level of attention of the listener is inherently variable, we investigated how it affected neural envelope tracking. Using a video game or a movie as distractors, we varied the level of attention while we estimated neural envelope tracking. We varied the intelligibility level by adding stationary noise. We found a significant difference in neural envelope tracking between the condition with maximal attention and the movie condition. This difference was most pronounced in the right-frontal region of the brain. The degree of neural envelope tracking remained highly correlated with the stimulus signal-to-noise ratio, even in the movie condition. In the video game condition, this correlation was absent. This could be due to a lack of residual resources to even passively listen to the stimulus. For applied research this means that when neural envelope tracking is used as a proxy of speech intelligibility, the procedure can be made more enjoyable and feasible by letting participants watch a movie during stimulus presentation. Keyword: auditory processing, envelope tracking, decoding, EEG, attention

1 Introduction

EEG-based measures of neural tracking of natural running speech are becoming increasingly popular to investigate neural processing of speech and for applications in domains such as audiology (e.g. Vanthornhout et al. (2018)) and disorders of consciousness (e.g. Braiman et al. (2018)). With the stimulus reconstruction method, natural running speech is presented to a listener and a feature of the speech signal, such as the envelope, is reconstructed from the brain responses. The correlation between the original and reconstructed signal is a measure of neural coding of speech (Ding and Simon, 2012). Inversely, the brain responses can be predicted from features of the speech signal. Lalor et al. (2009), for example, found that the transfer function from the acoustic envelope to brain responses, also called the temporal response function (TRF), exhibits interpretable peaks, such as the N1 and P2 peaks (cf. infra).

These methods, reconstructing the stimulus or predicting the brain responses, are often used with either a single speaker or in a competing talker paradigm. With a single speaker, it is usually assumed that the listener actively attends to and understands the stimulus. In the competing talker paradigm, the listener's task is usually to attend to one of several speakers. However, in either paradigm, it is possible that a listener tunes out once in a while. In this study, we investigated the effect of attention on neural tracking, in function of the signal-to-noise ratio. Participants paid full attention or we distracted them by letting them watch a movie, or play a computer game. We did this for two types of stimuli, a story and repeated sentences. By including 2 distraction tasks, we aimed to control their level of attention.

Attention is a conscious active process and has a strong top-down effect on processes along most of the auditory pathway (Forte et al., 2017; Fritz et al., 2007). The concept of auditory attention can be illustrated by the cocktail party problem described by Cherry (1953). Although it is possible to listen to a certain speaker while ignoring other speakers, some important information, such as your name, can still be recognised when uttered by one of the ignored speakers. The combination of bottom-up salience and top-down attention leads to speech understanding (Shinn-Cunningham, 2008).

The effect of attention has already been investigated in objective measures of hearing, such as auditory brainstem repsonses (ABRs), auditory steady-state responses (ASSRs) and late auditory evoked potentials. It is often assumed that attention has a minimal effect on the ABR, as it can even be measured when the subject is asleep. However, the results are inconclusive for short clicks, pure tones and speech (Brix, 1984; Hoormann et al., 2000; Galbraith et al., 2003; Varghese et al., 2015; Lehmann and Schönwiesner, 2014).

The effect of attention has also been investigated for ASSRs. Ross et al. (2004) used a modulation discrimination task to focus auditory attention on modulated tone stimuli. They found a significant effect of focused auditory attention on the 40-Hz ASSR amplitude. Roth et al. (2013b) measured 40-Hz ASSRs, while their participants played a computer game (Tetris), and investigated the effect of game difficulty level on the SNR of the 40-Hz ASSR. They found a significant reduction in SNR with increase in difficulty. This is consistent with the theory that irrelevant stimuli are suppressed when neural resources are required for another task(Hein et al., 2007). Müller et al. (2009) found some differences at 20 Hz. However, other studies found no effect of attention: Skosnik et al. (2007) did not find a difference at 20 Hz, Linden et al. (1987) did not find a difference at 40 Hz. A reason can be that the participants did not do what was expected from them. Furthermore, these differences could be due to differences in the attentional tasks used. Overall, there is no consensus on what the effect of attention is on neural tracking of the stimulus.

Late auditory evoked potentials allow investigation of the time-domain brain response to repeated transient sounds. As attention originates in the cortex (Fritz et al., 2007), we expect

that mainly later responses are modulated by attention as they have a cortical origin. The N1 and P2 components have been shown to be enhanced by attention to the stimulus (Astheimer and Sanders, 2009; Picton and Hillyard, 1974; Näätänen et al., 2011), and are also influenced by the visual load (Regenbogen et al., 2012).

As the human brain is finely attuned to speech perception, it is interesting to investigate the effect of attention on neural measures of speech tracking, which can be used with natural speech as the stimulus, in contrast to the artificial repeated stimuli used in the paradigms described above. There is a wide range of data available on neural tracking of speech in a competing talker paradigm. Two speakers or more are presented simultaneously to a listener, whose task it is to attend to one of them. A stimulus feature is then decoded from the EEG and correlated with the features of each speaker. A decoder transforms the multi-channel neural signal into a single-channel feature, by linearly combining amplitude samples across sensors and across a post-stimulus temporal integration window. Comparison of these correlations yields information on which speaker was attended. It has been shown that the attended speaker can be decoded with high accuracy (in the order of 80-90% for trials of 20-30s) (e.g. O'Sullivan et al. (2015); Mirkovic et al. (2015); Das et al. (2016, 2018)).

By changing the number of EEG samples included in the decoder, i.e. the latencies of EEG respective to the stimulus, it can be investigated at which time lags (and therefore neural sources) the effect of attention appears. Not unexpectedly, attention mostly has an effect at longer latencies, ranging from 70 ms to 400 ms (Hillyard et al., 1973). Ding and Simon (2012) investigated the neural responses in dual-talker scenario and found that peaks in the TRF at 100 ms were more influenced by attention than peaks at 50 ms. Other experiments show effects at a later stage, beyond 150 ms (Snyder et al., 2006; Ross et al., 2009). O'Sullivan et al. (2015) found best attention decoding performance with latencies around 180 ms. Moreover, Puvvada and Simon (2017) found that early responses (< 75 ms) are minimally affected by attention. However, even at the brainstem level, around 5 ms latency, modulation by attention can already be found, showing the top-down effects (Forte et al., 2017). As a conclusion, attention prominently affects in the later responses but can also be in very early responses.

In a competing talker paradigm, it is also interesting to investigate the relative level of neural speech tracking: is the attended speaker represented more strongly, the unattended one suppressed, or a combination? Bidet-Caulet et al. (2010) shows that the representation of the attended stimulus is not enhanced, but responses to the unattended stimulus are attenuated. Irrelevant stimuli are actively suppressed. Melara et al. (2002) on the other hand show that excitatory (enhancing the attended stimulus) and inhibitory (attenuating the unattended stimulus) processes work interactively to maintain sensitivity to environmental change, without being disrupted by irrelevant events. Many researchers have found enhancement of the cortical envelope tracking of attended sounds, relative to unattended sounds. This attentional effect can be found as early as 100 ms post stimulus (Melara et al., 2002; Choi et al., 2014), corresponding with lags associated with the auditory cortex. Kong et al. (2014) however demonstrate that top-down attention can both enhance the neural response to the attended sound stream and attenuate the neural responses to an unwanted sound stream.

The literature on the effect of attention on neural tracking of a single speaker is more sparse. Kong et al. (2014) measured neural tracking of a single talker in quiet, while the participant either actively listened to a stimulus or watched a movie and ignored the auditory stimulus. They found that neural tracking, measured as the peak cross-correlation between EEG signal and stimulus envelope, was not significantly affected by listening condition. However, the shape of the cross-correlation function showed stronger N1 and P2 responses in the active listening condition and weaker P1 response compared to the movie condition. However, they did not include more intensive distractors, nor did they investigate the effect of speech intelligibility.

Moreover, their analysis was limited to a cross-correlation while decoding the envelope from the neural responses would be more powerful as it uses information from all channels.

We investigated the effect of attention on envelope reconstruction. Attention was manipulated by letting the participants (1) actively attend to the stimulus and answer comprehension questions, (2) watch a silent movie and ignore the acoustic stimulus, (3) play a computer game and ignore the acoustic stimulus. This was done at multiple levels of speech understanding, by adding stationary background noise.

We hypothesised that the computer game, played at a difficult but possible level, would be a stronger distractor than the silent movie, and that therefore envelope tracking would be strongest in the attended condition, followed by the movie, followed by the computer game. On the other hand, watching a movie may stabilize the level of attention, as maintaining focus on the movie might be easier than maintaining focus on (uninteresting) sentences, therefore reducing inter-subject variability. We also hypothesized that this effect would be most apparent for decoders beyond 100 ms.

2 Methods

2.1 Participants

We recruited 28 young normal-hearing participants between 18 and 35 years old. Every subject reported normal hearing (thresholds lower than 20 dB HL for all audiometric octave bands), which was verified by pure tone audiometry. They had Dutch (Flemish) as their mother tongue and were unpaid volunteers. Before each experiment the subjects signed an informed consent form approved by the local Medical Ethics Committee (reference no. S57102, S58970 and S59040).

2.2 Apparatus

The experiments were conducted using APEX 3 (Francart et al., 2008), an RME Multiface II sound card (RME, Haimhausen, Germany) and Etymotic ER-3A insert phones (Etymotic Research, Inc., Illinois, USA) which were electromagnetically shielded using CFL2 boxes from Perancea Ltd. (London, United Kingdom). The speech was always presented at 60 dBA and the setup was calibrated with a 2 cm^3 coupler (Brüel & Kjær 4152, Nærum, Denmark) using the speech weighted noise of the corresponding speech material. The experiments took place in an electromagnetically shielded and soundproofed room. To measure EEG we used an ActiveTwo EEG setup with 64 electrodes from BioSemi, (Amsterdam, Netherlands).

2.3 Behavioural experiments

Behavioural speech understanding was measured using the Flemish Matrix test (Luts et al., 2015). Each Matrix sentence consists of 5 words spoken by a female speaker and was presented to the right ear. The sentences of the Flemish Matrix test have a fixed structure of 'name verb numeral adjective object', e.g., 'Sofie ziet zes grijze pennen' ('Sophie sees six grey pens'). Each category of words has 10 possibilities. The result of the Flemish Matrix test is a word score.

Several lists of sentences were presented at a fixed SNR ranging from -12 dB SNR to 1 dB SNR (and for some participants (n = 8) also in silence). For the constant procedure, we estimated the SRT of the participants by fitting a psychometric curve through their word scores, using the formula $score = \frac{1}{1+e^{-\frac{SNR-\alpha}{\beta}}}$, with α the SRT and β the slope. For some participants (n = 10) we used an adaptive procedure (Brand and Kollmeier, 2002) in which we changed the SNR until we obtained 29%, 50% or 71% speech understanding. We considered the SNR after the last trial as the SRT at the desired level.

2.4 EEG experiments

After the behavioural experiment, we conducted the EEG experiment. The stimuli were presented with the same set-up as the behavioural experiments, with the exception that we used diotic stimulation for the EEG experiment. During the Tetris experiments, we only stimulated the right ear. We had two groups of subjects, 20 subjects did the movie experiments in which the distractor was an animated movie, 8 subjects did the Tetris exeperiments in which the distractor was the video game Tetris.

2.4.1 Speech material

We presented stimuli created by concatenating two lists of Flemish Matrix sentences (2 s per sentence) with a random gap of minimum 0.8 s and maximum 1.2 s between the sentences. The total duration of this stimulus was around 120 seconds with 80 seconds of speech. The stimulus

was presented at different SNRs (-12.5 dB SNR up to +2.5 dB SNR and without noise). Each stimulus was presented 3 times. The total duration of the experiment was 2 hours excluding breaks. To keep the subjects attentive, they could take a break when desired. Also to keep the participants attentive, we asked questions during the trials without movie or the video game about the stimuli before and after the presentation of the stimulus. The questions were typically counting tasks, e.g. 'How many times did you hear "red balls"?'. The answers were noted but were not used for further processing.

The participants in the movie experiments also listened to the children's story 'Milan', written and narrated in Flemish by Stijn Vranken (Flemish male speaker). It was approximately 15 minutes long and was presented without any noise. The purpose was to have a continuous, attended stimulus to train the linear decoder (cf. infra). The participants in the Tetris experiments listened to 'De Wilde Zwanen', written by Hans Christian Andersen and narrated in Flemish by Katrien Devos (Flemish female speaker), again it was approximately 15 minutes long and was presented without any noise.

2.4.2 Attention conditions

While listening to the Matrix sentences, the participants' attention was manipulated using three different tasks. The participants were either instructed to (1) attentively listen to the sentences, and respond to questions, (2) watch a silent movie, and (3) play a computer game. We instructed the participants not to listen to the auditory stimulus when watching the movie or when playing the computer game.

In the movie condition, we used a subtitled cartoon movie of choice by the participant. The text dialogue effectively captures attention while not interfering with auditory processing. A cartoon movie was chosen to avoid realistic lip movements, which may activate auditory brain areas (O'Sullivan et al., 2017). Navarra (2003) investigated if incongruent linguistic lip movements interfere with the perception of auditory sentences, and found that visual linguistic stimuli produced a greater interference than non-linguistic stimuli. For some subjects, we also presented a movie during a story stimulus. This story stimulus was a 15 minutes excerpt from 'De Wilde Zwanen', however it was different from the previously mentioned story stimulus.

In the computer-game condition (labelled Tetris from here on), the participants were instructed to conduct a visuospatial task, namely play the computer game Tetris, with the difficulty level set such that they were just able to play the game, and had to allocate all of their mental resources to do the task, i.e. the game required maximal effort. They controlled the game using a numeric computer keyboard. Unlike the regular Tetris game they could only move the block and rotate it, they were unable to speed it up. The difficulty level was obtained for each participant by letting them play at different levels. The time of 1 drop of a block varied from 300 ms to 100 ms. The time of the drop was adjusted per subject, it was short enough so that they had to dedicate their full attentional resources to the task. This condition was similar to the difficult visuospatial task in Roth et al. (2013a).

2.5 Signal processing

All signal processing was implemented in MATLAB R2016b (The MathWorks, Inc.).

2.5.1 Tone pips

We also presented tone pips at a frequency of 1.92 Hz as a control condition. The tone pips were analysed using an approach commonly used for ASSRs with denoising source separation (DSS) (de Cheveigné and Simon, 2008). A one-sample Hotelling T^2 test (Hotelling, 1931),

with a significance level of $\alpha = 0.05$, was used to determine if the response amplitude differed significantly from the non-synchronized neural background activity.

2.5.2 Speech

We measured neural envelope tracking by calculating the correlation between the stimulus speech envelope and the envelope reconstructed using a linear decoder.

The speech envelope was extracted from the stimulus according to Biesmans et al. (2017), who investigated the effect of envelope extraction method on auditory attention detection and found best performance for a gammatone filterbank followed by a power law. In more detail, we used a gammatone filterbank (Søndergaard and Majdak, 2013; Søndergaard et al., 2012) with 28 channels spaced by 1 equivalent rectangular bandwidth, with center frequencies from 50 Hz to 5000 Hz. From each subband we extracted the envelope by taking the absolute value of each sample and raising it to the power of 0.6. The resulting 28 subband envelopes were averaged to obtain one single envelope.

To remove short transient signals evoked by the keyboard, we blanked each sample having a higher amplitude than 500 μV. These blanked portions were linearly interpolated. To decrease processing time the EEG data and the envelope were downsampled to 256 Hz. To reduce the influence of ocular artefacts, we used a multi-channel Wiener filter (Somers et al., 2018). This spatial filter estimates the artefacts, and subtracts them from the EEG. After artefact suppression, the EEG data were re-referenced to the average of the 64 channels.

The speech envelope and EEG signal were band-pass filtered. We investigated the delta band (0.5 - 4 Hz). The same filter (a zero phase Chebyshev type 2 filter with 80 dB attenuation at 10% outside the passband) was applied to the EEG and speech envelope. After filtering, the data were further downsampled to 128 Hz.

The decoder linearly combines EEG electrode signals and their time shifted versions to optimally reconstruct the speech envelope. In the training phase, the weights to be applied to each signal in this linear combination are determined. The decoder was calculated using the mTRF toolbox (version 1.1) (Lalor et al., 2006, 2009) and applied as follows. As the stimulus evokes neural responses at different delays along the auditory pathway, we define a matrix R containing the shifted neural responses of each channel. With g the linear decoder and R the shifted neural data, the reconstruction of the speech envelope $\hat{s}(t)$ was calculated as

$$\hat{s}(t) = \sum_{n=1}^{N} \sum_{\tau} g(n, \tau) R(t + \tau, n)$$

with t the time ranging from 0 to T, n the index of the recording electrode and τ the post-stimulus integration window length used to reconstruct the envelope. The matrix g can be determined by minimizing a least-squares objective function

$$g = arg\ min\ E(|\hat{s}(t) - s(t)|^2)$$

with E the expected value, $s(t)$ the real speech envelope and $\hat{s}(t)$ the reconstructed envelope. In practice we calculated the decoder by solving

$$g = (RR^T)^{-1}(RS^T)$$

with S a vector of stimulus envelope samples. The decoder was calculated using ridge regression on the inverse autocorrelation matrix. We used post-stimulus lags of 0 - 500 ms.

We trained a new decoder for each subject on the story stimulus, which was 15 minutes long. After training, the decoder was applied on the EEG responses to the Flemish Matrix

material. To measure the correspondence between the speech envelope and its reconstruction, we calculated the bootstrapped Spearman correlation between the real and reconstructed envelope. Bootstrapping was applied by Monte Carlo sampling of the two envelopes.

We also estimated the temporal response function on the stories and on the Matrix sentences. This is similar to the calculation of the decoder with the exception that we predict EEG instead of reconstructing the envelope.

3 Results

3.1 Behavioural speech understanding

For each subject, we fitted a psychometric curve on the SNR versus percentage correct score and estimated the corresponding SRT and slope. The average SRT is -8.03 dB SNR (standard deviation: 1.27 dB) with an average slope of 14.1 %/dB (standard deviation: 3.4 %/dB).

3.2 Tone pips

In addition to continuous speech, we also evaluated the responses to non-speech sounds. All participants had a significant ASSR in the first DSS component, indicating measurable cortical responses to sound.

3.3 Neural responses to speech

3.3.1 Effect of SNR and attention

Figures 1a and 1b show neural envelope tracking in function of SNR using respectively a 0 - 75 ms and a 0 - 500 ms integration window in the delta band (0.5 - 4 Hz) for the 3 conditions: maximal attention, watching a movie and playing Tetris. As we tested a wide variety of SNRs, we clustered the SNRs using k-means clustering in 7 clusters[1]. When multiple correlations per SNR were present, the average was taken. Visual assessment shows a systematic increase in neural tracking with SNR (related to intelligibility), most clearly in the attention and movie conditions. Indeed, the Spearman correlations between SNR and neural envelope tracking for the attention, movie and Tetris condition using a 0 - 75 ms integration window in the decoder are respectively: 0.38 ($p < 0.001$), 0.52 ($p < 0.001$) and 0.15 ($p = 0.072$). Using a 0 - 500 ms integration window they are respectively: 0.36 ($p < 0.001$), 0.48 ($p < 0.001$) and 0.12 ($p = 0.135$).

Using a 0 - 75 ms integration window, we found a significant difference in neural envelope tracking between the attention and movie condition at -9.1 dB SNR and at -6.6 dB SNR using the Wilcoxon rank-sum test ($p = 0.016$ and $p = 0.019$). Using a 0 - 500 ms integration window, we found a significant difference between the attention and movie condition at -11.3 dB SNR, at -9.1 dB SNR and at -6.6 dB SNR, ($p = 0.032$, $p = 0.004$, and $p = 0.024$). We did not find a significant difference in neural envelope tracking between the attention condition and the Tetris condition. As we hypothesised that the movie condition would have lower variance than the attention condition, we compared the variance of the neural envelope tracking per SNR. However, while such a trend seens to be present when visually assessing the size of the whiskers in the box plots, using a Brown-Forsythe test, we found no significant differences in spread between attention and movie or attention and Tetris.

---

[1]The maximal deviation between the shown SNR and the actual SNR was 2.5 dB.

(a) Neural envelope tracking in function of SNR in the delta band (0.5 - 4 Hz) using a 0 - 75 ms integration window.

(b) Neural envelope tracking in function of SNR in the delta band (0.5 - 4 Hz) using a 0 - 500 ms integration window.

Figure 1: Neural envelope tracking in function of SNR for multiple integration windows.

As the attention and watching condition show the expected increase of neural envelope tracking with SNR, we conducted a similar analysis as the behavioural data and attempted to estimate the SRT by fitting a psychometric function on the envelope tracking versus SNR data. We used the same psychometric curve as for the behavioural data with the exception that the guess-rate and lapse-rate were not fixed. Across subjects, for the attention condition we found an SRT of -9.15 dB SNR (95% confidence interval [-9.34; -8.96] dB SNR). For the watching condition we found an SRT of -6.96 dB SNR (95% confidence interval [-8.57; -5.35] dB SNR). Compare to the behaviourally measured SRT of -8.03 dB SNR. As the Tetris data show a huge variability, we did not attempt to estimate the SRT in this condition.

3.3.2 Difference in topographies

Figure 2 shows the difference in TRF between the attention and movie condition. After a cluster-based analysis, no significant clusters were found for the story data. The Matrix data however shows a significant difference. The difference from 141 ms to 188 ms is most pronounced in the right-frontal region. The actual TRFs for this interval are shown in Figure 3 and Figure 4. The TRFs are the average of the subject-specific TRFs.

Figure 2: The difference of the topography of the attention condition and the movie condition for the matrix data with a 0 - 500 ms integration window and unfiltered data. The channels part of significant cluster are indicated in bold.

Figure 3: Topography of the attention condition using the Matrix data between 141 - 203 ms.

Figure 4: Topography of the movie condition using the Matrix data between 141 - 203 ms.

3.3.3 Difference between TRFs

To better understand why the topographies are different, we averaged the channels contributing most to the difference and did a cluster-based analysis on this TRF. Figures 5a and 5b show the TRFs for the attention and the movie condition for both the story and the Matrix sentences using a 0 - 500 ms integration window and unfiltered data. 9 participants listened attentively to a story, while in another condition they listened passively to a story while watching a movie. 17 participants did the same for the Matrix sentences. We did a cluster-based analysis to find differences between the TRFs of the two attention conditions (Maris and Oostenveld, 2007).

We did not investigate the Tetris results as more artefacts are present in this dataset and the number of subjects was too limited to estimate good TRFs.

(a) The TRF of the attention and the movie condition for the story using a 0 - 500 ms integration window and unfiltered data. The TRFs are not significantly different.

(b) The TRF of the attention and the movie condition for the Matrix sentences using a 0 - 500 ms integration window and unfiltered data. The TRFs are significantly different, the difference is most pronounced from 141 - 188 ms.

Figure 5: The TRFs for both the Matrix and story stimulus for the attention and movie condition.

4 Discussion

We investigated the effect of attention on neural envelope tracking, in conditions of maximal attention, watching a silent cartoon movie, and playing Tetris at a difficult level. To gain insight in the neural origin of the differences, we estimated TRFs and investigated their time course and topography.

4.1 Effect of task and SNR

At low SNRs, and therefore lower levels of speech intelligibility, we found higher levels of neural envelope tracking in the attention condition than in the movie condition. This is consistent with the notion that attention results in the requirement of additional neural resources. The difference in envelope tracking between attention and movie was not visible at higher SNRs, possibly because participants could easily resort to passive listening in these conditions. At low SNRs, passive listening was not possible and the extensive resources needed for active listening were not available due to engagement with the movie. In contrast with our results, Kong et al. (2014) found no significant difference between active and passive listening. This can be explained by the number of participants or the stimulus type. Kong et al. (2014) used 8 participants and a story stimulus, while we have 17 participants for the Matrix condition. The higher amount of subjects gives us more statistical power and Matrix sentences have a very rigid structure compared to a story which may also reduce variance across participants. Similar to their results, we did not found a significant difference using the story where we used only 9 subjects.

Apart from the level of neural envelope tracking, its relation with SNR and thus speech intelligibility is also important. We saw a consistent increase in neural envelope tracking with SNR for both the attended condition and the movie condition. Unexpectedly, in the movie condition the correlation between SNR and neural level tracking was higher than in the attended condition. We hypothesize that while attention yields higher levels of envelope tracking, it is hard for the subjects to remain fully concentrated during the entire experiment. Therefore, while the movie condition yielded lower envelope tracking levels, it might also have yielded more *stable* attention, leading to less variability between SNR conditions and therefore a higher correlation between SNR and envelope tracking.

In the Tetris condition we found no significant correlation between neural tracking and the SNR. This may be because the resources of the participant were exhausted or because of motion artefacts introduced by playing Tetris reducing the EEG signal quality.

4.2 Neural sources related with attention

The literature shows that attentional modulation originates from the parietal cortex and prefrontal cortex (Yantis, 2008; Lavie, 2010a). To investigate this, we assessed the spatial maps of the TRFs for both the attention and movie condition. We found that the difference between the attended TRF and the movie TRF was most pronounced in the right, frontal region which is supported by other research (Alho, 2007).

4.3 Effect of latency

In the literature, using the competing talker paradigm, responses earlier than 75 ms are minimally affected by attention while later responses much more so (Snyder et al., 2006; Ross et al., 2009; Choi et al., 2014; Das et al., 2016; Puvvada and Simon, 2017). Using the forward model, we found a significant difference between the attention and movie TRF. This difference was most pronounced from 141 ms to 188 ms. This is in line with the competing talker literature. Moreover,

the attended TRF morphology is similar to LAEP literature, showing a P1 peak at 50 ms, N1 peak at 80 ms and a P2 peak at 160 ms. The movie TRF is similar with the exception that the P2 peak is less pronounced. Although the TRF at earlier latencies (< 75 ms) does not significantly differ between attention and movie TRF, we still find a significant difference in correlation at some low SNRs.

4.4 Distractors

When studying the effect of attention on neural envelope tracking, the difficulty is that there is no reference of the level of attention. Therefore one needs to resort to on the one hand ways to motivate the subject to focus solely on the task at hand (attentively listening to sentences), or on the other hand distract the participants from the task in a controlled way. The latter can be achieved by instructing the participants to ignore the stimulus and providing another task to distract them.

There is a body of research on attention and distraction in auditory and visual tasks. However, most of the literature is focused on how various secondary tasks can distract from a primary task (Murphy et al., 2017; Lavie, 2010b, 2005).

We chose two distractor tasks. One was a subtitled cartoon movie. The benefit is that it is engaging and relaxing for the participant. A potential downside is that reading the subtitles requires language processing, which is a resource also required for processing the auditory stimulus. Subtitles are a distractor but maybe they only have a small perceptual load. Another downside is that a movie does not exhaust the available attentional resources of the participants. The other task was the computer game Tetris, which is a visuospatial task (Hein et al., 2007). The benefit is that is engaging and does not require language processing, but it is tiring for the participant. In both conditions, the participants were instructed to watch the movie or play Tetris while ignoring the auditory stimulus. However, especially during the movie, this is difficult to enforce and to quantify how well the participants did.

Murphy et al. (2017) reviewed the literature regarding perceptual load in the auditory domain. A key point of perceptual load theory is that it proposes that our perceptual system has limited processing capacity, and that it is beyond our volitional control as to how much of that capacity will be engaged at any given time. Instead, all of the available information is automatically processed until an individual's perceptual capacity is exhausted. While this theory is confirmed by many experiments in the purely visual domain, it is less clear in the auditory domain. It seems that the auditory system, with its complicated auditory stream segregation (Shinn-Cunningham, 2008) allows for a less strong selection mechanism. While generally unattended information receives less or no processing, this is not consistently the case. The envelope tracking results with the competing talker paradigm (cf. supra) confirm this and this is also consistent with our results. In the movie TRF, we see that the auditory stimulus is still processed by the brain. However, later processing (from 140 ms on) is reduced.

A concern with using concurrent auditory stimuli to distract from the stimulus of interest is that auditory stream segregation might fail, especially if the listener has an unknown hearing deficit. Therefore a distractor in a non-auditory domain may be desirable. There is some evidence that perceptual load theory also holds across modalities. Macdonald and Lavie (2011); Raveh and Lavie (2015) demonstrated inattentional deafness (failure to notice an auditory stimulus) under visual load, thereby extending the load theory of attention across the auditory and visual modalities, making it clear that vision and audition share a common processing resource, which is consistent with our results. In the movie condition, we saw no P2 peak in the TRF. Also at low SNRs (< -6.6 dB SNR) we found higher neural envelope tracking in the attention condtion compared with the movie condition. The Tetris condition did not lead to significant differences

compared to the attention condition. This may be due to the muscle artefacts obscuring potential effects that were present in the EEG.

4.5 Implications for applied research - Neural envelope tracking as a measure of speech understanding

The stimulus reconstruction method is promising to obtain an objective measure of speech understanding for applications in diagnostics of hearing. Ding and Simon (2013) found a significant correlation between intelligibility and reconstruction accuracy at one signal stimulus SNR. Vanthornhout et al. (2018); Lesenfants et al. (2018) developed a clinically applicable method to objectively estimate the SRT based on reconstruction accuracy, and found a significant correlation between predicted and actual speech reception threshold. In the current study, the average SRT using a behavioural test was -8.03 dB SNR, using the stimulus reconstruction method we found an SRT of -9.15 dB SNR in the attention condition and an SRT of -6.96 dB SNR in the movie condition. Both objective methods are thus close to the behavioural method. The rank order of these SRT values also makes intuitive sense: when paying maximal attention, and estimating the SRT based on envelope tracking, the lowest value (best performance) is obtained. In the behavioural experiment, the subjects' neural resources are taxed more, because they need to repeat each sentence, leading to a slightly higher SRT. Finally, when not paying attention to the stimulus, the SRT reaches its highest value.

We found that neural envelope tracking was better correlated with SNR in the movie condition, which is important for the estimation of the SRT. While the level of attention influenced the level of neural tracking, to obtain an objective measure of speech understanding it may be more important to have stable attention and thus lower variability, than to have high levels of neural envelope tracking. Equalising the level of attention across subjects and conditions by giving them an unrelated and/or easy task, such as watching a movie might therefore yield the best results. Giving them a difficult, fully engaging task, such as Tetris detrimentally reduces neural envelope tracking, making it impossible to estimate speech intelligibility.

In addition to procedural benefits, an additional benefit of letting subjects watch a movie instead of attending to low-content sentences, is that it is much more pleasant for the subjects, and therefore easier to implement in the clinic, especially in populations such as children.

5 Conclusion

Using a video game or a movie, we varied the level of attention while we estimated the neural envelope tracking. Neural envelope tracking was significantly different between the condition with maximal attention and the movie condition. This difference is most pronounced in the right-frontal region of the brain. However, this does not seem to be a problem for estimating speech understanding as neural envelope tracking is still highly correlated with the stimulus SNR, even more in the movie condition. In the video game condition, this correlation was absent, probably because no resources were left to even passively listen to the stimulus.

6 Acknowledgements

The authors thank Lise Goris, Lauren Commers, Paulien Vangompel and Lies Van Dorpe for their help with the data acquisition. Financial support was provided by the KU Leuven Special Research Fund under grant OT/14/119 to Tom Francart. Research funded by a PhD grant of the Research Foundation Flanders (FWO). This project has received funding from the European Research Council (ERC) under the European Union's Horizon 2020 research and innovation programme (grant agreement No 637424), from the YouReCa Junior Mobility Programme under grant JUMO/15/034 to Jonas Vanthornhout. The authors declare that they have no conflict of interest.

References

Alho, K.
  2007. Brain activity during selective listening to natural speech. *Frontiers in Bioscience*, 12(8-12):3167.

Astheimer, L. B. and L. D. Sanders
  2009. Listeners modulate temporally selective attention during natural speech processing. *Biological Psychology*, 80(1):23–34.

Bidet-Caulet, A., C. Mikyska, and R. T. Knight
  2010. Load effects in auditory selective attention: Evidence for distinct facilitation and inhibition mechanisms. *Neuroimage*, 50(1):277–284.

Biesmans, W., N. Das, T. Francart, and A. Bertrand
  2017. Auditory-Inspired Speech Envelope Extraction Methods for Improved EEG-Based Auditory Attention Detection in a Cocktail Party Scenario. *IEEE Transactions on Neural Systems and Rehabilitation Engineering*, 25(5):402–412.

Braiman, C., E. A. Fridman, M. M. Conte, H. U. Voss, C. S. Reichenbach, T. Reichenbach, and N. D. Schiff
  2018. Cortical Response to the Natural Speech Envelope Correlates with Neuroimaging Evidence of Cognition in Severe Brain Injury. *Current Biology*, 28(23):3833–3839.e3.

Brand, T. and B. Kollmeier
  2002. Efficient adaptive procedures for threshold and concurrent slope estimates for psychophysics and speech intelligibility tests. *The Journal of the Acoustical Society of America*, 111(6):2801–2810.

Brix, R.
1984. The Influence of Attention on the Auditory Brain Stem Evoked Responses Preliminary Report. *Acta Oto-Laryngologica*, 98(1-2):89–92.

Cherry, E. C.
1953. Some Experiments on the Recognition of Speech, with One and with Two Ears. *The Journal of the Acoustical Society of America*, 25(5):975–979.

Choi, I., L. Wang, H. Bharadwaj, and B. Shinn-Cunningham
2014. Individual differences in attentional modulation of cortical responses correlate with selective attention performance. *Hearing research*, 314:10–19.

Das, N., A. Bertrand, and T. Francart
2018. EEG-based auditory attention detection: Boundary conditions for background noise and speaker positions. *Journal of Neural Engineering*, 15(6):066017.

Das, N., W. Biesmans, A. Bertrand, and T. Francart
2016. The effect of head-related filtering and ear-specific decoding bias on auditory attention detection. *J Neural Eng*, 13(5):056014.

de Cheveigné, A. and J. Z. Simon
2008. Denoising based on spatial filtering. *Journal of Neuroscience Methods*, 171(2):331–339.

Ding, N. and J. Z. Simon
2012. Emergence of neural encoding of auditory objects while listening to competing speakers. *Proceedings of the National Academy of Sciences*, 109(29):11854–11859.

Ding, N. and J. Z. Simon
2013. Adaptive Temporal Encoding Leads to a Background-Insensitive Cortical Representation of Speech. *J. Neurosci.*, 33(13):5728–5735.

Forte, A. E., O. Etard, and T. Reichenbach
2017. The human auditory brainstem response to running speech reveals a subcortical mechanism for selective attention. *eLife*, 6:e27203.

Francart, T., A. van Wieringen, and J. Wouters
2008. APEX 3: a multi-purpose test platform for auditory psychophysical experiments. *Journal of Neuroscience Methods*, 172(2):283 – 293.

Fritz, J. B., M. Elhilali, S. V. David, and S. A. Shamma
2007. Auditory attention—focusing the searchlight on sound. *Current Opinion in Neurobiology*, 17(4):437–455.

Galbraith, G. C., D. M. Olfman, and T. M. Hu
2003. Selective attention a¡ects human brain stem frequency-following response. *Neuroreport*, P. 4.

Hein, G., A. Alink, A. Kleinschmidt, and N. G. Müller
2007. Competing Neural Responses for Auditory and Visual Decisions. *PLoS One*, 2(3):e320.

Hillyard, S. A., R. F. Hink, V. L. Schwent, and T. W. Picton
1973. Electrical Signs of Selective Attention in the Human Brain. *Science, New Series*, 182(4108):177–180.

Hoormann, J., M. Falkenstein, and J. Hohnsbein
    2000. Early attention effects in human auditory-evoked potentials. *Psychophysiology*, P. 14.

Hotelling, H.
    1931. The Generalization of Student's Ratio. *Ann. Math. Statist.*, 2(3):360–378.

Kong, Y.-Y., A. Mullangi, and N. Ding
    2014. Differential modulation of auditory responses to attended and unattended speech in different listening conditions. *Hearing Research*, 316:73–81.

Lalor, E. C., B. A. Pearlmutter, R. B. Reilly, G. McDarby, and J. J. Foxe
    2006. The vespa: a method for the rapid estimation of a visual evoked potential. *Neuroimage*, 32(4):1549–1561.

Lalor, E. C., A. J. Power, R. B. Reilly, and J. J. Foxe
    2009. Resolving Precise Temporal Processing Properties of the Auditory System Using Continuous Stimuli. *Journal of Neurophysiology*, 102(1):349–359.

Lavie, N.
    2005. Distracted and confused?: Selective attention under load. *Trends Cogn. Sci.*, 9(2):75–82.

Lavie, N.
    2010a. Attention, Distraction, and Cognitive Control Under Load. *Current Directions in Psychological Science*, 19(3):143–148.

Lavie, N.
    2010b. Attention, Distraction, and Cognitive Control Under Load. *Curr. Dir. Psychol. Sci.*, 19(3):143–148.

Lehmann, A. and M. Schönwiesner
    2014. Selective Attention Modulates Human Auditory Brainstem Responses: Relative Contributions of Frequency and Spatial Cues. *PLoS ONE*, 9(1):e85442.

Lesenfants, D., J. Vanthornhout, E. Verschueren, L. Decruy, and T. Francart
    2018. Predicting individual speech intelligibility from the neural tracking of acoustic- and phonetic-level speech representations. *bioRxiv*.

Linden, R. D., T. W. Picton, G. Hamel, and K. B. Campbell
    1987. Human auditory steady-state evoked potentials during selective attention. *Electroencephalography and Clinical Neurophysiology*, 66(2):145–159.

Luts, H., S. Jansen, W. Dreschler, and J. Wouters
    2015. Development and normative data for the flemish/dutch matrix test. Technical report.

Macdonald, J. S. P. and N. Lavie
    2011. Visual perceptual load induces inattentional deafness. *Attention, Perception, Psychophys.*, 73(6):1780–1789.

Maris, E. and R. Oostenveld
    2007. Nonparametric statistical testing of EEG- and MEG-data. *Journal of Neuroscience Methods*, 164(1):177–190.

Melara, R. D., A. Rao, and Y. Tong
  2002. The duality of selection: excitatory and inhibitory processes in auditory selective attention. *Journal of Experimental Psychology: Human Perception and Performance*, 28(2):279.

Mirkovic, B., S. Debener, M. Jaeger, and M. De Vos
  2015. Decoding the attended speech stream with multi-channel EEG: Implications for online, daily-life applications. *Journal of Neural Engineering*, 12(4):046007.

Müller, N., W. Schlee, T. Hartmann, I. Lorenz, and N. Weisz
  2009. Top-Down Modulation of the Auditory Steady-State Response in a Task-Switch Paradigm. *Frontiers in Human Neuroscience*, 3.

Murphy, S., C. Spence, and P. Dalton
  2017. Auditory perceptual load: A review. *Hear. Res.*, 352:40–48.

Näätänen, R., T. Kujala, and I. Winkler
  2011. Auditory processing that leads to conscious perception: A unique window to central auditory processing opened by the mismatch negativity and related responses. *Psychophysiology*, 48(1):4–22.

Navarra, J.
  2003. Visual speech interference in an auditory shadowing task: the dubbed movie effect. In *Proc. 15th International Congress of Phonetic Sciences, Barcelona, Spain*, Pp. 1–4.

O'Sullivan, J. A., A. J. Power, N. Mesgarani, S. Rajaram, J. J. Foxe, B. G. Shinn-Cunningham, M. Slaney, S. A. Shamma, and E. C. Lalor
  2015. Attentional Selection in a Cocktail Party Environment Can Be Decoded from Single-Trial EEG. *Cerebral Cortex*, 25(7):1697–1706.

O'Sullivan, A. E., M. J. Crosse, G. M. Di Liberto, and E. C. Lalor
  2017. Visual cortical entrainment to motion and categorical speech features during silent lipreading. *Frontiers in human neuroscience*, 10:679.

Picton, T. W. and S. A. Hillyard
  1974. Human auditory evoked potentials. II: Effects of attention. *Electroencephalography and Clinical Neurophysiology*, 36:191–200.

Puvvada, K. C. and J. Z. Simon
  2017. Cortical representations of speech in a multitalker auditory scene. *Journal of Neuroscience*, 37(38):9189–9196.

Raveh, D. and N. Lavie
  2015. Load-induced inattentional deafness. *Attention, Perception, Psychophys.*, 77(2):483–492.

Regenbogen, C., M. D. Vos, S. Debener, B. I. Turetsky, C. Mößnang, A. Finkelmeyer, U. Habel, I. Neuner, and T. Kellermann
  2012. Auditory Processing under Cross-Modal Visual Load Investigated with Simultaneous EEG-fMRI. *PLOS ONE*, 7(12):e52267.

Ross, B., S. A. Hillyard, and T. W. Picton
  2009. Temporal dynamics of selective attention during dichotic listening. *Cerebral Cortex*, 20(6):1360–1371.

Ross, B., T. W. Picton, a. T. Herdman, and C. Pantev
  2004. The effect of attention on the auditory steady-state response. *Neurol. Clin. Neurophysiol.*, 2004(September):22.

Roth, C., C. N. Gupta, S. M. Plis, E. Damaraju, S. Khullar, V. Calhoun, and D. A. Bridwell
  2013a. The influence of visuospatial attention on unattended auditory 40 Hz responses. *Frontiers in Human Neuroscience*, 7.

Roth, C., C. N. Gupta, S. M. Plis, E. Damaraju, S. Khullar, V. D. Calhoun, and D. A. Bridwell
  2013b. The influence of visuospatial attention on unattended auditory 40 Hz responses. *Front Hum Neurosci*, 7:370.

Shinn-Cunningham, B. G.
  2008. Object-based auditory and visual attention. *Trends in Cognitive Sciences*, 12(5):182–186.

Skosnik, P. D., G. P. Krishnan, and B. F. O'Donnell
  2007. The effect of selective attention on the gamma-band auditory steady-state response. *Neuroscience Letters*, 420(3):223–228.

Snyder, J. S., C. Alain, and T. W. Picton
  2006. Effects of attention on neuroelectric correlates of auditory stream segregation. *Journal of cognitive neuroscience*, 18(1):1–13.

Somers, B., T. Francart, and A. Bertrand
  2018. A generic EEG artifact removal algorithm based on the multi-channel Wiener filter. *Journal of Neural Engineering*, 15(3):036007.

Søndergaard, P. L., B. Torrésani, and P. Balazs
  2012. The Linear Time Frequency Analysis Toolbox. *International Journal of Wavelets, Multiresolution Analysis and Information Processing*, 10(4).

Søndergaard, P. and P. Majdak
  2013. The auditory modeling toolbox. In *The Technology of Binaural Listening*, J. Blauert, ed., Pp. 33–56. Berlin, Heidelberg: Springer.

Vanthornhout, J., L. Decruy, J. Wouters, J. Z. Simon, and T. Francart
  2018. Speech intelligibility predicted from neural entrainment of the speech envelope. *J. Assoc. Res. Otolaryngol.*, in press.

Varghese, L., H. M. Bharadwaj, and B. G. Shinn-Cunningham
  2015. Evidence against attentional state modulating scalp-recorded auditory brainstem steady-state responses. *Brain Research*, 1626:146–164.

Yantis, S.
  2008. The Neural Basis of Selective Attention. *Current directions in psychological science*, 17(2):86–90.