Title:

Sequential compression of gene expression across dimensionalities and methods reveals

no single best method or dimensionality

Authors:

Gregory P. Way[1,2,3] (0000-0002-0503-9348), Michael Zietz[2] (0000-0003-0539-630X),

Vincent Rubinetti[2] (0000-0002-4655-3773), Daniel S. Himmelstein[2] (0000-0002- 3012-

7446) and Casey S. Greene[2*] (0000-0001-8713-9213)

Affiliations:

[1]Genomics and Computational Biology Graduate Group, Perelman School of Medicine,

University of Pennsylvania, Philadelphia, PA 19104, USA.

[2]Department of Systems Pharmacology and Translational Therapeutics, University of

Pennsylvania, Philadelphia, PA 19104, USA.

[3]Imaging Platform, Broad Institute of MIT and Harvard, Cambridge, MA 02142, USA.

Corresponding Author:

Casey S. Greene

10-131 SCTR 34[th] and Civic Center Blvd,

Philadelphia, PA 19104

Office: 215-573-2991

Fax: 215-573-9135

Keywords:

Machine Learning, Dimensionality Reduction, Latent Space, Gene Expression,

Autoencoders, Compression, Neural Network Interpretation

Abstract:

Background

Unsupervised compression algorithms applied to gene expression data extract latent, or hidden, signals representing technical and biological sources of variation. However, these algorithms require a user to select a biologically-appropriate latent dimensionality. In practice, most researchers select a single algorithm and latent dimensionality. We sought to determine the extent by which using multiple dimensionalities across ensemble compression models improves biological representations.

Results

We compressed gene expression data from three large datasets consisting of adult normal tissue, adult cancer tissue, and pediatric cancer tissue. We compressed these data into many latent dimensionalities ranging from 2 to 200. We observed various tradeoffs across latent dimensionalities and compression models. For example, we observed high model stability between principal components analysis (PCA), independent components analysis (ICA), and non-negative matrix factorization (NMF). We identified more unique biological signatures in ensembles of denoising autoencoder (DAE) and variational autoencoder (VAE) models in intermediate latent dimensionalities. However, we captured the most pathway-associated features using all compressed features across algorithms and dimensionalities. Optimized at different latent dimensionalities, compression models detect generalizable gene expression signatures representing sex, neuroblastoma MYCN amplification, and cell types. In two

supervised machine learning tasks, compressed features optimized predictions at different

latent dimensionalities.

Conclusions

There is no single best latent dimensionality or compression algorithm for analyzing

gene expression data. Instead, using feature ensembles from different compression models

across latent space dimensionalities optimizes biological representations.

Background:

Dimensionality reduction algorithms compress input data into feature representations

that capture sources of variation. Applied to gene expression data, compression algorithms can

identify latent biological representations and technical processes. These biological

representations reveal important information about the samples and can help to generate

hypotheses that are difficult or impossible to observe in the original genomic space. For

example, applying PCA to a large cancer transcriptomic compendium determined the influence

of copy number alterations on gene expression measurements [1]. Applying ICA to

transcriptome data aggregated gene modules representing core pathways and hidden

transcriptional programs [2,3]. Training NMF models using bulk gene expression data estimated

cell type proportion [4,5]. DAEs have revealed latent signals characterizing oxygen exposure

and transcription factor targets [6,7], and VAEs have identified biologically relevant latent

features that discriminate cancer subtypes and drug response [8,9]. Additional latent variable

approaches have been used to detect and remove technical artifacts, including batch effects

[10,11]. Here, we focus on using compression to identify biological representations by analyzing

processed data with batch effect already mitigated. Nevertheless, a major challenge to all

compression applications is the fundamental requirement that a researcher must determine

the number of latent dimensions (k) to compress input data.

Instead, it is possible that different biological signatures are best captured at different

latent space dimensionalities. To test this, we trained and evaluated various compression

models across a wide range of latent space dimensionalities, from $k = 2$ to $k = 200$. We train

PCA, ICA, NMF, DAE, and VAE models using RNAseq gene expression data. We selected these

methods because they are either widely established in practice (PCA, NMF) or use neural

networks that are rapidly growing in popularity (DAE, VAE). We included ICA to compare against

PCA: it has been used in practice [7] and also allows us to compare multiple rotations of the

low-dimensional space. We applied these methods to three different datasets. We applied

these methods to three different datasets: The Cancer Genome Atlas (TCGA) PanCanAtlas [12],

the Genome Tissue Expression Consortium Project (GTEx) [13], and the Therapeutically

Applicable Research To Generate Effective Treatments (TARGET) Project [14].

We demonstrate various model tradeoffs in reconstruction cost, stability, and gene set

coverage in training and testing sets across datasets, algorithms, and latent dimensionalities.

We observe that several distinct gene expression signatures are optimized in various models

spanning low, intermediate, and high latent dimensionalities. Our primary finding is that there

is no single algorithm or dimensionality that is best for all purposes: Instead, using various

latent dimensionalities and algorithms optimizes biological representations. Those who plan to

apply these algorithms may consider training multiple models over multiple dimensionalities to

avoid missing important biological features.

We name this sequential compression approach "BioBombe" after the large mechanical

device developed by Alan Turing and other cryptologists in World War II to decode encrypted

messages sent by Enigma machines. Using the BioBombe approach, we compress gene

expression input data with multiple latent dimensionalities to decipher and enhance biological

representations embedded within compressed gene expression features.

Results:

BioBombe implementation

We compressed processed RNAseq data from TCGA, GTEx, and TARGET using PCA, ICA,

NMF, DAE, and VAE across 28 different latent dimensionalities (k) ranging from $k = 2$ to $k = 200$.

We split each dataset into 90% training and 10% test sets balanced by cancer type or tissue

type and trained models using only the training data. We used real and permuted data and

initialized each model five times per latent dimensionality resulting in a total of 4,200 different

compression models (**Additional File 1: Figure S1**). We evaluated hyperparameters for DAE and

VAE models across dimensionalities and trained models using optimized parameter settings

(**Additional File 2**; **Additional File 1: Figure S2**). See **Fig. 1** for an outline of our approach. We

provide full BioBombe results for all compression models across datasets for both real [15–17]

and permuted data [18–20] in both training and test sets as publicly available resources (see

https://greenelab.github.io/BioBombe/).

107

Figure 1: *Overview of the BioBombe approach.* We implemented BioBombe on three datasets
using five different algorithms. We sequentially compressed input data into various latent
dimensionalities. We calculated various metrics that describe different benefits and trade-offs
of the algorithms. Lastly, we implemented a network projection approach to interpret the
compressed latent features. We used MSigDB collections and xCell gene sets to interpret
compressed features.
114

Assessing compression algorithm reconstruction

Reconstruction cost, a measurement of the difference between the input and output

matrices, is often used to describe the ability of compression models to capture fundamental

processes in latent space features that recapitulate the original input data. We tracked the

reconstruction cost for the training and testing data partitions for all datasets, algorithms,

latent dimensionalities, and random initializations. As expected, we observed lower

reconstruction costs in models trained with real data and with higher latent dimensionalities

(**Additional File 1: Figure S3**). Because PCA and ICA are rotations of one another, we used their

identical scores as a positive control. All the compression algorithms had similar reconstruction

costs, with the highest variability existing in low latent dimensionalities (**Additional File 1:**

Figure S3).

Evaluating model stability and similarity within and across latent dimensionalities

We applied singular vector canonical correlation analysis (SVCCA) to algorithm weight

matrices to assess model stability within algorithm initializations, and to determine model

similarity between algorithms [21]. Briefly, SVCCA calculates similarity between two

compression algorithm weight matrices by learning appropriate linear transformations and

iteratively matching the highest correlating features. Training with TCGA data, we observed

highly stable models within algorithms and within all latent dimensionalities for PCA, ICA, NMF

(along the matrix diagonal in **Fig 2a**). VAE models were also largely stable, with some decay in

higher latent dimensionalities. However, DAE models were unstable, particularly at low latent

dimensionalities (**Fig 2a**). We also compared similarity across algorithms. Because PCA and ICA

are rotations of one another, we used the high stability as a positive control for SVCCA

estimates. NMF was also highly similar to PCA and ICA, particularly at low latent

dimensionalities (**Fig. 2a**). VAE models were more similar to PCA, ICA, and NMF than DAE

models, particularly at low latent dimensionalities, and the instability patterns within DAE

models also led to large differences across algorithms (**Fig. 2a**). We observed similar patterns in

GTEx and TARGET data, despite TARGET containing only about 700 samples (**Additional File 1:**

Figure S4).

Figure 2: *Assessing algorithm and dimensionality stability with singular vector canonical correlation analysis (SVCCA).* **(a)** SVCCA applied to the weight matrices learned by each compression algorithm in gene expression data from The Cancer Genome Atlas (TCGA). The mean of all canonical correlations comparing independent iterations is shown. The distribution of mean similarity represents a comparison of all pairwise iterations within and across algorithms. The upper triangle represents SVCCA applied to real gene expression data, while the lower triangle represents permuted expression data. Both real and permuted data are plotted along the diagonal. **(b)** Mean correlations of all iterations within algorithms but across k dimensionalities. SVCCA will identify min(i, j) canonical vectors for latent dimensionalities k_i and k_j. The mean of all pairwise correlations is shown for all combinations of k dimensionalities.

We also used SVCCA to compare the similarity of weight matrices across latent

dimensionalities. Both PCA and ICA found highly similar solutions (**Fig. 2b**). This is expected

since the solutions are deterministic and are arranged with decreasing amounts of variance.

NMF also identified highly similar solutions in low dimensionalities, but solutions were less

similar in higher dimensionalities. DAE solutions were the least similar, with intermediate

dimensionalities showing the lowest mean similarity. VAE models displayed relatively high

model similarity, but there were regions of modest model stability in intermediate and high

dimensionalities (**Fig. 2b**). We observed similar patterns in GTEx and TARGET data (**Additional**

File 1: Figure S5).

BioBombe features capture various gene expression representations across different latent

dimensionalities

We tested the ability of features derived using the BioBombe approach to isolate

various biological representations. First, we tested the ability to differentiate sample sex; which

has been previously observed to be captured in latent space features [8,22,23]. We performed

a two-tailed t-test comparing male and female samples in the GTEx test set across all

initializations, algorithms, and latent dimensionalities. We optimally identified this phenotype

in higher latent dimensionalities, particularly in NMF and VAE models (**Fig. 3a**). The top feature

separating GTEx males and females was NMF feature 111 in $k = 200$ ($t = 44.5$, $p = 7.3 \times 10^{-176}$)

(**Fig 3b**). We examined the genes that contribute with high weight to this feature and found

only three genes had substantial influence. These three genes all had high positive weights and

were encoded on the Y chromosome. We performed the same approach using BioBombe

features to identify sex features in TCGA test data (**Fig. 3c**). The top latent dimensionality

identified was not consistent across algorithms. The top feature distinguishing TCGA males and

females was ICA feature 53 in the k = 90 model (t = 4.9, p = 2.0 x 10^{-6}) (**Fig. 3d**). The separation

was not as strong using the more complex TCGA data, but the top 10 gene weights were all

encoded on the X chromosome.

We also tested the ability of features derived from the BioBombe approach to

distinguish MYCN amplification in neuroblastoma (NBL) tumors. MYCN amplification is a

biomarker associated with poor prognosis in NBL patients [24]. We performed a two-tailed t-

test comparing MYCN amplified vs. MYCN not amplified NBL tumors for each of the latent

features derived from the full set of TARGET samples. Each algorithm discovered optimal signal

at various latent dimensionalities, but the top scoring features were generally identified in VAE

and NMF models with large latent space dimensionalities (**Fig. 3e**). Although there were some

potentially mischaracterized samples, feature 12 in VAE k = 50 robustly separated MYCN

amplification status in NBL tumors (t = -18.5, p = 6.6 x 10^{-38}) (**Fig. 3f**). This feature also

distinguished MYCN amplification status in NBL cell lines [25] that were previously not used in

training the compression model or for feature selection (t = -3.2, p = 4.2 x 10^{-3}) (**Fig. 3g**).

Figure 3: *Using BioBombe as a signature discovery tool.* Detecting GTEx sample sex across **(a)** various latent dimensionalities and algorithms, and **(b)** the latent feature with the highest enrichment. Detecting TCGA patient sex across **(c)** various latent dimensionalities, and **(d)** the latent feature with the highest enrichment. Detecting TARGET MYCN amplification in neuroblastoma (NBL) tumors **(e)** across various latent dimensionalities, and **(f)** the latent feature with the highest enrichment. **(g)** Applying the MYCN signature to an external dataset of NBL cell lines implicates MYCN amplified cell lines.

Assessing gene set coverage of compression models

We used gene sets from Molecular Signatures Database (MSigDB) and xCell [26–28] to

interpret biological signals activated in compressed features across all latent dimensionalities,

algorithms, and initializations. We applied a network projection approach to all compression

algorithm weight matrices to determine gene set coverage. Briefly, we projected all

compressed features onto a gene set network and assigned gene sets with the highest

enrichment that passed an adjusted statistical significance threshold to each compressed

feature (see methods for more details). We tracked coverage of three MSigDB gene set

collections representing transcription factor (TF) targets, cancer modules, and Reactome

pathways across latent dimensionalities in TCGA data (**Fig. 4**). In all cases, we observed higher

gene set coverage in models with larger latent dimensionalities. Considering individual models,

we observed high coverage in PCA, ICA, and NMF. In particular, ICA outperformed all other

algorithms (**Fig. 4a**). However, while these methods showed the highest coverage, the features

identified had relatively low enrichment scores compared to AE models (**Additional File 1:**

Figure S6).

Aggregating all five random initializations into ensemble models, we observed

substantial coverage increases, especially for AEs (**Fig. 4b**). VAE models had high coverage for all

gene sets in intermediate dimensions, while DAE improved in higher dimensions. However, at

the highest dimensions, ICA demonstrated the highest coverage. NMF consistently had the

highest enrichment scores, but the lowest coverage (**Fig. 4b**). When considering all models

combined (forming an ensemble of algorithm ensembles) within latent dimensionalities, we

observed substantially increased coverage of all gene sets. However, most of the unique gene

sets were contributed by the AE models (**Fig. 4c**).

Figure 4: *Assessing gene set coverage of specific gene set collections.* Tracking results in TCGA
data for three gene set collections representing transcription factor (TF) targets (C3TFT),
Reactome pathways (C2CPREACTOME), and cancer modules (C4CM). **(a)** Tracking coverage in
individual models, which represents the distribution of scores across five algorithm iterations.
(b) Tracking coverage in ensemble models, which represents coverage after combining all five
iterations into a single model. The size of the point represents relative enrichment strength. **(c)**
Tracking coverage in all models combined within *k* dimensionalities. The number of algorithm-
specific unique gene sets identified is shown as bar charts. Coverage for all models combined
across all *k* dimensionalities is shown as a dotted navy blue line.
242

Lastly, when we aggregated all BioBombe features across all algorithms and all latent

dimensionalities together into a single model, we observed the highest gene set coverage (**Fig.**

4c). These patterns were consistent across other gene set collections and datasets (**Additional**

File 1: Figure S7). In general, while models compressed with larger latent space dimensionalities

had higher gene set coverage, many individual gene sets were captured with the highest

enrichment in models with low and intermediate dimensionalities (**Additional File 1: Figure S8**).

These results did not reveal a best method or dimensionality: Various biological representations

are best discovered by using various compression algorithms with various latent space

dimensionalities.

Observing the latent dimensionality of specific tissue and cell type signatures

We measured the Pearson correlation between all samples' gene expression input and

reconstructed output. As expected, we observed increased mean correlation and decreased

variance as the latent dimensionalities increased in TCGA data (**Fig. 5a**). We also observed

similar patterns in GTEx and TARGET data (**Additional File 1: Figure S9**). Across all datasets, in

randomly permuted data, we observed correlations near zero (**Additional File 1: Figure S9**). The

correlation with real data was not consistent across all algorithms as PCA, ICA, and NMF

generally outperformed the AE models.

We tracked correlation differences across latent dimensionalities to determine the

dimensionality at which specific sample types are initially detected. Most cancer types,

including breast invasive carcinoma (BRCA) and colon adenocarcinoma (COAD), displayed

relatively gradual increases in sample correlation as the latent dimensionality increased (**Fig.**

5b). However, in other cancer types, such as low grade glioma (LGG), pheochromocytoma and

paraganglioma (PCPG), and acute myeloid leukemia (LAML), we observed large correlation

gains with a single increase in latent dimensionality (**Fig. 5c**). We also observed similar

performance spikes in GTEx data for several tissues including liver, pancreas, and blood (**Fig.**

5d). This sudden and rapid increase in correlation in specific tissues occurred at different latent

dimensionalities for different algorithms, but was consistent across algorithm initializations.

To determine if this rapid increase was a result of models learning specific biological

representations or if this observation represented a technical artifact, we more closely

examined the sharp increase in GTEx blood tissue correlation between latent space

dimensionalities 2 and 3 in VAE models (See **Fig. 5d**). We hypothesized that a difference in

reconstruction for a specific tissue at such a low dimensionality could be driven by a change in

the cell types captured by the model. We applied network projection of xCell gene sets to all

compressed features in both VAE models. xCell gene sets represent computationally derived

cell type signatures [27]. The top features identified for the VAE k = 2 model included skeletal

muscle, keratinocyte, and neuronal gene sets (**Fig. 6a**). Skeletal muscle was the most significant

gene set identified likely because it the tissue with the most samples in GTEx. Similar gene sets

were enriched in the k = 3 model, but we also observed enrichment for a specific neutrophil

gene set ("Neutrophils_HPCA_2") (**Fig. 6a**). Neutrophils represent 50% of all blood cell types,

which may explain the increased correlation in blood tissue observed in VAE k = 3 models. The

features implicated using the network projection approach were similar to an

overrepresentation analysis using high weight genes in both tails of the VAE k = 3 feature

(**Additional File 1: Figure S10**).

Figure 5: *Different latent dimensionalities implicate different tissue types.* **(a)** Sample Pearson correlation for all data in the testing data partition for The Cancer Genome Atlas (TCGA). The different algorithms follow the legend provided in panel d. **(b)** Mean Pearson correlation for select cancer types in the testing data partition. Pearson correlation gain between sequential latent dimensionalities for **(c)** select cancer types in TCGA and **(d)** select tissue-types in GTEx.

We also calculated the mean absolute value z scores for xCell gene sets in all

compression features for both VAE models with k = 2 and k = 3 dimensionalities (**Fig. 6b**). Again,

we observed skeletal muscle, keratinocytes, and neuronal gene sets to be enriched in both

models. However, we also observed a cluster of monocyte gene sets (including

"Monocytes_FANTOM_2") with enrichment in k = 3, but low enrichment in k = 2 (**Fig. 6b**).

Monocytes are also important cell types found in blood, and it is probable these signatures also

contributed to the increased correlation for the reconstructed blood samples in VAE k = 3

models. We provide the full list of xCell gene set genes for the neutrophil and monocyte gene

sets that intersected with the GTEx data in **Additional File 3**.

303   We scanned all other algorithms and latent dimensionalities to identify other

compression features with high enrichment scores in the "Neutrophils_HPCA_2" (**Fig. 6c**) and

"Monocytes_FANTOM_2" gene sets (**Fig. 6d**). We observed stronger enrichment of the

"Neutrophil_HPCA_2" gene set in AE models compared to PCA, ICA, and NMF, especially at

lower latent dimensionalities. We observed the highest score for the "Neutrophil_HPCA_2"

gene set at k = 14 in VAE models (**Fig. 6c**). The top VAE feature at k = 14 correlated strongly with

the VAE feature learned at k = 3 (**Additional File 1: Figure S10**). Conversely, PCA, ICA, and NMF

identified the "Monocytes_FANTOM_2" signature with higher enrichment than the AE models

(**Fig. 6d**). We observed a performance spike at k = 7 for both PCA and NMF models, but the

highest enrichment for "Monocytes_FANTOM_2" occurred at k = 200 in NMF models.

Validating GTEx neutrophil and monocyte signatures in external datasets

315   We downloaded a processed gene expression dataset (GSE103706) that applied two

treatments to induce neutrophil differentiation in two leukemia cell lines [29]. We hypothesized

that projecting the dataset on the "Neutrophil_HPCA_2" signature would reveal differential

scores in the treated cell lines. We observed large differences in sample activations of treated

vs untreated cell lines in the top Neutrophil signature (VAE k = 14) (**Fig. 6e**). We also tested the

"Monocytes_FANTOM_2" signature on a different publicly available dataset (GSE24759)

measuring gene expression of isolated cell types undergoing hematopoiesis [30]. We observed

increased scores for isolated monocyte cell population (MONO2) and relatively low scores for

several other cell types for top VAE features (**Fig. 6f**).

We applied the top signatures for the neutrophil and monocyte gene sets to each

external dataset (see **Fig. 6c, d**). We observed variable enrichment patterns across different

algorithms and latent dimensionalities (**Additional File 1: Figure S11a**). These separation

patterns were associated with network projection scores in NMF models, but were not

consistent with other algorithms (**Additional File 1: Figure S11b**). Taken together, in this

analysis we determined that 1) adding a single latent dimensionality that captured Neutrophil

and Monocyte signatures improved signal detection in GTEx blood, 2) these gene expression

signatures are enhanced at different latent dimensionalities and by different algorithms, and 3)

these signatures generalized to external datasets that were not encountered during model

training.

Figure 6: *Interpreting blood cell types in GTEx using xCell gene sets.* **(a)** Comparing BioBombe scores of all compressed latent features for variational autoencoder (VAE) models when bottleneck dimensionalities are set to *k* = 2 and *k* = 3. **(b)** Comparing mean BioBombe Z scores of aggregated latent features across two VAE models with *k* dimensionalities 2 and 3. Tracking the BioBombe Z scores of **(c)** "Neutrophils_HPCA_2" and **(d)** "Monocytes_FANTOM_2" gene sets across dimensionalities and algorithms. Only the top scoring feature per algorithm and dimensionality is shown. **(e)** Projecting the VAE feature *k* = 3 feature and the highest scoring feature (VAE *k* = 14) that best captures a neutrophil signature to an external dataset measuring neutrophil differentiation treatments (GSE103706). **(f)** Projecting the VAE *k* = 3 feature that best captures monocytes and the feature of the top scoring model (NMF *k* = 200) to an external dataset of isolated hematopoietic cell types (GSE24759).

Using BioBombe features in supervised learning applications

We used BioBombe compressed features in two supervised machine learning tasks.

First, we trained logistic regression models using compressed BioBombe features from

individual model iterations as input to predict each of the 33 different TCGA cancer types.

Nearly all cancer types could be predicted with high precision and recall (**Additional File 1:**

Figure S12). We observed multiple performance spikes at varying latent dimensionalities for

different cancer types and algorithms, which typically occurred in small latent dimensionalities

(**Fig. 7a**). Next, we input BioBombe features into the supervised classifier to predict samples

with alterations in the top 50 most mutated genes in TCGA (**Additional File 1: Figure S13**). We

focused on predicting four cancer genes and one negative control; *TP53*, *PTEN*, *PIK3CA*, *KRAS*,

and *TTN* (**Fig. 7b**). *TTN* is a particularly large gene and is associated with a high passenger

mutation burden and should provide no predictive signal [31]. As expected, we did not observe

any signal in predicting *TTN* (**Fig. 7b**). Again, we observed performance increases at varying

latent dimensionalities across algorithms. However, predictive signal for mutations occurred at

higher latent dimensionalities compared to cancer types (**Fig. 7c**). Compared to features trained

within algorithm and within iteration, an ensemble of five VAE models and an ensemble of five

models representing one iteration of each algorithm (PCA, ICA, NMF, DAE, and VAE) identified

cancer type and mutation status in earlier dimensionalities compared to single model iterations

(**Fig 7c**). We also tracked the logistic regression coefficients assigned to each compression

feature. DAE models consistently displayed sparse models, and the VAE ensemble and model

ensemble also induced high sparsity (**Fig. 7d**).

Lastly, we trained logistic regression classifiers using all 30,850 BioBombe features

generated across iterations, algorithms, and latent dimensionalities. These models were sparse

and high performing; comparable to logistic regression models trained using raw features (**Fig.**

7e). Of all 30,850 compressed features in this model, only 317 were assigned non-zero weights

(1.03%). We applied the network projection approach using Hallmark gene sets to interpret the

biological signatures of the top supervised model coefficients. The top positive feature was

derived from a VAE trained with k = 200. The top hallmarks of this feature included

"ESTROGEN_RESPONSE_EARLY", "ESTROGEN_RESPONSE_LATE", and "P53_PATHWAY". The top

negative feature was derived from a VAE trained with k = 150 and was associated with hallmark

gene sets including "BILE_ACID_METABOLISM", "EPITHELIAL_MESENCHYMAL_TRANSITION",

and "FATTY_ACID_METABOLISM". **Additional File 4** includes a full list of logistic regression

coefficients and hallmark network projection scores. Overall, the features selected by the

supervised classifier were distributed across algorithms and latent dimensionalities suggesting

that combining signatures across dimensionalities and algorithms provided the best

representation of the signal (**Fig. 7f**).

Figure 7: *Using BioBombe sequential compression in The Cancer Genome Atlas (TCGA) as features in supervised machine learning tasks*. Predicting **(a)** cancer-type status and **(b)** gene mutation status for select cancer-types and important cancer genes using five compression algorithms and two ensemble models. The area under the precision recall (AUPR) curve for cross validation (CV) data partitions is shown. The blue lines represent predictions made with permuted data input into each compression algorithm. The dotted lines represent AUPR on

untransformed RNAseq data. The dotted gray line represents a hypothetical random guess. **(c)**
Tracking the average change in AUPR between real and permuted data across latent
dimensionalities and compression models in predicting (*top*) cancer types and (*bottom*)
mutation status. The average includes the five cancer types and mutations tracked in panels a
and b. **(d)** Tracking the sparsity and performance of supervised models using BioBombe
compressed features in real and permuted data. **(e)** Performance metrics for the all-
compression feature ensemble model predicting *TP53* alterations. (*left*) Receiver operating
characteristic (ROC) and (*right*) precision recall curves are shown. **(f)** The average absolute value
weight per algorithm for the all-compression-feature ensemble model predicting *TP53*
alterations. The adjusted scores are acquired by dividing by the number of latent
dimensionalities in the given model.
405

Discussion:

Our primary observation is that compressing complex gene expression data using

multiple latent dimensionalities and algorithms improves biological representations. Across

multiple latent dimensionalities, we identified optimal features to stratify sample sex, MYCN

amplification, blood cell types, cancer types, and mutation status. These features generalized to

other data, providing additional evidence for the intrinsic qualities of biological representations

embedded in gene expression data [23,32–34]. Furthermore, the complexity of biological

features was associated with the number of latent dimensionalities used. We predicted gene

mutation using models with high dimensionality, but we detected cancer type with high

accuracy using models with low dimensionality. In general, unsupervised learning algorithms

applied to gene expression data extract biological and technical signals present in input

samples. When applying these algorithms, researchers must determine how many latent

dimensions to compress their input data into and different studies can have a variety of goals.

For example, compression algorithms used for visualization can stratify sample groups based on

the largest sources of variation [35–40]. In visualization settings, selecting a small number of

latent dimensions is often best, and there is no need to compress data across multiple latent

dimensionalities. However, if the analysis goal includes learning biological signatures to identify

more subtle patterns in input samples, then there is not a single optimal latent dimensionality

nor optimal algorithm. For example, though ICA and PCA represent rotations of each other, we

found that the methods varied in their ability to capture specific biological signals into single

features, which highlights the challenge of picking only a single algorithm. While compressing

data into a single latent dimensionality will capture many biological signals, the "correct"

dimensionality is not always clear, and several biological signatures may be better revealed by

alternative latent dimensionalities.

If optimizing a single model, a researcher can use one or many criteria to select an

appropriate latent dimensionality. Measurements such as Akaike information criterion (AIC),

Bayesian information criterion (BIC), stability, and cross validation (CV) can be applied to a

series of latent dimensionalities [41,42]. Other algorithms, like Dirichlet processes, can naturally

arrive at an appropriate dimensionality through several algorithm iterations [43]. Hidden layer

dimensions of unsupervised neural networks are tunable hyperparameters defined by expected

input data complexity and performance. However, applied to gene expression data, these

metrics often provide conflicting results and unclear suggestions. In genomics applications, the

method Thresher uses a combination of outlier detection and PCA to identify the optimal

number of clusters [44]. Compression model stability can also be used to determine an optimal

latent dimensionality in gene expression data [45]. By considering only reproducible features,

ICA revealed 139 modules from nearly 100,000 publicly available gene expression profiles [46].

However, rather than using heuristics to select a biologically-appropriate latent dimensionality,

a researcher may instead elect to compress gene expression data into many different latent

space dimensionalities to generate many different feature representations.

There are many limitations in our evaluation of compressing gene expression data into

many latent dimensionalities across multiple methods. First, our approach takes a long time to

run. We are training many different algorithms across many different latent dimensionalities

and iterations, which requires a lot of compute time (**Additional File 1: Figure S14**). However,

because we are training many models independently, this task can be parallelized. Additionally,

we did not evaluate dimensionalities above k = 200. It is likely that many more signatures can

be learned, and possibly with even higher association strengths in higher dimensionalities for

certain biology. We also did not focus on detecting compressed features that represent

technical artifacts, which has already been widely explored [47,48]. Moreover, we did not

explore adding hidden layers in AE models. Many models trained on gene expression data have

benefited from using multiple hidden layers in neural network architectures [7,49]. Additional

methods, like DeepLift, can be used to reveal gene importance values in internal

representations of deep networks [50,51].

An additional challenge is interpreting the biological content of the compressed gene

expression features. Overrepresentation analysis (ORA) and gene set enrichment analysis

(GSEA) are commonly applied but have significant limitations [26,52]. ORA requires a user to

select a cutoff, typically based on standard deviation, to build representative gene sets from

each feature. ORA tests also do not consider the weights, or gene importance scores, in each

compression feature. Conversely, GSEA operates on ranked features, but often requires many

permutations to establish significance. Furthermore, ORA requires each tail of the compressed

feature distribution to be interpreted separately in algorithms that also learn negative weights.

The weight distribution is dependent on the specific compression algorithm, and the same

cutoff may not be appropriate for all algorithms and all compressed features. Instead, we

implemented a network projection based approach to quickly interpret compressed latent gene

expression features [53,54]. The approach is applied to the full and continuous distribution of

gene weights, operates independently of the algorithm feature distribution, does not require

arbitrary thresholds, and obviates the need to consider both tails of the distribution separately.

Nevertheless, additional downstream experimental validation is necessary to determine if the

constructed feature actually represents the biology it has been assigned.

Conclusions:

To enhance biological signature discovery, it is best to compress gene expression data

using several algorithms and many different latent space dimensionalities. These signatures

represent important biological signals, including various cell types, phenotypes, biomarkers,

and other sample characteristics. We showed, through several experiments tracking lower

dimensional gene expression representations, gene set coverage, and supervised learning

performance, that optimal biological features are learned using a variety of latent space

dimensionalities and different compression algorithms. As unsupervised machine learning

continues to be applied to derive insight from biomedical datasets, researchers should shift

focus away from optimizing a single model based on certain mathematical heuristics, and

instead towards learning good and reproducible biological representations that generalize to

alternative datasets regardless of compression algorithm and latent dimensionality.

Methods:

Transcriptomic compendia acquisition and processing

We downloaded transcriptomic datasets from publicly available resources. We

downloaded the batch-corrected TCGA PanCanAtlas RNAseq data from the National Cancer

Institute Genomic Data Commons (https://gdc.cancer.gov/about-

data/publications/pancanatlas). These data consisted of 11,069 samples with 20,531 measured

genes quantified with RSEM and normalized with log transformation. We converted Hugo

Symbol gene identifiers into Entrez gene identifiers and discarded non-protein coding genes

and genes that failed to map. We also removed tumors that were measured from multiple sites.

This resulted in a final TCGA PanCanAtlas gene expression matrix with 11,060 samples, which

included 33 different cancer-types, and 16,148 genes. The breakdown of TCGA samples by

cancer-type is provided in **Additional File 5**.

We downloaded the TPM normalized GTEx RNAseq data (version 7) from the GTEx data

portal (https://gtexportal.org/home/datasets). There were 11,688 samples and 56,202 genes in

this dataset. After selecting only protein-coding genes and converting Hugo Symbols to Entrez

gene identifiers, we considered 18,356 genes. There are 53 different detailed tissue-types in

this GTEx version. The tissues types included in these data are provided in **Additional File 5**.

Lastly, we retrieved the TARGET RNAseq gene expression data from the UCSC Xena data

portal [55]. The TARGET data was processed through the FPKM UCSC Toil RNA-seq pipeline and

was normalized with RSEM and log transformed [56]. The original matrix consists of 734

samples and 60,498 Ensembl gene identifiers. We converted the Ensembl gene identifiers to

Entrez gene names and retained only protein-coding genes. This procedure resulted in a total of

18,753 genes measured in TARGET. There are 7 cancer-types profiled in TARGET and the

specific breakdown is available in **Additional File 5**. All specific downloading and processing

steps can be viewed and reproduced at

https://github.com/greenelab/BioBombe/tree/master/0.expression-download.

Training unsupervised neural networks

Autoencoders (AE) are unsupervised neural networks that learn through minimizing the

reconstruction of input data after passing the data through one or several intermediate layers

[57]. Typically, these layers are of a lower dimensionality than the input, so the algorithms must

compress the input data. Denoising autoencoders (DAE) add noise to input layers during

training to regularize solutions and improve generalizability [58]. Variational autoencoders

(VAE) add regularization through an additional penalty term imposed on the objective function

[59,60]. In a VAE, the latent space dimensions (k) are penalized with a Kullback-Leibler (KL)

divergence penalty restricting the distribution of samples in the latent space to Gaussian

distributions. We independently optimized each AE model across a grid of hyperparameter

combinations including 6 representative latent dimensionalities (described in **Additional File 2**

and **Additional File 1: Figure S2**).

Training compression algorithms across latent dimensionalities

Independently for each dataset (TCGA, GTEx, and TARGET), we performed the following

procedure to train the compression algorithms. First, we randomly split data into 90% training

and 10% testing partitions. We balanced each partition by cancer type or tissue type, which

meant that each split contained relatively equal representation of tissues. Before input into the

compression algorithms, we transformed the gene expression values by gene to the [0, 1] range

by subtracting the minimum value and dividing by the range for each specific gene. We applied

this transform independently for the testing and training partitions. We selected this range

because it was compatible with all of the algorithms. We used the training set to train each

compression algorithm. We used the scikit-learn implementations of PCA, ICA, and NMF, and

the Tybalt implementations of VAE and DAE [8,61].

After learning optimized compression models with the training data, we transformed

the testing data using these models. We assessed performance metrics using both training and

testing data to reduce bias. In addition to training with real data, we also trained all models

with randomly permuted data. To permute the training data, we randomly shuffled the gene

expression values for all genes independently. We also transformed testing partition data with

models trained using randomly permuted data. Training with permuted data removes the

correlational structure in the data and can help set performance metric baselines.

One of our goals was to assess differences in performance and biological signal

detection across a range of latent dimensionalities (k). To this end, we trained all algorithms

with various k dimensionalities including k = 2, 3, 4, 5, 6, 7, 8, 9, 10, 12, 14, 16, 18, 20, 25, 30,

35, 40, 45, 50, 60, 70, 80, 90, 100, 125, 150, and 200 for a total of 28 different dimensionalities.

All of these models were trained independently. Lastly, for each k dimensionality we trained

five different models initialized with five different random seeds. In total, considering the three

datasets, five algorithms, randomly permuted training data, all 28 k dimensionalities, and five

initializations, we trained 4,200 different compression models (**Additional File 2: Figure S1**).

Therefore, in total, we generated 185,100 different compression features.

Evaluating compression algorithm performance

We evaluated all compression algorithms on three main tasks: Reconstruction, sample

correlation, and weight matrix stability. First, we evaluated how well the input data is

reconstructed after passing through the bottleneck layer. Because the input data was

transformed to a distribution between 0 and 1, we used binary cross entropy to measure the

difference between algorithm input and output as a measure of reconstruction cost. The lower

the reconstruction cost, the higher fidelity reconstruction, and therefore the higher proportion

of signals captured in the latent space features. We also assessed the Pearson correlation of all

samples comparing input to reconstructed output. This value is similar to reconstruction and

can be quickly tracked at an individual sample level. Lastly, we used singular vector canonical

correlation analysis (SVCCA) to determine model stability within and model similarity between

algorithms and across latent dimensionalities [21]. The SVCCA method consisted of two distinct

steps. First, singular value decomposition (SVD) was performed on two input weight matrices.

The singular values that combined to reconstruct 98% of the signal in the data were retained.

Next, the SVD transformed weight matrix was input into a canonical correlation analysis (CCA).

CCA aligned different features in the weight matrix based on maximal correlation after learning

a series of linear transformations. Taken together, SVCCA outputs a single metric comparing

two input weight matrices that represents stability across model initializations and average

similarity of two different models. Because we used the weight matrices, the similarity

describes signature discovery. We use the distribution of SVCCA similarity measures across all

pairwise algorithm initializations and latent dimensionalities to indicate model stability [21].

Assessing gene expression signatures present in BioBombe features

We tested BioBombe sequentially compressed features to distinguish sample sex in

GTEx and TCGA data, and MYCN amplification in TARGET NBL data. We tested all compression

algorithms and latent space dimensionalities to determine the conditions in which these

features were best captured. First, we selected tissue-types and cancer-types in the GTEx and

TCGA sex analyses that were balanced by sex by selecting tissues with male to female ratios

between 0.5 and 1.5. We performed a two-tailed independent t-test assuming unequal

variance comparing male and female samples, and NBL samples with and without MYCN

amplification. We applied the t-test to all compression features identified across algorithms,

initializations, and dimensionalities. Shown in the figures are the top scoring feature per latent

space dimensionality and algorithm.

We applied the optimal MYCN signature learned in TARGET to an alternative dataset

consisting of a series of publicly available NBL cell lines [25]. The data were processed using

STAR, and we accessed the processed FPKM matrix from figshare [62]. We transformed the

dataset with the identified signatures using the following operation:

$$S_{g'}^{T} * D_{g' \, x \, n} = D'_{s \, x \, n}$$

Where *D* represents the respective RNAseq data to transform, *S* represents the specific

signature, *g'* represents the overlapping genes measured in both datasets, *n* represents

samples, and D'_s represents the signature scores in the transformed dataset. Of the 8,000 genes

measured in TARGET data, 7,653 were also measured in external NBL cell line dataset (95.6%).

Using the sample activation scores for each of the top scoring features for sample sex in

TCGA and GTEx, and MYCN amplification in TARGET and the validation set, we performed two

tailed t-test with unequal variance comparing each group. For the TCGA and GTEx sex

comparison, our t-test compared male vs. female activation scores. For the TARGET and NBL

cell line analyses, our t-test compared MYCN amplified NBL samples vs. MYCN non-amplified

NBL samples. We add t-test statistics and p values in each sub figure.

Gene network construction and processing

We constructed networks using gene set collections compiled by version 6.2 of the

Molecular Signatures Database (MSigDB) and cell types derived from xCell [26–28]. These gene

sets represent a series of genes that are involved in specific biological processes and functions.

We integrated all openly licensed MSigDB collections which included hallmark gene sets (H),

positional gene sets (C1), curated gene sets (C2), motif gene sets (C3), computational gene sets

(C4), Gene Ontology (GO) terms (C5), oncogenic gene sets (C6) and immunologic gene sets (C7).

We omitted MSigDB gene sets that were not available under an open license (KEGG, BioCarta,

and AAAS/STKE). The C2 gene set database was split into chemical and genetic perturbations

(C2.CPG) and Reactome (C2.CP.Reactome). The C3 gene set was split into microRNA targets

(C3.MIR) and transcription factor targets (C3.TFT). The C4 gene set was split into cancer gene

neighborhoods (C4.CGN) and cancer modules (C4.CM). Lastly, the C5 gene set was split into GO

Biological Processes (C5.BP), GO Cellular Components (C5.CC), and GO molecular functions

(C5.MF). xCell represents a gene set compendia of 489 computationally derived gene signatures

from 64 different human cell types. The number of gene sets in each curation is provided in

Additional File 6. In BioBombe network projection, only a single collection is projected at a

time.

To build the gene set network, we used hetnetpy [63]. Briefly, hetnetpy builds networks

that include multiple node types and edge relationships. We used hetnetpy to build a single

network containing all MSigDB collections and xCell gene sets listed above. The network

consisted of 17,451 unique gene sets and 2,159,021 edges representing gene set membership

among 20,703 unique gene nodes (**Additional File 6**). In addition to generating a single network

using curated gene sets, we also used hetnetpy to generate 10 permuted networks. The

networks are permuted using the XSwap algorithm, which randomizes connections while

preserving node degree (i.e. the number of gene set relationships per gene) [64]. Therefore, the

permuted networks are used to control for biases induced by uneven gene degree. We

compared the observed score against the distribution of permuted network scores to interpret

the biological signatures in each compression feature.

Rapid interpretation of compressed gene expression data

Our goal was to quickly interpret the automatically generated compressed latent

features learned by each unsupervised algorithm. To this end, we constructed gene set

adjacency matrices with specific MSigDB or xCell gene set collections using hetnetpy software.

We then performed the following matrix multiplication against a given compressed weight

matrix to obtain a raw score for all gene sets for each latent feature.

639
$$H_{c \times n} * W_{n \times k} = G_{c \times k}$$

Where *H* represents the gene set adjacency matrix, *c* is the specific gene set collection, and *n*

represents genes. *W* represents the specific compression algorithm weight matrix, which

includes *n* genes and *k* latent space features. The output of this matrix multiplication, *G*, is

represented by *c* gene sets and *k* latent dimensions. Through a single matrix multiplication, the

matrix *G* tracks raw BioBombe scores.

Because certain hub genes are more likely to be implicated in gene sets and longer gene

sets will receive higher raw scores, we compared *G* to the distribution of permuted scores

against all 10 permuted networks.

648
$$H_{p_{c \times n}}^{1-10} * W_{n \times k} = G_p$$

649
$$G_{z-score} = \frac{G_{c \times k} - \overline{G_p}}{\sigma(G_p)}$$

Where H_p^{1-10} represents the adjacency matrices for all 10 permuted networks and G_p represents

the distribution of scores for the same *k* features for all permutations. We calculated the z

score for all gene sets by latent features ($G_{z-score}$). This score represents the BioBombe Score.

Other network-based gene set methods consider gene set influence based on network

connectivity of gene set genes [53,54]. Instead, we used the latent feature weights derived

from unsupervised compression algorithms as input, and the compiled gene set networks to

assign biological function.

We also compared the BioBombe network projection approach to overrepresentation

analyses (ORA). We did not compare the approach to gene set enrichment analysis (GSEA)

because evaluating single latent features required many permutations and did not scale to the

many thousands of compressed features we examined. We implemented ORA analysis using a

Fisher's Exact test. The background genes used in the test included only the genes represented

in the specific gene set collection.

Calculating gene set coverage across BioBombe features

We were interested in determining the proportion of gene sets within gene set

collections that were captured by the features derived from various compression algorithms.

We considered a gene set "captured" by a compression feature if it had the highest positive or

highest negative BioBombe z score compared to all other gene sets in that collection. We

converted BioBombe z scores into p values using the pnorm() R function using a two-tailed test.

We removed gene sets from consideration if their p values were not lower than a Bonferroni

adjusted value determined by the total number of latent dimensionalities in the model.

We calculated coverage (C) by considering all unique top gene sets (U) identified by all

features in the compression model (w) and dividing by the total number of gene sets in the

collection (T_C).

$$C = \frac{U_w}{T_c}$$

We calculated the coverage metric for all models independently (C_i), for ensembles, or

individual algorithms across all five iterations (C_e), and for all models across k dimensions (C_k).

We also calculated the total coverage of all BioBombe features combined in a single model

(C_{all}). A larger coverage value indicated a model that captured a larger proportion of the

signatures present in the given gene set collection.

Downloading and processing publicly available expression data for neutrophil GTEx analysis

We used an external dataset to validate the neutrophil feature learned by compressing

GTEx gene expression data into three latent dimensionalities. We observed that this feature

contributed to improved reconstruction of blood tissue. To assess the performance of this

neutrophil signature, we downloaded data from the Gene Expression Omnibus (GEO) with

accession number GSE103706 [29]. RNA was captured in this dataset using Illumina NextSeq

500. The dataset measured the gene expression of several replicates of two neutrophil-like cell

lines, HL-60 and PLB-985, which were originally derived from acute myeloid leukemia (AML)

patients. The PLB-985 cell line was previously identified as a subclone of HL-60, so we expect

similar signature activity between the two lines [65]. Gene expression of the two cell lines was

measured with and without neutrophil differentiation treatments. Though DMSO is frequently

used to solubilize compounds and act as an experimental control, it has been used to create

neutrophil-like cells [66]. The validation dataset we used was generated to compare DMSO

activity with untreated cells and cells treated with DMSO plus Nutridoma [29]. We tested the

hypothesis that our neutrophil signature would distinguish the samples with and without

neutrophil differentiation treatment. We transformed external datasets with the following

operation:

$$W^T_{k \times g\prime} * D_{g\prime \times n} = D\prime_{k \times n}$$

Where *D* represents the processed RNAseq data from GSE103706. Of 8,000 genes measured in

W, 7,664 were also measured in *D* (95.8%). These 7,664 genes are represented by *g'*. All of the

"Neutrophils_HPCA_2" signature genes were measured in *W*. *D'* represents the GSE103706

data transformed along the specific compression feature. Each sample in *D'* is then considered

transformed by the specific signature captured in *k*. The specific genes representing

"Neutrophils_HPCA_2" is provided in **Additional File 3**.

Downloading and processing publicly available expression data for monocyte GTEx analysis

We used an additional external dataset to validate the identified monocyte signature.

We accessed processed data for the publicly available GEO dataset with accession number

GSE24759 [30]. The dataset was measured by Affymetrix HG-U133A (early access array) and

consisted of 211 samples representing 38 distinct and purified populations of cells, including

monocytes, undergoing various stages of hematopoiesis. The samples were purified from 4 to 7

independent donors each. Many xCell gene sets were computationally derived from this

dataset as well [27]. Not all genes in the weight matrices were measured in the GSE24759

dataset. For this application, 4,645 genes (58.06%) corresponded with the genes used in the

compression algorithms. Additionally, 168 out of 178 genes (94.38%) in the

"Monocyte_FANTOM_2" gene set were measured (**Additional File 3**). We investigated the

"Monocytes_FANTOM_2" signature because of its high enrichment in VAE *k* = 3 and low

enrichment in VAE *k* = 2.

Machine learning classification of cancer types and gene alterations in TCGA

We trained supervised learning classifiers using raw RNA-seq features and BioBombe-

derived features. In general, we trained supervised machine learning models to predict cancer

type from RNAseq features in TCGA PanCanAtlas RNAseq data. We implemented a logistic

regression classifier with an elastic net penalty. The classifiers were controlled for mutation

burden. More details about the specific implementation are described in Way et al. 2018 [67].

Here, we predicted all 33 cancer types using all 11,060 samples. These predictions were

independent per cancer type, which meant that we trained models with the same input gene

expression or BioBombe feature data, but used 33 different status matrices.

We also trained models to predict gene alteration status in the top 50 most mutated

genes in the PanCanAtlas. These models were controlled for cancer type and mutation burden.

We defined the status in this task using all non-silent mutations identified with a consensus

mutation caller [68]. We also considered large copy number amplifications for oncogenes and

deep copy number deletions for tumor suppressor genes as previously defined [69]. We used

the threshold GISTIC2.0 calls for large copy amplifications (score = 2) and deep copy deletions

(score = -2) in defining the status matrix [70]. For each gene alteration prediction, we removed

samples with a hypermutator phenotype, defined by having log10 mutation counts greater than

five standard deviations above the mean. For the mutation prediction task, we also did not

include certain cancer types in training. We omitted cancer types if they had less than 5% or

more than 95% representation of samples with the given gene alteration. The positive and

negative sets must have also included at least 15 samples. We filtered out cancer types in this

manner to prevent the classifiers from artificially detecting differences induced by unbalanced

training sets.

We trained models with raw RNAseq data subset by the top 8,000 most variably

expressed genes by median absolute deviation. The training data used was the same training

set used for the BioBombe procedure. We also trained models using all BioBombe compression

matrices for each latent dimension, and using real and permuted data. We combined

compressed features together to form three different types of ensemble models. The first type

grouped all five iterations of VAE models per latent dimensionality to make predictions. The

second type grouped features of five different algorithms (PCA, ICA, NMF, DAE, VAE) of a single

iteration together to make predictions. The third ensemble aggregated all features learned by

all algorithms, all initializations, and across all latent dimensionalities, which included a total of

30,850 features. In total, considering the 33 cancer types, 50 mutations, 28 latent

dimensionalities, ensemble models, raw RNAseq features, real and permuted data, and 5

initializations per compression, we trained and evaluated 32,868 different supervised models.

We optimized all of the models independently using 5-fold cross validation (CV). We

searched over a grid of elastic net mixing and alpha hyperparameters. The elastic net mixing

parameter represents the tradeoff between l1 and l2 penalties (where mixing = 0 represents an

l2 penalty) and controls the sparsity of solutions [71]. Alpha is a penalty that tunes the impact

of regularization, with higher values inducing higher penalties on gene coefficients. We

searched over a grid for both hyperparameters (alpha = 0.1, 0.13, 0.15, 0.2, 0.25, 0.3 and mixing

= 0.15, 0.16, 0.2, 0.25, 0.3, 0.4) and selected the combination with the highest CV AUROC. For

each model, we tested performance using the original held out testing set that was also used to

assess compression model performance.

Evaluating model training time

We evaluated the execution time of training each compression algorithm for all three

datasets across several latent dimensionalities. We used 8 representative latent

dimensionalities: k = 2, 4, 10, 16, 25, 50, 80, and 200. We conducted the time analysis using a

CPU machine with an Intel Core i3 dual core processer with 32 GB of DDR4 memory.

Reproducible software

All code to perform all analyses and generate all results and figures is provided with an open

source license at https://github.com/greenelab/biobombe [72]. All resources can be viewed

and downloaded from https://greenelab.github.io/BioBombe/.

List of abbreviations:

RNAseq = RNA sequencing; PCA = principal components analysis; ICA = independent

components analysis; NMF = non-negative matrix factorization; AE = autoencoder; DAE =

denoising autoencoder; VAE = variational autoencoder; TCGA = the cancer genome atlas; GTEx

= genome tissue expression project; TARGET = therapeutically applicable research to generate

effective treatments project; BRCA = breast invasive carcinoma; COAD = colon

adenocarcinoma; LGG = low grade glioma; PCPG = pheochromocytoma and paraganglioma;

LAML = acute myeloid leukemia; LUAD = lung adenocarcinoma; GEO = gene expression

omnibus; ROC = receiver operating characteristic; PR = precision recall; AUROC = area under the

receiver operating characteristic curve; AUPR = area under the precision recall curve; CV = cross

validation; ORA = overrepresentation analysis; GSEA = gene set enrichment analysis; SVD =

singular value decomposition; CCA = canonical correlation analysis; SVCCA = singular vector

canonical correlation analysis; TF = transcription factor; DMSO = dimethyl sulfoxide

Declarations:

Ethics approval and consent to participate

793   The TCGA, GTEx, and TARGET data used are publicly available and their use was

794   previously approved by their respective ethics committees.

795   *Consent for publication*

796   Not applicable.

797   *Availability of data and material*

798   All data used and results generated in this manuscript are publicly available. All results

799   of the analysis can be viewed and downloaded from

800   https://greenelab.github.io/BioBombe/. The analyzed data can be accessed in the

801   following locations: TCGA data can be accessed at https://gdc.cancer.gov/about-

802   data/publications/pancanatlas, the GTEx data can be accessed at

803   https://gtexportal.org/home/datasets, the TARGET data can be accessed at

804   https://toil.xenahubs.net/download/target_RSEM_gene_fpkm.gz, the neutrophil

805   validation data can be accessed using gene expression omnibus (GEO) accession number

806   GSE103706 (https://www.ncbi.nlm.nih.gov/geo/query/acc.cgi?acc=GSE103706), the

807   monocyte validation data can be accessed using GEO accession number GSE24759

808   (https://www.ncbi.nlm.nih.gov/geo/query/acc.cgi?acc=GSE24759). Software to

809   reproduce the analyses, and all results generated in this manuscript can be accessed at

810   https://github.com/greenelab/biobombe. The software has also been archived in an

811   additional publicly available repository at https://zenodo.org/record/3460539.

812   Additionally, all BioBombe results are available in a series of versioned archives (TCGA

BioBombe Results: https://zenodo.org/record/2110752); (GTEX BioBombe Results:

https://zenodo.org/record/2300616); (TARGET BioBombe Results:

https://zenodo.org/record/2222463); (Randomly permuted TCGA BioBombe Results:

https://zenodo.org/record/2221216); (Randomly permuted GTEx BioBombe Results:

https://zenodo.org/record/2386816); (Randomly Permuted TARGET BioBombe Results:

https://zenodo.org/record/2222469). The full results of the TCGA classification analysis

using BioBombe features is archived at https://zenodo.org/record/2535759.

Competing interests

The authors declare that they have no competing interests.

Funding

This work was funded in party by The Gordon and Betty Moore Foundation under GBMF

4552 (CSG) and the National Institutes of Health's National Human Genome Research

Institute under R01 HG010067 (CSG) and the National Institutes of Health under T32

HG000046 (GPW).

Authors' contributions

GPW performed the analysis, wrote the BioBombe software, generated the figures, and

wrote the manuscript. GPW and CSG designed the study and interpreted the results. MZ

and DSH developed the network software. VR developed the website. All authors read,

revised, and approved the final manuscript.

Acknowledgements

We would like to thank Jaclyn Taroni, Yoson Park, and Alexandra Lee for insightful

discussions and code review. We also thank Jo Lynne Rokita and John Maris for

insightful discussions regarding the neuroblastoma analysis.

References:

1. Fehrmann RSN, Karjalainen JM, Krajewska M, Westra H-J, Maloney D, Simeonov A, et al.
Gene expression analysis identifies global gene dosage sensitivity in cancer. Nat Genet.
2015;47:115–25.

2. Engreitz JM, Daigle BJ, Marshall JJ, Altman RB. Independent component analysis: Mining
microarray data for fundamental human gene expression modules. J Biomed Inform.
2010;43:932–44.

3. Kong W, Vanderburg CR, Gunshin H, Rogers JT, Huang X. A review of independent component
analysis application to microarray gene expression data. BioTechniques. 2008;45:501–20.

4. Gaujoux R, Seoighe C. CellMix: a comprehensive toolbox for gene expression deconvolution.
Bioinforma Oxf Engl. 2013;29:2211–2.

5. Shen-Orr SS, Gaujoux R. Computational deconvolution: extracting cell type-specific
information from heterogeneous samples. Curr Opin Immunol. 2013;25:571–8.

6. Tan J, Doing G, Lewis KA, Price CE, Chen KM, Cady KC, et al. Unsupervised Extraction of Stable
Expression Signatures from Public Compendia with an Ensemble of Neural Networks. Cell Syst.
2017;5:63–71.e6.

7. Chen L, Cai C, Chen V, Lu X. Learning a hierarchical representation of the yeast transcriptomic
machinery using an autoencoder model. BMC Bioinformatics. 2016;17:S9.

8. Way GP, Greene CS. Extracting a biologically relevant latent space from cancer
transcriptomes with variational autoencoders. Pac Symp Biocomput Pac Symp Biocomput.
2018;23:80–91.

9. Rampasek L, Hidru D, Smirnov P, Haibe-Kains B, Goldenberg A. Dr.VAE: Drug Response
Variational Autoencoder. ArXiv170608203 Stat [Internet]. 2017; Available from:
http://arxiv.org/abs/1706.08203

10. Johnson WE, Li C, Rabinovic A. Adjusting batch effects in microarray expression data using
empirical Bayes methods. Biostatistics. 2007;8:118–27.

11. Stegle O, Parts L, Piipari M, Winn J, Durbin R. Using probabilistic estimation of expression
residuals (PEER) to obtain increased power and interpretability of gene expression analyses. Nat
Protoc. 2012;7:500–7.

12. Weinstein JN, Collisson EA, Mills GB, Shaw KM, Ozenberger BA, Ellrott K, et al. The Cancer
Genome Atlas Pan-Cancer Analysis Project. Nat Genet. 2013;45:1113–20.

13. GTEx Consortium. The Genotype-Tissue Expression (GTEx) project. Nat Genet. 2013;45:580–
5.

14. Mullighan CG, Su X, Zhang J, Radtke I, Phillips LAA, Miller CB, et al. Deletion of IKZF1 and
prognosis in acute lymphoblastic leukemia. N Engl J Med. 2009;360:470–80.

15. Way G. TCGA BioBombe Results [Internet]. Zenodo; 2018 [cited 2019 Jan 20]. Available
from: https://zenodo.org/record/2110752

16. Way G. GTEX BioBombe Results [Internet]. Zenodo; 2018 [cited 2019 Jan 20]. Available
from: https://zenodo.org/record/2300616

17. Way G. TARGET BioBombe Results [Internet]. Zenodo; 2018 [cited 2019 Jan 20]. Available
from: https://zenodo.org/record/2222463

18. Way G. TCGA BioBombe Results - Randomly Permuted Data [Internet]. Zenodo; 2018 [cited
2019 Jan 20]. Available from: https://zenodo.org/record/2221216

19. Way G. GTEX BioBombe Results - Randomly Permuted Data [Internet]. Zenodo; 2018 [cited
2019 Jan 20]. Available from: https://zenodo.org/record/2386816

20. Way G. TARGET BioBombe Results - Randomly Permuted Data [Internet]. Zenodo; 2018
[cited 2019 Jan 20]. Available from: https://zenodo.org/record/2222469

21. Raghu M, Gilmer J, Yosinski J, Sohl-Dickstein J. SVCCA: Singular Vector Canonical Correlation
Analysis for Deep Learning Dynamics and Interpretability. Neural Inf Process Syst NeurIPS. 2017;

22. Clark B, Stein-O'Brien G, Shiau F, Cannon G, Davis E, Sherman T, et al. Comprehensive
analysis of retinal development at single cell resolution identifies NFI factors as essential for
mitotic exit and specification of late-born cells. bioRxiv [Internet]. 2018 [cited 2019 Feb
17];https://doi.org/10.1101/378950. Available from:
http://biorxiv.org/lookup/doi/10.1101/378950

23. Stein-O'Brien GL, Clark BS, Sherman T, Zibetti C, Hu Q, Sealfon R, et al. Decomposing Cell
Identity for Transfer Learning across Cellular Measurements, Platforms, Tissues, and Species.
Cell Syst. 2019;8:395–411.e8.

24. Huang M, Weiss WA. Neuroblastoma and MYCN. Cold Spring Harb Perspect Med.
2013;3:a014415–a014415.

25. Harenza JL, Diamond MA, Adams RN, Song MM, Davidson HL, Hart LS, et al. Transcriptomic
profiling of 39 commonly-used neuroblastoma cell lines. Sci Data. 2017;4:170033.

26. Subramanian A, Tamayo P, Mootha VK, Mukherjee S, Ebert BL, Gillette MA, et al. Gene set
enrichment analysis: A knowledge-based approach for interpreting genome-wide expression
profiles. Proc Natl Acad Sci. 2005;102:15545–50.

27. Aran D, Hu Z, Butte AJ. xCell: digitally portraying the tissue cellular heterogeneity landscape.
Genome Biol [Internet]. 2017 [cited 2019 Jan 15];18. Available from:
https://genomebiology.biomedcentral.com/articles/10.1186/s13059-017-1349-1

28. Liberzon A, Birger C, Thorvaldsdóttir H, Ghandi M, Mesirov JP, Tamayo P. The Molecular
Signatures Database Hallmark Gene Set Collection. Cell Syst. 2015;1:417–25.

29. Rincón E, Rocha-Gregg BL, Collins SR. A map of gene expression in neutrophil-like cell lines.
BMC Genomics. 2018;19:573.

30. Novershtern N, Subramanian A, Lawton LN, Mak RH, Haining WN, McConkey ME, et al.
Densely interconnected transcriptional circuits control cell states in human hematopoiesis. Cell.
2011;144:296–309.

31. Greenman C, Stephens P, Smith R, Dalgliesh GL, Hunter C, Bignell G, et al. Patterns of
somatic mutation in human cancer genomes. Nature. 2007;446:153–8.

32. Dincer AB, Celik S, Hiranuma N, Lee S-I. DeepProfile: Deep learning of cancer molecular
profiles for precision medicine. bioRxiv [Internet]. 2018 [cited 2019 Sep 17]; Available from:
http://biorxiv.org/lookup/doi/10.1101/278739

33. Taroni JN, Grayson PC, Hu Q, Eddy S, Kretzler M, Merkel PA, et al. MultiPLIER: a transfer
learning framework reveals systemic features of rare autoimmune disease. 2018 [cited 2018
Sep 9]; Available from: http://biorxiv.org/lookup/doi/10.1101/395947

34. Wang J, Agarwal D, Huang M, Hu G, Zhou Z, Ye C, et al. Data denoising with transfer learning
in single-cell transcriptomics. Nat Methods. 2019;16:875–8.

35. Shi J, Luo Z. Nonlinear dimensionality reduction of gene expression data for visualization
and clustering analysis of cancer tissue samples. Comput Biol Med. 2010;40:723–32.

36. Bartenhagen C, Klein H-U, Ruckert C, Jiang X, Dugas M. Comparative study of unsupervised
dimension reduction techniques for the visualization of microarray gene expression data. BMC
Bioinformatics [Internet]. 2010 [cited 2019 Jan 26];11. Available from:
https://bmcbioinformatics.biomedcentral.com/articles/10.1186/1471-2105-11-567

37. Becht E, McInnes L, Healy J, Dutertre C-A, Kwok IWH, Ng LG, et al. Dimensionality reduction
for visualizing single-cell data using UMAP. Nat Biotechnol. 2018;37:38–44.

38. Kobak D, Berens P. The art of using t-SNE for single-cell transcriptomics. bioRxiv [Internet].
2018 [cited 2019 Jan 26];http://biorxiv.org/lookup/doi/10.1101/453449. Available from:
http://biorxiv.org/lookup/doi/10.1101/453449

39. Maaten L van der, Hinton G. Visualizing Data using t-SNE. J Mach Learn Res. 2008;9:2579–
605.

40. McInnes L, Healy J, Melville J. UMAP: Uniform Manifold Approximation and Projection for
Dimension Reduction. arXiv:180203426 [Internet]. 2018; Available from:
https://arxiv.org/abs/1802.03426

41. Ben-Hur A, Elisseeff A, Guyon I. A stability based method for discovering structure in
clustered data. Pac Symp Biocomput Pac Symp Biocomput. 2002;6–17.

42. Wang J. Consistent selection of the number of clusters via crossvalidation. Biometrika.
2010;97:893–904.

43. Wang L, Wang X. Hierarchical Dirichlet process model for gene expression clustering.
EURASIP J Bioinforma Syst Biol. 2013;2013:5.

44. Wang M, Abrams ZB, Kornblau SM, Coombes KR. Thresher: determining the number of
clusters while removing outliers. BMC Bioinformatics. 2018;19:9.

45. Wu S, Joseph A, Hammonds AS, Celniker SE, Yu B, Frise E. Stability-driven nonnegative
matrix factorization to interpret spatial gene expression and build local gene networks. Proc
Natl Acad Sci. 2016;113:4290–5.

46. Zhou W, Altman RB. Data-driven human transcriptomic modules determined by
independent component analysis. BMC Bioinformatics [Internet]. 2018 [cited 2018 Dec 22];19.
Available from: https://bmcbioinformatics.biomedcentral.com/articles/10.1186/s12859-018-
2338-4

47. Leek JT, Storey JD. Capturing Heterogeneity in Gene Expression Studies by Surrogate
Variable Analysis. PLoS Genet. 2007;3:e161.

48. Teschendorff AE, Zhuang J, Widschwendter M. Independent surrogate variable analysis to
deconvolve confounding factors in large-scale microarray profiling studies. Bioinformatics.
2011;27:1496–505.

49. Lopez R, Regier J, Cole MB, Jordan MI, Yosef N. Deep generative modeling for single-cell
transcriptomics. Nat Methods. 2018;15:1053–8.

50. Shrikumar A, Greenside P, Kundaje A. Learning Important Features Through Propagating
Activation Differences. ArXiv170402685 Cs [Internet]. 2017; Available from:
http://arxiv.org/abs/1704.02685

51. Lin C, Jain S, Kim H, Bar-Joseph Z. Using neural networks for reducing the dimensions of
single-cell RNA-Seq data. Nucleic Acids Res. 2017;45:e156–e156.

52. Wang J, Vasaikar S, Shi Z, Greer M, Zhang B. WebGestalt 2017: a more comprehensive,
powerful, flexible and interactive gene set enrichment analysis toolkit. Nucleic Acids Res.
2017;45:W130–7.

53. Fang Z, Tian W, Ji H. A network-based gene-weighting approach for pathway analysis. Cell
Res. 2012;22:565–80.

54. Dong X, Hao Y, Wang X, Tian W. LEGO: a novel method for gene set over-representation
analysis by incorporating network-based gene weights. Sci Rep [Internet]. 2016 [cited 2019 Jan
14];6. Available from: http://www.nature.com/articles/srep18871

55. Goldman M, Craft B, Kamath A, Brooks AN, Zhu J, Haussler D. The UCSC Xena Platform for
cancer genomics data visualization and interpretation. bioRxiv [Internet]. 2018 [cited 2019 Jan
21]; Available from: http://biorxiv.org/lookup/doi/10.1101/326470

56. Vivian J, Rao AA, Nothaft FA, Ketchum C, Armstrong J, Novak A, et al. Toil enables
reproducible, open source, big biomedical data analyses. Nat Biotechnol. 2017;35:314–6.

57. Baldi P, Hornik K. Neural networks and principal component analysis: Learning from
examples without local minima. Neural Netw. 1989;2:53–8.

58. Vincent P, Larochelle H, Bengio Y, Manzagol P-A. Extracting and Composing Robust Features
with Denoising Autoencoders. Proc 25th Int Conf Mach Learn [Internet]. New York, NY, USA:
ACM; 2008. p. 1096–1103. Available from: http://doi.acm.org/10.1145/1390156.1390294

59. Kingma DP, Welling M. Auto-Encoding Variational Bayes. ArXiv13126114 Cs Stat [Internet].
2013 [cited 2017 Mar 6]; Available from: http://arxiv.org/abs/1312.6114

60. Rezende DJ, Mohamed S, Wierstra D. Stochastic Backpropagation and Approximate
Inference in Deep Generative Models. ArXiv14014082 Cs Stat [Internet]. 2014 [cited 2017 May
10]; Available from: http://arxiv.org/abs/1401.4082

61. Pedregosa F, Varoquaux G, Gramfort A, Michel V, Thirion B, Grisel O, et al. Scikit-learn:
Machine Learning in Python. J Mach Learn Res. 2011;12:2825–30.

62. Harenza JL. Transcriptomic profiling of 39 commonly-used neuroblastoma cell lines.
2019;https://figshare.com/articles/STAR-reads/7613975/3.

63. Himmelstein DS, Lizee A, Hessler C, Brueggeman L, Chen SL, Hadley D, et al. Systematic
integration of biomedical knowledge prioritizes drugs for repurposing. eLife. 2017;6.

64. Hanhijärvi S, Garriga GC, Puolamäki K. Randomization Techniques for Graphs. Proc 2009
SIAM Int Conf Data Min. 2009;780–91.

65. Drexler HG, Dirks WG, Matsuo Y, MacLeod R a. F. False leukemia-lymphoma cell lines: an
update on over 500 cell lines. Leukemia. 2003;17:416–26.

66. Jacob C, Leport M, Szilagyi C, Allen JM, Bertrand C, Lagente V. DMSO-treated HL60 cells: a
model of neutrophil-like cells mainly expressing PDE4B subtype. Int Immunopharmacol.
2002;2:1647–56.

67. Way GP, Sanchez-Vega F, La K, Armenia J, Chatila WK, Luna A, et al. Machine Learning
Detects Pan-cancer Ras Pathway Activation in The Cancer Genome Atlas. Cell Rep.
2018;23:172–180.e3.

68. Ellrott K, Bailey MH, Saksena G, Covington KR, Kandoth C, Stewart C, et al. Scalable Open
Science Approach for Mutation Calling of Tumor Exomes Using Multiple Genomic Pipelines. Cell
Syst. 2018;6:271–281.e7.

69. Vogelstein B, Papadopoulos N, Velculescu VE, Zhou S, Diaz LA, Kinzler KW. Cancer Genome
Landscapes. Science. 2013;339:1546–58.

70. Mermel CH, Schumacher SE, Hill B, Meyerson ML, Beroukhim R, Getz G. GISTIC2.0 facilitates
sensitive and confident localization of the targets of focal somatic copy-number alteration in
human cancers. Genome Biol. 2011;12:R41.

71. Zou H, Hastie T. Regularization and variable selection via the elastic net. J R Stat Soc Ser B
Stat Methodol. 2005;67:301–20.

72. Way G. greenelab/BioBombe: BioBombe Analysis Version 1.2 [Internet]. Zenodo; 2019
[cited 2019 Mar 9]. Available from: https://zenodo.org/record/3460539

1015