Hierarchical representation of multi-step tasks in multiple-demand and default mode networks

(Abbreviated title: Task episode representation in cortical networks)

Tanya Wen[1]*, John Duncan[1,2]†, and Daniel J Mitchell[1]†

[1]Medical Research Council, Cognition and Brain Sciences Unit, University of Cambridge, 15 Chaucer Road, Cambridge, CB2 7EF, United Kingdom

[2]Department of Experimental Psychology, University of Oxford, Radcliffe Observatory, Anna Watts Building, Woodstock Rd, Oxford, OX2 6GG, United Kingdom

* Corresponding author email address: tanya.wen@duke.edu

† Joint senior authors

Number of pages: 37

Number of figures: 6 (Images of faces are covered to comply with bioRxiv requirements)

Number of words for abstract: 230

Number of words for introduction: 649

Number of words for discussion: 1467

The authors declare no competing financial interests.

Acknowledgements

This work was supported by funding from the Medical Research Council (United Kingdom), program SUAG/045/G101400. TW was supported by the Medical Research Council PhD Studentship, Taiwan Cambridge Scholarship from the Cambridge Commonwealth, European & International Trust, and the Percy Lander studentship from Downing College.

Abstract

Task episodes consist of sequences of steps that are performed to achieve a goal. We used fMRI to examine neural representation of task identity, component items, and sequential position, focusing on two major cortical systems – the multiple-demand (MD) and default mode networks (DMN). Human participants (20 male, 22 female) learned six tasks each consisting of four steps. Inside the scanner, participants were cued which task to perform and then sequentially identified the target item of each step in the correct order. Univariate time-course analyses indicated that intra-episode progress was tracked by a tonically increasing global response, plus an increasing phasic step response specific to MD regions. Inter-episode boundaries evoked a widespread response at episode onset, plus a marked offset response specific to DMN regions. Representational similarity analysis was used to examine encoding of task identity and component steps. Both networks represented the content and position of individual steps, but the DMN preferentially represented task identity while the MD network preferentially represented step-level information. Thus, although both DMN and MD networks are sensitive to step-level and episode-level information in the context of hierarchical task performance, they exhibit dissociable profiles in terms of both temporal dynamics and representational content. The results suggest collaboration of multiple brain regions in control of multi-step behavior, with MD regions particularly involved in processing the detail of individual steps, and DMN adding representation of broad task context.

Significance Statement

Achieving one's goals requires knowing what to do and when. Tasks are typically hierarchical, with

smaller steps nested within overarching goals. For effective, flexible behavior, the brain must represent

both levels. We contrast response time-courses and information content of two major cortical systems –

the multiple-demand (MD) and default mode networks (DMN) – during multi-step task episodes. Both

networks are sensitive to step-level and episode-level information, but with dissociable profiles. Intra-

episode progress is tracked by tonically increasing global responses, plus MD-specific increasing phasic

step responses. Inter-episode boundaries evoke widespread responses at episode onset, plus DMN-specific

offset responses. Both networks encode content and position of individual steps, but the DMN and MD

networks favor task identity and step-level information respectively.

Introduction

Purposeful behavior requires retrieval of memorized sequences (Hsieh and Ranganath, 2015) to guide current actions, with overarching goals or "task episodes" (e.g., "make stew") decomposed into achievable steps ("wash vegetables" → "chop" → "cook") (Cooper and Shallice, 2000; Schneider and Logan, 2006; Duncan, 2010; Farooqui and Manly, 2019). As each step is completed, its specific content loses relevance, while higher-level representations of the full task episode remain in behavioral control. This raises the question of how brain regions work together to execute a current step while keeping an overall goal in mind.

Previous literature highlights the importance of a frontoparietal "multiple-demand" (MD) network in controlling complex mental programs (Duncan, 2010, 2013). MD regions are sensitive to hierarchical task structure (Farooqui et al., 2012; Desrochers et al., 2015), and are well-suited for focusing on specific contents of current cognition, preferentially encoding task-relevant information (Asaad et al., 2000; Everling et al., 2002; Li et al., 2007), and radically changing activity patterns across successive task steps (Sigala et al., 2008).

Representation of event sequences is also critical in episodic memory research (Ezzyat and Davachi, 2011; Hsieh et al., 2014; Cohn-Sheehy and Ranganath, 2017). Event segmentation theory (Zacks and Tversky, 2001; Radvansky and Zacks, 2017) proposes that humans segment incoming information into temporally meaningful chunks; when important situation features change, an update to the event model is experienced as an event boundary. Event boundaries may activate regions resembling the MD network (Zacks et al., 2001; Sridharan et al., 2007), but also areas associated with episodic memory, including the hippocampus (Ben-Yakov et al., 2013; Ben-Yakov and Henson, 2018) and the default mode network (DMN) (Speer et al., 2007), or both (Ezzyat and Davachi, 2011). The DMN is implicated in high-level cognition at a broad scale, including encoding of schemas (Robin and Moscovitch, 2017), situation models (Reagh and Ranganath, 2018), and cognitive contexts (Crittenden et al., 2015). The DMN response to event

boundaries likely reflects meaningful extended episodes, because activation is greater at boundaries rated

as separating long meaningful events than boundaries separating shorter events (Speer et al., 2007).

Similarly, temporal scrambling of narrative stimuli suggests a cortical hierarchy of temporal receptive

windows (Lerner et al., 2011), with short-timescale processing in sensory regions, where inter-subject

pattern consistency is robust to fine-scale scrambling, intermediate timescales in MD regions, and longest-

timescale processing in DMN regions, where pattern consistency is sensitive to even coarse scrambling

(Chen et al., 2016). An investigation of multi-voxel pattern transitions during narrative perception

(Baldassano et al., 2018) found the longest-timescale event representations in posterior medial cortex and

the intraparietal sulcus, within the DMN and MD networks respectively. Neural event structure was found

to match across visual and auditory modalities near the temporoparietal junction and in lateral frontal

cortex, again within DMN and MD networks respectively. Overall, the literature suggests that both DMN

and MD networks are potentially well-suited to representing task episodes over extended timescales.

To our knowledge, no study has contrasted the roles of the DMN and MD networks in representing

different aspects of task episodes. We therefore examined how these networks represent information at

multiple levels of abstraction within a task: individual steps, including content and position within an

episode, the whole task, and groups of related tasks. Participants learned four-step tasks associated with

different rooms (kitchen or bathroom), and then sequentially identified target items corresponding to each

step of cued tasks. Thus, we could quantify neural representation of rooms (e.g. kitchen), tasks (e.g. "make

stew"), steps (e.g. third) and items associated with steps (e.g. "wash vegetables"). We used univariate

event-related and finite impulse response (FIR) analyses to characterize the temporal evolution of activity

across episodes, and representational similarity analysis (RSA) to investigate representations of task

structure and content. We hypothesized that different brain regions would be preferentially sensitive to

different levels of the temporal task hierarchy, and focused on the MD and DMN networks as *a priori*

regions of interest.

Methods

Participants

42 participants (20 male, 22 female; ages 18-39, mean = 26.79, SD = 4.77) were included in the experiment at the MRC Cognition and Brain Sciences Unit. An additional 19 participants were excluded (two were discovered to have cysts, one lost several slices due to poor bounding box positioning, ten were excluded due to having no correct episodes for at least one combination of cued task × distractor task (see later), and a further six were excluded due to excessive head motion > 5 mm). All participants were neurologically healthy, right-handed, with normal or corrected-to-normal vision. Procedures were carried out in accordance with ethical approval obtained from the Cambridge Psychology Research Ethics Committee, and participants provided written, informed consent before the start of the experiment

Stimuli and task procedures

The study consisted of a learning session outside the scanner and an execution session in the scanner. During the learning session, participants learned six everyday task sequences, each based in one of two locations ("rooms"; three kitchen and three bathroom). Each task consisted of four ordered "steps". For example, the task "make a stew" consisted of the steps "take food from fridge", "wash vegetables", "chop vegetables", "cook on stove". Each step was associated with a unique image ("item"). The complete set of stimuli is shown in Figure 1A.

Figure 1. (A) Illustration of the six tasks (three kitchen and three bathroom tasks) memorized before going

into the scanner. Each task consisted of four steps to be completed in serial order (e.g., the task "make a

stew" consisted of "take food from fridge", "wash vegetables", "chop vegetables", "cook on stove").

(B) Structure of an example task episode. Episodes began with a cue indicating which task to perform

(e.g., "make a stew"). After a short delay, the first search array of four items appeared, and participants

were asked to select the item corresponding to the first step of that task (here, "take food from fridge").

Participants selected this same target in three search arrays (total step duration = 9 s), then were given

a brief indicator that the step had been completed, and moved on to the next step (here "wash

vegetables"). Completion of all four steps completed the entire task episode.

In the learning session, participants viewed the names and images of the steps of each task in sequential

order. The step images were presented simultaneously with a background image corresponding to the

room in which they occur (kitchen or bathroom). The learning was self-paced, in separate runs for each

room. Within each room, each task sequence was presented three times, and each item within the sequence

was presented until the participant decided to move on to the next item. There was a 1.5 s inter-stimulus

interval between items. After viewing all six sequences, participants were tested for their memory of the

tasks by (1) sorting picture cards representing all steps of the six tasks into the correct sequences, and (2)

completing a pen-and-paper test in which they were asked to write down the names of the steps in the

correct order for each task. Most participants performed both tests without error. A few participants made

a mistake on 1-2 items but were able to correct their answers after being told they made a mistake. The

tests ensured participants had memorized the specific step sequence of each task. Before entering the

scanner, participants practiced a shortened version of the main experiment, containing one episode of each

task. During scanning, participants performed two runs of the experiment, interleaved with shorter runs

(~5 minutes) of a localizer task that was not analyzed and is not described further.

Figure 1B illustrates the structure of the task episodes paradigm. At the start of each 45 s episode,

participants were presented with a cue (e.g., "make a stew") for 1 s, indicating which task to complete.

This was followed by a fixation period lasting between 1.5 – 7.5 s, selected randomly from a uniform

distribution, before the onset of the first step. On each step, participants had to perform three visual

searches. On each search, an array of four images was presented in a horizontal row (total left to right

visual angle approximately 12.6°). These included (randomly ordered from left to right): (1) the correct

image ("target") corresponding to the current task step; (2) a distractor image representing a random

incorrect step from the correct task; (3) a distractor representing the correct step but from an incorrect task

("distractor task"); and (4) an additional distractor representing the same incorrect step as (2), from the

same incorrect task as (3). To ensure that each display contained two images from each room, distractor

tasks were selected at random from the alternative room to the cued task. The array remained for 2 s, and

within this time, the participant had to indicate the position of the target image using a 4-choice button

box with their right hand. A 1 s fixation interval preceded onset of the next search array. Each step thus

lasted for 9 s, with the participant selecting the same target in each of three search events, to allow

separation of the hemodynamic response to successive task steps, while ensuring sustained focus on the

relevant item within each step. At the end of the third search event, a 0.2 s presentation of the words

"STEP COMPLETED" indicated the completion of that step, followed by a 0.8 s fixation interval.

Without further cueing, the participant then moved on to the next task step. After completing the last step,

a fixation interval of 0.5 – 6.5 s was presented before the onset of the cue for the next task. The total

interval between the last step of the previous task and the first step of the next task was fixed at 9 s.

Participants were not given feedback on their accuracy. Each run consisted of 36 task episodes (with an

additional dummy episode to start), constructed so that each task appeared following each possible

preceding task once. Task ordering was chosen before the start of each run to maximize the design

efficiency (Dale, 1999) of all pairwise contrasts between tasks. 1000 task orders were simulated, and the

most efficient one was chosen. Each of the two runs lasted ~28 min.

fMRI data acquisition and preprocessing

Scanning took place in a 3T Siemens Prisma scanner. Functional images were acquired using a multi-

band gradient-echo echo-planar imaging (EPI) pulse sequence (TR = 1373 ms, TE = 33.4 ms, flip angle

= 74°, 96 × 96 matrices, slice thickness = 2 mm, no gap, voxel size 2 mm × 2 mm × 2 mm, 72 axial slices

covering the entire brain, 4 slices acquired at once). The first 5 volumes served as dummy scans and were

discarded to avoid T1 equilibrium effects. Field maps were collected at the end of the experiment (TR =

400 ms, TE = 5.19 ms / 7.65 ms, flip angle = 60°, 64 × 64 matrices, slice thickness = 3 mm, 25% gap,

resolution 3 mm isotropic, 32 axial slices). High-resolution anatomical T1-weighted images were acquired

for each participant using a 3D MPRAGE sequence (192 axial slices, TR = 2250 ms, TI = 900 ms, TE =

2.99 ms, flip angle = 9°, field of view = 256 mm × 240 mm × 160 mm, matrix dimensions = 256 × 240 ×

160, 1 mm isotropic resolution).

The data were preprocessed and analyzed using automatic analysis (aa) pipelines and modules (Cusack et

al., 2015), which called relevant functions from Statistical Parametric Mapping software (SPM 12,

http://www.fil.ion.ucl.ac.uk/spm) implemented in Matlab (The MathWorks, Inc., Natick, MA, USA). EPI

images were realigned to correct for head motion using rigid-body transformation, unwarped based on the

field maps to correct for voxel displacement due to magnetic-field inhomogeneity, and slice time

corrected. The T1 image was coregistered to the mean EPI, and then coregistered and normalized to the

MNI template. The normalization parameters of the T1 image were applied to all functional volumes. The

data and models (see below) were temporally high-pass filtered with a cutoff at 1/128 Hz. Spatial

smoothing of 10 mm FWHM was applied for the univariate whole-brain analysis, but not for the univariate

ROI analysis or prior to multivariate analysis.

Regions of interest (ROIs)

For the primary analysis, we focused on the MD and DMN networks (see Figure 4). The MD network

was based on data from Fedorenko et al. (2013; Figure 2 in their paper), selecting frontoparietal regions

responsive   to   cognitive   demands   across   seven   diverse   tasks   (http://imaging.mrc-

cbu.cam.ac.uk/imaging/MDsystem). The DMN network was taken from Yeo et al. (2011), combining

three subnetworks from the 17 network parcellation (numbers 15, 16, and 17) (Andrews-Hanna, 2012).

The left and right hemispheres were averaged and projected back to both hemispheres to create a

symmetrical volume (similar to Fedorenko et al., 2013). The combined networks were then smoothed at

4 mm FWHM to eliminate isolated voxels.

Both the MD network (Dosenbach et al., 2006; Dosenbach et al., 2007; Crittenden et al., 2016) and the

DMN (Andrews-Hanna et al., 2010; Andrews-Hanna, 2012; Wen et al., 2019) can be divided into finer

components or subsystems, and following whole-network analysis, we examined separate sub-regions

within each network. MD component ROIs (Mitchell et al., 2016) included three clusters along the

anterior, middle, and posterior middle frontal gyrus (aMFG, mMFG, and pMFG), a posterior-dorsal region

of lateral frontal cortex (pdLFC) in the superior precentral sulcus, and clusters in the intraparietal sulcus

(IPS), anterior insula (AI), and anterior cingulate cortex (ACC). DMN component ROIs were defined as

spatially separate clusters within the overall network, consisting of the medial prefrontal cortex (MPFC)

and posterior cingulate cortex (PCC) along the midline, as well as the inferior frontal gyrus (IFG), inferior

parietal lobule (IPL), parahippocampal cortex (PHC), and parts of the lateral temporal cortex extending

to the temporal pole (Temp). Overlapping voxels of the AI and IFG were excluded from each ROI and

their corresponding networks. Analyses were first performed using each network as a single large ROI,

and then within each component ROI to examine more fine scale differences within each network. We

controlled the False Discovery Rate (FDR) to correct for multiple comparisons across the number of

networks (2) and component ROIs (13), respectively (Benjamini and Yekutieli, 2001).

Univariate analysis

FIR Model

Statistical analyses were performed first at the individual level, using a general linear model (GLM). To

capture the BOLD time-course throughout each task episode, as well as transitions between episodes, we

modeled each consecutive pair of episodes. The first (dummy) episode was separately modeled and not

analyzed. For the remaining data, a 90 s period starting from the onset of the first search array of every

even number episode to the first search array of the next even number episode was modeled using a finite

impulse response (FIR) basis set of 60 1.5 s boxcar regressors. In this way, the response throughout task

episodes could be modelled without making assumptions about the shape of the hemodynamic response.

Episodes with a high proportion of errors (episodes that had > 25% errors) were defined as error episodes,

with the total number of error episodes per participant ranging from 0-6 (mean = 0.95, SD = 1.43). Any

two consecutive error episodes were removed from the analysis using a similar but separate set of

regressors. Effects of cues, and errors on individual search arrays, were also modeled separately, by

convolving the duration of their respective events (1 s for cues and 2 s for error events) with a canonical

hemodynamic response function. The six motion parameters and block means were included as regressors

of no interest. Across the 90 s period, estimates for each FIR time bin were extracted from each whole

network or component ROI, averaged over voxels within the region and across the six tasks. These average

beta estimates for individual participants were entered into a random effects group analysis.

Event-based GLM analysis

To complement the FIR model, an event-based GLM analysis was performed. In this analysis, we aimed

to separate phasic activity linked to onset of each step from tonic activity across the whole step within

each episode. To control for the degree of visual difference between the search arrays of pairs of episodes,

each combination of cued task × distractor task was modeled separately. For each combination, each step

was modelled using two regressors, an onset regressor modelled with 0 s duration and an epoch regressor

modelled with 9 s duration. Additionally, an offset regressor modelled with 0 s duration was placed at the

end of the episode (following the final search array). Each regressor was convolved with the canonical

hemodynamic response function. There were accordingly 162 regressors of interest, two (onset and epoch)

for each of the four steps and one for the offset of the entire episode in each combination of six tasks ×

three possible distractor tasks from the other room (for example, the target task "make a stew" could be

paired with distractor tasks "wash face", "scrub toilet", or "clean teeth"). Error episodes (defined as

episodes that had > 25% errors) were removed from the analysis using a similar but separate set of

regressors. The cue was modelled separately using a similar combination of onset (0 s duration) and epoch

(duration from cue onset to the onset of the first task step) regressors. Motion parameters and block mean

regressors were included as before. Beta estimates were averaged across the 18 cued task × distractor task

combinations for individual participants, and entered into random effects group analyses. We first

examined the mean effect of onset/offset and epoch regressors versus implicit baseline (with FDR

correction across ROIs). Repeated measures analyses of variance (ANOVAs) were used to examine

changes across steps, including linear and quadratic trends. To complement the ROI analyses, contrasts

were also carried out at the whole brain level, using a voxel-wise FDR-corrected threshold of $p < 0.025$

per tail. Results were rendered using MRIcroGL (version 1.2.20190902;

www.nitrc.org/projects/mricrogl).

RSA analysis

We performed representational similarity analysis (RSA) using the linear discriminant contrast (LDC) to

quantify dissimilarities between activation patterns. The analysis used the RSA toolbox (Nili et al., 2014),

in conjunction with in-house software. The LDC was chosen because it is multivariate noise-normalized,

potentially increasing sensitivity, and is a cross-validated measure which is distributed around zero when

the true distance is zero (Walther et al., 2016). The LDC also allows inference on contrasts of

dissimilarities across multiple pairs of task events. A pattern for each step of each combination of cued

task and distractor task was obtained, by averaging the onset and epoched responses from the event-based

GLM described above. This resulted in 72 patterns in total in each run. For each pair of patterns, the

patterns from run 1 were projected onto a Fisher discriminant fitted for run 2, with the difference between

the projected patterns providing a cross-validated estimate of a squared Mahalanobis distance. This was

repeated projecting run 2 onto run 1, and we took the average as the dissimilarity measure between the

two patterns. All pairs of pattern dissimilarities therefore formed a symmetrical representational

dissimilarity matrix (RDM) with zeros on the diagonal by definition. To allow comparison of dissimilarity

magnitude across ROIs of different sizes, the LDC values were normalized by dividing by the number of

voxels within each ROI.

As for univariate analyses, we first performed RSA analysis using activation patterns from the DMN and MD networks treated as single large ROIs, and then repeated it on component ROIs. To introduce measures for room, task, step and item coding, Figure 2A shows a simplified version of the full 72×72 representational dissimilarity matrix (RDM), collapsing across distractor task to produce just a 24 x 24 matrix. In this matrix, each cell represents a cross-validated LDC dissimilarity between the corresponding two task events. These included event pairs that shared the same cued task (red cells; e.g., "take food from fridge" and "wash vegetables"); events that shared the same room but different cued tasks (purple cells; e.g., "take food from fridge" and "hand mix batter"); and events that differed in both cued task and room (orange cells; e.g. "take food from fridge" and "use facial wash"). All event pairs additionally differed in item. Saturation of the colors is used to indicate the difference in steps between event pairs. The cells on the diagonal (white) are zero by definition as they do not reflect a comparison between different task events.

To extract measures for room, task, step and item coding, we fit values in the matrix with the regression model illustrated in Figure 2B. In this model, the LDC estimate for any entry in the matrix is the linear sum of components from differences in target item (contributing equally to all cells; major diagonal of the matrix ignored), room, task, and step. As a measure of step coding, we used the slope of the function relating LDC estimate to step difference. For example, steps 1 and 2 have a step difference of 1, while steps 1 and 4 have a step difference of 3. As a measure of room coding, we used the difference in LDC estimate for different room and same room/different task cases (Figure 2B, orange vs. purple). As a measure of task coding, we used the difference in LDC dissimilarity for same room/different task and same task cases (Figure 2B, purple vs red). As item difference contributed similarly to all cells, it was estimated as the intercept of the full model (Figure 2B, black dot).

For the actual fitting, we used a more complex model based on the full 72 x 72 RDM, used to remove a potential visual confound (see Extended Data Figure 2-1). For any cell in the full RDM, search arrays

could share items from zero, one, or two tasks. For example, consider an episode with cued task "make a

stew" and distractor items coming from the distractor task "wash face". Search arrays from this episode

would share no items with search arrays from an episode of "bake cupcakes" with distractors from "scrub

toilet"; arrays would share items from one task when compared to the episode "make a stew" with

distractors from "wash face"; arrays would share items from both tasks when compared to the episode

"wash face" with distractors from "make a stew". In the full model, we added an additional regressor to

remove this potential visual confound. This was defined as "visual difference", with values of 1 for no

shared tasks, 0.5 for one shared task, and 0 for two shared tasks. The mean coding estimates across subjects

were tested against zero using 1-tailed t-tests, and multiple comparisons across ROIs were corrected using

FDR <0.05 per measure.

Figure 2. Illustration of representational similarity analysis. A. Simplified conceptual RDM. LDC dissimilarities are computed between every possible pair of events (6 cued tasks × 4 steps), generating a 24 × 24 RDM. Diagonal cells of the RDM are zero by definition as they do not reflect a dissimilarity between different events. Off-diagonal cells reflect pattern dissimilarity between events that always differ in search item, with varying additional differences in room, task, and step. B. Hypothetical pattern dissimilarities resulting from room, task, and item coding across step differences. Item coding can be estimated as the intercept, i.e., estimated LDC dissimilarity in in the absence of room, task, or step differences.

Experimental Design and Statistical Analysis

All statistical tests were performed across 42 participants (20 male, 22 female), with no between-subject factors. Behavioral analyses used repeated measures ANOVA to compare conditions. Univariate fMRI analyses used one-sample (paired–sample) two-tailed t-tests to compare responses against baseline, between conditions, or linear contrasts of regression coefficients, and repeated measures ANOVA to compare multiple conditions. RSA fMRI analyses used one-sample one-tailed t-tests to test for greater-than-chance encoding of each information type, paired-sample two-tailed t-tests to compare networks, and repeated measures ANOVA to test the interaction of information type and network. Within-subject factors are detailed in the relevant Results sections. For each analysis, multiple comparisons (across 2 networks, 13 component ROIs, or all brain voxels) were accounted for by controlling the FDR at 0.05, unless noted otherwise. Effect sizes were calculated using partial Eta-squared for ANOVAs and Cohen's d for t-tests. Analyses were performed using Matlab (The MathWorks, Inc., Natick, MA, USA), SPM 12 (http://www.fil.ion.ucl.ac.uk/spm), and SPSS (version 25). In repeated measures ANOVA, Greenhouse-Geisser correction was used to adjust for non-sphericity. Data are available on request.

Results

Behavioral results

Group behavioral performance is shown in Figure 3. Error rates were calculated after removal of occasional whole error episodes (defined as episodes that had > 25% errors, suggesting that the correct cue was not being followed; 0-6 across participants), and reaction time was calculated for only correct trials. Overall accuracy was 97.5% ± 0.4% (mean ± SEM) and overall reaction time was 849 ± 23 ms. Error responses were broken into four error types: choosing an item from the correct task but wrong step, wrong task but correct step, wrong task and step, and missed response. Results show poorest performance

for the first search array of each step, when participants were required to switch from one step to the next.

A step (steps 1-4) × search array (first, second, third within each step) ANOVA was performed for each

type of error. All error types showed a main effect of step (all $F(3,123) > 3.79$, all $ps < 0.03$, all $\eta_p^2 >$

0.08), and linear trend analyses indicated an overall increase in error across steps (all $F(1,41) > 7.70$, all

$ps < 0.01$, all $\eta_p^2 > 0.15$). A main effect of search array was found for correct task wrong step errors, as

well as for missed responses (both $F(2,82) > 14.36$; both $ps < 0.001$, both $\eta_p^2 > 0.25$), reflecting higher

errors on the first search array of each step. Finally, correct task wrong step errors showed a significant

step × array interaction ($F(6,246) = 5.96$, $p < 0.001$, $\eta_p^2 = 0.13$). A similar ANOVA for reaction time also

showed a significant main effect for step ($F(3,123) = 17.21$, $p < 0.001$, $\eta_p^2 = 0.30$), a significant main

effect for search array ($F(2,82) = 234.42$, $p < 0.001$, $\eta_p^2 = 0.85$), and a significant step × array interaction

($F(6,246) = 9.83$, $p < 0.001$, $\eta_p^2 = 0.19$).

Figure 3. Behavioral performance summarized according to four possible error types (choosing an item

from correct task but wrong step, wrong task but correct step, wrong task and step, and missed response),

as well as reaction time for correct responses. For each step, the three bars indicate performance on each

of the three successive search arrays. Error bars indicate standard error of the mean.

Univariate results

ROI analysis

The FIR model provided estimates of the observed BOLD response time-course across a pair of task

episodes, in successive 1.5 s windows starting from the onset of the first step. In the main analysis, we

extracted these FIR responses from *a priori* networks (Figure 4, left). The MD network exhibited positive

activity throughout each episode, along with four peaks corresponding to the four steps. These results

suggest involvement in setting up and executing individual task steps. Additionally, overall MD activity

gradually increased throughout the task episode, suggesting that the MD network is also sensitive to

progress through the episode. For DMN regions, in contrast, tonic activation began below baseline but

gradually increased through the episode, culminating in a large phasic response at episode completion.

For both networks, the signal clearly resets between episodes.

To quantify the phasic and tonic components contributing to the BOLD response at each task step, we

performed a complementary GLM analysis with onset and epoch regressors modelling each task step

(Figure 4, middle). Four onset regressors were designed to reflect phasic activity at the onset of each task

step. The final offset regressor was included to capture the phasic activity at the end of the episode. Finally,

epoch regressors were designed to reflect tonic activity throughout each step.

Within the MD network, there were strong onset responses, in line with FIR results. Contrasts with

baseline showed that all four step onsets were significantly greater than baseline (all ts > 10.91, all ps <

0.001, all ds > 1.68) and there was a smaller yet significant offset response ($t = 2.48$, $p = 0.02$, $d = 0.38$).

A one-way repeated measures ANOVA showed a significant difference across the four step onsets

($F(3,123) = 5.60$, $p < 0.01$, $\eta_p^2 = 0.12$), with a quadratic ($F(1,41) = 21.61$, $p < 0.001$, $\eta_p^2 = 0.35$) but not

linear ($F(1,41) = 0.22$, $p = 0.64$, $\eta_p^2 < 0.01$) trend across steps, reflecting an increasing response across

steps 2-4, but a disproportionate response to the onset of the first step, i.e. the onset of the entire episode.

Looking at epoch regressors, all four epoch responses were greater than baseline (all ts > 3.96, all ps <

0.001, all ds > 0.61). ANOVA showed a significant main effect of step ($F_{(3,123)} = 7.73$, $p = 0.01$, $\eta_p^2 =$

0.16), as well as a significant linear ($F_{(1,41)} = 9.48$, $p < 0.01$, $\eta_p^2 = 0.19$) and quadratic trend ($F_{(1,41)} =$

5.08, $p = 0.03$, $\eta_p^2 = 0.11$), reflecting an increasing but saturating response.

The DMN network showed a different profile. Only the onset of the first step ($t = 3.22$, $p < 0.01$, d = 0.50)

and the offset response at the end of the episode ($t = 4.38$, $p < 0.001$, d = 0.68) were greater than baseline.

Step onsets 2-4 were not significantly different from baseline (all $|t|$s < 2.09, all ps > 0.07, all $|d|$s < 0.33).

ANOVA of the four step onsets showed a significant main effect of step ($F_{(3,123)} = 9.87$, $p < 0.001$, η_p^2

= 0.19), as well as significant linear ($F_{(1,41)} = 9.70$, $p < 0.01$, $\eta_p^2 = 0.19$) and quadratic ($F_{(1,41)} = 7.16$,

$p = 0.01$, $\eta_p^2 = 0.15$) trends, consistent with the larger response to the first onset. Among the epoch

responses, the first step was significantly lower than baseline (t = -3.21, p = 0.01, d = -0.49; for steps 2-4

all $|t|$s < 1.60, all ps > 0.23, all $|d|$s < 0.19). ANOVA showed a significant main effect of step ($F_{(3,123)} =$

18.42, $p < 0.001$, $\eta_p^2 = 0.31$), as well as a significant linear trend ($F_{(1,41)} = 38.89$, $p < 0.001$, $\eta_p^2 = 0.49$),

suggesting an increase in activation across steps. As seen in the FIR time-course, this implies a gradual

release of tonic deactivation across the duration of the task episode.

To examine whether the profiles of different regions within each network showed unique responses, we

performed the same analyses (FIR time-course modelling and event-based GLM) on individual ROIs (see

Extended Data Figure 4-1). Trends of activation across the four steps for individual ROIs were largely

similar to the network in which they belong, though there were some differences between ROIs. Within

the MD network, aMFG and AI showed negative epoch responses, in contrast to other regions. The

episode offset response was also especially high in aMPFC and especially small in pdLFC and IPS. Within

the DMN, PHC showed positive epoch responses, in contrast to other regions.

Figure 4. Univariate analysis of MD network (A) and DMN (B) BOLD response across task episodes. For each network, the left plot shows results of the FIR analysis, with BOLD response as a function of time as participants progressed across two consecutive episodes. The upper middle plot shows beta estimates associated with the step onsets (bars 1-4), and with the end of the episode (bar "off"). The lower middle plot shows beta estimates for epoch regressors for each step. Error bars indicate standard error of the mean. The right panel depicts component ROIs within each network.

Whole-brain analysis

Results from the whole-brain analysis, again separating onset and epoch regressors, are shown in Figure 5. Panel A shows responses within an episode, with the left-hand side showing contrasts of the mean onset (i) and epoch (ii) response against baseline, and the right-hand side showing increasing trends across steps for the onset response (iii) and the epoch response (iv). The onset of step 1 and the offset of step 4 are special, since these correspond to the onset and offset of a whole episode, and it is evident from the ROI analysis that their neural response also differs from step onsets within an episode. Therefore, these episode-boundary responses were not included in the within-episode contrasts, but were instead examined separately. Panel B of figure 5 shows onset responses at episode onset (left) and offset (right), contrasted against both baseline (i, iii) and against the adjacent step onset response (ii, iv).

In comparison to baseline, the mean step onset response (Figure 5Ai) was significantly positive throughout

the MD network, as well as visual cortex, motor cortex, and subcortical structures including the

cerebellum. The mean step onset response was significantly negative throughout the DMN. Mean epoch

responses greater than baseline (Figure 5Aii) were also extensive, including parietal and frontal regions

overlapping with the MD ROIs, as well as expected regions of visual and motor cortex. Again, we saw

negative epoch responses in much of the DMN. We next examined activity changes across steps within

an episode. An increase in the amplitude of the step onset response was restricted to MD regions (Figure

5Aiii). In contrast, a linear increase in the tonic epoch response was widespread across most of the brain

(Figure 5Aiv). The only exception was areas of visual cortex, where both onset and epoch responses

decreased across an episode. Finally, we were interested in the response at episode boundaries, i.e. the

onset of the first step (initiation of an episode) and the offset of the fourth step (completion of an episode).

The response to step 1 onset was substantial across much of the brain, whether compared to baseline or

to step 2 onset (Figure 5Bi and 5Bii), including visual cortex and parts of DMN and MD networks. The

episode completion response was also significantly greater than baseline in many brain regions (Figure

5Biii), including parts of both MD and DMN networks, while deactivations were mainly observed in

visual cortex. Interestingly, this response exceeded the previous step onset response in the DMN but not

the MD network (Figure 5Biv).

Figure 5. Whole brain univariate analysis. (A) Responses within an episode, including (i) mean phasic responses to the onset of each step; (ii) mean tonic responses across the duration of each step; (iii) increases in the phasic response across step onsets; (iv) increases in the tonic response across step epochs. (B) Transient responses at episode boundaries, including (i) episode onset versus baseline; (ii) episode onset versus step 2 onset; (iii) episode offset versus baseline; (iv) episode offset versus step 4 onset. Colors indicate t-values, with warm and cool scales indicating positive and negative tails respectively. All activation maps are thresholded at FDR < 0.025 per tail.

The results may be summarized as follows. Most MD regions, along with visual cortex, showed positive onset and epoch responses to all steps, suggesting direct involvement in setting up and executing task steps. Sensitivity to the large-scale structure of the task episode was evident in gradually increasing activity as the episode progressed, along with phasic responses at onset and offset of the whole episode. Interestingly, tonic ramping activity was widespread throughout the brain, whereas increasing onset

responses were highly specific to the MD network, and an episode offset response exceeding the preceding

step onset was largely specific to the DMN.

RSA results

Results of the RSA analysis are shown in Figure 6. In panel A, LDC representational distance estimates

are plotted for various comparisons of events (see also Figure 2), based on activation patterns across the

DMN and MD networks. The coefficients of the linear model fit to these data are plotted in panel B,

quantifying coding of different types of information – room, cued task, step, and item. Analyses of

individual ROIs within the two networks are shown in Extended Data Figure 6-1.

Figure 6. (A) LDC representational distance estimates, modelled as in figure 2b. To avoid clutter, data

points are plotted separately for different levels of visual difference (0%, 50%, 100% task overlap), and

are offset fractionally along the x-axis. Lines represent the mean linear model fit, estimated using all data

(except matched-item comparisons). (B) LDC contrasts representing strength of room, cued task, step,

and item coding in DMN and MD network-level ROIs. Asterisks above each bar indicate significance of

1-tailed t-tests against zero, after controlling FDR <0.05 across ROIs; horizontal lines indicate a

significant 2-tailed paired t-test between networks; *** p < 0.001, ** p < 0.01, * p < 0.05. Error bars

represent +/- 1 standard error of the mean across subjects.

Network comparison

First, we asked whether activity patterns in the MD and DMN networks differentially carried information

about distinct aspects of task episodes. A 2 (network) × 4 (type of information) repeated measures

ANOVA showed a significant interaction ($F_{(4,164)}$ = 3.13, p = 0.033), as well as a main effect of

information type ($F_{(4,164)}$ = 3.65, p = 0.016) but not network ($F_{(1,41)}$ = 0.25, p = 0.62). The interaction

was driven by the DMN having a relative preference for coding the identity of the cued task, while the

MD network had a relative preference for step-level coding (step position, and item identity). We next

assessed coding of each information type in turn.

Room coding

Neither the DMN nor MD network ROIs showed significant room coding (both *t*s < 0.25, both *p*s > 0.39,

both *d*s < 0.04). Similarly, none of the individual ROIs showed significant room coding (all *t*s < 1.70, all

*p*s > 0.11, *d*s < 0.27), though it was numerically strongest in the MPFC.

Task coding

The DMN network showed significant coding of the cued task (t = 2.18, p = 0.02, d = 0.33), while the

MD network did not (t = 0.26, p = 0.40, d = 0.04); the difference between networks was also significant

(t = 2.52, p = 0.02, d = 0.39). None of the individual ROIs showed significant task coding after FDR

correction for multiple comparisons across ROIs. PCC, and ACC showed task coding before correction

(both ts > 1.74, both ps < 0.044, both ds > 0.27). Task coding was positive in all six DMN ROIs, but only

four of seven MD ROIs.

It is possible that the response to regressors modelling adjacent steps could be similar due to imperfect

temporal separation of the signal, such that pairs of steps within the same task appear more similar than

those from different tasks due to differences in temporal separation in addition to differences in task

identity. We examined this possibility by fitting four separate linear regression models using subsets of

cells, chosen to differ in separation of one, two, or three steps. That is, we extracted LDC values from

cells of the DMN network RDM that represented one step apart (1 vs. 2, 2 vs. 3, and 3 vs. 4), two steps

apart (1 vs. 3 and 2 vs. 4), or three steps apart (1 vs. 4), and, in each case, fitted a model with room, cued

task, and visual difference regressors. If temporal proximity were contributing to activity pattern

similarity, and hence to apparent task coding in the DMN, we should expect a stronger effect for steps

closer together in time. However, we found no evidence of any difference in task coding across these three

conditions ($F(2, 82) = 0.39$, $p = 0.61$, $\eta_p^2 = 0.01$), nor a linear trend as a function of step ($F(1,41) = 0.44$,

$p = 0.51$, $\eta_p^2 = 0.01$). Task coding as a function of step difference is shown in Extended Data Figure 6-2.

Step coding

Step coding was significant in both the DMN ($t = 6.34$, $p < 0.001$, $d = 0.98$) and MD ($t = 7.25$, $p < 0.001$,

$d = 1.12$) network ROIs. The MD network showed significantly greater step coding than the DMN ($t =$

2.38, $p = 0.02$, $d = 0.37$). Step coding was also significant in all the individual ROIs (all $ts > 2.02$, all $ps <$

0.03, all $ds > 0.31$). This was not surprising, as in our univariate analysis we observed strong linear trends

across the task episode for most of the brain (see Figure 5Aiv).

Item coding

Both DMN ($t = 3.15$, $p = 0.002$, $d = 0.49$) and MD ($t = 4.00$, $p < 0.001$, $d = 0.62$) network ROIs showed

significant coding of item. The two networks did not significantly differ in item coding ($t = 1.88$, $p = 0.07$,

$d = 0.29$). In the individual ROIs, item coding was especially strong in parietal regions, with only IPS (t

$= 4.58$, $p < 0.001$, $d = 0.71$) and IPL ($t = 2.89$, $p < 0.01$, $d = 0.44$) showing significant item coding after

FDR correction for multiple comparisons (prior to correction, item coding was also present in ACC (t =

2.05, p = 0.02, d = 0.32) and PCC (t = 1.90, p = 0.03, d = 0.29)).

Discussion

We used fMRI to examine how cortical networks respond to and represent different aspects of multi-step

task episodes. Specifically, we focused on the DMN and MD networks. Using FIR and event-related

analyses to capture the evolution of the BOLD response throughout a multi-step episode, we found that

MD regions showed positive activity throughout the episode, with separate peaks for successive steps.

These results suggest involvement in setting up and executing individual task steps. In contrast, the DMN

showed overall deactivation. Along with widespread other regions, both DMN and MD showed sensitivity

to the large-scale structure of the episode, with phasic responses to onset and offset, and gradually

increasing tonic activity as the episode progressed. MD regions were unique in showing an increase in the

phasic step response across the episode, while a characteristic feature of DMN regions was an episode

offset response that exceeded the final step response.

Representational similarity analysis indicated that MD regions showed strong coding of individual items

but not the identity of the cued task, while for DMN, both item and task coding were significant. Both

networks additionally showed strong step coding, which was significantly greater in the MD network than

the DMN. The finding that MD regions are especially sensitive to the identity of a current task step and

its specific item content is consistent with prior research. Many previous experiments have shown coding

of task-relevant information in MD regions that can rapidly change according to task demands (Freedman

et al., 2001; Li et al., 2007; Woolgar et al., 2011), including radical reorganization between successive

task steps (Sigala et al., 2008). fMRI studies show strong MD activity when a sub-goal is completed and

in transitions from one event to another (Sridharan et al., 2007; Farooqui et al., 2012), with progressively

increasing activity as a goal is approached (Farooqui et al., 2012; Desrochers et al., 2015; Desrochers et

al., 2019). The pattern of MD activation in our study is broadly consistent with these previous findings. The results suggest that, as a task episode progresses, MD representations in particular are in constant flux, reorganizing to encode the detailed contents of each task step. Representational content includes the position of the step within the task episode and the identity of the item required on that step, which, in the current task, may serve as an attentional template for visual search decisions (Desimone and Duncan, 1995).

Within the DMN, univariate results showed a burst of activity at the beginning of each episode, but no significant onset responses to subsequent steps. At the completion of the episode, DMN also exhibited an especially strong offset response. These findings are consistent with prior reports of transient DMN activation at event boundaries (Speer et al., 2007), including transitions to a new task (Smith et al., 2018). Our data showed, however, that both onset and offset responses were widespread in the brain (Fox et al., 2005) and it was the magnitude of the offset response that was most specific to the DMN. It has been proposed that the mental programs required for carrying out a task are assembled at the beginning of task execution (Schneider and Logan, 2006; Farooqui and Manly, 2019). It is possible that the DMN, along with multiple other brain regions, is involved in long-term memory retrieval for the entire task sequence at episode initiation, and long-term memory storage at episode completion. The DMN's marked response to task episode boundaries, along with its significant representation of task identity, are consistent with the proposal that the DMN has long temporal receptive windows and codes for information accumulated over long time scales (Hasson et al., 2008; Lerner et al., 2011; Chen et al., 2016).

For the DMN as a whole, significant coding of cued task identity suggests representation of broad task context. A particular role of the DMN in task coding is consistent with its proposed function in representing "situation models" — higher-level cognitive representations of relationships between different elements of an episode — as part of a "posterior medial system" centered on PHC and retrosplenial cortex (Diana et al., 2007; Ranganath and Ritchey, 2012; Reagh and Ranganath, 2018). The

MPFC sub-region of the DMN has been implicated in schema representation, capturing similarities across

multiple episodes (Preston and Eichenbaum, 2013; Ghosh and Gilboa, 2014; Robin and Moscovitch,

2017), and might therefore have been expected to show room coding. Although room coding was

numerically strongest in this ROI, it was not significant. Stronger room coding might have been observed

if the grouping by room had been behaviorally relevant rather than incidental.

We also found that the DMN showed significant coding for items, and thus represents not just full tasks,

but also specific contents within a task episode. Although we found both item and task representations

coexisting in the DMN, consistent with a compositional code, this experiment cannot determine whether

and where items and tasks might be bound into a conjunctive representation, or maintained as independent

factorized components (Behrens et al., 2018): because items were unique to each task, item-task

conjunctions are indistinguishable from item coding. Disentangling these different forms of co-

representation requires designs where the same item appears in different contexts. Such designs have

identified item-context conjunctions in the hippocampus (Hsieh et al., 2014) item-order associations in

various frontal and temporal regions (Reverberi et al., 2012; Kalm and Norris, 2014), rule-rule

compositionality in lateral frontal cortex (Cole et al., 2011), and factorized coding of sequence and

position in midcingulate cortex (Holroyd et al., 2018) and in electrophysiological signals during learning

and replay (Liu et al., 2019).

Both MD and DMN, along with most regions of the brain, tracked progress through the task episode,

shown by increasing trends in the univariate data. These observations are consistent with previous studies

that reported ramping activity across task episodes in specific MD (Farooqui et al., 2012; Desrochers et

al., 2015; Desrochers et al., 2019) and DMN regions (Farooqui and Manly, 2018), but suggest that it might

be a much more global property of brain function (Farooqui and Manly, 2018). While parts of visual

cortex showed a decrease in sustained activity over the episode, which may reflect adaptation to the

sensory input (Grill-Spector and Malach, 2001; Grill-Spector et al., 2006), most other cortical regions

showed an increase in sustained activity over the episode, which reset at episode boundaries. As this effect

was so widespread, it is difficult to offer a precise interpretation, and different areas may increase for

different reasons (Kalm and Norris, 2017). For example, it is possible that increased activations in some

regions reflect revision and reconfiguration of control representations that may increase in demand as

larger portions of the task are complete (Farooqui et al., 2012; Desrochers et al., 2015; Desrochers et al.,

2019), or expectation of, and preparation for, trial completion (Shidara and Richmond, 2002). These

activity changes could also reflect gradual accumulation and integration of new information into an

episode representation (Hasson et al., 2008; Dumontheil et al., 2011; Lerner et al., 2011). The global

nature of the signal is potentially consistent with models of multi-step decision-making, in which evidence

accumulation is massively parallel within temporal chunks that are serially chained (Zylberberg et al.,

2011; Dehaene and Sigman, 2012). In rats, anticipation of distant goals has been associated with slowly

ramping dopamine release (Howe et al., 2013), which could suggest a mechanism for the widespread

cortical effects observed here. In contrast to the global nature of the tonically increasing response,

increases in the phasic step response appeared highly specific to the MD network. Speculatively, the

phasic MD response may track progress in discrete steps, in addition to the tonic global signal which

reflects a more continuous measure of progress. A similar distinction between neural signals that track

progress in a smooth versus action-linked manner has also been observed in the rat brain (Ma et al., 2014).

A hierarchical control structure is an organized representation of control elements, including task identity,

local entities, and serial position codes (Rosenbaum et al., 1983; Schneider and Logan, 2006). Our results

describe how broad brain networks are involved in the execution of task sequences, with MD and DMN

regions exhibiting distinct time-courses throughout the episode, and different profiles of information

representation. The DMN, we suggest, may establish overall cognitive context, representing both

individual cognitive operations and their broader context, and perhaps involved in binding them together.

These functions may be consistent with representing a "situation model" (Ranganath and Ritchey, 2012).

At the same time, the MD system, along with sensory regions, processes and tracks the detailed content

of individual cognitive operations, locked to discrete events within the episode. Both networks respond to

the broad temporal structure of task episodes, with phasic activity at task onset and offset, and gradually

increasing activity as the whole sequence of steps progresses. Acting together, they reflect the hierarchical

structure of goal-directed behavior.

References

Andrews-Hanna JR (2012) The brain's default network and its adaptive role in internal mentation.

Neuroscientist 18:251-270.

Andrews-Hanna JR, Reidler JS, Sepulcre J, Poulin R, Buckner RL (2010) Functional-anatomic

fractionation of the brain's default network. Neuron 65:550-562.

Asaad WF, Rainer G, Miller EK (2000) Task-specific neural activity in the primate prefrontal cortex. J

Neurophysiol 84:451-459.

Baldassano C, Hasson U, Norman KA (2018) Representation of Real-World Event Schemas during

Narrative Perception. J Neurosci 38:9689-9699.

Behrens TEJ, Muller TH, Whittington JCR, Mark S, Baram AB, Stachenfeld KL, Kurth-Nelson Z (2018)

What Is a Cognitive Map? Organizing Knowledge for Flexible Behavior. Neuron 100:490-509.

Ben-Yakov A, Henson RN (2018) The Hippocampal Film Editor: Sensitivity and Specificity to Event

Boundaries in Continuous Experience. J Neurosci 38:10057-10068.

Ben-Yakov A, Eshel N, Dudai Y (2013) Hippocampal immediate poststimulus activity in the encoding of

consecutive naturalistic episodes. J Exp Psychol Gen 142:1255-1263.

Benjamini Y, Yekutieli D (2001) The control of the false discovery rate in multiple testing under

dependency. Annals of Statistics 29:1165-1188.

Chen J, Honey CJ, Simony E, Arcaro MJ, Norman KA, Hasson U (2016) Accessing Real-Life Episodic

Information from Minutes versus Hours Earlier Modulates Hippocampal and High-Order Cortical

Dynamics. Cereb Cortex 26:3428-3441.

Cohn-Sheehy BI, Ranganath C (2017) Time Regained: How the Human Brain Constructs Memory for

Time. Curr Opin Behav Sci 17:169-177.

Cole MW, Etzel JA, Zacks JM, Schneider W, Braver TS (2011) Rapid transfer of abstract rules to novel

contexts in human lateral prefrontal cortex. Front Hum Neurosci 5:142.

Cooper R, Shallice T (2000) Contention scheduling and the control of routine activities. Cogn

Neuropsychol 17:297-338.

Crittenden BM, Mitchell DJ, Duncan J (2015) Recruitment of the default mode network during a

demanding act of executive control. Elife 4:e06481.

Crittenden BM, Mitchell DJ, Duncan J (2016) Task Encoding across the Multiple Demand Cortex Is

Consistent with a Frontoparietal and Cingulo-Opercular Dual Networks Distinction. J Neurosci

36:6147-6155.

Cusack R, Vicente-Grabovetsky A, Mitchell DJ, Wild C, Auer T, Linke AC, Peelle JE (2015) Automatic

analysis (aa): Efficient neuroimaging workflows and parallel processing using Matlab and XML.

Frontiers in Neuroinformatics 8.

Dale AM (1999) Optimal experimental design for event-related fMRI. Hum Brain Mapp 8:109-114.

Dehaene S, Sigman M (2012) From a single decision to a multi-step algorithm. Curr Opin Neurobiol

22:937-945.

Desimone R, Duncan J (1995) Neural mechanisms of selective visual attention. Annu Rev Neurosci

18:193-222.

Desrochers TM, Chatham CH, Badre D (2015) The Necessity of Rostrolateral Prefrontal Cortex for

Higher-Level Sequential Behavior. Neuron 87:1357-1368.

Desrochers TM, Collins AGE, Badre D (2019) Sequential Control Underlies Robust Ramping Dynamics

in the Rostrolateral Prefrontal Cortex. J Neurosci 39:1471-1483.

Diana RA, Yonelinas AP, Ranganath C (2007) Imaging recollection and familiarity in the medial temporal

lobe: a three-component model. Trends Cogn Sci 11:379-386.

Dosenbach NU, Visscher KM, Palmer ED, Miezin FM, Wenger KK, Kang HC, Burgund ED, Grimes AL,

Schlaggar BL, Petersen SE (2006) A core system for the implementation of task sets. Neuron

50:799-812.

Dosenbach NU, Fair DA, Miezin FM, Cohen AL, Wenger KK, Dosenbach RA, Fox MD, Snyder AZ,

Vincent JL, Raichle ME, Schlaggar BL, Petersen SE (2007) Distinct brain networks for adaptive

and stable task control in humans. Proc Natl Acad Sci U S A 104:11073-11078.

Dumontheil I, Thompson R, Duncan J (2011) Assembly and use of new task rules in fronto-parietal cortex.

J Cogn Neurosci 23:168-182.

Duncan J (2010) The multiple-demand (MD) system of the primate brain: mental programs for intelligent

behaviour. Trends Cogn Sci 14:172-179.

Duncan J (2013) The structure of cognition: attentional episodes in mind and brain. Neuron 80:35-50.

Everling S, Tinsley CJ, Gaffan D, Duncan J (2002) Filtering of neural signals by focused attention in the

monkey prefrontal cortex. Nat Neurosci 5:671-676.

Ezzyat Y, Davachi L (2011) What constitutes an episode in episodic memory? Psychol Sci 22:243-252.

Farooqui AA, Manly T (2018) Hierarchical Cognition Causes Task-Related Deactivations but Not Just in

Default Mode Regions. eNeuro 5.

Farooqui AA, Manly T (2019) We do as we construe: extended behavior construed as one task is executed

as one cognitive entity. Psychological Research-Psychologische Forschung 83:84-103.

Farooqui AA, Mitchell D, Thompson R, Duncan J (2012) Hierarchical organization of cognition reflected

in distributed frontoparietal activity. J Neurosci 32:17373-17381.

Fedorenko E, Duncan J, Kanwisher N (2013) Broad domain generality in focal regions of frontal and
parietal cortex. Proc Natl Acad Sci U S A 110:16616-16621.

Fox MD, Snyder AZ, Barch DM, Gusnard DA, Raichle ME (2005) Transient BOLD responses at block
transitions. Neuroimage 28:956-966.

Freedman DJ, Riesenhuber M, Poggio T, Miller EK (2001) Categorical representation of visual stimuli in
the primate prefrontal cortex. Science 291:312-316.

Ghosh VE, Gilboa A (2014) What is a memory schema? A historical perspective on current neuroscience
literature. Neuropsychologia 53:104-114.

Grill-Spector K, Malach R (2001) fMR-adaptation: a tool for studying the functional properties of human
cortical neurons. Acta Psychol (Amst) 107:293-321.

Grill-Spector K, Henson R, Martin A (2006) Repetition and the brain: neural models of stimulus-specific
effects. Trends Cogn Sci 10:14-23.

Hasson U, Yang E, Vallines I, Heeger DJ, Rubin N (2008) A hierarchy of temporal receptive windows in
human cortex. J Neurosci 28:2539-2550.

Holroyd CB, Ribas-Fernandes JJF, Shahnazian D, Silvetti M, Verguts T (2018) Human midcingulate
cortex encodes distributed representations of task progress. Proc Natl Acad Sci U S A 115:6398-
6403.

Howe MW, Tierney PL, Sandberg SG, Phillips PE, Graybiel AM (2013) Prolonged dopamine signalling
in striatum signals proximity and value of distant rewards. Nature 500:575-579.

Hsieh LT, Ranganath C (2015) Cortical and subcortical contributions to sequence retrieval: Schematic
coding of temporal context in the neocortical recollection network. Neuroimage 121:78-90.

Hsieh LT, Gruber MJ, Jenkins LJ, Ranganath C (2014) Hippocampal activity patterns carry information
about objects in temporal context. Neuron 81:1165-1178.

Kalm K, Norris D (2014) The representation of order information in auditory-verbal short-term memory.
J Neurosci 34:6879-6886.

Kalm K, Norris D (2017) Reading positional codes with fMRI: Problems and solutions. PLoS ONE 12:e0176585.

Lerner Y, Honey CJ, Silbert LJ, Hasson U (2011) Topographic mapping of a hierarchy of temporal receptive windows using a narrated story. J Neurosci 31:2906-2915.

Li S, Ostwald D, Giese M, Kourtzi Z (2007) Flexible coding for categorical decisions in the human brain. J Neurosci 27:12321-12330.

Liu Y, Dolan RJ, Kurth-Nelson Z, Behrens TEJ (2019) Human Replay Spontaneously Reorganizes Experience. Cell 178:640-652 e614.

Ma L, Hyman JM, Phillips AG, Seamans JK (2014) Tracking progress toward a goal in corticostriatal ensembles. J Neurosci 34:2244-2253.

Mitchell DJ, Bell AH, Buckley MJ, Mitchell AS, Sallet J, Duncan J (2016) A Putative Multiple-Demand System in the Macaque Brain. J Neurosci 36:8574-8585.

Nili H, Wingfield C, Walther A, Su L, Marslen-Wilson W, Kriegeskorte N (2014) A toolbox for representational similarity analysis. PLoS Comput Biol 10:e1003553.

Preston AR, Eichenbaum H (2013) Interplay of hippocampus and prefrontal cortex in memory. Curr Biol 23:R764-773.

Radvansky GA, Zacks JM (2017) Event Boundaries in Memory and Cognition. Curr Opin Behav Sci 17:133-140.

Ranganath C, Ritchey M (2012) Two cortical systems for memory-guided behaviour. Nat Rev Neurosci 13:713-726.

Reagh ZM, Ranganath C (2018) What does the functional organization of cortico-hippocampal networks tell us about the functional organization of memory? Neurosci Lett 680:69-76.

Reverberi C, Gorgen K, Haynes JD (2012) Distributed representations of rule identity and rule order in human frontal cortex and striatum. J Neurosci 32:17420-17430.

Robin J, Moscovitch M (2017) Details, gist and schema: hippocampal-neocortical interactions underlying

recent and remote episodic and spatial memory. Curr Opin Behav Sci 17:114-123.

Rosenbaum DA, Kenny SB, Derr MA (1983) Hierarchical control of rapid movement sequences. J Exp

Psychol Hum Percept Perform 9:86-102.

Schneider DW, Logan GD (2006) Hierarchical control of cognitive processes: switching tasks in

sequences. J Exp Psychol Gen 135:623-640.

Shidara M, Richmond BJ (2002) Anterior cingulate: single neuronal signals related to degree of reward

expectancy. Science 296:1709-1711.

Sigala N, Kusunoki M, Nimmo-Smith I, Gaffan D, Duncan J (2008) Hierarchical coding for sequential

task events in the monkey prefrontal cortex. Proc Natl Acad Sci U S A 105:11969-11974.

Smith V, Mitchell DJ, Duncan J (2018) Role of the Default Mode Network in Cognitive Transitions.

Cereb Cortex 28:3685-3696.

Speer NK, Zacks JM, Reynolds JR (2007) Human brain activity time-locked to narrative event boundaries.

Psychol Sci 18:449-455.

Sridharan D, Levitin DJ, Chafe CH, Berger J, Menon V (2007) Neural dynamics of event segmentation

in music: converging evidence for dissociable ventral and dorsal networks. Neuron 55:521-532.

Walther A, Nili H, Ejaz N, Alink A, Kriegeskorte N, Diedrichsen J (2016) Reliability of dissimilarity

measures for multi-voxel pattern analysis. Neuroimage 137:188-200.

Wen T, Mitchell DJ, Duncan J (2019) The functional convergence and heterogeneity of social, episodic,

and self-referential thought in the default mode network. bioRxiv.

Woolgar A, Hampshire A, Thompson R, Duncan J (2011) Adaptive coding of task-relevant information

in human frontoparietal cortex. J Neurosci 31:14592-14599.

Yeo BT, Krienen FM, Sepulcre J, Sabuncu MR, Lashkari D, Hollinshead M, Roffman JL, Smoller JW,

Zollei L, Polimeni JR, Fischl B, Liu H, Buckner RL (2011) The organization of the human cerebral

cortex estimated by intrinsic functional connectivity. J Neurophysiol 106:1125-1165.

Zacks JM, Tversky B (2001) Event structure in perception and conception. Psychol Bull 127:3-21.

Zacks JM, Braver TS, Sheridan MA, Donaldson DI, Snyder AZ, Ollinger JM, Buckner RL, Raichle ME

(2001) Human brain activity time-locked to perceptual event boundaries. Nat Neurosci 4:651-655.

Zylberberg A, Dehaene S, Roelfsema PR, Sigman M (2011) The human Turing machine: a neural

framework for mental programs. Trends Cogn Sci 15:293-300.