1

# Discovery of ongoing selective sweeps within *Anopheles* mosquito populations using deep learning

Short title: Classifying partial sweeps in *Anopheles* populations via deep learning

Alexander T. Xue[1,*], Daniel R. Schrider[2], Andrew D. Kern[3], Ag1000G Consortium

[1] Simons Center for Quantitative Biology, Cold Spring Harbor Laboratory, One Bungtown Road, Cold Spring Harbor, NY 11724

[2] Department of Genetics, University of North Carolina, 120 Mason Farm Road, Chapel Hill, NC 27514

[3] Institute of Ecology and Evolution, 5289 University of Oregon, Onyx Bridge 272, Eugene, OR 97403

[*] Corresponding Author: xanderxue@gmail.com

## Abstract

Identification of partial sweeps, which include both hard and soft sweeps that have not currently reached fixation, provides crucial information about ongoing evolutionary responses. To this end, we introduce *partialS/HIC*, a deep learning method to discover selective sweeps from population genomic data. *partialS/HIC* uses a convolutional neural network for image processing, which is trained with a large suite of summary statistics derived from coalescent simulations incorporating population-specific history, to distinguish between completed versus partial sweeps, hard versus soft sweeps, and regions directly affected by selection versus those merely linked to nearby selective sweeps. We perform several simulation experiments under various demographic scenarios to demonstrate *partialS/HIC*'s performance, which exhibits excellent resolution for detecting partial sweeps. We also apply our classifier to whole genomes from eight mosquito populations sampled across sub-Saharan Africa by the *Anopheles gambiae* 1000 Genomes Consortium, elucidating both continent-wide patterns as well as sweeps unique to specific geographic regions. These populations have experienced intense insecticide exposure over the past two decades, and we observe a strong overrepresentation of sweeps at insecticide resistance loci. Our analysis thus provides a list of candidate adaptive loci that may be relevant to mosquito control efforts. More broadly, our supervised machine learning approach introduces a method to distinguish between completed and partial sweeps, as well as between hard and soft sweeps, under a variety of demographic scenarios. As whole-genome data rapidly accumulate for a greater diversity of organisms, *partialS/HIC* addresses an increasing demand for useful selection scan tools that can track in-progress evolutionary dynamics.

# Introduction

Malaria represents an enormous burden on human health, with an estimated 214 million cases and 438,000 deaths in 2015 [1]. As mosquitos of the *Anopheles gambiae* species complex are the major vector for *Plasmodium* parasites, roughly 70% of global malaria relief budgets have been focused on mosquito control, including insecticide treated bed-nets, indoor residual spraying, and larva control through the direct modification of habitats as well as the application of larvicide. While these vector control efforts have successfully produced major reductions of malaria transmission rates over the past 15 years [1], there has been an alarming increase in mosquitos resistant to insecticides, specifically pyrethroids, observed across nearly all areas of the world covered by anti-malarial efforts [2]. Pyrethroids are the only class of insecticide used in long-lasting insecticidal nets and are applied in many indoor spraying programs, thus the evolutionary innovation of resistance is a well-recognized Achilles heel of anti-malarial efforts.

The increase in insecticide resistant mosquitoes is to be expected from an evolutionary standpoint: anti-malaria control efforts exert a strong selective pressure to which mosquito populations will respond through the differential survivorship and reproduction of those individuals that can best cope with the applied insecticides. Pyrethroid resistance was reported within African malaria vectors first in Sudan during the 1970s, then later in West Africa during the 1990s, most likely stemming from accidental exposure of mosquitos to crop applications of pyrethroids [3,4]. Subsequent analysis showed this earliest resistance to be a result of mutations in the knockdown resistance locus *kdr*, which is known to contribute to pyrethroid resistance in other insect species [5]. Mutations conferring resistance at *kdr* as well as other loci have since spread throughout Africa, and threaten to nullify the gains in malaria control achieved over the past decade [6]. While control efforts are now looking toward non-pyrethroid insecticides [2,7] as well as gene drive technologies [8], it is anticipated that resistance to these control modalities will eventually evolve as well [9,10]. Hence, an important goal in the continued fight against malaria is to identify genomic targets of resistance in *Anopheles*, especially in such a way that might inform vector managers in the field.

Alleles that confer resistance to control efforts should rapidly increase in frequency

within *Anopheles* populations in a manner consistent with selective sweeps. When an allele

increases in frequency under selection, its linked genetic background comes with it in a

process known as genetic hitchhiking. Selective sweeps, through this hitchhiking effect,

lead to decreased levels of polymorphism [11–13], skewed allele frequency spectra [14,15],

and increases in linkage disequilibrium surrounding the site under selection [16].

Classically, methods for finding sweeps have focused on a particular aspect of genetic

variation, for instance observing the site frequency spectrum (SFS) at a locus and

comparing it to expectations under neutrality and selective sweeps [17]. More recently, the

field has made excellent progress in combining signals across multiple features of genetic

variation through supervised machine learning (SML) [18–25], which has substantially

improved power, accuracy, and robustness in what have been stubbornly difficult inference

problems within population genetics [26]. While much attention has been paid to applying

SML for the identification and classification of completed selective sweeps in the genome

[22,24], less effort has been made for using SML to identify sweeps that are incomplete

within a population, sometimes called partial sweeps (although see Sugden *et al.* [25] for a

recent example). In these cases, the beneficial allele is not currently fixed within the

population, thereby creating a weaker hitchhiking effect in comparison to a completed

sweep, and accordingly a more subtle perturbation of patterns of genetic variation [27].

Although difficult to detect, partial sweeps could be implicated in cases where recently

initiated selective forces cause presently ongoing adaptation, directional selection ceases

prior to fixation, or an intermediate allele frequency is favored by balancing, polygenic,

and/or pleiotropic selection. Therefore, it is important to address the challenge of

capturing such genomic signatures that represent a significant facet of evolution, which

may also give insight into future dynamics.

## New Approaches

99  Recent successful efforts to reduce malaria transmission are in danger of collapse due to

100  evolving insecticide resistance in the mosquito vector *Anopheles gambiae*. We aim to

understand the genetic basis of current adaptation to vector control efforts by deploying a novel method that can classify multiple categories of selective sweeps, including partial sweep classes, from population genomic data. To this end, we extend a recent SML method to partial sweep inference and apply it to elucidate ongoing selective sweeps from *Anopheles* population genomic samples.

Specifically, we introduce here an extension of *S/HIC* [22] and *diploS/HIC* [24], *partialS/HIC*, a SML classifier that uses a deep convolutional neural network (CNN) to classify a genomic window from a set of selection states that includes both hard and soft partial sweeps along with their associated linked classes (*i.e.* regions adjacent to either a partial hard or soft sweep). Importantly, this implementation achieves increased inferential power by utilizing dozens of additional summary statistics, including summaries for the distribution of *iHS* scores [28] as well as derivatives of a recently developed SNP-specific compound statistic called SAFE (selection of allele favored by evolution) [29], under a deep learning framework that involves training convolutional neural networks with coalescent simulations that accommodate demographic history and are converted into spatially-explicit two-dimensional feature vector images. We validate *partialS/HIC*'s performance through extensive simulation-based experiments that were modeled after data from phase I of the *Anopheles gambiae* 1000 genomes project (Ag1000G) [6], with particular emphasis on discovering sweeps currently in progress such as what might result from ongoing vector control efforts (*e.g.* insecticide spraying). Our findings demonstrate that our method is effective for detecting partial sweeps even in the face of complex population size histories such as those found among the Ag1000G samples. Furthermore, for binary classification of selective sweeps when partial sweeps are included, *partialS/HIC* has greater accuracy than *iHS* or SAFE alone as well as two alternative approaches to sweep inference based on the same suite of summary statistics. Subsequently, we apply our method to the empirical Ag1000G data, revealing many partial sweeps as well as completed sweeps from standing genetic variation. Moreover, we find that our sweep candidates are highly enriched for loci that have been previously identified as contributing to insecticide resistance.

# Results

## Coalescent simulations of feature vector images for *partialS/HIC* training

To train *partialS/HIC*, we deployed the program *discoal* [30] to perform coalescent simulations of completed and partial as well as hard and soft selective sweeps, along with simulations without sweeps, in a manner analogous to Schrider and Kern [22] (Figure S1). Individual simulations were converted into two-dimensional matrices, or feature vector images, built from 89 rows corresponding to different summary statistics, and 11 columns corresponding to adjacent sub-windows. The 89 statistics include, along with 14 that were previously implemented in *S/HIC* and/or *diploS/HIC*, 3 genomic region variants of the SNP-specific *iHS* statistic [28] and 72 derivatives of the SAFE score [29]. *partialS/HIC* is trained to classify genomic segments into one of nine states: unaffected by selection (*i.e.* neutral); containing a completed hard, completed soft, partial hard, or partial soft sweep, respectively; or linked to a completed hard, completed soft, partial hard, or partial soft sweep, respectively. To this end, we defined the four completed hard/soft and partial hard/soft selective sweep states as containing a sweep within the central, focal sub-window (*i.e.* the fifth out of the 11 columns of sub-windows). In contrast, the four classification states involving linkage to a selective sweep were defined as having a sweep of the given type within one of the remaining ten sub-windows. Therefore, every linked selection state was trained from simulations that vary in genetic distance to the sweep target site, such that the total set of simulations all had a sweep occurring in any of the ten non-focal sub-windows. This allowed us to accommodate a range of linked classes that differ in spatial patterns within a genomic window, as well as assess how linkage distance affects misclassification bias during our simulation experiments. Simulations were run for each of eight population size histories corresponding to the empirical Ag1000G population datasets, which were previously inferred as part of the initial data release [6]. These *Anopheles* population datasets from Miles *et al.* [6] are labeled here as AOM (*A. coluzzii* from Angola), BFM (*A. coluzzii* from Burkina Faso), BFS (*A. gambiae* from Burkina Faso), CMS (*A. gambiae* from Cameroon), GAS (*A. gambiae* from Gabon), GNS (*A. gambiae* from

158 Guinea), GWA (*Anopheles* of uncertain species from Guinea-Bissau), and UGS (*A. gambiae*
159 from Uganda).

160   Heatmaps constructed from median values across simulations reveal expected
spatial patterns, such that values immediately flanking a sweep are substantially different
than those further from the focal sub-window, while neutral regions display no discernible
pattern among sub-windows (Figure S2). Additionally, spatial patterns of statistics differ
qualitatively between selection states. These observations are consistent regardless of
mosquito population history, suggesting that there is signal within this collection of
summary statistics to isolate the location of a sweep to a specific sub-window as well as
distinguish among neutral regions and types of selective sweeps.

## 169 Deep learning excels in detecting selective sweeps, including partial
## 170 hard sweeps

*Figure 1. CNN architecture of neural network layers.* *Our partialS/HIC classifier utilizes a*
*convolutional neural network whereby the input feature vector image, composed of 89*
*summary statistics organized into rows and across 11 contiguous genomic sub-windows*
*organized into columns, is passed to a 2D convolutional layer with 256 filters using a 3×6*
*receptive field. Next is a 2D max pooling layer given a 3×3 receptive field. Then there is a*
*second 2D convolutional layer of 256 filters based also on a 3×3 receptive field and ReLU*
*activation. Afterward is a second 2D max pooling layer with a 3×1 receptive field. The tensor*
*is then flattened after a dropout layer (p=0.25) and passed to two fully-connected layers with*
*ReLU activation, resulting in 512 and 128 nodes with subsequent dropout (p=0.50)*
*respectively. Finally, a softmax activation layer classifies the 9 responses.*

We utilized *partialS/HIC* to train and test a CNN for nine-state classification independently

on each of the eight demographic histories associated with the Ag1000G population

samples (Figures S1, 1). To this end, we produced eight batches of simulations that were

split into separate training, validation, and testing sets. During the training process, CNN

hyperparameters were tuned on the training set while the validation set allowed mitigation

of over-fitting (Figure S3). Each CNN was subsequently assessed for accuracy with the

corresponding held-out testing set, which was generated under the same specifications as

the training/validation data except linked selection classes were kept discrete versus being

grouped together into the four linked selection states. Among the eight test sets, there was

moderate overall accuracy for this simulation experiment (median accuracy = 66.4%; Table

S1). However, confusion matrix heatmaps provide a more informative view of our

classifier's performance, which exhibited reliability in identifying neutral regions,

completed hard and soft sweeps, partial hard sweeps, and individual regions linked to

completed hard/completed soft/partial hard sweeps (Figures 2, S4). In general (*i.e.* all

demographic scenarios save for AOM), completed hard sweep is the class that experienced

the highest degree of correct assignment (median accuracy = 96.0%). We also had high

accuracy for identification of linked completed hard regions, demonstrating a strong ability

to localize completed hard sweeps. The behavior of our *partialS/HIC* classifier is likewise

favorable for completed soft sweeps (median accuracy = 84.2%), with completed soft

sweeps rarely detected incorrectly as hard sweeps and instead typically mistaken for either

the neutral or partial soft sweep state. Moreover, sub-windows linked to completed soft

sweeps beyond one sub-window away had low levels of misclassification to any of the non-

linked sweep states, again allowing for dependable localization of the sweep.

Importantly, the purpose of *partialS/HIC* is to extend our state space to identify

ongoing selective sweeps while distinguishing these from completed sweeps. We find that

our ability to identify partial hard sweeps was generally strong across population histories

(median accuracy = 74.6%) and is often comparable to that of completed soft sweeps.

However, localization of partial hard sweeps along the chromosome was more difficult

than for completed sweeps, as can be seen from the moderate levels of confusion between

partial hard sweep and linked partial hard sweep sub-windows. Undoubtedly, this is due to

the limited amount of time recombination has had to whittle down the haplotype carrying

the beneficial mutation.

Identifying partial soft sweeps was a much more challenging task (median accuracy
= 45.3%), with a high false negative rate (median rate of misclassification as neutral =
27.6%) as well as a substantial probability of misclassification as a completed soft sweep
(median rate = 14.4%). It is encouraging though that partial soft sweeps were almost never
misclassified as a completed nor partial hard sweep. Additionally, while our accuracy in
classifying partial soft sweeps was poor, false positives were not a major concern (median
rate of misclassifying neutral regions as partial soft sweep = 3.2%). Although even fairly
low false positive rates can be problematic when the true number of sweeps is low,
*partialS/HIC* achieved acceptably low false discovery rates for partial soft sweeps in our
application to the *Anopheles gambiae* 1000 Genomes dataset, as we show below.
Furthermore, linked partial soft sweeps beyond one sub-window away from the focal sub-
window were rarely mistaken for a sweep state, and likewise partial soft sweeps were
seldom confused for being linked (median rate of misclassification as linked partial soft
sweep = 4.3%), thus demonstrating that accurate localization of partial soft sweeps may be
possible.

In summary, *partialS/HIC* has excellent ability to distinguish partial from completed
sweeps for *de novo* mutations, and lesser yet still substantial power for sweeps from
standing variation. Moreover, we demonstrated very strong performance in differentiating
between hard and soft sweeps, regardless of whether a sweep was completed or
incomplete. Importantly, this is all while maintaining an acceptable false positive rate
across each of the population histories tested (median accuracy for neutral regions =
85.1%; median rate of misclassifying neutral regions as any one of the four non-linked
sweep states = 4.6%).

**Figure 2. Confusion matrix heatmap of partialS/HIC simulation experiment.** *Given the BFS population history. Each row designates a true simulation class, which for linked sweeps is differentiated by distance in genomic sub-windows to the target selective sweep. In total, there are 45 simulated scenarios shown, including 11 for each sweep type (i.e. one case whereby the sweep is within the central sub-window, and 10 whereby a linked sweep is located within one of the flanking sub-windows) and neutrality. Each column indicates one of nine inferred states, with the linked simulation classes collapsed into a single category per selective sweep type for training and classification, allowing partialS/HIC to learn to distinguish between sweeps located in the focal sub-window and those somewhere nearby. Darker blue cells represent a higher proportion of the 1,000 calls for each true class. Importantly, there is generally high accuracy in discriminating between sweeps within the focal sub-window versus linked sub-windows, especially when linkage is beyond one sub-window away and particularly for completed sweeps. However, discovering partial soft sweeps is noticeably a challenging task. Moreover, there is greater sensitivity separating full completion from partial completion for hard sweeps in contrast to soft sweeps.*

## Robustness to demographic model misspecification

To assess robustness to demographic misspecification, we applied a CNN trained on
simulations from one population sample to data generated from an alternate demographic
history. Specifically, we used training data from the GAS population size history, which was
fairly stable over time, and leveraged it against the CMS test dataset, which experienced a
dramatic population expansion (overall accuracy = 55.0%; rate of misclassifying neutral
regions as any one of the four non-linked sweep states = 1.7%). Despite this
misspecification, the confusion matrix (Figure S5) strongly resembles the corresponding
matrix that is correctly specified for demography (*i.e.* for CMS in Figure S4). In particular,
accuracies for finding neutral regions, completed hard sweeps, and partial hard sweeps are
roughly equivalent between the correctly specified model and misspecified model (Figure
S5). For soft sweeps, while confusion between completed and partial sweeps is increased
for the misspecified model, the overall ability to distinguish sweeps from neutrality is
largely preserved. Moreover, the rates at which examples from the linked classes were
mistaken for sweeps are seemingly unaffected.

To further examine the impact of increasingly misspecified demography, we
produced five additional full testing datasets assuming a simple two-epoch instantaneous
contraction model. The five test sets differed only by bottleneck severity, which increased
in even intervals from 20× to 100×. We then applied the CNN that was trained given the
BFS population history and measured overall accuracies. These accuracy measurements
are generally similar to that of our baseline, *i.e.* the corresponding original experiment
whereby the testing data were simulated under the inferred demography for BFS, thus the
demography was correctly specified with respect to the training set underlying this CNN
(Figure S6). However, performance gradually worsens with decreasing bottleneck severity
across the test sets, but this may be largely an effect from the number of polymorphisms.
To address this, we generated another six test sets that identically replicated the
specifications for the BFS training simulations except with $\theta$ fixed in value yet varying
between the six datasets. Notably, the range we utilized here for $\theta$ exceeded the $\theta$ prior
distribution for the original BFS training and testing simulations, hence further evaluating
model misspecification. We find no loss in overall accuracy except in the case with the least
genetic diversity simulated, where there is a moderate decrease (Figure S7). This is

unsurprising given that low levels of genetic diversity lead to noisy estimates of the
statistics employed by *partialS/HIC*. It is encouraging however that sensitivity is
maintained throughout most of our $\theta$ prior distribution range and accuracy does not fall
below that of our baseline experiment until $\theta$ is at a low value toward the bounds ($\theta$ <
5,000 for the full genomic window size of 55,000 base-pairs). To put this into perspective,
genetic diversity measures for the corresponding empirical BFS dataset are consistent with
simulations generated with $\theta \geq 5,000$, and likewise are beyond nearly the entirety of the $\theta$
= 1,000 simulated values; among the sub-windows that passed our filtering thresholds
(Figure S1), there is a median value of $\theta_W$ = 2.633e-2 (central 95% density: 6.484e-3 –
3.547e-2) and $\theta_H$ = 6.318e-3 (central 95% density: 2.381e-3 – 1.231e-2), compared to a
median value of $\theta_W$ = 1.218e-2 (central 95% density: 1.116e-3 – 1.849e-2) and $\theta_H$ = 3.863e-
3 (central 95% density: 8.592e-4 – 9.696e-3) across all sub-windows generated under the $\theta$
= 5,000 condition, whereas the simulations given $\theta$ = 1,000 have a median value of $\theta_W$ =
2.353e-3 (central 95% density: 9.802e-5 – 3.861e-3) and $\theta_H$ = 7.043e-4 (central 95%
density: 5.950e-8 – 2.571e-3).

Together, these results indicate that sweep discovery and localization is not strongly
impacted by several forms of demographic model misspecification during training.

## Partial sweeps are unpredictably misclassified as either completed sweep or neutral when not explicitly considered

Since the previous versions of *partialS/HIC* (*S/HIC* and *diploS/HIC*) did not allow for partial
sweep selection states, we were interested in how such five-state classifiers would behave
when confronted with partial sweeps. To explore this, we conducted a simulation
experiment that first removed partial hard and soft sweeps as well as their associated
linked classes from the CNN training process, thus training on only five states rather than
all nine. Next, in an effort to examine the classification behavior for these five-state CNNs,
we applied the full test set that included the partial sweep classes. Unsurprisingly, the
trend was for partial sweeps to be most often confused for linked selection (Figures 3, S8).

Perhaps more concerning is the false negative rate (*i.e.* rate at which partial sweeps were

misclassified as neutral), which was substantial in partial hard sweeps for several

populations (median = 8.8%; max = 32.4%; >1% in all populations) and extreme in partial

soft sweeps (>50% in three populations, >40% in three more populations, and >24% in all

populations). Partial hard sweeps that were discovered were also often misclassified as a

completed soft sweep (median rate of misclassification as completed soft sweep = 5.5%).

However, when training included partial sweeps, there is universal and dramatic

improvement in both finding sweeps and correctly identifying the model of selection

(Figures 2, S4). Meanwhile, overall accuracy remains similar among the five-state and nine-

state classifiers with respect to simulations of neutral, completed sweep, and linked classes

exclusively (Figures 3, S8; Table S2). As a result, accuracy should only stand to benefit from

incorporating partial sweeps into training since ignoring such information leads to

unacceptably high false negative rates of partial sweeps being called neutral or linked.

*Figure 3. Confusion matrix heatmap of simulation experiment with partial sweeps ignored during training. Given the BFS population history. Structured in the same manner as Figure 2, each row designates a true simulation class and darker blue cells represent a higher proportion of the 1,000 calls for each true class. In contrast to Figure 2 though, each column indicates one of five inferred states instead of nine, as the two partial sweep and two linked partial sweep classification states were omitted from training to determine misclassification bias when partial sweeps are ignored. There is a substantial decrease in discovery of partial sweeps, especially partial hard sweeps (20.5% total sweep discovery compared to 78.2% in Figure 2; 46.3% total sweep discovery of partial soft sweeps compared to 62.3% in Figure 2). Specifically for partial hard sweeps, a large proportion of the detected sweeps are misclassified as soft sweeps instead of hard sweeps (19.0%; i.e. 3.9% of calls = soft sweeps : 16.6% of calls = hard sweeps).*

## *partialS/HIC* binary classification outperforms several competing approaches

*Figure 4. ROC curves for binary classification of selective sweeps, including partial*
*sweeps, versus regions neutrally evolving or under linked selection. Given the BFS*
*population history. The partialS/HIC deep learning classifier outcompetes two other*
*approaches for managing the same suite of summary statistics: Composite of Multiple Signals*
*and principal component analysis. Furthermore, partialS/HIC excels in performance over*
*several sub-window derivatives of two summary statistics, SAFE and iHS, which were all*
*included within our set of summary statistics used for training. Notably, Composite of Multiple*
*Signals, SAFE, and iHS were all designed to uncover selective sweeps. Additionally, the SAFE*
*score is itself a compound statistic that captures signal from several constituent statistics, and*
*the majority of our training data is derived from either the SAFE score or one of its*
*components.*

To assess whether the collection of summary statistics under our deep learning method

extends inferential resolution beyond the signal conferred by *iHS* or SAFE alone, and to

determine if our CNN approach leverages these statistics in a more informative manner

than other aggregation schemes, we compared receiver operating characteristic (ROC)

curves, which plot true positive against false positive rates given varying thresholds, for the
binary classification task of broadly detecting selective sweeps (*i.e.* any of the four selection
states involving a sweep within the focal sub-window) vs. neutral regions or linked sweeps.
We selected for our comparison *iHS*-derived statistics (mean, maximum, and proportion of
outlier *iHS* values within the central sub-window of the testing simulations) because *iHS*
was explicitly designed for detecting partial sweeps [28], and SAFE-based statistics
(variance and maximum of SAFE scores within the central sub-window of the testing
simulations) since SAFE is a compound of many variables, of which the vast majority of our
training data are summaries [29]. Additionally, we conducted a principal component
analysis (PCA) from the training data, restricted to only the focal sub-window as well as for
the entire dataset throughout the full window respectively in two separate PCAs, and
projected the testing data onto the first two principal components (PC1, PC2). We then
produced a ROC curve from each set of principal component values transformed from the
testing data, respectively to both PC1 and PC2 as well as the PCA on solely the central sub-
window versus the full-scale window, for a total of four individual ROC curves. These ROC
curves allow contrast to a simple dimensionality reduction approach. Lastly, we computed
Composite of Multiple Signals scores from the testing data for both the focal sub-window
and full window respectively, using the training data to derive probability distributions.
Deploying the Composite of Multiple Signals metric provides an alternative method that is
intended to exploit multiple summary statistics for inference of positive selection [31]. For
a direct comparison, we altered *partialS/HIC* slightly to create a CNN that had two final
output responses (*i.e.* sweep in central sub-window vs. no sweep in central sub-window)
instead of nine, with the training dataset as well as architecture of network layers (Figure
1) remaining the same. The CNN optimized for binary classification was then applied to the
testing simulations, with the output probability of a selective sweep utilized as input to
generate the ROC curve.

The *partialS/HIC* binary classifier consistently outperforms other methods in
identifying selective sweeps to the focal sub-window when partial sweeps are included
(median AUC = 0.943; Figures 4, S9). Interestingly, we demonstrate that the Composite of
Multiple Signals also has a strong ability to extract information from our selection of

summary statistics, though it always trails behind *partialS/HIC*; in every case, the best performance after *partialS/HIC* is for the Composite of Multiple Signals based on all sub-window statistics (median AUC = 0.876), while the next best ROC curve is from the Composite of Multiple Signals calculated from only the central sub-window (median AUC = 0.859). In contrast, with the unexpected exception of PC2 for central sub-window statistics (median AUC = 0.749), PCA appears to be an unfavorable approach for combining summary statistics to infer selective sweeps (*e.g.* median AUC for PC1 of all sub-window statistics = 0.500). Furthermore, there is evidence that SAFE scores capture important signal about selective sweeps in a manner that is robust to the final frequency of the selected mutation, particularly the variance of SAFE scores within the focal sub-window (median AUC = 0.787). Conversely, there seems to be decreased signal in *iHS*, as all its focal sub-window variants individually performed quite poorly (*e.g.* median AUC for proportion of *iHS* outliers = 0.582).

## Soft and partial sweeps are commonplace among *A. gambiae* populations

*Figure 5. Genome-wide partialS/HIC sweep calls across empirical mosquito population datasets.* *For all eight datasets, there is a minimal number of calls for completed hard sweeps, represented here on the Y-axis as the relative proportion to the total set of empirical calls across every genomic window per population dataset. However, there is indeed a substantial proportion of sweep calls for hard sweeps, yet are incomplete or in-progress. In most cases, the number of both completed and partial soft sweeps further exceeds that of partial hard sweeps. Furthermore, the majority of sweeps have not reach fixation across these Anopheles populations.*

Turning our attention to the Ag1000G phase I data, we applied our nine-state CNNs to the corresponding *A. gambiae* population datasets, classifying 5 KB segments using a 55 KB full sliding window throughout the whole genome (Figure S1). Each of the eight mosquito populations contains a large number of sub-windows identified as completed soft sweeps (median fraction of total calls genome-wide = 5.01%) as well as partial sweeps (median fraction of total calls genome-wide for partial hard sweep = 2.84%; median fraction of total calls genome-wide for partial soft sweep = 7.24%), coupled with only a handful of completed hard sweep predictions (median fraction of total calls genome-wide = 0.03%)

(Figure 5; Table S3). Partial soft sweeps were typically discovered most often (median
proportion of sweep calls = 52.59%), with completed soft sweeps often following (median
proportion of sweep calls = 28.80%) and partial hard sweeps usually being the third most
numerous class of detected sweep (median proportion of sweep calls = 19.75%). Notably,
our estimated false discovery rates (FDRs) are higher for soft sweeps (median FDR for
completed soft sweeps = 11.09%; median FDR for partial soft sweeps = 12.20%) compared
to hard sweeps (median FDR for completed hard sweeps = 0.00%; median FDR for partial
hard sweeps = 0.39%); this implies that individual soft sweep candidates should be viewed
with more caution, though we should be able to estimate the genome-wide proportion of
these classes well. Specifically, classifications for partial soft sweeps outnumber those for
completed soft sweeps in every population besides GNS, as well as partial hard sweep calls
in all populations but GAS. Importantly, these findings remain the same, with the exception
that calls for partial hard sweeps now slightly exceed partial soft sweep classifications in
GNS, after false discovery correction (Table S3). Additionally, had partial sweeps not been
accounted for in the training process, our results suggest that we would have both
underestimated the total number of sweeps and incorrectly labeled many of our partial
sweeps (Figures 3, S8). This would have led to the conclusion that adaptation from
standing variation rather than *de novo* mutations dominate selective sweep dynamics in
these *A. gambiae* populations. While it is clear that soft sweeps are indeed more common in
these data, our results suggest that hard sweeps often occur as well, though with few
reaching fixation. Furthermore, the *partialS/HIC* classifications indicate that most selective
sweeps in these population samples are incomplete, suggesting that we are capturing a
view of selection in progress.

**Selective sweeps are significantly enriched in functional regions of the *A.***
***gambiae* genome**

To elucidate broad characteristics underlying the genomic targets of selection, we used
permutation tests of sweep call locations to discover enrichment patterns in the following
DNA regions of interest: gene, mRNA, exon, CDS, five-prime UTR, and three-prime UTR.

Permutation tests were based on the total number of calls for the four selection states with

sweeps occurring within the focal sub-window, as well as the individual number of calls for

each of these states respectively. Across all eight population datasets and for all six DNA

regions under investigation, there is a statistically significant enrichment of total sweep

calls along with completed soft sweeps calls in particular, whereas completed hard sweep

calls are not significantly enriched in any single case (Figures 6, S10; Table S4). Conversely,

partial sweep enrichment varies among populations as well as individual DNA regions.

Specifically, partial hard sweeps are significantly enriched in five of the six DNA regions for

BFS and CMS, and four of the DNA regions for UGS; while partial soft sweeps are

significantly enriched in all six DNA regions for UGS, five of the DNA regions for BFM, and

four of the DNA regions for BFS.

*Figure 6. Enrichments of partialS/HIC empirical selective sweep calls within DNA regions.* *For the BFS population empirical dataset. Statistically significant (p < 0.05) enrichments in green. No enrichment (i.e. single-fold enrichment based on the permuted calls) is represented by the dotted line. Completed soft sweeps are enriched within all six DNA regions that experienced permutation tests. Similarly, all of the DNA regions have an enrichment of partial sweeps, hard and/or soft. In contrast, there is no significant enrichment*

*of completed hard sweeps for any of the DNA regions. Overall though, selective sweeps in general are enriched for each of the DNA regions.*

## Insecticide resistance loci, especially related to metabolism, are significantly enriched for selective sweeps

We performed a similar permutation analysis for four sets of genes known to confer insecticide resistance (IR), finding at least one set of IR genes to be statistically significant for every population dataset in enrichment of total sweep calls (*i.e.* aggregate of all four sweep classes) and completed soft sweeps, respectively (Figures 7, S11; Table S5). In particular, metabolism-related IR genes are significantly enriched for each of these cases. Furthermore, IR genes corresponding to well-characterized resistance loci (*i.e.* target sites) are significantly enriched for AOM and BFM total sweep calls as well as completed soft sweeps in AOM, BFM, and GNS; IR genes associated with behavior are significantly enriched for BFM and GNS total sweep calls as well as completed soft sweeps in AOM, CMS, and GAS; and IR genes affiliated with cuticular activity are significantly enriched for completed soft sweeps in GWA and UGS. In contrast, completed hard sweeps are only significantly enriched in BFS, GNS, GWA, and UGS for IR genes connected to behavior (as well as metabolism for BFS). For partial sweeps, significant enrichment only occurs within BFM (partial soft sweeps in metabolism as well as behavior IR genes), CMS (partial hard sweeps in metabolism as well as target site IR genes), and UGS (partial hard sweeps in metabolism IR genes).

## Completed soft sweeps are significantly enriched within the same GO term annotations across populations

To uncover further functional traits targeted by selection, we used our permuted datasets to find individual gene ontology (GO) terms that are enriched in our sweep candidates. Partial soft sweeps are not significantly enriched for any GO terms among populations,

while completed hard sweeps and partial hard sweeps are each enriched only in UGS for a

single GO term belonging to the cellular components GO domain; specifically, "membrane"

is enriched of completed hard sweeps and "nuclear cohesion complex" is enriched of partial

hard sweeps. Otherwise, GO term enrichment pertains to just completed soft sweeps as

well as the total of all four sweep states in combination (Table S6). For the completed soft

sweep significant enrichments, we found six cases of the same GO term in all eight

populations. Three of these are related to cellular components ("nucleus", "membrane" and

"integral component of membrane"), and the other three are connected to molecular

function, specifically binding ("nucleic acid binding", "protein binding" and "ATP binding").

All six of these terms, especially those conferring binding function, are also enriched for

total sweep calls across multiple datasets: "nucleic acid binding" and "ATP binding" in

seven populations; "protein binding" and "nucleus" in six populations; "integral component

of membrane" in five populations; and "membrane" in three populations, one of which is

significantly enriched for this GO term of completed hard sweeps as well, the single

example of such among all populations. Other cases involving the same GO term

significantly enriched for completed soft sweeps in over half of the populations include:

"binding", "cytoplasm", and "zinc ion binding" in seven populations; "RNA binding" in six

populations; and "mRNA splicing, via spliceosome" and "ATPase activity" in five

populations.

*Figure 7. Enrichments of partialS/HIC empirical selective sweep calls within groupings of insecticide resistance genes.* For the BFS population empirical dataset. Statistically significant ($p < 0.05$) enrichments in green. No enrichment (i.e. single-fold enrichment based on the permuted calls) is represented by the dotted line. Rows without a plotted point are due to the insecticide resistance gene group not having any calls of that sweep type (e.g. there are no completed hard sweeps called within target site genes). In this mosquito population, there

521    *is evidence for several mechanisms through which insecticide resistance evolved, both in*
522    *sweep types and categories of genes under selection.*

524                                    **Discussion**

***partialS/HIC* elucidates both species-wide and population-specific sweep**
**dynamics within *A. gambiae***

The Ag1000G data provided the opportunity to investigate selection at both the continental
scale, where wide-reaching impact across the whole species complex could be uncovered,
and the regional level, revealing population-specific sweep dynamics. For the former, we
observed that *A. gambiae* populations consistently experienced very few completed hard
sweeps, with nearly all sweeps being partial and/or soft. In fact, the impact of completed
hard sweeps on the adaptive process within mosquitos appears to be even more limited
than what was observed previously in humans [32]. This is likely a result of the much
larger population sizes and concordant levels of genetic variation that are maintained
within *Anopheles* populations. Importantly, we find a large number of ongoing selective
sweeps within these populations, particularly in comparison to the number of completed
sweeps. There are multiple reasons why this might be the case. A trivial explanation may
simply be that we only have power to detect sweeps that have completed in the past few
hundred generations, though this seems unlikely. More plausibly, a large number of
ongoing sweeps might be expected given the recent change in environment induced by
vector control efforts. Another possible explanation is that the frequency dynamics of
beneficial alleles within a population is often more complex than assumed and may indeed
contain an overdominant component [33]. This would mean that some portion of the
partial sweeps that we are observing in *Anopheles* is actually balanced, or transiently
balanced, polymorphisms. A fourth class of explanation is that beneficial mutations may
not be able to fix in populations due to competition with beneficial mutations on other
genes that have originated in different parts of the species range [34]. Indeed, each of these
factors may play some role in our reported abundance of partial sweeps.

Although such genome-wide sweep patterns occur species-wide, enrichment

behavior seems much more population-specific. For instance, while every population

possesses significant enrichment of completed soft sweeps coupled with no completed

hard sweep significant enrichments for the six functional DNA regions studied here, partial

sweep enrichments vary widely among datasets. Sweep behavior is even more

idiosyncratic for insecticide resistance genes, as the only constant between populations is

that metabolism is a recurring target of selection, especially for completed soft sweeps.

These findings from the Ag1000G data provide important genomic resources that

could inform continental-wide malaria control strategies for the entire *A. gambiae* species

complex, as well as have relevance to management efforts specialized to certain

populations and localities. Such insight into mosquito vector evolution may also help curb

future insecticide resistance adaptation, and in turn prevent impending crises of vector

control failure. However, it is important to consider that our partial sweep calls could be

capturing more complex selective dynamics at play, for example polygenic and quantitative

trait adaptation [35,36], balancing selection [37], and introgression of beneficial alleles.

These could lead to different modes of adaptation for the same genomic region across

populations, for instance a favorable SNP undergoing a soft sweep at its origin and then

carried to neighboring populations (as was suggested in Miles *et al.* [6]) may appear to be

experiencing a partial hard sweep in those recipient populations. Such complicated

interactions merit further investigation on the Ag1000G data, which would not only

continue advancing methodological development for population genetics, but also address

interesting questions for a widespread and ecologically important organism that has

crucial ramifications on wildlife management and public health.

*partialS/HIC* **offers unprecedented detection of partial sweeps**

Supervised machine learning approaches are rapidly gaining traction among population

geneticists, with deep learning in particular beginning to experience increased attention

and methodological development due to its exciting potential to unlock classic population

genetics problems. Examples of successful SML implementation in population genomics
include demographic model choice [38], demographic parameter inference [39],
comparative analysis of independent single-population size changes [40], identification of
introgressed regions [41], recombination rate estimation [42–44], and genomic scans of
selective sweeps [22]; deep learning specifically has been employed for joint inference of
demography and selection [23], discovery of recombination hotspots [45], estimation of
demographic and recombination parameters [46,47], discovery of functional variants [48],
prediction of geographic origin [49], and differentiating between hard and soft sweeps
from neutral regions [24]. These applications especially benefit from the ability to handle
high dimensional input data and bypassing the need of a likelihood function, which is due
to SML uncovering data patterns from leveraging *a priori* information through a training
algorithm [23,26]. CNNs expand this utility to image processing, which has been
demonstrated with *diploS/HIC* to be a powerful tool for exploiting the genomic spatial
distribution of multiple population-level summary statistics to detect selective sweeps [24].

Here, we demonstrated with *partialS/HIC* that deep learning can be extended to
partial sweeps, especially partial hard sweeps, yielding greater accuracy and robustness
than has been previously attained. We also showcased consistent performance in the face
of several underlying demographic backgrounds. Specifically, *partialS/HIC* is capable of
discovering selective sweeps when partial sweeps are considered, simultaneous
disambiguation between partial and completed sweeps as well as between hard and soft
sweeps, and spatial localization of selection targets in the genome. Moreover, we have
shown that partial sweeps remain mostly undetected if ignored from the training process,
even though such selection may be commonplace throughout a genome as with the
Ag1000G data. As a result, many previous studies scanning for either complete or ongoing
selective sweeps solely (*i.e.* not jointly inferring both types of selection) may have
overlooked an important subset of evolutionary events [34]. Researchers may then be
interested in reexamining datasets with *partialS/HIC* to elucidate the relative contributions
of fixed versus incomplete sweeps to adaptive evolution.

Importantly, the efficacy of *partialS/HIC* relies on several factors that are
unexplored here, including simulation prior specifications, CNN architecture with respect

to construction and parameterization of neural network layers, and data structure. Hence,
it is prudent for future implementations to validate performance by testing a range of
configurations, given a project's individual intricacies, to assess robustness and inherent
assumptions. In particular, future exploration of alternate image constructions could be
potentially of great methodological benefit. Such images could be derived from different
ordering schemes and/or suites of summary statistics, as well as without summary
statistics entirely, instead directly exploiting sequence alignments [45–47,49] or even raw
reads. More broadly, CNNs can be further extended to address other long-standing efforts
in evolutionary biology, such as parameter inference under complex isolation-migration
models or phylogenetic reconstruction [50].

## Methods

### Simulations for training and testing CNN classifier

We used *discoal* [30] to simulate training and test datasets corresponding to each *A.*
*gambiae* population under nine different selection states: neutrally evolving, completed
hard sweep, completed soft sweep, partial hard sweep, partial soft sweep, and linked
region for every one of the four sweep classes (Figure S1; Table S7). For the four sweep
types, the target SNP was located in the exact middle position within the central, or sixth in
sequence, sub-window of 11 in total; the selected SNP was placed in the middle within one
of the other ten sub-windows for linked sweeps. There were 2,000 training examples per
selection state (with the specific sub-window under selection, *i.e.* one of ten possible
simulation classes, randomized for linked sweeps) and 1,000 test examples per class
(including for each of the ten linked sweep locations), resulting in a training dataset of
18,000 simulations and a test dataset of 45,000 simulations given each demographic
history, thus totaling 144,000 training and 360,000 test simulations (as well as 495,000
additional test simulations from 11 test datasets all under the BFS population history to
explore demographic misspecification; see below). To conduct single-population
simulations with *discoal*, we used the *stairway plot* [51] point estimates from Miles *et al.* [6]

for size change parameters as well as $N_0$ (present-day effective population size), assumed a

mutation rate ($\mu$) of $3.5\times10^{-9}$ mutations per base pair per generation, and performed

random draws for locus-wide mutation and recombination rates from the following

distributions for each independent replicate: $\theta \sim U(\frac{2\times E[\theta]}{11.0}, \frac{2\times E[\theta]}{1.1})$, whereby $E[\theta] = 4N_0\mu L$

and $L$ is the length of the simulated sequence with $L$ = 55,000 base pairs; $\rho \sim TEXP(2\times E[\theta]$,

$6\times E[\theta])$, where $\rho = 4N_0 rL$, $r$ is the recombination rate per base pair, and $TEXP(\beta$, maximum

value) is a truncated exponential distribution with mean $\beta$; $s \sim U(1.0\times10^{-4}, 1.0\times10^{-2})$; end

time of sweep $\sim U(0, 2,000)$ generations ago, which represents fixation for completed

sweeps and the transition back to neutral evolution for partial sweeps; selected SNP allele

frequency at onset of soft sweep $\sim U(\frac{1}{N_0}, 0.2)$; and selected SNP allele frequency at end of

partial sweep $\sim U(0.20, 0.99)$.

## Constructing two-dimensional feature vector images of summary statistics

The eight training and test datasets (including an additional 11 BFS datasets for testing

demographic misspecification), as well as empirical datasets, were converted into two-

dimensional feature vector matrices for downstream deep learning (Figure S1); this was

performed within the Python environment and required usage of the module *numpy*. Prior

to this two-dimensional transformation, the simulated data were modified to better

account for uncertainty within the empirical data, specifically: 1) sites that were missing

any individual calls or could not be polarized against the outgroup were excluded; and 2)

incorrect identification of the derived allele. For the former, each simulation randomly

drew from a distribution of 1,552 masking profiles (with test simulations drawing without

replacement per selection class of 1,000 simulations), which determined the exact sites to

be omitted from further analysis; a masking profile consisted of the site positions within a

single full 55 KB window on the *A. gambiae* genome that had absent at least one sample

throughout the entirety of the Ag1000G data and/or ancestral state information, and the

total set represented all 1,552 sequential, non-overlapping windows (*e.g.* 2L: 1–55,000; 2L:

55,001–110,000; 2L: 110,001–165,000; etc.) where the proportion of masked sites did not

exceed 75% in any of the constituent sub-windows (*i.e.* 1,250 sites). To account for

mispolarization, estimated rates were obtained from Miles *et al.* [6] and exploited via a

binomial distribution to mispolarize a random subset of SNPs to the other allele per

simulation.

The empirical data similarly underwent processing for compatibility with the

simulated data. First, chromosomes were delineated into sequential 5 KB sub-windows

(*e.g.* positions 1-5,000 formed the first sub-window, positions 5,001-10,000 formed the

second sub-window, etc.), with the aforementioned masking criteria applied across sites

and remaining SNPs polarized. Within each population dataset, all polymorphic positions

composed of more than two alleles were further removed from analysis, such that only

polarized monomorphic and biallelic sites comprising a full data matrix of no missing data

were left. Sub-windows containing no SNPs or less than 25% of the original sites were

subsequently discarded, and every configuration of 11 contiguous 5 KB sub-windows of

those remaining formed a single full window, which would be classified into one of the nine

selection states based upon its central sub-window while using spatial information from

the neighboring five sub-windows on either side. To clarify, this eliminated any window

that did not have a consecutive sequence of 11 sub-windows that survived data filtering,

and resulted in a sliding window that progressed a single sub-window at a time, such that

succeeding full windows could be overlapping by up to ten sub-windows.

Every independent simulation totaling 55 KB in length from 11 sub-windows of 5

KB, as well as empirical sequence of 11 adjacent sub-windows per population, was then

transformed into 89 separate summary statistic vectors that capture aspects of population-

level variation across the sampled individuals, with each vector consisting of 11 elements

corresponding to the sub-windows. The first 17 summary statistics were $\pi$ [52], $\theta_W$ [53],

Tajima's $D$ [14], $\theta_H$ [15], Fay-Wu's $H$ [15], number of unique haplotypes, $H_1$ [54], $H_{12}$ [54],

$H_2/H_1$ [54], $Z_{nS}$ [55], maximum $\omega$ [16], $E[iHS]$ [28], maximum $iHS$ [28], proportion of outlier

*iHS* values [28], variance of pairwise genotype distances [24], skewness of pairwise

genotype distances [24], and kurtosis of pairwise genotype distances [24]. These were

previously implemented in *S/HIC* [22] and/or *diploS/HIC* [24] except for $H_1$ (though a

multilocus genotype equivalent was used in *diploS/HIC*) and the *iHS*-based statistics. We

employed the Python package *scikit-allel* to calculate $\pi$, $\theta_W$, Tajima's $D$, $\theta_H$, Fay-Wu's $H$,

number of unique haplotypes, $H_1$, $H_{12}$, $H_2/H_1$, and the statistics related to *iHS*. Values for *iHS*

were standardized within 50 derived allele frequency bins, following mispolarization in the

case of simulated data. Outlier *iHS* values were defined as within either 2.0% tail of the

distribution obtained from simulations of neutral evolution under the appropriate

demographic history.

The remaining 72 summary statistics were distribution summaries of SAFE and its

various components [29], specifically: haplotype allele frequency (HAF), which is the sum

of derived allele counts across all the derived alleles present within a sequence; unique

HAF score (*i.e.* each unique HAF value is counted only once, even if representing multiple

individuals); $\varphi$, which is the sum of HAF scores for sequences harboring the derived allele,

divided by the total sum of HAF scores across all sequences; $\kappa$, which is the proportion of

distinct HAF scores that carry the derived allele; derived allele frequency; and the SAFE

score itself, which is the difference between $\varphi$ and $\kappa$ normalized against the derived allele

frequency. Notably, HAF is calculated per sequence, whereas $\varphi$, $\kappa$, derived allele frequency,

and SAFE are calculated per polymorphism. The following distribution summaries were

utilized to construct individual values spanning a sub-window: mean, median, mode; 2.5%,

25%, 75%, and 97.5% quartiles; maximum, variance, standard deviation, skewness, and

kurtosis. Importantly, each summary statistic vector was normalized, in the same manner

as the preceding versions to *partialS/HIC* [22,24], to capture signal solely from the relative

spatial distribution of the summary statistics across the 11 sub-windows, rather than

allowing influence from absolute values. Subsequently, the 89 vectors were vertically

collated to form a two-dimensional matrix that could then be exploited for image

processing. The arrangement of these vectors were such that the 11 columns corresponded

to the series of sub-windows from left to right, and the 89 rows of summary statistics were

in the order presented here (with the distribution summaries iterating first for every SAFE

component, *e.g.* row 52: skewness of $\varphi$ values; row 53: kurtosis of $\varphi$ values; row 54: $E[\kappa]$).

Importantly, column and row order affects deep learning optimization, which may have

consequences on overall efficacy, due to the convolutional and pooling windows employed

by the CNN architecture, hence related summary statistics were grouped together (*e.g.*

alternative distribution summaries of a SNP-based statistic, various SAFE derivatives).

Heatmap images, based on median values per statistic and sub-window, were generated in

R for the neutral case and each of the four sweep states under every population history

from the training simulations.

## Training and testing CNNs for deep learning implementation

The architecture of our CNN was composed of the following sequential layers: 1) 2D

convolutional layer with 256 filters using 3×6 windows and "same" padding; 2) 2D max

pooling layer given a 3×3 window; 3) a second 2D convolutional layer of 256 filters based

also on 3×3 windows, "same" padding, and ReLU activation; 4) a second 2D max pooling

layer with a 3×1 window; 5) dropout layer with p=0.25; 6) flattening layer; 7) fully-

connected layer with ReLU activation to 512 responses; 8) a second dropout layer with

p=0.50; 9) a second fully-connected layer with ReLU activation to 128 elements; 10)

another dropout layer with p=0.50; and 11) softmax activation layer to 9 states (Figure 1).

This architecture was trained using the Python module *Keras* [56] given the *Adam*

optimizer [57], with 20 epochs, batch size of 32 simulations per step within an epoch, and

10% of the training data (*e.g.* 1800 simulations from the total nine-state training dataset)

randomly removed as a validation set during optimization (Figure S1). Training was

performed for every population demography under three experimental settings: 1) given

the full set of training data distributed across nine selection states; 2) exploiting a subset of

the training data from only five of the selection states, specifically those involving neutral

regions or completed sweeps; 3) deploying the entire training data, but with binary

classification between selective sweeps in the focal sub-window and all unselected classes

(*i.e.* neutral class together with every linked class). The three training regimes were then

applied to the test dataset that corresponded in underlying simulated history, resulting in

predictions of selection state given the default *Keras* threshold parameters for the first two

training schemes, whereas the softmax probability of a focal sweep was instead exploited

under training on binary classification. In the former case, individual inferences per test

simulation were collated and compared against true values to produce overall accuracy
measures as well as confusion matrix heatmaps to assess misclassification bias for each of
the 45 simulated scenarios (*i.e.* 11 sub-window sweep locations for each of the four sweep
types, plus neutrality).

Moreover, to explore the effect of demographic misspecification, we conducted a
single additional test under the first experimental set-up whereby the CNN trained on the
GAS simulations was applied to the CMS test simulations. Furthermore, we engaged in two
more misspecification experiments that involved simulating, for the first experiment, five
testing datasets that changed the underlying demographic model, and for the second
experiment, six testing datasets that differed in fixed $\theta$ value. In the five test sets that
altered the demographic history, we used an instantaneous contraction model that
experienced a population crash at 0.0001 time units with an intensity of, respectively
across the five datasets: 20×, 40×, 60×, 80×, 100×. Priors for $\theta$, $\rho$, $s$, end time of sweep,
selected SNP allele frequency at onset of soft sweep, and selected SNP allele frequency at
end of partial sweep remained the same as for the initial BFS simulations. In the six test
sets that varied $\theta$, we employed the same parameterization from the initial BFS simulations
with the exception that $\theta$ was set to, respectively across the six datasets: 1,000; 5,000;
10,000; 15,000; 20,000; 25,000. Our motivation for these intervals was to exceed the
bounds of the original prior distribution, $\theta \sim U(1,750.204699, 17,502.046985)$. After
simulation, we leveraged the nine-state CNN trained under the BFS specifications against
each of the 11 testing datasets to obtain overall accuracies for comparison among these test
datasets and to the original test dataset whereby the BFS history was correctly modeled.

Regarding the binary classification experiment, the Python module *sklearn* [58] was
used for building the ROC curves to evaluate accuracy and sensitivity. Additionally, *sklearn*
was utilized for conducting PCA on the training simulations, on either the focal sub-window
or across the entire full-scale genomic window respectively, with subsequent projection of
the testing simulations into independent sets of PC1 and PC2 values, to obtain a total of
four individual ROC curves. To calculate the Composite of Multiple Signals [31], training
data were separated into the two categories of selection versus neutrality (*i.e.* 4,000
simulations from four selection states versus 41,000 simulations from 41 neutral or linked

classes), which were respectively converted into a histogram of 200 bins for every
summary statistic. Assuming the Composite of Multiple Signals for the central sub-window
only, this resulted in a total of 178 distributions given the 89 statistics for both selection
and neutral; for all sub-windows, this was instead a total of 1,958 distributions due to the
11 total sub-windows of statistics. These distributions were then employed to calculate
probabilities both under selection and neutrality for the corresponding testing data
summary statistics; for bins with a zero value, 0.1 of the smallest possible increment (*i.e.*
selection: $\frac{0.1 \times 1}{4000}$; neutrality: $\frac{0.1 \times 1}{41000}$) was assigned as the probability. To determine the prior
for each probability, represented in the original Composite of Multiple Signals equation by
π, we utilized the proportional composition of the training simulations (*i.e.* selection: $\frac{4}{45}$;
neutrality: $\frac{41}{45}$). Finally, probabilities were natural log transformed and summed among
summary statistics to compute the Composite of Multiple Signals.

## Detecting selective sweeps for *A. gambiae* population datasets

To scan the genome for signatures of selective sweeps, the nine-state trained CNNs were
applied to the eight empirical mosquito datasets, with the underlying simulated
demography matched to the sampled population (Figure S1). Calls were corrected for false
discovery by exploiting the accuracy and error rates for neutral regions from the nine-state
simulation experiment, such that the amount of neutral calls was assumed to be
underestimated while the amount of calls for the remaining eight selection states were
assumed to be inflated. Subsequently, we produced sets of 10,000 randomly permuted calls
across the genome to derive null expectations of sweep enrichment, following Schrider and
Kern      [32].      Using      the      gene      annotation      file      "Anopheles-gambiae-
PEST_BASEFEATURES_AgamP4.7.gff3.gz" from VectorBase, we exploited these permuted
datasets to assess statistically significant enrichment within certain DNA regions,
groupings of known IR genes (N. Harding, *pers. comm.*), and all basic GO term definitions
from http://www.geneontology.org (last accessed February 18, 2015). The DNA regions of
interest included gene, mRNA, exon, CDS, five-prime UTR, and three-prime UTR; IR genes

were assigned to four functional categories: metabolism, target sites, behavior, and
cuticular. To determine significant enrichment, the number of inferred calls for a particular
DNA region or IR gene category had to have a $p$-value < 0.05 based on the respective
distribution of 10,000 permutations; for the GO terms, we deployed a corrected $q$-value <
0.05 due to concerns of false discovery stemming from the large number of terms tested for
enrichment.

# Acknowledgments

818 We thank Jeff Adrion for comments on the manuscript. This work was supported by NIH
819 award no. R01GM117241 to ADK and NIH award no. K99HG008696 to DRS.

# References

1. WHO. World Malaria Report 2015 [Internet]. 2015. Available:
http://www.who.int/malaria/publications/world-malaria-report-2015/en/

2. Hemingway J, Ranson H, Magill A, Kolaczinski J, Fornadel C, Gimnig J, et al. Averting a
malaria disaster: Will insecticide resistance derail malaria control? Lancet. 2016;387:
1785–1788. doi:10.1016/S0140-6736(15)00417-1

3. Brown AW. Insecticide resistance in mosquitoes: a pragmatic review. J Am Mosq
Control Assoc. 1986;2: 123—140.

4. Elissa N, Mouchet J, Rivière F, Meunier J-Y, Yao K. Resistance of Anopheles gambiae
s.s. to pyrethroids in Côte d'Ivoire. Ann Soc Belg Med Trop (1920). 1993;73: 291–
294.

5. Martinez-Torres D, Chandre F, Williamson MS, Darriet F, Bergé JB, Devonshire AL, et
al. Molecular characterization of pyrethroid knockdown resistance (kdr) in the major
malaria vector Anopheles gambiae s.s. Insect Mol Biol. 1998;7: 179–184.
doi:10.1046/j.1365-2583.1998.72062.x

6. Miles A, Harding NJ, Bottà G, Clarkson CS, Antão T, Kozak K, et al. Genetic diversity of
the African malaria vector anopheles gambiae. Nature. 2017;552: 96–100.
doi:10.1038/nature24995

7. Oxborough RM, N'Guessan R, Jones R, Kitau J, Ngufor C, Malone D, et al. The activity of
the pyrrole insecticide chlorfenapyr in mosquito bioassay: Towards a more rational
testing and screening of non-neurotoxic insecticides for malaria vector control. Malar
J. 2015;14: 124. doi:10.1186/s12936-015-0639-x

8. Hammond A, Galizi R, Kyrou K, Simoni A, Siniscalchi C, Katsanos D, et al. A CRISPR-
Cas9 gene drive system targeting female reproduction in the malaria mosquito
vector Anopheles gambiae. Nat Biotechnol. 2016;34: 78–83. doi:10.1038/nbt.3439.A

9. Unckless RL, Messer PW, Connallon T, Clark AG. Modeling the manipulation of
natural populations by the mutagenic Chain reaction. Genetics. 2015;201: 425–431.
doi:10.1534/genetics.115.177592

10. Unckless RL, Clark AG, Messer PW. Evolution of resistance against CRISPR/Cas9 gene
drive. Genetics. 2017;205: 827–841. doi:10.1534/genetics.116.197285

11. Maynard Smith J, Haigh J. The hitch-hiking effect of a favourable gene. Genet Res
(Camb). Rutgers University; 1974;23: 23–35. doi:10.1017/S0016672308009579

12. Kaplan NL, Hudson RR, Langley CH. The "hitchhiking effect" revisited. Genetics.
1989;123: 887–899.

13. Stephan W, Wiehe THE, Lenz MW. The effect of strongly selected substitutions on
neutral polymorphism: analytical results based on diffusion theory. Theor Popul Biol.

1992;41: 237–254. doi:10.1016/0040-5809(92)90045-U

14.    Tajima F. Statistical method for testing the neutral mutation hypothesis by DNA
858           polymorphism. Genetics. 1989;123: 585–595.

859    15.    Fay JC, Wu C-I. Hitchhiking under positive Darwinian selection. Genetics. 2000;155:
860           1405–1413.

861    16.    Kim Y, Neilsen R. Linkage disequilibrium as a signature of selective sweeps. Genetics.
862           2004;167: 1513–1524. doi:10.1534/genetics.103.025387

863    17.    Nielsen R, Williamson S, Kim Y, Hubisz MJ, Clark AG, Bustamante C. Genomic scans
864           for selective sweeps using SNP data. Genome Res. 2005;15: 1566–75.
865           doi:10.1101/gr.4252305

866    18.    Pavlidis P, Jensen JD, Stephan W. Searching for footprints of positive selection in
867           whole-genome SNP data from nonequilibrium populations. Genetics. 2010;185: 907–
868           922. doi:10.1534/genetics.110.116459

869    19.    Lin K, Li H, Schlötterer C, Futschik A. Distinguishing positive selection from neutral
870           evolution: Boosting the performance of summary statistics. Genetics. 2011;187: 229–
871           244. doi:10.1534/genetics.110.122614

872    20.    Ronen R, Udpa N, Halperin E, Bafna V. Learning natural selection from the site
873           frequency spectrum. Genetics. 2013;195: 181–193.
874           doi:10.1534/genetics.113.152587

875    21.    Pybus M, Luisi P, Dall'Olio GM, Uzkudun M, Laayouni H, Bertranpetit J, et al.
876           Hierarchical boosting: A machine-learning framework to detect and classify hard
877           selective sweeps in human populations. Bioinformatics. 2015;31: 3946–3952.
878           doi:10.1093/bioinformatics/btv493

879    22.    Schrider DR, Kern AD. S/HIC: Robust Identification of Soft and Hard Sweeps Using
880           Machine Learning. PLoS Genet. 2016;12: e1005928.
881           doi:10.1371/journal.pgen.1005928

882    23.    Sheehan S, Song YS. Deep Learning for Population Genetic Inference. PLoS Comput
883           Biol. 2016;12: e1004845. doi:10.1371/journal.pcbi.1004845

884    24.    Kern AD, Schrider DR. diploS/HIC: An Updated Approach to Classifying Selective
885           Sweeps. G3 Genes, Genomes, Genet. 2018;8: 1959–1970. doi:10.1534/g3.118.200262

886    25.    Sugden LA, Atkinson EG, Fischer AP, Rong S, Henn BM, Ramachandran S. Localization
887           of adaptive variants in human genomes using averaged one-dependence estimation.
888           Nat Commun. Springer US; 2018;9: 703. doi:10.1038/s41467-018-03100-7

889    26.    Schrider DR, Kern AD. Supervised Machine Learning for Population Genetics: A New
890           Paradigm. Trends Genet. Elsevier Ltd; 2018;34: 301–312.
891           doi:10.1016/j.tig.2017.12.005

27.  Coop G, Ralph P. Patterns of neutral diversity under general models of selective
sweeps. Genetics. 2012;192: 205–224. doi:10.1534/genetics.112.141861

28.  Voight BF, Kudaravalli S, Wen X, Pritchard JK. A map of recent positive selection in
the human genome. PLoS Biol. 2006;4: e72. doi:10.1371/journal.pbio.0040072

29.  Akbari A, Vitti JJ, Iranmehr A, Bakhtiari M, Sabeti PC, Mirarab S, et al. Identifying the
favored mutation in a positive selective sweep. Nat Methods. Nature Publishing
Group; 2018;15: 279–282. doi:10.1038/nmeth.4606

30.  Kern AD, Schrider DR. Discoal: Flexible Coalescent Simulations With Selection.
Bioinformatics. 2016;32: 3839–3841. doi:10.1093/bioinformatics/btw556

31.  Grossman SR, Shylakhter I, Karlsson EK, Byrne EH, Morales S, Frieden G, et al. A
Composite of Multiple Signals Distinguishes Causal Variants in Regions of Positive
Selection. Science (80- ). 2010;327: 883–886. doi:10.1126/science.1183863

32.  Schrider DR, Kern AD. Soft sweeps are the dominant mode of adaptation in the
human genome. Mol Biol Evol. 2017;34: 1863–1877. doi:10.1093/molbev/msx154

33.  Sellis D, Callahan BJ, Petrov DA, Messer PW. Heterozygote advantage as a natural
consequence of adaptation in diploids. Proc Natl Acad Sci. 2011;108: 20666–20671.
doi:10.1073/pnas.1114573108

34.  Ralph PL, Coop G. Parallel Adaptation: One or Many Waves of Advance of an
Advantageous Allele? Genetics. 2010;186: 647–668.
doi:10.1534/genetics.110.119594

35.  Pritchard JK, Pickrell JK, Coop G. The Genetics of Human Adaptation: Hard Sweeps,
Soft Sweeps, and Polygenic Adaptation. Curr Biol. Elsevier Ltd; 2010;20: R208–R215.
doi:10.1016/j.cub.2009.11.055

36.  Booker TR, Jackson BC, Keightley PD. Detecting positive selection in the genome.
BMC Biol. BMC Biology; 2017;15: 98. doi:10.1186/s12915-017-0434-y

37.  Connallon T, Clark AG. Antagonistic versus nonantagonistic models of balancing
selection: Characterizing the relative timescales and hitchhiking effects of partial
selective sweeps. Evolution (N Y). 2013;67: 908–917. doi:10.1111/j.1558-
5646.2012.01800.x

38.  Smith ML, Ruffley M, Espíndola A, Tank DC, Sullivan J, Carstens BC. Demographic
Model Selection using Random Forests and the Site Frequency Spectrum. Mol Ecol.
2017; doi:10.1111/mec.14223

39.  Pudlo P, Marin J-M, Estoup A, Cornuet J-M, Gauthier M, Robert CP. Reliable ABC
model choice via random forests. Bioinformatics. 2016;32: 859–866.
doi:10.1093/bioinformatics/btv684

40.  Xue AT, Hickerson MJ. Multi-DICE⍰: R package for comparative population genomic

inference under hierarchical co-demographic models of independent single-
population size changes. Mol Ecol Resour. 2017; doi:10.1111/1755-0998.12686

41.    Schrider DR, Ayroles J, Matute DR, Kern AD. Supervised machine learning reveals
introgressed loci in the genomes of Drosophila simulans and D. sechellia. PLOS Genet.
2018;14: e1007341. doi:10.1371/journal.pgen.1007341

42.    Lin K, Futschik A, Li H. A fast estimate for the population recombination rate based
on regression. Genetics. 2013;194: 473–484. doi:10.1534/genetics.113.150201

43.    Adrian AB, Corchado JC, Comeron JM. Predictive models of recombination rate
variation across the drosophila melanogaster genome. Genome Biol Evol. 2016;8:
2597–2612. doi:10.1093/gbe/evw181

44.    Gao F, Ming C, Hu W, Li H. New Software for the Fast Estimation of Population
Recombination Rates (FastEPRR) in the Genomic Era. G3 Genes, Genomes, Genet.
2016;6: 1563–1571. doi:10.1534/g3.116.028233

45.    Chan J, Perrone V, Spence JP, Jenkins PA, Mathieson S, Song YS. A Likelihood-Free
Inference Framework for Population Genetic Data using Exchangeable Neural
Networks. bioRxiv. 2018; 1802.06153. doi:10.1101/267211

46.    Flagel L, Brandvain Y, Schrider DR. The Unreasonable Effectiveness of Convolutional
Neural Networks in Population Genetic Inference. bioRxiv. 2018; 336073.
doi:10.1101/336073

47.    Adrion JR, Galloway JG, Kern AD. Predicting the landscape of recombination using
deep learning. Mol Biol Evol. 2020; doi:10.1093/molbev/msaa038

48.    Zhou J, Troyanskaya OG. Predicting effects of noncoding variants with deep learning-
based sequence model. Nat Methods. 2015;12: 931–934. doi:10.1038/nmeth.3547

49.    Battey CJ, Ralph PL, Kern AD. Predicting Geographic Location From Genetic Variation
with Deep Neural Networks. bioRxiv. 2019; 2019.12.11.872051.
doi:10.1101/2019.12.11.872051

50.    Suvorov A, Hochuli J, Schrider DR. Accurate Inference of Tree Topologies from
Multiple Sequence Alignments Using Deep Learning. Syst Biol. 2020;69: 221–233.
doi:10.1093/sysbio/syz060

51.    Liu X, Fu Y-X. Exploring population size changes using SNP frequency spectra. Nat
Genet. 2015;47: 555–559. doi:10.1038/ng.3254

52.    Tajima F. Evolutionary relationship of DNA sequences in finite populations. Genetics.
1983;105: 437–460.

53.    Watterson GA. On the number of segregating sites in genetical models without
recombination. Theor Popul Biol. 1975;7: 256–276. doi:10.1016/0040-
5809(75)90020-9

54.    Garud NR, Messer PW, Buzbas EO, Petrov DA. Recent Selective Sweeps in North
965           American Drosophila melanogaster Show Signatures of Soft Sweeps. PLoS Genet.
966           2015;11: e1005004. doi:10.1371/journal.pgen.1005004

967    55.    Kelly JK. A test of neutrality based on interlocus associations. Genetics. 1997;146:
968           1197–1206.

969    56.    Chollet F. Keras [Internet]. 2015. Available: https://keras.io

970    57.    Kingma DP, Ba JL. Adam: A Method for Stochastic Optimization. arXiv. 2014;
971           1412.6980. doi:http://doi.acm.org.ezproxy.lib.ucf.edu/10.1145/1830483.1830503

972    58.    Pedregosa F, Varoquaux G, Gramfort A, Michel V, Thirion B, Grisel O, et al. Scikit-
973           learn: Machine Learning in Python. J Mach Learn Res. 2011;12: 2825–2830.
974           doi:10.1007/s13398-014-0173-7.2

# Figure Captions

**Figure 1. CNN architecture of neural network layers.** Our *partialS/HIC* classifier utilizes
a convolutional neural network whereby the input feature vector image, composed of 89
summary statistics organized into rows and across 11 contiguous genomic sub-windows
organized into columns, is passed to a 2D convolutional layer with 256 filters using a 3×6
receptive field. Next is a 2D max pooling layer given a 3×3 receptive field. Then there is a
second 2D convolutional layer of 256 filters based also on a 3×3 receptive field and ReLU
activation. Afterward is a second 2D max pooling layer with a 3×1 receptive field. The
tensor is then flattened after a dropout layer (p=0.25) and passed to two fully-connected
layers with ReLU activation, resulting in 512 and 128 nodes with subsequent dropout
(p=0.50) respectively. Finally, a softmax activation layer classifies the 9 responses.

**Figure 2. Confusion matrix heatmap of *partialS/HIC* simulation experiment.** Given the
BFS population history. Each row designates a true simulation class, which for linked
sweeps is differentiated by distance in genomic sub-windows to the target selective sweep.
In total, there are 45 simulated scenarios shown, including 11 for each sweep type (*i.e.* one
case whereby the sweep is within the central sub-window, and 10 whereby a linked sweep
is located within one of the flanking sub-windows) and neutrality. Each column indicates
one of nine inferred states, with the linked simulation classes collapsed into a single
category per selective sweep type for training and classification, allowing *partialS/HIC* to
learn to distinguish between sweeps located in the focal sub-window and those somewhere
nearby. Darker blue cells represent a higher proportion of the 1,000 calls for each true
class. Importantly, there is generally high accuracy in discriminating between sweeps
within the focal sub-window versus linked sub-windows, especially when linkage is beyond
one sub-window away and particularly for completed sweeps. However, discovering partial
soft sweeps is noticeably a challenging task. Moreover, there is greater sensitivity
separating full completion from partial completion for hard sweeps in contrast to soft
sweeps.

**Figure 3. Confusion matrix heatmap of simulation experiment with partial sweeps**
**ignored during training.** Given the BFS population history. Structured in the same

manner as Figure 2, each row designates a true simulation class and darker blue cells
represent a higher proportion of the 1,000 calls for each true class. In contrast to Figure 2
though, each column indicates one of five inferred states instead of nine, as the two partial
sweep and two linked partial sweep classification states were omitted from training to
determine misclassification bias when partial sweeps are ignored. There is a substantial
decrease in discovery of partial sweeps, especially partial hard sweeps (20.5% total sweep
discovery compared to 78.2% in Figure 2; 46.3% total sweep discovery of partial soft
sweeps compared to 62.3% in Figure 2). Specifically for partial hard sweeps, a large
proportion of the detected sweeps are misclassified as soft sweeps instead of hard sweeps
(19.0%; *i.e.* 3.9% of calls = soft sweeps : 16.6% of calls = hard sweeps).

**Figure 4. ROC curves for binary classification of selective sweeps, including partial**
**sweeps, versus regions neutrally evolving or under linked selection.** Given the BFS
population history. The *partialS/HIC* deep learning classifier outcompetes two other
approaches for managing the same suite of summary statistics: Composite of Multiple
Signals and principal component analysis. Furthermore, *partialS/HIC* excels in performance
over several sub-window derivatives of two summary statistics, SAFE and *iHS*, which were
all included within our set of summary statistics used for training. Notably, Composite of
Multiple Signals, SAFE, and *iHS* were all designed to uncover selective sweeps. Additionally,
the SAFE score is itself a compound statistic that captures signal from several constituent
statistics, and the majority of our training data is derived from either the SAFE score or one
of its components.

**Figure 5. Genome-wide *partialS/HIC* sweep calls across empirical mosquito**
**population datasets.** For all eight datasets, there is a minimal number of calls for
completed hard sweeps, represented here on the Y-axis as the relative proportion to the
total set of empirical calls across every genomic window per population dataset. However,
there is indeed a substantial proportion of sweep calls for hard sweeps, yet are incomplete
or in-progress. In most cases, the number of both completed and partial soft sweeps further
exceeds that of partial hard sweeps. Furthermore, the majority of sweeps have not reach
fixation across these *Anopheles* populations.

**Figure 6. Enrichments of *partialS/HIC* empirical selective sweep calls within DNA regions.** For the BFS population empirical dataset. Statistically significant ($p < 0.05$) enrichments in green. No enrichment (*i.e.* single-fold enrichment based on the permuted calls) is represented by the dotted line. Completed soft sweeps are enriched within all six DNA regions that experienced permutation tests. Similarly, all of the DNA regions have an enrichment of partial sweeps, hard and/or soft. In contrast, there is no significant enrichment of completed hard sweeps for any of the DNA regions. Overall though, selective sweeps in general are enriched for each of the DNA regions.

**Figure 7. Enrichments of *partialS/HIC* empirical selective sweep calls within groupings of insecticide resistance genes.** For the BFS population empirical dataset. Statistically significant ($p < 0.05$) enrichments in green. No enrichment (*i.e.* single-fold enrichment based on the permuted calls) is represented by the dotted line. Rows without a plotted point are due to the insecticide resistance gene group not having any calls of that sweep type (*e.g.* there are no completed hard sweeps called within target site genes). In this mosquito population, there is evidence for several mechanisms through which insecticide resistance evolved, both in sweep types and categories of genes under selection.

**Figure S1. Flowchart of *partialS/HIC* methodological procedure for training, testing, and empirical application given eight *Anopheles* mosquito population datasets.** Major steps highlighted in green, specifically data simulation, training and testing of CNN classifier, and genome-wide inference of selection state per focal sub-window within a full window of 11 sequential sub-windows. Important data processing details that define genomic sub-windows as well as account for uncertainties within the empirical data from missing sites and polarization are also included. However, we omit our various misclassification experiments, which are ancillary to our primary demonstration of *partialS/HIC* to detect selective sweeps from population genomic datasets while obtaining baseline measures of accuracy. For organizational and conceptual purposes, our protocol is presented here mostly contained within two columns, representing simulated versus empirical data respectively, but the actual order of events oscillates between these two sides of the diagram. In fact, many of the tasks could be accomplished in parallel, though certain actions must occur sequentially. For example, training and testing data were

generated after demographic inference in order to inform parameterization of the
simulations. Moreover, we filtered the empirical data of missing calls and missing
polarization information prior to constructing masking profiles for application to the
simulated data, which invoked an intermediate step hence our usage of a dotted arrow.
Additionally, the CNN first had to be optimized from the training simulations before
conducting empirical analysis.

**Figure S2. Feature vector heatmaps for neutral and four sweep states under each**
**population history.** Heatmaps derived from median values of a single training dataset,
each assuming a different population history. Across populations, feature vectors
demonstrate distinctive characteristics per classification state, especially in the focal sub-
window and for the neutral state in comparison to the four sweep states.

**Figure S3. Training and validation loss over samples and epochs during *partialS/HIC***
**CNN optimization under each population history.** Black circles represent loss function
outputs from training for every 32 samples out of a total 16,200 samples per each of 20
epochs. Green asterisks indicate loss function outputs from the validation set at the
conclusion of epochs. The degree to which training loss is less than validation loss likely
reflects the magnitude of overfitting the CNN to the training data.

**Figure S4. Confusion matrix heatmaps of *partialS/HIC* simulation experiment under**
**each population history.** Extension of Figure 2 for all eight population histories.
Importantly, the patterns highlighted in Figure 2, which displays the confusion matrix
given the BFS population history and is reproduced identically here, are largely present
throughout the other confusion matrices.

**Figure S5. Confusion matrix heatmap of *partialS/HIC* demographic misspecification**
**test.** Training on simulations given the GAS population history while testing on simulations
given the CMS population history. Importantly, the patterns highlighted in Figures 2 and S4
are largely retained here, though there is a modest decrease in soft sweep discovery for
both completed and partial.

**Figure S6. Overall *partialS/HIC* accuracies between testing datasets generated with varying demographic misspecification given training on the BFS population history.** The CNN trained on the simulations assuming the BFS population history was separately applied against five testing datasets that were produced under a simple two-epoch instantaneous population crash model, with each dataset differing only in relative magnitude of the size change. The overall accuracy from the original testing dataset whereby the demography was accurately specified on the BFS population history is marked by the green dotted line at 67.76%. The final population size ranges from 5% (*i.e.* 20×) to 1% (*i.e.* 100×) of the original size, with increased accuracy for more severe contractions (*i.e.* 45.98% accuracy for reduction to 5.00% of original size; 55.27% for reduction to 2.50%; 59.46% for reduction to 1.67%; 61.99% for reduction to 1.25%; and 63.50% for reduction to 1.00%). Notably, the greater error at lower magnitudes could be largely due to the decrease in simulated polymorphisms (Figure S7).

**Figure S7. Overall *partialS/HIC* accuracies between testing datasets generated with varying $\theta$ values given training on the BFS population history.** The CNN trained on the simulations assuming the BFS population history was separately applied against six testing datasets that were produced under identical conditions as the training data except differing in fixed $\theta$ values. The overall accuracy from the original testing dataset whereby $\theta$ was drawn from a prior distribution is marked by the green dotted line at 67.76%. Across values of 1,000, 5,000, 10,000, 15,000, 20,000, and 25,000, which collectively is inclusive of and exceeds the original prior distribution ($\theta \sim U(1,750.204699,\ 17,502.046985)$), there is comparable accuracy to the original (50.99%, 67.78%, 70.36%, 70.74%, 70.72%, and 70.74% respectively). In fact, accuracy exceeded the original for all tested $\theta$ values except $\theta$ = 1,000.

**Figure S8. Confusion matrix heatmaps of simulation experiment with partial sweeps ignored during training under each population history.** Extension of Figure 3 for all eight population histories. Importantly, the patterns highlighted in Figure 3, which displays the confusion matrix given the BFS population history and is reproduced identically here, are largely present throughout the other confusion matrices.

**Figure S9. ROC curves for binary classification of selective sweeps, including partial**
**sweeps, versus regions neutrally evolving or under linked selection for each**
**population history.** Extension of Figure 4 for all eight population histories. Importantly,
the patterns highlighted in Figure 4, which displays the ROC curves given the BFS
population history and is reproduced identically here, are largely present throughout the
other plots of ROC curves.

**Figure S10. Enrichments of *partialS/HIC* empirical selective sweep calls within DNA**
**regions for each empirical mosquito population dataset.** Extension of Figure 6 for all
eight empirical population datasets. Importantly, the patterns highlighted in Figure 6,
which displays the dot chart for the BFS permutation test and is reproduced here with a
wider X-axis to match the other plots, are largely present throughout the other dot charts,
though partial sweep enrichment is highly variable.

**Figure S11. Enrichments of *partialS/HIC* empirical selective sweep calls within**
**groupings of insecticide resistance genes for each empirical mosquito population**
**dataset.** Extension of Figure 7 for all eight empirical population datasets. Importantly, as in
Figure 7, which displays the dot chart for the BFS permutation test and is reproduced
identically here, there is evidence for several mechanisms through which insecticide
resistance evolved, both in sweep types and categories of genes under selection as well as
both within individual populations and between different populations.