Machine Source Localization of *Tursiops truncatus* Whistle-like Sounds in a Reverberant Aquatic Environment

SF Woodward[1]*, D Reiss[2], MO Magnasco[1]

1 Laboratory of Integrative Neuroscience, Center for Studies in Physics and Biology, The Rockefeller University, New York, NY, United States
2 Department of Psychology, Hunter College, City University of New York, New York, NY, United States

* sf.woodward@gmail.com

Abstract

Most research into bottlenose dolphins' (*Tursiops truncatus'*) capacity for communication has centered on tonal calls termed *whistles*, in particular individually distinctive contact calls referred to as *signature whistles*. While "non-signature" whistles exist, and may be important components of bottlenose dolphins' communicative repertoire, they have not been studied extensively. This is in part due to the difficulty of attributing whistles to specific individuals, a challenge that has limited the study of not only non-signature whistles but the study of general acoustic exchanges among socializing dolphins. In this paper, we propose the first machine-learning-based approach to identifying the source locations of tonal, whistle-like sounds in a highly reverberant space, specifically a half-cylindrical dolphin pool. We deliver time-of-flight and normalized cross-correlation measurements to a random forest model for high-feature-volume classification and feature selection, and subsequently deliver the selected features into linear discriminant analysis, linear and quadratic Support Vector Machine (SVM), and Gaussian process models. In our 14-point setup, we achieve perfect classification accuracy and high (0.981 ± 0.802 m) regression accuracy with fewer than 10,000 features, suggesting an upgrade in accuracy and computational efficiency to the whole-pool-sampling SRP-PHAT method that is the only competitive alternative at present, apart from tag-based methods.

Author summary

The common bottlenose dolphin (*Tursiops truncatus*) has attracted attention as a distinctly nonhuman, yet intelligent and social species that may be capable of complex communication. Despite the great interest in probing the "vocal" interactions of socializing dolphins to evaluate this possibility, a prerequisite to any rigorous attempt is the matching of vocalizations with their corresponding vocalizers. At present, no reliable method exists for consistently performing this matching, particularly over long periods of time and with complete information about the physical condition of all vocalizers. In this study, we propose the first machine learning-based method for accomplishing sound localization – the primary step of sound attribution – of dolphin-like vocalizations in a dolphin pool. On our sample data, this method proves extremely accurate within the body length of a dolphin, and is suggestive of greater practical reliability than other available methods.

Introduction

Dolphin communication research is in an active period of growth. Many researchers expect to find significant communicative capacity in dolphins given their complex social structure [1–3], advanced cognition including the capacity for mirror self-recognition [4], culturally transmitted tool-use and other behaviors [5], varied and adaptive foraging strategies [6], and their capacity for metacognition [7]. Moreover, given dolphins' well-studied acoustic sensitivity and echolocation ability [8–10], some researchers have speculated that dolphin vocal communication might share properties with human languages [11–13]. However, there is an insufficiency of work in this area to make significant comparisons.

Among most dolphin species, a particular tonal class of call, termed the *whistle*, has been identified as socially important. In particular, for the common bottlenose dolphin, *Tursiops truncatus* – arguably the focal species of most dolphin cognitive and communication research – research has focused on *signature whistles*, individually distinctive whistles [14–16] that may convey an individual's identity to conspecifics [15, 17] and that can be mimicked, potentially to gain conspecifics' attention [18].

Signature whistle studies aside, most studies of bottlenose dolphin calls concern group-wide repertoires of whistles and other, pulse-form call types [19–23]; there is only a paucity of studies that seek to examine individual repertoires of non-signature whistles or the phenomenon of non-signature acoustic exchanges among dolphins. Regarding the latter, difficulties with sound attribution at best allow for sparse sampling of exchanges [17, 24]. Nevertheless, such studies constitute a logical prerequisite to an understanding of the communicative potential of whistles.

The scarcity of such studies can be explained in part by a methodological limitation in the way in which dolphin sounds are recorded. In particular, no established method exists for recording the whistles of an entire social group of dolphins so as to reliably attribute the signals to specific dolphins. The general problem of sound attribution, which is encountered in almost every area of communication research, is typically approached in one of two ways: (1) by attaching transducers to all potential sound sources, in which case the source identities of sounds can usually be obtained by discarding all but the highest-amplitude sounds in each source-distinctive recorder, or (2), by using a fixed array (or arrays) of transducers, a physics-based algorithm for identifying the physical origin of each sound, and cameras that monitor the physical locations of all potential sources for matching.

While notable progress has been made implementing attached transducers (or tags) to identify the sources of dolphin whistles [25–27], shortfalls include the need to manually tag every member of the group under consideration, the tendency of tags to fall off, and the tags' inherent lack of convenient means for visualizing caller behavior. On the other hand, a consistently reliable implementation of the array/camera approach to dolphin whistles has not been achieved, even if it has been achieved for dolphin clicks [28]. In the context of whistles in reverberant environments, authors have noted the complications introduced by multipath effects – resulting from the combination of sounds received from both the sound source and acoustically reflective boundaries – to standard signal processing techniques. These complications generally arise from the overlap of original and reflected sounds that confound standard, whole-signal methods of obtaining time-of-flight differences. Standard techniques have at best obtained modest results in relatively irregular, low-reverberation environments where they have been evaluated [29–32]. In unpublished work, we have achieved similar results. One method of improving a standard signal processing tool for reverberant conditions, the cross-correlation, has been proposed without rigorous demonstration and has not be reproduced [33]. Among all the methods attempted, one, termed Steer Response Power

Phase Transform (SRP-PHAT), has achieved more success than others (about 40% recall of caller identity), however it relies on a computationally exhausting sampling of all space and has not yet been tested in highly reverberant space [34].

We propose the first machine-learning-based solution to the problem of localizing whistle-like sounds in a highly reverberant environment, a half-cylindrical concrete dolphin pool, located at the National Aquarium in Baltimore, Maryland. We apply it to a broad variety of artificial tonal whistle-like sounds that vary over a range of values within a universally recognized parameter space for classifying dolphin sounds, for a limited number of sampling points. We begin with a random forest classification model and eventually find that a linear classification model that achieves similar results, as well as a regression model that achieves dolphin-length accuracy. The latter two models rely on tight feature sets containing less than 10,000 features to locate a single whistle, and even with preprocessing avoid the computational burden of the full-space cross-correlation sampling required by SRP-PHAT.

Materials and methods

Sample Set

All data were obtained from equipment deployed at the Dolphin Discovery exhibit of the National Aquarium in Baltimore, Maryland. The exhibit's 110-ft-diameter cylindrical pool is subdivided into one approximate half cylinder, termed the *exhibit pool* (*EP*), as well three smaller holding pools, by thick concrete walls and 6 ft x 4.25 ft (1.83 m x 1.30 m) perforated wooden gates; all pools are acoustically linked. The data were obtained from the EP, when the seven resident dolphins were in the holding pools; their natural sounds were present in recordings.

To ensure that the sound samples used for classification were not previously distorted by multipath phenomena (i.e., were not pre-recorded), were obtained in sufficient quantity at several precise, known locations inside the EP, and were representative of the approximate "whistle space" for *Tursiops truncatus*, we chose to use computer-generated whistle-like sounds that would be played over an underwater Lubbell LL916H speaker.

We generated 128 unique sounds (with analysis done on 127) to fill the available time. To be acoustically similar to actual *T. truncatus* whistles, these sounds were to be "tonal" – describable as smooth functions in time-frequency space, excluding harmonics – and to be defined by parameters and parameter ranges, given in Table 1, representative of those used by field researchers to classify dolphin whistles [35, 36]. To construct a waveform to be played, we began with an instantaneous frequency, $f(t)$, that described a goal time-frequency (or spectrographic) trace, for instance the trace shown in Fig 1. For simplicity, and consistent with the parameters typically used to describe dolphin whistles, we approximated dolphin whistles as sinusoidal traces in spectrographic space – thus $f(t)$ was always a sinusoid. Based on the standard definition of the instantaneous frequency as $f(t) = \frac{1}{2\pi}\frac{d\Phi(t)}{dt}$, we obtained the phase $\Phi(t)$ by integration of $f(t)$ with respect to time. The phase could be straightforwardly transformed into a playable waveform $y(t)$ as $y(t) = A(t)sin(\Phi(t))$, where $A(t)$ represented a piecewise function that modulated the strength of the signal at different times (the beginning and end of a signal were gradually increased to full intensity and decreased to zero, respectively, as functions of the "Power Onset/Decay Rate," and the absolute beginning occurred at a peak or trough of the sinusoid $f(t)$ according to "Phase Start"). Alternatively, the phase could be transformed with a heuristic into a waveform that generates a modification of the trace $f(t)$ in spectrographic space, a quasi-sinusoid with "sharpened" peaks and approximate whistle-harmonic-like traces on top of the original trace. This heuristic is

Table 1. Parameters of training set sinusoids.

Parameter	Value Set
Duration (sec)	[0.3, 1]
Number of Cycles	[1, 2]
Center Frequency (Hz)	[6000, 10500]
Cycle Amplitude (Hz)	[2000, 5000]
Phase Start (rad)	$[-\frac{\pi}{2}, \frac{\pi}{2}]$
Power Onset/Decay Rate *	[0.1, 0.25]

* Values indicate fraction of signal length over which a sin^2 rise/falls occurs.

$y(t) = A(t)\frac{arcsin(m \cdot sin(\Phi(t)))}{arcsin(\Phi(t))}$, where m is a parameter that simultaneously affects the "sharpness" of the peaks and the number of harmonics; we used a value of 0.8.

Waveforms were played in Matlab through a MOTU 8M audio interface at calibrated volumes and a rate of 192 kHz. An example of such a sound is given in Fig 1.

Fig 1. Spectrogram of an artificial whistle. Displayed is a standard, 1024-bin, Hamming-window spectrogram of one of the 128 whistle-like sounds that were generated (and here sampled) at 192 kHz; frequency resolution of the plot is 187.5 Hz. Note that the spectrogram was constructed from the original, source signal. In this case, Duration = 1 second, Number of Cycles = 2, Center Frequency = 6000 Hertz, Cycle Amplitude = 2000 Hertz, Phase Start = -π/2.

The 128 sounds were played at each of 14 locations within the EP; they corresponded to 7 unique positions on the water surface on a 3 x 5 cross, at 6 ft (1.83 m) and 18 ft (5.49 m) deep. Approximate surface positions are shown in Fig 2; the difference between adjacent horizontal and vertical positions was 10-15 ft (3.05-4.57 m). The LL916H speaker was suspended by rope from a custom flotation device and moved

across the pool surface by four additional ropes extending from the device to research assistants standing on ladders poolside. Importantly, the speaker was permitted to sway from its center point by as much as a meter in arbitrary direction during calibration. These assistants also used handheld Bosch 225 ft (68.58 m) Laser Measure devices to determine the device's distance from their reference points (several measurements were taken for each location), and through a least-squares trilateration procedure [38] the device location could always be placed on a Cartesian coordinate system common with the hydrophones. Each sound in a 128-sound run was played after a 2-second delay as well as after a 0.25-second, 2-kHz tone, that allowed for the creation of a second set of time-stamps in order to compensate for clock drift during the automated signal extraction.

Fig 2. Pool test point and hydrophone array layout. The National Aquarium Exhibit Pool (EP) is shown, as visualized by the overhead AXIS P1435-LE camera. Circled in red are the approximate surface projections of the fourteen points (each of the seven points represents a pair) at which sounds were played. Circled in yellow are the four hydrophone arrays, each containing four hydrophones.

Recording System

Acoustic and visual data was obtained from a custom audiovisual system consisting of 16 hydrophones (SQ-26-08's from Cetacean Research Technology, with approximately flat frequency responses between 200 and 25,000 Hz) split among 4 semi-permanent, tamper-resistant arrays and 5 overhead cameras – for the purpose of this study, only one central AXIS P1435-LE camera, managed by Xeoma surveillance software, was used. The four arrays were spaced approximately equally around the half-circle boundary of the EP (a "splay" configuration). The physical coordinates of all individual hydrophones were obtained by making underwater tape-measure measurements as well as above-water laser-rangefinder measurements; various calibrations were performed that are outside the scope of the present paper. During this test, sounds were collected at 192 kHz by two networked MOTU 8M into the Audacity AUP sound format, to avoid the size limitations of standard audio formats – this system was also used for playing the sounds. Standard passive system operation was managed by Matlab scripts recording to successive WAV files; for consistency Matlab was also used for most data management

and handling. Data is available at `https://doi.org/10.6084/m9.figshare.7956212`. 137

Classification and Regression 138

1,605 recorded tones were successfully extracted to individual 2-second-long, 16-channel 139
WAV's that were approximately but not precisely aligned in time. Each tone was 140
labeled with a number designating at which of 14 pool locations it was played. A 141
random 10% of sounds were set aside for final testing, with sinusoids and quasi-sinusoids 142
with the same parameters grouped together given their extreme similarity. 143

Each sound was initially digested into 1,333,877 continuous, numerical features (or 144
variables), together composing the so-called feature set. 145

The first 120 features were *time-difference-of-arrivals* (TDOA's) obtained using the 146
Generalized Cross-Correlation Phase Transform (GCC-PHAT) method [39], which in 147
currently unpublished work we found to be most successful among correlation-based 148
methods for obtaining whistle TDOA's. Briefly, a TDOA is the time difference between 149
the appearance of a signal (such as a whistle) in one sensor (such as a hydrophone) 150
versus another. Possession of a signal's TDOA's for all pairs of 4 sensors (with known 151
geometry) in 3-dimensional space is theoretically, but often not practically, sufficient to 152
calculate the exact source position of that signal from geometry [40]. While we establish 153
elsewhere that the 120 TDOA's (i.e., one TDOA for each distinct pair of our 16 154
hydrophones, excluding self-pairs) obtained from GCC-PHAT are practically not 155
sufficient to calculate the exact source position of our signals using a standard 156
geometric technique that accommodates more than four sensors, Spherical 157
Interpolation [41, 42], we suspected that these TDOA's might still contain information 158
helpful to a machine learning model. 159

The next 6601 x 136 features consisted of elements from standard, normalized 160
circular cross-correlations [43]: for each unique pair of the 16 hydrophones (including 161
self-pairs), 136 in total, we computed the standard circular cross-correlation of a 162
whistle's two corresponding audio snippets. While each correlation series was initially 163
384,000 elements long (192,000 samples/second x 2 seconds), we only kept the central 164
6601 elements from each, corresponding to a time-shift range of approximately ± 17 165
milliseconds; based on geometry, the first incidence of any sound originating from inside 166
the pool must have arrived within 17 milliseconds between any two sensors (very 167
conservatively), meaning cross-correlation elements corresponding to greater delays 168
could be expected to be less helpful to in-pool source location prediction. 169

Lastly, we included 27,126 x 16 discrete Fourier transform elements (one set for each 170
of 16 hydrophones, for frequencies from 0 Hz to 27,126 Hz). However, preliminary 171
analysis found these features to be universally unhelpful to classification. Thus, they 172
were discarded from the feature set, leaving 897,871 features. 173

Possessing the above feature set for each whistle, each "labeled" by the whistle 174
source location and coordinates, we constructed predictive models on the 90% of 175
whistles made available for model construction (or training). We began with multiclass 176
classification [44], training models to predict which of the 14 possible locations a novel 177
whistle originated from. Given our limited computational resources, our feature set 178
remained too large to accommodate most classifiers. A notable exception was the 179
Breiman random forest [45, 46], which was suitable not only for classification – being a 180
powerful nonlinear multiclass classifier with built-in resistance to overfitting – but for 181
feature reduction (i.e., the process of shrinking feature set size while minimizing loss of 182
classification accuracy), via the permuted variable delta error metric. The permuted 183
variable delta error roughly describes the increase in classification error when a 184
particular feature is effectively randomized, providing a measure of that feature's 185
importance in classification. We grew a Breiman random forest composed of CART 186
decision trees [47] on the training data; each tree was sequentially trained on a random 187

subset of ~75% of the training samples using a random ~$\sqrt{897,871}$ feature subset (as per standard practice). Out-of-bag (OOB) error, referring to the classification error on samples not randomly chosen for the training subset, was used for validation. While an introduction to machine learning is beyond the scope of this paper, these and subsequent techniques are standard with reader-friendly documentation available at such sources as MathWorks (`https://www.mathworks.com`) and sciikit-learn (`https://scikit-learn.org/stable/`), to which we direct interested readers.

We subsequently used permuted variable delta error as a measure of feature importance, both to examine the selected features for physical significance – recall that cross-correlation element features correspond to pairs of sensors – and to obtain a reduced feature set appropriate for training additional models. On the reduced feature set, we considered a basic CART decision tree [44, 47], a linear and quadratic Support Vector Machine (SVM) [44, 48], and linear discriminant analysis [49]. We also considered Gaussian process regression (also termed *kriging*) [50, 51] – a nontraditional, nonparametric method of regression that could accommodate our under-constrained data. Whereas the goal of our classification models was to predict which of 14 possible points from which a sound originated, the goal of our regression models was to predict the 3-dimensional coordinates from which the sound originated.

We then assessed our ability to locate sounds not originating on the training/testing grid using Gaussian process models. We trained models on training data exclusive of a single grid point, and then evaluated the regression's performance predicting the coordinates of test sounds from that point. We repeated this process for all grid points and generated statistics.

Lastly, we obtained a minimal, nearly sufficient feature set by training a single, sparse-feature (or parsimonious) decision tree classifier on all features of all training data. We then investigated these minimal features for physical significance, by mapping features' importance (again, using a random forest's permuted variable delta error) back to the sensor and array pairs from which they derived.

Results

The random forest trained on the full feature set, as specified above, reached 100.0% OOB accuracy at a size of approximately 180 trees. We continued training to 300 trees, and evaluated the resulting model on the test set: 100.0% accuracy was achieved, with 6,788 features possessing permuted variable delta error greater than 0 (based on OOB evaluations). Note that, given the stochastic construction of the random forest, these features did not represent a unique set or superset of sufficient features for obtaining 100.0% test accuracy. When we considered which array pairs the 6,778 TDOA and cross-correlation features represented, we found that all pairs of the four hydrophone arrays were represented with no significant preference.

We trained several more models on the reduced feature set, including a basic decision tree, a linear and quadratic SVM, and linear discriminant analysis, using 10-fold cross-validation. The quadratic SVM as well as linear discriminant analysis achieved 100.0% cross-validation and 100.0% test accuracy, the basic decision tree achieved 96.9% cross-validation and 97.75% test accuracy, and the linear SVM achieved 100.0% cross-validation accuracy and 99.44% test accuracy.

On the reduced feature set we also performed Gaussian process regression (kriging), generating one model for each spatial dimension. The predicted locations of testing samples for a subset of test locations are plotted in Fig 3. The calculated Euclidean (straight-line) error was 0.981 ± 0.802 m; in the "EP Rear" direction the error was 0.305 ± 0.375 m, in the "EP Wall" direction the error was 0.781 ± 0.640 m, and in the "EP Side" direction the error was 0.347 ± 0.574. Comparing the "EP Rear" and "EP Wall"

sets of errors using a two-sided Wilcoxon rank sum test (a non-parametric equivalent of the t-test), the p-value for rejection of the null hypothesis that samples are drawn from distributions with equal medians was 2.02×10^{-11}; between "EP Wall" and "EP Side," the p-value was 7.89×10^{-13}; between "EP Rear" and "EP Side," the p-value was 0.0876. Although standard deviations are indicated above to give the reader some concept of the data spread, we warn the reader that these distributions are not strictly normal according to Anderson-Darling testing.

Fig 3. Predictions of test sound locations by Gaussian process regressors.
The half-cylindrical National Aquarium EP is depicted. Large unfilled circles indicate the true coordinates of the test sounds; each has a unique color. Small filled circles indicate the test sound coordinates predicted by Gaussian process regression, colors matching their respective true coordinates.

When the Gaussian process regression models were prompted to predict the coordinates of test sounds from single grid points from which they received no training data, the Euclidean error was significantly greater, at 3.27 ± 0.747 m. In the "EP Rear" direction the error was 0.747 ± 0.689 m, in "EP Wall" direction the error was 2.73 ± 0.937 m, and in the "EP Side" direction the error was 0.948 ± 1.01 m. Comparing the "EP Rear" and "EP Wall" sets of errors using a two-sided Wilcoxon rank sum test, the p-value for rejection of the null hypothesis that samples are drawn from distributions with equal medians was 1.10×10^{-48}; between "EP Wall" and "EP Side," the p-value was 1.85×10^{-36}; between "EP Rear" and "EP Side," the p-value was 0.949. Again, we warn the reader that these distributions are not strictly normal.

Next, we trained a single, sparse-feature decision tree on the full training set. The severe feature reduction left 22 features. While the decision tree achieved only 96.63% accuracy on the test set, a random forest trained on the same features achieved 98.88% test accuracy. Thus, we considered this feature set both sufficient and sparse enough to meaningfully ask these features tell us about sensor-sensor pairs a classifier might emphasize. The permuted variable delta error was summed across hydrophone and array pairs, visualized in Fig 4. Overall, we note that, directly or indirectly, features representing all pairs of hydrophone arrays are utilized.

Discussion

We provided a proof of concept that sound source localization of bottlenose whistles can be achieved implicitly as a classification task and explicitly as a regression task in a

Fig 4. Minimal Cross-Hydrophone and Cross-Array Feature Importances.
Aggregate feature importance values for a minimal set of 22 features across hydrophone
and hydrophone array pairs are formed by summing the importances (permuted variable
delta error) of features across hydrophone pairs, and subsequently averaging hydrophone
pair sums across array pairs. a: Cross-hydrophone importances for cross-correlation
features. Hydrophones belonging to common panels (1-4, 5-8, 9-12, 13-16) are grouped
by red boxes. b: Cross-array importances for cross-correlation features. Facing the pool
from the panels increase in number from left to right. c: Cross-hydrophone importances
for TDOA features. d: Cross-array importances for TDOA features.

highly reverberant, half-cylindrical aquatic environment. We began with 127 unique
tonal sounds played at 14 positions in the primary dolphin pool at the National
Aquarium, recorded with four four-hydrophone arrays. First, we showed that a random
forest classifier with less than 200 trees can achieve 100% testing accuracy using 6,788
of 897,871 features, including TDOA's obtained from GCC-PHAT and normalized
cross-correlations between all pairs of sensors. We then showed that linear discriminant
analysis and a quadratic SVM can achieve the same results on the reduced feature set.
If the linear model in particular were to remain valid when trained on a finer grid of
training/testing points (finer by about two fold, which would reduce the distance
between grid points to approximately the length of a mature bottlenose dolphin), it
would constitute a simple and computationally efficient method of locating the origin of
tonal sounds in a reverberant environment.

Although it remains unclear to what extent sounds originating off-grid are classified
to the most logical (i.e., nearest) grid points, a concern even for a classifier trained on a
finer grid, we note that our classifiers' success was achieved despite the few-foot drift of
the speaker during play-time; this may indicate a degree of smoothness in the classifiers'
decision-making. Also, that a linear classifier, which by definition cannot support

nonlinear decision making, suffices for this task on features (TDOA's, cross-correlations) that are generally expected to vary continuously in value across space is reassuring. Nevertheless, this question does warrant further investigation, perhaps with deliberately, faster moving sources.

We more suitably addressed the question of off-grid prediction for Gaussian process regression, which was also quite successful when trained on the full training data set, achieving test error of 0.981 ± 0.802 m – less than the expected length of an adult common bottlenose dolphin [52]. Not only is regression inherently suited to interpolation, but it was straightforward to assess regression's performance on test data from grid points excluded during training. While the regression's overall performance on novel points was not satisfactory, admitting error larger than average dolphin length at 3.27 ± 0.747 m, when we decomposed the error into three dimensions (0.747 ± 0.689 m in "EP Rear," 0.948 ± 1.01 m in "EP Side," 2.73 ± 0.937 m in "EP Wall," with the underlying "EP Wall" errors significantly different from the other sets of errors by Wilcoxon rank sum testing), we saw that much of the error originated in the direction of pool depth. This is unsurprising given that all data are evenly distributed between only two depths; we would expect a significant boost to performance by introducing additional depth(s) to the data.

It also remains unclear to what extent sounds outside the training set, specifically real dolphin whistles, are properly assigned. A test of this would require a large set of dolphin whistles played at known locations in the pool, which we do not possess at present. However, even were an evaluation of real dolphin whistles to fail, we note that in general captive dolphins' "vocabularies" tend to be limited – groups seem to possess less than 100 unique types [21] – and that it would be realistic to train classification/regression models with whistles closely resembling group members' sounds, avoiding the need for the model to generalize in whistle type space.

We also showed that an extremely sparse, 22-item feature set that lends itself to relatively strong classification accuracy includes time-of-flight comparisons from all four pairs of arrays. As much sound amplitude information was removed in the process of feature creation, this suggests that the decision tree and random forest implicitly use time-of-arrival information for classification from four maximally spaced sensors, consistent with a naive analytic-geometric approach to sound source localization. However, the inner decision making of the models ultimately remains unclear.

Overall, we feel this study offers a strong demonstration that machine learning methods are suitable to solving the problem of sound-localization for tonal whistles in highly reverberant aquaria. Were the performance of the methods presented here extend to a finer grid – which was not and will not be feasible in our own work at the National Aquarium, as a result of changes to husbandry policy – they would constitute the most accurate methods to sound source localization of dolphin-whistle-like sounds in a highly reverberant environment yet proposed that avoid the need for tagging; currently, successful localization of whistles in similar environments is no greater than 70% [29–32]. Moreover, as these methods do not require the computation of cross-correlations across the whole sample space, we expect these methods to be less computationally expensive than SRP-PHAT, the primary alternative. With a set of four permanent hydrophone arrays surrounding a subject enclosure, automated overhead tracking, and suitable training set, this method may allow for the creation of a high-fidelity record of dolphin exchanges suitable to statistical analysis in many settings.

Acknowledgments

We thank the National Aquarium for participating in this study, as well the National Science Foundation (Awards 1530544, 1607280), the Eric and Wendy Schmidt Fund for

Strategic Innovation, and the Rockefeller University for funding. While regrettably we   333
cannot name everyone, we also thank the approximately two dozen people at the   334
National Aquarium, the Rockefeller University, and Hunter College for assisting with   335
various aspects of the project.   336

References

1. Shirihai H, Jarrett B. Whales, Dolphins, and Other Marine Mammals of the World. Princeton and Oxford: Princeton University Press; 2006.

2. Connor RC, Heithaus MR, Barre LM. Complex social structure, alliance stability and mating access in a bottlenose dolphin 'super-alliance'. Proceedings of the Royal Society B: Biological Sciences. 2001;268(1464):263–267.

3. Krutzen M, Sherwin WB, Connor RC, Barre LM, Van de Casteele T, Mann J, et al. Contrasting relatedness patterns in bottlenose dolphins (Tursiops sp.) with different alliance strategies. Proceedings of the Royal Society B: Biological Sciences. 2003;270(1514):497–502.

4. Reiss D, Marino L. Mirror self-recognition in the bottlenose dolphin: A case of cognitive convergence. Proceedings of the National Academy of Sciences. 2001;98(10):5937–5942.

5. Krutzen M, Mann J, Heithaus MR, Connor RC, Bejder L, Sherwin WB. Cultural transmission of tool use in bottlenose dolphins. Proceedings of the National Academy of Sciences. 2005;102(25):8939–8943.

6. Sargeant BL, Mann J, Berggren P, Krutzen M. Specialization and development of beach hunting, a rare foraging behavior, by wild bottlenose dolphins (Tursiop sp.). Canadian Journal of Zoology. 2005;83(11):1400–1410.

7. Smith JD. Inaugurating the Study of Animal Metacognition. International Journal of Comparative Psychology. 2010;23(3):401–413.

8. Au WWL, Moore PWB, Pawloski D. Echolocation transmitting beam of the Atlantic bottlenose dolphin. The Journal of the Acoustical Society of America. 1986;80:688–691.

9. Johnson CS. Discussion. In: Busnel RG, editor. Animal Sonar Systems Biology and Bionics. Jouy-en-Josas, France; 1967. p. 384–398.

10. Au WWL. Echolocation in Dolphins. In: Hearing by Whales and Dolphins. New York City, New York: Springer; 2000.

11. Lilly JC, Miller AM. Vocal Exchanges between Dolphins. Science. 1961;134(3493):1873–1876.

12. Dreher JJ. Linguistic Considerations of Porpoise Sounds. The Journal of the Acoustical Society of America. 1961;33(12):1799–1800.

13. McCowan B, Hanser SF, Doyle LR. Quantitative tools for comparing animal communication systems: information theory applied to bottlenose dolphin whistle repertoires. Animal Behaviour. 1998;57(2):409–419.

14. Caldwell MC, Caldwell DK. Individualized Whistle Contours in Bottlenosed Dolphins (*Tursiops truncatus*). Nature. 1965;207(1):434–435.

15. Caldwell MC, Caldwell DK, Tyack PL. Review of the signature-whistle-hypothesis for the Atlantic bottlenose dolphin. In: Leatherwood S, Reeves RR, editors. The Bottlenose Dolphin. San Diego; 1990. p. 199–234.

16. Sayigh LS, Esch HC, Wells RS, Janik VM. Facts about signature whistles of bottlenose dolphins, *Tursiops truncatus*. Animal Behaviour. 2007;74(6):1631–1642.

17. Janik VM, Sayigh LS. Communication in bottlenose dolphins: 50 years of signature whistle research. Journal of Comparative Physiology A. 2013;199(6):479–489.

18. Tyack PL. Whistle Repertoires of Two Bottlenosed Dolphins, *Tursiops truncatus*: Mimicry of Signature Whistles? Behavioral Ecology and Sociobiology. 1986;18(4):251–257.

19. McCowan B. A New Quantitative Technique for Categorizing Whistles Using Simulated Signals and Whistles from Captive Bottlenose Dolphins (Delphinidae, *Tursiops truncatus*). Ethology. 1995;100:177–193.

20. McCowan B, Reiss D. Whistle Contour Development in Captive-Born Infant Dolphins (*Tursiops truncatus*): Role of Learning. Journal of Comparative Psychology. 1995;109(3):242–260.

21. McCowan B, Reiss D. Quantitative Comparison of Whistle Repertoires from Captive Adult Bottlenose Dolphins (Delphinidae, *Tursiops truncatus*): a Re-evaluation of the Signature Whistle Hypothesis. Ethology. 1995;100:194–209.

22. McCowan B, Reiss D, Gubbins C. Social familiarity influences whistle acoustic structure in adult female bottlenose dolphins (*Tursiops truncatus*). Aquatic Mammals. 1998;24(1):27–40.

23. McCowan B, Reiss D. The fallacy of 'signature whistles' in bottlenose dolphins: a comparative perspective of 'signature information' in animal vocalizations. Animal Behaviour. 2001;62(6):1151–1162.

24. Janik VM, King SL, Sayigh LS, Wells RS. Identifying signature whistles from recordings of groups of unrestrained bottlenose dolphins (*Tursiops truncatus*). Marine Mammal Science. 2013;29(1):109–122.

25. Tyack PL. An optical telemetry device to identify which dolphin produces a sound. The Journal of the Acoustical Society of America. 1985;78(5):1892–1895.

26. Watwood SL, Owen ECG, Tyack PL, Wells RS. Signature whistle use by temporarily restrained and free-swimming bottlenose dolphins, Tursiops truncatus. Animal Behaviour. 2005;69(6):1373–1386.

27. Akamatsu T, Wang D, Wang K, Naito Y. A method for individual identification of echolocation signals in free-ranging finless porpoises carrying data loggers. The Journal of the Acoustical Society of America. 2000;108(3):1353–5.

28. Watkins WA, Schevill WE. Listening to Hawaiian Spinner Porpoises, *Stenella* Cf. *Longirostris*, with a Three-Dimensional Hydrophone Array. Journal of Mammalogy. 1974;55(2):319–328.

29. Bell BM, Ewart TE. Separating Multipaths by Global Optimization of a Multidimensional Matched Filter. IEEE Transactions on Acoustic, Speech, and Signal Processing. 1986;ASSP-34(5):1029–1036.

30. Freitag LE, Tyack PL. Passive acoustic localization of the Atlantic bottlenose dolphin using whistles and echolocation clicks. The Journal of the Acoustical Society of America. 1993;93(4):2197–2205.

31. Janik VM, Thompson M. A Two-Dimensional Acoustic Localization System for Marine Mammals. Marine Mammal Science. 2000;16(2):437–447.

32. López-Rivas RM, Bazúa-Durán C. Who is whistling? Localizing and identifying phonating dolphins in captivity. Applied Acoustics. 2010;71(11):1057–1062.

33. Spiesberger JL. Linking auto- and cross-correlation functions with correlation equations: Application to estimating the relative travel times and amplitudes of multipath. The Journal of the Acoustical Society of America. 1998;104(1):300–312.

34. Thomas RE, Fristrup KM, Tyack PL. Linking the sounds of dolphins to their locations and behavior using video and multichannel acoustic recordings. The Journal of the Acoustical Society of America. 2002;112(4):1692–1701.

35. Steiner WW. Species-Specific Differences in Pure Tonal Whistle Vocalizations of Five Western North Atlantic Dolphin Species. Behavioral Ecology and Sociobiology. 1981;9(4):241–246.

36. Rendell LE, Matthews JN, Gill A, Gordon JCD, MacDonald DW. Quantitative analysis of tonal calls from five odontocete species, examining interspecific and intraspecific variation. Journal of Zoology, London. 1999;249:403–410.

37. Weisstein EW. type;. Available from: http://mathworld.wolfram.com/TriangleWave.html.

38. Navidi W, Jr WSM, undefined, Hereman W. Statistical methods in surveying by trilateration. Computational Statistics & Data Analysis. 1998;27:209–227.

39. Knapp CH, Carter C. The Generalized Correlation Method for Estimation of Time Delay. IEEE Transactions on Acoustic, Speech, and Signal Processing. 1976;24(4):320–327.

40. Li X, Deng ZD, Rauchenstein LT, Carlson TJ. Source-localization algorithms and applications using time of arrival and time difference of arrival measurements. Review of Scientific Instruments. 2016;87(4):041502–13.

41. Smith JO, Abel JS. The Spherical Interpolation Method of Source Localization. IEEE Journal of Oceanic Engineering. 1987;OE-12(1):246–252.

42. Zimmer WMX. Passive Acoustic Monitoring of Cetaceans. Cambridge: Cambridge University Press; 2011.

43. Oppenheim AV, Schafer RW, Buck JR. Discrete-Time Signal Processing. Upper Saddler River, NJ; 1999.

44. Kotsiantis SB, Zaharakis ID, Pintelas PE. Machine learning: a review of classification and combining techniques. Artificial Intelligence Review. 2006;26:159–190. doi:10.1007/s10462-007-9052-3.

45. Breiman L. Random Forests. Machine Learning. 2001;45(1):5–32.

46. Belgiu M, Drăguţ L. Random forest in remote sensing: A review of applications and future directions. ISPRS Journal of Photogrammetry and Remote Sensing. 2016;114:24–31. doi:10.1016/j.isprsjprs.2016.01.011.

47. Breiman L, Friedman J, Stone CJ, Olshen RA. Classification and Regression Trees. Monterey, CA: Wadsworth & Brooks/Cole Advanced Books & Software; 1984.

48. Cortes C, Vapnik V. Support-vector networks. Machine Learning. 1995;20:273–297. doi:10.1007/bf00994018.

49. Fisher RA. The use of Multiple Measurements in Taxonomic Problems. Annals of Eugenics. 1936;7:179–188. doi:10.1111/j.1469-1809.1936.tb02137.x.

50. Wahba G. Spline Models for Observational Data; 1990.

51. Williams CKI. Prediction with Gaussian Processes: From Linear Regression to Linear Prediction and Beyond. In: Jordan MI, editor. Learning in Graphical Models. NATO ASI Series (Series D: Behavioural and Social Sciences). vol. 89. Springer, Dordrecht; 1998.

52. Fernandez S, Hohn AA. Age, growth, and calving season of bottlenose dolphins, Tursiops truncatus, off coastal Texas. Fishery Bulletin - National Oceanic and Atmospheric Administration. 1998;(96):357–365.