Cortical Sensitivity to Natural Scene Structure

Daniel Kaiser[1,2], Greta Häberle[2,3,4], Radoslaw M. Cichy[2,3,4,5]

[1]Department of Psychology, University of York, York, UK

[2]Department of Education and Psychology, Freie Universität Berlin, Berlin, Germany

[3]Einstein Center for Neurosciences Berlin, Berlin, Germany

[4]Berlin School of Mind and Brain, Humboldt-Universität Berlin, Berlin, Germany

[5]Bernstein Center for Computational Neuroscience Berlin, Berlin, Germany

Correspondence:

Dr. Daniel Kaiser

Department of Psychology

University of York

Heslington, York

YO10 5DD, UK

danielkaiser.net@gmail.com

Abstract

Natural scenes are inherently structured, with meaningful objects appearing in

predictable locations. Human vision is tuned to this structure: When scene structure

is purposefully jumbled, perception is strongly impaired. Here, we tested how such

perceptual effects are reflected in neural sensitivity to scene structure. During

separate fMRI and EEG experiments, participants passively viewed scenes whose

spatial structure (i.e., the position of scene parts) and categorical structure (i.e., the

content of scene parts) could be intact or jumbled. Using multivariate decoding, we

show that spatial (but not categorical) scene structure profoundly impacts on cortical

processing: Scene-selective responses in occipital and parahippocampal cortices

(fMRI) and after 255ms (EEG) accurately differentiated between spatially intact and

jumbled scenes. Importantly, this differentiation was more pronounced for upright

than for inverted scenes, indicating genuine sensitivity to spatial structure rather than

sensitivity to low-level attributes. Our findings suggest that visual scene analysis is

tightly linked to the spatial structure of our natural environments. This link between

cortical processing and scene structure may be crucial for rapidly parsing naturalistic

visual inputs.

Keywords: visual perception, scene representation, spatial structure, fMRI,

EEG, multivariate decoding

45   **Cortical Sensitivity to Natural Scene Structure**

Humans can efficiently extract information from natural scenes even from just

a single glance (Potter, 1975; Thorpe et al., 1996). A major reason for this perceptual

efficiency lies in the structure of natural scenes: for instance, a scene's spatial

structure tells us where specific objects can be found and its categorical structure

tells us which objects are typically encountered within the scene (Kaiser et al., 2019;

Oliva and Torralba, 2007; Võ et al., 2019; Wolfe et al., 2011).

The beneficial impact of scene structure on perception becomes apparent in

jumbling paradigms, where the scene's structure is purposefully disrupted by

shuffling blocks of information across the scene. For instance, jumbling makes it

harder to categorize scenes (Biederman et al., 1974), recognize objects within them

(Biederman, 1972; Biederman et al., 1973) or to detect subtle visual changes (Varakin

and Levin, 2008; Zimmermann et al., 2010). These findings suggest that typical scene

structure contributes to efficiently perceiving a scene and its contents.

Such perceptual effects prompt the hypothesis that scene structure also

impacts perceptual stages of cortical scene processing. However, while there is

evidence that real-world structure impacts visual cortex responses to everyday

objects (Kim and Biederman, 2011; Kaiser and Cichy, 2018; Kaiser and Peelen, 2018;

Roberts and Humphreys, 2010) and human beings (Bernstein et al., 2010; Brandman

and Yovel, 2016; Chan et al., 2010), it is unclear whether real-world structure has a

similar impact on scene-selective neural responses.

To answer this question, we conducted multivariate pattern analysis (MVPA)

and univariate analyses on fMRI and EEG responses to intact and jumbled scenes,

which allowed us to spatially and temporally resolve whether cortical scene

processing is indeed sensitive to scene structure. During the fMRI and EEG

experiments, participants viewed scene images in which we manipulated two facets

of natural scene structure: We orthogonally jumbled the scene's spatial structure (i.e.,

whether the scene's parts appear in their typical positions or not) or its categorical

structure (i.e., whether the scene's parts belong to the same category or different

categories).

Our results provide three key insights into how scene structure affects scene

representations: (1) Cortical scene processing is primarily sensitive to the scene's

spatial structure, more so than to the scene's categorical structure. (2) Spatial

structure impacts the perceptual analysis of scenes, in occipital and

parahippocampal cortices (Epstein, 2012) and shortly after 200ms (Harel et al., 2016).

(3) Spatial structure impacts cortical responses more strongly for upright than

inverted scenes, indicating robust sensitivity to spatial scene structure that goes

beyond sensitivity to low-level features.

85   **Materials and Methods**

Participants

In the fMRI experiment, 20 healthy adults participated in session 1 (mean age

25.5, *SD*=4.0; 13 female) and 20 in session 2 (mean age 25.4, *SD*=4.0; 12 female).

Seventeen participants completed both sessions, three participants only session 1 or

session 2, respectively. In the EEG experiment, 20 healthy adults (mean age 26.6,

SD=5.8; 9 female) participated in a single session. Samples sizes were determined

based on typical samples sizes in related research; a sample of *N*=20 yields 80%

power for detecting effects sizes greater than *d*=0.66[1]. All participants had normal or

corrected-to-normal vision. Participants provided informed consent and received

monetary reimbursement or course credits. All procedures were approved by the

ethical committee of Freie Universität Berlin and were in accordance with the

Declaration of Helsinki.

Stimuli and design

Stimuli were 24 scenes from four different categories (church, house, road,

supermarket; Figure 1a), taken from an online resource (Konkle et al., 2010); the

complete scene image set can be found in the Supplementary Information. We split

each image into quadrants and systematically recombined the resulting parts in a 2×2

---

[1] Related studies on object-object and object-scene consistencies typically yield large effect sizes which exceed this value, both for fMRI responses, *d*=0.72 (Brandman and Peelen, 2017), *d*=0.67 (Kaiser and Peelen, 2018), *d*=2.14 (Kim and Biederman, 2011), *d*=0.94 (Roberts and Humphreys, 2010), and EEG responses, *d*=0.71 (Draschkow et al., 2018), *d*=0.88 (Ganis and Kutas, 2003), *d*=0.67 (Mudrik et al., 2010), *d*=0.69 (Võ and Wolfe, 2013).

design, where both the scenes' spatial structure and their categorical structure could

be either intact or jumbled (Figure 1b/c). This yielded four conditions: (1) In the

"spatially intact & categorically intact" condition, parts from four scenes of the same

category were combined in their correct locations. (2) In the "spatially intact &

categorically jumbled" condition, parts from four scenes from different categories

were combined in their correct locations. (3) In the "spatially jumbled & categorically

intact" condition, parts from four scenes of the same category were combined, and

their locations were exchanged in a crisscrossed way. (4) In the "spatially jumbled &

categorically jumbled" condition, parts from four scenes from different categories

were combined, and their locations were exchanged in a crisscrossed way. For each

participant separately, 24 unique stimuli were generated for each condition by

randomly drawing suitable fragments from different scenes[2]. During the experiment,

all scenes were presented both upright and inverted.

fMRI paradigm

The fMRI experiment (Figure 1d) comprised two sessions. In the first session,

upright scenes were shown, in the second session inverted scenes were shown; the

sessions were otherwise identical. Each session consisted of five runs of 10min. Each

run consisted of 25 blocks of 24 seconds. In 20 blocks, scene stimuli were shown

with a frequency of 1Hz (0.5s stimulus, 0.5s blank). Each block contained all 24 stimuli

of a single condition. In 5 additional fixation-only blocks, no scenes were shown.

---

[2] Note that all scenes were jumbled to some extent, as also in the categorically intact scenes four different exemplars were intermixed.

Block order was randomized within every five consecutive blocks, which contained

each condition (four scene conditions and fixation-only) exactly once.

Figure 1. Stimuli and Paradigm. We combined parts from 24 scene images from four

categories (a) to create a stimulus set where the scenes' structural (e.g. the spatial

arrangements of the parts) and their categorical structure (e.g., the category of the

parts) was orthogonally manipulated; all scenes were presented both upright and

inverted (b/c). In the fMRI experiment, scenes were presented in a block design,

where each block of 24s exclusively contained scenes of a single condition (d). In the

EEG experiment, all conditions were randomly intermixed (e). During both

experiments, participants responded to color changes of the central crosshair.

Scene stimuli appeared in a black grid (4.5° visual angle), which served to mask

visual discontinuities between quadrants. Participants were monitoring a central red

crosshair, which twice per block (at random times) darkened for 50ms; participants

had to press a button when they detected a change. Participants on average detected

80.0% (*SE*=2.5)[3] of the changes. Stimulus presentation was controlled using the

Psychtoolbox (Brainard, 1997).

In addition to the experimental runs, each participant completed a functional

localizer run of 13min, during which they viewed images of scenes, objects, and

scrambled scenes. The scenes were new exemplars of the four scene categories

used in the experimental runs; objects were also selected from four categories (car,

jacket,   lamp,   sandwich).   Participants   completed   32   blocks   (24

scene/object/scrambled blocks and 8 fixation-only blocks), with parameters identical

to the experimental runs (24s block duration, 1Hz stimulation frequency, color change

task).

EEG paradigm

In the EEG experiment (Figure 1e), all conditions were randomly intermixed

within a single session of 75min (split into 16 runs). During each trial, a scene

appeared for 250ms, followed by an inter-trial interval randomly varying between

700ms and 900ms. In total, there were 3072 trials (384 per condition), and an

additional 1152 target trials (see below).

As in the fMRI, stimuli appeared in a black grid (4.5° visual angle) with a central

red crosshair. In target trials, the crosshair darkened during the scene presentation;

participants had to press a button and blink when detecting this change. Participants

on average detected 78.1% (*SE*=3.6) of the changes. Target trials were not included

in subsequent analyses.

---

[3] For two participants, due to technical problems, no button presses were recorded.

fMRI recording and preprocessing

MRI data was acquired using a 3T Siemens Tim Trio Scanner equipped with a

12-channel head coil. T2*-weighted gradient-echo echo-planar images were

collected as functional volumes (TR=2s, TE=30ms, 70° flip angle, 3mm^3 voxel size,

37 slices, 20% gap, 192mm FOV, 64×64 matrix size, interleaved acquisition).

Additionally, a T1-weighted anatomical image (MPRAGE; 1mm^3 voxel size) was

obtained. Preprocessing was performed using SPM12 (www.fil.ion.ucl.ac.uk/spm/).

Functional volumes were realigned, coregistered to the anatomical image, and

normalized into MNI-305 space. Images from the localizer run were additionally

smoothed using a 6mm full-width-half-maximum Gaussian kernel.

EEG recording and preprocessing

EEG signals were recorded using an EASYCAP 64-electrode[4] system and a

Brainvision actiCHamp amplifier. Electrodes were arranged in accordance with the

10-10 system. EEG data was recorded at 1000Hz sampling rate and filtered online

between 0.03Hz and 100Hz. All electrodes were referenced online to the Fz electrode.

Offline preprocessing was performed using FieldTrip (Oostenveld et al., 2011). EEG

data were epoched from -200ms to 800ms relative to stimulus onset, and baseline-

corrected by subtracting the mean pre-stimulus signal. Channels and trials containing

excessive noise were removed based on visual inspection. Blinks and eye movement

artifacts were removed using independent component analysis and visual inspection

of the resulting components. The epoched data were down-sampled to 200Hz.

---

[4] For two participants, due to technical problems, only data from 32 electrodes was recorded.

fMRI region of interest definition

We restricted fMRI analyses to three regions of interest (ROIs): early visual

cortex (V1), scene-selective occipital place area (OPA), and scene-selective

parahippocampal place area (PPA) (Figure 2). We additionally localized scene-

selective retrosplenial cortex (RSC), but did not observe reliable above-baseline

activations to our scene stimuli in this region, all $t(19)<0.14$, $p>.45$. The results for

RSC can be found in the Supplementary Information.

V1 was defined based on a functional group atlas (Wang et al., 2015), from

which we selected all voxels that had a higher probability of belonging to V1 than

belonging to another region in the atlas (905 voxels). Changing the number of voxels

included did not qualitatively change the results in V1 (see Supplementary

Information).

Scene-selective ROIs were defined using the localizer data, which were

modelled in a general linear model (GLM) with 9 predictors (3 regressors for the

scene/object/scrambled blocks and 6 movement regressors). Scene-selective ROI

definition was constrained by group-level activation masks for OPA and PPA (Julian

et al., 2012). Within these masks, we first identified the voxel exhibiting the greatest

t-value in a scene>object contrast, separately for each hemisphere, and then defined

the ROI as a 125-voxel sphere around this voxel (similar results were obtained for

different ROI sizes, see Supplementary Information). Left- and right-hemispheric ROIs

were concatenated for further analysis[5].

---

[5] Analysing the data from the two hemispheres separately did not yield any significant differences between hemispheres (*F*<2.04, *p*>.17, for all interactions with hemisphere).

Figure 2. Location of the fMRI regions of interest (ROIs). fMRI data analysis was

restricted to three ROIs: primary visual cortex (V1), the occipital place area (OPA) and

the parahippocampal place area (PPA). The V1 ROI was based on a functional atlas

(Wang et al., 2015), and identical for all participants. The scenes-selective regions

were defined as spheres around each participant's peak activation in a separate

scene-localizer run, constrained by functional group masks (Julian et al., 2012). The

colormap represents the consistency of ROI locations across participants (i.e., how

many participants' ROIs covered the respective voxels).

fMRI decoding

fMRI response patterns for each ROI were extracted directly from the volumes

recorded during each block. After shifting the activation time course by three TRs

(i.e., 6s) to account for the hemodynamic delay, we extracted voxel-wise activation

values from the 12 TRs corresponding to each block of 24s. Activation values for

these 12 TRs were then averaged, yielding a single response pattern across voxels

for each block. To account for activation differences between runs, the mean

activation across all blocks was subtracted from each voxel's values, separately for

each run. Decoding analyses were performed using CoSMoMVPA (Oosterhof et al.,

2016), and were carried out separately for each ROI and participant. We used data

from four runs to train linear discriminant analysis (LDA) classifiers to discriminate

multi-voxel response patterns (i.e., patterns of voxel activations across all voxels of

an ROI) for two conditions (e.g., spatially intact versus spatially jumbled scenes).

Classifiers were tested using response patterns for the same two conditions from the

left-out, fifth run. This classification routine was done repeatedly until every run was

left out once and decoding accuracy was averaged across these repetitions.

fMRI univariate analysis

To establish univariate activation differences, we modeled the fMRI data in a

GLM analysis. For this analysis, all functional volumes were smoothed using a 6mm

full-width-half-maximum Gaussian kernel. For each run, we constructed a GLM with

10 predictors (4 regressors reflecting the four scene conditions and 6 movement

regressors). For each of the four scene conditions, this analysis yielded 5 beta maps

(one for each run) for the upright scenes (from session 1), and 5 beta maps (one for

each run) for the inverted scenes (from session 2). We first averaged beta weights for

every condition across runs. These beta weights were then averaged across all voxels

of each ROI, yielding one activation value for each condition, ROI, and participant.

For each ROI (V1, OPA, PPA), and separately for the two stimulus orientations

(upright, inverted), we computed three effects: (1) The main effect of spatial structure,

reflecting the difference between the two spatially intact and the two spatially jumbled

scenes, (2) the main effect of categorical structure, reflecting the difference between

the two categorically intact and the two categorically jumbled scenes, and (3) the

interaction effect of spatial and categorical structure. Subsequently, to uncover

inversion effects, we compared these effects across the upright scenes and inverted

scenes to reveal inversion effects.

EEG decoding

EEG decoding was performed separately for each time point (i.e., every 5ms)

from -200ms to 800ms relative to stimulus onset, using CoSMoMVPA (Oosterhof et

al., 2016). We used data from all-but-one trials for two conditions to train LDA

classifiers to discriminate topographical response patterns (i.e., patterns across all

electrodes) for two conditions (e.g., spatially intact versus spatially jumbled scenes).

Classifiers were tested using response patterns for the same two conditions from the

left-out trials. This classification routine was done repeatedly until each trial was left

out once and decoding accuracy was averaged across these repetitions.

Classification time series for individual participants were smoothed using a running

average of five time points (i.e., 25ms).

EEG univariate analysis

To establish univariate EEG response differences (i.e., ERP effects) between

conditions, we averaged evoked responses for all trials of each condition. Based on

a previous study on scene-selective ERPs (Harel et al., 2016), we then averaged these

responses across six posterior-lateral EEG electrodes (P4, P8, O2, P7, P3, O1),

yielding one ERP response for each condition and participant. For these ERPs, we

computed the same effects as outlined above for the fMRI data: a main effect of

spatial structure, a main effect of categorical structure, and interactions with scene

inversion[6].

Statistical testing

For the fMRI data, we used *t*-tests to compare decoding against chance and

between conditions. For the univariate data, we used ANOVAs to tests for differences

in activations. To Bonferroni-correct for comparisons across ROIs, all *p*-values were

multiplied by 3. For the EEG data, given the larger number of comparisons, we used

a threshold-free cluster enhancement procedure (Smith and Nichols, 2009) and

multiple-comparison correction based on a sign-permutation test (with null

distributions created from 10,000 bootstrapping iterations), as implemented in

CoSMoMVPA (Oosterhof et al., 2016). The resulting statistical maps were thresholded

at $z>1.96$ (i.e., $p_{corr}<.05$).

Data Availability

291   Data are publicly available on OSF (doi.org/10.17605/OSF.IO/W9874).

292   Materials and code are available from the corresponding author upon request.

---

[6] For using the same statistical tests as for the decoding results, interactions in the univariate EEG analyses were computed by testing the differences between conditions against each other (e.g., the difference between intact and jumbled scenes in the upright condition versus the difference between intact and jumbled scenes in the inverted conditions).

294   **Results**

For both the fMRI and EEG data, we performed two complimentary decoding

analyses. In the first analysis, we tested sensitivity for spatial structure by decoding

spatially intact from spatially jumbled scenes (Figure 3a). In the second analysis, we

tested sensitivity for categorical structure by decoding categorically intact from

categorically jumbled scenes (Figure 3d). To investigate whether successful decoding

indeed reflected sensitivity to scene structure, we performed both analyses

separately for the upright and inverted scenes. Critically, inversion effects (i.e., better

decoding in the upright than in the inverted condition) indicate genuine sensitivity to

natural scene structure that goes beyond purely visual differences.

Sensitivity to spatial scene structure

First, to uncover where and when cortical processing is sensitive to spatial

structure, we decoded between scenes whose spatial structure was intact or jumbled

(Figure 3a).

For the fMRI data (Figure 3b), we found highly significant decoding between

spatially intact and spatially jumbled scenes. For upright scenes, significant decoding

emerged in V1, $t(19)=13.03$, $p_{corr}<.001$, OPA, $t(19)=7.61$, $p_{corr}<.001$, and PPA,

$t(19)=5.92$, $p_{corr}=.002$, and for inverted scenes in V1, $t(19)=9.92$, $p_{corr}<.001$, but not in

OPA, $t(19)=2.08$, $p_{corr}=.16$, and PPA, $t(19)=0.85$, $p_{corr}>1$. Critically, we observed

inversion effects (i.e., better decoding for the upright scenes) in the OPA, $t(16)=4.41$,

p_{corr}=.001[7], and PPA, t(16)=3.67, p_{corr}=.006, but not in V1, t(16)=1.32, p_{corr}=.62.

Therefore, decoding in V1 solely reflects visual differences, whereas OPA and PPA

exhibit genuine sensitivity to the spatial scene structure. This result was confirmed by

further ROI analyses and a spatially unconstrained searchlight analysis (see

Supplementary Information).

For the EEG data (Figure 3c), we also found strong decoding between spatially

intact and jumbled scenes. For upright scenes, this decoding emerged between 55ms

and 465ms, between 505ms and 565ms, and between 740ms and 785ms, peak

z>3.29, p_{corr}<.001, and for inverted scenes between 65ms and 245ms, peak z>3.29,

p_{corr}<.001. As in scene-selective cortex, we observed inversion effects, indexing

stronger sensitivity to spatial structure in upright scenes, between 255ms and 300ms

and between 340ms and 395ms, peak z=2.78, p_{corr}=.005.

Together, these results show that in scene-selective OPA and PPA, and after

255ms, cortical activations are sensitive to the spatial structure of natural scenes.

Critically, this sensitivity becomes apparent in inversion effects, and thus cannot be

attributed to image-specific differences between intact and jumbled scenes, as these

are identical for the upright and inverted scenes. Our findings rather indicate a

genuine sensitivity to spatial structure consistent with real-world experience.

---

[7] Statistics for fMRI inversion effects are based on the 17 participants who completed both sessions.

Figure 3. MVPA results. To reveal sensitivity to spatial scene structure, we decoded

between scenes with spatially intact and spatially jumbled parts (a). Already during

early processing (in V1 and before 200ms) spatially intact and jumbled scenes could

be discriminated well, both for the upright and inverted conditions. Critically, during

later processing (in OPA/PPA and from 255ms) inversion effects (i.e., better decoding

for upright than inverted scenes) revealed genuine sensitivity to spatial scene

structure (b/c). To reveal sensitivity to categorical scene structure, we decoded

between scenes with categorically intact and categorically jumbled parts (d). In this

analysis, no pronounced decoding and no inversion effects were found, neither

across space (e) nor time (f). Error margins reflect standard errors of the difference.

Significance markers denote inversion effects (p_{corr}<.05).

Sensitivity to categorical scene structure

Second, to uncover where and when cortical processing is sensitive to

categorical structure, we decoded between scenes whose categorical structure was

intact or jumbled (Figure 3a).

For the fMRI (Figure 3e), the upright scenes' categorical structure could be

decoded only from V1, $t(19)=3.11$, $p_{corr}=.017$, but not the scene-selective ROIs, both

$t(19)<2.15$, $p_{corr}>.13$. Similarly, for the inverted scenes, significant decoding was only

observed in V1, $t(19)=4.58$, $p_{corr}<0.001$, but not in the scene-selective ROIs, both

$t(19)<2.29$, $p_{corr}>.10$. No inversion effects were observed, all $t(16)<0.60$, $p_{corr}>1$.

For the EEG (Figure 3f), we found only weak decoding between the

categorically intact and jumbled scenes. In the upright condition, decoding was

significant between 165ms and 175ms and between 215ms and 265ms, peak $z=2.32$,

$p_{corr}=.02$, and in the inverted condition at 120ms, peak $z=1.97$, $p_{corr}=.049$. No

significant inversion effects were observed, peak $z=1.64$, $p_{corr}=.10$[8].

Together, these results reveal no substantial sensitivity to the categorical

structure of a scene, at least when none of the scenes are fully coherent and when

they are not relevant for behavior. Please note that this absence of an effect does not

in no way entail that there is no representation of category during scene analysis. In

our analysis, we did not decode between different scene categories, but between

scenes whose categories were intact or shuffled (collapsed across their categorical

content): as a consequence, our analysis only reveals an absence of sensitivity for

categorical structure, but not an absence of sensitivity for category per se.

This absence of sensitivity for categorical scene structure is in marked contrast

with sensitivity for spatial scene structure, which is observed in the absence of

behavioral relevance and is disrupted by stimulus inversion.

---

[8] Note that the strongest tendency towards an inversion effect (at 115ms) was against the predicted direction.

374   Enhanced responses to spatially structured scenes

Our decoding analyses show that scene-selective cortex exhibits a profound

sensitivity to spatial scene structure. To further understand this sensitivity, we

conducted a univariate analysis, in which we compared the magnitude of responses

evoked by intact and jumbled scenes (Figure 4a/c). Critically, this analysis allowed us

to disentangle two opposing interpretations: On one side, sensitivity to scene

structure could indeed reflect a visual tuning to real-world properties – in this case,

enhanced responses to intact scenes, compared to jumbled scenes, are expected.

On the other side, sensitivity to scene structure could mainly reflect the coding of

stimuli that are incoherent with real-world experience, reflecting a type of "surprise"

response – in this case, enhanced responses to jumbled scenes, compared to intact

scenes, are expected. Analyzing response magnitudes across space (fMRI) and time

(EEG) allowed us to arbitrate these two interpretations.

In the fMRI, we found significant main effects of spatial structure in the upright

condition in OPA, $F(1,19)=21.00$, $p_{corr}<.001$, and PPA, $F(1,19)=55.30$, $p_{corr}<.001$, but

not in V1, $F(1,19)=5.11$, $p_{corr}=.11$ (Figure 4b). No main effects of categorical structure,

all $F(1,19)<5.69$, $p_{corr}>.08$, and no interactions between spatial and categorical

structure were found, all $F(1,19)<1.18$, $p_{corr}>.88$. In the inverted condition, we

observed no significant effects, all $F(1,19)<1.12$, $p_{corr}>.92$ (Figure 4e). Critically, we

inversion effects revealed greater effects of spatial structure in the upright than in the

inverted condition in OPA, $F(1,16)=17.04$, $p_{corr}=.002$, and PPA, $F(1,16)=21.82$,

$p_{corr}<.001$. In accordance with the MVPA results, this finding indicates genuine

sensitivity to spatial scene structure in OPA and PPA. Additionally, the univariate

results highlight that scene-selective cortex preferentially responds to the spatially

intact scenes, rather than the spatially jumbled scenes.

Figure 4. Univariate Results. To reveal sensitivity to scene structure in univariate

response magnitudes, we looked at average responses to each of the four conditions,

separately for the upright scenes (a) and the inverted scenes (d). For the upright

scenes, we found main effects of spatial structure in OPA and PPA (b) and between

225ms and 425ms (c), while no effects of spatial structure were found for the inverted

scenes (e/f). Supporting our MVPA results, inversion effects (i.e., greater effects of

spatial structure in the upright, compared to the inverted scenes) were found in OPA

and PPA (at p_{corr}<.05) and from 260ms (at a more liberal p_{corr}<.1), indicating increased

responsiveness to spatially structured scenes. No main effects of categorical

structure and no interaction effects were found. Error margins reflect standard errors

of the mean. Significance markers denote main effects of spatial structure (p_{corr}<.05).

413   In the EEG, we only found a significant main effect of spatial structure for the

upright scenes (Figure 4c/f), which emerged between 225ms and 425ms, peak

$z=3.09$, $p_{corr}=.002$. None of the other main effects or interactions were significant.

However, we observed trending inversion effects (at a more liberal threshold of

$p_{corr}<.1$), which emerged between 260ms and 270ms, and at 305ms, peak $z=1.72$,

$p_{corr}=.086$. Although not significant, these trending effects qualitatively resemble the

findings obtained in the more sensitive MVPA, which showed that from 255ms

responses become sensitive to spatial scene structure.

Together, the univariate results highlight that responses to natural scenes are

stronger for scenes that are spatially structured. This suggests a preferential

processing of scenes that are composed in accordance with real-world experience –

rather than an enhanced response to scenes that do not adhere to this experience.

Discussion

Our findings provide the first spatiotemporal characterization of cortical

sensitivity to natural scene structure. As the key result, we observed sensitivity to

spatial (but not categorical) scene structure, which emerged in scene-selective cortex

and from 255ms of vision. By showing that this effect is stronger for upright than for

inverted scenes, we provide strong evidence for genuine sensitivity to spatial

structure, rather than low-level properties.

Sensitivity to spatial structure may index mechanisms enabling efficient scene

understanding. Previous work on object processing shows that in order to efficiently

parse the many objects contained in natural scenes, the visual system exploits

regularities in the environment, such as regularities in individual objects' positions

(Kaiser and Cichy, 2018; Kaiser et al., 2018), relationships between objects (Kim and

Biederman, 2011; Kaiser and Peelen, 2018; Kaiser et al., 2014; Roberts and

Humphreys, 2010), and relationships between objects and scenes (Brandman and

Peelen, 2017; Faivre et al., 2019). Further, a recent fMRI study suggests that low-level

representations of small and incomplete scene fragments partly depend on the

fragment's typical position within the visual world (Mannion, 2015). Relatedly, we

recently showed that in scene-selective occipital cortex and after 200ms of vision,

the representations of such scene fragments are sorted with respect to their typical

location in the world (Kaiser et al., 2019a). Focusing on the interplay of multiple scene

elements, the current study shows that on higher levels of the scene processing

hierarchy, the visual system uses spatial regularities to concurrently process the

multiple elements of complex scenes in an efficient way. This result is in line with the

emerging view that real-world structure facilitates processing in the visual system

across diverse naturalistic contents (Kaiser et al., 2019b).

What mechanism underlies the preferential processing of spatially structured

scenes? As one possibility, a scene's intact spatial structure may trigger integrative

processing across the scene, akin to integrative processing of multiple objects that are

positioned in accordance with spatial regularities (Baldassano et al., 2017; Kaiser and

Peelen, 2018). Alternatively, spatially structured scenes may contain typical global

properties (Oliva and Torralba, 2006) that are absent in spatially jumbled scenes, and

the sensitivity to spatial structure may partly reflect sensitivity to the formation of such

global properties. At this point, more studies are needed to understand which types of

features drive the sensitivity to spatial structure.

Our results also shine new light on the temporal processing cascade during

scene perception. Sensitivity to spatial structure emerged after 255ms of processing,

which is only after scene-selective peaks in ERPs (Harel et al., 2016; Sato et al.,

1999)[9] and after basic scene attributes are computed (Cichy et al., 2017). Interestingly,

after 250ms brain responses not only become sensitive to scene structure, but also to

object-scene consistencies (Draschkow et al., 2018; Ganis and Kutas, 2003; Mudrik

et al., 2010; Võ and Wolfe, 2013). Together, these results suggest a dedicated

processing stage for the structural analysis of objects, scenes, and their relationships,

which is different from basic perceptual processing. However, whether these different

findings indeed reflect a common underlying mechanism requires further investigation.

For instance, future investigations need to clarify which of these studies effects reflect

---

[9] In our study, ERP responses in posterior-lateral electrodes peaked at 235ms.

enhanced processing of consistent structure (as our study does) and which primarily

reflect responses to inconsistencies.

Our findings suggest more pronounced sensitivity to spatial structure than to

categorical structure. This is in line with studies showing that scene-selective

responses are mainly driven by spatial layout, rather than scene content (Dillon et al.,

2018; Harel et al., 2013; Henriksson et al., 2019; Kravitz et al., 2011). However, our

results need not to be taken as evidence that categorical structure is not represented

at all during visual analysis[10]. It is conceivable that visual processing is less sensitive

to categorical structure when, as in our study, all scenes are jumbled to some extent

and not behaviorally relevant.

On the contrary, robust sensitivity to spatial scene structure emerged in the

absence of behavioral relevance. This suggests that spatial structure is analyzed

automatically during perceptual processing and is not strongly dependent on

attentional engagement with the scene. As in real-world situations we cannot

explicitly engage with all aspects of a scene concurrently, this automatic analysis of

spatial structure may be crucial for rapid scene understanding.

489   **Acknowledgements**

491   We thank Sina Schwarze for help in EEG data collection and manuscript preparation.

492   D.K. and R.M.C. are supported by Deutsche Forschungsgemeinschaft (DFG) grants

493   (KA4683/2-1, CI241/1-1, CI241/3-1). R.M.C. is supported by a European Research

---

[10] In the Supplementary Information, we show that the four scene categories can be successfully decoded from the EEG signals.

494   Council Starting Grant (ERC-2018-StG 803370). The authors declare no conflict of

495   interest.

Author Contributions

499   D. K. and R.M.C. designed research, D.K. and G.H. acquired data, D.K. and G.H.

500   analyzed data, D.K., G.H., and R.M.C. interpreted results, D.K. prepared figures, D.K.

501   drafted manuscript, D.K., G.H., and R.M.C. edited and revised manuscript. All authors

502   approved the final version of the manuscript.

505   **References**

Baldassano, C., Beck, D. M., & Fei-Fei, L. (2017). Human-object interactions are more

than the sum of their parts. *Cerebral Cortex, 27*, 2276-2288.

Bernstein, M., Oron, J., Sadeh, B., & Yovel G. (2014). An integrated face-body

representation in the fusiform gyrus but not the lateral occipital cortex. *Journal*

of Cognitive Neuroscience, 26, 2469-2478.

Biederman, I. (1972). Perceiving real-world scenes. *Science, 177*, 77-80.

Biederman, I., Glass, A. L., & Stacy, E. W. (1973). Searching for objects in real-world

scenes. *Journal of Experimental Psychology, 97*, 22-27.

Biederman, I., Rabinowitz, J. C., Glass, A. L., & Stacy, E. W. (1974). On the information

extracted from a glance at a scene. *Journal of Experimental Psychology, 103*,

597-600.

Brainard, D. H. (1997). The psychophysics toolbox. *Spatial Vision, 10*, 433-436.

Brandman, T., & Peelen, M. V. (2017). Interaction between scene and object

processing revealed by human fMRI and MEG decoding. *Journal of*

Neuroscience, 37, 7700-7710.

Brandman, T., & Yovel, G. (2016). Bodies are represented as wholes rather than their

sum of parts in the occipital-temporal cortex. *Cerebral Cortex, 26*, 530-543.

Chan, A. W., Kravitz, D. J., Truong, S., Arizpe, J., & Baker, C. I. (2010). Cortical

representations of bodies and faces are strongest in commonly experienced

configurations. *Nature Neuroscience, 13*, 417-418.

Cichy, R. M., Khosla, A., Pantazis, D., & Oliva, A. (2017). Dynamics of scene

representations in the human brain revealed by magnetoencephalography and

deep neural networks. *NeuroImage, 153*, 346-358.

Dillon, M. R., Persichetti, A. S., Spelke, E. S., & Dilks, D. D. (2018). Places in the brain:

bridging layout and object geometry in scene-selective cortex. *Cerebral

Cortex, 28*, 2365-2374.

Draschkow, D., Heikel, E., Võ, M. L.-H., Fiebach, C. J., Sassenhagen, J. (2018). No

evidence for different processes underlying the N300 and N400 incongruity

effects in object-scene processing. *Neuropsychologia, 120*, 9-17.

Epstein, R. A. (2014). Neural systems for visual scene recognition. In M. Bar & K.

Keveraga (Eds.), *Scene Vision* (pp. 105-134). Cambridge, MIT Press.

Faivre, N., Dubois, J., Schwartz, N., & Mudrik, L. (2019). Imaging object-scene

relations processing in visible and invisible natural scenes. *Scientific Reports,

9*, 4567.

Ganis, G., & Kutas, M. (2003). An electrophysiological study of scene effects on object

identification. *Brain Research Cognitive Brain Research, 16*, 123-144.

Harel, A., Groen, I. I. A., Kravitz, D. J., Deouell, L. Y., & Baker, C. I. (2016). The

temporal dynamics of scene processing: A multifaceted EEG investigation.

eNeuro, 3, ENEURO.0139-16.2016.

Harel, A., Kravitz, D. J., & Baker, C. I. (2013). Deconstructing visual scenes in cortex:

gradients of object and spatial layout information. *Cerebral Cortex, 23*, 947-

957.

Henriksson, L., Mur, M., & Kriegeskorte, N. (2019). Rapid invariant encoding of

scene layout in human OPA. *Neuron*, https://doi.org/

10.1016/j.neuron.2019.04.014

Julian, J. B., Fedorenko, E., Webster, J., & Kanwisher N. (2012). An algorithmic

method for functionally defining regions of interest in the ventral visual

pathway. *NeuroImage, 60*, 2357-2364.

Kaiser, D., & Cichy, R. M. (2018). Typical visual-field locations enhance processing in

object-selective channels of human occipital cortex. *Journal of*

Neurophysiology, 120, 848-853.

Kaiser, D., Moeskops, M. M., & Cichy, R. M. (2018). Typical retinotopic locations

impact the time course of object coding. *NeuroImage, 176*, 372-379.

Kaiser, D., & Peelen, M. V. (2018). Transformation from independent to integrative

coding of multi-object arrangements in human visual cortex. *NeuroImage 169*,

334-341.

Kaiser, D., Quek, G. L., Cichy, R. M., & Peelen, M. V. (2019b). Object vision in a

structured world. *Trends in Cognitive Sciences, 23*, 672-685.

Kaiser, D., Stein, T., & Peelen, M. V. (2014). Object grouping based on real-world

regularities facilitates perception by reducing competitive interactions in visual

cortex. *Proceedings of the National Academy of Sciences USA, 111*, 11217-

11222.

Kaiser, D., Turini, J., & Cichy, R. M. (2019a). A neural mechanism for contextualizing

fragmented inputs during naturalistic vision. *eLife Sciences*,

httsp://doi.org/10.7554/eLife.48182

Kim, J. G., & Biederman, I. (2011). Where do objects become scenes? *Cerebral*

Cortex, 21, 1738-1746.

Konkle, T., Brady, T. F., Alvarez, G. A., & Oliva, A. (2010). Scene memory is more

detailed than you think: the role of categories in visual long-term memory.

Psychological Science, 21, 1551-1556.

Kravitz, D. J., Peng, C. S., & Baker, C. I. (2011). Real-world scene representations in

high-level visual cortex: it's the spaces more than the places. *Journal of*

Neuroscience, 31, 7322-7333.

Mannion, D. J. (2015). Sensitivity to the visual field origin of natural image patches in

human low-level visual cortex. *PeerJ, 3*, e1038.

Mudrik, L., Lamy, D., & Deouell, L. Y. (2010). ERP evidence for context congruity

effects during simultaneous object-scene processing. *Neuropsychologia, 48*,

507-517.

Oliva, A., & Torralba, A. (2007). The role of context in object recognition. *Trends in*

Cognitive Sciences, 11, 520-527.

Oliva, A, & Torralba, A. (2006). Building the gist of a scene: the role of global image

features in recognition. *Progress in Brain Research, 155*, 23-36.

Oostenveld, R., Fries, P., Maris, E., & Schoffelen, J. M. (2011). FieldTrip: Open source

software   for   advanced   analysis   of   MEG,   EEG,   and   invasive

electrophysiological data. *Computational Intelligence and Neuroscience, 2011,*

156869.

Oosterhof, N. N., Connolly, A. C., & Haxby, J V. (2016). CoSMoMVPA: Multi-modal

multivariate pattern analysis of neuroimaging data in Matlab/GNU Octave.

Frontiers in Neuroinformatics, 10, 20.

Potter, M. C. (1975). Meaning in visual search. *Science, 187*, 965-966.

Roberts, K. L., & Humphreys, G. W. (2010). Action relationships concatenate

representations of separate objects in the ventral visual cortex. *NeuroImage*

52, 1541-1548.

Sato, N., Nakamura, K., Nakamura, A., Sugiura, M., Iko, K., Fukuda, H., & Kawashima,

R. (1999). Different time course between scene processing and face

processing: a MEG study. *Neuroreport, 10*, 3633-3637.

Smith, S. M., & Nichols, T. E. (2009). Threshold-free cluster enhancement: addressing

problems of smoothing, threshold dependence and localisation in cluster

inference. *NeuroImage, 44,* 83-98.

Thorpe, S., Fize, D., & Marlot, D. (1996). Speed of processing in the human visual

system. *Nature, 381*, 520-522.

Varakin, D. A., & Levin, D. T. (2008). Scene structure enhances change detection. *The*

Quarterly Journal of Experimental Psychology, 61, 543-551.

Võ, M. L.-H., Boettcher, S. E. P., & Draschkow, D. (2019). Reading scenes: How scene

grammar guides attention and aids perception in real-world environments.

Current Opinion in Psychology, https://doi.org/10.1016/j.copsyc.2019.03.009

Võ, M. L.-H., & Wolfe, J. M. (2013). Differential electrophysiological signatures of

semantic and syntactic scene processing. *Psychological Science, 24*, 1816-18-

23.

Wang, L., Mruczek, R. E., Arcaro, M. J., & Kastner, S. (2015). Probabilistic maps of

visual topography in human cortex. *Cerebral Cortex, 25,* 3911-3931.

Wolfe, J. M., Võ, M. L.-H., Evans, K. K., & Greene, M. R. (2011). Visual search in

scenes involves selective and nonselective pathways. *Trends in Cognitive*

Sciences, 15, 77-84.

Zimmermann, E., Schnier, F., & Lappe, M. (2010). The contribution of scene context

on change detection performance. *Vision Research, 50*, 2062-2068.