Deep learning enables therapeutic antibody optimization in mammalian cells by deciphering high-dimensional protein sequence space

Derek M Mason[1], Simon Friedensohn[1], Cédric R Weber[1], Christian Jordi[1], Bastian Wagner[1], Simon Meng[1], Pablo Gainza[2], Bruno E Correia[2] and Sai T Reddy[1]*

[1]Department of Biosystems Science and Engineering, ETH Zurich, 4058, Basel, Switzerland
[2]Institute of Bioengineering, École Polytechnique Fédérale de Lausanne, 1015, Lausanne, Switzerland

Correspondence: *sai.reddy@ethz.ch

ABSTRACT (150 words)

Therapeutic antibody optimization is time and resource intensive, largely because it requires low-throughput screening (10^3 variants) of full-length IgG in mammalian cells, typically resulting in only a few optimized leads. Here, we use deep learning to interrogate and predict antigen-specificity from a massively diverse sequence space to identify globally optimized antibody variants. Using a mammalian display platform and the therapeutic antibody trastuzumab, rationally designed site-directed mutagenesis libraries are introduced by CRISPR/Cas9-mediated homology-directed repair (HDR). Screening and deep sequencing of relatively small libraries (10^4) produced high quality data capable of training deep neural networks that accurately predict antigen-binding based on antibody sequence. Deep learning is then used to predict millions of antigen binders from an *in silico* library of ~10^8 variants, where experimental testing of 30 randomly selected variants showed all 30 retained antigen specificity. The full set of *in silico* predicted binders is then subjected to multiple developability filters, resulting in thousands of highly-optimized lead candidates. With its scalability and capacity to interrogate high-dimensional protein sequence space, deep learning offers great potential for antibody engineering and optimization.

INTRODUCTION

In antibody drug discovery, the 'target-to-hit' stage is a well-established process, as screening hybridomas, phage or yeast display libraries typically result in a number of potential lead candidates. However, the time and costs associated with lead candidate optimization often take up the majority of the preclinical discovery and development cycle[1]. This is largely due to the fact that lead optimization of antibody molecules consists of addressing multiple parameters in parallel, including expression level, viscosity, pharmacokinetics, solubility, and immunogenicity[2,3]. Once a lead candidate is discovered, additional engineering is often required; phage and yeast display offer a powerful method for high-throughput screening of large mutagenesis libraries (>10^9), however they are primarily only used for increasing affinity or specificity to the target antigen[4]. The fact that nearly all therapeutic antibodies require expression in mammalian cells as full-length IgG means that the remaining development and optimization steps must occur in this context. Since mammalian cells lack the capability to stably

replicate plasmids, this last stage of development is done at very low-throughput, as elaborate cloning,

transfection and purification strategies must be implemented to screen libraries in the max range of 10^3,

meaning only minor changes (e.g., point mutations) are screened[5]. Interrogating such a small fraction

of protein sequence space also implies that addressing one development issue will frequently cause

rise of another or even diminish antigen binding altogether, making multi-parameter optimization very

challenging. This challenge frequently results in antibodies with suboptimal biophysical properties for

clinical development, which can lead to adverse side effects or even drug failure. For example, self-

administered, subcutaneous injection of antibodies is becoming an increasingly used approach for

patients requiring frequent dosing, but the identification of highly soluble, non-viscous antibodies which

retain high biological activity is immensely difficult[6]. The withdrawal of Pfizer's anti-PCSK9 antibody,

bococizumab, from clinical trials is an even more drastic example, where the immunogenicity of the

molecule adversely effected long-term treatment efficacy. Conversely, Sanofi and Regeneron's

clinically approved antibody, alirocumab, has the same molecular target of PCSK9, but shows almost

no immunogenic effects[7].

Machine learning applied to biological sequence data offers a powerful approach to augment protein

engineering by constructing models capable of making predictions of genotype-phenotype

relationships[8,9]. This is due to the capability of models to extrapolate complex relationships between

sequence and function. One of the principle challenges in constructing accurate machine learning

models is the collection of appropriate high-quality training data. Directed evolution platforms are well-

suited for this as they rely on the linking of biological sequence data (DNA, RNA, protein) to a phenotypic

output[10]. In fact, it has long been proposed to use machine learning models trained on data generated

by mutagenesis libraries as a means to guide protein engineering[11,12]. Recently, Gaussian processes,

a Bayesian learning model, were used to engineer cytochrome enzymes, enabling navigation through

a vast protein sequence space to discover highly thermostable variants[13]. Similarly, the design and

screening of a structure-guided library of channel rhodopsin membrane proteins was used to train

Gaussian process regression models, which were able to accurately predict variants that could express

and localize on mammalian cell membranes[14].

In recent years, access to deep sequencing and parallel computing has enabled the construction of

deep learning models capable of predicting molecular phenotype from sequence data[15,16]. For example,

deep learning has been used to learn the sequence specificities of RNA- and DNA-binding proteins[17],

regulatory grammar of protein expression in yeast[18], and HLA-neoantigen presentation on tumor cells[19].

In most cases deep (artificial) neural networks represent the class of algorithm utilized. While the

complexity of neural networks has changed drastically since their conception, the fundamental concept

remains the same: mimicking the connections of biological neurons to learn complex relationships

between variables[20]. As an extension of a single-layer neural network, or perceptron[21], deep learning

incorporates multiple hidden layers to decipher relationships buried in large, high-dimensional data sets,

such as the millions of reads gathered from a single deep sequencing experiment. Well trained models

can then be used to make predictions on completely unseen and novel variants. This application of

model extrapolation lends itself perfectly to protein engineering because it provides a way to interrogate

a much larger sequence space than what is physically possible. For example, even for a short stretch

of just 10 amino acids, the combinatorial sequence diversity explodes to 10^{13}, a size which is nearly
impossible to interrogate experimentally.

Here, we leverage the power of deep learning to perform multi-parameter optimization of therapeutic
antibodies (full-length IgG) directly in mammalian cells (Figure 1). Starting with a mammalian display
cell line[22] expressing the therapeutic antibody trastuzumab (Herceptin), we use CRISPR-Cas9-
mediated homology-directed repair (HDR) to introduce site-directed mutagenesis libraries in the
variable heavy chain complementarity determining region 3 (CDRH3)[23]. In order to generate information
rich training data, single-site deep mutational scanning (DMS) is first performed[24], which is then used
to guide the design of combinatorial mutagenesis libraries. An experimental (physical) library size of 5
x 10^4 variants was then screened for specificity to the antigen HER2. All binding and non-binding variant
sequences were then used to train recurrent and convolutional deep neural networks, which when fully-
trained and optimized were able with high accuracy and precision to predict antigen-specificity based
on antibody sequence. Neural networks are then used to predict antigen-specificity on a subset of
sequence variants from the DMS-based combinatorial mutagenesis library (~10^8 sequences), resulting
in >3.0 x 10^6 variants predicted to have a high probability of being antigen-specific. A random selection
of variants were recombinantly expressed and tested, resulting in 30 out of 30 showing antigen-specific
binding. The *in silico* library of predicted binders are then subjected to several sequence-based *in silico*
filtering steps to optimize for developability parameters such as viscosity, clearance, solubility and
immunogenicity, resulting in nearly 5,000 antibody sequence variants predicted to have more optimal
properties than the starting trastuzumab sequence.

Figure 1: Implementing deep learning to predict antibody target specificity

(a) Generating quality data capable of training accurate models. First, deep mutational scanning assesses the impact mutations have on protein function across many different positions. These insights can then be applied to combinatorial mutagenesis strategies to guide protein library design capable of producing thousands of binding variants. **(b)** Sequence information for binders and non-binders can then be used to train deep neural networks to accurately predict antigen specificity of unknown antibody variants, producing millions of predicted binders. These binders can then be subjected to any available in silico methods for predicted various developability attributes.

RESULTS

Deep mutational scanning determines antigen-specific sequence landscapes and guides
rational antibody library design

As the amino acid sequence of an antibody's CDRH3 is a key determinant of antigen specificity, we
performed DMS on this region to resolve the specificity determining residues. To start, a hybridoma
cell-line was used that expressed a trastuzumab variant that could not bind HER2 antigen (mutated
CDRH3 sequence) (Supplementary Fig. 1). Libraries were generated by CRISPR-Cas9-mediated
homology-directed mutagenesis (HDM)[23] by transfecting guide RNA (gRNA) targeting the CDRH3 and
a pool of homology templates in the form of single-stranded oligonucleotides (ssODNs) containing NNK
degenerate codons at single-sites tiled across CDRH3 (Figure 2a, Supplementary Fig. 2). Libraries
were then screened by fluorescence activated cell sorting (FACS), and populations expressing surface
IgG which either were binding or not binding to antigen were isolated and subjected to deep sequencing
(Illumina MiSeq) (Supplementary Table 1). Deep sequencing data was then used to calculate
enrichment scores of the 10 positions investigated, which revealed six positions that were sufficiently
amenable to a wide-range of mutations and an additional three positions that were marginally accepting
to defined mutations (Figure 2b). Although residues 102D, 103G, 104F, and 105Y appear to be
contacting amino acids of the CDRH3 loop with HER2[25,26], 105Y is the only residue completely fixed.
In addition to DMS, we also explored the capacity of structural modeling to identify the prospective
antigen-binding landscape by using structure-guided modeling with Rosetta, a leading software platform
for computational protein design[27]. After performing 5,000 redesigns of trastuzamab (PDB id: 1N8Z),
preceded by a stochastic backbone flexibility (FastRelax) step, 48 possible variants were generated
(Figure 2c). The resulting sequence logo plot from these generated variants, however, differed
substantially from the DMS-based sequence logo plot.

The limited number of predictions and diversity from Rosetta suggested that sequence logo plots
generated by DMS are a better option to guide the rational design of a combinatorial mutagenesis
library, which consisted of degenerate codons across all positions (except 105Y) (Supplementary Fig.
3, Supplementary Table 7). Degenerate codons were selected per position based on their amino acid
frequencies which most closely resembled the degree of enrichment found in the DMS data following
1, 2, and 3 rounds of antigen-specific enrichment (Supplementary Fig. 2, Equation 2). This
combinatorial library possesses a theoretical protein sequence space of 7.17×10^8, far greater than the
single-site DMS library diversity of 200. Libraries containing CDRH3 variants were again generated in
hybridoma cells through CRISPR-Cas9-mediated HDM in the same non-binding trastuzumab clone
described previously (Figure 2d). Antigen binding cells were isolated by two rounds of enrichment by
FACS (Figure 2d, Supplementary Fig. 3) and the binding/non-binding populations were subjected to
deep sequencing. Sequencing data identified 11,300 and 27,539 unique binders and non-binders,
respectively (Supplementary Table 2). These sequence variants represented only a miniscule 0.0054%
of the theoretical protein sequence space of the combinatorial mutagenesis library.

Figure 2: Sequence and structure-based analysis of the mutational landscape

(a) Flow cytometry profile following integration of tiled mutations by homology-directed mutagenesis. Antigen specific variants underwent 3 rounds of enrichment (Supplementary Fig. 2) (b) Corresponding heatmap (left) following sequencing analysis of the pre-sorted (Ab+) and post-sorted (Ag+) populations (Supplementary Table 1). Wild type amino acids are marked by black circles. The resulting sequence logo plot (right) generated by positively enriched mutations per position. (c) 3D protein structure of trastuzumab in complex with its target antigen, HER2[25,26] (left). Locations of surface exposed residues: 102D, 103G, 104F, and 105Y are given. The protein design program Rosetta was run 5,000 times to generate sequence variants of trastuzumab predicted to bind the antigen HER2. The resulting sequence logo plot of the 48 generated CDRH3 loops (right) differs substantially from the DMS-based sequence logo plot. (d) Combinatorial mutagenesis libraries are designed from enrichment ratios observed in DMS data and integrated into the trastuzumab variant by homology-directed mutagenesis. Flow cytometry plots resulting from transfection of the rationally designed library. Deep sequencing was performed on the library (Ab+), non-binding variants (Ag-), and binding variants after 1 and 2 rounds of enrichment (Ag+1, Ag+2) (Supplementary Fig. 3, Supplementary Table 2). (e) Amino acid frequency plots of antigen binding and non-binding variants reveals nearly indistinguishable amino acid usages across all positions. (f) Distribution plot for the predicted Rosetta ddG scores for each sequence in the experimentally determined binding population (11,300 binders, shown in blue) and non-binding population (27,539 non-binders, shown in red) (left). The distribution plot is normalized for comparison purposes. Receiver operating characteristic (ROC) curve with area under curve (AUC) using the Rosetta ddG score to predict binding and non-binding variants shows poor classification (right).

Discriminating between the binding and non-binding sequences in the combinatorial library is challenging at the sequence level. Amino acid usage per position was comparatively similar between antigen binding and non-binding populations (Figure 2e), thus making it difficult to develop any sort of heuristic rules or decipher observable patterns to identify binding sequences. Thus, we investigated whether structure-based analysis could accurately predict antigen-binding sequences. We used Rosetta to model each of the 11,300 binder and 27,539 non-binder sequences from the combinatorial

161 library on the antibody structure of trastuzumab, and used Rosetta's predicted free energy of binding
162 (ddG) as the discrimination score. This approach, however, yielded a very poor classifier (ROC curve
163 AUC: 0.55, Figure 2f) and revealed that high-dimensional patterns determining antigen-specificity could
164 not be extracted by structural modeling.

Training deep neural networks to classify antigen-specificity based on antibody sequence

To learn the high-dimensional patterns that determine antigen binding, we set out to develop and train
sequence-based deep learning models capable of predicting antibody specificity towards the target
antigen HER2. After having compiled deep sequencing data on binding and non-binding CDRH3
variants, amino acid sequences were converted to an input matrix by one-hot encoding, an approach
where each column of the matrix represents a specific residue and each row corresponds to the position
in the sequence, thus a 10 amino acid CDRH3 sequence as here results in a 10 x 20 matrix. Each row
will contain a single '1' in the column corresponding to the residue at that position, whereby all other
columns/rows receive a '0'. We utilized long short-term memory recurrent neural networks (LSTM-RNN)
and convolutional neural networks (CNN), which represent two of the main classes of deep learning
models used for biological sequence data[16]. LSTM-RNNs and CNNs both stem from standard neural
networks, where information is passed along neurons that contain learnable weights and biases,
however, there are fundamental differences in how the information is processed. LSTM-RNN layers
contain loops, enabling information to be retained from one step to the next, allowing models to
efficiently correlate a sequential order with a given output; CNNs, on the other hand, apply learnable
filters to the input data, allowing it to efficiently recognize spatial dependencies associated with a given
output. Model architecture and hyperparameters (Figures 3a, c) were selected by performing a grid
search across various parameters (LSTM-RNN: nodes per layer, batch size, number epochs and
optimizing function; CNN: number of filters, kernel size, dropout rate and dense layer nodes) using a k-
fold cross-validation of the data set. All models were built to assess their accuracy and precision of
classifying binders and non-binders from the available sequencing data. 70% of the original data set
was used to train the models and the remaining 30% was split into two test data sets used for model
evaluation: one test data set contained the same class split of sequences used to train the model and
the other contained a class split of approximately 10/90 binders/non-binders to resemble physiological
frequencies (Figure 2d). Performance of the LSTM-RNN and CNN were assessed by constructing
receiver operating characteristic (ROC) curves and precision-recall (PR) curves derived from
predictions on the unseen testing data sets (Figure 3b, d). Based on conventional approaches to training
classification models, the data set was adjusted to allow for a 50/50 split of binders and non-binders
during training. Under these training conditions, the LSTM-RNN and CNN were both able to accurately
classify unseen test data (ROC curve AUC: 0.9 ± 0.0, average precision: 0.9 ± 0.0, Supplementary Fig.
5).

Next, we used the trained LSTM-RNN and CNN models to classify a random sample of 1 x 10^5
sequences from the potential sequence space. We observed, however, an unexpectedly high
occurrence of positive classifications (25,318 ± 1,643 sequences or 25.3 ± 1.6%, Supplementary Table
3b). With the knowledge that the physiological frequency of binders should be approximately 10-15%,

we sought to adjust the classification split of the training data with the hypothesis that models were
being subject to some unknown classification bias. Additional models were then trained on classification
splits of both 20/80, and 10/90 binders/non-binders, as well as a classification split with all available
data (approximately 30/70 binders/non-binders). Unbalancing the sequence classification led to a
significant reduction in the percentage of sequences classified as binders, but also led to a reduction in
the model performance on the unseen test data (Supplementary Fig. 4-7, Supplementary Tables 3a,
b). Through our analysis, we concluded that the optimal data set for training the models was the set
inclusive of all known CDRH3 sequences for the following reasons: 1) the percentage of sequences
predicted as binders reflects this physiological frequency, 2) this data set maximizes the information
the model sees, and 3) model performance on both test data sets. Final model architecture, parameters,

Figure 3: Deep learning models accurately predict antigen specificity

The selected network architectures and their model performance curves for classification of binding and non-binding sequences. Model training was performed on 70% of the data and testing was performed by withholding the remaining 30% and then comparing the model's classification of test sequences with the known classification. In lieu of adjusting the data set to a defined class split of binding/non-binding sequences, all known information was utilized to train and test the networks (approx. class split of 31%). (a) LSTM-RNN architecture and parameters used for model fitting. (b) ROC (receiver operating character) curve and PR (precision-recall) curve observed on the classification of sequences in the test set by the LSTM-RNN. (c) CNN architecture and parameters used for model fitting. (d) ROC curve and PR curve observed on the classification of sequences in the test set by the CNN. The high values observed for the ROC area under curve (AUC) and average precision of both networks represent robust measures of model accuracy and precision.

210 and evaluation are shown in Figure 3. As a final measure of model validation, neural networks were
211 trained with a data set containing randomly shuffled binding and non-binding class labels. Model
212 performance of these networks revealed indiscriminate sequence classification on unseen test data
213 (Supplementary Fig. 8), signifying the identification of learned patterns for networks trained with
214 properly classified data.

Figure 4: Deep neural network predicted sequences are experimentally validated to be antigen-specific

(a) To test the precision of the neural network predictions, 30 variants were randomly selected after increasing the prediction threshold (P(binder) > 0.75) and taking the consensus sequences between the LSTM-RNN and CNN. These sequences were integrated into individual hybridoma cells lines by separately transfecting ssODN donor sequences with gRNA. **(b)** Affinities for the 30 variant sequences were determined by biolayer interferometry (BLI). Although most sequences display a minor decrease in affinity for the target antigen, the majority of sequences still exude affinities of therapeutic relevance in the single nanomolar (24/30) or sub-nanomolar range (5/30). **(c)** Iso-affinity graph of the variant sequences.

Predicted binding sequences are recombinantly expressed and antigen-specific

Using our DMS-based combinatorial mutagenesis library as a guide (Figure 2d), 7.2×10^7 possible
sequence variants were generated in silico. The fully-trained LSTM-RNN and CNN models were used
to classify all 7.2×10^7 sequence variants as either antigen binders or non-binders based on a probability
score (P), resulting in a prediction of 8.55×10^6 (LSTM-RNN) and 9.52×10^6 (CNN) potential binders
($P > 0.50$). This represented a reasonable fraction (11-13%) of antigen-specific variants based on
experimental screening (Figure 2d). To increase confidence, we increased the prediction threshold for
binder classification to $P > 0.75$ and took the consensus binders between the LSTM-RNN and CNN.

This reduced the antigen-specific sequence space down to 3.1×10^6 variants. To validate the precision

of our fully trained LSTM-RNN and CNN models, we randomly selected and tested a subset of 30

CDRH3 sequences predicted to be antigen-specific (Figure 4a). To further demonstrate the capacity of

deep learning to identify novel sequence variants, we also added the criteria that the selected variants

must have a minimum Levenshtein distance (*LD)* of 5 from the original CDRH3 sequence of

trastuzumab. CRISPR-Cas9-mediated HDR was used to generate mammalian display cell lines

expressing the 30 different sequence variants. Flow cytometry was performed and revealed that 30 of

the 30 variants (100%) were antigen-specific (Supplementary Fig. 9). Further analysis was performed

on the 30 antigen-binding variants to more precisely quantify the binding kinetics via biolayer

interferometry (BLI, FortéBio Octet RED96e) (Figure 4b). The original trastuzumab sequence was

measured to have an affinity towards HER2 of 4.0×10^{-10} M (equilibrium dissociation constant, K_D); and

although the majority of variants tested had a slight decrease in affinity, 80% (24/30) were still in the

single-digit nanomolar range, 17% (5/30) remained sub-nanomolar, and even one variant (3%) showed

a near 3-fold increase in affinity compared to trastuzumab ($K_D = 1.4 \times 10^{-10}$ M) (Figure 4a, c). We also

investigated if there were correlations between model prediction values and measured affinities

(Supplementary Fig. 10). While no strong trend was observable, the highest affinity variants tended to

have higher prediction values.

Sequence space analysis of deep learning predicted variants

In order to investigate the sequence space of the predicted binding and non-binding variants, we

conducted a sequence similarity network analysis[28] of 5,000 randomly selected binding and non-binding

sequences (Supplementary Table 4, Supplementary Fig. 11). When generating similarity networks by

clustering CDRH3 sequences with a $LD \leq 3$, we observed 99.7% of all sequences to be within a single

cluster, but when increasing the clustering stringency to a $LD \leq 2$, the fraction of sequences found within

the largest cluster is reduced to 30%, with the majority of other sequences not clustering with any other

sequence (Figure 5a). While a large portion of the sequences found within the largest cluster are

predicted binding sequences, non-binding sequences are also present, illustrating the complexities of

the patterns identified by deep neural networks. To further elucidate the high-dimensional patterns of

the antigen-binding landscape that deep learning models have identified, we performed the attribution

method of *Integrated Gradients*[29] on closely related sequences ($LD \leq 2$) (Figure 5b). This analysis

provides a means to visualize non-linear combinations of amino acids that contribute to classification

as a binder or non-binder. This revealed that unlike position-weight matrices, LSTM-RNN and CNN

models did not equally weight individual residues and positions and thus learned complex non-linear

patterns associated with binding and non-binding.

Figure 5: Deep neural networks decipher non-linear interactions to accurately classify binding and non-binding sequences

(a) A sequence similarity network analysis was completed on 5,000 randomly selected predicted binding (blue) and 5,000 non-binding variants (black) to investigate potential sequence similarities of the classification choices (left). Clustering was performed at a Levenshtein distance (LD) $\leq$ 2; Similarity network analyses performed with additional *LD*s can be found in Supplementary Table 4 and Supplementary Fig. 12. Although the largest cluster within the network (middle) contains 90% predicted binding variants, this comprises only 30% of all sequences in the network. Conversely, 42% of sequences do not cluster with any other neighboring sequences, thereby revealing that for the majority of variants, there are no discernible clusters of binding or non-binding predictions. **(b)** The Integrated Gradients method efficiently extracts and enables visualization of the classification patterns established by the LSTM-RNN (left) and the CNN (right). For the specific example, variants identified in the network with a *LD* of only 2 were classified as binding and non-binding sequences respectively. The LSTM-RNN and CNN uniquely identify non-linear combinations of amino acids that contribute to its classification as a binder (highlighted in green) or its classification as a non-binder (highlighted in red).

Multi-parameter optimization for developability by in silico screening of antibody sequence
space

Next, we characterized the full 3.1×10^6 deep learning predicted antigen-specific sequences on a
number of parameters to identify highly developable candidates compared to the original trastuzumab
sequence. As a preliminary metric, we investigated their sequence similarity to the original trastuzumab
sequence by calculating the *LD*. The majority of sequences showed an edit distance of *LD* > 4 (Figure
6a). The first step in filtering was to calculate the net charge and hydrophobicity index in order to
estimate the molecule's viscosity and clearance[2]. According to Sharma et al., viscosity decreases with
increasing variable fragment (Fv) net charge and increasing Fv charge symmetry parameter (FvCSP);
however, the optimal Fv net charge in terms of drug clearance is between 0 and 6.2 with a
CDRL1+CDRL3+CDRH3 hydrophobicity index sum (HI sum) < 4. Based on the wide range of values
for these parameters in the 3.1×10^6 predicted variants (Figure 6b, c), we filtered any sequences out
that had a FvCSP < 6.61 (trastuzumab FvCSP) or if they contained a Fv net charge > 6.2, and an HI
sum > 4, < 0. This filtering criteria greatly reduced the sequence space down to 4.02×10^5 variants. We
next padded the CDRH3 sequences with 10 amino acids on the 5' and 3' ends and then ran these
sequences through CamSol, a protein solubility predictor developed by Sormanni et al.[30], which
estimates and ranks sequence variants based on their theoretical solubility. The remaining variants
produced a wide-range of protein solubility scores (Figure 6d) and sequences with a score < 0.5
(trastuzumab score) were filtered out, leaving 14,125 candidates for further analysis. As a last step in
our *in silico* screening process, we aimed at reducing immunogenicity by predicting the peptide binding
affinity of the variant sequences to MHC Class II molecules by utilizing NetMHCIIpan, a model
previously developed by Jensen et al.[31]. One output from the model is a given peptide's % Rank of
predicted affinity compared to a set of 200,000 random natural peptides. Typically, molecules with a %
Rank < 2 are considered strong binders and those with a % Rank < 10 are considered weak binders to
the MHC Class II molecules scanned. All possible 15-mers from the padded CDRH3 sequences were
run through NetMHCIIpan. After predicting the affinities for a set of 26 HLA alleles determined to cover
over 98% of the global population[32], sequences were filtered out if any of the 15-mers contained a %
Rank < 5.5 (trastuzumab minimum % Rank) (Figure 6e). The number of 15-mers with a % Rank less
than 10 and the average % Rank across all 15-mers for the remaining sequences were also calculated.
Sequences with more than two 15-mers with a % Rank < 10 (Figure 6f) and those with an average %
Rank < 60.56 (trastuzumab average % Rank) were also filtered out (Figure 6g). All remaining 4,881
variants contain values equal to or greater than the parameters of the original trastuzumab sequence.
When applying this same filtering scheme on the 11,300 experimentally determined binding sequences
(obtained from training / test data), only 9 variants remained. Lastly, to determine the best developable
sequences, we calculated an overall developability improvement score based on the mean of
normalized values for each relevant parameter (see Materials and Methods), where trastuzumab would
have a developability improvement score equal to 0. Of the remaining 4,881 predicted binding
sequences, 293 variants were identified to have a higher developability score compared to the
maximum developability score of the 9 experimentally determined binding sequences (Figure 6h). The

filtering parameters and number of remaining variants at each step for the *in silico* library are provided

in Figure 6i.

Figure 6: In silico screening of predicted binders identifies globally optimized variants

Antigen specific variants result in a wide range of *in silico* calculated parameters for developability. The following are staggered histograms showing the parameter distributions of all deep learning (DL)-predicted binders (light) and the experimentally observed binders (dark) at the different stages of filtering. Red boxes indicate filtering cut-offs determined by the developability metric calculated for the original trastuzumab sequence. **(a)** Levenshtein distance from wild-type trastuzumab. **(b)** Net charge of the VH domain. **(c)** CDRH3 hydrophobicity index. **(d)** CamSol intrinsic solubility score. **(e)** The minimum NetMHCIIpan % Rank (< 2 ~ strong affinity; < 10 ~ weak affinity) across all possible 15-mers for a given CDRH3 sequence and across all HLA alleles. **(f)** The number of 15-mers found within a given CDRH3 sequence that have a % Rank < 10 across all alleles. **(g)** The average NetMHCIIpan % Rank across all possible 15-mers and HLA alleles. **(h)** Scatter/violin plot for the overall developability improvement score (Eq. 3) of the remaining sequence variants passing all filtering criteria. 293 sequences of the predicted binders have a higher overall developability improvement score than the maximum score identified from an experimental binder. **(i)** Filtering parameters and the number of sequences at the corresponding stage of filtering.

DISCUSSION

Addressing the limitation of antibody optimization in mammalian cells, we have developed an approach

based on deep learning that enables us to identify antigen-specific sequences with high precision.

Calculating and predicting various biophysical properties of antigen-specific variants allows for efficient

identification of the most developable antibody molecule, resulting in significant time and cost savings

and greatly reducing risk for downstream clinical development. Using the clinically approved antibody

trastuzumab, we performed single-site DMS followed by combinatorial mutagenesis to determine the
antigen-binding landscape of CDRH3. This DMS-based mutagenesis strategy is crucial for attaining
high quality training data that is enriched with antigen-binding variants, in this case nearly 10% of our
library (Figure 2d). In contrast, if a completely randomized combinatorial mutagenesis strategy was
employed (i.e., NNK degenerate codons), it would be unlikely to produce any significant fraction of
antigen-binding variants. In the future, other approaches to mutagenesis that generate enriched training
data[33], such as shotgun scanning mutagenesis[34], binary substitution[35] and recombination[14,36] may also
be explored for training deep neural networks.

Our initial single-site DMS libraries screened for enriched mutations through antigen-binding, yet
combining these mutations in a cohesive manner to alter biophysical properties while retaining high
antigen affinity is challenging. The amino acid composition of binding and non-binding variants is highly
similar (Figure 2e), and visually identifying the sequence patterns that lead to binding is a daunting, if
not impossible task. Moreover, structure-based modeling was unable to discriminate between binders
and non-binders as predicting fine-grained protein-complex affinities is highly challenging using
generalistic methods such as Rosetta[27]. This is compounded by introducing CDRH3 loop mutations
which likely result in challenging loop conformational changes[37]. While more advanced, ensemble-
based ddG prediction methods[38] could result in better performance, applying this to millions of
sequences may be infeasible, further exemplifying the value of deep neural networks that are able to
learn the high-dimensional space of antigen-binding sequences.

A remarkable finding in this study was that experimental screening of a library of only 5×10^4 variants,
which reflected a tiny fraction (0.0054%) of the total sequence diversity of the DMS-based combinatorial
mutagenesis library (7.17×10^8), was capable of training accurate neural networks. This suggests that
physical library size limitations of mammalian expression systems (or other expression platforms such
as phage and yeast) and deep sequencing read depth will not serve as a limitation for deep learning-
guided protein engineering. Another important result was that deep sequencing of antigen-binding and
non-binding populations showed nearly no observable difference in their positional amino acid usage
(Figure 2e), revealing that neural networks are effectively capturing high-dimensional and non-linear
patterns/interactions (Figure 5b).

In the current study, we selected LSTM-RNNs and CNNs as the basis of our classification models, as
they represent two state of the art approaches in deep learning. Other machine learning approaches
such as k-nearest neighbors, random forests, and support vector machines are also well-suited at
identifying complex patterns from input data, but as data set sizes continue to grow, as is realizable
with biological sequence data, deep neural networks tend to outperform these classical techniques[17].
Furthermore, deep generative modeling methods such as variational autoencoders and generative
adversarial networks may also be used to explore the mutagenesis sequence space from directed
evolution[39].

We *in silico* generated approximately 7.2×10^7 CDRH3 variants from DMS-based combinatorial
diversity and used fully trained LSTM-RNN and CNN models to classify each sequence as a binder or
non-binder. The 7.2×10^7 sequence variants comprise only a subset of the potential sequence space

and was chosen to minimize the computational effort, however, it still represents a library size several
orders of magnitude greater than what is experimentally achievable in mammalian cells. We easily
envision extending the screening capacity through script optimization and employing parallel computing
on high performance clusters. Out of all variants classified, the LSTM-RNN and CNN predicted
approximately 11-13% to bind the target antigen, showing exceptional agreement with the
experimentally observed frequencies by flow cytometry (Figure 2d). In order to experimentally validate
the precision of neural networks to predict antigen specificity, we randomly selected and expressed 30
variants from the library of sequences with a minimum edit distance of 5 from trastuzumab. The
precision of the LSTM-RNN and CNN models were each estimated to be ~85% (at $P > 0.75$) according
to predictions made on the test data sets (Figure 3b, d). By taking the consensus between models,
however, we experimentally validated that all randomly selected (30/30) of the antigen-predicted
sequences were indeed binders, and several of which were high affinity. While we anticipate false
positives would be observed by increasing the sample size tested, validation of this subset strongly
infers that potentially thousands of optimized lead candidates maintain a binding affinity in the range of
therapeutic relevance, while also containing substantial sequence variability from the starting
trastuzumab sequence. Future work to increase the stringency of selection during screening or a more
detailed investigation of correlations between prediction probability and affinity could prove insightful
towards retaining high target affinities. Experimentally validating the accuracy of the models to predict
the binding status of sequence variants led us to take a more in depth look at the sequence space of
predicted binding and non-binding variants. A sequence similarity network analysis at various *LD*s
revealed no distinct clusters between binding and non-binding sequences, indicating an overall
sequence similarity of both classifications. By then quantitatively analyzing neural network predictions,
we were able to shed light on the high-dimensional patterns captured by the respective models and
decipher amino acid combinations contributing to a sequence's classification.

Once an antibody's affinity for its target antigen is within a desirable range for efficacious biological
modification, addressing other biophysical properties becomes the focus of antibody development. With
recent advances in computational predictions[40,41], a number of these properties, including viscosity,
clearance, stability[2], specificity[42], solubility[30] and immunogenicity[31] can be approximated from sequence
information alone. With the aim of selecting antibodies with improved characteristics, we subjected the
library of predicted binders to a number of these *in silico* approaches in order to provide a ranking
structure and filtering strategy for developability (Figure 6). After implementing these methods to
remove variants with a high likelihood of having poor viscosity, clearance or solubility, as well as those
with high immunogenic potential, nearly 5,000 multi-parameter optimized antibody variants remained
with developability scores greater than the original trastuzumab sequence. Although a limited number
of developable sequences can be initially identified experimentally (Figure 6h), this only reflects a small
fraction of the highly-developable sequence space (0.2%). By screening *in silico* libraries, the presence
of every sequence variant within the defined space is guaranteed, ensuring the identification of globally
optimized sequences. Future work to apply more stringent or additional filters which address other
developability parameters (e.g. stability, specificity, humanization) could also be implemented to further
reduce the sequence space down to the most developable therapeutic candidates across even more

parameters. For instance, previous studies have investigated the likeness of therapeutic antibodies to

the human antibody repertoire[43]. We also envision this approach to enable the optimization of other

functional properties of therapeutic antibodies, such as pH-dependent antibody recycling[44] or

affinity/avidity tuning[45,46]. Additionally, extending this approach to other regions across the variable light

and heavy chain genes, namely other CDRs, may yield deep neural networks that are able to capture

long-range, complex relationships between an antibody and its target antigen. To explore these patterns

in greater depth, it may be useful to compare neural network predictions with other advanced structural

modeling techniques such as ones that take advantage of geometric deep learning[47].

METHODS

Mammalian cell culture and transfection

Hybridoma cells were cultured and maintained according to the protocols described by Mason et al.[23].

Hybridoma cells were electroporated with the 4D-Nucleofector™ System (Lonza) using the SF Cell Line

4D-Nucleofector® X Kit L or X Kit S (Lonza, V4XC-2024, V4XC-2032) with the program CQ-104. Cells

were prepared as follows: cells were isolated and centrifuged at 125 x G for 10 minutes, washed with

Opti-MEM® I Reduced Serum Medium (Thermo, 31985-062), and centrifuged again with the same

parameters. The cells were resuspended in SF buffer (per kit manufacturer guidelines), after which Alt-

R gRNA (IDT) and ssODN donor (IDT) were added. All experiments performed utilize constitutive

expression of Cas9 from *Streptococcus pyogenes* (SpCas9). Transfections of 1×10^6 and 1×10^7 cells

were performed in 100 μl, single Nucleocuvettes™ with 0.575 or 2.88 nmol Alt-R gRNA and 0.5 or 2.5

nmol ssODN donor respectively. Transfections of 2×10^5 cells were performed in 16-well, 20 μl

Nucleocuvette™ strips with 115 pmol Alt-R gRNA and 100 pmol ssODN donor.

Flow cytometry analysis and sorting

Flow cytometry-based analysis and cell isolation were performed using the BD LSR Fortessa™ (BD

Biosciences) and Sony SH800S (Sony), respectively. When labeling with fluorescently conjugated

antigen or anti-IgG antibodies, cells were first washed with PBS, incubated with the labeling antibody

and/or antigen for 30 minutes on ice, protected from light, washed again with PBS and then analyzed

or sorted. The labeling reagents and working concentrations are described in Supplementary Table 5.

For cell numbers different from 10^6, the antibody/antigen amount and incubation volume were adjusted

proportionally.

Sample preparation for deep sequencing

Sample preparation for deep sequencing was performed similar to the antibody library generation

protocol of the primer extension method described previously[48]. Genomic DNA was extracted from 1-

5×10^6 cells using the Purelink™ Genomic DNA Mini Kit (Thermo, K182001). Extracted genomic DNA

was subjected to a first PCR step. Amplification was performed using a forward primer binding to the

beginning of the VH framework region and a reverse primer specific to the intronic region immediately

3' of the J segment. PCRs were performed with Q5® High-Fidelity DNA polymerase (NEB, M0491L) in

parallel reaction volumes of 50 ml with the following cycle conditions: 98˚C for 30 seconds; 16 cycles

of 98˚C for 10 sec, 70˚C for 20 sec, 72˚C for 30 sec; final extension 72˚C for 1 min; 4˚C storage. PCR

products were concentrated using DNA Clean and Concentrator (Zymo, D4013) followed by 0.8X

SPRIselect (Beckman Coulter, B22318) left-sided size selection. Total PCR1 product was amplified in

a PCR2 step, which added extension-specific full-length Illumina adapter sequences to the amplicon

library. Individual samples were Illumina-indexed by choosing from 20 different index reverse primers.

Cycle conditions were as follows: 98°C for 30 sec; 2 cycles of 98°C for 10 sec, 40°C for 20 sec, 72°C

for 1 min; 6 cycles of 98°C for 10 sec, 65°C for 20 sec, 72°C for 1 min; 72°C for 5 min; 4°C storage.

PCR2 products were concentrated again with DNA Clean and Concentrator and run on a 1% agarose

gel. Bands of appropriate size (~550bp) were gel-purified using the Zymoclean™ Gel DNA Recovery

kit (Zymo, D4008). Concentration of purified libraries were determined by a Nanodrop 2000c

spectrophotometer and pooled at concentrations aimed at optimal read return. The quality of the final

sequencing pool was verified on a fragment analyzer (Advanced Analytical Technologies) using DNF-

473 Standard Sensitivity NGS fragment analysis kit. All samples passing quality control were

sequenced. Antibody library pools were sequenced on the Illumina MiSeq platform using the reagent

kit v3 (2x300 cycles, paired-end) with 10% PhiX control library. Base call quality of all samples was in

the range of a mean Phred score of 34.

Bioinformatics analysis and graphics

The MiXCR v2.0.3 program was used to perform data pre-processing of raw FASTQ files[49]. Sequences

were aligned to a custom germline gene reference database containing the known sequence

information of the V- and J-gene regions for the variable heavy chain of the trastuzumab antibody gene.

Clonotype formation by CDRH3 and error correction were performed as described by Bolotin et al[49].

Functional clonotypes were discarded if: 1) a duplicate CDRH3 amino acid sequence arising from

MiXCR uncorrected PCR errors, or 2) a clone count equal to one. Downstream analysis was performed

using R v3.2.2[50] and Python v3.6.5[51]. Graphics were generated using the R packages ggplot2[52],

RColorBrewer[53], and ggseqlogo[54].

Calculation of enrichment ratios (ERs) in DMS

455 The ERs of a given variant was calculated according to previous methods[55]. Clonal frequencies of

456 variants enriched for antigen specificity by FACS, $f_{i,Ag+}$, were divided by the clonal frequencies of the

457 variants present in the original library, $f_{i,Ab+}$, according to Equation 1.

458
$$ER = \frac{f_{i,Ag+}}{f_{i,Ab+}}$$

459 *(Eq. 1)*

460 A minimum value of -2 was designated to variants with log[ER] values less than or equal -2 and variants

461 not present in the dataset were disregarded in the calculation. A clone was defined based on the exact

462 a.a. sequence of the CDRH3.

Redesign of trastuzumab in Rosetta for diversity of sequences

The Rosetta program[27] was used to redesign the trastuzumab antibody in complex with the extracellular

domain of HER2 (PDB id: 1N8Z)[25]. Ten residues in the CDRH3 loop of trastuzumab (residues 98-108

of the heavy chain) were allowed to mutate to any natural amino acid, while all other residues were

allowed to change rotameric conformation. A RosettaScript invoked the PackRotamersMover, a

stochastic MonteCarlo algorithm, to optimize the sequence of the antibody to CDRH3 according to the

Rosetta energy function, followed by backbone minimization. Energies were computed using Rosetta's

ddG filter. Rosetta was run to generate 5000 sequences stochastically, and this resulted in 48

sequences. Rosetta's output files were processed using RS-Toolbox[56].

Classification of experimentally-determined sequences in Rosetta

Each of the 11,300 binding and 27,539 non-binding sequences from the combinatorial library were

modelled in Rosetta[27]. For each experimentally-determined binding or non-binding sequence, the

structure of the HER2:trastuzumab complex was used as input and the residues diverging from the

wildtype were mutated using the PackRotamersMover in RosettaScripts[57]. The backbone and the side

chains were minimized with Rosetta's MinMover after the sequence was modeled to optimized intra-

and inter-chain contacts. Rosetta's predicted interface score (ddG) was used as the relative

classification score.

Codon selection for rational library design

Codon selection for rational library design was based off the equation provided by Mason et al.[23],

(Equation 2), where $Y_{n,deg}$ represents the amino acid frequency for a given degenerate codon scheme,

$Y_{n,target}$ is the target amino acid frequency, and n is the number of amino acids, 20. Residues identified

in DMS analysis to have a positive enrichment (ER > 1, or log[ER] > 0) were normalized according to

their enrichment ratios and were converted to theoretical frequencies and taken as the target amino

acid frequencies. Degenerate codon schemes were then selected which most closely reflect these

frequencies as calculated by the mean squared error between the degenerate codon and the target

frequencies.

489
$$Optimal\ Codon\ =\ arg_x min(\frac{1}{n}\sum_{i=1}^{n}(Y_{n,deg} - Y_{n,target})^2)$$

490   *(Eq. 2)*

491   In certain instances, if the selected degenerate codon did not represent desirable amino acid

492   frequencies or contained undesirable amino acids, a mixture of degenerate codons were selected and

493   pooled together to achieve better coverage of the functional sequence space.

Deep learning model construction

Machine learning models were built in Python v3.6.5. LSTM-RNNs, and CNNs were built using the

Keras[58] v2.1.6 Sequential model as a wrapper for TensorFlow[59] v1.8.0. Model architecture and

hyperparameters were optimized by performing a grid search of relevant variables for a given model.

These variables include nodes per layer, activation function(s), optimizer, loss function, dropout rate,

batch size, number of epochs, number of filters, kernel size, stride length, and pool size. Grid searches
were performed by implementing a k-fold cross validation of the data set.

Deep learning model training and testing

Data sets for antibody expressing, non-binding, and binding sequences (Sequencing statistics:
Supplementary Tables 1, 2) were aggregated to form a single, binding/non-binding data set where
antibody expressing sequences were classified as non-binders, unless also identified among the
binding sequences. Sequences from one round of antigen enrichment were excluded from the training
data set. The complete, aggregated data set was then randomly arranged and appropriate class labeled
sequences were removed to achieve the desired classification ratio of binders to non-binders (50/50,
20/80, 10/90, and non-adjusted). The class adjusted data set was further split into a training set (70%),
and two testing sets (15% each), where one test set reflected the classification ratio observed for
training and the other reflected a classification ratio of approximately 10/90 to resemble the
physiological expected frequency of binders.

Sequence similarity and model attribution analysis of predicted variants

Sequence similarity networks of sequences predicted to be antigen positive and antigen negative were
constructed for Levenshtein Distance 1-6 were constructed using the igraph R package[60] v1.2.4. The
resulting networks were analyzed with respect to their overall connectivity, the composition of their
largest clusters and the overall degree distribution between the classes.

The Integrated Gradients technique[29] was used to assess the relative attribution of each feature of a
given input sequence towards the final prediction score. First, a baseline was obtained by zeroing out
the input vector and the path integral of the gradients from baseline to the input vector was then
approximated with a step size of 100. Integrated gradients were visualized as sequence logos.
Sequence logos were created by the python module Logomaker[61].

In silico sequence classification and sequence parameters

All possible combinations of amino acids present in the DMS-based combinatorial mutagenesis libraries
were used to calculate the total theoretical sequence space of 7.17×10^8. 7.2×10^7 sequence variants
were generated *in silico* by taking all possible combinations of the amino acids used per position in the
combinatorial mutagenesis library designed from the DMS data following three rounds of enrichment
for antigen binding variants (Supplementary Fig. 2c, 3c); Alanine was also selected to be included at
position 103. All *in silico* sequences were then classified as a binder or non-binder by the trained LSTM-
RNN and CNN models. Sequences were selected for further analysis if they were classified in both
models with a prediction probability (*P*) of more than 0.75.

The Fv net charge and Fv charge symmetry parameter (FvCSP) were calculated as described by
Sharma et al. Briefly, the net charge was determined by first solving the Henderson-Hasselbalch
equation for each residue at a specified pH (here 5.5) with known amino acid pKas[62]. The sum across
all residues for both the VL and VH was then calculated as the Fv net charge. The FvCSP was
calculated by taking the product of the VL and VH net charges. The hydrophobicity index (HI) was also
calculated as described by Sharma et al., according to the following equation: $HI = -(\sum n_i E_i / \sum n_j E_j)$. E

represents the Eisenberg value of an amino acid, n is the number of an amino acid, and i and j are

hydrophobic and hydrophilic residues respectively.

The protein solubility score was determined for each, full-length CDRH3 sequence (15 a.a.) padded

with 10 amino acids on both the 5' and 3' ends (35 a.a.) by the CamSol method[30] at pH 7.0.

The binding affinities for a reference set of 26 HLA alleles[32] were determined for each 15-mer contained

within the 10 amino acid padded CDRH3 sequence (35 a.a.) by NetMHCIIpan 3.2[31]. The output provides

for each 15-mer a predicted affinity in nM and the % Rank which reflects the 15-mer's affinity compared

to a set of random natural peptides. The % Rank measure is unaffected by the bias of certain molecules

against stronger or weaker affinities and is used to classify peptides as weak or strong binders towards

the specified MHC Class II allele. The minimum % Rank, the number of 15-mers with % Rank less than

10 (classification of weak binder), and the average % Rank were calculated across all 21 15-mers for

a single CDRH3 sequence across all 26 HLA alleles.

Overall developability improvement of the antibody sequences was determined by first normalizing the

FvCSP, CamSol score, and average NetMHCII % Rank according to the range of values observed in

the remaining sequences post-filtering. The normalized CamSol protein solubility score was then

weighted by a factor of 2 for its importance in determining developability. Lastly, the mean across these

three parameters was taken to produce the overall developability improvement score. Since the

sequences were filtered with the calculated values for trastuzumab, trastuzumab would have an overall

developability improvement equal to 0.

$Overall\ developability$

557
$$= \frac{1}{3}\left(\left(\frac{FvCSP - \min(FvCSP)}{\max(FvCSP) - \min(FvCSP)}\right) + 2*\left(\frac{CamSol - \min(CamSol)}{\max(CamSol) - \min(CamSol)}\right)\right.$$

558
$$\left. + \left(\frac{avgNetMHC - \min(avgNetMHC)}{\max(avgNetMHC) - \min(avgNetMHC)}\right)\right)$$

(Eq. 3)

Affinity measurements by biolayer interferometry

Monoclonal populations of the individual variants were isolated by performing a single-cell sort.

Following expansion, supernatant for all variants was collected and filtered through a 0.20 μm filter

(Sartorius, 16534-K). Affinity measurements were then performed on an Octet RED96e (FortéBio) with

the following parameters. Anti-human capture sensors (FortéBio, 18-5060) were hydrated in

conditioned media diluted 1 in 2 with kinetics buffer (FortéBio, 18-1105) for at least 10 minutes before

conditioning through 4 cycles of regeneration consisting of 10 seconds incubation in 10 mM glycine, pH

1.52 and 10 seconds in kinetics buffer. Conditioned sensors were then loaded with 0 μg/mL (reference

sensor), 10 μg/mL trastuzumab (reference sample), or hybridoma supernatant (approximately 20

μg/mL) diluted 1 in 2 with kinetics buffer followed by blocking with mouse IgG (Rockland, 010-0102) at

50 μg/mL in kinetics buffer. After blocking, loaded sensors were equilibrated in kinetics buffer and

incubated with either 5 nM or 25 nM HER2 protein (Sigma-aldrich, SRP6405-50UG). Lastly, sensors

were incubated kinetics buffer to allow antigen dissociation. Kinetics analysis was performed in analysis

software Data Analysis HT v11.0.0.50.

ACKNOWLEDGEMENTS

We acknowledge the ETH Zurich D-BSSE Single Cell Unit and the ETH Zurich D-BSSE Genomics

Facility for support, in particular, M. Di Tacchio, A. Gumienny, E. Burcklen, and C. Beisel. We also thank

the Vendruscolo Lab (Cambridge, UK), in particular P. Sormanni, for assistance with implementing the

CamSol method on large libraries, as well as the group of Prof. Morten Nielson (DTU, Denmark) for

providing an easy-to-use package for MHC Class II affinity predictions. Funding was provided by the

National Competence Center for Research on Molecular Systems Engineering.

AUTHOR CONTRIBUTIONS

D.M.M., S.F., C.R.W. and S.T.R. developed the methodology; D.M.M. and S.T.R. designed the

experiments and wrote the manuscript; D.M.M., C.R.W. and S.F. analyzed sequencing data and

performed deep learning analysis; P.G. and B.E.C. designed and performed structural modelling

experiments and analysis; C.J. generated in silico libraries; D.M.M. performed experiments; B.W., and

S.M.M. performed cell line development.

COMPETING INTERESTS

ETH Zurich has filed for patent protection on the technology described herein, and D.M.M., S.F.,

C.R.W., and S.T.R. are named as co-inventors on this patent (United States Patent and Trademark

Office Provisional Application: 62/831,663).

REFERENCES

1.   Paul, S. M. *et al.* How to improve R&D productivity: the pharmaceutical industry's grand challenge.

Nat. Rev. Drug Discov. **9**, 203–214 (2010).

2.   Sharma, V. K. *et al.* In silico selection of therapeutic antibodies for development: Viscosity,

clearance, and chemical stability. *Proc. Natl. Acad. Sci.* **111**, 18601–18606 (2014).

3.   Jain, T. *et al.* Biophysical properties of the clinical-stage antibody landscape. *Proc. Natl. Acad. Sci.*

114, 944–949 (2017).

4.   Hu, D. *et al.* Effective Optimization of Antibody Affinity by Phage Display Integrated with High-

Throughput DNA Synthesis and Sequencing Technologies. *PLOS ONE* **10**, e0129125 (2015).

5. Bos, A. B. *et al.* Development of a semi-automated high throughput transient transfection system.
J. Biotechnol. **180**, 10–16 (2014).

6. Tomar, D. S., Kumar, S., Singh, S. K., Goswami, S. & Li, L. Molecular basis of high viscosity in
concentrated antibody solutions: Strategies for high concentration drug product development.
mAbs **8**, 216–228 (2016).

7. Roth, E. M. *et al.* Antidrug Antibodies in Patients Treated with Alirocumab. *N. Engl. J. Med.* **376**,
1589–1590 (2017).

8. Greiff, V. *et al.* Learning the High-Dimensional Immunogenomic Features That Predict Public and
Private Antibody Repertoires. *J. Immunol.* ji1700594 (2017). doi:10.4049/jimmunol.1700594

9. Christensen, T., Frandsen, A., Glazier, S., Humpherys, J. & Kartchner, D. Machine Learning
Methods for Disease Prediction with Claims Data. in *2018 IEEE International Conference on*
Healthcare Informatics (ICHI) 467–4674 (2018). doi:10.1109/ICHI.2018.00108

10. Packer, M. S. & Liu, D. R. Methods for the directed evolution of proteins. *Nat. Rev. Genet.* **16**, 379–
394 (2015).

11. Fox, R. *et al.* Optimizing the search algorithm for protein engineering by directed evolution. *Protein*
Eng. Des. Sel. **16**, 589–597 (2003).

12. Fox, R. Directed molecular evolution by machine learning and the influence of nonlinear
interactions. *J. Theor. Biol.* **234**, 187–199 (2005).

13. Romero, P. A., Krause, A. & Arnold, F. H. Navigating the protein fitness landscape with Gaussian
processes. *Proc. Natl. Acad. Sci.* **110**, E193–E201 (2013).

14. Bedbrook, C. N., Yang, K. K., Rice, A. J., Gradinaru, V. & Arnold, F. H. Machine learning to design
integral membrane channelrhodopsins for efficient eukaryotic expression and plasma membrane
localization. *PLOS Comput. Biol.* **13**, e1005786 (2017).

15. Angermueller, C., Pärnamaa, T., Parts, L. & Stegle, O. Deep learning for computational biology.
Mol. Syst. Biol. **12**, 878 (2016).

16. Wainberg, M., Merico, D., Delong, A. & Frey, B. J. Deep learning in biomedicine. *Nat. Biotechnol.*
36, 829–838 (2018).

17. Alipanahi, B., Delong, A., Weirauch, M. T. & Frey, B. J. Predicting the sequence specificities of
DNA- and RNA-binding proteins by deep learning. *Nat. Biotechnol.* **33**, 831–838 (2015).

18. Cuperus, J. T. *et al.* Deep learning of the regulatory grammar of yeast 5′ untranslated regions from

500,000 random sequences. *Genome Res.* (2017). doi:10.1101/gr.224964.117

19. Bulik-Sullivan, B. *et al.* Deep learning using tumor HLA peptide mass spectrometry datasets

improves neoantigen identification. *Nat. Biotechnol.* **37**, 55–63 (2019).

20. LeCun, Y., Bengio, Y. & Hinton, G. Deep learning. *Nature* **521**, 436–444 (2015).

21. Rosenblatt, F. The Perceptron, a Perceiving and Recognizing Automation. (1957).

22. Pogson, M., Parola, C., Kelton, W. J., Heuberger, P. & Reddy, S. T. Immunogenomic engineering

of a plug-and-(dis)play hybridoma platform. *Nat. Commun.* **7**, 12535 (2016).

23. Mason, D. M. *et al.* High-throughput antibody engineering in mammalian cells by CRISPR/Cas9-

mediated homology-directed mutagenesis. *Nucleic Acids Res.* (2018). doi:10.1093/nar/gky550

24. Whitehead, T. A. *et al.* Optimization of affinity, specificity and function of designed influenza

inhibitors using deep sequencing. *Nat. Biotechnol.* **30**, 543 (2012).

25. Cho, H.-S. *et al.* Structure of the extracellular region of HER2 alone and in complex with the

Herceptin Fab. *Nature* **421**, 756–760 (2003).

26. Rose, A. S. *et al.* NGL viewer: web-based molecular graphics for large complexes. *Bioinformatics*

34, 3755–3758 (2018).

27. Leaver-Fay, A. *et al.* Chapter nineteen - Rosetta3: An Object-Oriented Software Suite for the

Simulation and Design of Macromolecules. in *Methods in Enzymology* (eds. Johnson, M. L. &

Brand, L.) **487**, 545–574 (Academic Press, 2011).

28. Miho, E., Roškar, R., Greiff, V. & Reddy, S. T. Large-scale network analysis reveals the sequence

space architecture of antibody repertoires. *Nat. Commun.* **10**, 1321 (2019).

29. Sundararajan, M., Taly, A. & Yan, Q. Axiomatic Attribution for Deep Networks. *ArXiv170301365 Cs*

(2017).

30. Sormanni, P., Aprile, F. A. & Vendruscolo, M. The CamSol Method of Rational Design of Protein

Mutants with Enhanced Solubility. *J. Mol. Biol.* **427**, 478–490 (2015).

31. Jensen, K. K. *et al.* Improved methods for predicting peptide binding affinity to MHC class II

molecules. *Immunology* **154**, 394–406 (2018).

32. Greenbaum, J. *et al.* Functional classification of class II human leukocyte antigen (HLA) molecules

reveals seven different supertypes and a surprising degree of repertoire sharing across supertypes.

Immunogenetics **63**, 325–335 (2011).

33. Wu, Z., Kan, S. B. J., Lewis, R. D., Wittmann, B. J. & Arnold, F. H. Machine learning-assisted
directed protein evolution with combinatorial libraries. *Proc. Natl. Acad. Sci.* 201901979 (2019).
doi:10.1073/pnas.1901979116

34. Vajdos, F. F. *et al.* Comprehensive Functional Maps of the Antigen-binding Site of an Anti-ErbB2
Antibody Obtained with Shotgun Scanning Mutagenesis. *J. Mol. Biol.* **320**, 415–428 (2002).

35. Townsend, S. *et al.* Augmented Binary Substitution: Single-pass CDR germ-lining and stabilization
of therapeutic antibodies. *Proc. Natl. Acad. Sci.* **112**, 15354–15359 (2015).

36. Trudeau, D. L., Smith, M. A. & Arnold, F. H. Innovation by homologous recombination. *Curr. Opin.*
Chem. Biol. **17**, 902–909 (2013).

37. Weitzner, B. D. *et al.* Modeling and docking of antibody structures with Rosetta. *Nat. Protoc.* **12**,
401–416 (2017).

38. Barlow, K. A. *et al.* Flex ddG: Rosetta Ensemble-Based Estimation of Changes in Protein–Protein
Binding Affinity upon Mutation. *J. Phys. Chem. B* **122**, 5389–5399 (2018).

39. Riesselman, A. J., Ingraham, J. B. & Marks, D. S. Deep generative models of genetic variation
capture the effects of mutations. *Nat. Methods* **15**, 816–822 (2018).

40. Sormanni, P., Aprile, F. A. & Vendruscolo, M. Third generation antibody discovery methods: in
silico rational design. *Chem. Soc. Rev.* **47**, 9137–9157 (2018).

41. Raybould, M. I. J. *et al.* Five computational developability guidelines for therapeutic antibody
profiling. *Proc. Natl. Acad. Sci.* **116**, 4025–4030 (2019).

42. Rabia, L. A., Zhang, Y., Ludwig, S. D., Julian, M. C. & Tessier, P. M. Net charge of antibody
complementarity-determining regions is a key predictor of specificity. *Protein Eng. Des. Sel.* (2019).
doi:10.1093/protein/gzz002

43. Abhinandan, K. R. & Martin, A. C. R. Analyzing the "Degree of Humanness" of Antibody
Sequences. *J. Mol. Biol.* **369**, 852–862 (2007).

44. Igawa, T. *et al.* Antibody recycling by engineered pH-dependent antigen binding improves the
duration of antigen neutralization. *Nat. Biotechnol.* **28**, 1203–1207 (2010).

45. Kang, J. C. *et al.* Engineering a HER2-specific antibody–drug conjugate to increase lysosomal
delivery and therapeutic efficacy. *Nat. Biotechnol.* 1 (2019). doi:10.1038/s41587-019-0073-7

46. Slaga, D. *et al.* Avidity-based binding to HER2 results in selective killing of HER2-overexpressing
cells by anti-HER2/CD3. *Sci. Transl. Med.* **10**, eaat5775 (2018).

47. Gainza, P. *et al.* Deciphering interaction fingerprints from protein molecular surfaces. *bioRxiv*
606202 (2019). doi:10.1101/606202

48. Menzel, U. *et al.* Comprehensive Evaluation and Optimization of Amplicon Library Preparation
Methods for High-Throughput Antibody Sequencing. *PLoS ONE* **9**, e96727 (2014).

49. Bolotin, D. A. *et al.* MiXCR: software for comprehensive adaptive immunity profiling. *Nat. Methods*
12, 380–381 (2015).

50. R. Development Core Team. *R: A Language and Environment for Statistical Computing.* (R
Foundation for Statistical Computing).

51. van Rossum, G. & Drake, F. L. *The Python Language Reference Manual.* (Network Theory Ltd.,
2011).

52. Wickham, H. *ggplot2: Elegant Graphics for Data Analysis.* (Springer International Publishing,
2016).

53. Brewer, C. A., Hatchard, G. W. & Harrower, M. A. ColorBrewer in Print: A Catalog of Color Schemes
for Maps. *Cartogr. Geogr. Inf. Sci.* **30**, 5–32 (2003).

54. Wagih, O. ggseqlogo: a versatile R package for drawing sequence logos. *Bioinformatics* **33**, 3645–
3647 (2017).

55. Fowler, D. M. *et al.* High-resolution mapping of protein sequence-function relationships. *Nat.*
Methods **7**, 741 (2010).

56. Bonet, J., Harteveld, Z., Sesterhenn, F., Scheck, A. & Correia, B. E. rstoolbox - a Python library for
large-scale analysis of computational protein design data and structural bioinformatics. *BMC*
Bioinformatics **20**, 240 (2019).

57. Fleishman, S. J. *et al.* RosettaScripts: A Scripting Language Interface to the Rosetta
Macromolecular Modeling Suite. *PLOS ONE* **6**, e20161 (2011).

58. Chollet, F. Keras. (2015). Available at: https://keras.io/. (Accessed: 24th April 2019)

59. Abadi, M. *et al.* TensorFlow: A System for Large-scale Machine Learning. in *Proceedings of the*
12th USENIX Conference on Operating Systems Design and Implementation 265–283 (USENIX
Association, 2016).

60. Csárdi, G. & Nepusz, T. The igraph software package for complex network research. in (2006).

61. Tareen, A. & Kinney, J. B. Logomaker: Beautiful sequence logos in python. *bioRxiv* 635029 (2019).
doi:10.1101/635029

62. Kline, P. Amino Acid pKa Values and Side Chain Identities. (2006). Available at:

http://homepage.smc.edu/kline_peggy/Organic/Amino_Acid_pKa.pdf. (Accessed: 24th April 2019)