Title

Differential Expression Gene Explorer (DrEdGE): A tool for generating interactive online data

visualizations for exploration of quantitative transcript abundance datasets

Authors

Sophia C. Tintori(1), Patrick Golden(2), Bob Goldstein(1)*

Affiliations

(1) Department of Biology, University of North Carolina at Chapel Hill, Chapel Hill, NC 27599,

USA

(2) School of Information and Library Science, University of North Carolina at Chapel Hill,

Chapel Hill, NC 27599, USA

* Correspondence: bobg@unc.edu

Abstract

As the scientific community becomes increasingly interested in data sharing, there is a growing

need for tools that facilitate the querying of public data. Mining of RNA-seq datasets, for

example, has value to many biomedical researchers, yet is often effectively inaccessible to non-

genomicist experts, even when the raw data are available. Here we present DrEdGE

(dredge.bio.unc.edu), a free Web-based tool that facilitates data sharing between genomicists and

their colleagues. The DrEdGE software guides genomicists through easily creating interactive

online data visualizations, which colleagues can then explore and query according to their own

conditions to discover genes, samples, or patterns of interest. We demonstrate DrEdGE's

features with three example websites we generated from publicly available datasets—human

neuronal tissue, mouse embryonic tissue, and a *C. elegans* embryonic series. DrEdGE increases

the utility of large genomics datasets by removing the technical obstacles that prevent interested

parties from exploring the data independently.

Keywords

data sharing, data mining, data access, interactive, data visualization, high throughput

sequencing, next generation sequencing, RNA-seq, differential expression

Background

Data sharing, in the interest of transparency, openness, and reproducibility, is

increasingly becoming embraced by the scientific community[1-6]. The practice of data sharing

allows colleagues to independently reproduce and verify analyses, and to build future research

upon them more reliably. In burgeoning big data fields such as genomics, sharing enables data

mining, wherein other researchers can perform their own analyses on large, multivalent datasets

that may have only been used for a small fraction of possible applications at the time of initial

publication[7-9].

Currently, the primary method for sharing data is to publish raw data on databases, such

as the NCBI Gene Expression Omnibus, the NCBI Sequence Read Archive, DNA Data Bank of

Japan, European Nucleotide Archive, Figshare, and Dryad[10-15]. These raw data repositories are

critical, as they allow for independent analyses from entirely unprocessed material. Also critical

are tools for sharing partially processed data in an interactive format. Such tools facilitate

communication with non-genomicist collaborators and colleagues by allowing them to explore

the data without having to reprocess them starting from the rawest form, which can be

considerably, often prohibitively, time consuming. Without such tools, the data may be available

but are not effectively accessible to most non-genomicist researchers[16,17].

Genome browsers (such as those of UCSC[18], Ensembl[19], and NCBI[20]) represent one such

type of interactive tool that allows researchers to explore partially processed data. Users can

browse sequencing read density at each nucleotide in the genome from a given experiment,

alongside annotation of genomic features such as introns and exons, GC content, repeats, and

conservation scores. While this kind of tool is critically useful for visually identifying patterns in

the data, users cannot generate statistical results, nor easily ask biological questions that span

more than one locus. As sequencing costs continue to drop[21] and multiplexing technology

becomes more sophisticated[22-24], the rate at which large multivalent datasets are generated is

increasing[25]. In turn, the need for tools that make these datasets accessible continues to grow.

To address this need, we have created the Differential Expression Gene Explorer

(DrEdGE, dredge.bio.unc.edu), a web-based interactive data visualization tool. DrEdGE allows

genomics researchers to share their datasets in a readily accessible, queryable format, and allows

collaborators or colleague to explore the datasets and identify genes or samples of interest.

DrEdGE's flexible design can be used to visualize any number of sample types, and any type of

quantitative unit (transcripts, DNA fragments, proteins, etc.), using any statistical model for

differential expression. The user can interact with three different data representations on a

DrEdGE website—a differential expression plot, a statistical table, and an experiment-wide heat

map—which each feed into the other representations, creating an iterative workflow that can be

cycled through repeatedly for the continuous fine tuning or elaboration of hypotheses. We

provide a video to illustrate the features of a DrEdGE website

(https://vimeo.com/336521735/c1e473b81e), and a video to guide researchers in creating their

own DrEdGE website (https://vimeo.com/336521569/816b9585d8).

Results

GENERAL PROPERTIES

DrEdGE is designed to connect two groups of researchers: those who create, process, and

publish genomic datasets, and those interested in asking biological questions of genomic data

(who may or may not have specialized computational genomics skills). In this manuscript we

distinguish between these two types of users. The first user—the author—makes an interactive

DrEdGE website by importing their dataset. The author can publish this website alongside their

data and analyses in a peer-reviewed journal, or he or she can share it privately with colleagues.

The second user—the reader—explores the DrEdGE website, querying the data with his or her

own biological questions.

We will first describe the DrEdGE Web application, as used by the reader for exploration

and analysis of biological data. Then, we will describe a few sample datasets used to make

sample DrEdGE websites. Finally, we will describe the process by which the author prepares and

uploads a new dataset to create his or her own novel DrEdGE website.

PRIMARY FEATURES OF DREDGE VISUALIZATION

The DrEdGE website displays gene expression data based on two variables: (1) units of

genetic material (i.e. cDNA, genome fragments, proteins—because we showcase RNA-seq

experiments in examples below, we will call these units "transcripts"), and (2) sets of

experimental replicates (i.e. tissue types, chemical treatments, stages in a time course—we will

call these units "treatments") within an experiment.

Three visual elements make up the visualization: (1) a dot plot displaying relative

abundance of transcripts between two treatments, (2) a data table listing transcript abundance

measurements and statistics, and (3) a heat map displaying the relative abundances of transcripts

across every treatment in the experiment. Results from each data representation can be used as

input for another representation, allowing the user to build upon their hypotheses in an iterative

fashion. A video description of these features is available at

https://vimeo.com/336521735/c1e473b81e.

MA plot - The reader begins an investigation by selecting two treatments to compare

(Figure 1A). Treatments are selected from either a vector graphic representing the dataset, or a

simple dropdown menu in which all treatments are listed. The treatments will then populate the

rest of the visualization, starting with the MA (log ratio *M* by mean average *A*) plot, which

describes differential abundance (in RPKM or otherwise normalized values) between the two

treatments for all transcripts (Figure 1B). These plots are commonly used to visualize how

abundant a transcript is and how specifically it is enriched in one treatment over another. Each

dot on this plot represents one or more transcripts. Transcripts in the top half are more abundant

in the treatment specified above the plot, and those on the bottom half are more abundant in the

treatment specified below. Transcripts to the right of the plot have a greater average abundance

than those to the left. The reader selects transcripts in an area of the MA plot by brushing

(clicking and dragging) with the mouse, and transcripts selected in this way then populate further

elements of the visualization. The reader can filter out transcripts by p-value of differential

abundance by sliding the p-value cutoff selector (Figure 1C).

Data table – Transcripts highlighted on the MA plot appear in the table to the right

(Figure 1D). This table displays the fold change values between the two treatments selected, p-

values for fold change, and transcript abundance values for each treatment. The reader can then

sort the transcripts by name, average abundance, ratio of abundances between the two treatments,

or p-value. Abundance levels for each treatment are available both as mean and median, which

allows some insight into the distribution of data across replicates.

The reader can curate a list of transcripts of note by adding them to a "watched" list in the

data table. These watched transcripts will persist in the table, highlighted by red dots, when no

area is brushed and when new treatments are selected for comparison. Watched transcripts can

be added or removed, allowing the reader to curate a list of transcripts that fit multiple criteria

spanning several pairwise comparisons. To add transcripts one-by-one to the watched list, the

reader can either click the arrow next to a selected transcript name on the table, or type

transcripts in a search bar. To add groups of transcripts to the watched list, the user can upload a

comma delineated file with one transcript name on each line, or the user can click "watch

selected," which will add all transcripts currently brushed over on the plot. To remove transcripts

the reader either clicks the X next to each transcript on the table, brushes over a region of the

MA plot then clicks "remove selected," or clicks "remove all." At any point the reader can

export their current list of watched transcripts.

As the user hovers over or clicks transcripts in the data table, the visualization updates to

display additional information. First, an orange circle appears in the MA plot around that

transcript's position. Second, a heat map diagram is populated under the table, showing the

relative abundance of the transcript for all treatments within the dataset.

Heat map – The heat map (Figure 1E) graphically represents abundances of a single

transcript across all experimental treatments. This feature allows a reader to examine the

experiment-wide context for a transcript that was selected based on just a pairwise comparison.

If the heat map reveals that another treatment besides the two selected for the MA plot is of

interest, the reader can click on that treatment's icon to replace the top or bottom treatment in the

MA plot. Heat maps may be shown as a grid of boxes (as in Figure 1F), as illustrated icons (as in

Figure 1G), or both.

Iterative analysis – Data points from each of the three data representations—the MA plot,

the table, and the heat map—can be further investigated in one of the other representations: A

transcript with an interesting differential abundance in the MA plot can be selected to populate

the table, a transcript with interesting statistical values in the table can be selected to generate an

experiment-wide heat map, and treatments with an interesting transcript abundance in the context

of the whole experiment can be selected to generate a new MA plot. Curated lists of transcripts

of interest can be generated, added to, and pruned continuously (Figure 1H). The export and

import functions (Figure 1I) allow analyses to be continued across datasets and experiments, if

transcript names remain consistent across experiments.

EXAMPLE DATASETS FROM HUMAN, MOUSE, AND WORM

To demonstrate the utility of DrEdGE we have generated three sample DrEdGE websites

using data mined from published human, mouse, and worm RNA-seq studies. These examples

showcase a range of options for heat map graphics (Figure 2A-E), each designed to suit the

different sizes and biological features of the dataset. The final input files for these websites are

available in Supplementary File 1, and can be referenced as templates for new DrEdGE websites.

Although we have generated these examples from publicly available datasets, we strongly

encourage the lab generating and analyzing original data to create a DrEdGE website themselves.

This will ensure that the website is created with the most thorough understanding of the

idiosyncrasies of the data, and the statistics they require.

Forty-two whole embryo C. elegans developmental time points- Total RNA-seq data from whole

C. elegans embryos were mined from Boeck et al, 2016[26] to create dredge.bio.unc.edu/c-elegans-

timecourse. In this study, RNA abundance was reported for forty-two time points from 28 to 737

minutes after the two-cell stage.

Because these samples were numerous and have a linear relationship to each other, we

graphically represented them in the heat map using box icons in a custom arrangement, as shown

in Figure 2B.

Nine neuronal tissues from humans- Human total RNA sequencing data were mined from the

ENCODE consortium[4]. We selected nine neuronal tissues—camera-type eye, cerebellum,

diencephalon, frontal cortex, occipital lobe, parietal lobe, spinal cord, temporal lobe, and tibial

nerve—to generate dredge.bio.unc.edu/human-neuronal-tissue. All libraries were originally

prepared and sequenced by the Gingeras lab for the ENCODE consortium.

Because the number of treatments used was relatively small, and because the treatments

have a spatial and anatomical relationship to each other, we created custom SVG icons to

illustrate each tissue type in the heat map data representation, as shown in Figure 2C.

Forty embryonic tissues from mice- Mouse polyadenylated RNA sequencing data were mined

from the ENCODE consortium[4] to create dredge.bio.unc.edu/mouse-embryonic-tissue. Sixteen

tissue or cell types were selected: embryonic facial prominence, forebrain, heart, hindbrain,

intestine, kidney, limb, liver, midbrain, neural tube, skeletal muscle tissue, spleen, stomach,

C2C12 cells, C3H10T1/2 cells, and C3H myocyte cells from C2C12. All samples were prepared

and sequenced by the Wold lab for the ENCODE consortium.

Because these samples are numerous we used the default box icons, rather than

illustrations, to represent them in the heat map. Because the samples can each be defined by two

factors—time point and tissue type—we organized the icons in a custom 2D grid, with each row

describing a developmental stage and each column describing a tissue type, as shown in Figure

2D. In some instances, it may be appropriate to show treatments defined in space *and* time with

illustrative icons, as in the example from Tintori et al 2016 shown Figure 2E[27].

USAGE STEPS FOR GENERATING A DREDGE WEBSITE

Specific detail about the format and function of each file is provided in Supplementary File 2, on

the DrEdGE configuration page (http://dredge.bio.unc.edu/blank/?page=configure) and in the

instructional video (https://vimeo.com/336521569/816b9585d8). Here we present a brief

summary.

Coding requirements - We designed the DrEdGE software such that no coding is necessary to

create a DrEdGE website, if the author starts with normalized transcript abundance data. If

starting from sequence files (.fasta or .fastq), the author must independently align reads to the

genome and process the alignments to generate normalized transcript count files.

Input files - The DrEdGE software builds a DrEdGE website from five required components, and

four optional components (Figure 3, and described in full detail in Supplementary File 2): (1) a

table of transcript abundance counts, (2) a table describing the experimental design, (3) a

directory of pairwise comparison tables, (4) minimum and maximum values from the

comparison tables within that directory, and (5) a JSON file describing the experimental design.

The author can provide only the first two components and use R scripts from the DrEdGE

package to generate the last three components. Alternatively, if the author has specific statistical

methods they prefer to use, the author can generate all five components independently.

There are four optional components the DrEdGE software can additionally accept. These

include (6) a table of transcript synonyms, or alternate names, (7) a base URL for searching for

transcripts on an external organism-specific database, (8) a custom grid scheme for organizing

treatments in a 2D heat map grid, and (9) custom SVG icons representing treatments in an

illustrated heat map.

Processing input files to generate a DrEdGE website – To process the 5-9 components described

above into a DrEdGE website, the author must download the DrEdGE package from

dredge.bio.unc.edu, unzip the package, and host this DrEdGE directory locally. The index.html

file within that directory will present instructions for how to upload each of these components,

perform a test run, and save the project once assembly is complete. The author may then upload

the directory to the Web to share their DrEdGE website privately with collaborators, or publicly

as part of a publication.

Storage space required to host DrEdGE website – The final size of the DrEdGE directory will

depend primarily on the pairwise comparison tables. If the number of transcripts evaluated (t) is

known, and the number of treatments (n) in the experiment is known, the size of the DrEdGE

directory can be estimated: Size = (t) * (n^2) * 15 bytes. The three samples presented in this

publication range in size from 40 to 500 MB.

Discussion

As the genomic era ushers in larger and larger datasets, there is a growing need for tools that

facilitate data mining and collaboration by sharing genomics datasets in a partially processed,

interactive format. Here, we have presented DrEdGE, a program that allows genomicists to

easily create interactive data visualization websites. On a DrEdGE website, others can explore a

dataset by comparing differential transcript abundance between samples, surveying experiment-

wide transcript abundance patterns, and filtering or sorting by specific statistics. This tool allows

genomics researchers to share their work with other interested parties, either during collaboration

or for data mining after publication.

For simplicity, we have limited our demonstration of DrEdGE's utility to RNA-seq

experiments. DrEdGE's flexible design, however, allows users to visualize any two-dimensional

numeric dataset, including comparative proteomics, population diversity maps, or even non-

biological datasets.

Iterative analysis- DrEdGE's iterative analysis design allows readers to select data points of

interest from each data representation to investigate further in the next representation. The reader

can curate a list of transcripts through multiple analyses. This allows the reader to ask

sophisticated biological questions of the data, and generate statistically supported results. This

differs from current interactive genomics data visualization websites, such as genome browsers,

because comparative biological questions can be asked, tested, refined, and tested again

continuously. Exporting curated lists of transcripts from one experiment and importing it to

another experiment also allows for integrated analyses across different datasets or types of

assays.

Statistical flexibility and low technical overhead- The potential for authors to use statistical

methods of their choice has two benefits. First, it means that DrEdGE consists solely of static

files, making it easier to host and maintain than a typical dynamic Web application powered by a

database and server-side program (written in e.g. PHP, Python, Perl)[29]. Second, it allows

DrEdGE to fit within diverse data analysis pipelines. Each experiment requires unique statistical

considerations, whether due to idiosyncrasies of the genome, the molecular technique, or the

philosophy of the researcher, which DrEdGE is able to accommodate. This flexibility expands

DrEdGE's utility in a rapidly changing field.

Conclusions

We have presented DrEdGE, a tool for generating interactive visualizations of large genomics

datasets. These visualizations allow interested parties to independently explore data by

generating their own MA plots, transcript abundance statistics tables, and experiment-wide heat

maps, and to modify lists of transcripts of interest through multiple analyses. This tool fills the

gap in data sharing practices between raw data on databases (that require a substantial amount of

time and expertise to process) and a handful of completed analyses in publications (that are static

and cannot be queried further). By removing the technical obstacles that prevent interested

parties from exploring multivalent datasets, DrEdGE can increase the utility and impact of these

datasets.

Methods

Implementation and availability: DrEdGE is a browser-based application powered by client-side

JavaScript. The entire application is bundled into one HTML file and one JavaScript file, using

the JavaScript compiler Browserify[30] and the automation tool GNU Make[31]. All of the pages in

the application are built and rendered using the React library[32]. Interactive data visualizations are

created using the D3.js library[33]. All code is freely available on GitHub

(github.com/ptgolden/dredge) under the GNU Affero General Public License (AGPLv3).

Sourcing of sample datasets- RNA-seq data for humans, mice, and worms were collected from

ENCODE[4] or Boeck et al., 2016[26]. Human experiment accession numbers: ENCSR000AFO,

ENCSR000AEW, ENCSR000AEX, ENCSR000AEY, ENCSR000AFD, ENCSR000AFE,

ENCSR000AFJ, ENCSR858QEL, ENCSR648OSR, ENCSR796HLX, ENCSR272UNO,

ENCSR000AFH. Mouse experiment accession numbers: ENCSR809VYL, ENCSR851HEC,

ENCSR823VEE, ENCSR636CWO, ENCSR160IIN, ENCSR970EWM, ENCSR752RGN,

ENCSR691OPQ, ENCSR284YKY, ENCSR727FHP, ENCSR597UZW, ENCSR526SEX,

ENCSR420QTO, ENCSR848GST, ENCSR537GNQ, ENCSR173PJN, ENCSR347SQR,

ENCSR830IVQ, ENCSR648YEP, ENCSR448MXQ, ENCSR867YNV, ENCSR826HIQ,

ENCSR096STK, ENCSR457RRW, ENCSR992WBR, ENCSR307BCA, ENCSR908JWT,

ENCSR343YLB, ENCSR557RMA, ENCSR719NAJ, ENCSR337FYI, ENCSR115TWD,

ENCSR667TOX, ENCSR946HWC, ENCSR579FCW, ENCSR290RRR, ENCSR178GUS,

ENCSR000AHY, ENCSR000AHZ, ENCSR000AHX, ENCSR000AIA. Counts were compiled

into transcript count abundance tables and experimental design tables in R. Transcript synonym

tables for humans, mice, and worms were generated from the HUGO Gene Nomenclature

Committee's Biomart[34,35], Mouse Genome Informatics[36], and Wormmine[37], respectively.

DECLARATIONS

Availability of data and material

The datasets used in this study are all previously published (Boeck et al. 2016, The ENCODE

Project Consortium 2012, and Tintori et al. 2016). The reformatted and processed data used to

create the three example DrEdGE websites are available in Supplementary File 1. Original code

for the DrEdGE program is available at dredge.bio.unc.edu and github.com/ptgolden/dredge.

Competing interests

The authors declare that they have no competing interests.

Funding

BG was supported by NIH R01 GM083071 and NSF IOS 1557432.

Authors' contributions

Project was conceived of by ST, and designed by PG and ST with input from BG. Javascript

code by PG, R code by ST. Manuscript written by ST with input from PG and BG.

Acknowledgements

The authors would like to thank Dan McKay, Jonathan Seguin, Max Boeck, David King, Ann

Wehman, and Kira Heikes for their thoughtful feedback on the preprint of this manuscript.

References

1. Nosek BA, Alter G, Banks GC, Borsboom D, Bowman SD, Breckler SJ, et al. Promoting an open research culture. Science. 2015,348(6242):1422-5.

2. Gewin V. Data sharing: An open mind on open data. Nature. 2016;529:117–119.

3. Bioarxiv. http://www.bioarxiv.org/ (2013).

4. The ENCODE Project Consortium. An integrated encyclopedia of DNA elements in the human genome. Nature. 2012,489(7414):57-74.

5. The Cancer Genome Atlas. http://cancergenome.nih.gov/ (2006).

6. The 1000 Genomes Project Consortium. A global reference for human genetic variation. Nature. 2015,526;68–74.

7. Grabowski P, Rappsilber J. A Primer on Data Analytics in Functional Genomics: How to Move from Data to Insight? Trends in Biochemical Sciences. 2018,1521.

8. Huttenhower C, Hofmann O. A Quick Guide to Large-Scale Genomic Data Mining. PLoS Comput Biol. 2010,6(5):e1000779.

9. Cheng PF, Dummer R, Levesque MP. Data mining The Cancer Genome Atlas in the era of precision cancer medicine. Swiss Medicine Weekly. 2015;145:w14183.

10. Edgar R, Domrachev M, Lash AE. NCBI GEO - Gene Expression Omnibus: NCBI gene expression and hybridization array data repository. Nucleic Acids Research. 2002,30(1):207-10.

11. Leinonen R, Sugawara H, Shumway M, on behalf of the International Nucleotide Sequence Database Collaboration. The Sequence Read Archive. Nucleic Acids Research. 2011,39: D19–D21.

12. Toribio AL, Alako B, Amid C, Cerdeño-Tarrága A, Clarke L, Cleland I, et al. European

Nucleotide Archive in 2016. Nucleic Acids Research. 2017,45;D32–D36.

13. Figshare. https://figshare.com/ (2011).

14. Dryad. http://datadryad.org/ (2008).

15. Mashima J, Kodama Y, Kosuge T, Fujisawa T, Katayama T, Nagasaki H, Okuda Y,

Kaminuma E, Ogasawara O, Okubo K, Nakamura Y, Takagi T. DNA data bank of Japan

(DDBJ) progress report. Nucleic Acids Research. 2016,44;D51–D57.

16. Markowetz F. All biology is computational biology. PLoS Biol. 2017,15(3):e2002050.

17. Longo DL, Drazen JM. Data Sharing. New England Journal of Medicine. 2016,374;3.

18. Kent WJ, Sugnet CW, Furey TS, Roskin KM, Pringle TH, Zahler AM, Haussler D. The

human genome browser at UCSC. Genome Research. 2002,12(6):996-1006.

19. Spudich G, Fernández-Suárez XM, Birney E. Genome Browsing with Ensembl: a practical

overview. Brief Funct Genomic Proteomic. 2007,6: 202-219.

20. NCBI Genome Data Viewer. https://www.ncbi.nlm.nih.gov/genome/gdv/.

21. Wetterstrand KA. DNA Sequencing Costs: Data from the NHGRI Genome Sequencing

Program (GSP). 2018. www.genome.gov/sequencingcostsdata. Accessed December 6, 2018.

22. Wong KH, Jin Y, Moqtaderi Z. Multiplex Illumina Sequencing Using DNA Barcoding.

Current Protocols in Molecular Biology. 2013,7.11.1-7.11.11.

23. Klein AM, Mazutis L, Akartuna I, Tallapragada N, Veres A, Li V, Peshkin L, Weitz DA,

Kirschner MW. Droplet Barcoding for Single-Cell Transcriptomics Applied to Embryonic

Stem Cells. Cell. 2015;161,1187–1201.

24. Hashimshony T, Senderovich N, Avita G, Klochendler A, de Leeuw Y, Anavy1 L, Gennert

D, Li S, Livak KJ, Rozenblatt-Rosen O, Dor Y, Regev A, Yanai I. CEL-Seq2: sensitive

highly-multiplexed single-cell RNA-Seq. Genome Biology. 2016,17:77.

25. Karsch-Mizrachi I, Takagi T, Cochrane G on behalf of the International Nucleotide Sequence

Database Collaboration. The international nucleotide sequence database collaboration.

Nucleic Acids Research. 2018,46(D1):D48-D51.

26. Boeck ME, Huynh C, Gevirtzman L, Thompson OA, Wang G et al. The time-resolved

transcriptome of C. elegans. Genome Research. 2016,26:1441–1450.

27. Tintori SC, Osborne Nishimura E, Golden P, Lieb JD, Goldstein B. A transcriptional lineage

of the early *C. elegans* embryo. Developmental Cell. 2016;38(4):430-44.

28. Robinson MD, McCarthy DJ, Smyth GK. edgeR: a Bioconductor package for differential

expression analysis of digital gene expression data. Bioinformatics. 2010;26(1):139-40.

29. Hedstrom M. Digital preservation: A time bomb for digital libraries. Computers and the

Humanities. 1998;31:189-202.

30. Browserify. http://browserify.org/ (2011).

31. GNU Make. https://www.gnu.org/software/make/.

32. React. https://reactjs.org/.

33. D3. https://d3js.org/ (2010).

34. Yates B, Braschi B, Gray K, Seal R, Tweedie S, Bruford E. Genenames.org: the HGNC and

VGNC resources in 2017. Nucleic Acids Res. 2017;45(D1):D619-625.

35. HUGO Gene Nomenclature Committee at the European Bioinformatics Institute. HUGO

Mart. https://biomart.genenames.org/martform/#!/default/HGNC?datasets=hgnc_gene_mart.

Accessed August 21, 2018.

36. MGI Data and Statistical Reports. Mouse Genome Informatics. 1996.

http://www.informatics.jax.org/downloads/reports/index.html. Accessed August 15, 2018.

37. Wormmine. Wormbase. http://intermine.wormbase.org/tools/wormmine/begin.do. Accessed

August 10, 2015.

 Figures

Figure 1: Layout of DrEdGE visualization. A) The user can select two treatments to compare,

using icons or a drop column. B) An MA plot shows differential expression between two

treatments. C) A slider that filters transcripts out of the MA plot by p-value. D) A table shows

statistical values of transcripts highlighted from the MA plot. E) A heat map shows relative

transcript abundance across all treatments for a transcript selected from the table, graphically

represented as F) a grid of square icons, G) an illustration, or both. H) A curated list of

transcripts can be saved, added to, pruned, or cleared, through multiple analyses. I) Lists of

transcripts can be imported or exported to save, share with colleagues, or interface with other

methods and analyses in the user's analytical pipeline. Data is from Tintori et al, 2016[27].

Figure 2: Graphical options for heat map. A) Default box icons in a default compact grid. B) Box

icons in a custom linear arrangement. C) Box icons custom-arranged in a grid. D) SVG

illustrated icons. E) SVG illustrated icons (from Tintori et al. 2016)[27].

Figure 3: Pipeline of data input and products. Each file in described in further detail in

Supplementary File 2.

SUPPLEMENT

Supplementary File 1: Materials used to generate the three example DrEdGE websites

Because these data files cannot be uploaded at Word or LaTex files, we are providing an external

link to the source data tables. It is a 240 MB zipped file.

https://www.dropbox.com/s/la89lezajk2c1pp/Supplement%201%20-

6%20source%20files.zip?dl=0

Supplementary File 2: Descriptions of input files for generating a DrEdGE website

All files and numbers correspond to Figure 3.

1 - Transcript abundance table: The table of normalized transcript counts must have one row for

each transcript, and one column for each individual replicate in the experiment. Row names

(transcript IDs) must be unique, and column names (replicate IDs) must be unique and match the

experimental design metadata (Files #2 and #5).

2 - Experimental design metadata table: The experimental design table must include a row for

each replicate, and must include the following columns: "replicate.id", "treatment.id", and

"treatment.name". Replicate IDs must match the column names of the transcript abundance table

(File #1). Treatment names should be meaningful to a new reader exploring the DrEdGE

website. No row names are necessary.

3 - Directory of all pairwise comparison data tables: This directory must contain a unique file

for each unique pair of treatments, including self-to-self comparisons. Each file must be a table

with a row for each transcript, and the following three columns in this order: (1) the logarithm of

the fold change in transcript abundance between the first and second treatment, (2) the logarithm

of the average transcript abundance amongst all replicates of both treatments, and (3) the P-value

for fold change described in column 1. Row names (transcript IDs) must match the row names in

the transcript abundance file (File #1). The names of the files must reference the treatment IDs

used in the experimental design metadata (Files #2 and #5). The author is encouraged to use his

or her own preferred analytic methods to create the pairwise comparison tables, but is also

welcome to run the pairwise_comparisons.R script provided in the DrEdGE package. This script

receives the transcript abundance table (File #1) and the experimental design file (File #2) as

input, and uses edgeR to generate, name, and export all possible pairwise comparisons. The

edgeR analysis models the data as a negative binomial distribution, and models overdispersion as

a Poisson model. An empirical Bayes procedure is used to moderate the degree of overdispersion

across transcripts, and differential expression is assessed using an exact test adapted for

overdispersed data[28].

4 - Minima and maxima from pairwise comparison tables: These minima and maxima will be

used to set the default axis limits for the MA plots. The numbers will be entered manually, so

format is not important. If the author has run the pairwise_comparisons.R script to generate the

directory of pairwise comparison tables (Files #3), these minima and maxima values will

automatically be calculated and a report will be generated.

5 - Experimental design metadata JSON: The experimental design metadata (File #2) must also

be provided as a JSON (JavasScript Object Notation) file in which each first-order object

describes each treatment from the experiment. The JSON_treatments.R script provided in the

DrEdGE package will accept File #2 and generate this JSON file. If the author wishes to

generate the JSON file independently, the first order object keys must be the short unique codes

for the treatment ("treatment.id" in File #2), and the values must include the following second

order objects: (1) A "label" key that points to a verbose name for the treatment

("treatment.name" in File #2), and a "replicates" key that points to the full list of replicate IDs for

the treatment ("replicate.id" in File #2).

6 - Transcript synonyms or alternate names: The author may wish to associate a preferred

"readable" name with each transcript, and include other code names that readers might use in the

search bar. In this case the author may include a file of alternative names, or synonyms, for

transcripts. With one line of the file per transcript, each line must begin with the transcript name

that the DrEdGE visualization will show. Following that first-choice name should be a list all

other names or codes for the transcript, separated by tabs. In the input files for our three example

websites (Supplementary File 1), we have included transcript synonym tables for human, mouse,

and worm.

7 - Organism-specific database search URL: If the author would like transcripts to link to an

external database (i.e. Wormbase[37]), he or she may provide a generic search URL for this

database, with "%name" inserted where the transcript name would be (e.g.

http://wormbase.org/search/gene/%name).

8 - Custom grid layout for grid heat map: The default settings represent each treatment as a box

icon, with boxes fit together in a compact grid (Figure 2A). Alternatively, the author can specify

how he or she would like these boxes arranged (Figure 2B,D). To do this, the author must create

a comma delineated file in which each row of text describes the sequence of treatments (or white

space) for each row of the grid.

9 - Custom SVG for illustrated heat map: The author can display the heatmap as a graphic

illustration by uploading an SVG (Scalable Vector Graphics) file with custom icons representing

each sample (Figure 2C,E). The author must create a vector file with one object for each

treatment, and each object must be given a name that matches the treatment ID used in the

experimental design metadata files (Files #2 and #5).