Simulating bout-and-pause patterns with reinforcement learning

Kota Yamada

Keio University & LeapMind Inc.

Atsunori Kanemura

LeapMind Inc.

Author Note

Correspondence should be addressed to K. Yamada, Department of Psychology,

Keio University, Tokyo 108-8345, Japan (Email: haroldthebarrel.yk@gmail.com).

Abstract

Animal responses occur according to a specific temporal structure composed of two
states, where a bout is followed by a long pause until the next bout. Such a
bout-and-pause pattern has three components: the bout length, the within-bout
response rate, and the bout initiation rate. Previous studies have investigated how
these three components are affected by experimental manipulations. However, it
remains unknown what underlying mechanisms cause bout-and-pause patterns. In this
article, we propose a computational model based on reinforcement learning. The model
is characterized by two mechanisms. The first mechanism is choice—an agent makes a
choice between operant and other behaviors. The second mechanism is cost—a cost is
associated with the changeover of behaviors. The model has three states instead of two,
and we show that the third state is required to reproduce bout-and-pause patterns
through computer simulations. We further analyzed the proposed model and found that
it reproduced the relationships between experimental manipulations and the three
components that have been reported by previous studies. Simulation results suggested
that both the choice and cost mechanisms are required to generate bout-and-pause
patterns. Another implication of out study is that computational approaches are useful
to investigate mechanisms of animal behavior.

Keywords: bout-and-pause patterns, reinforcement learning, choice, cost

Simulating bout-and-pause patterns with reinforcement learning

Introduction

Animals engage in various activities in their daily lives. For humans, they may be working, studying, practicing sports, or playing video games. For rats, they may be grooming, foraging, or escaping from a predator. Although specific activities are different between different species, common behavioral features are often observed.

Bout-and-pause patterns are one of the behavioral features commonly observed in many species. Activities engaged by an animal do not occur uniformly through time but often have short periods in which a burst of engaged responses is observed. For example, in an operant conditioning experiment, a rat presses a lever repeatedly in a short period and then it stops lever pressing. After a moment, the rat starts lever pressing again. The rat switches between the lever pressing state and the no lever pressing state again and again throughout the experiment. Such a temporal structure comprising of short-period response bursts and long pauses is observed in various species and activities; for example, email and letter communication by humans (Barabasi, 2005), foraging by cows (Tolkamp & Kyriazakis, 1999), and walking by Drosophila (Sorribes, Armendariz, Lopez-Pigozzi, Murga, & de Polavieja, 2011).

Shull, Gaynor, and Grimes (2001) showed that bout-and-pause patterns can be described with a broken-stick shape in the log-survivor plot of interresponse times (IRTs), which are characterized by a bi-exponential probability model. If IRTs follow a single exponential distribution, then the log-survivor plot shows a straight line. If IRTs follow a mixture exponential distribution called a bi-exponential model, the log-survior plot shows a broken-stick shape composed of two straight lines that have different slopes. Killeen, Hall, Reilly, and Kettle (2002) found that lever pressing by rats is well described with a bi-exponential model, suggesting that this behavior has a bout-and-pause pattern. If IRTs follow a bi-exponential distribution, there are two different types of responses; within-bout responses, which have short IRTs, and between-bout responses, which have long IRTs. Each response type has its own exponential distribution in a bi-exponential model. Killeen et al. (2002) formulated the

bi-exponential model as follows:

$$p(IRT = \tau) = (1 - q)\omega e^{-\omega\tau} + qbe^{-b\tau}, \tag{1}$$

where the first term describe IRTs of within-bout responses and the second term describes IRTs of between-bout responses. This model has three free parameters: q, ω, and b, each of which corresponds to a different component in the bout-and-pause pattern. First, q denotes the mixture ratio of the two exponential distributions in the model and it corresponds to the length of a bout. The bout length is the number of responses contained in one bout. Second, ω denotes the rate parameter for the exponential distribution of within-bout IRTs and it corresponds to the within-bout response rate. Finally, b denotes the rate parameter for the exponential distribution of between-bout IRTs and it corresponds to the bout initiation rate. These three model parameters define the overall response rate. They are also called bout components.

The bout length, the within-bout response rate, and the bout initiation rate are affected by motivational and schedule-type manipulations (Brackney, Cheung, Neisewander, & Sanabria, 2011; Podlesnik, Jimenez-Gomez, Ward, & Shahan, 2006; Shull, 2004; Shull et al., 2001; Shull, Grimes, & Bennett, 2004; Tanno, 2016). Motivational manipulations include the reinforcement rate, the response-reinforcement contingency, and the deprivation level. An example of schedule-type manipulations is adding a small variable ratio (VR) schedule in tandem to a VI schedule. Table 1 summarizes existing findings on the relationships between experimental manipulations and the two bout components, where we omit the within-bout response rate since we will not study this bout component because of a model complexity issue and insufficient experimental findings on it. The bout length was reported to be affected by manipulations as follows:

- It increases or stays the same as the reinforcement rate increases (Shull et al., 2001; Shull et al., 2004).
- It increases or stays the same as the deprivation level increases (Podlesnik et al., 2006; Shull, 2004; Shull et al., 2001).

- It decreases or stays the same by extinction (Brackney et al., 2011; Cheung, Neisewander, & Sanabria, 2012).
- It increases by tandem VR (Shull et al., 2001; Shull et al., 2004). When a VI schedule is followed by a small VR (tandem VI VR), an animal stays in a bout longer and emits more responses in each bout.

The bout initiation rate was reported to be:

- It increases as the reinforcement rate increases (Shull et al., 2001; Shull et al., 2004).
- It increases as the deprivation level increases (Podlesnik et al., 2006; Shull, 2004; Shull et al., 2001).
- It decreases by extinction (Brackney et al., 2011; Cheung et al., 2012).
- It decreases or stays the same by tandem VR (Brackney et al., 2011). Brackney et al. (2011) showed that if we add a small VR schedule in tandem to a VI schedule, the bout initiation rate decreased slightly.

Although previous studies have investigated the relationships between some experimental manipulations and the bout components, underlying mechanisms that generate bout-and-pause patterns have not been elucidated. Smith, McLean, Shull, Hughes, and Pitts (2014) showed experimentally that choice and cost play important roles in organizing responses into bout-and-pause patterns. When pigeons were trained under a single schedule, the log-survivor plot did not showed a broken-stick shape (Bennett, Hughes, & Pitts, 2007; Bowers, Hill, & Palya, 2008). Smith et al. (2014) trained pigeons under a concurrent VI VI schedule with and without a changeover delay (COD). When pigeons were trained under the concurrent VI VI schedule without a COD, the log-survivor plot still did not show a broken stick, resulting in the a straight line. However, under the concurrent VI VI schedule with a COD, the log-survivor plot showed a broken stick, indicating that bout-and-pause patterns were clearly observed. From these experimental observations, we extracted the following three facts. 1) When animals engage only in one response in a given situation, bout-and-pause patterns are not observed. 2) If animals can choose responses from two alternatives without a COD,

bout-and-pause patterns are still not observed. 3) Considering 1) and 2), we conclude
that bout-and-pause patterns emerge only when animals have two (or more) possible
alternative responses under a given situation and there is a COD between the start of
engagement and a reinforcement. These facts are interesting but they remain to be
inductive, and we still do not have constructive explanation that generate
bout-and-pause patterns. Existing studies on bout-and-pause patterns have investigated
to describe the phenomena rather than to provide causal models. Although rich
knowledge on changes in bout-and-pause patterns are available (Killeen et al., 2002;
Matsui, Yamada, Sakagami, & Tanno, 2018; Tanno, 2016), they did not answer the
question of "what mechanisms shape responses into bout-and-pause patterns?"

In this article, we propose a computational model based on reinforcement learning
that accounts for the causal generation mechanism of bout-and-pause patterns. We
assume that bout-and-pause patterns are generated by two mechanisms: a choice
between operant and other behaviors and a cost that is required to a transition from
one behavior to another. We suppose that motivational manipulations affect only the
choice mechanism and schedule-type manipulations affect the cost mechanism. To
incorporate those two mechanisms, we design a three-state Markov transition model,
which has an extra state in addition to the bout and pause states. We perform two
simulation studies to analyze the proposed model. In Simulation 1, we introduce our
model on the basis of the two different mechanisms, choice and cost. We show that the
proposed model can reproduce bout-and-pause patterns by finding that the log-survivor
plot shows a broken-stick shape. We compare three models: a dual model, a no cost
model, and a no choice model. The dual model is composed of both the choice and cost
mechanisms. The no cost model has only the choice mechanism and the no choice model
has only the cost mechanism. Simulation results demonstrate that the dual model can
reproduce bout-and-pause patterns but the other two models failed to reproduce them.
It implies that both of choice and cost are required for animal responses to be organized
into bout-and-pause patterns. In Simulation 2, we analyze the dual model in depth and
report its behavior under various experimental settings to test if the dual model can

reproduce the relationships between the experimental manipulations and the bout components discovered so far. Simulation results suggest that the dual model can reproduce them not only qualitatively but also quantitatively. We speculate that real animals might have similar mechanisms that generate bout-and-pause patterns as the dual model, which can be a useful computational tool for studying animal behavior.

Simulation 1

Method: Simulation 1

Model.   Our model is based on reinforcement learning (Sutton & Barto, 2018). We designed a three-state Markov process for modeling bout-and-pause patterns (Figure 1(a)). Two of the three states are "Operant" and "Others," in which the agent engages in the operant behavior or performs other behaviors, respectively. We call them Operant and Others instead of engagement or visit and disengagement or pause, thereby we emphasize that bout-and-pause patterns are results of a choice between operant and other behavior. In the third "Choice" state, the agent makes a decision between the operant and other behaviors. By having the Choice state in our model, we incorporate the knowledge that animals can choose their behavior from available options (e.g. grooming, exploration, and excretion) when they move freely during an experiment. The second knowledge that is observed in animal behavior is a cost required to make a transition from one behavior to another. Animals must decide whether to keep doing the same behavior or to make a transition, because a fast switching is not optimal if a transition incurs a cost. Figure 1(b) and (c) shows two knockout models, the no choice model and the no cost model, respectively. In each model, one of the two mechanisms from the dual model is removed. In the no choice model, an agent can choose only the operant behavior in a given situation. In the no cost model, no cost is required when a transition is made.

Here is how the agent travels in the proposed model. In the Choice state, the agent chooses either the operant or other behaviors. As a result of the choice, it moves from the Choice state to one of the Operant or Others states. It makes the choice based

on the preferences for each behavior, which is denoted by Q_{pref}. We will explain how to calculate Q_{pref} in the next paragraph. In the Operant state, the agent engages in the operant behavior and decides whether to stay in the Operant state or to move back to the Choice state after every response. It decides to stay or move based on Q_{cost}, which represents a transition cost to the Choice state, whose mathematical definition is given in the paragraph after next. The Others state is the same as the Operant state except for that the agent performs other behaviors.

The preference Q_{pref} is a function that compares the operant and other behaviors when the agent makes a choice between them. The Q_{pref} function changes over time since it is updated based on the presence (or absence) of a reinforcer per bout. The following equation describes the updating rule for Q_{pref}:

$$
Q_{\text{pref}}^{(i)}(t+1) = \begin{cases} Q_{\text{pref}}^{(i)}(t) + \alpha_{\text{rft}}(r^{(i)}(t) - Q_{\text{pref}}^{(i)}(t)), & \text{if a reinforcer is presented,} \quad (2) \\ Q_{\text{pref}}^{(i)}(t) + \alpha_{\text{ext}}(0 - Q_{\text{pref}}^{(i)}(t)), & \text{otherwise,} \quad (3) \end{cases}
$$

where t denotes time in session; α_{rft} and α_{ext} denotes the learning rates of reinforcement and extinction, respectively; r denotes the reinforcer value and we assume $r > 0$ when a reinforcer is present and $r = 0$ when a reinforcer is absent; and $i \in \{\text{Operant}, \text{Others}\}$ denotes each option, that is, $i = \text{Operant}$ if the operant behavior is chosen and if $i = \text{Others}$ if other behaviors are chosen. We omit superscript (i) and denote Q_{pref} when it can be any of $i = \text{Operant}$ or Others.

The cost Q_{cost} is a function that defines a barrier in making a transition from the performed behavior to the Choice state. We assumed that the cost is independent from the preference and depends only on the number of responses that are emitted to obtain a reinforcer from a bout initiation. When a reinforcer is presented, the cost function Q_{cost} is updated according to

$$
Q_{\text{cost}}^{(i)}(t+1) = Q_{\text{cost}}^{(i)}(t) + \alpha_{\text{rft}}(\log x^{(i)}(t) - Q_{\text{cost}}^{(i)}(t)), \quad (4)
$$

where x denotes the number of responses that are emitted to obtain a reinforcer from a bout initiation. The other parameters are the same as Equations 2 and 3. The same (i)-omitting rule applies also to Q_{cost}.

In the Choice state, the agent chooses either of the Operant or Others states
according to the probability distribution calculated from the preferences for the two
behaviors. The probability of transition to option $i \in \{\text{Operant}, \text{Others}\}$ is defined as
follows:

$$p_i = \frac{\exp\{\beta Q_{\text{pref}}^{(i)}(t)\}}{\sum_{i \in \{\text{Operant}, \text{Others}\}} \exp\{\beta Q_{\text{pref}}^{(i)}(t)\}}, \tag{5}$$

where the softmax inverse temperature parameter β represents the degree to which a
choice is focused on the highest-value option.

If the agent is in either of the Operant or Others states, it makes a decision
whether to stay in the same state or to go back to the Choice state. A decision is made
according to the probability of staying in the same state calculated from the cost and
the preference for the state, which is defined as follows:

$$p_{\text{stay}} = \exp\left\{\frac{-1}{w_{\text{pref}} Q_{\text{pref}}^{(i)}(t) + w_{\text{cost}} Q_{\text{cost}}^{(i)}(t)}\right\}, \tag{6}$$

where w_{pref} and w_{cost} are positive weighting parameters for Q_{pref} and Q_{cost}, respectively.
We assumed $w_{\text{cost}} > w_{\text{pref}}$ because schedule-type operations have stronger effects on the
bout length than motivational manipulations.

Simulation.   In Simulation 1, we compared the three possible models; the dual
model, the no choice model, and the no cost model. The dual model (Figure 1(a)),
which includes both the choice and cost mechanisms as we described in the Model
section. The second model was the no choice model (Figure 1(b)), which has only the
cost mechanism and it can be thought of as a model made by removing the choice
mechanism from the dual model. In the no choice model, the agent only engages in the
operant behavior. In other words, this model chooses only the operant behavior in the
Choice state. The third model was the no cost model, which has only the choice
mechanism without the cost mechanism. The no cost model chooses either operant or
other behavior independent of the previous behavior; that is, according to this model,
the agent does not continue to be in the same state and comes back to the Choice state
after each response.

Simulation conditions were as follows. The schedule for the operant behavior was
VI 120 s (0.5 reinforcer per min) without an intertrial interval, and the schedule for the

other behavior was FR 1. The maximum number of reinforcers in the Operant state was

1,000; that is, if the number of reinforcers reached 1,000, the simulation was terminated.

The value of a reinforcer given by taking the operant behavior was $r^{(\text{Operant})} = 1.0$ and

that by taking other behaviors was $r^{(\text{Others})} = 0.5$. The model parameters were α_{rft}, α_{ext},

β, ω_{pref}, and ω_{cost}. We set $\alpha_{\text{rft}} = 0.05$, $\alpha_{\text{ext}} = 0.01$, $\beta = 12.5$, $\omega_{\text{pref}} = 1.0$ and $\omega_{\text{cost}} = 3.5$.

The response probabilities in the Operant and the Others states were fixed at 1/3 in

each time step. Before the start of the simulation, we initialized the agent and the

experimental environment. The initial values of $Q^{(i)}_{\text{pref}}$ and $Q^{(i)}_{\text{cost}}$ were both 0 and we

created a VI table according to Fleshler and Hoffman (1962). We set the time step in

the simulation to be 0.1 s.

We show pseudocode of the model and simulation in Algorithm 1.

Results: Simulaton 1

Figure 2(a) shows event records of IRTs generated by each model and Figure 3

shows the model schemes with transition probabilities between each state. The top

panel shows that the no choice model generated a dense repetition of only the operant

behavior at a high rate without long pauses. The probability the agent stayed in the

Operant state was empirically 0.95. In the middle panel, the response rate under the no

cost model was low and each response was separated by long pauses. The probability of

the agent choosing to transit to the Operant state was empirically 0.06 and the agent

returned to the Choice state immediately after it responded. In the bottom panel, the

agent with the dual model generated a repetitive pattern of responses with a high rate

in a short period followed by a long pause. The agent in the Choice state made a

transition to the Operant state with a 0.12 probability and it stayed in the Operant

state with a 0.71 probability.

Figure 2(b) show log-survivor plots in to see whether they show a straight line or

a broken stick. We used the IRTs from after the agent obtained 500 reinforcers to the

end of the simulation. The log-survivor plots of the no choice model and the no cost

model were described by one straight line whereas that of the dual model was described

---

Algorithm 1 Pseudocode of simulation

Input: MeanInterval
Initialize: $t = 0$, $NumRewards = 0$, $ResponseTimes = \{\}$
  while $NumRewards < 1000$ **do**
    $t = t + 0.1$
    if $i =$ Choice **then**
      Select a state $i \in \{\text{Operant}, \text{Others}\}$ with probability defined by Equation 5
    end if
    if $i =$ Operant **and** $uniform(0,1) \leq 1/3$ **then**
      Append t to $ResponseTimes$
      if reward is presented **then**
        Update $Q_{\text{pref}}^{(\text{Operant})}(t)$ according to Equation 2
        Update $Q_{\text{cost}}^{(\text{Operant})}(t)$ according to Equation 4
        $NumRewards \mathrel{+}= 1$
      end if
      if reward is absent **then**
        Update $Q_{\text{pref}}^{(\text{Operant})}(t)$ according to Equation 3
      end if
      if $uniform(0,1) \leq p_{\text{stay}}$ defined by Equation 6 **then**
        $i = i$
      else
        $i =$ Choice
      end if
    end if
    if $i =$ Others **and** $uniform(0,1) \leq 1/3$ **then**
      Update $Q_{\text{pref}}^{(\text{Others})}(t)$ according to Equation 2
      Update $Q_{\text{cost}}^{(\text{Others})}(t)$ according to Equation 4
      if $uniform(0,1) \leq p_{\text{stay}}$ defined by Equation 6 **then**
        $i = i$
      else
        $i =$ Choice
      end if
    end if
  end while

---

with a broken-stick shape. The no choice model has a steeper slope than the no cost model and is tangential to the curve of the dual model at the leftmost position. The no cost model slope was slightly steeper than that of the dual model at the right side.

Discussion: Simulaton 1

Both event records and log-survivor plots in Figure 2 imply that only the dual model generated bout-and-pause patterns and the other two models failed to reproduce bout-and-pause patterns. The event records in Figure 2(a) suggests only the dual model exhibit bout-and-pause patterns. The log-survivor plot of only the dual model in

Figure 2(b) showed not a straight but a broken-stick shape, which is an evidence that
the underlying IRTs follow a bi-exponential distribution. Thus, only the dual model
reproduced bout-and-pause patterns.

We posit both of the choice and cost mechanisms are necessary to organize
responses into bout-and-pause patterns. The no choice model failed because it lacks the
choice mechanism. Without the choice mechanism, the agent almost always stayed in
the Operant state and responded at a high rate without pauses. The reason behind the
failure of the no cost model was the knockout of the cost mechanism. When the cost of
switching behaviors is zero, the agent easily return to the Choice state, resulting in
operant responses followed by long pauses. The choice and cost mechanisms contribute
differently to generate bout-and-pause patterns; the choice mechanism generates pauses
and the cost mechanism produces response bursts. Since the dual model has the both
mechanisms, it reproduced bout-and-pause patterns.

Simulation 2

Having demonstrated in Simulation 1 that the dual model successfully reproduced
bout-and-pause patterns, in Simulation 2 we analyzed this model under various
environments. The previous studies (Brackney et al., 2011; Podlesnik et al., 2006; Shull,
2004; Shull et al., 2001, 2002; Shull et al., 2004; Tanno, 2016) have applied various
experimental manipulations to animals to understand bout-and-pause patterns, as
summarized in Table 1. We applied manipulations to the agent in the model by
changing environmental settings.

Method: Simulation 2

Using the dual model, we performed four experiments by manipulating only one of
the four variables while keeping the other three variables the same as Simulation 1. The
procedure of simulation is also the same as Simulation 1.

The four experimental manipulations are applied independently to each of the
four variables: 1) the rate of reinforcement, 2) the deprivation level, 3) the presence of
extinction, and 4) the schedule type. 1) We manipulated the rate of reinforcement by

varying mean intervals of the VI schedule. Mean intervals used in this simulation were

VI 30 s, 120 s, and 480 s (2.0, 0.5, and 0.125 reinforcer per min). 2) We varied reward

values obtained in the Operant state to control the deprivation level of the agent. Those

values were 0.5, 1.0, and 1.5 to induce low deprivation, baseline, and high deprivation

levels, respectively. The reward value that the agent received by taking other behaviors

was the same as Simulation 1 throughout all the simulations. 3) To attenuate the

engagement to the operant response, we switched the schedule from VI 120 (0.5

reinforcer per min) s to extinction after the agent obtained 1,000 reinforcers. The

extinction phase finished when 3,600 s (36,000 time steps) elapsed. 4) We manipulated

the schedule type by adding a small VR schedule in tandem to a VT schedule. The

mean interval of the VT schedule was fixed to 120 s and VR values were 0, 4, and 8.

When we analyzed the IRTs data from the extinction simulation, we used a

dynamic bi-exponential model (Brackney et al., 2011), in which the model parameters,

q, ω, and b, are time-dependent and Equation 1 is rewritten as follows:

$$p(IRT = \tau) = (1 - q_t)\omega_t e^{-\omega_t \tau} + q_t b_t e^{-b_t \tau}. \tag{7}$$

Extinction causes exponential decay of the model parameters according to the following

equations:

$$1 - q_t = (1 - q_0)e^{-\gamma t}, \tag{8}$$

$$b_t = b_0 e^{-\delta t}, \tag{9}$$

where the parameters γ and δ denote the decay rates of q and b, respectively. Since the

decay of any of the three model parameters q and b can cause extinction, we need to

identify which of these parameters actually decayed during the extinction simulation.

We excluded ω because it was fixed during the simulation. To identify whether one or

both of the q and/or b parameters decayed, we compared three models, that is, the

qb-decay, q-decay, and b-decay models. We calculated WAIC (widely applicable

information criterion) for each model.

Results: Simulation 2

Figure 4 shows the log-survivor plots of IRTs from each of the four simulations.
Figure 4(a) and (b) shows that manipulating the rate of reinforcement or the
deprivation level changed the slope of the right limb. As the rate of reinforcement or
the deprivation level increased, the slope of the right limb became steeper, indicating
that the bout initiation rate became larger. The broken sticks in Figure 4(c) have
different slopes and y-axis intercepts, suggesting that both the bout initiation rate and
the bout length were changed. Figure 4(d) shows that adding the tandem VR schedule
to the VT schedule affected only the y-axis intercept of the right limb without changing
its slope. As the required response increased from the baseline to VR 4 or VR 8, the
bout length became larger. However, the right limbs were not stable and we performed
a fitting analysis described in the next paragraph.

Table 2 shows estimated parameters of the bi-exponential model, q, w, and b in
three simulations except for extinction. Parameter q increased as the reinforcement
rate, the deprivation level, and the number of required responses increased. Parameter
ω is not changed in all manipulations. Parameter b is increased as the rate of
reinforcement and the deprivation level increased.

In Figure 4(c), the total number of IRTs during the extinction phase was
insufficient to reliably estimate the right limb. Then, we analyzed the dynamic
bi-exponential model fitted to the IRTs during extinction. Table 3 shows the WAIC
values for the three models. The smallest WAIC was attained by the qb-decay model,
suggesting that the bout initiation rate and the bout length decayed during extinction.

Figure 5 shows the boxplots of Q_{pref} and Q_{cost} in the three simulations except for
extinction, which are to be used for assessing how the changes in the bout components
are mediated. We excluded the extinction simulation because we already knew that
Q_{pref} causes the change of the bout components since Q_{cost} is fixed during the extinction
phase. The top panel shows that Q_{pref} and Q_{cost} increased as the rate of reinforcement
increased. The middle panel indicates that increasing the deprivation level moved Q_{pref}
and Q_{cost} upward. From the bottom panel, we can see that adding tandem VR schedule

increased Q_{cost} without affecting Q_{pref}.

Discussion: Simulation 2

In Simulation 2, we tested whether the dual model has the same characteristics as animals reported by the previous studies. We analyzed the model with four experimental manipulations: the rate of reinforcement, the deprivation level, the schedule type, and the presence of extinction. The rate of reinforcement, the deprivation level and the presence of extinction affected the bout initiation rate and the bout length and adding the tandem VR schedule to the VT schedule affected only the bout length.

Table 4 summarizes the relationship between the experimental manipulations and the bout components observed in the dual model, which suggests that the behaviors of the dual model are consistent with the existing knowledge on animal behaviors. Therefore, the dual model satisfies at least the necessary conditions to be a model to be analyzed for the generation mechanism of bout-and-pause patterns.

How Q_{pref} and Q_{cost} depend on experimental manipulations can be understood according to the categorization of motivational and schedule-type manipulations proposed by Shull et al. (2001). In our simulations, manipulating any of the three motivational variables, i.e. the rate of reinforcement, the deprivation level, or extinction, changed Q_{pref} and Q_{cost}. The change of Q_{cost} was not a primary but a secondary effect because Q_{cost} was changed as a result of the increased Q_{pref}; with a higher Q_{pref}, the agent emits more responses. The schedule type manipulation affected only Q_{cost}. These changes of Q_{pref} and Q_{cost} are consistent with what was proposed by Shull et al. (2001).

The dual model is limited to reproduce only some of the previous findings. Here are two examples of limitations. First, our model is not designed for analyzing the addition of a tandem VR schedule to a VT schedule, by which Tanno (2016) and Matsui et al. (2018) found the change of the within-bout response rate, which was fixed in our model. Second, the value and the delay between a response and a reinforcer is fixed in our model. Brackney et al. (2011) and Podlesnik et al. (2006) considered a delayed reinforcement from a bout initiation causes the inverse correlation between the

bout initiation rate and the bout length. This result can be reproduce if required
responses by tandem VR is very high (more than 32). Third, sometimes the bout length
does not decrease during extinction (Brackney et al., 2011). Our dual model could not
reproduce this result even if we changed the model parameters.

General Discussion

In this paper, we have developed a computational model with reinforcement
learning. The model is meant to explain how bout-and-pause patterns can be generated
and we examined its validity by comparing computer simulations and experimental
findings. We hypothesized that a three-state model involving two independent
mechanisms, the choice between Operant and Others and the cost in the changeover of
behaviors, are necessary to organize responses into bout-and-pause patterns. We
demonstrated in Simulation 1 that the dual model reproduced bout-and-pause patterns
under a VI schedule. Simulation 2 found that the relationships between various
experimental manipulations and the bout components in our model were consistent.
These results support our hypothesis that assumes that an agent transitioning between
the three states driven by the choice and cost mechanisms organizes its responses into
bout-and-pause patterns. This is our answer to "why bout-and-pause patterns emerge?"

Our generative model reproduced the descriptive results reported by (Shull, 2004;
Shull et al., 2001, 2002; Shull et al., 2004). Although our dual model does not include
Equation 1 explicitly, IRTs generated by the dual model followed the bi-exponential
model. This is an example of the first advantage of reinforcement learning discussed in
the next paragraph.

Our model is developed based on reinforcement learning, which has two
advantages. First, reinforcement learning models consist of simple rules. Instead of
describing complicated behaviors of animals by abstract rules, we implement a simple
model designed by decomposing animal behaviors into basic rules that are likely to be
implemented also in real animals. This is a divide-and-conquer approach to develop a
model. Second, reinforcement learning is a computational approach, where the model is

described with mathematical expressions that are translated into programming code.
We can run simulations to analyze what happens inside the model. Internal states of a
real animal are difficult to observe, but it is easy for a computational model. Such a
computational approach is more quantitative than models described by natural
languages.

Our model has at least two shortcomings, which are the range of parameters and
the redundancy of the model. The parameters α_{rft}, α_{ext}, β, ω_{pref}, and ω_{cost} in our model
have not been optimized to fit to behavioral data from real animals. The evidence that
supports our parameter selection is that our model quantitatively reproduced
bout-and-pause patterns. Second, although our model has five parameters, real animals
may have fewer parameters. To verify our model for these two points, it would be useful
to compare empirical data from real animals and our computational model.

Standing on our model proposed in this paper, we can extend our research to
many directions to explain more various aspects of bout-and-pause patterns. Here we
discuss two of them. First, our results were retrospective to data from previous
behavioral experiments and the proposed model was not tested by its prediction ability
to unseen data. The second approach is verification based on neuroscientific knowledge.
Even if the model can correctly predict unseen data from behavioral experiments, it is
not guaranteed that animals employ the same the model. To explore real mechanisms
that animals implement, it would be effective to compare the internal variables of the
model with neural activities measured from real animals during behavioral experiments.
Possible experiments are to perform knock out experiments by inducing lesions at
specific areas of the brain that should be active during the experiments, or to activate
or deactivate specific neurons during the experiment.

Reinforcement learning can be employed to model and explain animal behaviors
other than bout-and-pause patterns, since it is a general framework where an agent
learns optimal behaviors in a given environment through trial-and-error (Sutton &
Barto, 2018). Such a reinforcement learning framework agrees well with the three-term
contingency in behavior analysis. There are three essential elements in reinforcement

learning; a state, an action, and a reward. The state is what agent observe and is information about the environment. The action is a behavior that the agent takes in a given state. The reward is what the agent obtains as the result of the action. These three elements are similar to a discriminative stimulus, a response, and an outcome. This similarity would allow behavior analysts to employ reinforcement learning in their research. For example, Sakai and Fukai (2008) employed actor-critic reinforcement learning to modeling the matching law. We hope more computational studies will be performed to expand methods of behavioral science.

References

Barabasi, A.-L. (2005). The origin of bursts and heavy tails in human dynamics.
   Nature, 435(7039), 207.

Bennett, J. A., Hughes, C. E., & Pitts, R. C. (2007). Effects of methamphetamine on
   response rate: a microstructural analysis. *Behavioural Processes, 75*(2), 199–205.

Bowers, M. T., Hill, J., & Palya, W. L. (2008). Interresponse time structures in
   variable-ratio and variable-interval schedules. *Journal of the Experimental
   Analysis of Behavior, 90*(3), 345–362.

Brackney, R. J., Cheung, T. H., Neisewander, J. L., & Sanabria, F. (2011). The isolation
   of motivational, motoric, and schedule effects on operant performance: a modeling
   approach. *Journal of the Experimental Analysis of Behavior, 96*(1), 17–38.

Cheung, T. H., Neisewander, J. L., & Sanabria, F. (2012). Extinction under a
   behavioral microscope: isolating the sources of decline in operant response rate.
   Behavioural Processes, 90(1), 111–123.

Fleshler, M. & Hoffman, H. S. (1962). A progression for generating variable-interval
   schedules. *Journal of the Experimental Analysis of Behavior, 5*(4), 529–530.

Killeen, P. R., Hall, S. S., Reilly, M. P., & Kettle, L. C. (2002). Molecular analyses of
   the principal components of response strength. *Journal of the Experimental
   Analysis of Behavior, 78*(2), 127–160.

Matsui, H., Yamada, K., Sakagami, T., & Tanno, T. (2018). Modeling bout–pause
   response patterns in variable-ratio and variable-interval schedules using
   hierarchical Bayesian methodology. *Behavioural Processes, 157*, 346–353.

Podlesnik, C. A., Jimenez-Gomez, C., Ward, R. D., & Shahan, T. A. (2006). Resistance
   to change of responding maintained by unsignaled delays to reinforcement: a
   response-bout analysis. *Journal of the Experimental Analysis of Behavior, 85*(3),
   329–347.

Sakai, Y. & Fukai, T. (2008). The actor-critic learning is behind the matching law:
   matching versus optimal behaviors. *Neural Computation, 20*(1), 227–251.

Shull, R. L. (2004). Bouts of responding on variable-interval schedules: effects of
deprivation level. *Journal of the Experimental Analysis of Behavior*, *81*(2),
155–167.

Shull, R. L., Gaynor, S. T., & Grimes, J. A. (2001). Response rate viewed as
engagement bouts: effects of relative reinforcement and schedule type. *Journal of
the Experimental Analysis of Behavior*, *75*(3), 247–274.

Shull, R. L., Gaynor, S. T., & Grimes, J. A. (2002). Response rate viewed as
engagement bouts: Resistance to extinction. *Journal of the Experimental Analysis
of Behavior*, *77*(3), 211–231.

Shull, R. L., Grimes, J. A., & Bennett, J. A. (2004). Bouts of responding: the relation
between bout rate and the rate of variable-interval reinforcement. *Journal of the
Experimental Analysis of Behavior*, *81*(1), 65–83.

Smith, T. T., McLean, A. P., Shull, R. L., Hughes, C. E., & Pitts, R. C. (2014).
Concurrent performance as bouts of behavior. *Journal of the Experimental
Analysis of Behavior*, *102*(1), 102–125.

Sorribes, A., Armendariz, B. G., Lopez-Pigozzi, D., Murga, C., & de Polavieja, G. G.
(2011). The origin of behavioral bursts in decision-making circuitry. *PLoS
Computational Biology*, *7*(6), e1002075.

Sutton, R. S. & Barto, A. G. (2018). *Reinforcement learning: an introduction*. MIT
press.

Tanno, T. (2016). Response-bout analysis of interresponse times in variable-ratio and
variable-interval schedules. *Behavioural Processes*, *132*, 12–21.

Tolkamp, B. J. & Kyriazakis, I. (1999). To split behaviour into bouts, log-transform the
intervals. *Animal Behaviour*, *57*(4), 807–817.

Table 1

*Previous findings from animal experiments on the relationships between manipulations
and bout components. The three cells marked with "?" do not have agreement within the
previous reports.*

	Motivational			Schedule type
	Reinforcement rate	Deprivation level	Extinction	Tandem VR
Bout length	↗ or →?	↗ or →?	↘ or →?	↗
Bout initiation rate	↗	↗	↘	↘ or →?

Table 2

Estimated parameters of the bi-exponential model in simulations.

Manipulation	Condition	ω	b	q
Rate of reinforcement	VI 30 (2.0 per min)	3.08	0.23	0.17
	VI 120 (0.5 per min)	3.06	0.09	0.27
	VI 480 (0.125 per min)	3.19	0.03	0.31
Deprivation level	High deprivation	3.04	0.24	0.17
	Baseline	3.15	0.08	0.26
	Low deprivation	3.17	0.03	0.31
Tandem VT 120 VR x	VR 0	3.07	0.09	0.26
	VR 4	3.23	0.08	0.19
	VR 8	3.11	0.08	0.16

Table 3

Parameter selection for the dynamic bi-exponential model with WAIC. The lower

WAIC, the better the model.

Model	WAIC
qb-decay	1.936
b-decay	1.940
q-decay	1.980

Table 4

The behavior of the dual model. The cells marked with "" indicates the consistency with the animal findings shown in Table 1. The cells marked with "†" were the cells with "?" in Table 1.*

	Motivational			Schedule type
	Reinforcement rate	Deprivation level	Extinction	Tandem VR
Bout length	↗*	↗*	↘†	↗*
Bout initiation rate	↗*	↗*	↘*	→†

Table 5

The dependency of Q_{pref} and Q_{cost} to experimental manipulations in the dual model.

	Motivational			Schedule type
	Reinforcement rate	Deprivation level	Extinction	Tandem VR
Q_{pref}	↗	↗	↘	→
Q_{cost}	↗	↗	→	↗

Figure 1. Model schemes of the dual model, the no choice model and the no cost model.
(a) The model scheme of the dual model. The upper node, the bottom left node, and
the bottom right node correspond to the Choice state, the Operant state, and the
Others state respectively. Each arrow denotes the transition from one state to others.
(b) The model scheme of the no choice model. In this model, the Others state is
omitted. (c) The model scheme of the no cost model. In this model, self-transitions in
the Operant and Others state is omitted.

Figure 2. (a) Response event records in the (top) no choice, (middle) no cost, and

(bottom) dual models in the 50 s period just after 500 reinforcers were presented (event

records were stable after 500 reinforcer presentations). Each vertical line denotes one

response. (b) Log-survivor plots of the three models drawn by using all the IRTs after

500 reinforcers.

Figure 3. The transition probabilities between the three states that were calculated

from the simulation data after the agent obtained 500 reinforcers.

Figure 4. The log-survivor plots of IRTs generated under the manipulation of (a) the

rate of reinforcement, (b) the deprivation level, (c) the schedule type, and (d) the

presence of extinction drawn by all data after the agent obtained 500 reinforcers.

Figure 5. Boxplots of Q_{pref} and Q_{cost} in each simulation. The top, middle, and bottom

rows correspond to the reinforcement rate, the deprivation level, and the tandem VT

VR simulations, respectively, and the left and right columns show Q_{pref} and Q_{cost},

respectively.