1   **An active inference model of concept learning**

2   Ryan Smith,[1] Philipp Schwartenbeck,[2] Thomas Parr,[2] Karl J. Friston,[2]

4   [1]Laureate Institute for Brain Research, Tulsa, OK, USA

5   [2]Wellcome Centre for Human Neuroimaging, Institute of Neurology, University

6   College London, WC1N 3BG, UK

11   Corresponding Author Information:

13   Ryan Smith

14   Laureate Institute for Brain Research

15   6655 S Yale Ave, Tulsa, OK 74136, USA

16   Email: rsmith@laureateinstitute.org

17   **Abstract**

The algorithmic and neural basis of concept learning remains poorly understood. In

this paper, we articulate a novel, biologically plausible approach to concept learning

based on active inference, and on the idea that a generative model can be equipped

with extra (hidden state or cause) 'slots' that can be engaged when an agent learns

about novel concepts. This can be combined with a Bayesian model reduction

process, in which any concept learning – associated with these slots – can be reset in

favor of a simpler model with higher model evidence. We use simulations to

illustrate this model's ability to add new concepts to its state space, increase the

granularity of the concepts it currently possesses, and accomplish a simple form of

'one-shot' generalization to new stimuli. Although deliberately simple, these results

suggest that active inference may offer useful resources in developing

neurocomputational models of concept learning.

Keywords: Model Expansion; Structure Learning; Concepts; Computational

Neuroscience; Active Inference

Introduction

The ability to conceptualize and understand regularly observed patterns in co-occurring feature observations is central to human cognition. For example, we do not simply observe particular sets of colors, textures, shapes, and sizes – we also observe *identifiable object*s such as, say, a 'screwdriver'. If we were tool experts, we might also recognize particular types of screwdrivers (e.g., flat vs. Phillip's head), designed for a particular use. This ability to recognize co-occurring features under conceptual categories (as opposed to just perceiving sensory qualities; e.g., red, round, etc.) is also highly adaptive. Only if we know an object is a screwdriver could we efficiently infer that it affords putting certain structures together and taking them apart; and only if we know the specific type of screwdriver could we efficiently infer, say, the artefacts to use it on. Many concepts of this sort require experience-dependent acquisition (i.e., learning).

From a computational perspective, the ability to acquire a new concept can be seen as a type of Bayesian model comparison or structure learning (Botvinick, Niv, & Barto, 2009; S. J. Gershman & Niv, 2010; MacKay & Peto, 1995; Salakhutdinov, Tenenbaum, & Torralba, 2013; Tervo, Tenenbaum, & Gershman, 2016). Specifically, concept acquisition can be cast as an agent learning (or inferring) that a new hypothesis (referred to here as a hidden cause or state) should be added to the internal or generative model with which she explains her environment, because existing causes cannot account for new observations (e.g., an agent might start out believing that the only tools are hammers and screwdrivers, but later learn that there are also wrenches). In other words, the structure of the space of hidden causes

itself needs to expand to accommodate new patterns of observations. This model

expansion process is complementary to a process called Bayesian model reduction

(Karl Friston & Penny, 2011); in which the agent can infer that there is redundancy

in her model, and a model with fewer states or parameters provides a more

parsimonious (i.e. simpler) explanation of observations (KJ Friston, Lin, et al., 2017;

Schmidhuber, 2006). For example, in some instances it may be more appropriate to

differentiate between fish and birds as opposed to salmon, peacocks and pigeons.

This reflects a reduction in model complexity based on a particular feature space

underlying observations and thus resonates with other accounts of concept learning

as dimensionality reduction (Behrens et al., 2018; Stachenfeld, Botvinick, &

Gershman, 2016) – a topic we discuss further below.

A growing body of work in a number of domains has approached this

problem from different angles. In developmental psychology and cognitive science,

for example, probability theoretic (Bayesian) models have been proposed to account

for word learning in children and the remarkable human ability to generalize from

very few (or even one) examples in which both broader and narrower categorical

referents could be inferred (Kemp, Perfors, & Tenenbaum, 2007; Lake,

Salakhutdinov, & Tenenbaum, 2015; Perfors, Tenenbaum, Griffiths, & Xu, 2011; Xu &

Tenenbaum, 2007a, 2007b). In statistics, a number of nonparametric Bayesian

models, such as the "Chinese Room" process and the "Indian Buffet" process, have

been used to infer the need for model expansion (S. Gershman & Blei, 2012). There

are also related approaches in machine learning, as applied to things like Gaussian

mixture models (McNicholas, 2016).

These are the generative models that underwrite various clustering

algorithms that take sets of data points in a multidimensional space and divide them

into spatially separable clusters. While many of these approaches assume the

number of clusters is known in advance, various goodness-of-fit criteria may be

used to determine the optimal number. However, a number of approaches require

much larger amounts of data than humans do to learn new concepts (Geman,

Bienenstock, & Doursat, 1992; Hinton et al., 2012; LeCun, Bengio, & Hinton, 2015;

Lecun, Bottou, Bengio, & Haffner, 1998; Mnih et al., 2015). Many also require

corrective feedback to learn and yet fail to acquire sufficiently rich conceptual

structure to allow for generalization (Barsalou, 1983; Biederman, 1987; Feldman,

1997; Jern & Kemp, 2013; A. B. Markman & Makin, 1998; Osherson & Smith, 1981;

Ward, 1994; Williams & Lombrozo, 2010).

One potentially fruitful research avenue that has not yet been examined is to

explore concept learning from the perspective of Active Inference models based on

the free-energy principle (KJ Friston, 2010; KJ Friston et al., 2016; KJ Friston, Lin, et

al., 2017; KJ Friston, Parr, & de Vries, 2017). In this paper, we explore the potential

of this approach. In brief, we conclude that structure learning is an emergent

property of active inference (and learning) under generative models with 'spare

capacity'; where spare or uncommitted capacity is used to expand the repertoire of

representations (Baker & Tenenbaum, 2014), while Bayesian model reduction (KJ

Friston, Lin, et al., 2017; Hobson & Friston, 2012) promotes generalization by

minimizing model complexity – and releasing representations to replenish 'spare

capacity'.

In what follows, we first provide a brief overview of active inference. We then

introduce a model of concept learning (using basic and subordinate level animal

categories) to produce synthetic cognitive (semantic) processes associated with

adding new concepts to a state space and increasing the granularity of an existing

state space. We then establish the validity of this model using numerical analyses of

concept learning when repeatedly presenting a synthetic agent with different

animals characterized by different combinations of observable features. We will

demonstrate how particular approaches combining Bayesian model reduction and

expansion can reproduce successful concept learning without the need for

corrective feedback, and allow for generalization. We conclude with a brief

discussion of the implications of this work.

118   **An Active Inference model of concept learning**

A primer on Active Inference

Active Inference suggests that the brain is an inference machine that

approximates optimal probabilistic (Bayesian) belief updating across perceptual,

cognitive, and motor domains. Active Inference more specifically postulates that the

brain embodies an internal model of the world that is "generative" in the sense that

it can simulate the sensory data that it should receive if its model of the world is

correct. These simulated (predicted) sensory data can be compared to actual

observations, and differences between predicted and observed sensations can be

used to update the model. Over short timescales (e.g., a single observation) this

updating corresponds to inference (perception), whereas on longer timescales it

corresponds to learning (i.e., updating expectations about what will be observed

later). Another way of putting this is that perception optimizes beliefs about the

current state of the world, while learning optimizes beliefs about the relationships

between the variables that constitute the world. These processes can be seen as

ensuring the generative model (entailed by recognition processes in the brain)

remains an accurate model of the world that it seeks to regulate (Conant & Ashbey,

1970).

138   Active Inference casts decision-making in similar terms. Actions can be

chosen to resolve uncertainty about variables within a generative model (i.e.,

sampling from domains in which the model does not make precise predictions),

which can prevent anticipated deviations from predicted outcomes. In addition,

some expectations are treated as a fixed phenotype of an organism. For example, if

an organism did not continue to "expect" to observe certain amounts of food, water,

and shelter, then it would quickly cease to exist (McKay & Dennett, 2009) – as it

would not pursue those behaviors that fulfill these expectations (c.f. the 'optimism

bias' (Sharot, 2011)). Thus, a creature should continually seek out observations that

support – or are internally consistent with – its own continued existence. Decision-

making can therefore be cast as a process in which the brain infers the sets of

actions (policies) that would lead to observations consistent with its own survival-

related expectations (i.e., its "prior preferences"). Mathematically, this can be

described as selecting sequences of actions (policies) that maximize "Bayesian

model evidence" expected under a policy, where model evidence is the (marginal)

likelihood that particular sensory inputs would be observed under a given model.

In real-world settings, directly computing Bayesian model evidence is

generally intractable. Thus, some approximation is necessary. Active Inference

proposes that the brain computes a quantity called "variational free energy" that

provides a bound on model evidence, such that minimization of free energy

indirectly maximizes model evidence (this is exactly the same functional used in

machine learning where it is known as an evidence lower bound or ELBO). In this

case, decision-making will be approximately (Bayes) optimal if it infers (and enacts)

the policy that will minimize expected free energy (i.e., free energy with respect to a

policy, where one takes expected future observations into account). Technically,

expected free energy is the variational free energy averaged under the posterior

predictive density over policy-specific outcomes.

Expected free energy can be decomposed in different ways that reflect

uncertainty and prior preferences, respectively (e.g., epistemic and instrumental

affordance or ambiguity and risk). This formulation means that any agent that

minimizes expected free energy engages initially in exploratory behavior to

minimise uncertainty in a new environment. Once uncertainty is resolved, the agent

then exploits that environment to fulfil its prior preferences. The formal basis for

Active Inference has been thoroughly detailed elsewhere (KJ Friston, FitzGerald,

Rigoli, Schwartenbeck, & Pezzulo, 2017), and the reader is referred there for a full

mathematical treatment.

When the generative model is formulated as a partially observable Markov

decision process (a mathematical framework for modeling decision-making in cases

where some outcomes are under the control of the agent and others are not, and

where states of the world are not directly known but must be inferred from

observations), active inference takes a particular form. Here, the generative model is

specified by writing down plausible or allowable policies, hidden states of the world

(that must be inferred from observations), and observable outcomes, as well as a

number of matrices that define the probabilistic relationships between these

quantities (see right panel of figure 1).

Figure 1. Left: Illustration of the trial structure performed by the agent. At the first time
point, the agent is exposed to one of 8 possible animals that are each characterized by a
unique combination of visual features. At the 2nd time point, the agent would then report
which animal concept matched that feature combination. The agent could report a specific

category (e.g., pigeon, hawk, minnow, etc.) or a general category (i.e., bird or fish) if
insufficiently certain about the specific category. See the main text for more details. Right:
Illustration of the Markov decision process formulation of active inference used in the
simulations described in this paper. The generative model is heredepicted graphically, such
that arrows indicate dependencies between variables. Here observations (**o**) depend on
hidden states (**s**), as specified by the **A** matrix, and those states depend on both previous
states (as specified by the **B** matrix, or the initial states specified by the **D** matrix) and the
policies (**π**) selected by the agent. The probability of selecting a particular policy in turn
depends on the expected free energy (**G**) of each policy with respect to the prior preferences
(**C**) of the agent. The degree to which expected free energy influences policy selection is also
modulated by a prior policy precision parameter (**γ**), which is in turn dependent on beta (*β*)
–where higher values of beta promote more randomness in policy selection (i.e., less
influence of the differences in expected free energy across policies). For more details
regarding the associated mathematics, see (KJ Friston, Lin, et al., 2017; KJ Friston, Parr, et
al., 2017).
203

The 'A' matrix indicates which observations are generated by each

combination of hidden states (i.e., the likelihood mapping specifying the probability

that a particular set of observations would be observed given a particular set of

hidden states). The 'B' matrix is a transition matrix, indicating the probability that

one hidden state will evolve into another over time. The agent, based on the selected

policy, controls some of these transitions (e.g., those that pertain to the positions of

its limbs). The 'D' matrix encodes prior expectations about the initial hidden state

the agent will occupy. Finally, the 'C' matrix specifies prior preferences over

observations; it quantifies the degree to which different observed outcomes are

rewarding or punishing to the agent. In these models, observations and hidden

states can be factorized into multiple outcome *modalities* and hidden state *factors*.

This means that the likelihood mapping (the 'A' matrix) can also model the

interactions among different hidden states when generating outcomes

(observations). In what follows, we describe how this type of generative model was

specified to perform concept inference/learning.

A model of concept inference and learning

To model concept inference, we constructed a simple task for an agent to

perform (see figure 1, left panel). In this task, the agent was presented with different

animals on different trials and asked to answer a question about the type of animal

that was seen. As described below, in some simulations the agent was asked to

report the type of animal that was learned previously; in other simulations, the

agent was instead asked a question that required conceptual generalization.

Crucially, to answer these questions the agent was required to observe different

animal features, where the identity of the animal depended on the combination of

features. There were three feature categories (size, color, and species-specific;

described further below) and two discrete time points in a trial (observe and

report).

To simulate concept learning (based on the task described above) we need to

specify an appropriate generative model. Once this model has been specified, one

can use standard (variational) message passing to simulate belief updating and

behavior in a biologically plausible way: for details, please see (KJ Friston,

FitzGerald, et al., 2017; KJ Friston, Parr, et al., 2017). In our (minimal) model, the

first hidden state factor included (up to) eight levels, specifying four possible types

of birds and four possible types of fish (Figure 2A). The outcome modalities

included: a feature space including two size features (big, small), two color features

(gray, colorful), and two species-differentiating features (wings, gills). The 'A' matrix

specified a likelihood mapping between features and animal concepts, such that

each feature combination was predicted by an animal concept (Hawk, Pigeon,

Parrot, Parakeet, Sturgeon, Minnow, Whale shark, Clownfish). This model was

deliberately simple to allow for a clear illustration, but it is plausibly scalable to

include more concepts and a much larger feature space. The 'B' matrix for the first

hidden state factor was an identity matrix, reflecting the belief that the animal

identity was conserved during each trial (i.e., the animals were not switched out

mid-trial).

249
250

251
Figure 2. (A) Illustration of the first hidden state factor containing columns (levels) for 8
different animal concepts. Each of these 8 concepts generated a different pattern of visual
feature observations associated with the outcome modalities of size, color, and species-
specific features. The B matrix was an identity matrix, indicating that the animal being
observed did not change within a trial (white = 1, black = 0). The A matrix illustrates the
specific mapping from animal concepts to feature combinations. As depicted, each concept
corresponded to a unique point in a 3-dimensional feature space. (B) illustration of the 2nd
hidden state factor corresponding to the verbal reports the agent could choose in response
to her observations. These generated feedback as to whether their verbal report was
accurate with respect to a basic category report or a specific category report. As illustrated
in the C matrix, the agent most preferred to be correct about specific categories, but least
preferred being incorrect. Thus, reporting the basic categories was a safer choice if the
agent was too uncertain about the specific identity of the animal.
265

The second hidden state factor was the agent's report. That this is assumed

to factorise from the first hidden state factor means that there is no prior constraint

that links the chosen report to the animal generating observations. The agent could

report each of the eight possible specific animal categories, or opt for a less specific

report of a bird or a fish. Only one category could be reported at any time. Thus, the

agent had to choose to report only bird vs. fish or to report a more specific category.

In other words, the agent could decide upon the appropriate level of coarse-graining

of her responses (figure 2B).

During learning trials, the policy space was restricted such that the agent

could not provide verbal reports or observe corrective feedback (i.e., all it could do

is "stay still" in its initial state and observe the feature patterns presented). This

allowed the agent to learn concepts in an unsupervised manner (i.e. without being

told what the true state was or whether it was correct or incorrect). After learning,

active reporting was enabled, and the 'C' matrix was set so that the agent preferred

to report correct beliefs. We defined the preferences of the agent such that she

preferred correctly reporting specific category knowledge and was averse to

incorrect reports. This ensured that she only reported the general category of bird

vs. fish, unless sufficiently certain about the more specific category.

In the simulations reported below, there were two time points in each trial of

categorisation or conceptual inference. At the first time point, the agent was

presented with the animals features, and always began in a state of having made no

report (the "start" state). The agent's task was simply to observe the features, infer

the animal identity, and then report it (i.e., in reporting trials). Over 32 simulations

(i.e., 4 trials per animal), we confirmed that, if the agent already started out with full

knowledge of the animal concepts (i.e., a fully precise 'A' matrix), it would report the

specific category correctly 100% of the time. Over an additional 32 simulations, we

also confirmed that, if the agent was only equipped with knowledge of the

distinction between wings and gills (i.e., by replacing the rows in the 'A' matrix

corresponding to the mappings from animals to size and color with flat

distributions), it would report the generic category correctly 100% of the time but

would not report the specific categories.[1] This was an expected and straightforward

consequence of the generative model – but provides a useful example of how agents

trade off preferences and different types of uncertainty.

300   **Simulating concept learning and the acquisition of expertise**

302   Having confirmed that our model could successfully recognize animals if

303   equipped with the relevant concepts (i.e., likelihood mappings) – we turn now to

304   concept learning.

306   **Concept acquisition**

307   We first examined our model's ability to acquire concept knowledge in two

308   distinct ways. This included 1) the agent's ability to "expand" (i.e., fill in an unused

309   column within) its state space and add new concepts, and 2) the agent's ability to

310   increase the granularity of its conceptual state space and learn more specific

311   concepts, when it already possessed broader concepts.

313   *Adding Concepts*

---

[1] However, "risky" reporting behavior could be elicited by manipulating the strengths of the agent's preferences such that she placed a very high value on reporting specific categories correctly (i.e., relative to how much it disliked reporting incorrectly).

To assess whether our agent could expand her state space by acquiring a new

concept, we first set one column of the previously described model's 'A' matrix

(mapping an animal concept to its associated features) to be a uniform distribution[2];

creating an imprecise likelihood mapping for one concept – essentially, that concept

predicted all features with nearly equal probability. Here, we chose sturgeon (large,

gray, gills) as the concept for which the agent had no initial knowledge (see Figure

3A, right-most column of left-most 'pre-learning' matrix). We then generated 2000

observations based on the outcome statistics of a model with full knowledge of all

eight animals (the "generative process"), to test whether the model could learn the

correct likelihood mapping for sturgeon (note: this excessive number of

observations was used for consistency with later simulations, in which more

concepts have to be learned, and also to evaluate how performance improved as a

function of the number of observations the agent was exposed to; see figure 3B).

In these simulations, learning was implemented via updating (concentration)

parameters for the model's 'A' matrix after each trial. For details of these free energy

minimizing learning processes, please see (KJ Friston et al., 2016). An intuitive way

to think about this belief updating process is that the strength of association

between a concept and an observation is quantified simply by counting how often

they are inferred to co-occur. This is exactly the same principle that underwrites

Hebbian plasticity and long-term potentiation (Brown, Zhao, & Leung, 2010).

Crucially, policies were restricted during learning, such that the agent could not

---

[2] To break the symmetry of the uniform distribution, we added small amounts of Gaussian noise
(with a variance of .001) to avoid getting stuck in local free energy minima during learning.

select reporting actions; thus, learning was driven entirely by repeated exposure to

different feature combinations. We evaluated successful learning in two ways. First,

we compared the 'A' matrix learned by the model to that of the generative process.

Second, we disabled learning after various trial numbers (i.e., such that

concentration parameters no longer accumulated) and enabled reporting. We then

evaluated reporting accuracy with 20 trials for each of the 8 concepts.

As shown in Figure 3A, the 'A' matrix (likelihood) mapping – learned by the

agent – and the column for sturgeon in particular, strongly resembled that of the

generative process. When first evaluating reporting, the model was 100 % accurate

across 20 reporting trials, when exposed to a sturgeon (reporting accuracy when

exposed to each of the other animals also remain at 100%) and first reached this

level of accuracy after around 50 exposures to all 8 animals (with equal probability)

(figure 3B). The agent also always chose to report specific categories (i.e., it never

chose to only report bird or fish). Model performance was stable over 8 repeated

simulations.

Crucially, during learning, the agent was not told which state was generating

its observations. This meant that it had to solve both an inference and a learning

problem. First, it had to infer whether a given feature combination was better

explained by an existing concept, or by a concept that predicts features uniformly. In

other words, it had to decide that the features were sufficiently different – from

things it had seen before – to assign it a new hypothetical concept. Given that a novel

state is only inferred when another state is not a better explanation, this precludes

learning 'duplicate' states that generate the same patterns of observations. The

second problem is simpler. Having inferred that these outcomes are caused by

something new, the problem becomes one of learning a simple state-outcome

mapping through accumulation of Dirichlet parameters.

To examine whether this result generalized, we repeated these simulations

under conditions in which the agent had to learn more than one concept. When the

model needed to learn one bird (parakeet) and one fish (minnow), the model was

also able to learn the appropriate likelihood mapping for these 2 concepts (although

note that, because the agent did not receive feedback about the state it was in during

learning, the new feature mappings were often not assigned to the same columns as

in the generative process; see figure 3A). Reporting also reached 100% accuracy,

but required a notably greater number of trials. Across 8 repeated simulations, the

mean accuracy reached by the model after 2000 trials was 98.75% (SD = 2%).

A

B

Figure 3. (A) illustration of representative simulation results in which the agent successfully
learned 1, 2, or 3 new animal concept categories with no prior knowledge beforehand. The
generative process is shown in the upper right, illustrating the feature combinations to be
learned. Pre-learning, either 1, 2 or 3 columns in the likelihood mapping began as a flat
distribution with a slight amount of Gaussian noise. The agent was and then provided with
2000 observations of the 8 animals with equal probability. Crucially, the agent was
prevented from providing verbal reports during these 2000 trials and thus did not receive
feedback about the true identity of the animal. Thus learning was driven completely by
repeated exposure in an unsupervised manner. Also note that, while the agent was
successful at learning the new concepts, it did not always assign the new feature patterns to
the same columns as illustrated in the generative process. This is to be expected given that
the agent received no feedback about the true hidden state that generated her observations.
(B) illustration of how reporting accuracy, and the proportion of basic category and specific
category responses, changed as a function of repeated exposures. This was accomplished by
taking the generative model at a number of representative trials and then testing it with 20
observations of each animal in which reporting was enabled. As can be seen, maximal
accuracy was achieved much more quickly when the agent had to learn fewer concepts.
When it had learned 3 concepts, it also began by reporting the general categories and then
subsequently became sufficiently confident to report the more specific categories.
391

When the model needed to learn all 4 birds, performance varied somewhat

more when the simulations were repeated. The learned likelihood mappings after

2000 trials always resembled that of the generative process, but with variable levels

of precision; notably, the model again assigned different concepts to different

columns relative to the generative process, as would be expected when the agent is

not given feedback about the state she is in. Over 8 repeated simulations, the model

performed well in 6 (92.50 % – 98.8 % accuracy) and failed to learn one concept in

the other 2 (72.50 % accuracy in each) due to overgeneralization (e.g., mistaking

parrot for Hawk in a majority of trials; i.e., the model simply learned that there are

large birds). Figure 3A and 3B illustrate representative results when the model was

successful (note: the agent never chose to report basic categories in the simulations

where only 1 or 2 concepts needed to be learned).

To further assess concept learning, we also tested the agent's ability to

successfully avoid state duplication. That is, we wished to confirm that the model

would only learn a new concept if actually presented with a new animal for which it

did not already have a concept. To do so, we equipped the model with knowledge of

seven out of the eight concept categories, and then repeatedly exposed it only to the

animals it already knew over 80 trials. We subsequently exposed it to the eighth

animal (Hawk) for which it did not already have knowledge over 20 additional

trials. As can be seen in figure 4, the unused concept column was not engaged during

the first 80 trials (bottom left and middle). However, in the final 20 trials, the agent

correctly inferred that her current conceptual repertoire was unable to explain her

new pattern of observations, leading the unused concept column to be adumbrated

and the appropriate state-observation mapping to be learned (bottom right). We

repeated these simulations under conditions in which the agent already had

knowledge of six, five, or four concepts. In all cases, we observed that unused

concept columns were never engaged inappropriately.

Avoiding State Duplication

420
Figure 4. Illustration of representative simulation results when the agent had to avoid
inappropriately learning a new concept (i.e., avoid state duplication)after only being
exposed to animals for which it already had knowledge. Here the agent began with prior
knowledge about seven concept categories, and was also equipped with an eighth column
that could be engaged to learn a new concept category (bottom left). The agent was then
presented with several instances of each of the seven animals that she already knew (80
trials in total). In this simulation, the agent was successful in assigning each stimulus to an
animal concept she had already acquired, and did not engage the unused concept 'slot'
(bottom middle). Finally, the agent was presented with a new animal (a hawk) that she did
not already know over 20 trials. In this case, the agent successfully engaged the additional
column (i.e., she inferred that none of the concepts she possessed could account for her new
observations), and learn the correct state-observation mapping (bottom right).
433

Crucially, these simulations suggest that adaptive concept learning needs to

be informed by existing knowledge about other concepts, such that a novel concept

should only be learned if observations cannot be explained with existing conceptual

knowledge. Here, this is achieved via the interplay of inference and learning, such

that agents initially have to infer whether to assign an observation to an existing

concept, and only if this is not possible an 'open slot' is employed to learn about a

novel concept.

Increasing granularity

Next, to explore the model's ability to increase the granularity of its concept

space, we first equipped the model with only the distinction between birds and fish

(i.e., the rows of the likelihood mapping corresponding to color and size features

were flattened in the same manner described above). We then performed the same

procedure used in our previous simulations. As can be seen in Figure 5A (bottom

left), the 'A' matrix learned by the model now more strongly resembled that of the

generative process. Figure 5A (bottom) also illustrates reporting accuracy and the

proportion of basic and specific category reports as a function of trial number. As

can be seen, the agent initially only reported general categories, and became

sufficiently confident to report specific categories after roughly 50 – 100 trials, but

its accuracy increased gradually over the next 1000 trials (i.e., the agent reported

specific categories considerably before its accuracy improved). Across 8 repeated

simulations, the final accuracy level reached was between 93% – 98% in 7

simulations, but she failed to learn one concept in the 8th case, with 84.4% overall

accuracy (i.e., a failure to distinguish between pigeon and parakeet, and therefore

only learned a broader category of "small birds").

To assess whether learning basic categories first was helpful in subsequently

learning specific categories, we also repeated this simulation without any initial

knowledge of the basic categories. As exemplified in figure 5A and 5B, the model

tended to perform reasonably well, but most often learned a less precise likelihood

mapping and reached a lower reporting accuracy percentage after 2000 learning

trials (across 8 repeated simulations: mean = 81.21%, SD = 6.39%, range from

68.80% – 91.30%). Thus, learning basic concept categories first appeared to

facilitate learning more specific concepts later.

A

467
468

B

Increasing Granularity:
Reporting Accuracy as a Function of Trial Number (without feedback)

No Prior Knowledge

After Learning Basic Categories

469
Figure 5. (A, left) Illustration of representative simulation results when the agent had to
learn to increase the granularity of its concept space. Here the agent began with prior
knowledge about the basic concept categories (i.e., it had learned the broad categories of
"bird" and "fish") but had not learned the feature patterns (i.e., rows) that differentiate
different types of birds and fish. Post learning (i.e., after 2000 exposures), the agent did
successfully learn all of the more granular concept categories, although again note that
specific concepts were assigned to different columns then depicted in the generative
process due to the unsupervised nature of the learning. (A, right) illustration of the
analogous learning result when the agent had to learn all 8 specific categories without prior
knowledge of the general categories. Although moderately successful, learning tended to be
more difficult in this case. (B) Representative plots of reporting accuracy in each of the 2
learning conditions as a function of the number of exposures. As can be seen, when the
model starts out with prior knowledge about basic categories, it slowly become sufficiently
confident to start reporting the more specific categories, and its final accuracy is high. In
contrast, while the agent that did not start out with any prior knowledge of the general
categories also grew confident in reporting specific categories over time, its final accuracy
levels tended to be lower. In both cases, the agent began reporting specific categories before
it achieved significant accuracy levels, therefore showing some initial overconfidence.
488

Overall, these findings provide a proof of principle that this sort of active

inference scheme can add concepts to its state space in an unsupervised manner

(i.e., without feedback) based purely on (expected) free energy minimization. In this

case, it was able to accomplish this starting from a completely uninformative

likelihood distribution. It could also learn more granular concepts after already

acquiring more basic concepts, and our results suggest that learning granular

concepts may be facilitated by first learning basic concepts (e.g., as in currently

common educational practices).

The novel feature of this generative model involved 'building in' a number of

"reserve" hidden state levels. These initially had uninformative likelihood mappings;

yet, if a new pattern of features was repeatedly observed, and the model could not

account for this pattern with existing (informative) state-observation mappings,

these additional hidden state levels could be engaged to improve the model's

explanatory power. This approach therefore accommodates a simple form of model

expansion.

Integrating model expansion and reduction

We next investigated ways in which model expansion could be combined with

Bayesian model reduction (KJ Friston, Lin, et al., 2017) – allowing the agent to adjust

her model to accommodate new patterns of observations, while also precluding

unnecessary conceptual complexity (i.e., over-fitting). To do so, we again allowed

the agent to learn from 2000 exposures to different animals as described in the

previous section – but also allowed the model to learn its 'D' matrix (i.e., accumulate

concentration parameters reflecting prior expectations over initial states). This

allowed an assessment of the agent's probabilistic beliefs about which hidden state

factor levels (animals) it had been exposed to. In different simulations, the agent

was only exposed to some animals and not others. We then examined whether a

subsequent model reduction step could recover the animal concepts presented

during the simulation; eliminating those concepts that were unnecessary to explain

the data at hand. The success of this 2-step procedure could then license the agent to

"reset" the unnecessary hidden state columns after concept acquisition, which

would have accrued unnecessary likelihood updates during learning. Doing so

would allow the optimal ability for those "reserve" states to be appropriately

engaged, if and when the agent was exposed to truly novel stimuli.

The 2nd step of this procedure was accomplished by applying Bayesian model

reduction to the 'D' matrix concentration parameters after learning. This is a form of

post-hoc model optimization (K. J. Friston et al., 2016; Karl Friston, Parr, & Zeidman,

2018) that rests upon estimation of a 'full' model, followed by analytic computation

of the evidence that would have been afforded to alternative models (with

alternative, 'reduced', priors) had they been used instead. Mathematically, this

procedure is a generalization of things like automatic relevance determination (Karl

Friston, Mattout, Trujillo-Barreto, Ashburner, & Penny, 2007; Wipf & Rao, 2007) or

the use of the Savage Dickie ratio in model comparison (Cornish & Littenberg,

2007). It is based upon straightforward probability theory and, importantly, has a

simple physiological interpretation; namely, synaptic decay and the elimination of

unused synaptic connections. In this (biological) setting, the concentration

parameters of the implicit Dirichlet distributions can be thought of as synaptic tags.

For a technical description of Bayesian model reduction techniques and their

proposed neural implementation, see (KJ Friston, Lin, et al., 2017; Hobson & Friston,

2012; Hobson, Hong, & Friston, 2014a)).

The posterior concentration parameters were compared to the prior

distribution for a full model (i.e., a flat distribution over 8 concepts) and prior

distributions for possible reduced models (i.e., which retained different possible

combinations of some but not all concepts; technically, reduced models were

defined such that the to-be-eliminated concepts were less likely than the to-be-

retained concepts). If Bayesian model reduction provided more evidence for one or

more reduced models, the reduced model with the most evidence was selected.

Note: an alternative would be to perform model reduction on the 'A' matrix, but this

is more complex due to a larger space of possible reduced models; it also does not

address the question of the number of hidden state levels to retain in a

straightforward manner.

In our first simulation, we presented our agent with all animals except for

parakeets with equal probability over 2000 trials. When compared to the full model,

the winning model corresponded to the correct 7-animal model matching the

generative process in 6/8 cases (log evidence differences ranged from -3.12 to -8.3),

and in 2/8 cases it instead selected a 6-animal model due to a failure to distinguish

between 2 specific concepts during learning (log evidence differences = -5.30, -

7.70). Figure 6 illustrates the results of a representative successful case). In the

559 successful cases, this would correctly license the removal of changes in the model's

560 'A' and 'D' matrix parameters for the 8th animal concept during learning in the

561 previous trials. Similar results were obtained whenever any single animal type was

562 absent from the generative process.

564 Figure 6. Representative illustrations of simulations in which the agent performed Bayesian
565 model reduction after learning. In these simulations, the agent was first exposed to 2000
566 trials in which either 7, 6, or 5 animals were actually presented (i.e., illustrated in the top
567 row, where only the white columns had nonzero probabilities in the generative process). In
568 each case, model reduction was often successful at identifying the reduced model with the
569 correct number of animal types presented (bottom row, where black columns should be
570 removed) based on how much evidence it provided for the posterior distribution over
571 hidden states learned by the agent (2nd row). This would license the agent to reset
572 the unneeded columns in its likelihood mapping (3rd row) to their initial state (i.e., a
573 flat distribution over features) such that it could be engaged if/when a new type of
574 animal began to be observed (i.e., as in the simulations illustrated in the previous
575 sections).

In a second simulation, the generative process contained 2 birds and all 4

fish. Here, the correct reduced model was correctly selected in 6/8 simulations (log

evidence differences range from -.96 to -8.24, with magnitudes greater than -3 in

5/6 cases), whereas it incorrectly selected the 5-animal model in 2 cases (log

evidence differences = -3.54, -4.50). In a third simulation, the generative process

contained 1 bird and all 4 fish. Here, the correct reduced model had the most

evidence in only 3/8 simulations (log evidence differences = -4.10, -4.11, -5.48),

whereas a 6-animal model was selected in 3/8 cases and a 3-animal and 7-animal

model were each selected once (log evidence differences > -3.0). Figure 6 also

illustrates representative examples of correct model recovery in these 2nd and 3rd

simulations.

While we have used the terms 'correct' and 'incorrect' above to describe the

model used to generate the data, we acknowledge that 'all models are wrong' (Box,

Hunter, & Hunter, 2005), and that the important question is not whether we can

recover the 'true' process used to generate the data, but whether we can arrive at

the simplest but accurate explanation for these data. The failures to recover the

'true' model highlighted above may reflect that a process other than that used to

generate the data could have been used to do so in a simpler way. Simpler here

means we would have to diverge to a lesser degree, from our prior beliefs, in order

to explain the data under a given model, relative to a more complex model. It is

worth highlighting the importance of the word *prior* in the previous sentence. This

means that the simplicity of the model is sensitive to our prior beliefs about it. To

illustrate this, we repeated the same model comparisons as above, but with precise

beliefs in an 'A' matrix that complies with that used to generate the data. Specifically,

we repeated the three simulations above but only enabled 'D' matrix learning (i.e.,

the model was already equipped with the 'A' matrix of the generative process). In

each case, Bayesian model reduction now uniquely identified the correct reduced

model in 100% of cases.

These results demonstrate that – after a naïve model has expanded its hidden

state space to include likelihood mappings and initial state priors for a number of

concept categories – Bayesian model reduction can subsequently be used to

eliminate any parameter updates accrued for *one or two* redundant concept

categories. In practice, the 'A' and 'D' concentration parameters for these redundant

categories could be reset to their default pre-learning values – and could then be re-

engaged if new patterns of observations were repeatedly observed in the future.

However, when three concepts should be removed, Bayesian model reduction was

much less reliable. This appeared to be due to imperfect 'A' matrix learning, when

occurring simultaneously with the (resultingly noisy) accumulation of prior

expectations over hidden states – as a fully precise 'A' matrix led to correct model

reduction in every case tested (i.e., suggesting that this type of model reduction

procedure could be improved by first allowing state-observation learning to

proceed alone, then subsequently allowing the model to learn prior expectations

over hidden states, which could then be used in model reduction).

Can concept acquisition allow for generalization?

One important ability afforded by concept learning is generalization. In a

final set of simulations, we asked if our model of concept knowledge could account

for generalization. To do so, we altered the model such that it no longer reported

what it saw, but instead had to answer a question that depended on generalization

from particular cross-category feature combinations. Specifically, the model was

shown particular animals and asked: "could this be seen from a distance?" The

answer to this question depended on both size and color, such that the answer was

yes only for colorful, large animals (i.e., assuming small or gray animals would blend

in with the sky or water and be missed).

Crucially, this question was asked of animals that the model had not been

exposed to, such that it had to generalize from knowledge it already possessed (see

Figure 7). To simulate and test for this ability, we equipped the model's 'A' matrix

with expert knowledge of 7 out of the 8 animals (i.e., as if these concepts had been

learned previously, as in our simulations above). The 8[th] animal was unknown to the

agent, in that it's likelihood mapping was set such that the 8[th] animal state "slot"

predicted all observations roughly equally. In one variant, the model possessed all

concepts except for "parrot," and it knew that the answer to the question was yes for

"whale shark" but not for any other concept it knew. To simulate one-shot

generalization, learning was disabled and a parrot (which it had never seen before)

was presented 20 times to see if it would correctly generalize and answer "yes" in a

reliable manner. In another variant, the model had learned all concepts except

"minnow" and was tested the same way to see if it would reliably provide the

correct "no" response.

Here, we observed that in both of these cases (as well as all others we tested)

the model generalized remarkably well. It answered "yes" and "no" correctly in

100% of trials. Thus, the agent did not simply possess concepts to explain things it

saw. It instead demonstrated generalizable knowledge and could correctly answer

questions when seeing a novel stimulus.

Generalization:

Could this novel animal be seen from a distance?

Parrot: "Yes"

Minnow: "No"

Figure 7. Depiction of simulations in which we tested the agents ability to generalize from
prior knowledge and correctly answered questions about new animals to which it had not
previously been exposed. In the simulations, the generative model was modified so that the
agent instead chose to report either "yes" or "no" to the question: "could this animal be seen
from a distance?" Here, the answer was only yes if the animal was both large and colorful.
We observed that when the agent started out with no knowledge of parrots it still correctly
answered this question 100% of the time, based only on its knowledge of other animals.
Similarly, when it started with no knowledge of minnows, it also correctly reported "no"
100% of the time. Thus, the agent was able to generalize from prior knowledge with no
additional learning.

Open Questions and relation to other theoretical accounts of concept learning

As our simulations show, this model allows for learning novel concepts (i.e.,

novel hidden states) based on assigning one or more 'open slots' that can be utilised

to learn novel feature combinations. In a simple example, we have shown that this

setup offers a potential computational mechanism for 'model expansion'; i.e., the

process of expanding a state space to account for novel instances in perceptual

categorisation. We also illustrated how this framework can be combined with model

reduction, which may be a mechanism for 're-setting' these open slots based on

recent experience.

This provides a first step towards understanding how agents flexibly expand

or reduce their model of active inference to adapt to ongoing experience. Yet,

several open questions remain, which have partly been addressed in previous work.

For example, the proposed framework resonates with previous similarity-based

accounts of concept learning. Previous work has proposed a computational

framework for arbitrating between assigning an observation to a previously formed

memory or forming a novel (hidden) state representation (S. J. Gershman, Monfils,

Norman, & Niv, 2017), based on evidence that this observation was sampled from an

existing or novel latent state. This process is conceptually similar to our application

of Bayesian model reduction over states. In the present framework, concept learning

relies on a process based on inference and learning. First, agents have to *infer*

whether ongoing observations can be sufficiently explained by existing conceptual

knowledge – or speak to the presence of a novel concept that motivates the use of an

'open slot'. This process is cast as inference on (hidden) states. Second, if the agent

infers that there is a novel concept that explains current observations, it has to *learn*

about the specific feature configuration of that concept (i.e., novel state). This

process highlights the interplay between inference, which allows for the acquisition

of knowledge on a relatively short timescale, and learning, which allows for

knowledge acquisition on a longer and more stable timescale.

Similar considerations apply to the degree of 'similarity' of observations. In

the framework proposed here, we have assumed that the feature space of

observations is already learned and fixed. However, these feature spaces have to be

learned in the first place, which implies learning the underlying components or

feature dimensions that define observations. This relates closely to notions of

structure learning as dimensionality reduction based on covariance between

observations, as prominently discussed in the context of spatial navigation (Behrens

et al., 2018; Dordek, Soudry, Meir, & Derdikman, 2016; Stachenfeld et al., 2016;

Whittington, Muller, Mark, Barry, & Behrens, 2018).

Another important issue is how such abstract conceptual knowledge is

formed across different contexts or tasks. For example, the abstract concept of a

'bird' will be useful for learning about the fauna in a novel environment, but specific

types of birds – tied to a previous context – might be less useful in this regard. This

speaks to the formation of abstract, task-general knowledge that results from

training across different tasks, as recently discussed in the context of meta-

reinforcement learning (Ritter, Wang, Kurth-Nelson, & Botvinick, 2018; J X Wang et

al., 2016) with a putative link to the prefrontal cortex (Jane X. Wang et al., 2018). In

the present framework, such task-general knowledge would speak to the formation

of a hierarchical organisation that allows for the formation of conceptual knowledge

both within and across contexts. Also note that our proposed framework depends

on a pre-defined state space, including a pre-defined set of 'open slots' that allow for

novel context learning. The contribution of the present framework is to show how

these 'open slots' can be used for novel concept learning and be re-set based on

model reduction. It will be important to extend this approach towards learning the

structure of these models in the first place, including the number of 'open slots' (i.e.,

columns of the A-matrix) and the relevant feature dimensions of observations (i.e.,

rows of A-matrix).

This is a potentially powerful and simple application of Bayesian model

reduction, in which candidate models (i.e., reduced forms of a full model) are readily

identifiable based upon the similarity between the likelihoods conditioned upon

different hidden states. If two or more likelihoods are sufficiently similar, the hidden

states can be merged (by assigning the concentration parameters accumulated

during experience-dependent learning to one or other of the hidden states). The

ensuing change in model evidence scores the reduction in complexity. If this

reduction is greater than the loss of accuracy – in relation to observations

previously encountered – Bayesian model reduction will, effectively, merge one

state into another; thereby freeing up a state for the learning of new concepts. We

will demonstrate this form of structure learning via Bayesian model reduction in

future work.

Discussion

The Active Inference formulation of concept learning presented here

demonstrates a simple way in which a generative model can acquire both basic and

highly granular knowledge of the hidden states/causes in its environment. In

comparison to previous theoretical work using active inference (e.g., (M. Mirza,

Adams, Mathys, & Friston, 2016; Parr & Friston, 2017; Schwartenbeck, FitzGerald,

Mathys, Dolan, & Friston, 2015)), the novel aspect of our model was that it was

further equipped with "reserve" hidden states initially devoid of content (i.e., these

states started out with uninformative likelihood mappings that predicted all

outcomes with roughly equal probability). Over multiple exposures to different

stimuli, these hidden states came to acquire conceptual content that captured

distinct statistical patterns in the features of those stimuli. This was accomplished

via the model's ability to infer when its currently learned hidden states were unable

to account for a new observation, leading an unused hidden state column to be

engaged that could acquire a new state-observation mapping.

Crucially, the model was able to start with some concepts and then expand its

representational repertoire to learn others, but would only do so when a new

stimulus was observed. This is conceptually similar to nonparametric Bayesian

learning models, such as the "Chinese Room" process and the "Indian Buffet"

process, that can also infer the need to invoke additional hidden causes with

additional data (S. Gershman & Blei, 2012). These statistical learning models do not

need to build in additional "category slots" for learning as in our model and can, in

principle, entertain infinite state spaces. On the other hand, it is less clear at present

how the brain could implement this type of learning. An advantage of our model is

that learning depends solely on biologically plausible Hebbian mechanisms (for a

possible neural implementation of model reduction, see (KJ Friston, Lin, et al., 2017;

Hobson & Friston, 2012; Hobson, Hong, & Friston, 2014b)).

The distinction between nonparametric Bayesian learning and the current

active learning scheme may be important from a neurodevelopmental perspective.

In brief, structure learning in this paper starts with a generative model with 'spare

capacity', where uncommitted or naive conceptual 'slots' are used to explain the

sensorium, during optimization of free energy or model evidence. In contrast,

nonparametric Bayesian approaches add new slots when appropriate. One might

imagine that neonates are equipped with brains with 'spare capacity' (Baker &

Tenenbaum, 2014) that is progressively leveraged during neurodevelopment, much

in the spirit of curriculum learning (Al-Muhaideb & Menai, 2011). In this sense, the

current approach to structure learning may be better considered as active learning

with generative models that are equipped with a large number of hidden states,

which are judiciously reduced – via a process of Bayesian model reduction.

Furthermore, as in the acquisition of expertise, our model can also begin with broad

category knowledge and then subsequently learn finer-grained within-category

distinctions, which has received less attention from the perspective of the

aforementioned models. Reporting broad versus specific category recognition is

also a distinct aspect of our model – driven by differing levels of uncertainty and an

expectation (preference) not to incorrectly report a more specific category.

Although not the primary topic of the present paper, it is worth briefly noting

that our model could shape hypotheses about the micro-anatomical neural

implementation of concept acquisition. In current micro-anatomical neural process

theories associated with active inference (Bastos et al., 2012; KJ Friston, FitzGerald,

et al., 2017; KJ Friston, Rosch, Parr, Price, & Bowman, 2018; Parr & Friston, 2018),

distinct cortical columns represent distinct hidden states. Based on these theories,

the present model would predict that the brain contains "reserve" cortical columns

and synapses (most likely within secondary sensory and association cortices)

available to capture new patterns in observed features. To our knowledge, no direct

evidence supporting the presence of unused cortical columns in the brain has been

observed, although the generation of new neurons (with new synaptic connections)

is known to occur in the hippocampus (Chancey et al., 2013). "Silent synapses" have

also been observed in the brain, which does appear consistent with this prediction;

such synapses can persist into adulthood and only become activated when new

learning becomes necessary (e.g., see (Chancey et al., 2013; Funahashi, Maruyama,

Yoshimura, & Komatsu, 2013; Kerchner & Nicoll, 2008)). One way in which this idea

of "spare capacity" or "reserve" cortical columns might be tested in the context of

neuroimaging would be to examine whether greater levels of neural activation

within conceptual processing regions are observed after learning additional

concepts, which would imply that additional populations of neurons are now

capable of being activated. In principle, single-cell recording methods might also test

for the presence of neurons that remain at baseline firing rates during task

conditions that would activate conceptual processing, but then become sensitive to

new stimuli within the relevant conceptual domain after learning.

Our simulation results also demonstrated that, when combined with

Bayesian model reduction, the model can guard against learning too many

categories during model expansion – often retaining only the number of hidden

causes actually present in its environment – and to keep "reserve" hidden states for

learning about new causes if or when they appear. With perfect "expert" knowledge

of the possible animal types it could observe (i.e., fully precise likelihood mappings

matching the generative process) this was true in general. Interestingly, however,

with an imperfectly learned likelihood mapping, model reduction only succeeded

when the agent had to remove either 1 or 2 concepts from her model; when 3

potential categories needed to be removed, the correct reduced model was

identified less than half the time. It would be interesting to empirically test whether

similar learning difficulties are present in humans.

Neurobiological theories associated with Active Inference also make

predictions about the neural basis of this process (Hobson & Friston, 2012; Hobson

et al., 2014b). Specifically, during periods of rest (e.g., daydreaming) or sleep, it is

suggested that, because sensory information is down-weighted, learning is driven

mainly by internal model simulations (e.g., as appears to happen in the phenomenon

of hippocampal replay; (Feld & Born, 2017; Lewis, Knoblich, & Poe, 2018; Pfeiffer &

Foster, 2013)); this type of learning can accomplish a model reduction process in

which redundant model parameters are identified and removed to prevent model

over-fitting and promote selection of the most parsimonious model that can

successfully account for previous observations. This is consistent with work

suggesting that, during sleep, many (but not all) synaptic strength increases

acquired in the previous day are attenuated (Tononi & Cirelli, 2014). The role of

sleep and daydreaming in keeping "reserve" representational resources available

for model expansion could therefore be especially important to concept learning –

consistent with the known role of sleep in learning and memory (Ackermann &

Rasch, 2014; Feld & Born, 2017; Perogamvros & Schwartz, 2012; Stickgold, Hobson,

Fosse, & Fosse, 2001; Walker & Stickgold, 2010).

In addition, an emergent feature of our model was its ability to generalize

prior knowledge to new stimuli to which it had not previously been exposed. In fact,

the model could correctly generalize upon a single exposure to a new stimulus – a

type of "one-shot learning" capacity qualitatively similar to that observed in humans

(Landau, Smith, & Jones, 1988; E. Markman, 1989; Xu & Tenenbaum, 2007b). While

it should be kept in mind that the example we have provided is very simple, it

demonstrates the potential usefulness of this novel approach. Some other

prominent approaches in machine-learning (e.g., deep learning) tend to require

larger amounts of data (Geman et al., 1992; Hinton et al., 2012; LeCun et al., 2015;

Lecun et al., 1998; Mnih et al., 2015), and do not learn the rich structure that allows

humans to use concept knowledge in a wide variety of generalizable functions

(Barsalou, 1983; Biederman, 1987; Feldman, 1997; Jern & Kemp, 2013; A. B.

Markman & Makin, 1998; Osherson & Smith, 1981; Ward, 1994; Williams &

Lombrozo, 2010). Other recent hierarchical Bayesian approaches in cognitive

science have made progress in this domain, however, by modeling concepts as types

of probabilistic programs (Ghahramani, 2015; Goodman, Tenenbaum, &

Gerstenberg, 2015; Lake et al., 2015).

It is important to note that this model is deliberately simple and is meant

only to represent a proof of principle that categorical inference and conceptual

knowledge acquisition can be modeled within this particular neurocomputational

framework. We chose a particular set of feature combinations to illustrate this, but it

remains to be demonstrated that learning in this model would be equally successful

with a larger feature space and set of learnable hidden causes.

Finally, another topic for future work would be the expansion of this type of

model to context-specific learning (e.g., with an additional hidden state factor for

encoding distinct contexts). In such cases, regularities in co-occurring features differ

in different contexts and other cues to context may not be directly observable (e.g.,

the same species of bird could be a slightly different color or size in different parts

of the world that otherwise appear similar) – creating difficulties in inferring when

to update previously learned associations and when to instead acquire competing

associations assigned to new contexts. At present, it is not clear whether the

approach we have illustrated would be successful at performing this additional

function (for related work on context-dependent contingency learning, see (S. J.

Gershman et al., 2017; S. Gershman, Jones, Norman, Monfils, & Niv, 2013)). Another

point worth highlighting is that we have made particular choices with regard to

various model parameters and the number of observations provided during

learning. Further investigations of the space of these possible parameter settings

will be important. With this in mind, however, our current modelling results could

offer additional benefits. For example, the model's simplicity could be amenable to

empirical studies of saccadic eye movements toward specific features during novel

category learning (e.g. following the approach of (M. B. Mirza, Adams, Mathys, &

Friston, 2018)). This approach could also be combined with measures of neural

activity in humans or other animals, allowing more direct tests of the predictions

highlighted above. In addition, the introduction of exploratory, novelty-seeking,

actions could be used to reduce the number of samples required for learning, with

agents selecting those data that are most relevant.

In conclusion, the Active Inference scheme we have described illustrates

feature integration in the service of conceptual inference: it can successfully

simulate simple forms of concept acquisition and concept differentiation (i.e.

increasing granularity), and it spontaneously affords one-shot generalization.

Finally, it speaks to empirical work in which behavioral tasks could be designed to

fit such models, which would allow investigation of individual differences in concept

learning and its neural basis. For example, such a model could simulate (neuronal)

belief updating to predict neuroimaging responses; i.e., to identify the neural

networks engaged in evidence accumulation and learning (Schwartenbeck et al.,

2015). In principle, the model parameters (e.g., 'A' matrix precision) can also be fit

to behavioral choices and reaction times – and thereby phenotype subjects in terms

of the priors under which they infer and learn (Schwartenbeck & Friston, 2016).

This approach could therefore advance neurocomputational approaches to concept

learning in several directions.

References

Ackermann, S., & Rasch, B. (2014). Differential Effects of Non-REM and REM Sleep

on Memory Consolidation? *Current Neurology and Neuroscience Reports*, *14*(2),

430. https://doi.org/10.1007/s11910-013-0430-8

Al-Muhaideb, S., & Menai, M. E. B. (2011). Evolutionary computation approaches to

the Curriculum Sequencing problem. *Natural Computing*, *10*(2), 891–920.

https://doi.org/10.1007/s11047-010-9246-5

Baker, C., & Tenenbaum, J. (2014). Modeling human plan recognition using Bayesian

theory of mind. In G. Sukthankar, C. Geib, H. Dui, D. Pynadath, & R. Goldman

(Eds.), *Plan, activity, and intent recognition* (pp. 177–204). Boston: Morgan

Kaufmann.

Barsalou, L. W. (1983). Ad hoc categories. *Memory & Cognition*, *11*(3), 211–227.

https://doi.org/10.3758/bf03196968

Bastos, A., Usrey, W., Adams, R., Mangun, G., Fries, P., & Friston, K. (2012). Canonical

microcircuits for predictive coding. *Neuron*, *76*(4), 695–711.

https://doi.org/10.1016/j.neuron.2012.10.038

Behrens, T. E. J., Muller, T. H., Whittington, J. C. R., Mark, S., Baram, A. B., Stachenfeld,

K. L., & Kurth-Nelson, Z. (2018). What Is a Cognitive Map? Organizing

Knowledge for Flexible Behavior. *Neuron*, *100*(2), 490–509.

https://doi.org/10.1016/J.NEURON.2018.10.002

Biederman, I. (1987). Recognition-by-components: a theory of human image

understanding. *Psychological Review*, *94*(2), 115–147.

https://doi.org/10.1037/0033-295X.94.2.115

Botvinick, M. M., Niv, Y., & Barto, A. C. (2009). Hierarchically organized behavior and

its neural foundations: A reinforcement learning perspective. *Cognition*, *113*(3),

262–280. https://doi.org/10.1016/J.COGNITION.2008.08.011

Box, G. E., Hunter, J. S., & Hunter, W. G. (2005). *Statistics for experimenters. Wiley*

Series in Probability and Statistics. Hoboken, NJ.: Wiley.

Brown, T. H., Zhao, Y., & Leung, V. (2010). Hebbian plasticity. In *Encyclopedia of*

Neuroscience (pp. 1049–1056). https://doi.org/10.1016/B978-008045046-

9.00796-8

Chancey, J., Adlaf, E., Sapp, M., Pugh, P., Wadiche, J., & Overstreet-Wadiche, L. (2013).

GABA depolarization is required for experience-dependent synapse unsilencing

in adult-born neurons. *The Journal of Neuroscience : The Official Journal of the*

Society for Neuroscience, *33*(15), 6614–6622.

https://doi.org/10.1523/JNEUROSCI.0781-13.2013

Conant, C., & Ashbey, W. (1970). Every good regulator of a system must be a model

of that system. *International Journal of Systems Science*, *1*(2), 89–97.

https://doi.org/10.1080/00207727008920220

Cornish, N. J., & Littenberg, T. B. (2007). Tests of Bayesian model selection

techniques for gravitational wave astronomy. *Physical Review D*, *76*(8), 083006.

https://doi.org/10.1103/PhysRevD.76.083006

Dordek, Y., Soudry, D., Meir, R., & Derdikman, D. (2016). Extracting grid cell

characteristics from place cell inputs using non-negative principal component

analysis. *ELife*, *5*(MARCH2016), 1–36. https://doi.org/10.7554/eLife.10094

Feld, G., & Born, J. (2017). Sculpting memory during sleep: concurrent consolidation

and forgetting. *Current Opinion in Neurobiology*, *44*, 20–27.

https://doi.org/10.1016/J.CONB.2017.02.012

Feldman, J. (1997). The Structure of Perceptual Categories. *Journal of Mathematical*

Psychology, *41*(2), 145–170. https://doi.org/10.1006/jmps.1997.1154

Friston, K. (2010). The free-energy principle: a unified brain theory? *Nature Reviews.*

Neuroscience, *11*(2), 127–138. https://doi.org/10.1038/nrn2787

Friston, K., FitzGerald, T., Rigoli, F., Schwartenbeck, P., O Doherty, J., & Pezzulo, G.

(2016). Active inference and learning. *Neuroscience and Biobehavioral Reviews*,

68, 862–879. https://doi.org/10.1016/j.neubiorev.2016.06.022

Friston, K., FitzGerald, T., Rigoli, F., Schwartenbeck, P., & Pezzulo, G. (2017). Active

Inference: A Process Theory. *Neural Computation*, *29*(1), 1–49.

https://doi.org/10.1162/NECO_a_00912

Friston, K. J., Litvak, V., Oswal, A., Razi, A., Stephan, K. E., van Wijk, B. C. M., …

Zeidman, P. (2016). Bayesian model reduction and empirical Bayes for group

(DCM) studies. *NeuroImage*, *128*, 413–431.

https://doi.org/10.1016/J.NEUROIMAGE.2015.11.015

Friston, K., Lin, M., Frith, C., Pezzulo, G., Hobson, J., & Ondobaka, S. (2017). Active

Inference, Curiosity and Insight. *Neural Computation*, *29*(10), 2633–2683.

https://doi.org/10.1162/neco_a_00999

Friston, K., Mattout, J., Trujillo-Barreto, N., Ashburner, J., & Penny, W. (2007).

Variational free energy and the Laplace approximation. *NeuroImage*, *34*(1),

220–234. https://doi.org/10.1016/J.NEUROIMAGE.2006.08.035

Friston, K., Parr, T., & de Vries, B. (2017). The graphical brain: Belief propagation

and active inference. *Network Neuroscience*, *1*(4), 381–414.

https://doi.org/10.1162/NETN_a_00018

Friston, K., Parr, T., & Zeidman, P. (2018). Bayesian model reduction. Retrieved from

http://arxiv.org/abs/1805.07092

Friston, K., & Penny, W. (2011). Post hoc Bayesian model selection. *NeuroImage*,

56(4), 2089–2099. https://doi.org/10.1016/J.NEUROIMAGE.2011.03.062

Friston, K., Rosch, R., Parr, T., Price, C., & Bowman, H. (2018). Deep temporal models

and active inference. *Neuroscience & Biobehavioral Reviews*, *90*, 486–501.

https://doi.org/10.1016/J.NEUBIOREV.2018.04.004

Funahashi, R., Maruyama, T., Yoshimura, Y., & Komatsu, Y. (2013). Silent synapses

persist into adulthood in layer 2/3 pyramidal neurons of visual cortex in dark-

reared mice. *Journal of Neurophysiology*, *109*(8), 2064–2076.

https://doi.org/10.1152/jn.00912.2012

Geman, S., Bienenstock, E., & Doursat, R. (1992). Neural Networks and the

Bias/Variance Dilemma. *Neural Computation*, *4*(1), 1–58.

https://doi.org/10.1162/neco.1992.4.1.1

Gershman, S., & Blei, D. (2012). A tutorial on Bayesian nonparametric models.

Journal of Mathematical Psychology, *56*(1), 1–12.

https://doi.org/10.1016/J.JMP.2011.08.004

Gershman, S. J., Monfils, M.-H., Norman, K. A., & Niv, Y. (2017). The computational

nature of memory modification. *ELife*, *6*. https://doi.org/10.7554/eLife.23763

Gershman, S. J., & Niv, Y. (2010). Learning latent structure: carving nature at its

joints. *Current Opinion in Neurobiology*, *20*(2), 251–256.

https://doi.org/10.1016/J.CONB.2010.02.008

Gershman, S., Jones, C., Norman, K., Monfils, M., & Niv, Y. (2013). Gradual extinction

prevents the return of fear: implications for the discovery of state. *Frontiers in*

Behavioral Neuroscience, *7*, 164. https://doi.org/10.3389/fnbeh.2013.00164

Ghahramani, Z. (2015). Probabilistic machine learning and artificial intelligence.

Nature, *521*(7553), 452–459. https://doi.org/10.1038/nature14541

Goodman, N. D., Tenenbaum, J. B., & Gerstenberg, T. (2015). *Concepts: New*

Directions. (E. Margolis & S. Laurence, Eds.). Cambridge, MA: MIT Press.

Hinton, G., Deng, L., Yu, D., Dahl, G., Mohamed, A., Jaitly, N., … Kingsbury, B. (2012).

Deep Neural Networks for Acoustic Modeling in Speech Recognition: The

Shared Views of Four Research Groups. *IEEE Signal Processing Magazine*, *29*(6),

82–97. https://doi.org/10.1109/MSP.2012.2205597

Hobson, J., & Friston, K. (2012). Waking and dreaming consciousness:

neurobiological and functional considerations. *Progress in Neurobiology*, *98*(1),

82–98. https://doi.org/10.1016/j.pneurobio.2012.05.003

Hobson, J., Hong, C.-H., & Friston, K. (2014a). Virtual reality and consciousness

inference in dreaming. *Frontiers in Psychology*, *5*, 1133.

https://doi.org/10.3389/fpsyg.2014.01133

Hobson, J., Hong, C.-H., & Friston, K. (2014b). Virtual reality and consciousness

inference in dreaming. *Frontiers in Psychology*, *5*, 1133.

https://doi.org/10.3389/fpsyg.2014.01133

Jern, A., & Kemp, C. (2013). A probabilistic account of exemplar and category

generation. *Cognitive Psychology*, *66*(1), 85–125.

https://doi.org/10.1016/j.cogpsych.2012.09.003

Kemp, C., Perfors, A., & Tenenbaum, J. (2007). Learning overhypotheses with

hierarchical Bayesian models. *Developmental Science*, *10*(3), 307–321.

https://doi.org/10.1111/j.1467-7687.2007.00585.x

Kerchner, G., & Nicoll, R. (2008). Silent synapses and the emergence of a

postsynaptic mechanism for LTP. *Nature Reviews. Neuroscience*, *9*(11), 813–

825. https://doi.org/10.1038/nrn2501

Lake, B., Salakhutdinov, R., & Tenenbaum, J. (2015). Human-level concept learning

through probabilistic program induction. *Science (New York, N.Y.)*, *350*(6266),

1332–1338. https://doi.org/10.1126/science.aab3050

Landau, B., Smith, L. B., & Jones, S. S. (1988). The importance of shape in early lexical

learning. *Cognitive Development*, *3*(3), 299–321.

https://doi.org/10.1016/0885-2014(88)90014-7

LeCun, Y., Bengio, Y., & Hinton, G. (2015). Deep learning. *Nature*, *521*(7553), 436–

444. https://doi.org/10.1038/nature14539

Lecun, Y., Bottou, L., Bengio, Y., & Haffner, P. (1998). Gradient-based learning

applied to document recognition. *Proceedings of the IEEE*, *86*(11), 2278–2324.

https://doi.org/10.1109/5.726791

Lewis, P., Knoblich, G., & Poe, G. (2018). How Memory Replay in Sleep Boosts

Creative Problem-Solving. *Trends in Cognitive Sciences*, *22*(6), 491–503.

https://doi.org/10.1016/j.tics.2018.03.009

MacKay, D. J. C., & Peto, L. C. B. (1995). A hierarchical Dirichlet language model.

Natural Language Engineering, *1*(03), 289–308.

https://doi.org/10.1017/S1351324900000218

Markman, A. B., & Makin, V. S. (1998). Referential communication and category

acquisition. *Journal of Experimental Psychology. General*, *127*(4), 331–354.

https://doi.org/10.1037/0096-3445.127.4.331

Markman, E. (1989). *Categorization and Naming in Children*. Cambridge, MA: MIT

Press.

McKay, R., & Dennett, D. (2009). The evolution of misbelief. *Behavioral and Brain*

Sciences, *32*(06), 493. https://doi.org/10.1017/S0140525X09990975

McNicholas, P. (2016). Model-Based Clustering. *Journal of Classification*, *33*(3), 331–

373. https://doi.org/10.1007/s00357-016-9211-9

Mirza, M., Adams, R., Mathys, C., & Friston, K. (2016). Scene Construction, Visual

Foraging, and Active Inference. *Frontiers in Computational Neuroscience*, *10*, 56.

https://doi.org/10.3389/fncom.2016.00056

Mirza, M. B., Adams, R. A., Mathys, C., & Friston, K. J. (2018). Human visual

exploration reduces uncertainty about the sensed world. *PLOS ONE*, *13*(1),

e0190429. https://doi.org/10.1371/journal.pone.0190429

Mnih, V., Kavukcuoglu, K., Silver, D., Rusu, A. A., Veness, J., Bellemare, M. G., …

Hassabis, D. (2015). Human-level control through deep reinforcement learning.

Nature, *518*(7540), 529–533. https://doi.org/10.1038/nature14236

Osherson, D. N., & Smith, E. E. (1981). On the adequacy of prototype theory as a

theory of concepts. *Cognition*, *9*(1), 35–58. https://doi.org/10.1016/0010-

0277(81)90013-5

Parr, T., & Friston, K. (2017). Working memory, attention, and salience in active

inference. *Scientific Reports*, *7*(1), 14678. https://doi.org/10.1038/s41598-

017-15249-0

Parr, T., & Friston, K. (2018). The Anatomy of Inference: Generative Models and

Brain Structure. *Frontiers in Computational Neuroscience*, *12*, 90.

https://doi.org/10.3389/fncom.2018.00090

Perfors, A., Tenenbaum, J., Griffiths, T., & Xu, F. (2011). A tutorial introduction to

Bayesian models of cognitive development. *Cognition*, *120*(3), 302–321.

https://doi.org/10.1016/j.cognition.2010.11.015

Perogamvros, L., & Schwartz, S. (2012). The roles of the reward system in sleep and

dreaming. *Neuroscience & Biobehavioral Reviews*, *36*(8), 1934–1951.

https://doi.org/10.1016/J.NEUBIOREV.2012.05.010

Pfeiffer, B., & Foster, D. (2013). Hippocampal place-cell sequences depict future

paths to remembered goals. *Nature*, *497*(7447), 74–79.

https://doi.org/10.1038/nature12112

Ritter, S., Wang, J., Kurth-Nelson, Z., & Botvinick, M. (2018). Episodic Control as

Meta-Reinforcement Learning. *BioRxiv*, 360537.

https://doi.org/10.1101/360537

Salakhutdinov, R., Tenenbaum, J. B., & Torralba, A. (2013). Learning with

hierarchical-deep models. *IEEE Transactions on Pattern Analysis and Machine*

Intelligence, *35*(8), 1958–1971. https://doi.org/10.1109/TPAMI.2012.269

Schmidhuber, J. (2006). Developmental robotics, optimal artificial curiosity,

creativity, music, and the fine arts. *Connection Science*, *18*(2), 173–187.

https://doi.org/10.1080/09540090600768658

Schwartenbeck, P., FitzGerald, T., Mathys, C., Dolan, R., & Friston, K. (2015). The

Dopaminergic Midbrain Encodes the Expected Certainty about Desired

Outcomes. *Cerebral Cortex*, *25*(10), 3434–3445.

https://doi.org/10.1093/cercor/bhu159

Schwartenbeck, P., & Friston, K. (2016). Computational Phenotyping in Psychiatry: A

Worked Example. *ENeuro*, *3*(4), ENEURO.0049-0016.2016.

https://doi.org/10.1523/ENEURO.0049-16.2016

Sharot, T. (2011). The optimism bias. *Current Biology*, *21*(23), R941–R945.

https://doi.org/10.1016/J.CUB.2011.10.030

Stachenfeld, K. L., Botvinick, M. M., & Gershman, S. J. (2016). The hippocampus as a

predictive map.

Stickgold, R., Hobson, J., Fosse, R., & Fosse, M. (2001). Sleep, learning, and dreams:

off-line memory reprocessing. *Science*, *294*(5544), 1052–1057.

https://doi.org/10.1126/science.1063530

Tervo, D. G. R., Tenenbaum, J. B., & Gershman, S. J. (2016). Toward the neural

implementation of structure learning. *Current Opinion in Neurobiology*, *37*, 99–

105. https://doi.org/10.1016/J.CONB.2016.01.014

Tononi, G., & Cirelli, C. (2014). Sleep and the Price of Plasticity: From Synaptic and

Cellular Homeostasis to Memory Consolidation and Integration. *Neuron*, *81*(1),

12–34. https://doi.org/10.1016/J.NEURON.2013.12.025

Walker, M., & Stickgold, R. (2010). Overnight alchemy: sleep-dependent memory

evolution. *Nature Reviews. Neuroscience*, *11*(3), 218; author reply 218.

https://doi.org/10.1038/nrn2762-c1

Wang, J. X., Kurth-Nelson, Z., Kumaran, D., Tirumala, D., Soyer, H., Leibo, J. Z., …

Botvinick, M. (2018). Prefrontal cortex as a meta-reinforcement learning

system. *Nature Neuroscience*, *21*(6), 860–868.

https://doi.org/10.1038/s41593-018-0147-8

Wang, J. X., Kurth-Nelson, Z., Tirumala, D., Soyer, H., Leibo, J. Z., Munos, R., …

Botvinick, M. (2016). Learning to reinforcement learn. *ArXiv:1611.05763*.

Ward, T. B. (1994). Structured Imagination: the Role of Category Structure in

Exemplar Generation. *Cognitive Psychology*, *27*(1), 1–40.

https://doi.org/10.1006/cogp.1994.1010

Whittington, J. C. R., Muller, T. H., Mark, S., Barry, C., & Behrens, T. E. J. (2018).

Generalisation of structural knowledge in the hippocampal-entorhinal system.

Williams, J. J., & Lombrozo, T. (2010). The role of explanation in discovery and

generalization: evidence from category learning. *Cognitive Science*, *34*(5), 776–

806. https://doi.org/10.1111/j.1551-6709.2010.01113.x

Wipf, D. P., & Rao, B. D. (2007). An Empirical Bayesian Strategy for Solving the

Simultaneous Sparse Approximation Problem. *IEEE Transactions on Signal*

Processing, *55*(7), 3704–3716. https://doi.org/10.1109/TSP.2007.894265

Xu, F., & Tenenbaum, J. (2007a). Sensitivity to sampling in Bayesian word learning.

Developmental Science, *10*(3), 288–297. https://doi.org/10.1111/j.1467-

7687.2007.00590.x

Xu, F., & Tenenbaum, J. (2007b). Word Learning as Bayesian Inference. *Psychological*

Review, *114*(2), 245–272.

1124

1125