An active inference approach to modeling structure learning: concept learning

as an example case

Ryan Smith,[1] Philipp Schwartenbeck,[2] Thomas Parr,[2] Karl J. Friston,[2]

[1]Laureate Institute for Brain Research, Tulsa, OK, USA

[2]Wellcome Centre for Human Neuroimaging, Institute of Neurology, University

College London, WC1N 3BG, UK

12   Corresponding Author Information:

14   Ryan Smith

15   Laureate Institute for Brain Research

16   6655 S Yale Ave, Tulsa, OK 74136, USA

17   Email: rsmith@laureateinstitute.org

18   **Abstract**

Within computational neuroscience, the algorithmic and neural basis of structure

learning remains poorly understood. Concept learning is one primary example,

which requires both a type of internal model expansion process (adding novel

hidden states that explain new observations), and a model reduction process

(merging different states into one underlying cause and thus reducing model

complexity via meta-learning). Although various algorithmic models of concept

learning have been proposed within machine learning and cognitive science, many

are limited to various degrees by an inability to generalize, the need for very large

amounts of training data, and/or insufficiently established biological plausibility.

Using concept learning as an example case, we introduce a novel approach for

modeling structure learning – and specifically state-space expansion and reduction

– within the active inference framework and its accompanying neural process

theory. Our aim is to demonstrate its potential to facilitate a novel line of active

inference research in this area. The approach we lay out is based on the idea that a

generative model can be equipped with extra (hidden state or cause) 'slots' that can

be engaged when an agent learns about novel concepts. This can be combined with a

Bayesian model reduction process, in which any concept learning – associated with

these slots – can be reset in favor of a simpler model with higher model evidence.

We use simulations to illustrate this model's ability to add new concepts to its state

space (with relatively few observations) and increase the granularity of the

concepts it currently possesses. We also simulate the predicted neural basis of these

processes. We further show that it can accomplish a simple form of 'one-shot'

generalization to new stimuli. Although deliberately simple, these simulation results

highlight ways in which active inference could offer useful resources in developing

neurocomputational models of structure learning. They provide a template for how

future active inference research could apply this approach to real-world structure

learning problems and assess the added utility it may offer.

Keywords: Bayesian Model Expansion; Bayesian Model Reduction; Structure

Learning; Concepts; Computational Neuroscience; Active Inference

Introduction

The ability to learn the latent structure of one's environment – such as inferring the existence of hidden causes of regularly observed patterns in co-occurring feature observations – is central to human cognition. For example, we do not simply observe particular sets of colors, textures, shapes, and sizes – we also observe *identifiable object*s such as, say, a 'screwdriver'. If we were tool experts, we might also recognize particular types of screwdrivers (e.g., flat vs. Phillip's head), designed for a particular use. This ability to learn latent structure, such as learning to recognize co-occurring features under conceptual categories (as opposed to just perceiving sensory qualities; e.g., red, round, etc.), is also highly adaptive. Only if we knew an object was a screwdriver could we efficiently infer that it affords putting certain structures together and taking them apart; and only if we knew the specific type of screwdriver could we efficiently infer, say, the artefacts to use it on. Many concepts of this sort require experience-dependent acquisition (i.e., learning).

From a computational perspective, the ability to acquire a new concept can be seen as a type of structure learning involving Bayesian model comparison (MacKay and Peto, 1995; Botvinick et al., 2009; Gershman and Niv, 2010; Salakhutdinov et al., 2013a; Tervo et al., 2016). Specifically, concept acquisition can be cast as an agent learning (or inferring) that a new hypothesis (referred to here as a hidden cause or state) should be added to the internal or generative model with which it explains its environment, because existing causes cannot account for new observations (e.g., an agent might start out believing that the only tools are hammers and screwdrivers, but later learn that there are also wrenches). In other

words, the structure of the space of hidden causes itself needs to expand to

accommodate new patterns of observations. This model expansion process is

complementary to a process called Bayesian model reduction (Friston and Penny,

2011); in which the agent can infer that there is redundancy in its model, and a

model with fewer states or parameters provides a more parsimonious (i.e. simpler)

explanation of observations (Schmidhuber, 2006; Friston et al., 2017b). For

example, in some instances it may be more appropriate to differentiate between fish

and birds as opposed to salmon, peacocks and pigeons. This reflects a reduction in

model complexity based on a particular feature space underlying observations and

thus resonates with other accounts of concept learning as dimensionality reduction

(Stachenfeld et al., 2016; Behrens et al., 2018) – a topic we discuss further below.

83   A growing body of work in a number of domains has approached this

problem from different angles. In developmental psychology and cognitive science,

for example, probability theoretic (Bayesian) models have been proposed to account

for word learning in children and the remarkable human ability to generalize from

very few (or even one) examples in which both broader and narrower categorical

referents could be inferred (Kemp et al., 2007; Xu and Tenenbaum, 2007a, 2007b;

Perfors et al., 2011; Lake et al., 2015). In statistics, a number of nonparametric

Bayesian models, such as the "Chinese Room" process and the "Indian Buffet"

process, have been used to infer the need for model expansion (Gershman and Blei,

2012). There are also related approaches in machine learning, as applied to things

like Gaussian mixture models (McNicholas, 2016), as well as models based on

Bayesian program learning (Lake et al., 2015) and combinations of deep learning

and hierarchical Bayesian methods (Salakhutdinov et al., 2013b).

Such approaches often employ clustering algorithms, which take sets of data

points in a multidimensional space and divide them into separable clusters (e.g., see

(Anderson, 1991; Love et al., 2004; Sanborn et al., 2010)). While many of these

approaches assume the number of clusters is known in advance, various goodness-

of-fit criteria may be used to determine the optimal number. However, a number of

approaches require much larger amounts of data than humans do to learn new

concepts (Geman et al., 1992; Lecun et al., 1998; Hinton et al., 2012; LeCun et al.,

2015; Mnih et al., 2015). Many also require corrective feedback to learn and yet fail

to acquire sufficiently rich conceptual structure to allow for generalization

(Osherson and Smith, 1981; Barsalou, 1983; Biederman, 1987; Ward, 1994;

Feldman, 1997; Markman and Makin, 1998; Williams and Lombrozo, 2010; Jern and

Kemp, 2013).

Approaches to formally modeling structure learning, including concept

learning, have not yet been examined within the emerging field of research on

Active Inference models within computational neuroscience (Friston, 2010; Friston

et al., 2016a, 2017b, 2017c). This represents a novel and potentially fruitful research

avenue that, as discussed below, may offer unique advantages in research focused

on understanding the neural basis of learning latent structure. In this paper, we

explore the potential of this approach. We aim to provide a type of modeling

template that could be used in future active inference research on real-world

structure learning problems – and assess the additional utility it might offer. We

provide a number of example simulations demonstrating how structure learning can

be seen as an emergent property of active inference (and learning) under generative

models with 'spare capacity'; where spare or uncommitted capacity is used to

expand the repertoire of representations (Baker and Tenenbaum, 2014), while

Bayesian model reduction (Hobson and Friston, 2012; Friston et al., 2017b)

promotes generalization by minimizing model complexity – and releasing

representations to replenish 'spare capacity'.

From a machine learning perspective, Bayesian model reduction affords the

opportunity to consider generative models with a large number of hidden states or

latent factors and then optimize the number (or indeed partitions) of latent factors

with respect to a variational bound on model evidence. This could be regarded as a

bounded form of nonparametric Bayes, in which a potentially infinite number of

latent factors are considered; with appropriate (e.g., Indian buffet process) priors

over the number of hidden states generating data features[1]. The approach we

articulate here is bounded in the sense that an upper bound on the number of

hidden states is specified prior to structure learning. Furthermore, in virtue of the

(biologically plausible) variational schemes used for model reduction, there is no

need to explicitly compute model evidence; thereby emulating the computational

efficiency of nonparametric Bayes (Gershman and Blei, 2012), while accommodating

any prior over models.

---

[1] Generally motivated by starting with a finite parametric model and taking the limit as the number of latent states with more parameters tends to infinity.

In what follows, we first provide a brief overview of active inference. We then

introduce a model of concept learning (using basic and subordinate level animal

categories), as a representative example of structure learning. We specifically model

cognitive (semantic) processes that add new concepts to a state space and that

optimize the granularity of an existing state space. We then establish the validity of

this model using numerical analyses of concept learning, when repeatedly

presenting a synthetic agent with different animals characterized by different

combinations of observable features. We demonstrate how particular approaches

combining Bayesian model reduction and expansion can reproduce successful

concept learning without the need for corrective feedback – and allow for

generalization. We further demonstrate the ability of this model to generate

predictions about measurable neural responses based on the neural process theory

that accompanies active inference. We conclude with a brief discussion of the

implications of this work. Our goal is to present an introductory proof of concept –

that could be used as the foundation of future active inference research on the

neurocomputational basis of structure learning.

An Active Inference approach for modeling concept learning through state-

155   **space expansion**

A primer on Active Inference

Active Inference suggests that the brain is an inference machine that

approximates optimal probabilistic (Bayesian) belief updating across perceptual,

cognitive, and motor domains. Active Inference more specifically postulates that the

brain embodies an internal model of the world that is "generative" in the sense that

it can simulate the sensory data that it should receive if its model of the world is

correct. These simulated (predicted) sensory data can be compared to actual

observations, and differences between predicted and observed sensations can be

used to update the model. Over short timescales (e.g., a single observation) this

updating corresponds to inference (perception), whereas on longer timescales it

corresponds to learning (i.e., updating expectations about what will be observed

later). Another way of putting this is that perception optimizes beliefs about the

current state of the world, while learning optimizes beliefs about the relationships

between the variables that constitute the world. These processes can be seen as

ensuring the generative model (entailed by recognition processes in the brain)

remains an accurate model of the world that it seeks to regulate (Conant and

Ashbey, 1970).

Active Inference casts decision-making in similar terms. Actions can be

chosen to resolve uncertainty about variables within a generative model (i.e.,

sampling from domains in which the model does not make precise predictions),

which can prevent anticipated deviations from predicted outcomes. In addition,

some expectations are treated as a fixed phenotype of an organism. For example, if

an organism did not continue to "expect" to observe certain amounts of food, water,

and shelter, then it would quickly cease to exist (McKay and Dennett, 2009) – as it

would not pursue those behaviors that fulfill these expectations (c.f. the 'optimism

bias' (Sharot, 2011)). Thus, a creature should continually seek out observations that

support – or are internally consistent with – its own continued existence. Decision-

making can therefore be cast as a process in which the brain infers the sets of

actions (policies) that would lead to observations consistent with its own survival-

related expectations (i.e., its "prior preferences"). Mathematically, this can be

described as selecting sequences of actions (policies) that maximize "Bayesian

model evidence" expected under a policy, where model evidence is the (marginal)

likelihood that particular sensory inputs would be observed under a given model.

In real-world settings, directly computing Bayesian model evidence is

generally intractable. Thus, some approximation is necessary. Active Inference

proposes that the brain computes a quantity called "variational free energy" that

provides a bound on model evidence, such that minimization of free energy

indirectly maximizes model evidence (this is exactly the same functional used in

machine learning where it is known as an evidence lower bound or ELBO). In this

case, decision-making will be approximately (Bayes) optimal if it infers (and enacts)

the policy that will minimize expected free energy (i.e., free energy with respect to a

policy, where one takes expected future observations into account). Technically,

expected free energy is the average free energy under the posterior predictive

density over policy-specific outcomes.

Expected free energy can be decomposed in different ways that reflect

uncertainty and prior preferences, respectively (e.g., epistemic and instrumental

affordance or ambiguity and risk). This formulation means that any agent that

minimizes expected free energy engages initially in exploratory behavior to

minimize uncertainty in a new environment. Once uncertainty is resolved, the agent

then exploits that environment to fulfill its prior preferences. The formal basis for

Active Inference has been thoroughly detailed elsewhere (Friston et al., 2017a), and

the reader is referred there for a full mathematical treatment.

When the generative model is formulated as a partially observable Markov

decision process (a mathematical framework for modeling decision-making in cases

where some outcomes are under the control of the agent and others are not, and

where states of the world are not directly known but must be inferred from

observations), active inference takes a particular form. Here, the generative model is

specified by writing down plausible or allowable policies, hidden states of the world

(that must be inferred from observations), and observable outcomes, as well as a

number of matrices that define the probabilistic relationships between these

quantities (see right panel of figure 1).

Figure 1. Left: Illustration of the trial structure performed by the agent. At the first time
point, the agent is exposed to one of 8 possible animals that are each characterized by a
unique combination of visual features. At the 2^{nd} time point, the agent would then report
which animal concept matched that feature combination. The agent could report a specific
category (e.g., pigeon, hawk, minnow, etc.) or a general category (i.e., bird or fish) if
insufficiently certain about the specific category. See the main text for more details. Right:
Illustration of the Markov decision process formulation of active inference used in the
simulations described in this paper. The generative model is here depicted graphically, such
that arrows indicate dependencies between variables. Here observations (**o**) depend on
hidden states (**s**), as specified by the **A** matrix, and those states depend on both previous
states (as specified by the **B** matrix, or the initial states specified by the **D** matrix) and the
policies (**π**) selected by the agent. The probability of selecting a particular policy in turn
depends on the expected free energy (**G**) of each policy with respect to the prior preferences
(**C**) of the agent. The degree to which expected free energy influences policy selection is also
modulated by a prior policy precision parameter (**γ**), which is in turn dependent on beta (**β**)
–where higher values of beta promote more randomness in policy selection (i.e., less
influence of the differences in expected free energy across policies). For more details
regarding the associated mathematics, see (KJ Friston, Lin, et al., 2017; KJ Friston, Parr, et
al., 2017).
239

The '**A**' matrix indicates which observations are generated by each

combination of hidden states (i.e., the likelihood mapping specifying the probability

that a particular set of observations would be observed given a particular set of

hidden states). The '**B**' matrix is a transition matrix, indicating the probability that

one hidden state will evolve into another over time. The agent, based on the selected

policy, controls some of these transitions (e.g., those that pertain to the positions of

its limbs). The '**D**' matrix encodes prior expectations about the initial hidden state

the agent will occupy. Finally, the '**C**' matrix specifies prior preferences over

observations; it quantifies the degree to which different observed outcomes are

rewarding or punishing to the agent. In these models, observations and hidden

states can be factorized into multiple outcome *modalities* and hidden state *factors*.

This means that the likelihood mapping (the **A** matrix) can also model the

interactions among different hidden states when generating outcomes

(observations).

From principles to process theories

One potential empirical advantage of the present approach stems from the

fact that active inference models have a plausible biological basis that affords

testable neurobiological predictions. Specifically, these models have well-articulated

companion micro-anatomical neural process theories, based on commonly used

message-passing algorithms (Friston et al., 2017a; Parr and Friston, 2018; Parr et

al., 2019). In these process theories, for example, the activation level of different

263 neural populations (typically portrayed as consisting of different cortical columns)

264 can encode posterior probability estimates over different hidden states. These

265 activation levels can then be updated by synaptic inputs with particular weights that

266 convey the conditional probabilities encoded in the **A** and **B** (among other) matrices

267 described above, where active learning then corresponds to associative synaptic

268 plasticity. Phasic dopamine responses also play a particular role in these models, by

269 reporting changes in policy precision (i.e., the degree of confidence in one policy

270 over others) upon new observations (see Figure 2 and the associated legend for

271 more details). In what follows, we describe how the type of generative model – that

272 underwrites these processes – was specified to perform concept inference/learning.

Figure 2. This figure illustrates the mathematical framework of active inference and
associated neural process theory used in the simulations described in this paper. The
differential equations in the left panel approximate Bayesian belief updating within the
graphical model depicted in the right panel of Figure 1, via a gradient descent on free
energy (**F**). The right panel illustrates a possible neural basis by which neurons making up
cortical columns could implement these equations. The equations have been expressed in
terms of two types of prediction errors. State prediction errors ($\boldsymbol{\varepsilon}$) are used to update
expectations over states (**s**) by driving depolarization (**v**) in neurons encoding those hidden
states. The probability distribution over hidden states is then obtained via a softmax
(normalized exponential) function ($\boldsymbol{\sigma}$). Outcome prediction errors ($\boldsymbol{\varsigma}$) convey the difference
between preferred observations and those predicted under each policy ($\boldsymbol{\pi}$), and are used to
evaluate the expected free energy (**G**) of each policy. This term additionally considers the
expected ambiguity or conditional entropy (**H**) between states and outcomes, as well as a
novelty term (**W**) reflecting the degree to which beliefs about how states generate outcomes
would change upon observing different possible state-outcome mappings. Outcome
prediction errors thus allow policies to be evaluated based on both expected information
gain and expected reward. Policy-specific free energies are then integrated to give the
policy probabilities via a softmax function. Actions at each time point (**u**) are then chosen
out of the possible actions under each policy (**U**), weighted by the probability of each policy.
In our simulations, the model learned associations between hidden states and observations
(**A**) via a process in which counts were accumulated (**a**) reflecting the number of times the
agent observed a particular outcome when it believed that it occupied each possible hidden
state. Although not displayed explicitly, learning prior expectations over initial hidden
states (**D**) is similarly accomplished via accumulation of concentration parameters (**d**).
These prior expectations reflect counts of how many times the agent believes it previously
occupied each possible initial state. Concentration parameters are converted into expected
log probabilities using digamma functions ($\boldsymbol{\psi}$). The way in which Bayesian model reduction
was performed in this paper is also written in the lower left (where B indicates a beta
function, and **m** is the posterior probability of each model). Here, the posterior distribution
over initial states (**d**) is used to assess the difference in the evidence ($\boldsymbol{\Delta F}$) it provides for the
number of hidden states in the current model and other possible models characterized by
fewer hidden states. Prior concentration parameters are shown in italics, posteriors in bold,
and those priors and posteriors associated with the reduced model are equipped with a
tilde (**~**). As already stated, the right panel illustrates a possible neural implementation of
the update equations in the left panel. In this implementation, probability estimates have
been associated with neuronal populations that are arranged to reproduce known intrinsic
(within cortical area) connections. Red connections are excitatory, blue connections are
inhibitory, and green connections are modulatory (i.e., involve a multiplication or
weighting). These connections mediate the message passing associated with the equations
in the left panel. Note that the various messages passed between neurons to implement the
equations on the left are denoted with corresponding numbers in the left and right panels –
conveying policy values (message 1), prior expectations (messages 2,3), sensory signals
(message 4), and expected free energies (message 5). Cyan units correspond to expectations
about hidden states and (future) outcomes under each policy, while red states indicate their
Bayesian model averages (i.e., a "best guess" based on the average of the probability
estimates for the states and outcomes across policies, weighted by the probability estimates
for their associated policies). Pink units correspond to (state and outcome) prediction
errors that are averaged to evaluate expected free energy and subsequent policy
expectations (in the lower part of the network). This (neural) network formulation of belief
updating means that connection strengths correspond to the parameters of the generative

model described in the text. Learning then corresponds to changes in the synaptic
connection strengths. Only exemplar connections are shown to avoid visual clutter.
Furthermore, we have just shown neuronal populations encoding hidden states under two
policies over three time points (i.e., two transitions), whereas in the task described in this
paper there are greater number of allowable policies. For more information regarding the
mathematics and processes illustrated in this figure, see (KJ Friston, Lin, et al., 2017; KJ
Friston, Parr, et al., 2017).
333

A model of concept inference and learning through state-space expansion

To model concept inference, we constructed a simple task for an agent to

perform (see figure 1, left panel). In this task, the agent was presented with different

animals on different trials and asked to answer a question about the type of animal

that was seen. As described below, in some simulations the agent was asked to

report the type of animal that was learned previously; in other simulations, the

agent was instead asked a question that required conceptual generalization.

Crucially, to answer these questions the agent was required to observe different

animal features, where the identity of the animal depended on the combination of

features. There were three feature categories (size, color, and species-specific;

described further below) and two discrete time points in a trial (observe and

report).

To simulate concept learning and state-space expansion (based on the task

described above) we needed to specify an appropriate generative model. Once this

model has been specified, one can use standard (variational) message passing to

simulate belief updating and behavior in a biologically plausible way: for details,

please see (Friston et al., 2017a, 2017c). In our (minimal) model, the first hidden

state factor included (up to) eight levels, specifying four possible types of birds and

four possible types of fish (Figure 3A). The outcome modalities included: a feature

space including two size features (big, small), two color features (gray, colorful), and

two species-differentiating features (wings, gills). The **A** matrix specified a

likelihood mapping between features and animal concepts, such that each feature

combination was predicted by an animal concept (Hawk, Pigeon, Parrot, Parakeet,

Sturgeon, Minnow, Whale shark, Clownfish). This model was deliberately simple to

allow for a clear illustration, but it is plausibly scalable to include more concepts and

a much larger feature space. The **B** matrix for the first hidden state factor was an

identity matrix, reflecting the belief that the animal identity was conserved during

each trial (i.e., the animals were not switched out mid-trial).

362
363

364
Figure 3. (A) Illustration of the first hidden state factor containing columns (levels) for 8
different animal concepts. Each of these 8 concepts generated a different pattern of visual
feature observations associated with the outcome modalities of size, color, and species-
specific features. The **B** matrix was an identity matrix, indicating that the animal being
observed did not change within a trial (white = 1, black = 0). The **A** matrix illustrates the
specific mapping from animal concepts to feature combinations. As depicted, each concept
corresponded to a unique point in a 3-dimensional feature space. (B) illustration of the 2nd
hidden state factor corresponding to the verbal reports the agent could choose in response
to its observations. These generated feedback as to whether its verbal report was accurate
with respect to a basic category report or a specific category report. As illustrated in the **C**
matrix, the agent most preferred to be correct about specific categories, but least preferred
being incorrect. Thus, reporting the basic categories was a safer choice if the agent was too
uncertain about the specific identity of the animal.
378

The second hidden state factor was the agent's report. That this is assumed

to factorize from the first hidden state factor means that there is no prior constraint

that links the chosen report to the animal generating observations. The agent could

report each of the eight possible specific animal categories, or opt for a less specific

report of a bird or a fish. Only one category could be reported at any time. Thus, the

agent had to choose to report only bird vs. fish or to report a more specific category.

In other words, the agent could decide upon the appropriate level of coarse-graining

of its responses (figure 3B).

387   During learning trials, the policy space was restricted such that the agent

could not provide verbal reports or observe corrective feedback (i.e., all it could do

is "stay still" in its initial state and observe the feature patterns presented). This

allowed the agent to learn concepts in an unsupervised manner (i.e. without being

told what the true state was or whether it was correct or incorrect). After learning,

active reporting was enabled, and the **C** matrix was set so that the agent preferred to

report correct beliefs. We defined the preferences of the agent such that it preferred

correctly reporting specific category knowledge and was averse to incorrect reports.

This ensured that it only reported the general category of bird vs. fish, unless

sufficiently certain about the more specific category.

397   In the simulations reported below, there were two time points in each trial of

categorisation or conceptual inference. At the first time point, the agent was

presented with the animals features, and always began in a state of having made no

report (the "start" state). The agent's task was simply to observe the features, infer

the animal identity, and then report it (i.e., in reporting trials). Over 32 simulations

(i.e., 4 trials per animal), we confirmed that, if the agent already started out with full

knowledge of the animal concepts (i.e., a fully precise **A** matrix), it would report the

specific category correctly 100% of the time. Over an additional 32 simulations, we

also confirmed that, if the agent was only equipped with knowledge of the

distinction between wings and gills (i.e., by replacing the rows in the **A** matrix

corresponding to the mappings from animals to size and color with flat

distributions), it would report the generic category correctly 100% of the time but

would not report the specific categories.[2] This was an expected and straightforward

consequence of the generative model – but provides a useful example of how agents

trade off preferences and different types of uncertainty.

413   **Simulating concept learning and the acquisition of expertise**

415   Having confirmed that our model could successfully recognize animals if

416   equipped with the relevant concepts (i.e., likelihood mappings) – we turn now to

417   concept learning.

419   **Concept acquisition through state-space expansion**

420   We first examined our model's ability to acquire concept knowledge in two

421   distinct ways. This included 1) the agent's ability to effectively "expand" (i.e., fill in

422   an unused column within) its state space and add new concepts and 2) the agent's

423   ability to increase the granularity of its conceptual state space and learn more

424   specific concepts, when it already possessed broader concepts.

426   *Adding Concepts*

---

[2] However, "risky" reporting behavior could be elicited by manipulating the strengths of the agent's preferences such that it placed a very high value on reporting specific categories correctly (i.e., relative to how much it disliked reporting incorrectly).

To assess whether our agent could effectively expand its state space and

acquire a new concept, we first set one column of the previously described model's

A matrix (mapping an animal concept to its associated features) to be a uniform

distribution[3]; creating an imprecise likelihood mapping for one concept –

essentially, that concept predicted all features with nearly equal probability. Here,

we chose sturgeon (large, gray, gills) as the concept for which the agent had no

initial knowledge (see Figure 4A, right-most column of left-most 'pre-learning'

matrix). We then generated 2000 observations based on the outcome statistics of a

model with full knowledge of all eight animals (the "generative process"), to test

whether the model could infer that a novel animal was present and then learn the

correct likelihood mapping for sturgeon (note: this excessive number of

observations was used for consistency with later simulations, in which more

concepts had to be learned, and also to evaluate how performance improved as a

function of the number of observations the agent was exposed to; see figure 4B).

We refer to this as "effective" state space expansion because the dimensions

of the hidden state space do not change. Instead, based on the model structure

described above, the agent begins with implicit prior expectations about the

structure of its environment ('structural priors') – namely, that there could be up to

8 different concept categories accounting for (i.e., hidden causes generating)

patterns in its possible observations. When a new animal is presented, the agent

---

[3] To break the symmetry of the uniform distribution, we added small amounts of Gaussian noise (with a variance of .001) to avoid getting stuck in local free energy minima – or any locations with zero free energy gradient – during learning (e.g., in this case, exactly equal concentration parameter updates could repeatedly occur across state-outcome mappings on each trial and prevent the agent from converging to a more accurate model).

must first infer that the animal is novel and engage an unused "slot" in its state

space (i.e., infer that a noisy, flat distribution better accounts for the new pattern of

observations than any current state-observation mapping it knows), and then learn

the new state-outcome contingencies over repeated observations. Thus, as we use

the term, model expansion increases the number of hidden states the agent *uses*, but

not the formal dimensions of the state space itself.

In these simulations, learning was implemented via updating (concentration)

parameters for the model's **A** matrix after each trial. For details of these free energy

minimizing learning processes, please see (Friston et al., 2016a) as well as the left

panel of Figure 2 and associated legend. An intuitive way to think about this belief

updating process is that the strength of association between a concept and an

observation is quantified simply by counting how often they are inferred to co-

occur. This is exactly the same principle that underwrites Hebbian plasticity and

long-term potentiation (Brown et al., 2010). Crucially, policies were restricted

during learning, such that the agent could not select reporting actions; thus, learning

was driven entirely by repeated exposure to different feature combinations. We

evaluated successful learning in two ways. First, we compared the **A** matrix learned

by the model to that of the generative process. Second, we disabled learning after

various trial numbers (i.e., such that concentration parameters no longer

accumulated) and enabled reporting. We then evaluated reporting accuracy with 20

trials for each of the 8 concepts.

As shown in Figure 4A, the **A** matrix (likelihood) mapping – learned by the

agent – and the column for sturgeon in particular, strongly resembled that of the

generative process. When first evaluating reporting, the model was 100 % accurate

across 20 reporting trials, when exposed to a sturgeon (reporting accuracy when

exposed to each of the other animals also remained at 100%) and first reached this

level of accuracy after around 50 exposures to all 8 animals (with equal probability)

(figure 4B). The agent also always chose to report specific categories (i.e., it never

chose to only report bird or fish). Model performance was stable over 8 repeated

simulations.

Crucially, during learning, the agent was not told which state was generating

its observations. This meant that it had to solve both an inference and a learning

problem. First, it had to infer whether a given feature combination was better

explained by an existing concept, or by a concept that predicts features uniformly. In

other words, it had to decide that the features were sufficiently different – from

things it had seen before – to assign it a new hypothetical concept. Given that a novel

state is only inferred when another state is not a better explanation, this precludes

learning 'duplicate' states that generate the same patterns of observations. The

second problem is simpler. Having inferred that these outcomes are caused by

something new, the problem becomes one of learning a simple state-outcome

mapping through accumulation of Dirichlet parameters.

To examine whether this result generalized, we repeated these simulations

under conditions in which the agent had to learn more than one concept. When the

model needed to learn one bird (parakeet) and one fish (minnow), the model was

also able to learn the appropriate likelihood mapping for these 2 concepts (although

note that, because the agent did not receive feedback about the state it was in during

learning, the new feature mappings were often not assigned to the same columns as

in the generative process; see figure 4A). Reporting also reached 100% accuracy,

but required a notably greater number of trials. Across 8 repeated simulations, the

mean accuracy reached by the model after 2000 trials was 98.75% (SD = 2%).

498
Figure 4. (A) illustration of representative simulation results in which the agent successfully
learned 1, 2, or 4 new animal concept categories with no prior knowledge beforehand. The
generative process is shown in the upper right, illustrating the feature combinations to be
learned. Pre-learning, either 1, 2 or 4 columns in the likelihood mapping began as a flat
distribution with a slight amount of Gaussian noise. The agent was then provided with 2000
observations of the 8 animals with equal probability. Crucially, the agent was prevented
from providing verbal reports during these 2000 trials and thus did not receive feedback
about the true identity of the animal. Thus, learning was driven completely by repeated
exposure in an unsupervised manner. Also note that, while the agent was successful at
learning the new concepts, it did not always assign the new feature patterns to the same
columns as illustrated in the generative process. This is to be expected given that the agent
received no feedback about the true hidden state that generated its observations. (B)
illustration of how reporting accuracy, and the proportion of basic category and specific
category responses, changed as a function of repeated exposures. This was accomplished by
taking the generative model at a number of representative trials and then testing it with 20
observations of each animal in which reporting was enabled. As can be seen, maximal
accuracy was achieved much more quickly when the agent had to learn fewer concepts.
When it had learned 4 concepts, it also began by reporting the general categories and then
subsequently became sufficiently confident to report the more specific categories.
518

When the model needed to learn all 4 birds, performance varied somewhat

more when the simulations were repeated. The learned likelihood mappings after

2000 trials always resembled that of the generative process, but with variable levels

of precision; notably, the model again assigned different concepts to different

columns relative to the generative process, as would be expected when the agent is

not given feedback about the state it is in. Over 8 repeated simulations, the model

performed well in 6 (92.50 % – 98.8 % accuracy) and failed to learn one concept in

the other 2 (72.50 % accuracy in each) due to overgeneralization (e.g., mistaking

parrot for Hawk in a majority of trials; i.e., the model simply learned that there are

large birds). Figure 4A and 4B illustrate representative results when the model was

successful (note: the agent never chose to report basic categories in the simulations

where only 1 or 2 concepts needed to be learned).

To further assess concept learning, we also tested the agent's ability to

successfully avoid state duplication. That is, we wished to confirm that the model

would only learn a new concept if actually presented with a new animal for which it

did not already have a concept. To do so, we equipped the model with knowledge of

seven out of the eight concept categories, and then repeatedly exposed it only to the

animals it already knew over 80 trials. We subsequently exposed it to the eighth

animal (Hawk) for which it did not already have knowledge over 20 additional

trials. As can be seen in figure 5, the unused concept column was not engaged during

the first 80 trials (bottom left and middle). However, in the final 20 trials, the agent

correctly inferred that its current conceptual repertoire was unable to explain its

new pattern of observations, leading the unused concept column to be adumbrated

and the appropriate state-observation mapping to be learned (bottom right). We

repeated these simulations under conditions in which the agent already had

knowledge of six, five, or four concepts. In all cases, we observed that unused

concept columns were never engaged inappropriately.

547
Figure 5. Illustration of representative simulation results when the agent had to avoid
inappropriately learning a new concept (i.e., avoid state duplication) after only being
exposed to animals for which it already had knowledge. Here the agent began with prior
knowledge about seven concept categories and was also equipped with an eighth column
that could be engaged to learn a new concept category (bottom left). The agent was then
presented with several instances of each of the seven animals that it already knew (80 trials
in total). In this simulation, the agent was successful in assigning each stimulus to an animal
concept it had already acquired and did not engage the unused concept 'slot' (bottom
middle). Finally, the agent was presented with a new animal (a hawk) that it did not already
know over 20 trials. In this case, the agent successfully engaged the additional column (i.e.,
it inferred that none of the concepts it possessed could account for its new observations)
and learned the correct state-observation mapping (bottom right).
560

Crucially, these simulations suggest that adaptive concept learning needs to

be informed by existing knowledge about other concepts, such that a novel concept

should only be learned if observations cannot be explained with existing conceptual

knowledge. Here, this is achieved via the interplay of inference and learning, such

that agents initially have to infer whether to assign an observation to an existing

concept, and only if this is not possible is an 'open slot' employed to learn about a

novel concept.

Increasing granularity

Next, to explore the model's ability to increase the granularity of its concept

space, we first equipped the model with only the distinction between birds and fish

(i.e., the rows of the likelihood mapping corresponding to color and size features

were flattened in the same manner described above). We then performed the same

procedure used in our previous simulations. As can be seen in Figure 6A (bottom

left), the **A** matrix learned by the model now more strongly resembled that of the

generative process. Figure 6B (bottom) also illustrates reporting accuracy and the

proportion of basic and specific category reports as a function of trial number. As

can be seen, the agent initially only reported general categories, and became

sufficiently confident to report specific categories after roughly 50 – 100 trials, but

its accuracy increased gradually over the next 1000 trials (i.e., the agent reported

specific categories considerably before its accuracy improved). Across 8 repeated

simulations, the final accuracy level reached was between 93% – 98% in 7

simulations, but the model failed to learn one concept in the 8th case, with 84.4%

overall accuracy (i.e., a failure to distinguish between pigeon and parakeet, and

therefore only learned a broader category of "small birds").

To assess whether learning basic categories first was helpful in subsequently

learning specific categories, we also repeated this simulation without any initial

knowledge of the basic categories. As exemplified in figure 6A and 6B, the model

tended to perform reasonably well, but most often learned a less precise likelihood

mapping and reached a lower reporting accuracy percentage after 2000 learning

trials (across 8 repeated simulations: mean = 81.21%, SD = 6.39%, range from

68.80% – 91.30%). Thus, learning basic concept categories first appeared to

facilitate learning more specific concepts later.

A

Increasing Granularity: Features as Rows

Pre-Learning

Post-Learning

594
595

B

Increasing Granularity:
Reporting Accuracy as a Function of Trial Number (without feedback)

No Prior Knowledge

After Learning Basic Categories

Figure 6. (A, left) Illustration of representative simulation results when the agent had to learn to increase the granularity of its concept space. Here the agent began with prior knowledge about the basic concept categories (i.e., it had learned the broad categories of "bird" and "fish") but had not learned the feature patterns (i.e., rows) that differentiate different types of birds and fish. Post learning (i.e., after 2000 exposures), the agent did successfully learn all of the more granular concept categories, although again note that specific concepts were assigned to different columns then depicted in the generative process due to the unsupervised nature of the learning. (A, right) illustration of the analogous learning result when the agent had to learn all 8 specific categories without prior knowledge of the general categories. Although moderately successful, learning tended to be more difficult in this case. (B) Representative plots of reporting accuracy in each of the 2 learning conditions as a function of the number of exposures. As can be seen, when the model starts out with prior knowledge about basic categories, it slowly becomes sufficiently confident to start reporting the more specific categories, and its final accuracy is high. In contrast, while the agent that did not start out with any prior knowledge of the general categories also grew confident in reporting specific categories over time, its final accuracy levels tended to be lower. In both cases, the agent began reporting specific categories before it achieved significant accuracy levels, therefore showing some initial overconfidence.

Overall, these findings provide a proof of principle that this sort of active

inference scheme can add concepts to a state space in an unsupervised manner (i.e.,

without feedback) based purely on (expected) free energy minimization. In this

case, it was able to accomplish this starting from a completely uninformative

likelihood distribution. It could also learn more granular concepts after already

acquiring more basic concepts, and our results suggest that learning granular

concepts may be facilitated by first learning basic concepts (e.g., as in currently

common educational practices).

The novel feature of this generative model involved 'building in' a number of

"reserve" hidden state levels. These initially had uninformative likelihood mappings;

yet, if a new pattern of features was repeatedly observed, and the model could not

account for this pattern with existing (informative) state-observation mappings,

these additional hidden state levels could be engaged to improve the model's

explanatory power. This approach therefore accommodates a simple form of

structure learning (i.e., model expansion).

Integrating model expansion and reduction

We next investigated ways in which the form of effective model expansion simulated

above could be combined with an analogous form of Bayesian model reduction

(Friston et al., 2017b) – allowing the agent to adjust its model to accommodate new

patterns of observations, while also precluding unnecessary conceptual complexity

(i.e., over-fitting). To do so, we again allowed the agent to learn from 2000

exposures to different animals as described in the previous section – but also

allowed the model to learn its 'D' matrix (i.e., accumulate concentration parameters

reflecting prior expectations over initial states). This allowed an assessment of the

agent's probabilistic beliefs about which hidden state factor levels (animals) it had

been exposed to. In different simulations, the agent was only exposed to some

animals and not others. We then examined whether a subsequent model reduction

step could recover the animal concepts presented during the simulation; eliminating

those concepts that were unnecessary to explain the data at hand. The success of

this 2-step procedure could then license the agent to "reset" the unnecessary hidden

state columns after concept acquisition, which would have accrued unnecessary

likelihood updates during learning. Doing so would allow the optimal ability for

those "reserve" states to be appropriately engaged, if and when the agent was

exposed to truly novel stimuli. Thus, as with our model expansion procedure, model

reduction is not formally changing the dimensions of the agent's state space. It

instead prevents the unnecessary use of the agent's "reserve" states so that they are

only engaged when a novel animal is truly present.

The 2nd step of this procedure was accomplished by applying Bayesian model

reduction to the **D** matrix concentration parameters after learning. This is a form of

post-hoc model optimization (Friston et al., 2016b, 2018) that rests upon estimation

of a 'full' model, followed by analytic computation of the evidence that would have

been afforded to alternative models (with alternative, 'reduced', priors) had they

been used instead. Mathematically, this procedure is a generalization of things like

automatic relevance determination (Friston et al., 2007; Wipf and Rao, 2007) or the

use of the Savage Dickie ratio in model comparison (Cornish and Littenberg, 2007).

It is based upon straightforward probability theory and, importantly, has a simple

physiological interpretation; namely, synaptic decay and the elimination of unused

synaptic connections. In this (biological) setting, the concentration parameters of

the implicit Dirichlet distributions can be thought of as synaptic tags. For a technical

description of Bayesian model reduction techniques and their proposed neural

implementation, see (Hobson and Friston, 2012; Hobson et al., 2014; Friston et al.,

2017b); see the left panel of Figure 2 for additional details).

The posterior concentration parameters were compared to the prior

distribution for a full model (i.e., a flat distribution over 8 concepts) and prior

distributions for possible reduced models (i.e., which retained different possible

combinations of some but not all concepts; technically, reduced models were

defined such that the to-be-eliminated concepts were less likely than the to-be-

retained concepts). If Bayesian model reduction provided more evidence for one or

more reduced models, the reduced model with the most evidence was selected.

Note: an alternative would be to perform model reduction on the **A** matrix (i.e.,

comparing the state-outcome mappings one has learned to alternative **A** matrices

that reset specific columns to flat distributions), but this is more complex due to a

larger space of possible reduced models.

In each simulation, we presented our agent with a different number of

animals (between 7 and 2 animals), with 250 exposures to each animal in

randomized order (mirroring the learning simulations shown in Figure 6). In Table

1, we present results of 100 repeated simulations using this setup and report the

number of times that the winning model corresponded to each possible reduced

model when compared to the full model. To provide a further sense of these results,

Table 1 also reports the number of times the 2nd-best model instead corresponded

to the number of causes in the generative process.

Table 1. Frequency of winning models using Bayesian model reduction with different
numbers of true hidden causes (animals) after learning.

Generative Process	Retain 8 animals	Retain 7 animals	Retain 6 animals	Retain 5 animals	Retain 4 animals	Retain 3 animals	Retain 2 animals	Correct 2nd-best model
7 animals	5	**56**	31	8	0	0	0	12
6 animals	4	18	**69**	8	0	0	1	20
5 animals	0	4	16	**80**	0	0	0	12
4 animals	0	2	23	30	**45**	0	0	14
3 animals	0	0	10	0	1	**0**	89	55
2 animals	0	0	0	57	43	0	**0**	0

693   * Results are based on frequencies obtained over 100 repeated simulations. Bolded
694   numbers correspond to matches with the underlying generative process.
695

As can be seen there, the frequency with which model reduction successfully

recovered the number of causes in the generative process varied depending on the

number of different types of animals presented (Figure 7 illustrates examples of

successful recovery in the case of generative processes with 7, 6, and 5 causes). In

the presence of 4-7 animals, the most frequently winning model was the correct

model. When the winning model was not the correct model, this was most often due

to the agent learning simpler, coarser-grained representations (such as "large bird,"

treating color as irrelevant; e.g., the 31/100 cases where a 6-animal model was

retained after 7 different animals were presented). In some other cases, the agent

instead retained overly fine-grained distinctions (such as the existence of distinct

types of gray birds with different frequencies of being large vs. small; e.g., the

several cases where a 5- or 6-animal model was retained when only 4 different

animals were presented). In these cases where the incorrect model was favored, the

correct model was often the model with the 2nd-most evidence. The difference in

log evidence between the winning and 2nd-best model in such cases was also often

small (average differences between -.40 and -1.23). In the approach outlined here, in

the cases where model reduction was successful, this would correctly license the

removal of changes in the model's **A** and **D** matrix parameters for unobserved

animals during learning in the previous trials (i.e., re-setting them to then again be

available for future learning).

When there were 3 causes to recover, the winning model most often only retained 2

animal representations (typically learning one more coarse-grained concept; e.g.,

"colorful fish", ignoring size). However, the true 3-animal model had the 2nd-most

evidence in the majority of unsuccessful cases (average log evidence difference with

the winning model in these cases was -1.64).

When there were only 2 causes to recover (in this case, one bird and one fish),

model reduction reliably failed to select the 2-animal model. Further inspection

revealed that this was due to the agent learning – and failingly to subsequently

remove – redundant state-outcome mappings across multiple (either 4 or 5)

columns (i.e., it retained a fairly flat distribution over these states in **D**). Essentially,

the agent learned 2 or 3 redundant mappings for 'bird' and 2 or 3 redundant

mappings for 'fish'. Poor performance in this case could be seen as unsurprising, as

the presence of only 2 animals is quite different from the structural prior of 8

animals inherited by the agent prior to learning. Note, however, that despite a

failure to retain only 2 concept columns, the resulting state-outcome mappings were

coarse-grained in a manner similar to those of our simulated agent above that could

only distinguish birds vs. fish (i.e., as in in the upper-left 'pre-learning" matrix of

Figure 6A, prior to granularity learning). This type of mapping only distinguishes 2

concepts (despite having redundant mappings across several columns) – and leads

the agent to only report 2 coarse-grained categories (as shown in Figure 6B) – as

would be expected if only familiar with 2 different animals distinguished by 1

feature. So, from another perspective, the agent successfully retained the type of

mapping that reflects coarse-grained concept knowledge in our model and that

allows for the appropriate coarse-grained reports.

Figure 7. Representative illustrations of simulations in which the agent performed Bayesian model reduction after learning. In these simulations, the agent was first given 250 exposures per animal, where either 7, 6, or 5 animals were actually presented (i.e., illustrated in the top row, where only the white columns had nonzero probabilities in the generative process). In each case, model reduction was often successful at identifying the reduced model with the correct number of animal types presented (bottom row, where black columns should be removed) based on how much evidence it provided for the posterior distribution over hidden states learned by the agent (2nd row). This would license the agent to reset the unneeded columns in its likelihood mapping (3rd row) to their initial state (i.e., a flat distribution over features) such that they could be engaged if/when new types of animals began to be observed (i.e., as in the simulations illustrated in the previous sections).

When consider our overall model reduction results, it is worth noting that a

model's accuracy need not always correspond to its adaptiveness (McKay and

Dennett, 2009; Al-Muhaideb and Menai, 2011; Gigerenzer and Gaissmaier, 2011;

Baltieri and Buckley, 2019; Tschantz et al., 2019). In some cases, making either

coarser- or finer-grained distinctions could be more adaptive for an organism

depending on available resources and environmental/behavioral demands. It is also

worth noting that, while we have used the terms 'correct' and 'incorrect' above to

describe the model used to generate the data, we acknowledge that 'all models are

wrong' (Box et al., 2005), and that the important question is not whether we can

recover the 'true' process used to generate the data, but whether we can arrive at

the simplest but accurate explanation for these data. The failures to recover the

'true' model highlighted above (especially in the cases where only coarser-grained

representations were learned) may reflect that a process other than that used to

generate the data could have been used to do so in a simpler way. Simpler here

means we would have to diverge to a lesser degree from our prior beliefs in order to

explain the data under a given model, relative to a more complex model. It is worth

highlighting the importance of the word *prior* in the previous sentence. This means

that the simplicity of the model is sensitive to our prior beliefs about it. To illustrate

this, we repeated the same model comparisons as above, but with precise beliefs in

an **A** matrix that complies with that used to generate the data. Specifically, we

repeated the simulations above but only enabled **D** matrix learning (i.e., the model

was already equipped with the **A** matrix of the generative process). In each case,

Bayesian model reduction now uniquely identified the correct reduced model in

100% of repeated simulations.

Overall, these results demonstrate that – after a naïve model has effectively

expanded its hidden state space to include likelihood mappings and initial state

priors for a number of concept categories – Bayesian model reduction can

subsequently be used with moderate success to eliminate any parameter updates

accrued for redundant concept categories. In practice, the **A** and **D** concentration

parameters for the redundant categories identified by model reduction could be

reset to their default pre-learning values – and could then be re-engaged if new

patterns of observations were repeatedly observed in the future. The variable

performance of model reduction in our simulations appeared to be due to imperfect

A matrix learning (recall that the analogous learning simulations in Figure 6 only led

to 81% reporting accuracy on average). Another potential consideration is that,

because **A** and **D** matrix learning occurred simultaneously, this may have also led to

noisier accumulation of prior expectations over hidden states – as **D** matrix learning

with a fully precise **A** matrix led to correct model reduction in every case tested (i.e.,

perhaps suggesting that this type of model reduction procedure could be improved

by first allowing state-observation learning to proceed alone, then subsequently

allowing the model to learn prior expectations over hidden states, which could then

be used in model reduction).

Can concept acquisition allow for generalization?

One important ability afforded by concept learning is generalization. In a

final set of simulations, we asked if our model of concept knowledge could account

for generalization. To do so, we altered the model such that it no longer reported

what it saw, but instead had to answer a question that depended on generalization

from particular cross-category feature combinations. Specifically, the model was

shown particular animals and asked: "could this be seen from a distance?" The

answer to this question depended on both size and color, such that the answer was

yes only for colorful, large animals (i.e., assuming small or gray animals would blend

in with the sky or water and be missed).

808   Crucially, this question was asked of animals that the model had not been

exposed to, such that it had to generalize from knowledge it already possessed (see

Figure 8). To simulate and test for this ability, we equipped the model's **A** matrix

with expert knowledge of 7 out of the 8 animals (i.e., as if these concepts had been

learned previously, as in our simulations above). The 8^{th} animal was unknown to the

agent, in that it's likelihood mapping was set such that the 8^{th} animal state "slot"

predicted all observations equally (i.e., with a small amount of Gaussian noise, as

above). In one variant, the model possessed all concepts except for "parrot," and it

knew that the answer to the question was yes for "whale shark" but not for any

other concept it knew. To simulate one-shot generalization, learning was disabled

and a parrot (which it had never seen before) was presented 20 times to see if it

would correctly generalize and answer "yes" in a reliable manner. In another

variant, the model had learned all concepts except "minnow" and was tested the

same way to see if it would reliably provide the correct "no" response.

822   Here, we observed that in both of these cases (as well as all others we tested)

823   the model generalized remarkably well. It answered "yes" and "no" correctly in

824   100% of trials. Thus, the agent did not simply possess concepts to explain things it

825   saw. It instead demonstrated generalizable knowledge and could correctly answer

826   questions when seeing a novel stimulus.

Figure 8. Depiction of simulations in which we tested the agent's ability to generalize from
prior knowledge and correctly answered questions about new animals to which it had not
previously been exposed. In the simulations, the generative model was modified so that the
agent instead chose to report either "yes" or "no" to the question: "could this animal be seen
from a distance?" Here, the answer was only yes if the animal was both large and colorful.
We observed that when the agent started out with no knowledge of parrots it still correctly
answered this question 100% of the time, based only on its knowledge of other animals.
Similarly, when it started with no knowledge of minnows, it also correctly reported "no"
100% of the time. Thus, the agent was able to generalize from prior knowledge with no
additional learning.

Open questions and relation to other theoretical accounts of concept learning

As our simulations show, this model allows for learning novel concepts (i.e.,

novel hidden states) based on assigning one or more 'open slots' that can be utilised

to learn novel feature combinations. In a simple example, we have shown that this

setup offers a potential computational mechanism for 'model expansion'; i.e., the

process of effectively expanding a state space to account for novel instances in

perceptual categorisation. We also illustrated how this framework can be combined

with model reduction, which may be a mechanism for 're-setting' these open slots

based on recent experience.

851   This provides a first step towards understanding how agents flexibly expand

or reduce their model to adapt to ongoing experience. Yet, several open questions

remain, and for the approach we illustrate to address real-world problems in future

active inference research, these issues will need to be examined and integrated with

insights from previous work that has already grappled with them. For example, the

proposed framework resonates with previous similarity-based accounts of concept

learning. Previous work has proposed a computational framework for arbitrating

between assigning an observation to a previously formed memory or forming a

novel (hidden) state representation (Gershman et al., 2017), based on evidence that

this observation was sampled from an existing or novel latent state. This process is

conceptually similar to our application of Bayesian model reduction over states. In

the present framework, concept learning relies on a process based on inference and

learning. First, agents have to *infer* whether ongoing observations can be sufficiently

explained by existing conceptual knowledge – or speak to the presence of a novel

concept that motivates the use of an 'open slot'. This process is cast as inference on

(hidden) states. Second, if the agent infers that there is a novel concept that explains

current observations, it has to *learn* about the specific feature configuration of that

concept (i.e., novel state). This process highlights the interplay between inference,

which allows for the acquisition of knowledge on a relatively short timescale, and

learning, which allows for knowledge acquisition on a longer and more stable

timescale.

872   Similar considerations apply to the degree of 'similarity' of observations. In

the framework proposed here, we have assumed that the feature space of

observations is already learned and fixed. However, these feature spaces have to be

learned in the first place, which implies learning the underlying components or

feature dimensions that define observations. This relates closely to notions of

structure learning as dimensionality reduction based on covariance between

observations, as prominently discussed in the context of spatial navigation (Dordek

et al., 2016; Stachenfeld et al., 2016; Behrens et al., 2018; Whittington et al., 2018).

880   Another important issue is how such abstract conceptual knowledge is

formed across different contexts or tasks. For example, the abstract concept of a

'bird' will be useful for learning about the fauna in a novel environment, but specific

types of birds – tied to a previous context – might be less useful in this regard. This

speaks to the formation of abstract, task-general knowledge that results from

training across different tasks, as recently discussed in the context of meta-

reinforcement learning (Wang et al., 2016; Ritter et al., 2018) with a putative link to

the prefrontal cortex (Wang et al., 2018). In the present framework, such task-

general knowledge would speak to the formation of a hierarchical organisation that

allows for the formation of conceptual knowledge both within and across contexts.

Also note that our proposed framework depends on a pre-defined state space,

including a pre-defined set of 'open slots' that allow for novel context learning. The

contribution of the present framework is to show how these 'open slots' can be used

for novel concept learning and be re-set based on model reduction. It will be

important to extend this approach towards learning the structure of these models in

the first place, including the appropriate number of 'open slots' (i.e., columns of the

A-matrix) for learning in a particular content domain and the relevant feature

dimensions of observations (i.e., rows of A-matrix). (Note: In addition to ontogenetic

learning, in some cases structural priors regarding the appropriate number of open

slots [and relevant feature inputs for learning a given state space of open slots]

might also reflect inherited [i.e., genetically/developmentally pre-specified] patterns

of structural neuronal connectivity – based on what was adaptive within the

evolutionary niche of a given species – which could then be modified based on

subsequent experience.)

This corresponds to a potentially powerful and simple application of

Bayesian model reduction, in which candidate models (i.e., reduced forms of a full

model) are readily identifiable based upon the similarity between the likelihoods

conditioned upon different hidden states. If two or more likelihoods are sufficiently

similar, the hidden states can be merged (by assigning the concentration

parameters accumulated during experience-dependent learning to one or other of

the hidden states). The ensuing change in model evidence scores the reduction in

complexity. If this reduction is greater than the loss of accuracy – in relation to

observations previously encountered – Bayesian model reduction will, effectively,

merge one state into another; thereby freeing up a state for the learning of new

concepts. We will demonstrate this form of structure learning via Bayesian model

reduction in future work.

We must also highlight here that cognitive science research on concept and

category learning has a rich empirical and theoretical history, including many

previously proposed formal models. While our primary focus has been on using

concept learning as an example of a more general approach by which state space

expansion and reduction can be implemented within future active inference

research, it is important to recognize this previous work and highlight where it

overlaps with the simulations we've presented. For example, our results suggesting

that first learning general categories facilitates the learning of more specific

categories relates to both classic and contemporary findings showing that children

more easily acquire "basic" and "superordinate" (e.g., dog, animal) concepts before

learning "subordinate" (e.g., chihuahua) concepts (Mervis and Rosch, 1981; Murphy,

2016), and that this may involve a type of "bootstrapping" process (Beck, 2017).

Complementary work has also highlighted ways in which learning new words

during development can invoke a type of "placeholder" structure, which then

facilitates the acquisition of a novel concept – which bears some resemblance to our

notion of blank "concept slots" that can subsequently acquire meaningful semantics

(Gelman and Roberts, 2017).

There is also a series of previously proposed formalisms within the literature

on category learning. For example, two previously proposed models – the "rational

model" (Anderson, 1991; Sanborn et al., 2010) and the SUSTAIN model (Love et al.,

2004) – both describe concept acquisition as involving cluster creation mechanisms

that depend on statistical regularities during learning and that use probabilistic

updating. The updating mechanisms within SUSTAIN are based on

surprise/prediction-error in the context of both supervised and unsupervised

learning. This model also down-weights previously created clusters when their

associated regularities cease to be observed in recent experience. Although not built

in intentionally, this type of mechanism emerges naturally within our model in two

ways. First, when a particular hidden state ceases to be inferred, concentration

parameters will accumulate to higher values for other hidden states in the **D** matrix,

reflecting relatively stronger prior expectations for hidden states that continue to be

inferred – which would favor future inference of those states over those absent from

recent experience. Second, if one pattern of observations were absent from recent

experience (while other patterns continued to be observed), concentration

parameters in the **A** matrix would also accumulate to higher values for patterns that

continued to be observed – resulting in relatively less confidence in the state-

outcome mapping for the less-observed pattern. (However, with respect to this

latter mechanism, so long as this mapping was sufficiently precise and distinct from

others [i.e., it had previously been observed many times farther in the past], this

would not be expected to prevent successful inference if this pattern were observed

again.)

It is also worth highlighting that, as our model is intended primarily as a

proof of concept and a demonstration of an available model expansion/reduction

approach that can be used within active inference research, it does not explicitly

incorporate some aspects – such as top-down attention – that are of clear

importance to cognitive learning processes, and that have been implemented in

previous models. For example, the adaptive resonance theory (ART) model

(Grossberg, 1987) was designed to incorporate top-down attentional mechanisms

and feedback mechanisms to address a fundamental knowledge acquisition problem

– the temporal instability of previously learned information that can occur when a

system also remains sufficiently plastic to learn new (and potentially overlapping)

information. While our simulations do not explicitly incorporate these additional

complexities, there are clear analogues to the top-down and bottom-up feedback

exchange in ART within our model (e.g., the prediction and prediction-error

signaling within the neural process theory associated with active inference). ART

addresses the temporal instability problem primarily through mechanisms that

learn top-down expectancies that guide attention and match them with bottom-up

input patterns – which is quite similar to the prior expectations and likelihood

mappings used within active inference.

As an emergent property of the "first principles" approach in active

inference, our model therefore naturally incorporates the top-down effects in ART

simulations, which have been used to account for known context effects on

categorical perception within empirical studies (McClelland and Rumelhart, 1981).

This is also consistent with more recent work on cross-categorization (Shafto et al.,

2011), which has shown that human category learning is poorly accounted for by

both a purely bottom-up process (attempting to explain observed features) and a

purely top-down approach (involving attention-based feature selection) – and has

instead used simulations to show that a Bayesian joint inference model better fits

empirical data.

Other proposed Bayesian models of concept learning have also had

considerable success in predicting human generalization judgments (Goodman et

al., 2008). The proof of concept model presented here has not been constructed to

explicitly compete with such models. It will be an important direction for future

work to explore the model's ability to scale up to handle more complex concept

learning problems. Here we simply highlight that the broadly Bayesian approach

within our model is shared with other models that have met with considerable

success – supporting the general plausibility of using this approach within active

inference research to model and predict the neural basis of these processes (see

below).

995   **Potential advantages of the approach**

The present approach may offer some potential theoretical and empirical

advantages in comparison to previous work. One theoretical advantage corresponds

to the parsimony of casting this type of structure learning as an instance of Bayesian

model selection. When integrated with other aspects of the active inference

framework, this means that perceptual inference, active learning, and structure

learning are all expressions of the same principle; namely, the minimization of

variational free energy, over three distinct timescales. Structure learning is

particularly interesting from this perspective, as it occurs both during an

individual's lifetime, and over the longer timescale of natural selection; which

implements a form of structure learning by selecting among phenotypes that entail

alternative models. It also highlights the importance of these nested timescales

within an individual's lifetime, in that active learning must proceed through

repeated perception of the consequences of action, and structure learning must

proceed by 1) accumulating evidence that the state-outcome mappings one has

already learned are insufficient to account for new observations (entailing the need

for model expansion), and 2) using model reduction to remove actively learned

state-outcome mappings that are unnecessary to account for past observations. A

second, related theoretical advantage is that, when this type of structure learning is

cast as Bayesian model selection/reduction, there is no need to invoke additional

procedures or schemes (e.g., nonparametric Bayes or 'stick breaking' processes;

(Gershman and Blei, 2012)). Instead, a generative model with the capacity to

represent a sufficiently complex world will automatically learn causal structure in a

way that contextualizes active inference within active learning, and active learning

within structure learning.

Based on the process theories summarized in Figure 2, the present model

would predict that the brain contains "reserve" cortical columns and synapses (most

likely within secondary sensory and association cortices) available to capture new

patterns in observed features. To our knowledge, no direct evidence supporting the

presence of unused cortical columns in the brain has been observed, although the

generation of new neurons (with new synaptic connections) is known to occur in

the hippocampus (Chancey et al., 2013). "Silent synapses" have also been observed

in the brain, which does appear consistent with this prediction; such synapses can

persist into adulthood and only become activated when new learning becomes

necessary (e.g., see (Kerchner and Nicoll, 2008; Chancey et al., 2013; Funahashi et

al., 2013)). One way in which this idea of "spare capacity" or "reserve" cortical

columns might be tested in the context of neuroimaging would be to examine

whether greater levels of neural activation – within conceptual processing regions –

are observed after learning additional concepts, which would imply that additional

populations of neurons become capable of being activated. In principle, single-cell

recording methods might also test for the presence of neurons that remain at

baseline firing rates during task conditions, but then become sensitive to new

stimuli within the relevant conceptual domain after learning.

Figure 9 provides a concrete example of two specific empirical predictions

that follow from simulating the neural responses that should be observed within our

concept learning task under these process theories. In the left panel, we plot the

firing rates (darker = higher firing rate) and local field potentials (rate of change in

firing rates) associated with neural populations encoding the probability of the

presence of different animals that would be expected across a number of learning

trials. In this particular example, the agent began with knowledge of the basic

categories of 'bird' and 'fish,' but needed to learn the eight more specific animal

categories over 50 interleaved exposures to each animal (only 10 equally spaced

learning trials involving the presentation of a parakeet are shown for simplicity). As

can be seen, early in learning the firing rates and local field potentials remain at

baseline levels; in contrast, as learning progresses, these neural responses take a

characteristic shape with more and more positive changes in firing rate in the

populations representing the most probable animal, while other populations drop

further and further below baseline firing rates.

The right panel depicts a similar simulation, but where the agent was

allowed to self-report what it saw on each trial (for clarity of illustration, we here

show 12 equally spaced learning trials for parakeet over 120 total trials). Enabling

policy selection allowed us to simulate expected phasic dopamine responses during

the task, corresponding to changes in the precision of the probability distribution

over policies after observing a stimulus on each trial. As can be seen, during early

trials the model predicts small firing rate increases when the agent is confident in its

ability to correctly report the more general animal category after observing a new

stimulus, and firing rate decreases when the agent becomes less confident in one

policy over others (i.e., as confidence in reporting the specific versus general

categories becomes more similar). Larger and larger phasic dopaminergic responses

are then expected as the agent becomes more and more confident in its ability to

correctly report the specific animal category upon observing a new stimulus. It will

be important for future neuroimaging studies to test these predictions in this type of

concept learning/stimulus categorization task.

1068

1069

1070

Figure 9. Simulated neuronal firing rates, local field potentials, and dopaminergic responses
across learning trials based on the neural process theory associated with active inference
that is summarized in Figure 2. The top left panel displays the predicted firing rates (darker
= higher firing rate) of neural populations encoding the probability of each hidden state
over 50 interleaved exposures to each animal (only 10 equally spaced learning trials
involving the presentation of a parakeet are shown for simplicity) in the case where the
agent starts out with knowledge of the basic animal categories but must learn the more
specific categories. As can be seen, initially each of the four neural populations encoding
possible bird categories (i.e., one row per possible category) have equally low firing rates
(gray); as learning continues, firing rates increase for the 'parakeet' population and
decrease for the others. The bottom left panel illustrates the predicted local field potentials
(based on the rate of change in firing rates) that would be measured across the task. The top
right panel displays the predicted firing rates of neural populations in an analogous
simulation in which reporting policies were enabled (for clarity of illustration, we here
show 12 equally spaced learning trials for parakeet over 120 total trials). Enabling policy
selection allowed us to simulate the phasic dopaminergic responses (reporting changes in
the precision of the probability distribution over policies) predicted to occur across
learning trials; here the agent first becomes confident in its ability to correctly report the
general animal category upon observing a stimulus, then becomes unsure about reporting
specific versus general categories, and then becomes confident in its ability to report the
specific categories.

1093

1094   **Discussion**

1095

1096   The Active Inference formulation of concept learning presented here

demonstrates a simple way in which a generative model can effectively expand its

state-space to acquire both basic and highly granular knowledge of the hidden

states/causes in its environment. In comparison to previous theoretical work using

active inference (e.g., (Schwartenbeck et al., 2015; Mirza et al., 2016; Parr and

Friston, 2017)), the novel aspect of our model was that it was further equipped with

"reserve" hidden states initially devoid of content (i.e., these states started out with

uninformative likelihood mappings that predicted all outcomes with roughly equal

probability). Over multiple exposures to different stimuli, these hidden states came

to acquire conceptual content that captured distinct statistical patterns in the

features of those stimuli. This was accomplished via the model's ability to infer

when its currently learned hidden states were unable to account for a new

observation, leading an unused hidden state column to be engaged that could

acquire a new state-observation mapping. This provides a simple illustration of how

this approach could be used in active inference research and applied to more

complex structure learning problems.

1112   Crucially, the model was able to start with some concepts and then expand its

representational repertoire to learn others – but would only do so when a novel

stimulus was observed and detected (i.e., when the model inferred that the

flat/noisy state-outcome mapping of an unused hidden state column better

accounted for its current observations than the existing concept mappings it had

already acquired – a type of "novel concept detection"). This is conceptually similar

to nonparametric Bayesian learning models, such as the "Chinese Room" process

and the "Indian Buffet" process, that can also infer the need to invoke additional

hidden causes with additional data (Gershman and Blei, 2012). These statistical

learning models do not need to build in additional "category slots" for learning as in

our model and can, in principle, entertain infinite state spaces. On the other hand, it

is less clear at present how the brain could implement this type of learning. An

advantage of our model is that learning depends solely on biologically plausible

Hebbian mechanisms (for a possible neural implementation of model reduction, see

(Hobson and Friston, 2012; Hobson et al., 2014; Friston et al., 2017b)).

The distinction between nonparametric Bayesian learning and the current

active learning scheme may be important from a neurodevelopmental perspective

as well. In brief, structure learning in this paper starts with a generative model with

a type of structural prior reflecting a specific amount of built in 'spare capacity',

where uncommitted or naive conceptual 'slots' are used to explain the sensorium,

during optimization of free energy or model evidence. In contrast, nonparametric

Bayesian approaches add new slots when appropriate. One might imagine that

neonates are equipped with brains with 'spare capacity' (Baker and Tenenbaum,

2014) that is progressively leveraged during neurodevelopment, much in the spirit

of curriculum learning (Al-Muhaideb and Menai, 2011). This suggestion appears

consistent with previous work demonstrating varying levels of category learning

ability across the lifespan, which has previously been formally modeled as an

individual difference in values of a parameter constraining the ability to form new

clusters in response to surprising events (Love and Gureckis, 2007) – which bears

similarity to the idea of capacity limitations arising from finite numbers of concept

slots in our model.

In this sense, the current approach to structure learning, and its

implementation for effectively expanding a state space (i.e., increasing the number

hidden states an agent actively uses to understand its environment) can be

understood as a specific type of active learning with generative models that are

equipped with a large number of available hidden states capable of acquiring

content, which are then judiciously reduced/reset – via a process of Bayesian model

reduction. Furthermore, as in the acquisition of expertise, our model can also begin

with broad category knowledge and then subsequently learn finer-grained within-

category distinctions, which has received less attention from the perspective of the

aforementioned models. Reporting broad versus specific category recognition is

also a distinct aspect of our model – driven by differing levels of uncertainty and an

expectation (preference) not to incorrectly report a more specific category.

Our simulation results also demonstrated that, when combined with

Bayesian model reduction, the model can guard against learning too many

categories during model expansion – often retaining only the number of hidden

causes actually present in its environment – and thus keep "reserve" hidden states

available for learning about new causes if or when they appear. With perfect

"expert" knowledge of the possible animal types it could observe (i.e., fully precise

likelihood mappings matching the generative process) this was true in general. With

an imperfectly learned likelihood mapping, model reduction performed moderately

well when only a few possible concepts needed to be removed, but performance

worsened when larger numbers of concepts needed to be removed. This is perhaps

unsurprising, as one might expect worse performance when the true number of

hidden causes in the environment diverges more strongly from the agent's

structural priors (e.g., when 5 vs. 2 animals are presented to an agent with a

structural prior for up to 8 animals). It would be interesting to test whether a

similar pattern of learning is present in humans.

1170   Neurobiological theories associated with Active Inference also make

predictions about the neural basis of this process (Hobson and Friston, 2012;

Hobson et al., 2014). Specifically, during periods of rest (e.g., daydreaming) or sleep,

it is suggested that, because sensory information is down-weighted, learning is

driven mainly by internal model simulations (e.g., as appears to happen in the

phenomenon of hippocampal replay; (Pfeiffer and Foster, 2013; Feld and Born,

2017; Lewis et al., 2018)); this type of learning can accomplish a model reduction

process in which redundant model parameters are identified and removed to

prevent model over-fitting and promote selection of the most parsimonious model

that can successfully account for previous observations. This is consistent with

work suggesting that, during sleep, many (but not all) synaptic strength increases

acquired in the previous day are attenuated (Tononi and Cirelli, 2014). The role of

sleep and daydreaming in keeping "reserve" representational resources available

for model expansion could therefore be especially important to concept learning –

consistent with the known role of sleep in learning and memory (Stickgold et al.,

2001; Walker and Stickgold, 2010; Perogamvros and Schwartz, 2012; Ackermann

and Rasch, 2014; Feld and Born, 2017).

It is worth highlighting that, because spare capacity will have finite limits, it follows

that state space expansion will also have limits (although these limits could be

extremely high in complex biological systems). To manage such limitations

effectively, an agent would need to come equipped with adaptive structural priors

about the maximum number of possible categories (hidden causes) that could be

'out there' to learn about in a given domain (e.g., at each relevant timescale, level of

abstraction, level of multimodal integration, etc.). Such priors for state space size –

in a given domain – could influence learning in important ways. Most

straightforwardly, having priors for a state space with too few possible causes

would prevent adaptive (granular) learning. In contrast, it is less obvious what the

effects of priors for a state space with too many possible causes would be. In the

simulations above, our model could avoid state duplication – a case where, even

when there was a prior for 8 possible categories, the model did not inappropriately

learn an 8^{th} concept when only exposed to known hidden causes. This is because the

agent only infers a new cause – and starts to learn a new state-outcome mapping –

when a flat (noisy) mapping provides a better explanation for observations than

previously learned mappings. This would therefore not be expected to occur in the

presence of a familiar hidden cause, even with priors for a much larger state space

(i.e., a greater number of empty 'slots'). However, in our simulations of model

reduction – where the agent started out with no prior category knowledge and had

to learn the correct number of causes – the model was less often successful when

fewer causes were present. In some cases, this was because the additional empty

'slots' allowed the agent to learn overly fine-grained or redundant mappings that

model reduction failed to remove. This demonstrates one way in which having prior

expectations that there are too many causes to learn about could also have

detrimental effects during early development – perhaps suggesting the need for

mechanisms that initially restrict spare capacity during early learning.

1214   Another emergent feature of our model was its ability to generalize prior

knowledge to new stimuli to which it had not previously been exposed. In fact, the

model could correctly generalize upon a single exposure to a new stimulus – a type

of "one-shot learning" capacity qualitatively similar to that observed in humans

(Landau et al., 1988; Markman, 1989; Xu and Tenenbaum, 2007b). While it should

be kept in mind that the example we have provided is very simple, it demonstrates

the potential usefulness of this novel approach. Some other prominent approaches

in machine-learning (e.g., deep learning) tend to require larger amounts of data

(Geman et al., 1992; Lecun et al., 1998; Hinton et al., 2012; LeCun et al., 2015; Mnih

et al., 2015), and do not learn the rich structure that allows humans to use concept

knowledge in a wide variety of generalizable functions (Osherson and Smith, 1981;

Barsalou, 1983; Biederman, 1987; Ward, 1994; Feldman, 1997; Markman and

Makin, 1998; Williams and Lombrozo, 2010; Jern and Kemp, 2013). Other recent

hierarchical Bayesian approaches in cognitive science have made progress in this

domain, however, by modeling concepts as types of probabilistic programs using

Bayesian program learning (Ghahramani, 2015; Goodman et al., 2015; Lake et al.,

2015), and by using models that integrate hierarchical Bayesian approaches with

deep learning (Salakhutdinov et al., 2013a) – both allowing learning from a smaller

number of training examples. Unlike many of the other approaches mentioned

above, these models are not based on clustering algorithms and represent an

important step forward within the context of Bayesian models of cognition.

It is important to note that this model is deliberately simple and is meant

only to represent a proof of principle that categorical inference and conceptual

knowledge acquisition can be modeled within this particular neurocomputational

framework, and to present this approach as a potentially useful tool in future active

inference research. We chose a particular set of feature combinations to illustrate

this, but it remains to be demonstrated that learning in this model would be equally

successful with a larger feature space and set of learnable hidden causes. Due to

limited scope, we have also not thoroughly addressed all other overlapping lines of

research. For example, work on exemplar models of concepts has also led to other

computational approaches. As one example, the EBRW model (Nosofsky and

Palmeri, 1997) has demonstrated ways of linking exemplar learning to drift

diffusion models. Another model within this line of research is the ALCOVE model

(Nosofsky et al., 1994) – an error-driven connectionist model of exemplar-based

category learning that employs selective attention and learns attentional weights

(this model also built on earlier work; see (Nosofsky, 2011)). Yet another

connectionist model with some conceptual overlap to our own is the DIVA model,

which learns categories by recoding observations as task-constrained principle

components and uses model fit for subsequent recognition (Kurtz, 2007). It will be

important in future work to examine the strengths and limitations of a scaled-up

version of our approach in relation to these models.

Yet another topic for future work would be the expansion of this type of

model to context-specific learning (e.g., with an additional hidden state factor for

encoding distinct contexts). In such cases, regularities in co-occurring features differ

in different contexts and other cues to context may not be directly observable (e.g.,

the same species of bird could be a slightly different color or size in different parts

of the world that otherwise appear similar) – creating difficulties in inferring when

to update previously learned associations and when to instead acquire competing

associations assigned to new contexts. At present, it is not clear whether the

approach we have illustrated would be successful at performing this additional

function, although the process of inferring the presence of a new hidden state level

in a second hidden state factor encoding context would be similar to what we have

shown within a single state factor (for related work on context-dependent

contingency learning, see (Gershman et al., 2013, 2017)). Another point worth

highlighting is that we have made particular choices with regard to various model

parameters and the number of observations provided during learning. Further

investigations of the space of these possible parameter settings will be important.

With this in mind, however, our current modelling results could offer additional

benefits. For example, the model's simplicity could be amenable to empirical studies

of saccadic eye movements toward specific features during novel category learning

(e.g. following the approach of (Mirza et al., 2018)). This approach could also be

combined with measures of neural activity in humans or other animals, allowing

more direct tests of the neural predictions highlighted above. In addition, the

introduction of exploratory, novelty-seeking, actions could be used to reduce the

number of samples required for learning, with agents selecting those data that are

most relevant.

Introducing actions allowing selective data sampling also brings with it other

interesting opportunities for using the general modeling approach used above. In

our model, the agent learned passively through observations (as a practical means

of preventing learning through feedback). Yet, while infants may initially be

somewhat restricted to passively observing their environment, observations quickly

come under the control of action (perhaps bootstrapping in a useful way on passive

observations to first acquire sensorimotor contingencies; (Deci and Ryan, 1985;

Oudeyer, 2007; Schmidhuber, 2010; Barto et al., 2013; Baltieri and Buckley, 2019))

– opening the possibility for both beneficial and detrimental effects on learning. By

incorporating action into our active inference model, further questions could be

addressed. For example, under what circumstances does choosing where to allocate

attention, or what states to visit, facilitate adaptively expanding or reducing a state

space? Under what circumstances (or perhaps unfortunate sequences of early

observations; e.g., see (Smith et al., 2019a)) might an agent fail to sample locations

in its environment that would have allowed for adaptive model expansions or

reductions? How might the structural priors or hyperpriors inherited by an

organism in a particular environmental niche guide adaptive action-guided

structure learning? These questions touch on deep problems in learning while

acting – here in the context of learning structure – that active inference models may

be especially well equipped to address (i.e., due to the intrinsic information-seeking

drive provided by expected free energy minimization; (Mirza et al., 2016; Parr and

Friston, 2017; Tschantz et al., 2019)).

1302   Here it is also again worth highlighting that, for agents acting within a

particular environmental niche, a model's accuracy need not correspond to a

model's adaptiveness (i.e., fitness or marginal likelihood). In some cases, it may be

more adaptive for an agent to efficiently learn to model only the features in its

environment relevant to its own survival, goal-achievement, etc. (Baltieri and

Buckley, 2019; Tschantz et al., 2019), and organisms can benefit in some cases from

acting based on false beliefs (McKay and Dennett, 2009); e.g., simplifications or

heuristic priors (Al-Muhaideb and Menai, 2011; Gigerenzer and Gaissmaier, 2011).

The distinction between accurate and adaptive models – where adaptive is

operationally defined as free energy minimizing – is the complexity or KL-

Divergence between posteriors and priors (i.e., not related to the notion of

satisficing (Oaksford and Chater, 2003)). Interestingly, it is exactly this (complexity)

term that structure learning by Bayesian model reduction optimizes – which, as

discussed above, is also important to consider when interpreting the 'accuracy' of

our model reduction results above across different simulated patterns of

experience.

1318   In conclusion, the Active Inference scheme we have described illustrates

feature integration in the service of conceptual inference: it can successfully

simulate simple forms of concept acquisition and concept differentiation (i.e.

increasing granularity), and it spontaneously affords one-shot generalization.

Finally, it speaks to empirical work in which behavioral tasks could be designed to

fit such models, which would allow investigation of individual differences in concept

learning and its neural basis. For example, such a model can simulate (neuronal)

belief updating to predict neuroimaging responses as we illustrated above; i.e., to

identify the neural networks engaged in evidence accumulation and learning

(Schwartenbeck et al., 2015). In principle, the model parameters (e.g., **A** matrix

precision) can also be fit to behavioral choices and reaction times – and thereby

phenotype subjects in terms of the priors under which they infer and learn

(Schwartenbeck and Friston, 2016). This approach could therefore advance

neurocomputational approaches to concept learning in several directions.

The issues raised here have a special importance in an active inference

setting, in the sense that minimizing expected free energy means choosing policies

that maximize information gain. In previous work, we have dealt with selection of

policies that yield informative data to help infer states of the world, or to actively

learn the parameters of the generative model. The results presented here propose

an additional challenge for future work: how do we select policies such that we

maximize information gain about the structure of the generative model itself?

Future research should investigate whether this basic approach can be successfully

extended to meet this challenge and assess the additional benefits it might offer

when applied to more complex real-world problems.

1342

Software note

Although the generative model – specified by the various matrices described in this

paper – changes from application to application, the belief updates are generic and

can be implemented using standard routines (here **spm_MDP_VB_X.m**). These

routines are available as Matlab code in the DEM toolbox of the most recent version

of SPM academic software: http://www.fil.ion.ucl.ac.uk/spm/. The simulations in

this paper can be reproduced (and customized) via running the Matlab code

included here is supplementary material (**Concepts_model.m**).

1351

1352   **Acknowledgment**

1353   This manuscript has been released as a Pre-Print at bioRxiv (Smith et al., 2019b).

1354

1355

1356   **References**

1357

Ackermann, S., and Rasch, B. (2014). Differential Effects of Non-REM and REM Sleep

on Memory Consolidation? *Curr. Neurol. Neurosci. Rep.* 14, 430.

doi:10.1007/s11910-013-0430-8.

Al-Muhaideb, S., and Menai, M. E. B. (2011). Evolutionary computation approaches

to the Curriculum Sequencing problem. *Nat. Comput.* 10, 891–920.

doi:10.1007/s11047-010-9246-5.

Anderson, J. R. (1991). The Adaptive Nature of Human Categorization. *Psychol. Rev.*

98, 409–429. doi:10.1037/0033-295X.98.3.409.

Baker, C., and Tenenbaum, J. (2014). "Modeling human plan recognition using

Bayesian theory of mind," in *Plan, activity, and intent recognition*, eds. G.

Sukthankar, C. Geib, H. Dui, D. Pynadath, and R. Goldman (Boston: Morgan

Kaufmann), 177–204.

Baltieri, M., and Buckley, C. L. (2019). Generative models as parsimonious

descriptions of sensorimotor loops. *Behav. Brain Sci.* 42, e218.

doi:10.1017/S0140525X19001353.

Barsalou, L. W. (1983). Ad hoc categories. *Mem. Cognit.* 11, 211–27.

doi:10.3758/bf03196968.

Barto, A., Mirolli, M., and Baldassarre, G. (2013). Novelty or Surprise? *Front. Psychol.*

4, 907. doi:10.3389/fpsyg.2013.00907.

Beck, J. (2017). Can bootstrapping explain concept learning? *Cognition* 158, 110–

121. doi:10.1016/j.cognition.2016.10.017.

Behrens, T. E. J., Muller, T. H., Whittington, J. C. R., Mark, S., Baram, A. B., Stachenfeld,

K. L., et al. (2018). What Is a Cognitive Map? Organizing Knowledge for Flexible

Behavior. *Neuron* 100, 490–509. doi:10.1016/J.NEURON.2018.10.002.

Biederman, I. (1987). Recognition-by-components: a theory of human image

understanding. *Psychol. Rev.* 94, 115–147. doi:10.1037/0033-295X.94.2.115.

Botvinick, M. M., Niv, Y., and Barto, A. C. (2009). Hierarchically organized behavior

and its neural foundations: A reinforcement learning perspective. *Cognition*

113, 262–280. doi:10.1016/J.COGNITION.2008.08.011.

Box, G. E., Hunter, J. S., and Hunter, W. G. (2005). *Statistics for experimenters. Wiley*

Series in Probability and Statistics. Hoboken, NJ.: Wiley.

Brown, T. H., Zhao, Y., and Leung, V. (2010). "Hebbian plasticity," in *Encyclopedia of*

Neuroscience, 1049–1056. doi:10.1016/B978-008045046-9.00796-8.

Chancey, J., Adlaf, E., Sapp, M., Pugh, P., Wadiche, J., and Overstreet-Wadiche, L.

(2013). GABA depolarization is required for experience-dependent synapse

unsilencing in adult-born neurons. *J. Neurosci.* 33, 6614–22.

doi:10.1523/JNEUROSCI.0781-13.2013.

Conant, C., and Ashbey, W. (1970). Every good regulator of a system must be a

model of that system. *Int. J. Syst. Sci.* 1, 89–97.

doi:10.1080/00207727008920220.

Cornish, N. J., and Littenberg, T. B. (2007). Tests of Bayesian model selection

techniques for gravitational wave astronomy. *Phys. Rev. D* 76, 083006.

doi:10.1103/PhysRevD.76.083006.

Deci, E., and Ryan, R. (1985). *Intrinsic motivation and self-determination in human*

behavior. New York: Plenum.

Dordek, Y., Soudry, D., Meir, R., and Derdikman, D. (2016). Extracting grid cell

characteristics from place cell inputs using non-negative principal component

analysis. *Elife* 5, 1–36. doi:10.7554/eLife.10094.

Feld, G., and Born, J. (2017). Sculpting memory during sleep: concurrent

consolidation and forgetting. *Curr. Opin. Neurobiol.* 44, 20–27.

doi:10.1016/J.CONB.2017.02.012.

Feldman, J. (1997). The Structure of Perceptual Categories. *J. Math. Psychol.* 41, 145–

70. doi:10.1006/jmps.1997.1154.

Friston, K. (2010). The free-energy principle: a unified brain theory? *Nat. Rev.*

Neurosci. 11, 127–38. doi:10.1038/nrn2787.

Friston, K., FitzGerald, T., Rigoli, F., Schwartenbeck, P., O Doherty, J., and Pezzulo, G.

(2016a). Active inference and learning. *Neurosci. Biobehav. Rev.* 68, 862–879.

doi:10.1016/j.neubiorev.2016.06.022.

Friston, K., FitzGerald, T., Rigoli, F., Schwartenbeck, P., and Pezzulo, G. (2017a).

Active Inference: A Process Theory. *Neural Comput.* 29, 1–49.

doi:10.1162/NECO_a_00912.

Friston, K. J., Litvak, V., Oswal, A., Razi, A., Stephan, K. E., van Wijk, B. C. M., et al.

(2016b). Bayesian model reduction and empirical Bayes for group (DCM)

studies. *Neuroimage* 128, 413–431. doi:10.1016/J.NEUROIMAGE.2015.11.015.

Friston, K., Lin, M., Frith, C., Pezzulo, G., Hobson, J., and Ondobaka, S. (2017b). Active

Inference, Curiosity and Insight. *Neural Comput.* 29, 2633–2683.

doi:10.1162/neco_a_00999.

Friston, K., Mattout, J., Trujillo-Barreto, N., Ashburner, J., and Penny, W. (2007).

Variational free energy and the Laplace approximation. *Neuroimage* 34, 220–

234. doi:10.1016/J.NEUROIMAGE.2006.08.035.

Friston, K., Parr, T., and de Vries, B. (2017c). The graphical brain: Belief propagation

and active inference. *Netw. Neurosci.* 1, 381–414. doi:10.1162/NETN_a_00018.

Friston, K., Parr, T., and Zeidman, P. (2018). Bayesian model reduction. Available at:

http://arxiv.org/abs/1805.07092 [Accessed March 27, 2019].

Friston, K., and Penny, W. (2011). Post hoc Bayesian model selection. *Neuroimage*

56, 2089–2099. doi:10.1016/J.NEUROIMAGE.2011.03.062.

Funahashi, R., Maruyama, T., Yoshimura, Y., and Komatsu, Y. (2013). Silent synapses

persist into adulthood in layer 2/3 pyramidal neurons of visual cortex in dark-

reared mice. *J. Neurophysiol.* 109, 2064–2076. doi:10.1152/jn.00912.2012.

Gelman, S. A., and Roberts, S. O. (2017). How language shapes the cultural

inheritance of categories. *Proc. Natl. Acad. Sci. U. S. A.* 114, 7900–7907.

doi:10.1073/pnas.1621073114.

Geman, S., Bienenstock, E., and Doursat, R. (1992). Neural Networks and the

Bias/Variance Dilemma. *Neural Comput.* 4, 1–58. doi:10.1162/neco.1992.4.1.1.

Gershman, S., and Blei, D. (2012). A tutorial on Bayesian nonparametric models. *J.*

Math. Psychol. 56, 1–12. doi:10.1016/J.JMP.2011.08.004.

Gershman, S. J., Monfils, M.-H., Norman, K. A., and Niv, Y. (2017). The computational

nature of memory modification. *Elife* 6. doi:10.7554/eLife.23763.

Gershman, S. J., and Niv, Y. (2010). Learning latent structure: carving nature at its

joints. *Curr. Opin. Neurobiol.* 20, 251–256. doi:10.1016/J.CONB.2010.02.008.

Gershman, S., Jones, C., Norman, K., Monfils, M., and Niv, Y. (2013). Gradual

extinction prevents the return of fear: implications for the discovery of state.

Front. Behav. Neurosci. 7, 164. doi:10.3389/fnbeh.2013.00164.

Ghahramani, Z. (2015). Probabilistic machine learning and artificial intelligence.

Nature 521, 452–9. doi:10.1038/nature14541.

Gigerenzer, G., and Gaissmaier, W. (2011). Heuristic Decision Making. *Annu. Rev.*

Psychol. 62, 451–482. doi:10.1146/annurev-psych-120709-145346.

Goodman, N. D., Tenenbaum, J. B., Feldman, J., and Griffiths, T. L. (2008). A rational

analysis of rule-based concept learning. *Cogn. Sci.* 32, 108–54.

doi:10.1080/03640210701802071.

Goodman, N. D., Tenenbaum, J. B., and Gerstenberg, T. (2015). *Concepts: New*

Directions. , eds. E. Margolis and S. Laurence Cambridge, MA: MIT Press.

Grossberg, S. (1987). Competitive learning: From interactive activation to adaptive

resonance. *Cogn. Sci.* 11, 23–63. doi:10.1016/S0364-0213(87)80025-3.

Hinton, G., Deng, L., Yu, D., Dahl, G., Mohamed, A., Jaitly, N., et al. (2012). Deep Neural

Networks for Acoustic Modeling in Speech Recognition: The Shared Views of

Four Research Groups. *IEEE Signal Process. Mag.* 29, 82–97.

doi:10.1109/MSP.2012.2205597.

Hobson, J., and Friston, K. (2012). Waking and dreaming consciousness:

neurobiological and functional considerations. *Prog. Neurobiol.* 98, 82–98.

doi:10.1016/j.pneurobio.2012.05.003.

Hobson, J., Hong, C.-H., and Friston, K. (2014). Virtual reality and consciousness

inference in dreaming. *Front. Psychol.* 5, 1133. doi:10.3389/fpsyg.2014.01133.

Jern, A., and Kemp, C. (2013). A probabilistic account of exemplar and category

generation. *Cogn. Psychol.* 66, 85–125. doi:10.1016/j.cogpsych.2012.09.003.

Kemp, C., Perfors, A., and Tenenbaum, J. (2007). Learning overhypotheses with

hierarchical Bayesian models. *Dev. Sci.* 10, 307–21. doi:10.1111/j.1467-

7687.2007.00585.x.

Kerchner, G., and Nicoll, R. (2008). Silent synapses and the emergence of a

postsynaptic mechanism for LTP. *Nat. Rev. Neurosci.* 9, 813–25.

doi:10.1038/nrn2501.

Kurtz, K. J. (2007). The divergent autoencoder (DIVA) model of category learning.

Psychon. Bull. Rev. 14, 560–576. doi:10.3758/BF03196806.

Lake, B. B. M., Salakhutdinov, R., and Tenenbaum, J. J. B. (2015). Human-level

concept learning through probabilistic program induction. *Science* 350, 1332–8.

doi:10.1126/science.aab3050.

Landau, B., Smith, L. B., and Jones, S. S. (1988). The importance of shape in early

lexical learning. *Cogn. Dev.* 3, 299–321. doi:10.1016/0885-2014(88)90014-7.

LeCun, Y., Bengio, Y., and Hinton, G. (2015). Deep learning. *Nature* 521, 436–44.

doi:10.1038/nature14539.

Lecun, Y., Bottou, L., Bengio, Y., and Haffner, P. (1998). Gradient-based learning

applied to document recognition. *Proc. IEEE* 86, 2278–2324.

doi:10.1109/5.726791.

Lewis, P., Knoblich, G., and Poe, G. (2018). How Memory Replay in Sleep Boosts

Creative Problem-Solving. *Trends Cogn. Sci.* 22, 491–503.

doi:10.1016/j.tics.2018.03.009.

Love, B. C., and Gureckis, T. M. (2007). Models in search of a brain. *Cogn. Affect.*

Behav. Neurosci. 7, 90–108. doi:10.3758/CABN.7.2.90.

Love, B. C., Medin, D. L., and Gureckis, T. M. (2004). SUSTAIN: a network model of

category learning. *Psychol. Rev.* 111, 309–32. doi:10.1037/0033-

295X.111.2.309.

MacKay, D. J. C., and Peto, L. C. B. (1995). A hierarchical Dirichlet language model.

Nat. Lang. Eng. 1, 289–308. doi:10.1017/S1351324900000218.

Markman, A. B., and Makin, V. S. (1998). Referential communication and category

acquisition. *J. Exp. Psychol. Gen.* 127, 331–54. doi:10.1037/0096-

3445.127.4.331.

Markman, E. (1989). *Categorization and Naming in Children*. Cambridge, MA: MIT

Press.

McClelland, J., and Rumelhart, D. (1981). An interactive activation model of context

effects in letter perception: I. An account of basic findings. *Psychol. Rev.* 88, 375–

407.

McKay, R., and Dennett, D. (2009). The evolution of misbelief. *Behav. Brain Sci.* 32,

493. doi:10.1017/S0140525X09990975.

McNicholas, P. (2016). Model-Based Clustering. *J. Classif.* 33, 331–373.

doi:10.1007/s00357-016-9211-9.

Mervis, C. B., and Rosch, E. (1981). Categorization of Natural Objects. *Annu. Rev.*

Psychol. 32, 89–115. doi:10.1146/annurev.ps.32.020181.000513.

Mirza, M., Adams, R., Mathys, C., and Friston, K. (2016). Scene Construction, Visual

Foraging, and Active Inference. *Front. Comput. Neurosci.* 10, 56.

doi:10.3389/fncom.2016.00056.

Mirza, M. B., Adams, R. A., Mathys, C., and Friston, K. J. (2018). Human visual

exploration reduces uncertainty about the sensed world. *PLoS One* 13,

e0190429. doi:10.1371/journal.pone.0190429.

Mnih, V., Kavukcuoglu, K., Silver, D., Rusu, A. A., Veness, J., Bellemare, M. G., et al.

(2015). Human-level control through deep reinforcement learning. *Nature* 518,

529–33. doi:10.1038/nature14236.

Murphy, G. L. (2016). Explaining the Basic-Level Concept Advantage in Infants…or Is

It the Superordinate-Level Advantage? *Psychol. Learn. Motiv. - Adv. Res. Theory*

64, 57–92. doi:10.1016/bs.plm.2015.09.002.

Nosofsky, R. M. (2011). "The generalized context model: An exemplar model of

classification," in *Formal approaches in categorization*, 18–39.

Nosofsky, R. M., Gluck, M. A., Palmeri, T. J., Mckinley, S. C., and Glauthier, P. (1994).

Comparing modes of rule-based classification learning: A replication and

extension of Shepard, Hovland, and Jenkins (1961). *Mem. Cognit.* 22, 352–369.

doi:10.3758/BF03200862.

Nosofsky, R. M., and Palmeri, T. J. (1997). An Exemplar-Based Random Walk Model

of Speeded Classification. *Psychol. Rev.* 104, 266–300. doi:10.1037/0033-

295X.104.2.266.

Oaksford, M., and Chater, N. (2003). Optimal data selection: Revision, review, and

reevaluation. *Psychon. Bull. Rev.* 10, 289–318. doi:10.3758/BF03196492.

Osherson, D. N., and Smith, E. E. (1981). On the adequacy of prototype theory as a

theory of concepts. *Cognition* 9, 35–58. doi:10.1016/0010-0277(81)90013-5.

Oudeyer, P.-Y. (2007). What is intrinsic motivation? A typology of computational

approaches. *Front. Neurorobot.* 1, 6. doi:10.3389/neuro.12.006.2007.

Parr, T., and Friston, K. (2017). Working memory, attention, and salience in active

inference. *Sci. Rep.* 7, 14678. doi:10.1038/s41598-017-15249-0.

Parr, T., and Friston, K. (2018). The Anatomy of Inference: Generative Models and

Brain Structure. *Front. Comput. Neurosci.* 12, 90.

doi:10.3389/fncom.2018.00090.

Parr, T., Markovic, D., Kiebel, S., and Friston, K. (2019). Neuronal message passing

using Mean-field, Bethe, and Marginal approximations. *Sci. Rep.* 9, 1889.

doi:10.1038/s41598-018-38246-3.

Perfors, A., Tenenbaum, J., Griffiths, T., and Xu, F. (2011). A tutorial introduction to

Bayesian models of cognitive development. *Cognition* 120, 302–21.

doi:10.1016/j.cognition.2010.11.015.

Perogamvros, L., and Schwartz, S. (2012). The roles of the reward system in sleep

and dreaming. *Neurosci. Biobehav. Rev.* 36, 1934–1951.

doi:10.1016/J.NEUBIOREV.2012.05.010.

Pfeiffer, B., and Foster, D. (2013). Hippocampal place-cell sequences depict future

paths to remembered goals. *Nature* 497, 74–9. doi:10.1038/nature12112.

Ritter, S., Wang, J., Kurth-Nelson, Z., and Botvinick, M. (2018). Episodic Control as

Meta-Reinforcement Learning. *bioRxiv*, 360537. doi:10.1101/360537.

Salakhutdinov, R., Tenenbaum, J. B., and Torralba, A. (2013a). Learning with

hierarchical-deep models. *IEEE Trans. Pattern Anal. Mach. Intell.* 35, 1958–71.

doi:10.1109/TPAMI.2012.269.

Salakhutdinov, R., Tenenbaum, J. B., and Torralba, A. (2013b). Learning with

hierarchical-deep models. *IEEE Trans. Pattern Anal. Mach. Intell.* 35, 1958–

1971. doi:10.1109/TPAMI.2012.269.

Sanborn, A. N., Griffiths, T. L., and Navarro, D. J. (2010). Rational Approximations to

Rational Models: Alternative Algorithms for Category Learning. *Psychol. Rev.*

117, 1144–1167. doi:10.1037/a0020511.

Schmidhuber, J. (2006). Developmental robotics, optimal artificial curiosity,

creativity, music, and the fine arts. *Conn. Sci.* 18, 173–187.

doi:10.1080/09540090600768658.

Schmidhuber, J. (2010). Formal Theory of Creativity, Fun, and Intrinsic Motivation

(1990–2010). *IEEE Trans. Auton. Ment. Dev.* 2, 230–247.

doi:10.1109/TAMD.2010.2056368.

Schwartenbeck, P., FitzGerald, T., Mathys, C., Dolan, R., and Friston, K. (2015). The

Dopaminergic Midbrain Encodes the Expected Certainty about Desired

Outcomes. *Cereb. Cortex* 25, 3434–3445. doi:10.1093/cercor/bhu159.

Schwartenbeck, P., and Friston, K. (2016). Computational Phenotyping in Psychiatry:

A Worked Example. *eNeuro* 3, ENEURO.0049-0016.2016.

doi:10.1523/ENEURO.0049-16.2016.

Shafto, P., Kemp, C., Mansinghka, V., and Tenenbaum, J. B. (2011). A probabilistic

model of cross-categorization. *Cognition* 120, 1–25.

doi:10.1016/j.cognition.2011.02.010.

Sharot, T. (2011). The optimism bias. *Curr. Biol.* 21, R941–R945.

doi:10.1016/J.CUB.2011.10.030.

Smith, R., Parr, T., and Friston, K. J. (2019a). Simulating Emotions: An Active

Inference Model of Emotional State Inference and Emotion Concept Learning.

Front. Psychol. 10, 2844. doi:10.3389/fpsyg.2019.02844.

Smith, R., Schwartenbeck, P., Parr, T., and Friston, K. (2019b). An active inference

approach to modeling structure learning: concept learning as an example case.

bioRxiv, 633677. doi:10.1101/633677.

Stachenfeld, K. L., Botvinick, M. M., and Gershman, S. J. (2016). The hippocampus as a

predictive map.

Stickgold, R., Hobson, J., Fosse, R., and Fosse, M. (2001). Sleep, learning, and dreams:

off-line memory reprocessing. *Science (80-.).* 294, 1052–7.

doi:10.1126/science.1063530.

Tervo, D. G. R., Tenenbaum, J. B., and Gershman, S. J. (2016). Toward the neural

implementation of structure learning. *Curr. Opin. Neurobiol.* 37, 99–105.

doi:10.1016/J.CONB.2016.01.014.

Tononi, G., and Cirelli, C. (2014). Sleep and the Price of Plasticity: From Synaptic and

Cellular Homeostasis to Memory Consolidation and Integration. *Neuron* 81, 12–

34. doi:10.1016/J.NEURON.2013.12.025.

Tschantz, A., Seth, A. K., and Buckley, C. L. (2019). Learning action-oriented models

through active inference. *bioRxiv*, 764969. doi:10.1101/764969.

Walker, M., and Stickgold, R. (2010). Overnight alchemy: sleep-dependent memory

evolution. *Nat. Rev. Neurosci.* 11, 218; author reply 218. doi:10.1038/nrn2762-

c1.

Wang, J. X., Kurth-Nelson, Z., Kumaran, D., Tirumala, D., Soyer, H., Leibo, J. Z., et al.

(2018). Prefrontal cortex as a meta-reinforcement learning system. *Nat.*

Neurosci. 21, 860–868. doi:10.1038/s41593-018-0147-8.

Wang, J. X., Kurth-Nelson, Z., Tirumala, D., Soyer, H., Leibo, J. Z., Munos, R., et al.

(2016). Learning to reinforcement learn. *arXiv:1611.05763*.

Ward, T. B. (1994). Structured Imagination: the Role of Category Structure in

Exemplar Generation. *Cogn. Psychol.* 27, 1–40. doi:10.1006/cogp.1994.1010.

Whittington, J. C. R., Muller, T. H., Mark, S., Barry, C., and Behrens, T. E. J. (2018).

Generalisation of structural knowledge in the hippocampal-entorhinal system.

Williams, J. J., and Lombrozo, T. (2010). The role of explanation in discovery and

generalization: evidence from category learning. *Cogn. Sci.* 34, 776–806.

doi:10.1111/j.1551-6709.2010.01113.x.

Wipf, D. P., and Rao, B. D. (2007). An Empirical Bayesian Strategy for Solving the

Simultaneous Sparse Approximation Problem. *IEEE Trans. Signal Process.* 55,

3704–3716. doi:10.1109/TSP.2007.894265.

Xu, F., and Tenenbaum, J. (2007a). Sensitivity to sampling in Bayesian word learning.

Dev. Sci. 10, 288–97. doi:10.1111/j.1467-7687.2007.00590.x.

Xu, F., and Tenenbaum, J. (2007b). Word Learning as Bayesian Inference. *Psychol.*

Rev. 114, 245–272.

1627

1628