ChIPSummitDB: A ChIP-seq- based database of human transcription factor binding sites and the topological arrangements of the proteins bound to them

Erik Czipa[1†], Mátyás Schiller[2†], Tibor Nagy[1], Levente Kontra[1,2], László Steiner[4], Júlia Koller[1,3], Orsolya Pálné-Szén[1] and Endre Barta[1,2*]

[†]These authors contributed equally

[1]Department of Biochemistry and Molecular Biology, Faculty of Medicine, University of Debrecen, Hungary

[2]Agricultural Genomics and Bioinformatics Group, Agricultural Biotechnology Institute, NARIC, Gödöllő, Hungary

[3]Semmelweis University, Institute of Genomic Medicines and Rare Disorders, Budapest, Hungary

[4]UD-GenoMed Medical Genomic Technologies Research & Development Services Ltd., Nagyerdei krt. 98., Debrecen, H-4032 Hungary

* To whom correspondence should be addressed. Email: barta.endre@unideb.hu.

ABSTRACT

ChIP-seq reveals genomic regions where proteins, e.g. transcription factors (TFs) interact with DNA. A substantial fraction of these regions, however, do not contain the cognate binding site for the TF of interest. Protein-protein interactions, co-binding, and DNA looping can explain this phenomenon. We uniformly processed 3727 human ChIP-seq data sets and determined the cistrome for 292 TFs together with the distances between the TF binding site (TFBS) centers and the ChIP-seq peak summits. In addition to providing a comprehensive human TFBS collection, the ChIPSummitDB database

and web interface allows to examine the topological arrangements of TF complexes on

the DNA.

Keywords

ChIP-seq, peak summit, TF topology, transcription factor binding site (TFBS)

BACKGROUND

ChIP-seq (Chromatin ImmunoPrecipitation followed by high-throughput sequencing)

is a powerful technique, which reveals the genome-wide positions of those DNA

sequences that co-precipitate with a given protein, which was used to generate the

antibody for the IP, [1,2]. The interaction between the protein and the DNA can be

direct or indirect. Direct interactions can be specific, i.e. when a protein (transcription

factor) recognizes and binds to a DNA sequence motif; or it can be nonspecific, as in

the case of histones or cohesins [3−5]. Indirect interactions between DNA and proteins

occur through transcriptional regulatory complexes and/or DNA looping. In such cases,

the cognate binding site for the given TF is not present under the ChIP-seq peaks

(Additional file 1) [6].

In a typical primary ChIP-seq analysis pipeline the sequence reads are mapped to a

reference genome, areas with the highest coverage (peaks) are determined, and the

enriched *de novo* or known motifs at the peaks are identified. These steps are followed

by downstream analyses, which typically involve peak annotation, comparison of

different ChIP-seq experiments, and visualization, for example generating profiles,

heat-maps and Venn-diagrams) [7]. The most critical step in such a pipeline is the peak

calling. Different peak calling algorithms provides different results and the number of

the determined peaks also depends on the number of the sequenced reads [8].

Today, raw data from more than 85000 human and mouse ChIP-seq experiments are

available [9], which gives the opportunity to perform further analyses and/or to set up

secondary databases using those data. Previously, such databases have been built based

on different parameters of ChIP-seq analyses. For some databases (CODEX,

BloodChIP, hmChIP), the experimental metadata were collected and the experiments

were classified by the cell type [10–12]. For other databases, for example Cistrome

Data Browser, GTDR, ChIP-Atlas, Factorbook, raw data from as many as possible

ChIP-seq experiments were collected and processed ([13–16]. Most of these databases

are not only a simple collection of ChIP-seq data and a display of ChIP-seq peaks.

Factorbook, for example, has an interactive tool to examine the nucleosome and histone

modification profiles around the ENCODE TF ChIP-seq peaks [16,17]. The gene

transcription regulation database (GTRD) project, among other things, focuses on

improving the peak calling procedure [14]. They use several peak calling algorithms

and make clusters of overlapping results. ChIP-Atlas provides a tool for extensive co-

localization and enrichment analyses [15]. TFBSbank focuses on annotating genomic

localizations, finding co-binding proteins, and searching for *de novo* and known motifs

within the peaks [18]. The Cistrome Data Browser combines ChIP-seq data with

chromatin accessibility data and provides a convenient web interface to browse and

download these data [13]. Most of the above-mentioned databases contain not only

human but mouse data too (Cistrome Data Browser, Factorbook, CODEX, hmChIP),

and, in some cases, ChIP-seq data for other species (GTRD, ChIP-Atlas, TFBSbank).

Enhancers are distant regulatory elements relative to transcription start sites [19]. They

can be characterized by TF binding (GTRD, TFBSbank), certain histone marks (SEdb),

and enhancer transcription (HACER) [20,21]. Because both TF binding and histone

modifications can be detected by ChIP-seq, secondary ChIP-seq database tools can

predict enhancer sequences as well if they determine the cognate binding sites under

the peaks of TF ChIP-seq experiments. The ChIP-seq peaks and the protein-binding

DNA-motifs under them can be further analyzed, and the resulted data can be integrated

into a higher level database, such as the TRRUST [22].

ChIP-seq databases can provide tools to search, analyze, visualize, and download

existing ChIP-seq data. Our previous results, however, demonstrated that ChIP-seq

peak summits can also help to understand the topological arrangements, the spatial

position(s) of different proteins bound to the DNA double helix. Therefore, our aim

was to extend our CCCTC-binding factor (CTCF) peak summit-based analysis to every

available ChIP-seq transcription factor, which was examined in human ChIP-seq

experiments [23]. For the study, we have manually selected 3727 ChIP-seq

experiments, which representing a very large number of human TFs and co-factors [9].

Since determining the correct positions of peak summits is critical for the analysis, we

have developed a robust peak filtering pipeline, by which the positions of peak summits

and the mapped TFBS motifs could be compared. Therefore, based on the ChIP-seq

peak regions for each TF, we defined the corresponding consensus motif binding site

sets for each of them. In addition to the consensus motif binding site sets, the

ChIPSummitDB contains the distances between each pair of mapped consensus motifs

and ChIP-seq peak summit.

The web interface of the ChIPSummitDB can display data in different views. Using the

GenomeView module, users can browse the genome for ChIP-seq peaks and consensus

motif binding site sets. The MotifView option can display the average distances

between the centers of consensus motif binding sites and the ChIP-seq peak summit

positions for each ChIP-seq experiment with overlapping peaks. Three different ChIP-

seq experiments can be compared in the PairShiftView module. Using the dbSNPView

option, users can evaluate whether a dbSNP entry overlaps with one or more consensus

motif binding sites from our database [24].

In addition to browsing all processed data, the analysis of the scatterplots provided in

the MotifView led us to hypothesize that the extent of the standard deviation of the

motif center vs peak summit distances may be proportional to the closeness of the given

protein to the DNA double helix.

CONSTRUCTION AND CONTENT

To construct the ChIPSummitDB, primary raw read data of ChIP-seq experiments and

the accompanying metadata were obtained from the NCBI SRA database [9].

Processing of the downloaded data into their final appearance in ChIPSummitDB is

summarized in Fig. 1. To determine peak regions, peak summits, consensus motif

positions, and the distances between peak summits and motif centers, we carried out

eight different processing steps (Additional file 1: Figure S1-S7). The scripts used

during   the   process   were   deposited   to   the   GitHub   repository

(https://github.com/summitdb). Below we provide some description of each step while

more details and explanation of them are on the ChIPSummitDB web site

(http://summit.med.unideb.hu/summitdb/Documentation.html) and in Additional file 1.

1. ChIP-seq data collection from public databases

We searched for human ChIP-seq experiments in the NCBI SRA database according to

its status as per November 1, 2017. We used the NCBI's run selector feature to

download all available metadata associated with the selected experiments [9]. A custom

PERL script was used to process the downloaded data in XML table format and to give

a unique (descriptive) name to every experiment. The names include the species, the

tissue, the cell line (if available), the pathology (eg. normal or cancer), the ChIP target

protein, and the experiment's SRA database ID. Our aim was to restrict the analysis to

transcription factors and to other non-histone proteins, thus experiments with other type

of proteins were filtered out by using a script. For simplicity and to avoid redundancy,

we processed only the normal (without any specific treatment, which influence the TF-

DNA interaction) ChIP-seq experiments. The final list contained 4052 experiments and

was converted into a table with the proper format (BED, BEDGRAPH) for further

processing (Additional file 1: Figure S1).

2. Basic ChIP-seq analysis

For the basic processing, we used a modified version of our ChIP-seq_anal BASH script

(Additional file 1: Figure S1) [7]. Briefly, the script needs two input files. The first is

the above-mentioned table with the experiments, while the second contained the SRR

IDs for each SRX ID. After downloading the SRR files and converting them into fastq

format, we mapped the reads to the hg19 (GRCh37) human reference genome using the

Burrows-Wheeler Aligner (BWA) program [25,26]. Peak calling, generation of the

bedgraph coverage files, and *de novo* identification of protein-binding DNA motifs

were performed by using the HOMER package. The output of the analysis contained

the BAM files with the read sequences, the HOMER tag directories, the peaks in BED

file format, the BEDGRAPH files, and both the *de novo* identified and previously

known motifs, in a single html report [27].

3. Peak splitting and summit prediction

The basic analysis provided the peak regions for each ChIP-seq experiment in two

forms, a BED file containing the borders of the HOMER predicted peak regions and a

BEDGRAPH file with the coverage values of the extended reads within these peak

regions [27]. It is possible to have more than one binding site within a peak region,

145 which can result in more than one summit. We employed the PeakSplitter program to

146 determine such summit positions using the BEDGRAPH files as input [28]. The result

147 of this step is a BED file for each experiment containing the positions of the identified

148 summit(s) for each peak (Additional file 1: Figure S2).

149  **4. Peak filtering**

150 The usefulness of the ChIPSummitDB largely relies on the correct determination of

151 peak regions. Different peak -finding algorithms can give surprisingly diverse peak sets

152 using the same ChIP-seq experiments. A number of parameters in the experiment, such

153 as the number of the cells in the biological sample, the conditions of the sonication, the

154 quality of the antibody, the library preparation, and especially the depth of the

155 sequencing affect the number of detected peaks. There are different approaches to

156 determine the biologically most relevant peak regions. One approach was to apply

157 different peak calling programs and find the consensus peak sets from the results.

158 Furthermore, we also developed a different approach, in which we used only the

159 HOMER peak calling program, but applied a rigorous filtering, which was based on the

160 shape of the peaks, to reduce the number of false positives/artifact peaks in the peak

161 sets obtained in the previous step for downstream summit based topology analysis

162 (Additional file 1: Figure S3). Using this approach, we filtered out about 35 percent of

163 all peaks [27] (Additional file 3).

164  **5. Assigning consensus motifs to TF ChIP-seq experiments**

165 We assume that if the antibody used during the immunoprecipitation is against a TF,

166 then the cognate binding site for that TF will be enriched in the peak set of the given

167 ChIP-seq experiment. During the basic analysis, we determined the enriched motifs for

168 each peak set. The problem was that even if the immunoprecipitated TF was the same,

the resulting *de novo* motif could be slightly different. Also, the *de novo* motif finding

algorithms usually give more than one enriched motif and it is unclear whether the best

one is the cognate binding site. To precisely determine the peak summit motif center

distances, however, we need to use the same binding site for every experiment with the

same TFBS. Therefore, we chose a reverse approach. Based on the antibody used

during the immunoprecipitation, we assigned a JASPAR core consensus motif to each

experiment by hand. This resulted in a table where there is a corresponding JASPAR

consensus motif for each TF experiment (Additional file 1: Figure S4, Additional file

2) [29].

6. Motif optimization

Many of the consensus motifs in the JASPAR database are based on *de novo* motif

finding in ChIP-seq peak regions [29]. Since we now have a good collection of

representative ChIP-seq experiments for most of the transcription factors, we decided

to further optimize the consensus motif matrices. For this, we first merged the peaks of

the experiments belonging to the same consensus motif, and then we used the HOMER

package to optimize the matrices on these merge peak regions (Additional file 1: Figure

S5) [27]. The resulting optimized matrices were further inspected and adjusted

manually. The motif optimization resulted in more than one similar motif in a few cases.

The decision between them couldn't be automatized. In these cases, the most analogous

motif was chosen.

7. Remapping motifs

Once we had all the optimized consensus motif matrices, we needed to map them back

to the genome. For each optimized JASPAR consensus motif matrix, we had a list of

corresponding ChIP-seq experiments (Additional file 1: Figure S4) [29]. We took the

peak regions for those experiments and merged them to create the merged peak regions

for each matrix. This is an important and, so far, a unique step among the similar ChIP-

seq databases. Using this method, we specifically determined the possible transcription

factor binding sites. For mapping, we used three different programs and we kept only

the positions where at least two of them gave a hit for the final consensus motif binding

site sets (Additional file 1: Figure S6) [27,30,31].

8. Motif center and summit distance calculation

After the peak filtering in step 4, we got the list of peak summits for each ChIP-seq

experiment. In step 7, we got the ChIP-seq verified positions of TFBSs for each

consensus motif. The majority of the peak regions do not contain the cognate binding

site, even for TF ChIP-seq experiments. We hypothesize that in these cases the given

TF can be part of a complex, which is bound to the DNA through another TF, which in

turn is bound to its cognate binding site, which is also present in our consensus binding

site set. Therefore, we investigated such cases as well. To do this, we calculated every

distance between consensus motif centers and the nearby ChIP-seq peak summit

positions. The calculation is motif based, which means that the output is a list for each

consensus motif set (i.e. a given transcription factor binding site), which contains the

distances of every peak summit inside the 50 bp range of the given consensus motif

binding site (Additional file 1: Figure S7) [32]. Practically, if we see a consensus motif

(e.g. CTCF), we will have the ChIP-seq verified instances of that motif in the genome

(88906) and a list of distances for each of the 3727 ChIP-seq experiments. These lists

were processed further in the database. The number of distances in these lists were used

as a cutoff value in the MotifView. The standard deviation of the distances in these lists

was also calculated and indicated in the Y-axis of the MotifView.

This processing of raw ChIP-seq read and metadata resulted in the following tables and

files:

1.   The HOMER *homerpeaks.txt files for each experiment. These files contain the peak regions and other parameters used in peak finding.

2.   A peak region and a summit bed format file for each experiment.

3.   A table with all the metadata related to the ChIP-seq experiments.

4.   A table with the average distances between each consensus binding site set and experiment.

5.   A table with all the distances between individual consensus binding sites and each overlapping peak summit.

6.   The HOMER *de novo* motif finding results for every experiment.

7.   The optimized consensus motif matrices for every consensus binding site set.

Based on these files and tables, the physical and logical scheme of the database was

developed using Oracle SQL Developer Database Modeler (version 4.2). For data

storage, MariaDB (version 5.5.60) was chosen because it is free and open source.

The website is hosted in CentOS Linux with Apache HTTP server and pages were

developed using PHP. Graphs and other visual elements representing statistical results

were made using the D3.js (version 3) JavaScript library.

UTILITY AND DISCUSSION

The ChIPSummitDB address two main aims. First, the database is a comprehensive

collection of ChIP-seq verified binding sites for 292 different TFs. Second, the database

provides a new tool for analyzing the topological relationship between bound and co-

bound proteins on the TFBSs.

There are six different views for exploring the database. From the main page, the user

can either choose one of them under the search view tab or click any of the example

pictures in order to go directly to a view page.

User interfaces

MotifView is the summary page for each of the examined TFs. During the construction

of the database, we have determined the ChIP-seq verified binding site sets for 292

different TFs (Additional file 2). For each ChIP-seq experiment, we also counted how

many times the filtered peak summits of that experiment overlapped with a binding site

of the chosen TF. Furthermore, we calculated the exact distances between each

occurrence of a peak summit and binding site pair (Additional file 1: Figure S7). In

MotifView, one can see the averages of these distances for each experiment, where the

number of calculated distances is above the given threshold. Thus, the scatterplot

presented in MotifView shows the average distances of the overlapping peak summits

relative to the center of the adjusted TFBS. In the Y-axis, one can choose between

showing the number of overlapping peak summits and TFBS pairs or the standard

deviation of those distances.

Each point on the plot represents one ChIP-seq experiment. Circles represent

experiments where the antibody was against a TF with a defined TFBS, while triangles

show co-factors and other proteins attached to the primarily bound TF. On the right

side of the plot, there is a color-coded list of antibodies or cell types used in these

experiments. The list can be sorted alphabetically or by the number of occurrences. By

clicking on these squares (TFs) or triangles (co-factors and other proteins), one can

change the displayed experiments. For example, the user can choose and examine only

the experiments belonged to one or more antibodies or cell types. This allows users to

flexibly change the displayed experiments. On the scatterplot, one can select up to three

experiments for further analysis in the other views.

The PairShiftView allows users to examine the distribution of individual peaks vs.

summit consensus motif distances for three experiments. To smooth the graph, a 5 bp

rolling bin is used in the histogram. Each curve represents one ChIP-seq experiment.

During the creation of the database, both the summit locations for all peaks for a given

experiment and the consensus motif binding sites of the chosen TF have been

determined. In the latter case, only those binding sites that have been counted are

shown, where the binding site in the genome overlaps at least one peak of a ChIP-seq

experiment immunoprecipitated with the antibody against the corresponding TF. In the

histogram, the highest points of the curves show the most likely topological position

for a given protein on the DNA double helix relative to the consensus motif. The height

of the curve depends on the number of overlapping consensus motif summit pairs

(element number). In most cases, the curve has one peak, but sometimes it also has a

shoulder. This indicates a more complex topological arrangement or a consequence of

other, still unknown, reasons. It is remarkable for example that in many cases the

distance between the main summit and the shoulder (or between two summits from

different experiments with the same antibody) is approximately 11 or 22 bp (Fig. 2)

(http://summit.med.unideb.hu/summitdb/paired_shift_view.php?exp1=419&exp2=19

60&exp3=3681&motive=FOXA1&motifid=77&limit=25&low_limit=-

25&formminid=1&formmaxid=10000&mnelem=100&formmaxelem=120000   ),

which represents one or two turn in the double helix and can be interpreted as a protein

on the same side of the DNA [33].

Although the highest point of the curve in the PairShiftView and the position of the

corresponding scatter in the X-axis indicate the same topological positioning of the

given protein on the DNA double helix, these values can be different. In most cases,

this is because in the histogram the distribution curve either has a shoulder or is simply

asymmetric. Therefore, we assume that while the scatterplot in the MotifView gives a

good overview of the differences in the topological arrangements of the given

consensus motif experiments pairs, the PairShiftView is a more accurate tool to

examine the relative topological arrangements of the three chosen experiments.

Although in most cases one gets to the PairShiftView from the MotifView by selecting

three experiments, the user can change both the consensus motif and the selected

experiments from inside the PairShiftView. This allows a quick comparison of any

three experiments.

Besides seeing the topological arrangement of three chosen immunoprecipitated

proteins relative to the given motif center, the extent to which the peaks of the three

ChIP-seq experiments share the same binding sites is also interesting. The VennView

is designed to allow this. During the processing of the ChIP-seq experiments, we

determined not only the filtered peaks for each ChIP-seq experiment but also the

consensus motif binding sets for each transcription factor. Thus, for each binding site

in the genome, the user can see which ChIP-seq experiment has an overlapping peak

(technically this means a peak summit position within 50 bp in either direction). In this

way, having the three chosen experiments and the consensus motif, we can count how

many sites have overlapping peak summits for each of the seven possible combinations.

In the VennView, the user can see these values in a Venn diagram. This can be useful

for comparing three experiments with not only the same antibody, but from different

tissues / developmental stages / treatments and also in examining the extent of

overlapping binding of a given transcription factor and its co-factors or co-bound

proteins.

In the recent release, the ChIPSummitDB contains data from the analysis of 3727

human ChIP-seq experiments. In the ExperimentView, the user can see an overview of

the main attributes for each experiment. Most importantly, there are links to the NCBI

SRA database [26]. The number of sequencing reads and the number of filtered peaks

called by the HOMER findPeaks program is also listed [27]. During the analysis

pipeline, we have determined the most enriched *de novo* and known motifs for each

experiment. The link for the results of this search is also located on this page.

The GenomeView allows users to see the database content (consensus binding sites,

peaks, etc.) in a genomic context through a web browser interface. This view is

implemented in the JBrowse framework [34]. The GenomeView can be used as a

standalone web page where the users can select tracks to load and display. Users can

select from the 292 consensus motif sets, the 3727 experiments or from miscellaneous

tracks like genomic features or know SNPs. Therefore, users can compare any

combinations of experiments versus consensus motif binding sites. Users can also get

to this JBrowse interface from the MotifView, the PairShiftView, and the VennView

after selecting up to three experiments. In this case, the consensus motif set of the

chosen motif and the overlapping peaks and summits of the three chosen experiments

will be displayed initially. The user can display any other previously mentioned tracks.

Our database provides a comprehensive catalogue of experimentally verified

transcription factor binding sites in the human genome. As the cost of whole genome

sequencing is drastically decreasing, the number of variations associated with a certain

phenotype is rapidly increasing. Most of these variations are in intronic or intergenic

regions. Therefore, there is a great interest in determining the overlap of transcription

factor binding sites. The dbSNPView allows users to check these cases. Users can enter

either a genomic region or a dbSNP ID [24]. In the first case, the webpage will then

display the given region with the variations on it and also the overlapping consensus

motif binding sites from our database. The overlapping SNPs are highlighted in red.

Either clicking on them or entering the dbSNP accession number directly into the search

field leads to the enlarged dbSNPView. Here the reference genome sequence together

with the logo of the consensus motif and the overlapping SNPs can be seen. This view

is useful for examining how severely the altered base can affect the transcription factor

binding. There is also a button to check which experiments give an overlapping peak

with the given variation.

The Novelty of the ChIPSummitDB

The ChIPSummitDB is the first ChIP-seq related database that analyzes and shows the

peak summit and consensus motif binding site center distances. The web interface of

the database provides several tools for displaying this kind of topological data. In the

MotifView, every experiment (antibodies used for the immunoprecipitation) that is

above the threshold number of overlapping peaks for a chosen consensus motif is

shown. Either direct binding (in the cases where the immunoprecipitated protein

recognizes and binds to the given binding site) or indirect binding is indicated. We

hypothesize that the standard deviation of the distances of the peak summit and binding

site centers shows the directness of the binding. For example, based on the standard

deviations, there are at least three groups of interacting proteins at the YY1 consensus

motif   binding   site

(http://summit.med.unideb.hu/summitdb/motif_view.php?maxid=10000&minid=1&m

nelem=1000&mxelem=120000&motive=YY1). In the first group, the YY1 ChIP-seq

experiments have a standard deviation value between 16 and 22 [35]. In the next layer,

the CTCF and the cohesin proteins and some other TF and co-factor have standard

deviation values between 23 and 27 [6]. Interestingly, there are many other ChIP-seq

experiments, which have a standard deviation above 27 but still have more than 1000

peaks (the threshold value set here), which are overlapping with the YY1 consensus

motif binding sites throughout the genome. If we further analyze the scatterplot, we

may notice that the YY1 experiments are grouped around 2 at the X-axis, while the

CTCF experiments are grouped around -2, as most of the other TFs and cofactors from

the third group. Based on these observations, we can hypothesize that the YY1 binds to

its cognate binding site. The CTCF-cohesin complex binds to the already bound YY1

protein in the same horizontal arrangement as can be seen at the CTCF binding sites

(http://summit.med.unideb.hu/summitdb/motif_view.php?maxid=10000&minid=1&m

nelem=100&mxelem=120000&motive=CTCF). The proteins in the third group most

likely bind to the CTCF-cohesin complex. There are, of course, not only CTCF-cohesin

proteins in the second group (e.g. SRF or auts2) [36]. Proteins in the second group are

most probably directly bound to the YY1 protein.

Besides the already analyzed CTCF-cohesin topology, the ChIPSummitDB provides

further evidence that the peak summit versus the binding site based analysis indicates

topological arrangements for TF-DNA complexes. One good example is the

GATA1::TAL1 composite element (http://jaspar.genereg.net/matrix/MA0140.2/) [37].

Here, the ChIPSummitDB clearly confirms the experimental results. The topological

arrangement of the two transcription factors is clearly visible at both the MotifView

(Fig.   3a)

(http://summit.med.unideb.hu/summitdb/motif_view.php?maxid=10000&minid=1&m

nelem=100&mxelem=120000&motive=GATA1%3A%3ATAL1)   and   at   the

PairShiftView   (Fig.   3a)

(http://summit.med.unideb.hu/summitdb/paired_shift_view.php?exp1=220&exp2=21

8&exp3=undefined&motive=GATA1::TAL1&motifid=89&limit=25&low_limit=-

25&formminid=1&formmaxid=10000&mnelem=100&formmaxelem=120000).

Theoretically, we expect that the peak summit will be in the middle of the transcription

factor binding site. We have already shown, in the case of the CTCF-cohesin complex,

that this is not necessarily true [38]. The ChIPSummitDB provides even more extreme

cases. For example, in the case of the NFYB motif observed in the MotifView (Fig. 3b)

(http://summit.med.unideb.hu/summitdb/motif_view.php?maxid=10000&minid=1&m

nelem=2000&mxelem=120000&motive=NFYB), the average distance values that the

NFYB binds are upstream, while the USF1 binds downstream of the motif. If we further

scrutinize the topology on the PairShiftView, which shows the real distribution of the

distances, we can see even more extremities (Fig. 3b)

(http://summit.med.unideb.hu/summitdb/paired_shift_view.php?exp1=2301&exp2=7

61&exp3=1597&motive=NFYB&motifid=175&limit=40&low_limit=-

40&mnelem=2000). In the case of NFYB, most of the distances between the

overlapping consensus motifs and peak summits are around the +15 - +17 positions. In

the case of USF1, however, the majority of the distance values are clustered around the

-18 position. It is also remarkable that in the distribution curves, there are also other

smaller shoulders.

Conclusions

ChIPSummitDB is the first ChIP-seq database based on a transcription factor binding

site centered analysis of peak summits. The database convincingly confirms our

previous hypothesis that if the different proteins are sitting on the DNA not exactly

above each other, then the average peak summit position will display a shifted value

relative to the motif center. There can be numerous reasons for this phenomenon. One

obvious example is when two different transcription factor binds nearby on a composite

element [37]. Surprisingly, there are cases, when a transcription factor is bound to its

cognate site in the DNA and somehow a different protein without a DNA binding

domain that is bound to that TF gets so close to the DNA double helix that it will

crosslink to it during the experiment. This will result in a shifted peak summit versus

motif center value in our analysis (as can be seen in MotifView and PairShiftView in

our database). We showed this shift for cohesion proteins (RAD21, SA1/2, and

SMC1/3), but this shift can also be recognized in other cases (e.g. at the ETS TFs like

the   ELF1,

http://summit.med.unideb.hu/summitdb/motif_view.php?maxid=2000&minid=1&mn

elem=3000&mxelem=120000&motive=ELF1) [23].

The detailed analysis of the ChIP-seq summit and motif center positions led us to a new

hypothesis: Taking a consensus binding site set (ChIP-seq verified binding sites for a

given transcription factor), the closer a given protein is to the DNA, the lower the

standard deviation of the distances between overlapping peak summits versus motif

center pairs. In other words, if a protein is very close to the DNA double helix, which

means in most cases that the protein is bound to the DNA, the resulting ChIP-seq peak

summits will more likely be centered in the middle of the DNA region covered by the

protein. This recognition can help us better understand how the protein complexes are

built on the DNA starting from binding of a transcription factor to its cognate binding

site.

In the MotifView of the different consensus binding site sets, ChIP-seq experiments

made by different protein antibodies give overlapping peaks on the same sites. An

interesting biological question is, if we take three different experiments (e.g. CTCF,

RAD21, and Znf143) from the same type of cells (GM12878) and analyze their peaks,

is there overlapping at the CTCF consensus binding sites and are they giving peaks on

the same sites? The VennView in the ChIPSummitDB gives an answer to this question

(http://summit.med.unideb.hu/summitdb/venn_diagramm.php?exp1=2672&exp2=273

4&exp3=2714&motive=CTCF&motifid=33&mnelem=10000) and, thus, may help to

elucidate the role of the different TF protein complexes on the DNA.

Besides these completely new features, the ChIPSummitDB provides a comprehensive,

experimental based collection of transcription factor binding sites. The site can be

browsed in the GenomeView and we have also developed a dbSNP view that allows

users to check whether a given SNP is overlapping a TFBS [24,34]. This feature can be

useful in determining the consequences of non-coding mutations.

List of abbreviations

bp: base pair

BWA: Burrows-Wheeler Aligner

ChIP-seq: Chromatin Immunoprecipitation Sequencing

CTCF: CCCTC-binding factor

DB: Database

dbSNP: Single Nucleotide Polymorphism Database

ELF1: E74-like factor 1

ETS1: E26 Oncogene Homolog 1

GATA1: GATA-binding factor 1

GM12878: Lymphoblastoid cell line

HOMER: Hypergeometric Optimization of Motif EnRichment

HTML: HyperText Markup Language

HTTP: HyperText Transfer Protocol

ID: identification number/identifier

NCBI: National Center for Biotechnology Information

463 NFYB: Nuclear transcription factor Y subunit beta

464 PHP: Hypertext Preprocessor

465 PWM: Position weight matrix

466 RAD21: Double-strand-break repair protein (Scc1, Mcd1)

467 SA1: Stromal Antigen 1

468 SMC1/3: Structural maintenance of chromosomes proteins

469 SNP: Single Nucleotide Polymorphism

470 SQL: Structured Query Language

471 SRA: Sequence Read Archive

472 TAL1: T-cell acute lymphocytic leukemia protein 1

473 TF: transcription factor

474 TFBS: transcription factor binding site

475 USF1: Upstream stimulatory factor 1

476 XML: Extensible Markup Language

477 YY1: Yin Yang 1

478 ZNF143: Zinc Finger Protein 143

479 **Declarations**

480 **Ethics approval and consent to participate**

481 Since this study carries out exclusively in silico analysis of already published data, it

482 does not need ethics committee approval, as it did not constitute biomedical research.

483 However, reporting is consistent with all ethical requirements.

484 **Consent for publication**

485 No consent for publication is required.

Funding

Authors' contributions

EB initiated the project. EB and EC conceived and designed the overall project. EC, JK and OPS carried out the data collection. EB carried out the basic data processing. EC designed and carried out the downstream analysis and the generation of data tables. The website was designed and created by MS and TN and LK. EC, TN and LS performed the statistical analyses and data filtering. EB and EC evaluated the results and wrote the manuscript.

Availability of data and materials

The datasets supporting the conclusions of this article are included within the article and in Additional file 1-3. The full list of guidelines and a glossary of terms can be found in ChIPSummitDB website (http://summit.med.unideb.hu/summitdb/) and in Additional file 1. The scripts used during the analysis are available at the following website: https://github.com/summitdb.

Competing interests

The authors declare no conflict of interest.

Acknowledgments:

The authors would like to thank Ferenc Marincs and Karen L. Uray for their critical discussion and technical assistance. Data analyses were performed on the High Performance Computing cluster at the Genomic Medicine and Bioinformatic Core

Facility of Department of Biochemistry and Molecular Biology, University of

Debrecen.

References

1. Ren B, Wyrick JJ, Aparicio O, Jennings EG, Simon I, Zeitlinger J, et al. Genome-

Wide Location and Function of DNA Binding Proteins. 2000;2306–10.

2. Vishwanath R. Iyer et al. Genomic binding sites of the yeast cell-cycle

transcription factors SBF and MBF. 2001;

3. Gordan R, Hartemink AJ, Bulyk ML. Distinguishing direct versus indirect

transcription factor-DNA interactions. Genome Res. United States; 2009;19:2090–

100.

4. Xiao T, Wallace J, Felsenfeld G. Specific sites in the C terminus of CTCF interact

with the SA2 subunit of the cohesin complex and are required for cohesin-dependent

insulation activity. Mol Cell Biol. United States; 2011;31:2174–83.

5. Bartke T, Vermeulen M, Xhemalce B, Robson SC, Mann M, Kouzarides T.

Nucleosome-interacting proteins regulated by DNA and histone methylation. Cell

[Internet]. 2010;143:470–84. Available from:

https://www.ncbi.nlm.nih.gov/pubmed/21029866

6. Beagan JA, Duong MT, Titus KR, Zhou L, Cao Z, Ma J, et al. YY1 and CTCF

orchestrate a 3D chromatin looping switch during early neural lineage commitment.

2017;1–14.

7. Barta E. Command line analysis of ChIP-seq results. EMBnet.journal; Vol 17, No 1

Next Gener Seq Data Anal - 1014806/ej171209 [Internet]. 2011; Available from:

http://journal.embnet.org/index.php/embnetjournal/article/view/209/480

8. Koohy H, Down TA, Spivakov M, Hubbard T. A Comparison of Peak Callers Used

for DNase-Seq Data. 2014;

9. Leinonen R, Sugawara H, Shumway M, Collaboration on behalf of the INSD. The

Sequence Read Archive. Nucleic Acids Res. Oxford University Press; 2011;39:D19–

21.

10. Sánchez-Castillo M, Ruau D, Wilkinson AC, Ng FSL, Hannah R, Diamanti E, et

al. CODEX: a next-generation sequencing experiment database for the

haematopoietic and embryonic stem cell communities. Nucleic Acids Res [Internet].

2014/09/30. Oxford University Press; 2015;43:D1117–23. Available from:

https://www.ncbi.nlm.nih.gov/pubmed/25270877

11. Chacon D, Beck D, Perera D, Wong JWH, Pimanda JE. BloodChIP: a database of

comparative genome-wide transcription factor binding profiles in human blood cells.

Nucleic Acids Res. England; 2014;42:D172-7.

12. Chen L, Wu G, Ji H. hmChIP: a database and web server for exploring publicly

available human and mouse ChIP-seq and ChIP-chip data. Bioinformatics [Internet].

2011/03/30. Oxford University Press; 2011;27:1447–8. Available from:

https://www.ncbi.nlm.nih.gov/pubmed/21450710

13. Mei S, Qin Q, Wu Q, Sun H, Zheng R, Zang C, et al. Cistrome Data Browser: a

data portal for ChIP-Seq and chromatin accessibility data in human and mouse.

Nucleic Acids Res. England; 2017;45:D658–62.

14. Yevshin I, Sharipov R, Valeev T, Kel A, Kolpakov F. GTRD: a database of

transcription factor binding sites identified by ChIP-seq experiments. Nucleic Acids

Res. England; 2017;45:D61–7.

15. Oki S, Ohta T, Shioi G, Hatanaka H, Ogasawara O. ChIP-Atlas : a data-mining

suite powered by full integration of public ChIP-seq data. 2018;1–10.

16. Wang J, Zhuang J, Iyer S, Lin X-Y, Greven MC, Kim B-H, et al. Factorbook.org:

a Wiki-based database for transcription factor-binding data generated by the

ENCODE consortium. Nucleic Acids Res [Internet]. 2012/11/29. Oxford University

Press; 2013;41:D171–6. Available from:

https://www.ncbi.nlm.nih.gov/pubmed/23203885

17. Landt SG, Marinov GK, Kundaje A, Kheradpour P, Pauli F, Batzoglou S, et al.

ChIP-seq guidelines and practices of the ENCODE and modENCODE consortia.

Genome Res [Internet]. Cold Spring Harbor Laboratory Press; 2012;22:1813–31.

Available from: https://www.ncbi.nlm.nih.gov/pubmed/22955991

18. Chen D, Jiang S, Ma X, Li F. TFBSbank: a platform to dissect the big data of

protein-DNA interaction in human and model species. Nucleic Acids Res [Internet].

2016/11/24. Oxford University Press; 2017;45:D151–7. Available from:

https://www.ncbi.nlm.nih.gov/pubmed/27899608

19. Blackwood EM, Kadonaga JT. Going the distance: a current view of enhancer

action. Science. United States; 1998;281:60–3.

20. Jiang Y, Qian F, Bai X, Liu Y, Wang Q, Ai B, et al. SEdb: a comprehensive

human super-enhancer database. Nucleic Acids Res. England; 2019;47:D235–43.

21. Wang J, Dai X, Berry LD, Cogan JD, Liu Q, Shyr Y. HACER: an atlas of human

active enhancers to interpret regulatory variants. Nucleic Acids Res. England;

2019;47:D106–12.

22. Han H, Cho J-W, Lee S, Yun A, Kim H, Bae D, et al. TRRUST v2: an expanded

reference database of human and mouse transcriptional regulatory interactions.

Nucleic Acids Res. England; 2018;46:D380–6.

23. Nagy G, Czipa E, Steiner L, Nagy T, Pongor S, Nagy L, et al. Motif oriented

high-resolution analysis of ChIP-seq data reveals the topological order of CTCF and

cohesin proteins on DNA. BMC Genomics. 2016;17:637.

24. Sherry ST, Ward MH, Kholodov M, Baker J, Phan L, Smigielski EM, et al.

dbSNP: the NCBI database of genetic variation. Nucleic Acids Res [Internet]. Oxford

University Press; 2001;29:308–11. Available from:

https://www.ncbi.nlm.nih.gov/pubmed/11125122

25. Li H, Durbin R. Fast and accurate short read alignment with Burrows-Wheeler

transform. Bioinformatics. England; 2009;25:1754–60.

26. Bethesda (MD): National Center for Biotechnology Information (US). Sequence

Read Archive Submissions Staff. Using the SRA Toolkit to convert .sra files into

other formats. 2011.

27. Heinz S, Benner C, Spann N, Bertolino E, Lin YC, Laslo P, et al. Simple

combinations of lineage-determining transcription factors prime cis-regulatory

elements required for macrophage and B cell identities. Mol Cell. United States;

2010;38:576–89.

28. Salmon-Divon M, Dvinge H, Tammoja K, Bertone P. PeakAnalyzer: Genome-

wide annotation of chromatin binding and modification loci. BMC Bioinformatics

[Internet]. 2010;11:415. Available from: https://doi.org/10.1186/1471-2105-11-415

29. Khan A, Fornes O, Stigliani A, Gheorghe M, Castro-Mondragon JA, van der Lee

R, et al. JASPAR 2018: update of the open-access database of transcription factor

binding profiles and its web framework. Nucleic Acids Res. 2018;46:D260–6.

30. Finak G, McDavid A, Yajima M, Deng J, Gersuk V, Shalek AK, et al. MAST: a

flexible statistical framework for assessing transcriptional changes and characterizing

heterogeneity in single-cell RNA sequencing data. Genome Biol. London: BioMed

Central; 2015;16:278.

31. Grant CE, Bailey TL, Noble WS. FIMO: scanning for occurrences of a given

motif. Bioinformatics. Oxford University Press; 2011;27:1017–8.

32. Quinlan AR, Hall IM. BEDTools: a flexible suite of utilities for comparing

genomic features. Bioinformatics. 2010;26.

33. Watson JD, Crick FHC. Molecular Structure of Nucleic Acids: A Structure for

Deoxyribose Nucleic Acid. Nature [Internet]. Nature Publishing Group;

1953;171:737. Available from: https://doi.org/10.1038/171737a0

34. Skinner ME, Uzilov A V, Stein LD, Mungall CJ, Holmes IH. JBrowse: a next-

generation genome browser. Genome Res [Internet]. Cold Spring Harbor Laboratory

Press; 2009;19:1630–8. Available from:

https://www.ncbi.nlm.nih.gov/pubmed/19570905

35. Yant SR, Zhu W, Millinoff D, Slightom JL, Goodman M, Gumucio DL. High

affinity YY1 binding motifs: identification of two core types (ACAT and CCAT) and

distribution of potential binding sites within the human beta globin cluster. Nucleic

Acids Res [Internet]. 1995;23:4353–62. Available from:

https://www.ncbi.nlm.nih.gov/pubmed/7501456

36. Basu A, Wilkinson FH, Colavita K, Fennelly C, Atchison ML. YY1 DNA binding

and interaction with YAF2 is essential for Polycomb recruitment. Nucleic Acids Res

[Internet]. 2013/11/26. Oxford University Press; 2014;42:2208–23. Available from:

https://www.ncbi.nlm.nih.gov/pubmed/24285299

37. Han GC, Vinayachandran V, Bataille AR, Park B, Chan-Salis KY, Keller CA, et

al. Genome-Wide Organization of GATA1 and TAL1 Determined at High

Resolution. Mol Cell Biol [Internet]. American Society for Microbiology;

2015;36:157–72. Available from: https://www.ncbi.nlm.nih.gov/pubmed/26503782

38. Nagy G, Czipa E, Steiner L, Nagy T, Pongor S, Nagy L, et al. Motif oriented

high-resolution analysis of ChIP-seq data reveals the topological order of CTCF and

cohesin proteins on DNA. BMC Genomics. 2016;17.

Fig. 1

Schematic overview of ChIP-seq data processing and imported content from MySQL. The analysis steps and data conversion are marked with thick arrows. The uploaded results/files are represented with dashed lines. A vast majority of processed data is available on ChIPSummitDB, including the predicted peak regions, optimized JASPAR CORE PWMs, identified TFBSs, and calculated protein position information.

	Experiment name	Antibody	Cell line	Element number
	hs_BreastCancer_T47D_cancer_FOXA1_SRX100454	FOXA1	T47D	53301
	hs_HepatocellularCarcinoma_HepG2_cancer_FOXA1_SRX100506	FOXA1	HEPG2	60468
	hs_VertebralCancerOfProstate_VCaP_cancer_FOXA1_SRX497612	FOXA1	VCAP	68559

Fig. 2

The distance distribution of FOXA1 summits relative to the motif centers of FOXA1

binding sites. The horizontal axis represents the distance of summits in different cell

lines (T47D (SRA ID: SRX100454, red curve), HepG2 (SRA ID: SRX100506 blue

curve) and VCaP (SRA ID: SRX497612, green curve)) relative to the FOXA1 motif

center. The vertical axis represents the distance frequencies. A rolling mean with a 5

bp window was applied to smooth the frequency curves. The distance between the

maxima (main summit, maxima at -3 bp) and the shoulder (7 bp) is approximately 10

bp. Element numbers in the table indicates the number of peak regions obtained in a

ChIP-seq experiment, which overlap with a particular consensus motif binding site set.

Fig. 3

Binding sites based analysis of topological arrangements of TF-DNA complexes as visualized in MotifView and PairShiftView. The plots show the preferred positions of different proteins on A) GATA1::TAL1 binding sites and on B) NFYB binding sites. The scatter plots display the average summit positions (X axis) of factors relative to the center of the binding sites (motif logos represented below the scatterplots with reference points which are marked as "0" position). The distances are measured in base pairs (bp). The standard deviation of summit- motif center distances are shown on the Y axis. Each dot represents a single ChIP-seq experiment. The histograms (at right) show the distribution of the summits relative to the midpoint (motif centers). The horizontal axis shows the distance from motif center, measured in base pairs. The vertical axis displays the distance frequency of summits at the given positions. Each ChIP-seq experiment is

represented by a frequency curve (A) GATA1:TAL1: blue - SRX386203, red -

SRX386202; B) NFYB: red - SRX037419, blue -SRX150508, and green -

SRX100471), which are smoothed with a rolling mean with a 5 bp window. Element

numbers in the tables indicates the number of peak regions obtained in a ChIP-seq

experiment, which overlap with a particular consensus motif binding site set.

Additional file 1. Supplementary notes and figures.

Figure S1: Schematic representation of the initial data processing. Processing starts

with data collection and proper naming. After processing and filtering steps, we get the

transcription factor binding sites in bed and bedgraph formats.

Figure S2: Summit prediction. Identification of local maxima within peak regions.

Figure S3: Peak filtering according to shape. (A) Peak with well-defined summit.

We filtered peaks depending on the symmetry of their two side (summit positions

serves as a symmetry axis) (B), the positions of the 2nd and 3rd quartiles (C), and the

symmetry between the read coverage of the two strands (D).

Figure S4: Pairing position weight matrices (PWMs) for processed ChIP-seq

experiments. (A) 2758 experiments could be paired to a proper JASPAR motif from

the downloaded and processed 3727 ChIP-seq experiments (B). This paired to 338

JASPAR CORE motifs from the 579 (C). The result was a table where the PWMs are

paired to their corresponding ChIP-seq experiments (D).

Figure S5: Motif optimization. JASPAR CORE motifs were optimized with the

findMotifsGenome program, which used the original PWMs and the merged peak

region set of corresponding ChIP-seq experiments (determined in the Motif- ChIP-seq

experiment pairing step).

Figure S6: Determining motif locations. To identify the location of motif instances,

we combined three different motif finding methods (MAST, HOMER, FIMO). The

merged peak region set of corresponding ChIP-seq experiments was used in the

identification (Figure 6A). To filter the identified motifs, we used the presented

formula in Figure 6B. In the case of overlapping motifs, the motif with the highest

Weighted Motif score was selected.

Figure S7: Measuring the distances between motif centers and the surrounding

summits. We calculated the concrete distance between motifs and the neighboring

summits (measured in base pairs). We took into account all of the possible summits

from every experiment.

Additional file 2. Summary table of the transcription factor motif, which has

identified instances in ChIPSummitDB. The table describes the following basic

information for the motifs:

1. column: Name of the motif

2. column: JASPAR record/ID

3. column: motifURL

4. column: Motif length

5. column: SRA antibody name paired to a motif

6. column: used ChIP-seq experiments in consensus motif creation

Additional file 3. Summary table of the ChIP-seq experiments. The table describes

the following basic information for the experiments:

1. column: name of the experiments

2. column: ftp address of SRA files

3. column: layout of experient (paired/single)

4. column: HTTP address of SRA record of ChIP-seq experiment

5. column: Link to SRA record

6. column: all identified peaks

7. column: filtered peak number

8. column: Transcription factor /cofactor + DNA binding motif

9. column: ExperimentView HTTP address

10. column: Link to ExperimentView