1   Humans can efficiently look for but not select multiple visual objects

3   Eduard Ort[1,2,*], Johannes J. Fahrenfort[1,2,3], Tuomas ten Cate[4], Martin Eimer[5], Christian N.L.
4   Olivers[1,2]

[1]Department of Experimental and Applied Psychology, Vrije Universiteit Amsterdam, 1081 BT
Amsterdam, Netherlands

[2]Institute for Brain and Behavior Amsterdam, 1081 BT Amsterdam, Netherlands

[3]Department of Brain and Cognition, University of Amsterdam, 1001 NK Amsterdam,
Netherlands

[4]Experimental Psychology, Utrecht University, 3584 CS Utrecht, Netherlands

[5]Department of Psychological Sciences, Birkbeck College, University of London, WC1E 7HX

London, UK

19   Author Note

20   *Corresponding author: E. Ort, Department of Experimental and Applied Psychology,

21   Institute for Brain and Behaviour, Vrije Universiteit Amsterdam, van der Boechorststraat 7,

22   1081 BT Amsterdam, The Netherlands. E-mail: eduardxort@gmail.com

23   **Abstract**

The human brain recurrently prioritizes task-relevant over task-irrelevant visual information. A

central, question is whether multiple objects can be prioritized simultaneously. To answer

this, we let observers search for two colored targets among distractors. Crucially, we

independently varied the number of target colors that observers anticipated, and the number

of target colors actually used to distinguish the targets in the display. This enabled us to

dissociate the preparation of selection mechanisms from the actual engagement of such

mechanisms. Multivariate classification of electroencephalographic activity allowed us to

track selection of each target separately across time. The results revealed only small neural

and behavioral costs associated with preparing for selecting two objects, but substantial

costs when engaging in selection. Further analyses suggest this cost is the consequence of

neural competition resulting in limited parallel processing, rather than a serial bottleneck. The

findings bridge diverging theoretical perspectives on capacity limitations of feature-based

attention.

Keywords: feature-based attention, visual search, attentional template, multiple targets, EEG,

MVPA

40   **Introduction**

Adaptive, goal-driven behavior demands the selection of relevant objects from the visual

environment while irrelevant information is being ignored. This requires the neural activation

of task-relevant representations in memory – often referred to as *attentional templates* –

which then bias selection towards matching sensory input through top-down recurrent

feedback loops (Duncan and Humphreys, 1989; Desimone and Duncan, 1995; Hamker,

2004; Eimer, 2014; Baldauf and Desimone, 2015). A fundamental yet unresolved question is

whether the brain can enhance multiple task-relevant representations concurrently – a

question that has recently generated considerable controversy, with arguments both for

(Houtkamp and Roelfsema, 2009; Menneer, Cave and Donnelly, 2009; Kristjánsson and

Campana, 2010; Dombrowe, Donk and Olivers, 2011; Olivers *et al.*, 2011; van Moorselaar,

Theeuwes and Olivers, 2014; Liu and Jigo, 2017; Ort, Fahrenfort and Olivers, 2017, 2018;

van Driel *et al.*, 2019) and against (Beck, Hollingworth and Luck, 2012; Irons, Folk and

Remington, 2012; Grubert and Eimer, 2015; Grubert, Carlisle and Eimer, 2016; Beck and

Hollingworth, 2017; Kristjánsson and Kristjánsson, 2017) a strong bottleneck.

55   We provide electrophysiological evidence showing that the real bottleneck is not so

much in the number of different templates that can be concurrently active in anticipation of a

visual task, but in the number of matching sensory representations in the incoming signal

that can subsequently be enhanced by those templates. Crucially, for the selection of

multiple targets to be truly simultaneous, two requirements have to be met. First, attentional

templates need to be set up in memory for each anticipated target feature (whether in visual

working memory [VWM] or through activating long-term memory [LTM] representations.

Although it is uncontroversial that multiple representations can be active in memory (whether

VWM or LTM; e.g., Cowan, 2001), in order to be able to bias selection, each of these

representations also needs to be in a state in which it can eventually engage, through

recurrent feedback, with matching sensory signals (which is not the same as merely

remembering; see Carlisle et al., 2011; Olivers and Eimer, 2011; Kiyonaga et al., 2012;

Chatham and Badre, 2015; van Driel et al., 2017). Second, to simultaneously select multiple

targets, the visual system must also be able to concurrently use those templates to

strengthen multiple matching representations in the incoming sensory signal. In other words,

multiple neural feedback loops must be able to engage concurrently. It is important to point

out that template activation and template-guided prioritization are distinct (cf., Huang and

Pashler, 2007): It may be that at any moment multiple templates are ready to potentially

engage in the prioritization of visual input, but that only one can actually do so following

visual stimulation. So far, studies of multiple-target selection have only focused on the brain's

limits in the readiness to engage in selection, and ignored potential limits in the selection

process itself.

To resolve this, we recorded electroencephalograms (EEG) from the scalp of healthy

human individuals while they were presented with heterogeneous visual search displays,

from which they always had to select two target objects (see Fig. 1A). Crucially, we varied

the number of unique target features (one or two colors) that the observer had to prepare for,

and the number of unique features that they would need to select from the search display.

This allowed us to disentangle the contribution of multiple template preparation on the one

hand, and multiple template engagement on the other. A bottleneck could either emerge

when going from one to two unique templates (reflecting a limit in the readiness to engage),

from one to two unique targets (reflecting a limit in the engagement itself), or both.

Traditionally, visual target selection is assessed using the N2pc, an event-related

potential (ERP) in the EEG signal that is characterized by increased negativity over posterior

electrodes contralateral to the hemifield in which the target is located (Luck and Hillyard,

1994; Eimer, 1996). However, because the N2pc can only distinguish between the left versus

right hemifield, it is not able to simultaneously track the selection of multiple targets at

different locations in more complex visual search displays. To overcome this limitation, we

used multivariate decoding, which has been proven to successfully track the spatiotemporal

dynamics of feature-based selection processes at any location in a search display

(Fahrenfort *et al.*, 2017). Here this technique allowed us to independently track attentional

selection over time for multiple concurrent targets at once, and also to investigate the parallel

versus serial nature of these selection processes.

98   **Results**

Twenty-four participants performed a visual search task for which they were always required

to find two color-defined target characters presented among an array of distractor characters,

and determine whether these two targets belonged to the same alphanumeric category (see

Fig. 1A,B). The task-relevant colors were cued prior to a block of trials. To assess if

prioritization of multiple targets is limited in terms of the number of attentional templates that

can be simultaneously set up, limited in the number of templates that can be simultaneously

engaged in the selection of target features in the display, or both, we independently

manipulated 1) how many colors were task-relevant and 2) how many of these target colors

actually appeared in the search display. Specifically, in *1TMP–1TGT* (one template, one

target feature) blocks, only one color was task-relevant, so that both targets had the same

color and thus participants knew beforehand which color template to prepare. In *2TMP–*

1TGT (two templates, one target feature) blocks, two unique colors were cued as task-

relevant, but per display only one of these was used to distinguish the two targets present

(i.e., both targets had the same color). Because participants could not predict which of the

two target colors would be present, they had to keep both templates active, even though only

one of them was then required for selecting the actual targets. Finally, in *2TMP–2TGT* (two

templates, two target features) blocks, again two unique colors were cued as task-relevant,

but now both these colors also had to be used to select the two target objects from the

search display, since one of the targets carried one color, and the other target carried the

other color. Note again that in all conditions, subjects had to select two targets, only the

number of target-defining features would vary across conditions. This controlled for other

task-related factors such as the number of characters that had to be identified and the

alphanumeric comparison that had to be performed on them.

Figure 1. Design and behavioral results. In all conditions, observers were required to select

two target characters and determine whether they were of the same (i.e., both letters or both

digits) or different category (i.e., letter and digit). (A) The target colors were cued once in the

beginning of a block and stayed constant for the rest of the block (64 trials). A trial started

with a fixation screen for a jittered interval of 850 to 950 ms, followed by the search display,

presented for 50 ms and another fixation screen that lasted for up to 2000 ms or until

participants responded. Depending on the response, feedback was presented for 500 ms

("correct", or "wrong"). If no response was given, a 10 second time out occurred and

participants were urged to try responding quicker. (B) Task design. Depending on the

condition, either one or two colors were cued to be task-relevant in the beginning of a block

(creating one vs. two unique templates). Similarly, whenever two colors were cued, search

displays could contain either one of them, or both (one vs. two unique target features). Thus,

in the one-template-one-target-feature condition *(1TMP–1TGT)* one color was cued, and

both targets carried this color in the search display, in the two-templates-one-target-feature

condition *(2TMP–1TGT)* two colors were cued but only one of these colors was present in

the search display with both targets carrying that color, and in the two-template-two-target-

feature condition *(2TMP–2TGT)* two colors were cued and both colors were present in the

search displays. One target always appeared on the horizontal meridian (above or below

fixation), and the other target on the vertical meridian (to the left or right of fixation). (C) and

(D) Behavioral results. The violin plots depict the distribution of (C) accuracy (see Figure 1 -

source data 1) and (D) response times (see Figure 1 - source data 2) across participants,

separately for the 1TMP–1TGT, 2TMP–1TGT, and 2TMP–2TGT conditions. The horizontal

lines in the box plots represent quartiles. The vertical line represents the minimum (lower

quartile - 1.5 * interquartile range) and maximum (upper quartile + 1.5 * interquartile range)

while single dots beyond that range indicate individual outliers.

Behavioral results

Fig. 1C and 1D show mean accuracy scores and mean response times (RTs) as a function

of experimental condition (1TMP–1TGT, 2TMP–1TGT, and 2TMP–2TGT). Performance

differences were assessed using pairwise, Bonferroni-corrected (to $\alpha = 0.025$) classical *t*-

tests and Bayesian *t*-tests on both measures. Any performance costs for the 2TMP–1TGT

relative to the 1TMP–1TGT condition reflect the cost of preparing for multiple templates

compared to a single template (*preparation cost*). Any performance cost in the 2TMP–2TGT

relative to the 2TMP–1TGT condition represents the cost of having to engage multiple

templates to select targets (*engagement cost*). We found evidence for both, with

engagement costs being most prominent. Specifically, there was an effect of the number of

templates on both accuracy and response times, with performance being reliably slower and

slightly more error-prone in the 2TMP–1TGT condition than in the 1TMP–1TGT condition

(RT: 731 ms vs. 679 ms, $t(23) = 5.03$, $p < .001$, *Cohen's d* = 0.64, *BF* = 572; accuracy:

95.4% vs. 96.5%, $t(23) = 2.76$, $p = .01$, *Cohen's d* = 0.61, *BF* = 4.4). Even stronger costs

were observed when the number of uniquely colored targets in the display was increased

from one to two, with performance being substantially slower and more error-prone) in the

2TMP–2TGT condition than in the 2TMP–1TGT condition (RT: 916 ms vs. 731 ms, $t(23) =$

9.05, $p < .001$, *Cohen's d* = 1.63, *BF* = 2.5×10^{6}; accuracy: 91.4% vs. 95.4%, $t(23) = 5.90$, p

$< .001$, *Cohen's d* = 1.48, *BF* = 3.9). Indeed, when we directly compared these two sources

of multiple-target cost to each other, the engagement cost was greater than the preparation

cost on both measures (accuracy: 4.0% vs. 1.2%, $t(23) = 3.36$, $p = .03$, *Cohen's d* = 1.03, *BF*

= 14.8; RT: 185 ms vs. 52 ms, $t(23) = 5.00$, $p < .001$, *Cohen's d* = 1.67, *BF* = 540).

Note further that in the 2TMP–1TGT condition, the actual target color in the display

could repeat or switch from trial to trial. Previous work has shown switch costs, in which

selection is slower after the target color changes from one trial to the next trial, compared to

when the target color stays the same (Maljkovic and Nakayama, 1994; Found and Müller,

1996; Monsell, 2003; Ort, Fahrenfort and Olivers, 2017, 2018). A closer analysis of the

current data also revealed that search suffered from switches, in terms of RTs (repeat trials:

M = 704 ms, switch trials: M = 754 ms; $t(23) = 8.1$, $p < .001$, *Cohen's d* = 0.56, $BF_{switchcosts} =$

4.2×10^{5}), and accuracy (repeat trials: M = 95.8%, switch trials: M = 94.9%; $t(23) = 2.7$, p

= .01, *Cohen's d* = 0.40, $BF_{switchcosts} = 4.0$).

The behavioral data thus reveal that multiple target search comes with costs, and that

these costs come in two forms. First, keeping two templates in mind results in relatively small

but reliable costs compared to keeping only one template. This effect is strongest when the

actual target color in the display has switched, suggesting a shift in weights on specific

templates from trial to trial. Second, considerably larger costs emerge when the observer not

only maintains two different templates, but also has to engage both of them in biasing

selection towards the two corresponding targets. Note that this is not the result of the number

of target objects *per se*, as participants had to select and compare two targets in all

conditions, but it is caused by the number of unique features defining these targets. Selecting

two objects by a single feature is thus more efficient and more accurate than selecting two

objects using two different features.

Decoding of target positions based on the raw EEG

Next, to determine whether the behavioral costs indeed reflected deficits in the selection of

the different targets, we used EEG to track the strength and dynamics of attentional

enhancement of the different target positions. To this end, one target was always placed on

the vertical meridian, and the other target always on the horizontal meridian, so that we could

train separate linear discriminant classifiers (with electrodes as features) for each of the

spatial target dimensions to distinguish left from right targets and top from bottom targets,

separately for each condition and time sample (see Methods for details). We reasoned that

any inefficiencies associated with setting up multiple unique templates (i.e., 1TMP vs. 2 TMP

conditions) and/or with actually using those templates to select multiple unique targets (i.e.,

1TGT vs. 2TGT conditions) should result in decoding to suffer in terms of relative delays,

strength, or both. Fig. 2A shows decoding performance for each of the conditions (1TMP–

1TGT, 2TMP–1TGT, and 2TMP–2TGT), separately for the horizontal (left versus right) and

vertical meridian (top versus bottom). Fig. 2B shows the topographical patterns associated

with the forward-transformed classifier weights over time, which are interpretable as neural

sources (see Haufe et al., 2014 and Methods). As a general finding, we were able to track

attentional selection on both the horizontal and vertical meridian, with comparable decoding

performance. Decoding performance was tested against chance for every sample, corrected

for multiple comparisons using cluster-based permutation testing (Maris and Oostenveld,

2007, also see Methods). After cluster-based permutation, we observed clear significant

clusters in each of the three conditions, with significant decoding emerging at different

moments in time. For the left-right distinction, the topographical pattern during the early time

window (200–350 ms) resembles that of the N2pc, while for later time windows (350–700

ms) it resembles SPCN or CDA-like patterns (Vogel and Machizawa, 2004; Mazza *et al.*,

2007; Grubert and Eimer, 2013). As shown in Figure 2 - Figure Supplement 1, more

traditional event-related analyses indeed revealed N2pc and SPCN components, which likely

contributed to the classifiers' performance. For vertically positioned targets a gradient from

frontal to posterior channels spread along the midline, similar to recent results from our labs

(Fahrenfort *et al.*, 2017; Grubert *et al.*, 2017). The fact that the decoding approach picks up

on information related to attentional selection also on the vertical midline is testament to its

power over conventional ERP methods, and allowed us to simultaneously track attentional

selection of both targets over time. However, as there were no main or interaction effects

involving the meridian in any of the comparisons, we averaged decoding performance across

the spatial dimensions.

Figure 2. MVPA decoding performance for target position. A) Decoding performance expressed as Area Under the Curve (AUC) for target position on the horizontal (left vs. right)

and on the vertical meridian (top vs. bottom) separately, as a function of number of templates

and number of target features. See also Figure 2 - source data 1 B) Topographical activation

maps for horizontal and vertical position decoding averaged over the typical N2pc time

window (200-350 ms) and the typical SPCN/CDA time window (350-700 ms). C) Decoding

performance collapsed across the horizontal and vertical dimensions, comparing the 1TMP–

1TGT and 2TMP–1TGT conditions, with the difference score thus showing the effect of the

number of templates. See also Figure 2 - source data 2. D) The same, now comparing the

2TMP–1TGT and 2TMP–2TGT conditions, thus showing the effect of multiple different target

features in the display. See also Figure 2 - source data 2. The shaded area represents 1

SEM above and below the mean for every time point. Thick lines as well as horizontal bars

indicate significant clusters (at α = .05) as produced by cluster-based permutation testing

(5000 permutations). For visualization purposes only, the classification scores over time were

fitted with a cubic spline (λ=15, comparable to a 30 Hz low-pass filter) to achieve temporal

smoothing. Note the statistical analyses and estimation of the onset latencies were done on

unsmoothed data. The marked time points indicate the latency of 50% maximum amplitude

as estimated using a jackknife approach, as a measure of the onset of selection (Miller,

Patterson and Ulrich, 1998; Luck, 2014; Liesefeld, 2018). The zero points on the x-axis of

panels A,C and D represent search display onset.

If there is a limit on how many templates can be prepared for, we should find reduced

and/or delayed classification for the 2TMP–1TGT condition compared to the 1TMP–1TGT

condition (Fig. 2C). If the limitation is on how many templates can be engaged in selection,

the cost should emerge in the comparison of the 2TMP–2TGT and 2TMP–1TGT conditions

(Fig. 2D). Indeed, we observed reliable differences for both comparisons that directly

resembled the behavioral pattern. First, we compared the latencies at which target positions

became decodable, thus providing a window on any delays in attentional selection. Because

differences in onset of significant clusters cannot be reliably interpreted as reflecting

differences in onsets of the underlying neurophysiological processes (Sassenhagen and

Draschkow, 2019), we instead used a jackknife-based approach to quantify the latency of the

50% maximum amplitude in the decoding window (Miller, Patterson and Ulrich, 1998; Luck,

2014; Liesefeld, 2018, see Methods). This revealed a reliable onset difference between the

1TMP–1TGT (M = 216 ms) and 2TMP–1TGT (M = 237 ms) conditions (M = 21 ms, $t_c(23)$ =

2.21, p = .04; Fig. 2C), indicating that attentional selection is delayed as a result of having to

prepare for two different target colors compared to having to prepare for only a single target

color. Comparing the onsets between the 2TMP–1TGT (M = 237 ms) and 2TMP–2TGT (M =

263 ms) conditions yielded a further delay of 25 ms associated with having to engage in

selecting two target colors compared to selecting a single target color ($t_c(23)$ = 2.35, p = .03;

Fig. 2D).

Finally, and also similar to the behavioral responses, the onset of the

neurophysiological response in the 2TMP–1TGT condition was delayed by 23 ms when the

target color switched from one trial to the next, compared to when it repeated ($t_c(23) = 4.34$, p

< .001; see Figure 2 - Figure Supplement 2).

Next, we assessed the strength of classification over time by testing AUC values of

the relevant conditions against each other using paired *t*-tests and cluster-based permutation

testing to correct for multiple comparisons (see Methods). This procedure revealed an early

and short-lasting difference of the number of templates (i.e., between 1TMP–1TGT and

2TMP–1TGT conditions; see Fig. 2C), with stronger classification for the single template

condition that reflects the onset latency difference reported above. Again, in line with the

behavioral results, more substantial cost in decoding performance emerged when the

number of target features in the displays increased from one to two (i.e., between the 2TMP–

2TGT and 2TMP–1TGT conditions; see Fig. 2D). To directly compare the cost of preparing

two templates to the cost of engaging them in selection, we also ran a cluster-based

permutation test on the difference scores (i.e [2TMP–1TGT – 2TMP–2TGT] – [1TMP–1TGT

– 2TMP–1TGT]). This revealed a window of 250 to 500 ms post stimulus in which the cost of

engaging was greater than the cost of preparing selection (first cluster: extent: 266 - 378 ms,

p = .001; second cluster: extent: 436 - 495 ms, *p* = .013, results not shown in Figure). This

suggests that generally engaging two templates is more costly than preparing two templates.

Thus, both the onset latency and strength of decoding performance show clear

deficits in attentional selection when observers need to select two different targets from a

display (i.e., engage two templates in selection) compared to when they have to select two

targets based on the same target color (i.e., engage one template in selection). In contrast,

having to set up two templates instead of one came with only minor onset latency differences

and no overall differences in decoding strength. This clearly points to a deficit when multiple

templates need to be engaged simultaneously rather than when multiple templates need to

be prepared simultaneously.

Sample-wise correlation of classifier confidence across trials as a measure of inter-

target dependency

While the previous section showed a clear impairment when two templates need to be

engaged in selection, it leaves unanswered whether selection is hindered by limitations in

parallel processing or by a serial bottleneck. That is, engaging two templates during search

may prioritize both unique targets in parallel but in a mutually competitive manner (Barrett

and Zobay, 2014), or the two templates may only be engaged (and thus the corresponding

targets prioritized) sequentially, possibly in continuously alternating fashion (e.g., Ort,

Fahrenfort and Olivers, 2017).

To investigate these competing hypotheses, we assessed performance for each

target dimension separately (horizontal and vertical). A serial model predicts that attention to

a target on one dimension should go at the expense of attention to the target on the other

dimension, and thus decoding performance for the vertical and horizontal axes to correlate

negatively. In case of parallel, independent selection, there should be no systematic

relationship between classification confidence for one dimension and classification

confidence for the other dimension, as selection of one target is impervious to the selection

of the other target. A positive correlation would arise from a common mechanism driving

selection of two different targets. Note that these possibilities are difficult to assess at the

group level as individuals may have different serial strategies. For example, one observer

may prefer to first select targets from the horizontal axis, while another may prefer the

vertical axis first, such that any existing correlation (if present) might cancel out. Hence, we

first plotted average performance over time separately for each individual and separately for

the horizontal and vertical axis. Then, to reveal whether consistent temporal dependencies

existed for any given participant, we correlated classification performance over time in the

150 ms to 700 ms post stimulus window. Although this revealed incidental positive and

negative correlations for individual participants, there was no systematically positive or

negative relationship (average correlation Spearman's ρ = 0.11; min-max range: -0.37-0.63;

see Figure 3 - Figure Supplement 1).

However, even individual participants themselves may not behave consistently across

trials, and, while selection is still serial, whether participants first prioritize horizontal or

vertical targets may also vary from trial to trial. Therefore, selection needs to be assessed at

the trial level. To this end, for every participant, trial and time point, we extracted the

classifier confidence scores separately for the horizontal and vertical dimension (see Ritchie

and Carlson, 2016; Grootswagers, Cichy and Carlson, 2018 and Methods), and correlated

the two dimensions across trials using Spearman's ρ. Classifier confidence, expressed as

the distance from the decision boundary, reflects the certainty of a classifier in predicting the

class membership of a certain instance. In the present design, classifiers predicted based on

the specific EEG activity pattern across electrodes on a given trial whether one target

appeared on the left or right and whether the other target appeared at the top or bottom

position. The confidence scores indicate how certain the classifiers were that a target

appeared at a particular position. We reasoned that if prioritization is limited to a single target

at a time, a classifier cannot simultaneously have high confidence about both targets, and

thus confidence should correlate negatively, that is if the horizontal target position can be

predicted with high confidence, then the confidence for the vertical target position should be

reduced and vice versa. The correlations between the confidence scores on the two spatial

dimensions are plotted in Fig. 3A. As can be seen, there was again no systematic

relationship between decoding the locations of the two targets, in any of the conditions. Apart

from a short-lasting positive correlation around the 500 ms time point in the 2TMP–2TG

condition which is likely to be spurious, correlations for all time points were close to zero,

which implies that classifying horizontal and vertical target positions is independent from

each other.

However, given that this is a null result, we sought to make sure that our approach is

in principle sensitive to existing correlations. To this end, we simulated a data set with the

same overall characteristics as the recorded data, but with either positive, negative, or no

correlations injected, under various signal to noise ratios (see Methods). The results of this

simulation are summarized in Figure 3 - Figure Supplement 2 and demonstrate that with

sufficiently high decoding AUC values (> approx. 0.55-0.60), correlations (whether positive or

negative) between the horizontal and vertical position classifiers can, in principle, be reliably

detected. However, because group classification performance in our dataset did not exceed

0.59 (in the 1TMP–1TGT condition), we instead assessed for each individual observer the

correlation between target dimensions for those time points at which classification

performance reached its maximum. As Fig. 3B shows, even for individuals with relatively

high classification scores, there was no evidence for a correlation between the classification

confidence between the two target dimensions. The absence of such a correlation in our data

is thus most consistent with a limited parallel independent selection model, rather than a

serial model or a parallel model operating under a common mechanism.

Nevertheless, there is the possibility that there was actually a relationship between

horizontal and vertical classification, but across time, trials, or both it was too short and

inconsistent such that the present approach might not have been sensitive enough to detect

it. For example, a negative correlation might exist for a short time window of which the timing

shifted across trials, causing the resulting average correlation might to be reduced beyond

detectability. We emphasize that the conclusion that our data are mostly consistent with a

limited parallel model is thus based on a null result and therefore has to be interpreted with

care.

Figure 3. Correlation of classifier confidence scores. A) For each condition, and trial, the

classification confidence scores per time point and subject were extracted for horizontal and

vertical classifiers and then correlated (Spearman's ρ) between these dimensions, across

trials. B) To examine whether a non-zero correlation would be present for individuals who

show high AUC scores, we plotted the individual correlation scores for those time points at

which individual classification was maximal, separately for the horizontal dimension (less

saturated dots) and the vertical dimension (more saturated dots). The curves represent the

correlation strengths that can be expected for a certain decoding strength (AUC,

corresponding to SNR) as based on our simulated data set (the simulated negative

correlation being the mirrored version of the positive correlation).

385   **Discussion**

Selection of task-relevant information from complex visual environments is limited, and a

central question in attention research has been whether observers can simultaneously

prepare for and select multiple different target objects. The current results provide evidence

that these limitations do not so much reside at the level of template preparation (i.e., the

number of target representations set up prior to the task), but at the extent to which

templates can then be concurrently engaged in selecting matching information from the

sensory input. By systematically varying not only the number of different target features

observers had to prepare for, but also the number of different target features they would

encounter in the displays, we were able to, for the first time, dissociate limitations in template

preparation from limitations in template engagement. Specifically, we observed relatively

small but reliable costs on both behavioral and EEG classification performance when two

templates needed to be activated instead of one, suggesting a reliable but relatively minor

bottleneck at this stage of processing. In contrast, substantial costs emerged on both

behavioral and EEG performance measures when two templates had to be prepared, and

both of these templates (rather than just one) had to be engaged in driving the selection of

two different targets.

We propose a model which extends existing frameworks that assume a crucial role

for top-down biased competition (Duncan and Humphreys, 1989; Desimone and Duncan,

1995; Hamker, 2004; Bundesen, Habekost and Kyllingsbæk, 2005). According to these

frameworks, the activation of target templates in memory involves the pre-activation or

biasing of associated sensory features. The presence of such features in the input will then

trigger a long-range recurrent feedback loop, leading the enhancement of the target

representation in VWM (including its location), and thus making it available for other cognitive

processes such as response selection (processes which are themselves limited, cf.

Dehaene, Kerszberg and Changeux, 1998; Lamme, 2003; Baars, 2005). Our data indicates

that while multiple top-down feedback connections may be prepared at once, there is a

limitation in how these feedback loops are engaged by matching input.

Figure 4 illustrates how we believe the existing framework should be extended.

Specifically, we propose that multiple templates may hold each other in a mutually

competitive relationship in memory, most likely through laterally suppressive connections

(Manohar *et al.,* 2019). Figure 4A depicts the situation when just one of the target features is

then encountered in the sensory input. The corresponding feedback loop is triggered, leading

to an enhanced representation of that target. If only one target feature is present, the

corresponding template will automatically win the competition. Although two templates can

be maintained in parallel, the mutual competition between them is slightly disadvantageous.

This will lead to the initial delay in target selection that we observed in the data when two

templates instead of just one were activated. Moreover, the selective enhancement of one

representation over another may carry over to the next trial, thus resulting in the target switch

costs that we also observed both in behavior and EEG performance measures.

The crucial situation occurs when the visual input contains multiple target features

and thus multiple feedback loops are being triggered, as is shown in Figure 4B. Because of

the mutually suppressive relationship, strengthening one feedback loop will automatically go

at the expense of the other. Although both loops are triggered in parallel, the mutually

aversive relationship results in slower and weaker accumulation of evidence for either of the

targets, consistent with what we observed in the data. In theory, the system may resolve

such competition in two ways. The first is to keep selection of both targets running in parallel,

and accept the slower evidence accumulation. The second option is to impose a serial

strategy in which selection is first biased in favor of one target, and then switched to the other

(or alternate between the two). Our data provides no evidence for the serial model. First, the

average group data nor the average individual subject data showed any systematic pattern of

switching between the two target positions (i.e., differences in classification performance for

left-right versus top-bottom). Second, also a trial-based correlation analysis of classifier

confidence scores showed the absence of a negative correlation between the target

positions. Our findings are therefore most consistent with a limited-capacity parallel model, in

which observers maintain two templates active during search, but with mutually aversive

consequences. However, we point out that our data do not exclude the possibility of seriality.

First, while there may have been little seriality in selecting the targets from the displays on

the basis of color, there may have been a serial component in accessing their alphanumeric

identity – a component to which our classifier was not sensitive. Moreover, there is still a

distinct possibility that imposing seriality is a valid strategy that observers may deploy to

resolve competition between different target features, but that such choices depend on tasks,

context, or instructions (Cave *et al.*, 2018; Stroud *et al.*, 2019). For example, we previously

observed evidence for serial switching in a different paradigm when observers had to select

only one of two targets present, and were instructed to switch at least a few times during a

block (Ort *et al.*, 2019; van Driel *et al.*, 2019). The current results indicate that the process

can occur in parallel, not that it must.

Figure 4. A limited parallel model. Attentional templates in memory engage in recurrent

feedback loops with matching sensory representations, resulting in target enhancement.

Multiple templates can be activated in parallel and may be equally active prior to search, but

they compete through mutual suppression, which has consequences during search. (A) The

presence of a single target feature in the sensory input will unequivocally trigger one of the

active templates, eventually resulting in as strong selection as when there is only one

template (not shown), albeit at a short delay. (B) When both templates are activated the

mutual suppression will prevent strong activation of either, resulting in substantially

weakened and delayed selection of both targets.

Our account has a resemblance to the Boolean Map Theory of Visual Attention

(Huang & Pashler, 2007), which proposes a division of attentional selection into two

components: (1) The feature-to-location routine, in which task-relevant features are being

located in the visual field (referred to by Huang and Pashler as *selection,* but here analogous

to what we call preparation for selection) and (2) the location-to-feature routine in which

individuals extract response-relevant features at a target location (*access*, analogous to what

we here call engagement in selection). However, in contrast to the model that we propose, in

which only what Huang and Pashler refer to as the access aspect of search is severely

limited, the Boolean Map theory poses a capacity limitation of one on both selection *and*

access.

We believe the distinction between template preparation and template engagement in

selection has great potential for resolving the current debate on whether observers can look

for more than a single target at the same time (Menneer, Cave and Donnelly, 2009; Beck,

Hollingworth and Luck, 2012; Irons, Folk and Remington, 2012; Grubert and Eimer, 2015;

Beck and Hollingworth, 2017; Ort, Fahrenfort and Olivers, 2017, 2018). Studies central to this

debate have largely focused on how many templates can be prepared in anticipation for a

search, rather than how many of these templates can then be concurrently engaged in

selection without costs. From our data, the answer to the question then appears to be yes,

observers may *look* for multiple targets simultaneously at little cost, but it is *selecting* those

targets that runs into real limitations.

Although we found the costs of going from one to two templates to be relatively small,

this leaves open the question whether costs will increase more strongly with more templates

being added. As there is more opportunity for memory representations to interfere with each

other when multiple memory representations need to be maintained, this would be expected.

Such interference will depend on the similarity of the to-be-remembered templates, as well

as the assumed capacity. Although the capacity of VWM is thought to be around three to four

items (at least for the standard colored shapes used in experiments like ours), and VWM is

assumed to be central to top-down driven search, there is ample evidence that visual search

needs not solely rely on VWM. In fact, given that in our experiment the target template

remained the same for a block of trials, observers may have at least partly relied on trained

templates in long term memory here (Carlisle et al., 2011; Gunseli, Meeter, & Olivers, 2014).

Moreover, work by Wolfe (2012) has shown that observers can successfully search for any

one of tens of different target objects if given the opportunity to first commit these objects to

long term memory. In fact, given that in our experiment the target template remained the

same for a block of trials, observers may have at least partly relied on long term memory

here, too (but see Grubert, Carlisle and Eimer, 2016 for evidence that measures of

attentional selection, i.e., the N2pc, are not affected by whether targets are stored in long

term memory or working memory). In our study, effects of capacity limits and any

interference arising from it may be have been stronger when the targets would have been

cued from trial to trial, rather than from block to block. Conversely, the fact that we find

limitations even with repeated targets is testament to the mechanistic bottleneck in the

engagement of selection that we propose. One reason may be that even LTM

representations would need to become activated for effective task-or context-driven guidance

(since only one set of trained colors is relevant in a particular block). Our data suggests that

the limit may well be in this goal-driven aspect of search – that is, the deployment of a

representation for perceptual bias rather than its storage per se. In line with this, Grubert,

Carlisle and Eimer (2016) reported evidence that attentional selection per se, as measured

by the N2pc (which at least partly underlies the signal also used here), is not affected by

whether targets are stored in long term memory or working memory. Future research will

need to shed further light which memory systems support search templates.

Finally, the question of memory capacity or interference is also important when

considering that current limitations were found when both target features were drawn from

the same dimension (color). There is evidence that different dimensions may to some extent

independently store (e.g., Wang *et al.*, 2017), or guide attention towards (Wolfe, 1994;

Jenkins, Grubert and Eimer, 2017), target features. Our methods may therefore prove useful

in assessing the exact limitations of selecting targets defined along different dimensions.

To sum up, we propose that models of visual selection need to consider the

difference between preparing for selection and engaging in selection of multiple visual

targets. We demonstrate that whereas the first process comes at little cost, the true

bottleneck of multiple-target selection is in engaging multiple template representations.

Declaration of Interest

The authors declare no competing interests.

Materials and Methods

Materials Availability All data and material will be made freely accessible at

https://osf.io/3bn64

Participants. Thirty-two participants naive to the purpose of the experiment were

recruited at the Vrije Universiteit Amsterdam and were compensated with money or course

credit. Eight were excluded due to poor behavioural performance in at least one experimental

condition (a predefined cutoff of accuracy <85% was used, see below) to ensure sufficient

numbers of correct trials for the EEG analyses. The remaining twenty-four participants (age:

19-30 years, M = 22.0; 17 females, 7 males) had normal or corrected-to-normal visual acuity

and color vision. All participants gave written informed consent in line with the Declaration of

Helsinki. The study was approved by the Scientific and Ethics Review Board of the Faculty of

Behavioural and Movement Sciences at the Vrije Universiteit Amsterdam (Reference

number: VCWE-2016-215).

Stimuli & Procedure. Displays consisted of eight colored alphanumerical characters

evenly spaced on an imaginary annulus with a radius of 2.5 degree visual angle (dva),

centered at the middle of the screen (Fig. 1A). The characters were uppercase letters (K, H,

M and T) and digits (7, 6, 3 and 4, each spanning approximately 1.2 dva vertically and

between 0.8 and 1.0 dva horizontally. In total, eight colors were used in the experiment: Red

(RGB-values: 224, 0, 38), green (0, 155, 0), blue (55, 110, 255), and yellow (160, 95, 5) were

potential target colors (all approximately isoluminant, ~21 cd/m^2, min-max range: 19-25 cd/

m^2), whereas purple (145, 30, 180), cyan (70, 240, 240), pink (250, 0, 179) and gray (130,

130, 130) were always used as distractor colors (M = 35 cd/m^2, min-max range: 16-63 cd/

m^2). The stimuli were presented on a black background (0, 0, 0).

Participants were instructed to find two color-defined target characters on each trial,

and indicate whether or not these belonged to the same alphanumerical category (i.e., letters

or numbers). Response keys were counterbalanced across participants. In the beginning of a

block, the task-relevant colors were shown to the participants as two target-colored disks

(spanning 1.2 dva each), for 2000 ms. Depending on the experimental condition (see below)

either one colored disk was presented in the middle of the screen, or 1.0 dva to the left and

right of the center, respectively. The target colors were valid for a block of 64 trials after

which new colors were shown. Throughout the trial a white fixation cross remained visible in

the middle of the screen which participants were required to keep fixating. The trial sequence

began with a fixation screen presented for 850 to 950 ms (randomly selected from a uniform

distribution), followed by a search display for 50 ms and another fixation screen until a

response was given or a 2000 ms timeout. Finally, a written message ("correct" or "wrong")

presented for 500 ms indicated whether the response was correct or not. In case participants

did not respond before the timeout, the experiment was paused for ten seconds to

encourage them to respond quicker henceforth. After every block, participants received

feedback on accuracy. Note that for the first two participants presentation time was two

display frames (~16.67 ms) shorter than for the rest of the sample. To facilitate good

behavioral performance, we increased presentation time from the third participant onwards.

However, as these two participants performed well, even with 16.7 ms presentation rates

(and thus met our inclusion criteria), we decided to keep them in the sample.

One target color was always presented on the horizontal axis (left or right of fixation),

while the other was always presented on the vertical axis (above or below fixation), with

color-position assignment randomly chosen but occurring equally often. Participants were

informed that targets would appear only on the cardinal axes of the search array. The

irrelevant items on the diagonals were added to the search display to increase competition,

increase color heterogeneity, and to prevent participants from looking for any color duplicates

rather than for the specific target color, whenever both target objects of a search array

shared the same color (as was the case in the one target feature conditions). To further

prevent participants from employing the strategy of selecting color duplicates or groups,

rather than setting up a template for the specific target color, one half of all trials, one of the

additional distractor colors was duplicated and presented at one of the diagonal positions. In

doing so, the mere presence of a duplicated color would not signal these to be the target

items, so that a color-specific would be necessary to perform the task efficiently. One target

color was always presented on the horizontal axis (left or right of fixation), while the other

was always presented on the vertical axis (above or below fixation), with color-position

assignment randomly chosen but occurring equally often. The alphanumerical identity of

each search item was chosen randomly with the restriction that the two target objects

belonged as often to the same category (both letters or both digits) as to different categories

(one letter and one digit). Consequently, alphanumerical category and positions of both

targets were fully counterbalanced within a block.

Design. Across blocks, we introduced three experimental conditions that differed in

(1) how many colors were task-relevant (i.e., the number of templates, TMP) and (2) how

many target colors appeared in a single search display (i.e., the number of different target

features, TGT). In *1TMP–1TGT* blocks, only one color was task-relevant, so that both target

characters had the same color and participants knew beforehand which color they would

need to select. In the *2TMP–1TGT* block type, two colors were cued as task-relevant, but

only one of the two target colors would actually appear in a search display, as was randomly

determined from trial to trial (with equal numbers for each target color). Participants could not

predict which of the two target colors would be present in a specific search display, therefore

they had to keep two templates active, even though only a single color was required for

selecting the actual targets. Finally, in the *2TMP–2TGT* block type, again two colors were

cued as task-relevant, but now both these target colors also appeared in each search

display, so that both colors were required for selection. Each condition was repeated eight

consecutive times.

We decided to use a blocked design rather than intermixing trials of all three

conditions within blocks because pilot data indicated that behavioral performance is rather

low if conditions are mixed within a block, so that many trials would have to be excluded.

Furthermore, intermixing conditions would also make it necessary to cue not only the

condition, but also the task-relevant colors before every trial. This would have increased the

duration of a trial, and hence reduced the total number of trials that we could fit in a session,

thus reducing power even more.

When only one color was task-relevant (1TMP–1TGT), each of the four colors would

thus serve as the target color twice, whereas in blocks in which two colors were task-relevant

(2TMP–1TGT and 2TMP–2TGT), observers would look for the combinations red and green

or blue and yellow, each four times. We chose these color combinations as they are not

linearly separable in color space and thus prevented participants from potentially setting up a

single template encompassing both target features. The order of conditions was

counterbalanced across participants. Prior to the start of the experiment, participants

received instructions and practiced all conditions in increasing order of difficulty (1TMP–

1TGT, 2TMP–1TGT, 2TMP–2TGT). During practice, participants repeated blocks of 32 trials

for each condition as often as necessary to reach an accuracy of 85%, but at least three

times. Note, even if participants had initially reached this inclusion criterion, they might still

have performed below 85% during the experiment. Therefore, eight participants with an

accuracy below 85% were excluded from the analysis.

Apparatus & EEG Acquisition. The experiment was designed and run using the

OpenSesame software package (version 3.2.2; Mathôt, Schreij and Theeuwes, 2012).

Stimuli were presented on a 22-inch Samsung Syncmaster 2233 monitor, with a resolution of

1680 x 1050 pixels at a refresh rate of 120 Hz. Participants were seated in a dimly lit, sound-

attenuated room in a distance from the screen of approximately 70 cm and the eyes aligned

with the center of the screen. A QWERTY PS/2 keyboard was placed in the lap of each

participant. They were instructed to place left and right index fingers on the *z* and *m* keys to

indicate whether targets were of the same or different category. Further, they were asked to

refrain from excessive blinking and motion during the experiment. The experimenter received

real-time feedback on behavioral performance and quality of EEG recording in an adjacent

room.

We used the BioSemi ActiveTwo system (Biosemi, Amsterdam, The Netherlands) to

record from 64 AG/AgCl EEG channels, four EOG channels and two reference channels at a

sampling rate of 512 Hz. EEG channels were placed according to the 10-20 system. EOG

channels were placed one cm outside the external canthi of each eye to measure horizontal

eye movements and two cm above and below the right eye, respectively to measure vertical

eye movements and blinks. Reference electrodes were placed on the left and right mastoids.

EEG Preprocessing. All EEG preprocessing and analyses were performed offline in

Matlab (2014b, The Mathworks) and Python (2.7, www.python.org), using a combination of

EEGLAB (Delorme and Makeig, 2004), the Amsterdam Decoding And Modeling toolbox

(ADAM, version: 1.07-beta, (Fahrenfort *et al.*, 2018) and custom scripts (freely accessible at

https://osf.io/3bn64). EEG data were first re-referenced to the average of the left and right

mastoids. No offline filters were applied to the data. Next, the continuous signal was split into

epochs from 300 ms before until 800 ms after search display onset. Epochs were baseline

corrected by removing the average activity in a pre-stimulus window between -100 and 0 ms

from each time point. All epochs in which participants failed to respond correctly, or response

times were lower than 200 ms (anticipatory errors) or greater than three standard deviations

above the block mean were removed from further analyses (mean exclusion: 6.6%, min-max

range across participants: 4.4% - 9.7%). To make sure that the EEG would not be

contaminated by eye movements, we scanned epochs for horizontal eye movements within

the first 500 ms after stimulus onset (amplitude threshold: 30 µV, window length: 100 ms,

step size: 50 ms) and removed epochs containing such. This resulted in an exclusion of on

average 2.4% (min-max range: 0.0% - 16.8%) of all epochs. Noise due to muscle activity

was removed using an automatic trial-rejection procedure. To specifically capture EMG, we

used a 110 - 140 Hz band-pass filter, and allowed for variable z-score cut-offs per participant

based on the within-subject variance of z-scores, resulting in the exclusion of on average

7.1% (min-max range: 1.8% - 13.1%). Next, all epochs were visually inspected for any

obviously contaminated trials that have been missed by the automatic trial-rejection

procedure (mean exclusion: 0.4%, min-max range: 0.0% - 0.9%). To identify and remove

components related to blinks, we used EEGLAB's implementation of independent component

analysis (ICA). In total, 15.6% (min-max range: 8.1% - 34.2%) of all epochs were removed

during preprocessing.

Decoding of Target Locations*.* The main analyses decoded target positions based

on the raw EEG of all 64 channels, using the ADAM toolbox (Fahrenfort *et al.*, 2018). To that

end, we used a 10-fold cross-validation scheme by splitting the data of individual participants

into ten equal-sized folds after randomizing the order in which trials occurred in the

experiment. A linear discriminant classifier was then trained on the data of nine folds and

tested on the data of the tenth one. This procedure was repeated ten times until each fold

served as a test set once. Finally, the classifier performance was averaged across all

individual folds. For each condition, we trained one classifier to differentiate trials on which

one of the targets was presented on the left versus the right position, and another classifier

to differentiate the same trials as to whether the other target was presented on the top versus

the bottom position. Furthermore, to account for minor incidental imbalances with respect to

the trial count per class introduced by the trial rejection procedure, we performed within-class

and between-class balancing. For within-class balancing, we undersampled trials to match

the number of trials in which the target appeared on the irrelevant dimension within each

class. For example, when training a classifier to differentiate trials in which the target

appeared on the left versus right position, we made sure that each class (e.g., left targets)

contained the same number of trials in which the second target appeared on the top or the

bottom position by removing trials of the more frequent trial type. Between-class balancing

entailed the oversampling of trials (generating synthetic samples based on the existing data;

see He et al., 2008) belonging to the less frequent class, so that the classifier would not

become biased toward the more frequent class. As performance measure we used the Area

Under the Curve (AUC, Hand and Till, 2001), which is an unbiased measure that is based in

signal detection theory and describes the area under the receiver-operator curve when

plotting hit rate over false alarm rate. The decoding performance for single conditions was

statistically tested against chance level (AUC = 0.5) by running two-sided one-sample t-tests

across participants for every time point, or by testing AUCs against each other when

comparing conditions directly. To correct for multiple comparisons, we used cluster-based

permutation tests (5000 permutations) on adjacent time points with the alpha level set to α

= .05 (Maris and Oostenveld, 2007). Next, to examine the topography of the activations, we

multiplied the classifier weights across all channels with the data covariance matrix, yielding

activation maps that can directly be interpreted as neural sources (Haufe *et al.*, 2014).

Estimating and Statistically Testing Onset Latency and Amplitude Difference To

estimate the onset latencies at which target location became decodable, we used an

approach in which we combined computing the fractional peak latency with a jackknife-based

approach (Miller, Patterson and Ulrich, 1998; Luck, 2014; Liesefeld, 2018). Group-averaged

classification scores were repeatedly computed over all but one participant, until each

participant was left out once. For each of these averages, we estimated its onset latency by

identifying the peak amplitude in the window of 150 to 700 ms after search display onset and

defined the onset as the first point in that time window in which the classification scores

exceeded 50% of the peak score. To mitigate the influence of high-frequency noise on the

latency estimation, for every time point we averaged the amplitude of that time point and the

two adjacent time points for peak and onset latency estimation. To statistically test for

potential differences in onset latencies across experimental conditions, we followed Miller et

al. (1998) and computed *t*-statistics for the pairwise comparisons between the 1TMP–1TGT

and 2TMP–1TGT condition, and between the 2TMP–1TGT and 2TMP–2TGT condition. The

procedure corrects for the artificially reduced error term due to the jackknifing by effectively

dividing the *t*-statistic by the degrees of freedom.

Finally, the 2TMP–1TGT condition (when two target colors were cued but only one of

them was present in any one search display) allowed us to asses intertrial switch costs

(Maljkovic and Nakayama, 1994; Olivers and Humphreys, 2003; Wolfe *et al.*, 2004;

Dombrowe, Donk and Olivers, 2011; Ort, Fahrenfort and Olivers, 2017), by splitting the

2TMP–1TGT condition into repeat and switch trials and to run all analyses separately for

these two trial types.

N2pc analysis Even though the backward decoding approach would already show

whether and when location-specific information would be present in the raw EEG, for the

sake of comparison to the existing N2pc literature, we also conducted a more common

event-related potential (ERP) analysis to examine latency and amplitude of the N2pc

component. First, to identify N2pc components, we computed ERPs locked to stimulus onset

at electrodes PO7 and PO8. ERPs at the ipsilateral electrode relative to the horizontal target

position (i.e., PO7 for targets on the left, PO8 for targets on the right), were subtracted from

ERPs at the contralateral electrode, collapsed over the vertical target position, but separately

for each participant and condition. The resulting difference wave forms were then statistically

tested against zero with two-sided one-sample *t*-tests at each time point. A cluster-based

permutation test (5000 permutations, α = .05) was performed on contiguous time points to

correct for multiple comparisons (Maris and Oostenveld, 2007). To quantify amplitudes and

onset latency the same approach as for the classification scores was used, with the

exception that we did not use the entire epoch when looking for the peak, but only the

window of 200 – 350 ms post stimulus, as this is the time window in which the N2pc is

typically observed (e.g., Eimer, 1996; Eimer and Grubert, 2014)

Correlating classification confidence*.* Another useful feature of the AUC measure

is that it considers the confidence that a classifier has about class membership of a particular

instance at every time point. Confidence is expressed as the distance from the decision

boundary and can be interpreted as the representativeness of a certain instance (EEG

activity across all channels for a given time point) of that class (Ritchie and Carlson, 2016;

Grootswagers, Cichy and Carlson, 2018). Applied to the present paradigm, we assumed that

the more strongly prioritized a particular target position, the higher the classifier's confidence

scores. Based on this logic, we reasoned that if prioritization is limited to a single target at a

time, a classifier cannot simultaneously have high confidence about both targets, and thus

confidence should correlate negatively. To test this hypothesis, we extracted the confidence

scores of both classifiers (left-right and top-bottom) and correlated these across trials

(Spearman's ρ), separately for each time point and condition. If prioritization is limited to a

single item for certain time points, we would expect a moderately negative correlation

between left-right and top-bottom classifiers for those points, because whenever the

classifier has high confidence in one dimension, it will have low or random confidence in the

other dimension, and vice versa. If on the other hand, prioritization occurs in parallel and

selection strength is driven by a common mechanism, one would expect a positive

correlation at those time points. Finally, if prioritization occurs in parallel but selection

strength is driven by independent mechanisms, one would expect zero correlation. To

assess these competing hypotheses, correlations were statistically tested against zero by

running two-sided one-sample t-tests across participants at every time point, using cluster-

based permutation tests (5000 permutations, α = .05) to correct for multiple comparisons

(Maris and Oostenveld, 2007).

Correlating classification confidence on simulated data with known underlying

correlational structure When correlating confidence scores, a lack of correlation could

reflect parallel processing of the two targets, but could also be caused by the decoding

strength being too weak, due to an insufficient signal-to-noise ratio (SNR) in the data. To

make sure that we had enough statistical power to detect a correlation if it was actually

present, we ran a simulation in which we embedded a signal in systematically

manipulated noise levels, and determined at which decoding strength a known

correlation could be reliably extracted. The exact same analysis pipeline was applied as

for the actual data. Specifically, we replaced the data of eight channels with simulated

data in which we injected either a positive, negative or null correlation between horizontal

and vertical targets and varied the overall noise level. The data were created by

generating half a cycle of a sine wave with an amplitude of 1 μV, extending over 400 ms

(200 – 600 ms post stimulus) and assigned to a subset of channels to reflect attentional

selection. To create location-specific effects (i.e., contra vs. ipsilateral), we injected the

same ERP with a negative amplitude on an orthogonal subset of the channels.

Therefore, attentional selection was simulated with a positive ERP on half the channels

and a negative ERP on the other half. Importantly, attentional selection of vertical and

horizontal targets was simulated independently, by using an orthogonal split of the

channels into contra- and ipsilateral. For every correlation pattern we simulated 512

trials, the same number as in the real experiment. For the positive correlation, we

injected the ERP for both vertical and horizontal targets on half of the simulated trials,

and no ERP on the other half, reflecting either both targets to be selected

simultaneously, or none of them (i.e. parallel selection). For the negative correlation, the

ERP was either injected for vertical targets or for horizontal targets (each half of the

trials), but never in both, reflecting the selection of either one or the other target (i.e.

serial selection). For the null correlation, per trial, we randomly chose whether an ERP

was present for one of the targets, both, or none. Next, we added random noise for all

trials. Critically, the SNR was parametrically manipulated, relative to the (constant)

amplitude of the ERP. For example, a SNR of 4 means the peak ERP amplitude was four

times as high as the maximum noise amplitude. In total, we used SNRs of 4, 2, 1.33, 1,

0.67, 0.5, 0.33, 0.25, 0.2, 0.17, 0.14, 0.13, 0.11, 0.1, 0.07, 0.05, and 0.04. Once the

simulated dataset was created, the same backward decoding model (see Methods) was

used to decode the target location, separately for the vertical and horizontal target, the

injected correlation and the SNR. Similarly, the classifiers' confidence scores were

correlated between vertical and horizontal targets, as was done for the actual data.

Supplemental Information

Figure 2 - Figure Supplement 1. Average N2pc difference waves for targets on the

horizontal (left vs. right) meridian as a function of number of templates and number of target

features. N2pc components were computed using the electrodes PO7 and PO8, by

subtracting ERPs ipsilateral to the visual field of lateral targets from contralateral ERPs. The

shaded area represents 1 SEM above and below the mean for every time point. Thick lines

and horizontal bars indicate significant clusters (at α = .05) as produced by cluster-based

permutation testing (5000 permutations). For visualization purposes only, the contra-

ipsilateral difference waves over time were fitted with a cubic spline (λ=15, comparable to a

30 Hz low-pass filter) to achieve temporal smoothing. Note the statistical analyses and

estimation of the onset latencies were done on unsmoothed data. The marked time points

indicate the latency of 50% maximum amplitude as estimated using a jackknife approach, as

a measure of the onset of selection (Miller, Patterson and Ulrich, 1998; Luck, 2014;

Liesefeld, 2018). Reliable N2pc and sustained posterior contralateral negativity (SPCN;

Mazza *et al.*, 2007; Jolicœur, Brisson and Robitaille, 2008; Eimer, 2014; Grubert, Carlisle

and Eimer, 2016) components were identified in all three conditions. Onset latency was

fastest for the 1TMP–1TGT condition (214 ms), followed by the 2TMP-2TGT condition (225

ms), and, surprisingly, the 2TMP–1TGT condition (237 ms, all ts> 2.2, ps < .05). Although

overall patterns are similar, these findings indicate that our main classification analyses

reflect more information than is present in just the N2pc, which is subject to inherent

electrode selection. See also Figure 2 - Figure Supplement 1 - source data 1.

Figure 2 - Figure Supplement 2. MVPA decoding performance for target position separately

for switch and repeat trials in the 2TMP-1TGT condition. The shaded area represents 1 SEM

above and below the mean for every time point. Thick lines as well as horizontal bars

indicate significant clusters (at α = .05) as produced by cluster-based permutation testing

(5000 permutations). For visualization purposes only, the classification scores over time were

fitted with a cubic spline (λ=15, comparable to a 30 Hz low-pass filter) to achieve temporal

smoothing. Note the statistical analyses and estimation of the onset latencies were done on

unsmoothed data. The marked time points indicate the latency of 50% maximum amplitude

as estimated using a jackknife approach (Miller, Patterson and Ulrich, 1998; Luck, 2014;

Liesefeld, 2018). See also Figure 2 - source data 2.

Figure 3 - Figure Supplement 1. Individual MVPA decoding performance for target

positions on the horizontal (left vs. right, less saturated red line) and on the vertical meridian

(top vs. bottom, more saturated red line) in the 2TMP-2TGT condition (which is the condition

where we expected serial processing, if any, to be most prominent). For each individual, we

computed Spearman's ρ correlation between the classifier performances in the time window

from 150 ms to 700 ms post stimulus (the values of which are shown in each plot). For

visualization purposes only, the classification scores over time were fitted with a cubic spline

(λ=15, comparable to a 30 Hz low-pass filter) to achieve temporal smoothing. Note that the

correlations were performed on unsmoothed data. See also Figure 3 - Figure Supplement 1 -

source data 1 and Figure 3 - Figure Supplement 1 -source data 2.

Figure 3 - Figure Supplement 2. Results of location decoding and correlation analysis

of a simulated dataset across several signal-to-noise ratios (SNRs). We simulated ERPs

for targets at all four target positions. These artificial ERPs were either positively,

negatively, or not correlated between vertical and horizontal target position. The SNR of

the simulated dataset was then manipulated by adding random noise of various levels

(relative to the peak amplitude of the ERP) to the data. A) AUC scores (color coded) are

shown for a location decoding analysis, separately for the injected correlation and SNR

across time. B) Spearman's ρ correlation (color coded) between confidence scores of the

vertical and horizontal classifiers, separately for the injected correlation and SNR across

time. For both A and B, only those time points were colored that survived cluster-based

permutation testing (α = 0.05, 5000 permutations). Dashed vertical lines indicate the time

window in which the ERP was injected. The figure shows that both location decoding and

the retrieving of the injected correlation declined with decreasing SNR. Importantly,

reliable correlations disappear before classification itself, indicating that for the average

group classification levels as observed in our data, any correlation present may have

been too low to be detected.

References

Baars, B. J. (2005) 'Global workspace theory of consciousness: Toward a cognitive neuroscience of human experience', *Progress in Brain Research*, pp. 45–53. doi: 10.1016/S0079-6123(05)50004-9.

Baldauf, D. and Desimone, R. (2015) 'Neural mechanisms of object-based attention', *Cerebral Cortex*, 25(4), pp. 1080–1092. doi: 10.1093/cercor/bht303.

Barrett, D. J. K. and Zobay, O. (2014) 'Attentional control via parallel target-templates in dual-target search', *PLoS ONE*, 9(1), pp. 1–9. doi: 10.1371/journal.pone.0086848.

Beck, V. M. and Hollingworth, A. (2017) 'Competition in saccade target selection reveals attentional guidance by simultaneously active working memory representations', *Journal of Experimental Psychology: Human Perception & Performance*, 43(2), pp. 225–230. doi: 10.1037/xhp0000306.

Beck, V. M., Hollingworth, A. and Luck, S. J. (2012) 'Simultaneous Control of Attention by Multiple Working Memory Representations', *Psychological Science*, 23(8), pp. 887–898. doi: 10.1177/0956797612439068.

Bundesen, C., Habekost, T. and Kyllingsbæk, S. (2005) 'A neural theory of visual attention: Bridging cognition and neurophysiology', *Psychological Review*, 112(2), pp. 291–328. doi: 10.1037/0033-295X.112.2.291.

Carlisle, N. B., Arita J. T., Pardo D., and Woodman, G. F. (2011) 'Attentional templates in visual working memory.', *The Journal of Neuroscience*, 31(25), pp. 9315–9322. doi: 10.1523/JNEUROSCI.1097-11.2011.

Cave, K. R., Menneer, T., Nomani, M. S., Stroud, M. J., and Donnelly, N. (2018) 'Dual target search is neither purely simultaneous nor purely successive', *Quarterly Journal of Experimental Psychology*, 71(1), pp. 169–178. doi: 10.1080/17470218.2017.1307425.

Chatham, C. H. and Badre, D. (2015) 'Multiple gates on working memory', *Current Opinion in Behavioral Sciences*, 1, pp. 23–31. doi: 10.1016/j.cobeha.2014.08.001.

Cowan, N. (2001) 'The magical number 4 in short-term memory: a reconsideration of mental storage capacity.', *The Behavioral and Brain Sciences*, 24(1), pp. 87–114. doi: 10.1017/S0140525X01003922.

Dehaene, S., Kerszberg, M. and Changeux, J. P. (1998) 'A neuronal model of a global
workspace in effortful cognitive tasks.', *Proceedings of the National Academy of Sciences of*
the United States of America, 95, pp. 14529–14534. doi: 10.1073/pnas.95.24.14529.

Delorme, A. and Makeig, S. (2004) 'EEGLAB: an open source toolbox for analysis of single-
trial EEG dynamics including independent component analysis.', *Journal of Neuroscience*
Methods, 134(1), pp. 9–21. doi: 10.1016/j.jneumeth.2003.10.009.

Desimone, R. and Duncan, J. (1995) 'Neural Mechanisms of Selective Visual Attention',
Annual Review of Neuroscience, 18(1), pp. 193–222. doi: 10.1146/annurev.neuro.18.1.193.

Dombrowe, I., Donk, M. and Olivers, C. N. L. (2011) 'The costs of switching attentional sets',
Attention, Perception, & Psychophysics, 73, pp. 2481–2488. doi: 10.3758/s13414-011-0198-
3.

van Driel, J., Gunseli E., Meeter M., and Olivers, C. N. L. (2017) 'Local and interregional
alpha EEG dynamics dissociate between memory for search and memory for recognition',
NeuroImage, 149, pp. 114–128. doi: 10.1016/j.neuroimage.2017.01.031.

van Driel, J., Ort E., Fahrenfort, J. J., and Olivers, C. N. L. (2019) 'Beta and theta oscillations
differentially support free versus forced control over multiple-target search', *Journal of*
Neuroscience, 39(9), pp. 1733–1743. doi: https://doi.org/10.1523/JNEUROSCI.2547-
18.2018.

Duncan, J. and Humphreys, G. W. (1989) 'Visual search and stimulus similarity.',
Psychological Review, 96(3), pp. 433–458. doi: 10.1037/0033-295X.96.3.433.

Eimer, M. (1996) 'The N2pc component as an indicator of attentional selectivity',
Electroencephalography and Clinical Neurophysiology, 99, pp. 225–234. doi:
10.1016/S0921-884X(96)95711-2.

Eimer, M. (2014) 'The neural basis of attentional control in visual search', *Trends in*
Cognitive Sciences, 18(10), pp. 526–535. doi: 10.1016/j.tics.2014.05.005.

Eimer, M. and Grubert, A. (2014) 'Spatial attention can be allocated rapidly and in parallel to
new visual objects', *Current Biology*, 24(2), pp. 193–198. doi: 10.1016/j.cub.2013.12.001.

Fahrenfort, J. J., Grubert, A., Olivers, C. N. L., and Eimer M. (2017) 'Multivariate EEG
analyses support high-resolution tracking of feature-based attentional selection', *Scientific*
Reports, 7(1), pp. 1–15. doi: 10.1038/s41598-017-01911-0.

Fahrenfort, J. J. *et al.* (2018) 'From ERPs to MVPA using the Amsterdam Decoding and
Modeling toolbox (ADAM)', *Frontiers in Neuroscience*, 12(JUL). doi:
10.3389/fnins.2018.00368.

Found, A. and Müller, H. J. (1996) 'Searching for unknown feature targets on more than one
dimension: investigating a "dimension-weighting" account.', *Perception & Psychophysics*,
58(1), pp. 88–101. doi: 10.3758/BF03205479.

Grootswagers, T., Cichy, R. M. and Carlson, T. A. (2018) 'Finding decodable information that
can be read out in behaviour', *NeuroImage*. Elsevier Inc., 179(June), pp. 252–262. doi:
10.1016/j.neuroimage.2018.06.022.

Grubert, A., Fahrenfort, J. J., Olivers, C. N. L., and Eimer M. (2017) 'Rapid top-down control
over template-guided attention shifts to multiple objects', *NeuroImage*, 146, pp. 843–858. doi:
10.1016/j.neuroimage.2016.08.039.

Grubert, A., Carlisle, N. B. and Eimer, M. (2016) 'The Control of Single-color and Multiple-
color Visual Search by Attentional Templates in Working Memory and in Long-term Memory',
Journal of Cognitive Neuroscience, 28(12), pp. 1947–1963. doi: 10.1162/jocn.

Grubert, A. and Eimer, M. (2013) 'Qualitative differences in the guidance of attention during
single-color and multiple-color visual search: behavioral and electrophysiological evidence.',
Journal of Experimental Psychology. Human Perception and Performance, 39(5), pp. 1433–
42. doi: 10.1037/a0031046.

Grubert, A. and Eimer, M. (2015) 'Rapid Parallel Attentional Target Selection in Single-Color
and Multiple-Color Visual Search', *Journal of Experimental Psychology. Human Perception
and Performance*, 41(1), pp. 86–101. doi: 10.1037/xhp0000019.

Gunseli, E., Meeter, M., Olivers, C. N. L., 2014. 'Is a search template an ordinary working
memory? Comparing electrophysiological markers of working memory maintenance for
visual search and recognition', *Neuropsychologia. 60*, 29–38. doi:
10.1016/j.neuropsychologia.2014.05.012.

Hamker, F. H. (2004) 'A dynamic model of how feature cues guide spatial attention', *Vision
Research*, 44(5), pp. 501–521. doi: 10.1016/j.visres.2003.09.033.

Hand, D. J. and Till, R. J. (2001) 'A Simple Generalisation of the Area Under the ROC Curve
for Multiple Class Classification Problems', *Machine Learning*, 45(2), pp. 171–186. doi:
10.1023/A:1010920819831.

Haufe, S. *et al.* (2014) 'On the interpretation of weight vectors of linear models in multivariate
neuroimaging.', *NeuroImage*, 87, pp. 96–110. doi: 10.1016/j.neuroimage.2013.10.067.

He, H. *et al.* (2008) 'ADASYN: Adaptive synthetic sampling approach for imbalanced
learning', in *Proceedings of the International Joint Conference on Neural Networks*. doi:
10.1109/IJCNN.2008.4633969.

Houtkamp, R. and Roelfsema, P. R. (2009) 'Matching of visual input to only one item at any
one time', *Psychological Research*, 73, pp. 317–326. doi: 10.1007/s00426-008-0157-3.

Huang, L. and Pashler, H. (2007) 'A Boolean map theory of visual attention.', *Psychological
Review*, 114(3), pp. 599–631. doi: 10.1037/0033-295X.114.3.599.

Irons, J. L., Folk, C. L. and Remington, R. W. (2012) 'All set! Evidence of simultaneous
attentional control settings for multiple target colors.', *Journal of Experimental Psychology:
Human Perception and Performance*, 38(3), pp. 758–775. doi: 10.1037/a0026578.

Jenkins, M., Grubert, A. and Eimer, M. (2017) 'Target objects defined by a conjunction of
colour and shape can be selected independently and in parallel', *Attention, Perception, &
Psychophysics*, 79, pp. 2310–2326. doi: 10.3758/s13414-017-1410-x.

Jolicœur, P., Brisson, B. and Robitaille, N. (2008) 'Dissociation of the N2pc and sustained
posterior contralateral negativity in a choice response task', *Brain Research*, 1215, pp. 160–
172. doi: 10.1016/j.brainres.2008.03.059.

Kiyonaga, A., Egner, T. and Soto, D. (2012) 'Cognitive control over working memory biases
of selection.', *Psychonomic Bulletin & Review*, 19(4), pp. 639–46. doi: 10.3758/s13423-012-
0253-7.

Kristjánsson, Á. and Campana, G. (2010) 'Where perception meets memory: A review of
repetition priming in visual search tasks', *Attention, Perception & Psychophysics*, 72(1), pp.
5–18. doi: 10.3758/APP.72.1.5.

Kristjánsson, T. and Kristjánsson, Á. (2017) 'Foraging through multiple target categories
reveals the flexibility of visual working memory', *Acta Psychologica*. Elsevier, 183(December
2017), pp. 108–115. doi: 10.1016/j.actpsy.2017.12.005.

Lamme, V. A. F. (2003) 'Why visual atention and awareness are different', *Trends in*
Cognitive Sciences, 7(1), pp. 12–18. doi: 10.1016/S1364-6613(02)00013-X.

Liesefeld, H. R. (2018) 'Estimating the Timing of Cognitive Operations With MEG/EEG
Latency Measures: A Primer, a Brief Tutorial, and an Implementation of Various Methods',
Frontiers in Neuroscience, 12(October), pp. 1–11. doi: 10.3389/fnins.2018.00765.

Liu, T. and Jigo, M. (2017) 'Limits in feature-based attention to multiple colors', *Attention,*
Perception, & Psychophysics. Attention, Perception, & Psychophysics, 79, pp. 2327–2337.
doi: 10.3758/s13414-017-1390-x.

Luck, S. J. (2014) *An introduction to the event-related potential technique*. Cambridge: MIT
Press.

Luck, S. J. and Hillyard, S. A. (1994) 'Electrophysiological correlates of feature analysis
during visual search.', *Psychophysiology*, pp. 291–308. doi: 10.1111/j.1469-
8986.1994.tb02218.x.

Maljkovic, V. and Nakayama, K. (1994) 'Priming of pop-out: I. Role of features.', *Memory &*
Cognition, 22(6), pp. 657–672. doi: 10.3758/BF03209251.

Manohar, S. G., Zokaei, N., Fallon, S. J., Vogels, T. P., and Husain, M. (2019) 'Neural
mechanisms of attending to items in working memory', *Neuroscience and Biobehavioral*
Reviews. doi: 10.1016/j.neubiorev.2019.03.017.

Maris, E. and Oostenveld, R. (2007) 'Nonparametric statistical testing of EEG- and MEG-
data', *Journal of Neuroscience Methods*, 164, pp. 177–190. doi:
10.1016/j.jneumeth.2007.03.024.

Mathôt, S., Schreij, D. and Theeuwes, J. (2012) 'OpenSesame: An open-source, graphical
experiment builder for the social sciences', *Behavior Research Methods*, 44(2), pp. 314–324.
doi: 10.3758/s13428-011-0168-7.

Mazza, V., Turatto M., Umiltà, C., and Eimer, M. (2007) 'Attentional selection and
identification of visual objects are reflected by distinct electrophysiological responses',
Experimental Brain Research, 181(3), pp. 531–536. doi: 10.1007/s00221-007-1002-4.

Menneer, T., Cave, K. R. and Donnelly, N. (2009) 'The cost of search for multiple targets:
effects of practice and target similarity.', *Journal of Experimental Psychology. Applied*, 15(2),
pp. 125–139. doi: 10.1037/a0015331.

Miller, J., Patterson, T. and Ulrich, R. (1998) 'Jackknife-based method for measuring LRP

onset latency differences', *Psychophysiology*, 35(1), pp. 99–115. doi: 10.1111/1469-

8986.3510099.

Monsell, S. (2003) 'Task switching', *Trends in Cognitive Sciences*, 7(3), pp. 134–140. doi:

10.1016/S1364-6613(03)00028-7.

van Moorselaar, D., Theeuwes, J. and Olivers, C. N. L. (2014) 'In competition for the

attentional template: Can multiple items within visual working memory guide attention?',

Journal of Experimental Psychology. Human Perception and Performance, 40, pp. 1450–64.

doi: 10.1037/a0036229.

Olivers C. N. L., Peters J., Houtkamp R., and Roelfsema P. R. (2011) 'Different states in

visual working memory: When it guides attention and when it does not', *Trends in Cognitive*

Sciences, 15(7), pp. 327–334. doi: 10.1016/j.tics.2011.05.004.

Olivers, C. N. L. and Eimer, M. (2011) 'On the difference between working memory and

attentional set', *Neuropsychologia*, 49(6), pp. 1553–1558. doi:

10.1016/j.neuropsychologia.2010.11.033.

Olivers, C. N. L. and Humphreys, G. W. (2003) 'Attentional guidance by salient feature

singletons depends on intertrial contingencies.', *Journal of Experimental Psychology. Human*

Perception and Performance, 29(3), pp. 650–657. doi: 10.1037/0096-1523.29.3.650.

Ort E., Fahrenfort, J. J., Reeder, R., Pollmann, S., and Olivers, C. N. L.(2019) 'The Role of

Proactive and Reactive Cognitive Control for Target Selection in Multiple-Target Search',

bioRxiv. doi: http://dx.doi.org/10.1101/559500.

Ort E., Fahrenfort, J. J., and Olivers, C. N. L. (2017) 'Lack of Free Choice Reveals the Cost

of Having to Look for More Than One Object', *Psychological Science*, 28(8), pp. 1137–1147.

doi: 10.1177/0956797617705667.

Ort E., Fahrenfort, J. J., and Olivers, C. N. L. (2018) 'Lack of free choice reveals the cost of

multiple-target search within and across feature dimensions', *Attention, Perception, and*

Psychophysics, 80, pp. 1904–1917. doi: 10.3758/s13414-018-1579-7.

Ritchie, J. B. and Carlson, T. A. (2016) 'Neural decoding and "inner" psychophysics: A

distance-to-bound approach for linking mind, brain, and behavior', *Frontiers in Neuroscience*,

10(APR), pp. 1–8. doi: 10.3389/fnins.2016.00190.

Sassenhagen, J. and Draschkow, D. (2019) 'Cluster-based permutation tests of MEG/EEG
data do not establish significance of effect latency or location', *Psychophysiology*, (August
2018), p. e13335. doi: 10.1111/psyp.13335.

Stroud, M. J., Menneer, T., Kaplan, E., Cave, K. R., and Donnelly, N. (2019) 'We can guide
search by a set of colors, but are reluctant to do it', *Attention, Perception, and*
Psychophysics, pp. 377–406. doi: 10.3758/s13414-018-1617-5.

Vogel, E. K. and Machizawa, M. G. (2004) 'Neural activity predicts individual differences in
visual working memory capacity.', *Nature*, 428(6984), pp. 748–51. doi: 10.1038/nature02447.

Wang, B., Cao, X., Theeuwes, J., Olivers, C. N. L., Wang, Z. (2017) 'Separate capacities for
storing different features in visual working memory.', *Journal of Experimental Psychology:*
Learning, Memory, and Cognition, 43(2), pp. 226–236. doi: 10.1037/xlm0000295.

Wolfe, J. M. (1994) 'Guided Search 2.0 A revised model of visual search', *Psychonomic*
Bulletin & Review, 1(2), pp. 202–238. doi: 10.3758/BF03200774.

Wolfe, J. M. *et al.* (2004) 'How fast can you change your mind? The speed of top-down
guidance in visual search', *Vision Research*, 44(12), pp. 1411–1426. doi:
10.1016/j.visres.2003.11.024.

Wolfe, J. M. (2012) 'Saved by a Log: How Do Humans Perform Hybrid Visual and Memory
Search?', *Psychological Science*, 23(7), pp. 698–703. doi: 10.1177/0956797612443968.